



US008965929B2

(12) **United States Patent**
Weiss et al.

(10) **Patent No.:** **US 8,965,929 B2**
(45) **Date of Patent:** **Feb. 24, 2015**

(54) **MANIPULATING ELECTRONIC BACKUPS**

(56) **References Cited**

(71) Applicant: **Apple Inc.**, Cupertino, CA (US)

U.S. PATENT DOCUMENTS

(72) Inventors: **Eric A. Weiss**, Paris (FR); **Pavel Cisler**,
Los Gatos (CA); **Peter McInerney**,
Cupertino, CA (US); **Dominic B.**
Giampaolo, Mountain View, CA (US)

5,150,407	A	9/1992	Chan
5,150,473	A	9/1992	Zulch
5,163,148	A	11/1992	Walls
5,276,867	A	1/1994	Kenley et al.
5,349,658	A	9/1994	O'Rourke et al.
5,369,570	A	11/1994	Parad

(73) Assignee: **Apple Inc.**, Cupertino, CA (US)

(Continued)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

FOREIGN PATENT DOCUMENTS

EP	629950	12/1994
EP	1152352	11/2001

(21) Appl. No.: **13/669,099**

(Continued)

(22) Filed: **Nov. 5, 2012**

OTHER PUBLICATIONS

(65) **Prior Publication Data**

US 2013/0066836 A1 Mar. 14, 2013

"Apple Previews Mac OS X Leopard," Aug. 7, 2006, [Online]
[Retrieved on Nov. 26, 2007] Retrieved from the Internet:
URL: <http://www.apple.com/pr/library/2006/aug/07leopard.html>,
pp. 1-2.

(Continued)

Related U.S. Application Data

(63) Continuation of application No. 11/760,604, filed on
Jun. 8, 2007, now Pat. No. 8,307,004.

Primary Examiner — Isaac M Woo

(74) *Attorney, Agent, or Firm* — Fish & Richardson P.C.

(51) **Int. Cl.**

G06F 17/30 (2006.01)

G06F 11/14 (2006.01)

(52) **U.S. Cl.**

CPC **G06F 11/1451** (2013.01); **G06F 11/1461**
(2013.01); **G06F 11/1458** (2013.01); **G06F**
17/30 (2013.01); **G06F 11/1466** (2013.01)

USPC **707/791**; 707/802; 707/822; 707/828

(58) **Field of Classification Search**

CPC G06F 17/30

USPC 707/600–899

See application file for complete search history.


(57)

ABSTRACT

Systems and methods are provided for storing and restoring
digital data. In some implementations, a method is provided.
The method includes initiating a backup operation of data
including a plurality of items, interrupting the backup opera-
tion, where interrupting occurs after a portion of the data has
been completed, receiving an input to resume the backup
operation, identifying a previously completed portion of the
backup data, and performing a backup of a remaining uncom-
pleted portion of the backup data. Other embodiments of this
aspect include corresponding systems, apparatus, computer
program products, and computer readable media.

16 Claims, 7 Drawing Sheets

600



(56)

References Cited

U.S. PATENT DOCUMENTS

5,659,614 A	8/1997	Bailey	7,401,194 B2	7/2008	Jewell
5,664,186 A	9/1997	Bennett et al.	7,418,619 B1	8/2008	Uhlmann et al.
5,680,562 A	10/1997	Conrad et al.	7,434,164 B2	10/2008	Salesin et al.
5,736,974 A	4/1998	Selker	7,434,177 B1	10/2008	Ording et al.
5,745,669 A	4/1998	Hugard et al.	7,440,125 B2	10/2008	Maekawa et al.
5,754,178 A	5/1998	Johnston et al.	7,483,693 B2	1/2009	Lueng et al.
5,758,359 A	5/1998	Saxon	7,505,762 B2	3/2009	Onyon et al.
5,790,120 A	8/1998	Lozares et al.	7,518,611 B2	4/2009	Boyd et al.
5,802,175 A	9/1998	Kara	7,558,930 B2	7/2009	Kitamura et al.
5,818,936 A	10/1998	Mashayekhi	7,559,016 B1	7/2009	Rakowski et al.
5,819,032 A	10/1998	De Vries et al.	7,574,459 B2	8/2009	Sen et al.
5,819,292 A	10/1998	Hitz et al.	7,590,668 B2	9/2009	Kathuria et al.
5,831,617 A	11/1998	Bhukhanwala	7,596,586 B2	9/2009	Gokhale et al.
5,832,526 A	11/1998	Schuyler	7,600,133 B2	10/2009	Long et al.
5,961,605 A	10/1999	Deng et al.	7,624,133 B1	11/2009	Ojalvo
5,987,566 A	11/1999	Vishlitzky et al.	7,630,021 B2	12/2009	Matsuzaka et al.
6,006,227 A	12/1999	Freeman et al.	7,657,450 B2	2/2010	Amit et al.
6,023,506 A	2/2000	Ote et al.	7,660,817 B2	2/2010	Smith et al.
6,097,313 A	8/2000	Takahashi et al.	7,669,141 B1	2/2010	Pegg
6,112,318 A	8/2000	Jouppi et al.	7,676,689 B1	3/2010	Shioyama et al.
6,134,660 A	10/2000	Boneh et al.	7,711,771 B2	5/2010	Kirnos
6,167,532 A	12/2000	Wisecup	7,734,594 B2	6/2010	Wang
6,188,405 B1	2/2001	Czerwinski et al.	7,739,464 B1	6/2010	Coulter et al.
6,269,381 B1	7/2001	St. Pierre et al.	7,739,622 B2	6/2010	DeLine et al.
6,366,988 B1	4/2002	Skiba et al.	7,809,687 B2	10/2010	Cisler et al.
6,396,500 B1	5/2002	Qureshi et al.	7,809,688 B2	10/2010	Cisler et al.
6,397,308 B1	5/2002	Ofek et al.	7,836,311 B2	11/2010	Kuriya et al.
6,424,626 B1	7/2002	Kidambi et al.	7,853,566 B2	12/2010	Cisler et al.
6,460,055 B1	10/2002	Midgley et al.	7,853,567 B2	12/2010	Cisler et al.
6,553,392 B1	4/2003	Mosher, Jr. et al.	7,856,424 B2	12/2010	Cisler et al.
6,574,733 B1	6/2003	Langford	7,860,839 B2	12/2010	Cisler et al.
6,604,118 B2	8/2003	Kleiman et al.	7,882,072 B1	2/2011	Axe et al.
6,625,704 B2	9/2003	Winokur	7,934,064 B1	4/2011	Per et al.
6,629,129 B1	9/2003	Bookspan et al.	7,974,948 B2	7/2011	Baer et al.
6,636,937 B2	10/2003	Peter	8,010,900 B2	8/2011	Hart et al.
6,638,313 B1	10/2003	Freeman et al.	8,055,911 B2	11/2011	Feng et al.
6,701,454 B1	3/2004	Fischer et al.	8,099,392 B2	1/2012	Paterson et al.
6,711,572 B2	3/2004	Zakharov et al.	8,166,415 B2	4/2012	Cisler et al.
6,714,201 B1	3/2004	Grinstein et al.	8,209,308 B2	6/2012	Rueben et al.
6,714,952 B2	3/2004	Dunham et al.	8,229,897 B2	7/2012	Cannon et al.
6,725,427 B2	4/2004	Freeman et al.	2001/0047368 A1	11/2001	Oshinsky et al.
6,728,735 B1	4/2004	Fong	2002/0016912 A1	2/2002	Johnson
6,768,999 B2	7/2004	Prager et al.	2002/0023198 A1	2/2002	Kokubun et al.
6,785,751 B1	8/2004	Connor	2002/0046220 A1	4/2002	Freeman et al.
6,785,786 B1	8/2004	Gold et al.	2002/0049883 A1	4/2002	Schneider et al.
6,801,229 B1	10/2004	Tinkler	2002/0054158 A1	5/2002	Asami
6,836,657 B2	12/2004	Ji et al.	2002/0063737 A1	5/2002	Feig et al.
6,857,001 B2	2/2005	Hitz et al.	2002/0065999 A1	5/2002	Kikuchi et al.
6,892,211 B2	5/2005	Hitz et al.	2002/0080180 A1	6/2002	Mander et al.
6,901,493 B1	5/2005	Maffezzoni	2002/0107886 A1	8/2002	Gentner et al.
6,918,124 B1	7/2005	Novik et al.	2002/0112237 A1	8/2002	Kelts
6,947,556 B1	9/2005	Matyas et al.	2002/0120648 A1	8/2002	Ball et al.
6,948,039 B2	9/2005	Biessener et al.	2002/0156921 A1	10/2002	Dutta et al.
6,959,368 B1	10/2005	St. Pierre et al.	2002/0160760 A1	10/2002	Aoyama
6,993,710 B1	1/2006	Coad et al.	2002/0174283 A1	11/2002	Lin
7,069,402 B2	6/2006	Coulter et al.	2003/0016248 A1	1/2003	Hayes Ubillos
7,072,916 B1	7/2006	Lewis et al.	2003/0018878 A1	1/2003	Dorward et al.
7,099,900 B1	8/2006	Bromley et al.	2003/0050940 A1	3/2003	Robinson
7,103,740 B1	9/2006	Colgrove et al.	2003/0063128 A1	4/2003	Salmimaa et al.
7,107,527 B2	9/2006	Takahashi et al.	2003/0065687 A1	4/2003	Momiji et al.
7,111,136 B2	9/2006	Yamagami	2003/0097640 A1	5/2003	Abrams et al.
7,133,902 B2	11/2006	Saha et al.	2003/0122874 A1	7/2003	Dieberger et al.
7,134,026 B2	11/2006	Horiuchi et al.	2003/0126247 A1	7/2003	Strasser et al.
7,155,486 B2	12/2006	Aoshima et al.	2003/0131007 A1	7/2003	Schirmer et al.
7,174,352 B2	2/2007	Kleiman et al.	2003/0135650 A1	7/2003	Kano et al.
7,185,028 B2	2/2007	Lechner	2003/0137540 A1	7/2003	Klevenz et al.
7,200,617 B2	4/2007	Kibuse	2003/0167380 A1	9/2003	Green
7,222,194 B2	5/2007	Kano et al.	2003/0172937 A1	9/2003	Faries et al.
7,257,717 B2	8/2007	Huang	2003/0195903 A1	10/2003	Manley et al.
7,275,075 B2	9/2007	Cannon	2003/0220949 A1	11/2003	Witt et al.
7,284,190 B2	10/2007	Chellis et al.	2004/0044707 A1	3/2004	Richard
7,289,973 B2	10/2007	Kiessig et al.	2004/0066414 A1	4/2004	Czerwinski et al.
7,318,134 B1	1/2008	Oliveira et al.	2004/0073560 A1	4/2004	Edwards
7,320,076 B2	1/2008	Caronni	2004/0078641 A1	4/2004	Fleischmann
7,386,801 B1	6/2008	Horvitz et al.	2004/0088331 A1	5/2004	Therrien et al.
			2004/0117459 A1	6/2004	Fry
			2004/0125137 A1	7/2004	Stata et al.
			2004/0133575 A1	7/2004	Farmer et al.
			2004/0139396 A1	7/2004	Gelernter et al.

(56)

References Cited**U.S. PATENT DOCUMENTS**

2004/0143652 A1 7/2004 Grannan et al.
 2004/0163009 A1 8/2004 Goldstein et al.
 2004/0167942 A1 8/2004 Oshinsky et al.
 2004/0175000 A1 9/2004 Caronni
 2004/0193953 A1 9/2004 Callahan et al.
 2004/0199779 A1 10/2004 Huang
 2004/0199826 A1 10/2004 Bertram et al.
 2004/0210608 A1 10/2004 Lee et al.
 2004/0220965 A1 11/2004 Harville et al.
 2004/0220980 A1 11/2004 Forster
 2004/0228493 A1 11/2004 Ma
 2004/0230892 A1 11/2004 Horton
 2004/0235523 A1 11/2004 Schrire et al.
 2004/0236769 A1 11/2004 Smith et al.
 2004/0236916 A1 11/2004 Berkowitz et al.
 2004/0236958 A1 11/2004 Teicher et al.
 2004/0267700 A1 12/2004 Dumais et al.
 2005/0010955 A1 1/2005 Elia et al.
 2005/0071390 A1 3/2005 Midgley et al.
 2005/0091596 A1 4/2005 Anthony et al.
 2005/0102695 A1 5/2005 Musser
 2005/0108253 A1 5/2005 Metsatahti et al.
 2005/0138013 A1 6/2005 Walker et al.
 2005/0138081 A1 6/2005 Alshab et al.
 2005/0144135 A1 6/2005 Juarez et al.
 2005/0149577 A1 7/2005 Okada et al.
 2005/0165867 A1 7/2005 Barton et al.
 2005/0187992 A1 8/2005 Prahlad et al.
 2005/0204186 A1 9/2005 Rothman et al.
 2005/0216520 A1 9/2005 He et al.
 2005/0216527 A1 9/2005 Erlingsson
 2005/0246398 A1 11/2005 Barzilai et al.
 2005/0262168 A1 11/2005 Helliker et al.
 2005/0262377 A1 11/2005 Sim-Tang
 2006/0026218 A1 2/2006 Urmston
 2006/0041603 A1 2/2006 Paterson et al.
 2006/0041823 A1 2/2006 Wolfgang et al.
 2006/0053332 A1 3/2006 Uhlmann
 2006/0064444 A1 3/2006 Van Ingen et al.
 2006/0064634 A1 3/2006 Dettinger et al.
 2006/0080521 A1 4/2006 Barr et al.
 2006/0085792 A1 4/2006 Traut
 2006/0085817 A1 4/2006 Kim et al.
 2006/0088167 A1 4/2006 Bade et al.
 2006/0101384 A1 5/2006 Sim-Tang et al.
 2006/0106893 A1 5/2006 Daniels et al.
 2006/0117309 A1 6/2006 Singhal et al.
 2006/0137010 A1 6/2006 Kramer et al.
 2006/0143250 A1 6/2006 Peterson et al.
 2006/0150107 A1 7/2006 Leung et al.
 2006/0156246 A1 7/2006 Williams et al.
 2006/0161861 A1 7/2006 Holecek et al.
 2006/0173848 A1 8/2006 Peterson et al.
 2006/0218363 A1 9/2006 Palapudi
 2006/0224956 A1 10/2006 Storisteanu et al.
 2006/0235907 A1* 10/2006 Kathuria et al. 707/204
 2006/0236406 A1 10/2006 Johnson
 2006/0248294 A1 11/2006 Nedved et al.
 2006/0253470 A1 11/2006 Friedman et al.
 2006/0288205 A1 12/2006 Linares
 2007/0027935 A1 2/2007 Haselton et al.
 2007/0030528 A1 2/2007 Quaeler et al.
 2007/0038884 A1 2/2007 Campbell et al.
 2007/0043715 A1 2/2007 Kaushik et al.
 2007/0043790 A1 2/2007 Kryger
 2007/0070066 A1 3/2007 Bakhash
 2007/0078910 A1 4/2007 Bopardikar
 2007/0088702 A1 4/2007 Fridella et al.
 2007/0094312 A1 4/2007 Sim-Tang
 2007/0106978 A1 5/2007 Felts
 2007/0136381 A1 6/2007 Cannon et al.
 2007/0136389 A1 6/2007 Bergant et al.
 2007/0156772 A1 7/2007 Lechner
 2007/0168497 A1 7/2007 Locker et al.
 2007/0180268 A1 8/2007 Filimon et al.

2007/0185879 A1 8/2007 Roublev et al.
 2007/0185922 A1 8/2007 Kapoor et al.
 2007/0186127 A1 8/2007 Desai et al.
 2007/0192386 A1 8/2007 Fries et al.
 2007/0266007 A1 11/2007 Arrouye et al.
 2007/0271263 A1 11/2007 Merrild
 2007/0271303 A1 11/2007 Menendez et al.
 2007/0288536 A1 12/2007 Sen et al.
 2008/0016576 A1 1/2008 Ueda et al.
 2008/0022393 A1 1/2008 Waltermann et al.
 2008/0028007 A1 1/2008 Ishii et al.
 2008/0033969 A1 2/2008 Koo et al.
 2008/0034004 A1 2/2008 Cisler et al.
 2008/0034011 A1 2/2008 Cisler et al.
 2008/0034016 A1 2/2008 Cisler et al.
 2008/0034017 A1 2/2008 Giampaolo et al.
 2008/0034019 A1 2/2008 Cisler et al.
 2008/0034039 A1 2/2008 Cisler et al.
 2008/0046557 A1 2/2008 Cheng
 2008/0065663 A1 3/2008 Farlee et al.
 2008/0070496 A1 3/2008 Jackson
 2008/0077808 A1 3/2008 Teicher et al.
 2008/0082578 A1 4/2008 Hogue et al.
 2008/0091655 A1 4/2008 Gokhale et al.
 2008/0126441 A1 5/2008 Giampaolo et al.
 2008/0126442 A1 5/2008 Cisler et al.
 2008/0141029 A1 6/2008 Culver
 2008/0168184 A1 7/2008 Freedman et al.
 2008/0168245 A1 7/2008 De Atley et al.
 2008/0168391 A1 7/2008 Robbin et al.
 2008/0172607 A1 7/2008 Baer
 2008/0177961 A1 7/2008 McSharry et al.
 2008/0208630 A1 8/2008 Fors et al.
 2008/0214163 A1 9/2008 Onyon et al.
 2008/0216011 A1 9/2008 Gould
 2008/0222512 A1 9/2008 Albornoz et al.
 2008/0229037 A1 9/2008 Bunte et al.
 2008/0250342 A1 10/2008 Clark et al.
 2008/0285754 A1 11/2008 Kezmann
 2008/0307017 A1 12/2008 Lyons et al.
 2008/0307018 A1 12/2008 Ulrich et al.
 2008/0307019 A1 12/2008 Weiss et al.
 2008/0307020 A1 12/2008 Ko et al.
 2008/0307175 A1 12/2008 Hart et al.
 2008/0307333 A1 12/2008 McInerney et al.
 2008/0307347 A1 12/2008 Cisler et al.
 2008/0310628 A1 12/2008 Fujioka et al.
 2008/0310633 A1 12/2008 Brown et al.
 2008/0313243 A1 12/2008 Poston et al.
 2009/0019291 A1 1/2009 Murray
 2009/0031401 A1 1/2009 Cudich et al.
 2009/0052669 A1 2/2009 Ma
 2009/0254591 A1 10/2009 Weiss et al.
 2009/0307333 A1 12/2009 Welingkar et al.
 2010/0017855 A1 1/2010 Johnson et al.
 2010/0063960 A1 3/2010 Lehto
 2010/0070844 A1 3/2010 Aymeloglu et al.
 2010/0169823 A1 7/2010 Audet
 2010/0217929 A1 8/2010 Kirshenbaum et al.
 2011/0016089 A1 1/2011 Freedman et al.
 2011/0083088 A1 4/2011 Cisler et al.
 2011/0083098 A1 4/2011 Cisler et al.
 2011/0087976 A1 4/2011 Cisler et al.
 2011/0202763 A1 8/2011 Martin et al.
 2011/0296351 A1 12/2011 Ewing et al.
 2011/0302502 A1 12/2011 Hart et al.
 2012/0124507 A1 5/2012 Paterson et al.
 2012/0185767 A1 7/2012 Schlegel
 2012/0198383 A1 8/2012 Cisler et al.
 2012/0246565 A1 9/2012 Kumamoto
 2012/0272173 A1 10/2012 Grossman et al.

FOREIGN PATENT DOCUMENTS

EP 1582982 10/2005
 WO WO 01/06356 1/2001
 WO WO 02/101540 12/2002

(56)

References Cited

FOREIGN PATENT DOCUMENTS

WO	WO 2005/045756	5/2005
WO	2008/019259	2/2008
WO	WO 2008/019237	2/2008

OTHER PUBLICATIONS

“Aulacllic: Unit 6. The Recycle Bin,” Nov. 2005, [Online] [Retrieved on Nov. 26, 2007] Retrieved from the Internet: URL: http://www.teacherclick.com/winxp/t_6_1.htm, pp. 1-2.

Bonwick, “ZFS The Last Word in File Systems,” [Online] [Retrieved on Jan. 22, 2008] Retrieved from the Internet: URL: <http://opensolaris.org/os/community/zfs/docs/zfs.pdf>, 34 pages.

Bonwick et al., “The Zettabyte File System,” [Online] [Retrieved on Jan. 22, 2008] Retrieved from the Internet: URL: http://partneradvantage.sun.com/protected/solaris10/adoptionkit/tech/zfs/zfs_overview.pdf, 13 pages.

Bott, “Windows XP Backup Made Easy,” [Online] [Retrieved on Jul. 7, 2009]; Retrieved from the Internet URL: http://www.microsoft.com/windowsxp/using/setup/learnmore/bott_03july14.msp, 4 pages.

Engst, “Retrospect 6.0: Powerful Backup Program Adds Panther Compatibility and Enterprise Features,” [Online] [Retrieved on Jul. 8, 2009]; Retrieved from the Internet URL: <http://www.macworld.com/article/31038/2004/06/retrospect6x0.html>, 8 pages.

Godfrey, Michael et al., “Using Original Analysis to Detect Merging and Splitting of Source Code Entities,” IEEE Transactions on Software Engineering, vol. 31, No. 2, Feb. 2005, pp. 166-181.

Griffiths, “Leopard first looks: Time Machine,” Aug. 8, 2006 [Online] [Retrieved on Nov. 23, 2007] Retrieved from the Internet: URL: <http://www.macworld.com/2006/08/firstlooks/leotimemac/index.php?pf=1>, pp. 1-2.

Harder, “Microsoft Windows XP System Restore,” [Online] [Retrieved on Jul. 7, 2009] Retrieved from the Internet URL: <http://msdn.microsoft.com/en-us/library/ms997627.aspx>, 8 pages.

“How to Interpret Windows Installer Logs,” [Online] [Retrieved on Dec. 12, 2009] Retrieved from the Internet URL: http://blogs.technet.com/richard_macdonald/archive/2007/04/02/How-to-Interpret-Windows-Installer-Logs.aspx; published Apr. 4, 2007; 6 pages.

In-link files, The Open Group Base, Specifications Issue 6 [online] IEEE Std 1003.1, 2004 Edition. [retrieved on Apr. 6, 2011]. Retrieved from the Internet: URL: <http://pubs.opengroup.org/onlinepubs/009695399/utilities/In.html>, 5 pages.

Microsoft Technet: “Restore a previous version of a file,” Jan. 21, 2005, [Online] [Retrieved on Oct. 20, 2011] Retrieved from the Internet URL: [http://technet.microsoft.com/en-us/library/cc778220\(d=printer,v=WS.10\).aspx](http://technet.microsoft.com/en-us/library/cc778220(d=printer,v=WS.10).aspx), pp. 1-2.

Microsoft-TechNet, “Using Encrypting File System,” Nov. 3, 2005, Microsoft, 40 pages.

“MSDN Academic Alliance Developer Center, Curriculum Repository Glossary,” [Online] [Retrieved on Apr. 22, 2009] Retrieved from the Internet URL: <http://www.academicresourcecenter.net/curriculum/glossary.aspx>, 4 pages.

Posey, Brien M., “Working with the Windows Server 2003 vol. Shadow Copy Service”. Published Jun. 24, 2004. http://www.windowsnetworking.com/articles_tutorials/Windows-Server-2003-Volume-Shadow-Copy-Service.html; 11 pages.

Rubel, “Easy Automated Snapshot-Style Backups with Rsync,” [Online] [Retrieved on Nov. 8, 2010] Retrieved from the Internet URL: http://www.mikerubel.org/computers/rsync_snapshots; 18 pages.

“StorageSync: Backup, Restore, & Synchronization Software User’s Guide”, SimpleTech, 2003, 100 pages.

Sun Microsystems, Inc., “ZFS On-Disk Specification,” Draft: Dec. 9, 2005, [Online] [Retrieved on Jan. 22, 2008]; Retrieved from the Internet URL: <http://opensolaris.org/os/community/zfs/docs/ondiskformat0822.pdf>, 55 pages.

Tittel, “An EAZ Way to Restore Crippled and Inoperable Systems,” ChannelWeb, Apr. 25, 2005, [Online] [Retrieved on Aug. 13, 2008] Retrieved from the Internet URL: <http://www.crn.com/white-box/161502165>, 10 pages.

“What’s New in Word 2002,” Wellesly College Information Services Computing Documentation, Jan. 2002, [Online] Retrieved on Aug. 14, 2008] Retrieved from the Internet URL: <http://www.wellesley.edu/Computing/Office02/Word02/word02.html>, 19 pages.

Extended European Search Report and Written Opinion, uropean Application No. 11171738.5, Aug. 29, 2011, 5 pages. (114EP2).

International Search Report and Written Opinion, PCT/US2007/074729, Jul. 12, 2007, 11 pages. (043WO1).

International Search Report and Written Opinion, PCT/US2007/074881, Jul. 12, 2007, 11 pages. (128WO1).

International Search Report and Written Opinion, PCT/US2007/074653, Aug. 14, 2008, 14 pages. (040WO1).

International Search Report and Written Opinion, PCT/US2008/065146, Oct. 31, 2008, 21 pages. (111WO1).

International Search Report and Written Opinion, PCT/US2008/066212, Mar. 9, 2009, 26 pages. (114WO1).

International Search Report and Written Opinion, PCT/US2007/074863 Apr. 21, 2009, 20 pages. (044WO1).

European Examiner Werner Ebert, Communication pursuant to Article 94(3) EPC for Application No. EP 07 799 899.5, dated May 14, 2009, 2 pages. (0040EP1).

European Examiner Eugenio Archontopoulos, Communication pursuant to Article 94(3) EPC for Application No. EP 07 813 540.7, dated Jun. 23, 2009, 2 pages. (0043EP1).

European Examiner Werner Ebert, Communication pursuant to Article 94(3) EPC for Application No. EP 07 799 899.5, dated Oct. 7, 2009, 4 pages. (0040EP1).

Examination Report from European Application No. 07 813 605.8 dated Oct. 27, 2011, 5 pages. (128EP1).

Examination Report from European Application No. 07 813 540.7 dated Oct. 27, 2011, 5 pages. (043EP1).

Extended European Search Report, European Application No. 11184579.8, Nov. 17, 2011, 6 pages. (0111EP2).

Office Action dated Feb. 29, 2012 from related Chinese Application No. 200880024710.0, 11 pages. (0111CN1).

Anonymous, “ForeverSave Version 1.1.3”, Published Jan. 1, 2009, 16 pgs [online]. Retrieved from the Internet: <URL: http://tool-forcesw.com/docs/ForeverSave_Manual.pdf>.

Chen et al., “Data Redundancy and Compression Methods for a Disk-based Network Backup System”, 2004, IEEE, pp. 1-8.

Microsoft Corporation, “Description of the AutoRecover Functions in Excel,” [online] Microsoft Corporation, Aug. 10, 2007, Article ID 289273; URL: <http://support.microsoft.com/kb/289273/en-us>.

Charles Rubin, Mary Millhollon and Katherine Murray, “Microsoft Office Word 2003, Official Manual”, First Edition, Japan, Nikkei BP Softpress, Jul. 12, 2004, vol. 1, p. 300, 815-818 [Source: 18962-0388JP1 JP office action dated Mar. 25, 2013].

Wang et al., “A Secure and Efficient Desktop Backup and Recovery System”, 2007, IEEE, pp. 304-309.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7A




FIG. 7B

1

MANIPULATING ELECTRONIC BACKUPS

CROSS-REFERENCE TO RELATED
APPLICATION

This application is a continuation application of and claims priority to U.S. application Ser. No. 11/760,604, filed on Jun. 8, 2007, the entire disclosure of which is incorporated herein by reference.

TECHNICAL FIELD

The disclosed implementations relate generally to storing and restoring digital data.

BACKGROUND

Modern graphical user interfaces allow a large number of graphical objects or items to be displayed on a display screen at the same time. Operating systems, e.g., Apple Mac OS®, provide user interfaces in which a number of graphical user interface windows can be displayed, overlapped, resized, moved, configured, and reformatted according to the needs of a user or a particular application. Taskbars, menus, virtual buttons, and other user interface elements provide mechanisms for accessing and activating windows even when they are hidden behind other windows.

With the sophisticated tools available, users are encouraged not only to create and save a multitude of items in their computers, but to revise or otherwise improve on them over time. For example, a user can work with a certain file and thereafter save the file's current version on a storage device. The next day, however, the user could have had second thoughts about the revisions, or could have come up with new ideas, and therefore opens the file again.

The revision process is usually straightforward if the user wants to add more material to the file or make changes to what is there. But it is typically more difficult for a user who has changed his/her mind about changes that were previously made and wants the file returned to a previous version. Application programs for word processing typically let the user "undo" previous edits of a text, at least up to a predefined number of past revisions. The undo feature also usually is configured so that the previously made revisions must be undone in reverse chronological order; that is, the user must first undo the most recently made edit, then the second-most recent one, and so on. If the user saves and closes the document and thereafter opens the document again, it might not be possible to automatically undo any previous edits.

Conventional backup applications allow for the recovery of previously stored data. A backup operation typically must be completed in a single session. If the backup is interrupted, the backup generally must be started over from the beginning.

SUMMARY

Systems and methods are provided for storing and restoring digital data. In general, in one aspect, a method is provided. The method includes initiating a backup operation of data including a plurality of items, interrupting the backup operation, where interrupting occurs after a portion of the data has been completed, receiving an input to resume the backup operation, identifying a previously completed portion of the backup data, and performing a backup of a remaining uncompleted portion of the backup data. Other embodiments of this aspect include corresponding systems, apparatus, computer program products, and computer readable media.

2

Implementations of the aspect can include one or more of the following features. The aspect can further include monitoring for modifications to one or more items of the plurality of items during the backup operation, completing the backup operation, and performing a second backup for the modified items. Interrupting the backup operation can include receiving a user input that causes the backup to be interrupted. Receiving the user input can include receiving a log out request or receiving a shut down request. Interrupting the backup can include interrupting the backup in response to a system crash. Receiving an input to resume the backup operation includes receiving a user request to resume the backup. Receiving an input to resume the backup operation can include receiving an automatic request to resume the backup. An automatic request to resume can be received when a user logs into the system after interrupting the backup operation.

Identifying a previously completed portion of the backup can include identifying backup data written to the backup before the backup was interrupted. Identifying backup data written to the backup can include identifying a timestamp of the backup data. Identifying backup data written to the backup can include identifying backup data that has not been marked as complete. Identifying a previously completed portion of the backup can include identifying a portion of a file system included in the completed portion.

In general, in one aspect, a method is provided. The method includes initiating a backup operation, determining whether a partially completed backup exists, when a partially completed backup exists, determining whether to resume the partially completed backup, and completing the backup using the partially completed backup when resuming the partially completed backup. Other embodiments of this aspect include corresponding systems, apparatus, computer program products, and computer readable media.

Implementations of the aspect can include one or more of the following features. Initiating a backup operation can include receiving a user input to initiate a backup operation. Initiating a backup operation can be according to a specified schedule. Determining whether a partially completed backup exists can include identifying backup data and determining whether the data is marked as complete. Determining whether a partially completed backup exists can include comparing time stamped backup data with a timestamp for a last completed backup. Determining whether to resume the partially completed backup can include prompting the user to indicate whether to resume the partially completed backup.

Particular embodiments of the subject matter described in this specification can be implemented to realize one or more of the following advantages. A partially completed backup operation can be resumed at a later time without restarting the backup operation. Resuming a partially completed backup operation provides efficient backup operations.

The details of one or more embodiments of the invention are set forth in the accompanying drawings and the description below. Other features, aspects, and advantages of the invention will become apparent from the description, the drawings, and the claims.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram of an example computer system.

FIG. 2 is a block diagram of an example architecture for providing backup and restoration of data.

FIG. 3 is a flow chart of an example method for resuming an interrupted backup operation.

FIG. 4 is a flow chart of an example method for performing a backup operation.

3

FIG. 5 shows a screen shot depicting an example of an ongoing backup procedure alert.

FIG. 6 shows a screen shot depicting an example of an interrupted backup procedure alert.

FIGS. 7A and 7B are a flow chart of an example operation that can be performed when a backup procedure is interrupted and later resumed.

DETAILED DESCRIPTION

FIG. 1 is a block diagram of an example computer system 100. The system 100 can be used for backup operations including capturing at least one earlier version of a user interface view and allowing a user to initiate a restoration based on the captured earlier version. As used herein, a view refers to an item, element or other content, capable of being presented in a user interface, that can be subjected to a backup operation by a backup component 117 included in system 100. For example, a user interface view can contain any number of icons, files, folders, application state information and/or machine state information, etc.

The system 100 includes a personal computer 102, communicatively coupled to a remote server 107 using a network interface 116, and a network 108 (e.g., local area network, wireless network, Internet, intranet, etc.). The computer 102 generally includes a processor 103, memory 105, one or more input devices 114 (e.g., keyboard, mouse, etc.), and one or more output devices 115 (e.g., a display device). A user interacts with the system 100 using the input and output devices 114, 115. The system 100 also includes various hardware elements. The system 100 can include hardware, software, and combinations of the two.

The computer 102 also includes a local storage device 106 and a graphics module 113 (e.g., a graphics card) for storing information and generating graphical objects, respectively. The local storage device 106 can be a computer-readable medium. The computer-readable medium can be a machine-readable storage device, a machine-readable storage substrate, a memory device, a composition of matter effecting a machine-readable propagated signal, or a combination of one or more of them.

While modifications of a user interface view are described herein with respect to a personal computer 102, it should be apparent that the disclosed implementations can be incorporated in, or integrated with, any electronic device that has a user interface, including without limitation, portable and desktop computers, servers, electronics, media players, game devices, mobile phones, email devices, personal digital assistants (PDAs), embedded devices, televisions, other consumer electronic devices, etc.

Systems and methods are provided for modifying an interface view (e.g., a user interface view). Systems and methods are also provided for handling interruptions during backup operations. The systems and methods can be stand alone, or otherwise integrated into a more comprehensive application.

Though discussion is made with reference to modifying a user interface view, those of ordinary skill will recognize that such a view can be based on various data structures, files, processes, and other aspects of information management. It follows that modification to file structures, data and the like is also contemplated in order to achieve the modification of the user interface view. In other words, while the restoration of the user interface view from one state to another can be the most apparent change from the user's perspective, this is accomplished through the corresponding changes in the underlying system content.

4

One of ordinary skill in the art will recognize that the engines, methods, processes and the like that are described can themselves be an individual process or application, part of an operating system, a plug-in, an application or the like. In one implementation, the system and methods can be implemented as one or more plug-ins that are installed and run on the personal computer 102. The plug-ins are configured to interact with an operating system (e.g., MAC OS® X, WINDOWS XP, LINUX, etc.) and to perform the various functions, as described below.

A system and method for modifying a user interface view can also be implemented as one or more software applications running on the computer 102. Such a system and method can be characterized as a framework or model that can be implemented on various platforms and/or networks (e.g., client/server networks, wireless networks, stand-alone computers, portable electronic devices, mobile phones, etc.), and/or embedded or bundled with one or more software applications (e.g., email, media player, browser, etc.).

The computer 102 includes the backup component 117 that allows for the storage of versions of the computer's files or other items, for example within the local storage 106 or in an external storage repository. In one implementation, the backup component 117 also allows a user to select any of the stored versions and use the selected version to initiate a restoration of that version in the computer.

FIG. 2 is a block diagram of an example architecture 200 for providing backup and restoration of data. The architecture 200 (e.g., a software architecture) can be used for enabling the back up and restoration of elements and items, e.g., application files, application data, settings, parameters, and other data including, for example, data associated with a set of applications 228.

In some implementations, each application 228 can include an application programming interface (API) 229. The architecture 200 can utilize API techniques to access applications 228 and enhance the applications 228 with additional functionality. For example, the API 229 can link several applications 228 together for providing a single service on all linked applications. Particularly, the backup component 117 can utilize API techniques to enhance the applications 228 with the functionality of the backup component 117. The API tools can link several applications to the backup component 117 by using an API 229 to provide a similar menu or icon for each of one or more applications 228. For example, the API 229 can be used by the backup component 117 when generating a backup view corresponding to a current state of the subject application 228.

As another example, the API 229 can be used when the application 228 is restored, using the backup component 117, to a prior view representing a prior state of the application. Although the API 229 is shown in FIG. 2 as part of application programs 228, the API can be separate from the application programs 228. For example, the API 229 can be separately located and made available by the system for use by one or more of the application programs 228.

In one implementation, the backup component 117 provides back up and restoration capability for the system 100. Many different items or elements can be the subject of a backup operation in the system 100. For example, folders, files, items, information portions, directories, images, system parameters, playlists, address books, e-mails, e-mail folders, application states, and the like all can be candidates for inclusion in an archive as backup data. Other types of data can be included as backup data.

In some implementations, the backup component 117 can include a local storage device 204 and an external storage

5

device **232**. The backup data can be stored on either or both. Any number of local and/or external storage devices can be used by the backup component **117** for storing backup data. In one implementation, no local storage is provided. In one implementation, the backup component **117** stores the backup data in a format corresponding to a file system structure. Backup data can be stored incrementally during a backup operation where backup data is periodically written to a particular storage device.

In one implementation, one copy of original data (e.g., folders, files, items, information portions, directories, images, system parameters, playlists, address books, e-mails, e-mail folders, application states, preferences, and the like) is stored in the system as backup data (e.g., an original version of the data). When one or more subsequent sets of backup data, or versions, of the data are generated through subsequent backup operations, the backup data can contain only the differences between a current data version and the prior backup data, thereby saving storage space. In some implementations, the storage devices **204** and **232** can be used to store the original backup data as well as links pointing to the original backup data. The links can be hard links which reference, or point to, physical data, or as another example can be symbolic links that reference another file on the storage device (e.g., by name or location).

The backup component **117** can interact with one or more of the applications using the corresponding API **229**. In one implementation, the interaction allows the backup component **117** to perform backup operations to capture a view of the application including the particular application's files, state, or other items, and can provide for user restoration of selected backup data, to name two examples.

In another implementation, the backup component **117** runs as a background task on an operating system **230**, where the task is generally not visible to the user. The backup component **117** can be configured to run across multiple user accounts.

The backup component **117** includes an activity monitoring engine **212**. In one implementation, the activity monitoring engine **212** monitors for changes within data (e.g., files or application states) targeted for inclusion in backup operations. A change can also include the addition of new files or other data structures and the modification or deletion of existing ones. For example, the activity management engine **212** can be responsible for verifying the integrity of a playlist in a music file management program, or for verifying that a corresponding song file exists for a listed song.

In one implementation, the activity monitoring engine **212** is capable of discerning between a substantive change (e.g., the text within a document has been modified) and a non-substantive change (e.g., the play count within an iTunes playlist has been updated, or several changes cancel each other out) through the activity monitoring engine's interaction with the application programs **228**. The activity monitoring engine **212** can, for example, create a list of modified elements (e.g., files) to be used when a backup operation is eventually triggered. In one implementation, the activity monitoring engine **212** can monitor the system for periods of inactivity. The activity monitoring engine **212** can then trigger a backup operation during a period of time in which the backup operation will not cause a system slowdown for an active user.

A preference management engine **214** specifies some operating parameters of the backup component **117**. In one implementation, the preference management engine **214** contains user-specified and/or system default application parameters for the backup component **117**. These can include settings for

6

the details of capturing and storing the views. For example, the preference management engine **214** can determine the frequency of backup operations, the storage location for the backup data, the types of elements (e.g., files or other items) that are eligible for inclusion in backup operations, and the events which trigger a backup operation (periodic or event-driven, etc.).

The preference management engine **214** can, in some implementations, determine what steps are to be taken in the event that a backup operation is interrupted, for example, due to a system shutdown, a user logging out, or an unexpected system failure. For example, the preference management engine **214** can determine if and when an alert can be generated regarding the interruption of a backup operation and/or the ability to complete a previously interrupted backup operation.

In one implementation, the preference management engine **214** can detect that a new storage device is being added to the system and prompt the user whether the new storage device should be included as a backup repository. Files and other items can be scheduled for a backup operation due to location (e.g., everything on the C: drive and within D:/photos), a correlation with specific applications (e.g., all pictures, music, e-mail in an inbox, an address book, and system settings), or a combination of strategies. Different types of items can be scheduled to be stored on different devices or on different segments of a storage device during a backup operation.

A backup management engine **216** coordinates the collection, storage, and retrieval of views performed by the backup component **117**. For example, the backup management engine **216** can trigger the activity monitoring engine **212** to monitor for activities that satisfy one or more criteria specified in the preference management engine **214** for initiating a backup operation.

A change identifying engine **218** locates specific element (e.g., files or other items) to determine if data associated with the elements has changed. The change identifying engine **218** can be capable of discerning a substantive change from a non-substantive change. For example, the change identifying engine **218** can identify a loss of data associated with a user's current view. In one implementation, the change identifying engine **218** traverses a target set of files or other items, comparing a previous version to the current version to determine whether or not a modification has occurred. In addition, the change identifying engine **218** can generate an alert identifying the loss of data and prompt the user to initiate a previous version of the current view to restore the lost data. For example, the change identifying engine **218** can be responsible for verifying whether a data loss has occurred in a music file management program or for verifying that a corresponding song file is unchanged for a listed song.

A backup capture engine **220** locates views (e.g., elements, files or other items) that are to be included in a backup operation. The backup capture engine **220** can invoke the activity monitoring engine **212** and/or the change identifying engine **218**, for example, to generate a capture list identifying data to be included in a next backup operation. The backup capture engine **220** can then store copies of listed data in one or more targeted storage repositories. The backup capture engine **220** can track multiple versions of elements or items included in the backup repository.

The backup component **117** includes a backup restoration engine **222** to restore previous versions of views (e.g., files or other items). In one implementation, the backup restoration engine **222** provides a user interface (e.g., a graphical user interface) where a user can select the item(s) to be restored.

The backup restoration engine **222** can initiate backup operations on one or more data elements or items as directed by a user, the system, or according to a specified or otherwise defined schedule. For example, the user can set up a scheduled backup operation to occur for any number of data files. The data files can be related to one another, such as when the files share similar attributes or a schema. For example, several files included on one particular webpage can have a similar schema and can require versions of each related file to remain consistent to display a successful webpage image.

Unless the backup operation is completed in a very short amount of time, there is a chance that one or more of the files to be included in the backup can be modified before the backup operation is complete. For example, the backup operation can be performed while a computer system is in use (e.g., executing operation received from a user). The use of the computer system during a backup operation can introduce inconsistencies, for example, between backed up data files and data files currently awaiting the backup operation.

In another example, if the backup operation is interrupted (e.g., because of a user logout, system shutdown, or system crash) and later completed, there is a chance that one or more of the files pending inclusion in the backup can be modified before the backup operation is complete. In these examples, such changes are monitored and the backup operation can be tailored to take them into account. If inconsistencies are found between files, the backup restoration engine **222** can attempt to resolve any discrepancies between data files, as described in greater detail below.

FIG. **3** is a flow chart of an example method **300** for resuming an interrupted backup operation. For convenience, the method **300** will be described with reference to a system (e.g., system **100**) performing the method **300**. The system initiates (**302**) a backup operation. For example, a user can choose to back up files and/or folders according to a specified time schedule. The backup component (e.g., backup component **117**) can begin the backup operation according to the specified time schedule.

During the backup operation, the backup component writes (e.g., periodically) backup data to a storage device. For example, the backup component can write data in a temporary manner (e.g., in a temporary location, marked as incomplete, etc.). Alternatively, the backup component can write the data as part of the backup on the storage device, which is not marked as complete until the backup operation has finished. For example, when backing up a large amount of data, the backup data can be written incrementally as portions of the backup operation are performed. In some implementations, the data has the form of a file system and backup data is written as portions of the file system are traversed during the backup operation. The data written to the storage device, in this example, can also include a timestamp. The timestamp can indicate the time at which the backup data was written to the backup.

The system interrupts (**304**) the backup operation. In some examples, a system reboot occurs in the middle of the backup operation, the system crashes, or the user logs out. When the backup operation is interrupted, only a partial backup has been completed. Consequently, only a portion of the data elements scheduled for inclusion in the backup have been written to the storage device.

The system resumes (**306**) the interrupted backup operation. The resumption of the backup operation can occur, for example, automatically when the system starts up again or when the user logs on again. Alternatively, resumption of backup operation can be initiated according to a user request or when the next backup operation is triggered (e.g., accord-

ing to a specified time schedule or in response to one or more backup events). In some implementations, the backup component prompts the user whether or not an incomplete backup operation should be resumed or a new backup operation begun.

The system identifies (**308**) the previously completed portion of the backup. For example, a backup capture engine (e.g., backup capture engine **220** (FIG. **2**)) can locate a partially completed backup by comparing timestamps on written backup data to the timestamp of the last completed backup operation. Additionally, the partially completed backup can be identified according to backup data that has not been marked as complete. In comparing the data stored in the partially completed backup with the schedule data to be included in the backup, a remaining set of data can be determined.

Using the remaining set of data, the system continues (**310**) the backup operation. For example, the identified data that has not yet been backed up can be added to the partial backup to provide a completed backup. In some implementations, the backup data is stored as a file system hierarchy. Completing the backup operation includes completing the backup of elements in the file system hierarchy that were scheduled to be included in the backup. In some implementations, when the backup operation is completed, the backup data is marked as a completed backup. The completed backup can also include a timestamp, for example, to compare the backup data of the completed backup with backup data from previous backup operations or future partial backups.

In some implementations, the procedures described in method **300** can be performed in a different order or in combination with each other, and more or fewer steps can be taken for the interrupted backup operation to complete. For example, in some implementations, the backup capture engine locates a partially completed backup and triggers the backup operation to resume. In another example, the interrupted backup operation can be canceled (e.g., by the system or by a user). In an alternative example, additional interruptions and resumptions could occur before a backup operation completes.

FIG. **4** is a flow chart of an example method **400** for performing a backup operation. For convenience, the method **400** will be described with reference to a system (e.g., system **100** including backup component **117**) performing the method **400**. The system initiates (**402**) a backup operation. For example, a user can choose to initiate a backup operation on files or folders upon system start (e.g., as the backup component **117** initializes). Alternatively, the initiated backup operation can be according to a specified schedule (e.g., hourly) or in response to one or more events (e.g., a specified number of detected data changes).

The system determines (**404**) whether a partially completed backup has occurred. A backup operation may fail to complete, in one example, due to a system failure on the computer **102**. In some implementations, the system (e.g., as backup restoration engine **222** or the change identifying engine **218** of the backup component **117**), can identify a partially completed backup by traversing the backup data for stored backup data that is not marked as completed. Additionally, the backup data that is not completed can have a timestamp that is later than the most recent backup data marked as a completed backup.

Alternatively, the system can identify backup data stored within a temporary directory, or those containing a more recent timestamp than the time at which the last full backup operation completed. In some implementations, the backup component can recognize an interruption as it occurs (e.g.,

due to a voluntary shutdown or log off operation) and write an interrupt indicator such as a flag that identifies the partially completed backup.

If the system identifies a partially completed backup, the system determines (406) whether to resume the incomplete backup operation. In some implementations, the user can be prompted to provide an input indicating whether or not the backup operation should be resumed, or whether, alternatively, the partially completed backup should be discarded. In other implementations, the system (e.g., the preference management engine 214) can have a parameter specifying when to resume an incomplete backup operation.

When a partially completed backup is resumed, the system completes (410) the interrupted backup operation using the partial backup data. For example, when the backup data is stored as a file system hierarchy, the elements of the file system hierarchy that were not yet included are added to the backup data. Additionally, once completed, the backup data can be flagged as a completed backup. In some implementations, when resuming the backup operation the system determines whether or not there have been changes to data previously stored in the partial backup. For example, a change identifying engine (e.g., change identifying engine 218) can check the partial backup data provided by a backup capture engine (e.g., backup capture engine 220) to verify that none of the items have changed since the previous backup operation was interrupted. The change identifying engine can provide an updated list of items to the backup capture engine so that the backup capture engine can complete the interrupted backup operation.

When a partially completed backup does not exist, or when the system determines (408) that the partially completed backup operation should not be resumed, the system initiates (412) a new backup operation. The new backup operation includes identifying modified data with respect to the most recently completed backup operation, if any, and generating a new backup including storing changed data. For example, the change identifying engine can generate a new list of modified items for the backup capture engine to use during the backup operation.

FIG. 5 shows a screen shot depicting an example of an ongoing backup procedure alert 500. Since backup operations can occur in the background, a user may be unaware that a backup operation is in progress. In one implementation, the alert 500 is generated by the activity monitoring engine 212 or the backup management engine 216 (FIG. 2). Within the alert 500, the user is warned that a backup operation is currently in progress. The alert 500 may be generated, for example, in response to a user attempting to log out of the computer 102 during an ongoing backup operation. A similar alert, in some implementations, may be generated in response to an attempt to shut down the backup component 117 or the computer 102 during a backup operation.

A user can select a “continue later” button 502 to request that the backup component 117 resume the backup operation at a later point in time (e.g., after the user logs back into the computer 102). A user can instead select a “cancel log out” button 504 so that the user may remain logged in while the backup operation runs to completion. Alternatively, in some implementations, a presented button allows the user to cancel the current backup operation and continue with the log out, shut down, or other operation that triggered the interrupt. In some implementations, if the user cancels the backup operation, the partial backup data is discarded.

In an alternative implementation, if the user continues with the log out, the backup process can be immediately termi-

nated or otherwise stopped at an appropriate point (e.g., after writing any processed, but unwritten, backup data).

FIG. 6 shows a screen shot depicting an example of an interrupted backup procedure alert 600. In one implementation, the alert 600 is generated by change identifying engine 218 or the backup management engine 216 (FIG. 2). Within the alert 600, the user is warned that an incomplete set of archive data exists due to an interrupted backup operation. The alert 600 can be generated, in some implementations, in response to a user logging into the computer 102 after an interrupted backup operation, during start up of the computer 102, or at the point of a next scheduled backup operation.

A user can select a “continue backup” button 602 to request that the backup component 117 resume the previously interrupted backup operation. Alternatively, the user can instead select a “cancel backup” button 604 so that the interrupted backup operation is canceled. In some implementations, upon selection of the cancel backup option, the backup data of the partially completed backup are discarded. Additionally, in some implementations, selection of the cancel backup option results in the initiation of a new backup operation.

FIGS. 7A and 7B are a flow chart of an example backup operation 700. The backup operation 700 can be performed, for example, to backup elements or items, including data files and folders. For convenience, the method 700 will be described with reference to a system (e.g., system 100 including backup component 117) performing the method 700.

The system initiates (702) a backup operation. For example, a user can choose to initiate a backup operation of data including, for example, files or folders stored in a storage device. The backup component (e.g., backup component 117) can begin the backup operation according to the specified time schedule. The system monitors (704) for modifications to one or more items during the backup operation. For example, the backup component can monitor file changes made by a user and determine whether or not the modifications cause an inconsistency between related items, such as the individual files used in combination for displaying a single web page.

In some implementations, the backup component can initially ignore modifications that have been made to related files, and back up the original files before determining whether or not the modifications cause an inconsistency in the files. Alternatively, in some implementations, the backup component can simply monitor for any changes to items occurring during the backup operation regardless of the items’ relationship to any other item. In particular, the backup component monitors for changes to items already stored in the backup data as part of the backup operation in progress.

The system interrupts (706) the backup operation. An interruption can occur, for example, due to a system shutdown, system failure, or user disconnection, or a manual user cancellation of the backup operation.

The backup operation resumes (708) at a later point in time, for example, as described above. The system resumes (710) monitoring for modifications. In addition to monitoring current modifications, in some implementations the monitoring task determines whether or not changes were made to items in the interval between the interruption (706) of the backup operation and the resumption (708) of the backup operation.

The system completes (712) the initial backup operation. The system determines (714) whether or not modifications have occurred during the backup operation. A query can be sent, for example, to a backup management engine to determine whether or not modifications occurred during a particular backup operation. If modifications did not occur during

11

the backup operation, the system determines (722) that the backup operations are complete and the backup data is stored for later use.

If modifications occurred during the backup operation, or between interruption and resumption of the backup operation, the backup component modifies (716) the backup data. In one implementation, the backup data can be modified to correspond to the state that the files (or other items) have at the end of the initial backup operation. In another implementation, the backup data can be modified to correspond to the state that the files (or other items) have at the beginning of their initial backup operation. In some implementations, the user can be given a prompt or an option to decline further backup operations. For example, when a modification is insignificant to the structure and content of the files (e.g., a title change or file name change), the system can present a pop-up window containing a decline or ignore option.

Upon completion of the backup modification operation, the system determines (718) whether or not modifications have occurred during the backup modification operation. If modifications did not occur during the backup modification operation, the system determines (722) that the backup is complete. When modifications have occurred during a backup modification operation, a query can be sent to determine (720) whether or not additional backup modification operations are permitted. For example, a user can set a maximum number of backup modification operations that can be carried out by configuring the backup component with a specified number of iterations. If further backup modification operations are allowed, the backup operation can be performed (716) again to resolve the inconsistencies.

The system can attempt to resolve inconsistencies by performing steps 716, 718, and 720 until the maximum number of iterations has been reached. Upon reaching the maximum number of backup modification operations, the system can generate 724 an alert to the user. The alert can notify the user of the intended resolution and can allow the user to decline, continue, or modify the backup operation. In some implementations, the user can choose to be prompted each time the time machine engine triggers the performance of the backup modification operation.

In the above description, for purposes of explanation, numerous specific details are set forth in order to provide a thorough understanding. It will be apparent, however, to one skilled in the art that implementations can be practiced without these specific details. In other instances, structures and devices are shown in block diagram form in order to avoid obscuring the disclosure.

In particular, one skilled in the art will recognize that other architectures and graphics environments can be used, and that the examples can be implemented using graphics tools and products other than those described above. In particular, the client/server approach is merely one example of an architecture for providing the functionality described herein; one skilled in the art will recognize that other, non-client/server approaches can also be used. Some portions of the detailed description are presented in terms of algorithms and symbolic representations of operations on data bits within a computer memory. These algorithmic descriptions and representations are the means used by those skilled in the data processing arts to most effectively convey the substance of their work to others skilled in the art. An algorithm is here, and generally, conceived to be a self-consistent sequence of steps leading to a desired result. The steps are those requiring physical manipulations of physical quantities. Usually, though not necessarily, these quantities take the form of electrical or magnetic signals capable of being stored, transferred, com-

12

bined, compared, and otherwise manipulated. It has proven convenient at times, principally for reasons of common usage, to refer to these signals as bits, values, elements, symbols, characters, terms, numbers, or the like.

It should be borne in mind, however, that all of these and similar terms are to be associated with the appropriate physical quantities and are merely convenient labels applied to these quantities. Unless specifically stated otherwise as apparent from the discussion, it is appreciated that throughout the description, discussions utilizing terms such as “processing” or “computing” or “calculating” or “determining” or “displaying” or the like, refer to the action and processes of a computer system, or similar electronic computing device, that manipulates and transforms data represented as physical (electronic) quantities within the computer system’s registers and memories into other data similarly represented as physical quantities within the computer system memories or registers or other such information storage, transmission or display devices.

An apparatus for performing the operations herein can be specially constructed for the required purposes, or it can comprise a general-purpose computer selectively activated or reconfigured by a computer program stored in the computer. Such a computer program can be stored in a computer readable storage medium, such as, but is not limited to, any type of disk including floppy disks, optical disks, CD-ROMs, and magnetic-optical disks, read-only memories (ROMs), random access memories (RAMs), EPROMs, EEPROMs, magnetic or optical cards, or any type of media suitable for storing electronic instructions, and each coupled to a computer system bus.

The algorithms and modules presented herein are not inherently related to any particular computer or other apparatus. Various general-purpose systems can be used with programs in accordance with the teachings herein, or it can prove convenient to construct more specialized apparatuses to perform the method steps. The required structure for a variety of these systems will appear from the description. In addition, the present examples are not described with reference to any particular programming language. It will be appreciated that a variety of programming languages can be used to implement the teachings as described herein. Furthermore, as will be apparent to one of ordinary skill in the relevant art, the modules, features, attributes, methodologies, and other aspects can be implemented as software, hardware, firmware or any combination of the three. Of course, wherever a component is implemented as software, the component can be implemented as a standalone program, as part of a larger program, as a plurality of separate programs, as a statically or dynamically linked library, as a kernel loadable module, as a device driver, and/or in every and any other way known now or in the future to those of skill in the art of computer programming. Additionally, the present description is in no way limited to implementation in any specific operating system or environment.

The subject matter described in this specification can be implemented as one or more computer program products, i.e., one or more modules of computer program instructions encoded on a computer readable medium for execution by, or to control the operation of, data processing apparatus. The instructions can be organized into modules (or engines) in different numbers and combinations from the exemplary modules described. The computer readable medium can be a machine-readable storage device, a machine-readable storage substrate, a memory device, a composition of matter affecting a machine-readable propagated signal, or a combination of one or more them. The term “data processing appa-

13

ratus” encompasses all apparatus, devices, and machines for processing data, including by way of example a programmable processor, a computer, or multiple processors or computers. The apparatus can include, in addition to hardware, code that creates an execution environment for the computer program in question, e.g., code that constitutes processor firmware, a protocol stack, a database management system, an operating system, or a combination of one or more of them. A propagated signal is an artificially generated signal, e.g., a machine-generated electrical, optical, or electromagnetic signal that is generated to encode information for transmission to suitable receiver apparatus.

While this specification contains many specifics, these should not be construed as limitations on the scope of what may be claimed, but rather as descriptions of features specific to particular implementations of the subject matter. Certain features that are described in this specification in the context of separate embodiments can also be implemented in combination in a single embodiment. Conversely, various features that are described in the context of a single embodiment can also be implemented in multiple embodiments separately or in any suitable subcombination. Moreover, although features may be described above as acting in certain combinations and even initially claimed as such, one or more features from a claimed combination can in some cases be excised from the combination, and the claimed combination may be directed to a subcombination or variation of a subcombination.

Similarly, while operations are depicted in the drawings in a particular order, this should not be understood as requiring that such operations be performed in the particular order shown or in sequential order, or that all illustrated operations be performed, to achieve desirable results. In certain circumstances, multitasking and parallel processing may be advantageous. Moreover, the separation of various system components in the embodiments described above should not be understood as requiring such separation in all embodiments, and it should be understood that the described program components and systems can generally be integrated together in a single software product or packaged into multiple software products.

The subject matter of this specification has been described in terms of particular embodiments, but other embodiments can be implemented and are within the scope of the following claims. For example, the actions recited in the claims can be performed in a different order and still achieve desirable results. As one example, the processes depicted in the accompanying figures do not necessarily require the particular order shown, or sequential order, to achieve desirable results. In certain implementations, multitasking and parallel processing may be advantageous. Other variations are within the scope of the following claims.

What is claimed is:

1. A method comprising:

initiating a backup operation of data including a plurality of items;

interrupting the backup operation after a portion of the data is backed up;

associating the backed up data with a timestamp;

receiving an input to resume the backup operation;

comparing the timestamp with a timestamp of a last completed backup operation;

based on the comparing, resuming the backup operation to back up a remaining portion of the data;

monitoring for modifications to one or more items of the plurality of items during the backup operation;

completing the backup operation; and

14

performing a second backup for modified items, where the method is performed by one or more processors.

2. The method of claim 1, wherein interrupting the backup operation includes at least one of receiving a user input that causes the backup operation to be interrupted or interrupting the backup operation in response to a system crash.

3. The method of claim 1, wherein receiving an input to resume the backup operation includes at least one of receiving a user request to resume the backup operation or receiving an automatic request to resume the backup operation.

4. The method of claim 1, wherein identifying the completed portion of the backup data includes at least one of identifying backup data written to a backup before the backup operation was interrupted or identifying a portion of a file system included in the completed portion.

5. A method comprising:

initiating a backup operation of a plurality of items;

after a first portion of the plurality of items is backed up, interrupting the backup operation;

determining a remaining portion of the plurality of items based on a timestamp of the backed-up first portion and a timestamp of a last-completed backup operation;

performing a backup of the remaining portion of the plurality of items

determining a modification occurs for an item of the plurality of items during the backup operation; and

after completing the backup operation, executing a subsequent backup for the modified item, where the method is performed by one or more processors.

6. The method of claim 5, wherein interrupting the backup operation includes at least one of receiving a user input that causes the backup operation to be interrupted or interrupting the backup operation in response to a system crash.

7. The method of claim 5, further comprising receiving a user request to resume the backup operation or receiving an automatic request to resume the backup operation.

8. The method of claim 5, wherein determining the remaining portion of the backup data includes at least one of identifying backup data written to a backup before the backup operation was interrupted or identifying a portion of a file system included in a completed portion of the backup operation.

9. A computer program product encoded on a tangible, non-transitory storage medium, the product comprising computer readable instructions for causing one or more processors to perform operations comprising:

initiating a backup operation of data including a plurality of items;

interrupting the backup operation after a portion of the data is backed up;

associating the backed up data with a timestamp;

receiving an input to resume the backup operation;

comparing the timestamp with a timestamp of a last completed backup operation;

based on the comparing, resuming the backup operation to back up a remaining portion of the data;

monitoring for modifications to one or more items of the plurality of items during the backup operation;

completing the backup operation; and

performing a second backup for modified items.

10. The computer program product of claim 9, wherein the instructions comprising interrupting the backup operation includes the instructions comprising at least one of receiving a user input that causes the backup operation to be interrupted or interrupting the backup operation in response to a system crash.

15

11. The computer program product of claim 9, wherein the instructions comprising receiving an input to resume the backup operation includes the instructions comprising at least one of receiving a user request to resume the backup operation or receiving an automatic request to resume the backup operation.

12. The computer program product of claim 9, wherein the instructions comprising identifying the completed portion of the backup data includes the instructions comprising at least one of identifying backup data written to a backup before the backup operation was interrupted or identifying a portion of a file system included in the completed portion.

13. A computer program product encoded on a tangible, non-transitory storage medium, the product comprising computer readable instructions for causing one or more processors to perform operations comprising:

- initiating a backup operation of a plurality of items;
- after a first portion of the plurality of items is backed up,
- interrupting the backup operation;
- determining a remaining portion of the plurality of items based on a timestamp of the backed-up first portion and a timestamp of a last-completed backup operation;

16

performing a backup of the second portion of the plurality of items;

determining a modification occurs for an item of the plurality of items during the backup operation; and

after completing the backup operation, executing a subsequent backup for the modified item.

14. The method of claim 13, wherein the instructions comprising interrupting the backup operation includes the instructions comprising at least one of receiving a user input that causes the backup operation to be interrupted or interrupting the backup operation in response to a system crash.

15. The method of claim 13, the instructions further comprising at least one of receiving a user request to resume the backup operation or receiving an automatic request to resume the backup operation.

16. The method of claim 13, wherein the instructions comprising identifying the remaining portion of the backup data includes the instructions comprising at least one of identifying backup data written to a backup before the backup operation was interrupted or identifying a portion of a file system included in a completed portion of the backup operation.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 8,965,929 B2
APPLICATION NO. : 13/669099
DATED : February 24, 2015
INVENTOR(S) : Eric A. Weiss et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

In the Claims

In Claim 14, column 16, line 7, delete “method” and insert -- computer program product --.

In Claim 15, column 16, line 12, delete “method” and insert -- computer program product --.

In Claim 16, column 16, line 16, delete “method” and insert -- computer program product --.

Signed and Sealed this
Sixteenth Day of June, 2015



Michelle K. Lee
Director of the United States Patent and Trademark Office