



US008973211B2

(12) **United States Patent**
Rote et al.

(10) **Patent No.:** **US 8,973,211 B2**
(45) **Date of Patent:** **Mar. 10, 2015**

(54) **DETECTOR CLEANER AND/OR TESTER
AND METHOD OF USING SAME**

(75) Inventors: **Scott Rote**, New Lenox, IL (US); **Dan Johnson**, Chicago, IL (US); **Aaron B. Eiger**, Chicago, IL (US)

(73) Assignee: **HSI Fire & Safety Group, LLC**, Elk Grove Village, IL (US)

5,139,699 A	8/1992	Cooper et al.	
5,170,148 A *	12/1992	Duggan et al.	340/515
5,361,623 A	11/1994	Wantz	
5,611,620 A	3/1997	Wantz	
5,670,946 A *	9/1997	Ellwood et al.	340/628
5,785,891 A	7/1998	Lim	
5,959,188 A	9/1999	Deutsch et al.	
6,015,230 A	1/2000	Wantz et al.	
6,143,090 A	11/2000	Lietz	
6,282,940 B1	9/2001	Hung et al.	

(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 154 days.

FOREIGN PATENT DOCUMENTS

CN	201161246 Y	12/2008
CN	201161246 Y *	12/2008

(Continued)

(21) Appl. No.: **13/366,309**

(22) Filed: **Feb. 4, 2012**

OTHER PUBLICATIONS

(65) **Prior Publication Data**

US 2013/0199260 A1 Aug. 8, 2013

International Search Report and Written Opinion for International Application No. PCT/US2013/024286 mailed May 7, 2013 (14 pages).

(Continued)

(51) **Int. Cl.**

A47L 5/14	(2006.01)
G08B 29/14	(2006.01)
G08B 29/12	(2006.01)

(52) **U.S. Cl.**

CPC **G08B 29/145** (2013.01); **G08B 29/126** (2013.01)
USPC **15/345**; 15/404; 73/865.9; 73/1.06

Primary Examiner — Bryan R Muller

(74) *Attorney, Agent, or Firm* — McDonnell Boehnen Hulbert & Berghoff LLP

(58) **Field of Classification Search**

CPC G08B 29/145; A47L 9/08; A47L 5/14
USPC 73/865.9, 1.06; 15/345
See application file for complete search history.

(57) **ABSTRACT**


An apparatus for cleaning a detector comprising a housing and a bowl connected to the housing having a detector chamber adapted for enclosing a detector to be cleaned, a contacting surface positioned on the bowl, and one of more air nozzles positioned within the detector chamber for directing one or more bursts of compressed air at a detector to clean the detector, and a fan positioned within the housing operable to draw air within the detector chamber into a filter, and a dust collector for containing dirt and debris dislodged from a detector during the cleaning operation.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,301,674 A	11/1981	Haines et al.	
4,315,344 A	2/1982	Woodward et al.	
4,333,205 A *	6/1982	Woodward et al.	15/345
4,462,244 A	7/1984	Lee	

47 Claims, 7 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

6,423,962 B1 7/2002 Pepper
 6,591,716 B2 7/2003 Wantz
 6,640,608 B2 11/2003 Pepper et al.
 6,741,181 B2 5/2004 Skaggs
 6,769,285 B2* 8/2004 Schneider et al. 73/1.06
 6,875,373 B2 4/2005 Elendu
 6,995,678 B2 2/2006 Wey
 D518,341 S 4/2006 Lowen
 D519,338 S 4/2006 Lowen
 7,167,098 B2 1/2007 Siber et al.
 7,212,734 B2 5/2007 Pepper et al.
 D558,549 S 1/2008 Ozaki-Owen
 7,320,735 B2 1/2008 Riske
 7,377,147 B1 5/2008 Scheffler et al.
 7,497,108 B2 3/2009 Scheffler
 7,587,926 B2* 9/2009 Ackerman 73/1.02
 D611,122 S 3/2010 Rossiter et al.
 7,703,344 B2 4/2010 MacPherson, III et al.
 7,805,974 B2 10/2010 Scheffler et al.
 7,852,227 B2 12/2010 Pepper et al.

7,878,079 B2 2/2011 Goodwin
 8,049,612 B2 11/2011 Pepper
 8,205,478 B1* 6/2012 Hallisey 73/1.06
 2002/0166361 A1 11/2002 Wantz et al.
 2004/0050137 A1 3/2004 Hoppenworth
 2007/0186618 A1 8/2007 Ackerman
 2009/0211382 A1* 8/2009 Feiter 73/865.9

FOREIGN PATENT DOCUMENTS

EP	1548676	12/2004
EP	1 548 676	6/2005
GB	2 432 703	5/2007
KR	988386	10/2010
WO	94/25946	11/1994
WO	2007/138329	12/2007
WO	2008/111895	9/2008

OTHER PUBLICATIONS

Feiter, Margaret A. et al., U.S. Appl. No. 13/251,919 entitled "Heat Detector Test" filed Oct. 3, 2011, 21 pages.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7A




FIG. 7B

DETECTOR CLEANER AND/OR TESTER AND METHOD OF USING SAME

BACKGROUND

The present invention generally relates to a device for cleaning and/or testing a detector and a method of using such a device for cleaning and/or testing a detector. The device and method are particularly well suited for cleaning a detector, such as a detector for detecting the presence of carbon monoxide, smoke, or heat. The device and method are also designed for testing a carbon monoxide detector or a smoke detector.

The use of various types of detectors has become widespread. For example, carbon monoxide detectors, smoke detectors, and heat detectors are commonly used in commercial and residential buildings, recreational vehicles, mobile homes, as well as boats. The use of such detectors is even required by law to be installed in some jurisdictions. The lifespan of the various detectors has also increased over time. As a result, detectors are often used for longer periods of time before they are replaced. Over time, detectors may become dirty as dust or other debris accumulates. The operational capability of the detectors may be reduced or compromised as a result. Thus, there is a need to provide a device and method for cleaning the various types of detectors that are used.

In addition, carbon monoxide detectors, smoke detectors, and heat detectors are often placed in areas that require a very clean environment. For example, in hospitals, laboratories, and sophisticated manufacturing and assembly facilities it may be important that any dust or debris dislodged or removed from the detectors during a cleaning operation does not contaminate the environment. Thus, for example, in "clean room" applications, it is desirable that any dust and debris dislodged during the cleaning of the detectors is captured and prevented from contaminating the environment. Thus, there is a need to provide a device and method for cleaning the various types of detectors that are used that includes means for capturing any dust or debris that is dislodged from the detector during the cleaning operation to help prevent contamination of the environment.

Furthermore, many detectors include a button that may be depressed to test and verify that the circuitry of the detector is working properly, or that the batteries are sufficiently charged. However, it is also desirable to check that the carbon monoxide and/or smoke detecting capability of the detectors is still working properly as well. Thus, there is a need to provide a device and method for testing the carbon monoxide and/or smoke detecting capabilities of the various detectors to see if they are properly working.

In addition, detectors come in various shapes and sizes. Some are circular, some are rectangular, some extend further from the mounting surface, etc. Therefore, it is desirable to provide a detector cleaner and/or tester that may accommodate a range of detector shapes and sizes.

SUMMARY

The present embodiments disclose an apparatus for cleaning a detector comprising a housing and a bowl connected to the housing having a detector chamber adapted for enclosing a detector to be cleaned, a contacting surface positioned on the bowl, and one or more air nozzles positioned within the detector chamber for directing one or more bursts of compressed air at a detector to clean the detector, and a fan positioned within the housing operable to draw air within the

detector chamber into a filter, and a dust collector for containing dirt and debris dislodged from a detector during the cleaning operation.

Further embodiments include a test container receptor within the housing adapted for receiving a container of test gas where test gas is released from the container of test gas and passes through a chimney into the detector chamber.

Example embodiments also disclose a method of cleaning a detector comprising the steps of positioning a detector chamber of a bowl attached to a housing over a detector to be cleaned, pressing a contacting surface positioned on the detector chamber against a surface to which the detector is positioned, discharging one or more bursts of compressed air through one or more nozzles positioned in the detector chamber towards the detector to clean dust or debris from the detector, operating a fan to draw air from the detector chamber into a filter, and collecting dust or debris dislodged from the detector in a dust bin.

Further embodiments disclose the additional step of releasing a test gas into the detector chamber, and operating a fan to remove test gas from the detection chamber and into the air filter.

An additional example embodiment is directed to a method including the steps of positioning a detector chamber of a bowl attached to a housing over a detector to be cleaned, discharging one or more bursts of compressed air through one or more nozzles positioned in the detector chamber towards the detector to clean dust or debris from the detector, operating a fan to draw air from the detector chamber into a filter, releasing test gas into the detector chamber; and operating a fan to draw the test gas from the detector chamber into the filter.

An additional example embodiment is directed to an apparatus for testing a detector that includes a housing, a bowl connected to the housing having a detector chamber adapted for enclosing a detector to be tested, a contacting surface positioned on the bowl, a passageway within the housing for test gas to enter the detector chamber, and a fan positioned within the housing operable to draw test gas from the detector chamber into a filter.

BRIEF DESCRIPTION OF THE DRAWINGS

Exemplary embodiments are described herein with reference to the drawings, wherein like parts are designated by like reference numerals, and wherein:

FIG. 1 is a perspective view of a detector cleaning and/or testing device 10;

FIG. 2 is an exploded view of the detector cleaning and/or testing device shown in FIG. 1;

FIG. 3 is a cut away view of the detector cleaning and/or testing device shown in FIGS. 1 and 2;

FIG. 4 is another cut away view of the detector cleaning and/or testing device shown in FIGS. 1-3;

FIG. 5 is an enlarged view of circle F shown in FIG. 3;

FIG. 6 is an enlarged view of circle E shown in FIG. 3;

FIG. 7A is an enlarged view of an upper left section of FIG. 3; and

FIG. 7B is an enlarged view of an upper right section of FIG. 3.

DETAILED DESCRIPTION OF THE INVENTION

FIG. 1 is a perspective view of a detector cleaning and/or testing device 10. Device 10 includes a housing 20. The housing 20 is comprised of a main housing 38, an upper housing 26, and a bottom 40. A bowl or cup 12 is connected

to the upper housing 26. The bowl 12 includes a detector chamber 16 that is sized to enclose a detector that is to be cleaned or tested. The bowl 12 includes contacting surface 18 that is designed for placement against a wall or ceiling during the cleaning or testing operation. Preferably the contacting surface 18 is comprised of a flexible, rubbery material such as silicone rubber or santoprene so that a seal may be formed around the detector between the bowl and the surface, ceiling or wall, where the detector is located. Device 10 also includes a handle 14 that is attached to the housing 20, and is shown pivotally mounted to upper housing 26. The handle 14 is adapted to receive a pole or other device to enable the device 10 to be positioned over a detector located on a ceiling. Housing 20 also includes a removable dust drawer 24 positioned in the upper housing 26 that serves to collect dust and debris that is dislodged during the cleaning operation. The handle 14, housing 20, and bowl 12 are preferably comprised of a durable, lightweight material such as a hard plastic, such as a polycarbonate. In a preferred embodiment, the handle 14 is comprised of glass-filled nylon, the components of housing 20 are comprised of ABS (acrylonitrile butadiene styrene, and bowl 12 is comprised of a polycarbonate having the trade name Lexan. In addition, the bowl 12 may be made from a translucent material so that the detector being cleaned or tested may be visible during the cleaning or testing process.

The detector chamber 16 is sized so that the bowl 12 may enclose a variety of the commonly used carbon monoxide detectors, smoke detectors, and heat detectors on the market. In FIG. 1, the detector chamber 16 is shown to have a round shape having a diameter of 8.5 inches, which is suitable to enclose the size of many round detectors found on the market. However, the shape of the bowl 12 or detector chamber 16 is not limited to a round shape, and may take any desired geometric shape, such as a square, rectangle, polygon, oval, etc.

FIG. 2 shows an exploded view of the detector cleaning and/or testing device 10 shown in FIG. 1. Device 10 includes a bowl 12 and a detector chamber 16 that is designed to enclose a detector to be cleaned and/or tested. Bowl 12 includes mounting surface 18 that is designed to engage the ceiling or wall where the detector is located. Positioned within upper housing 26 is an air nozzle 80. Air nozzle 80 is used to clean a detector positioned within the detector chamber 16 by delivering a burst of compressed air towards the detector to dislodge any dirt or debris that may have accumulated on the detector. Upper housing 26 also includes dust drawer 24 with a fan 28 positioned underneath the dust drawer 24. An air filter (not shown) is also positioned within the dust drawer 24 above the fan 28. During operation, the fan serves to create a vacuum to draw air and any dust or debris that is dislodged during a cleaning operation into the filter. The dust drawer 24 serves to contain the dust and debris that is dislodged during cleaning which helps to prevent contaminating the area where the detector is located. In this manner, the device serves as a self-contained cleaning unit that is able to both clean a detector and contain any dirt or debris that is dislodged during the cleaning operation.

Main housing 38 includes a battery pack 42 that is used to power the detector cleaning and/or testing device 10. Battery pack 42 is removably positioned on main housing 38 so that the battery pack 42 may be easily accessed or replaced. In a preferred embodiment, the battery pack 42 is a 25.2 volt lithium ion battery pack. The device 10 is controlled by control panel 32 and printed circuit board 30 positioned on main housing 38. Also positioned within main housing 38 is compressed air canister 48 and test canister 50 which may contain a test gas for a carbon monoxide tester or a test gas for a smoke detector. For example, test canister 50 may contain COCheck

carbon monoxide test gas or SmokeCheck smoke detector test gas available from HSI Fire & Safety Group of Elk Grove Village, Ill. However, any test gas suitable for testing the operation of a carbon monoxide detector or a smoke detector may be used. Moreover, compressed air canister 48 and test canister 50 are shown as cylindrical canisters, they could be a container of any suitable shape.

In addition, it is also contemplated that the compressed air could be provided by an external source. For example, instead of a container of compressed air, an accumulator could be positioned within the housing and an external pump could be used to periodically pressurize the accumulator. In this manner, pressurized air from the accumulator could be directed to the air nozzles. Alternately, an air compressor or air pump could be used to deliver compressed air to the detector cleaning and/or testing device 10. For example, a port could be positioned on the housing to which a connector at the end of a hose could be used to deliver compressed air to the device 10 from an air compressor or air pump. An air hose with a quick disconnect fitting could be used to connect the air compressor to the device 10 to deliver the compressed air for the cleaning operation. In addition, the test gas, whether containing carbon monoxide, or containing smoke or synthetic smoke could also be provided by an external source. For example a container of test gas could be connected to the cleaning and/or testing device test to deliver test gas to the detector chamber 16. Thus, the cleaning and/or testing device could be operated without having containers of compressed air or test gas positioned therein, as the compressed air or test gas used for the cleaning and testing operations could be provided from a source external to device 10.

As shown in FIG. 2, compressed air canister 48 is retained within receptor 102 and test canister 50 is positioned within receptor 112. Receptor 102 includes female threads that mate with corresponding male threads positioned on the top of compressed air canister 48. Thus, compressed air canister 48 is maintained in position by virtue of being threadingly engaged with receptor 102. Also shown in FIG. 2 is retainer 70 that generally retains the compressed air canister 48 and test canister 50 in proper alignment. Latch 72 extends from retainer 70 and fits over the bottom of test canister 50 to retain test canister 50 in proper position with respect to receptor 112. Knob 22 has a threaded portion that engages retainer 70 to retain bottom 40 of the housing in place. Thus, access to the canisters 48 and 50 may easily be achieved by unscrewing knob 22 to remove the bottom 40. The removable bottom 40 provides ready access to canisters 48 and 50 if they need to be replaced. Alternately, a quarter turn fastener that rotates 90 degrees could be used to secure the removable bottom 40. Other alternatives also exist for accessing the canisters 48 and 50 including a pair of side opening doors, or a door that opens to the side, up, or down, etc.

A linear actuator 120 is positioned within pocket 123 located on receptor 112 and includes an arm 121 that is connected to level 122 and is used to release carbon monoxide test gas or test gas for a smoke detector from test canister 50 and through passageway 130 of chimney 60 that extends from receptor 112. Passageway 130 provides a pathway between test canister 50 and detector chamber 16 so that the carbon monoxide test gas or test gas for a smoke detector may be provided in the vicinity of the detector to be tested. In this manner, the detecting capability of a carbon monoxide detector or a smoke detector may be tested.

FIG. 3 shows a different cross-sectional view of the detector cleaning and/or testing device 10 shown in FIGS. 1 and 2. FIG. 3 shows that a contact switch 90 is positioned beneath the contacting surface 18. A shoulder bolt 92 is also posi-

5

tioned beneath the contacting surface **18**. A spring **93** is positioned over the shoulder bolt **92** and normally biases the contacting surface **18** away from the contact switch **90**. When the contacting surface **18** is brought into contact against a ceiling or wall when cleaning or testing a detector, the spring **93** positioned over the shoulder bolt **92** is loaded and depressed, and the contacting surface travels on the order of 20 thousandths of an inch before the contact switch **90** is activated. A more detailed cross-sectional view of the top of the device showing contacting surface **18**, contact switch **90**, shoulder bolt **92** and spring **93** is shown in FIGS. 7A and 7B. In particular, FIG. 7A shows contact switch **90** positioned beneath contacting surface **18** and FIG. 7B shows how contacting surface **18** is connected to bowl **12** via shoulder bolt **92**, and also shows spring **93** positioned over shoulder bolt **92** to normally bias contacting surface **18** away from contact switch **90**. The activation of contact switch **90** places the detector cleaning and/or testing device **10** in a ready mode where it is ready to begin a cleaning or testing operation.

To operate the cleaning and/or testing device **10**, the control panel **32** includes a power button to turn on the power to device **10**. At this point, a user may select a number of different modes of operation. For example, a clean only mode, a test only mode, or a clean and test mode may be selected. For the clean mode, a heavy clean mode or normal clean mode may also be selected. Furthermore, a button for testing either a carbon monoxide detector or a test for a smoke detector may be selected. A start button may be used included to commence the clean and/or test mode of the device. The control panel may also include an indicator showing how much battery life remains.

In the cleaning mode of operation, when the cleaning operation begins, the fan operates to pull the air within the detector chamber through the air filter. Next, the solenoid valve is energized to open the manifold and release compressed air through the nozzle in one or more bursts directed towards the detector within the detector chamber to dislodge dust and debris that may have accumulated on the detector. It is contemplated that the one or more bursts of compressed air may preferably have a duration of up to 1 second. Each burst could be of varying duration, and any number of desired bursts could be employed. The fan may continue to run for 5 to 10 seconds to pull any dust or debris dislodged by the bursts of compressed air into the filter. In the test mode of operation, the test gas is released by operating the linear actuator to depress the aerosol trigger for a desired duration to deliver test gas to the detector chamber. The duration of time the aerosol trigger is depressed may depend on which test gas is being released. For example, when testing a smoke detector, the aerosol trigger may only need to be depressed for a 0.5 to 1 second, whereas when testing a carbon monoxide detector, the aerosol trigger may be depressed for up to 2 or 3 seconds.

When the cleaning and/or testing device **10** is removed from over the detector being tested, the test is completed. Next, the fan is operated to draw the test gas through the filter. When clean and test mode is selected, the clean mode is run, followed by the test mode. In one contemplated embodiment, the clean mode is performed by directed one or more blasts of compressed air towards the detector and the detector chamber is then cleared by having the fan draw air and any dust and debris dislodged by the compressed air blasts through the filter. Next, the test is performed by releasing test gas into the detector chamber. After the test, the test gas is drawn through the air filter to remove the test gas from the detector chamber. The test gas may be cleared once the test is completed, or after a predetermined period time, e.g., after one minute. Alternately, the test gas may be cleared automatically once contact

6

between the contacting surface and the contact switch is broken, which may include a delay, for example, a one second period of lack of contact before automatically clearing the detector chamber of test gas. Thus, the device may be used to perform clean, test, and clear functions.

Initially, the fan **28** shown in FIG. 2 may be turned on for five seconds to clear the test chamber and provide a vacuum to draw air through an air filter **25** (shown in FIG. 4). When normal clean mode is selected, a series of 3 bursts of compressed air each lasting around one half second, i.e., plus or minus 20%, may be directed through air nozzles **80**, **81**, **82**, and **83** towards the detector positioned within the detector chamber **18**. Any dust or debris that is dislodged from the detector during the cleaning operation is drawn by the fan **28** into the air filter **25** and collected in the dust drawer **24** (shown in FIG. 4). In a preferred embodiment, under normal clean mode operation, three bursts of compressed air each lasting around a half second are simultaneously directed through air nozzles **80**, **81**, **82**, and **83** towards a detector in the detector chamber **18** to clean the detector. However, the air bursts could also be sequentially performed, could be of a longer or shorter duration, and a greater or lesser number of air bursts could be also be provided. Nonetheless, the level of cleaning obtained using around three half second bursts simultaneously directed through the air nozzles towards a detector in the detector chamber **18** has proven to provide a sufficient level of cleaning for a detector. In heavy clean mode, the normal clean mode could be repeated or additional series of burst of compressed air could be used.

In test mode, test gas for either a carbon monoxide detector or a smoke detector is released from the test canister **50** and travels to detector chamber **16** to test the operational capability of the detector within the detector chamber **16**. In order to conduct the proper test, the test canister **50** should include the appropriate test gas. For example, when testing a carbon monoxide detector, the test gas within test canister **50** should contain carbon monoxide. When testing a smoke detector, the gas within test canister **50** should contain smoke or synthetic smoke. A user of the device may simply use a test canister **50** containing carbon monoxide when testing a carbon monoxide tester, and remove that test canister and replace it with a test canister containing smoke or synthetic smoke when it is desired to test a smoke detector. Optionally, the cleaning and/or testing device **10** could contain both a test canister with gas containing carbon monoxide and a test canister containing smoke or synthetic smoke. Thus, cleaning and/or testing device could contain a canister of compressed air, a canister of test gas containing carbon monoxide, and a canister of test gas containing smoke or synthetic smoke. Alternately, device **10** could contain any combination of two canisters, or contain only of the canisters.

In the view shown in FIG. 3, compressed air nozzle **80** is shown centrally located within the detector chamber **16**. Additional air nozzles **81** and **82** are also shown positioned at the bottom of detector chamber and directed towards the center of the detector chamber **16** at an angle of approximately 45 degrees. Alternate angles, including or example 30 degrees and 60 degrees are also contemplated. In the embodiments shown, there are four nozzles that are used to deliver bursts of compressed air towards a detector during a cleaning operation. Nozzle **80** is positioned directly below the detector to be cleaned and nozzles **81**, **82**, and **83** (not shown) are spaced apart from each other 120 degrees from one another, and positioned generally below and to the side of the detector to be cleaned. Compressed air from compressed air canister **48** is delivered to air nozzles **80**, **81**, **82** and **83** (not shown) through passageways **80a**, **81a**, **82a**, and **83a** (not shown).

These passageways could be in the form of flexible hoses that extend from the compressed air canister **48** to the air nozzles.

It is contemplated that the location, positioning, and number of the air nozzles may be changed. For example, the air nozzles could all be positioned on one side of the detector chamber, or positioned beneath the detector, or positioned at an angle perpendicular to the detector. In addition, only a single air nozzle could be used, or additional air nozzles added. However, testing has revealed that the particular configuration of the four air nozzles shown in FIGS. 1-3 provides for a good cleaning effect. The air nozzles that are shown may be obtained from Henkel Corporation, having part number 97230. However, any air nozzle or orifice with the capability of delivering a burst of compressed air towards a detector in the detector chamber may be used.

FIG. 3 illustrates how the threaded portion **23** of knob **22** engages the retainer **70** and barb **72** extends beneath test canister **50** to hold it in place. FIG. 3 includes encircled portion E that is shown in enlarged form in FIG. 6. As shown in FIGS. 3 and 6, a male threaded portion **49** of compressed air canister **48** is shown threaded into a manifold **100** located on receptor **102**, and having passageway **47** for directing compressed air from the compressed air canister **48** to the air nozzles **80-83**. The compressed air canister **48** may use a B188 female aerosol valve available from LINDAL. As shown in the present embodiment, the manifold **100** includes four separate passageways for directed compressed air to each of the four air nozzles **80, 81, 82, and 83**. Of course, in an embodiment using additional air nozzles, additional passageways could be provided in manifold **100**. A solenoid valve **101** may be used to control the discharge of compressed air through the air nozzles. When the solenoid valve **101** is energized, the passageways in the manifold **100** to the air nozzles are opened and a burst of air is allowed to travel through passageways (hoses) **80a, 81a, 82a, and 83a** (not shown) to the air nozzles **80, 81, 82, and 83** (not shown). The solenoid valve used for this application may be a Magnum Series 10 mm solenoid valve available from Hargraves. It will be appreciated that that use of a solenoid valve is simply a preferred means for controlling the discharge of compressed air from compressed air canister **48** and that other types of valves or controls could also be used that are suitable for controlling the discharges of compressed air from air canister **48**. For example, a rotating cam could be used to release the compressed, or a linear actuator could be used. In addition, a gear motor may also be used and mechanisms that are used to release chemicals in air fresheners may also be used.

FIG. 3 also includes encircled portion F that is shown enlarged in FIG. 5. As shown in FIGS. 3 and 5, a linear actuator **120** positioned within pocket **123** is used to control the discharge of carbon monoxide test gas or gas for testing a smoke detector from test canister **50**. In particular, linear actuator **120** includes an arm **121** that is drawn into the linear actuator **120** when the linear actuator is energized. Arm **121** is connected to lever **122**, such that when linear actuator **120** is energized, arm **121** is drawn into the linear actuator **120** and lever **122** is caused to push depressor **54** into contact with aerosol trigger **52** and depress aerosol trigger **52** to cause carbon monoxide test gas or gas for testing smoke detectors to be released from test canister **50**. The test gas is released into chimney **60** where it travels through passageway **130** of chimney **60** that provides a pathway between test canister **50** and detector chamber **16**. In this manner, test gas may be released and introduced into detector chamber **16** to test whether the detecting capabilities of a carbon monoxide detector or a smoke detector are working properly. In a preferred embodiment, an L12 series linear actuator from Firgelli may be used

to control the release of test gas from test canister **50**. It will be appreciated that that use of a linear actuator is simply a preferred means for controlling the discharge of test gas from test canister **50** and that other types of valves or controls could also be used that are suitable for controlling the discharges of test gas from test canister **50**. For example, a rotating cam could be used to release the compressed, or solenoid valve could be used. In addition, a gear motor may also be used and mechanisms that are used to release chemicals in air fresheners may also be used.

FIG. 4 shows an alternate cutaway view of the detector cleaning and/or testing device **10** shown in FIGS. 1-3. A different view of detector chamber **16** is shown with air nozzles **80, 81, and 83** and passageways **80a, 81a, and 83a** shown. A fan **28** is shown positioned beneath air filter **25**, and dust drawer **24**. When contacting surface **18** is positioned to enclose a detector to be cleaned or tested, the fan is used to create a vacuum that draws air, and any dust or debris dislodged during the cleaning operation, from detector chamber **16**, and into air filter **25**. Air filter **25** filters out dust and debris from the air which is collected in dust bin **123** of dust drawer **24**. The dust drawer **24** may be periodically removed to empty the dust and debris from dust bin **123** positioned on dust drawer **24**. The use of the dust drawer **24** with dust bin **123** allows any dust or debris dislodged during the cleaning operation to be collected and contained within the dust bin **123** so that the area surrounding the detector is not contaminated with dust and debris dislodged during the cleaning operation.

The air filter **25** is preferably a HEPA filter that filters out 99.97% of all particles greater than 0.3 micrometers in size from the air that passes through the filter. The air filter **25** may also be replaced periodically. In addition, the fan may also be used to clear the detector chamber **16** of test gas following a test of a detector within the detector chamber. For example, particulates within a test gas for testing a smoke alarm may be filtered out through air filter **25**.

The fan **28** is preferably a pancake style fan that draws the air from detector chamber **16** through air filter **25**. In a preferred embodiment, the fan **28** is made by Digikey having part number KDE2406PHS2. Handle **14** is shown having a cavity **15** adapted to receive a pole or other device for extending the detector cleaning and/or testing device into place over a detector positioned on a ceiling, wall, or other surface.

It is known that in the past, when detectors were cleaned, the extent of cleaning could vary widely depending on the technician performing the cleaning, the amount time spent cleaning each detector, the location and positioning of the detectors, etc. The present cleaning device **10** allows for more uniform cleaning of detectors within a certain location or facility. For example, the cleaning is highly repeatable where each detector may be given the identical cleaning treatment. This is desirable so that the time between required cleaning can better be determined.

It will be appreciated by those of skill in the art that the detector cleaning and/or testing device **10** shown in FIGS. 1-6 has the capability of both cleaning a detector as well as testing a carbon monoxide detector or smoke detector. However, the device could be limited to only a cleaning device or only a testing device, and does not require that the device is capable of both. The present embodiments simply disclose how a device that cleans and tests could be incorporated into a single device, but that is not required.

Example embodiments of the present invention have been described above. Those skilled in the art will understand that changes and modifications may be made to the described embodiments without departing from the true scope and spirit of the present invention, which is defined by the claims.

We claim:

1. An apparatus for cleaning a detector comprising:
a housing;
a bowl positioned on an upper portion of the housing and having an open upper surface, said bowl having a detector chamber adapted for enclosing a detector to be cleaned;
a contacting surface positioned on the bowl;
one of more air nozzles positioned within the detector chamber for directing one or more bursts of compressed air at a detector when positioned within the detector chamber;
a removable dust collector positioned in the housing for containing dirt or debris dislodged from a detector during a cleaning operation;
an air filter positioned within the dust collector;
a fan positioned within the housing and beneath the dust collector operable to draw air within the detector chamber into the air filter; and means for introducing test gas into the detector chamber.
2. The apparatus of claim 1, wherein a container of compressed air is positioned within the housing.
3. The apparatus of claim 2, wherein the container of compressed air is threaded into a receptor that is positioned within the housing.
4. The apparatus of claim 2, further including a manifold in communication with the container of compressed air, the manifold having a plurality of passages for directing compressed air to a plurality of the one or more of the air nozzles positioned in the detector chamber.
5. The apparatus of claim 4, wherein a valve is operable to control the flow of compressed air through the manifold.
6. The apparatus of claim 5, wherein the valve is a solenoid valve.
7. The apparatus of claim 2, including means for releasing compressed air from the container of compressed air.
8. The apparatus of claim 1, wherein one of the one or more nozzles is positioned directly beneath a detector, and pointed directly at the detector, when a detector is positioned within the detector chamber.
9. The apparatus of claim 8, wherein three air nozzles are positioned within the detector chamber and directed at an angle towards a detector when a detector is positioned within the detector chamber.
10. The apparatus of claim 9, wherein the angle is 45 degrees.
11. The apparatus of claim 9, wherein the three air nozzles are spaced apart 120 degrees from each other.
12. The apparatus of claim 1, wherein a container of test gas is positioned within the housing.
13. The apparatus of claim 1, wherein a latch is used to hold the container of test gas in position.
14. The apparatus of claim 12, wherein a linear actuator is positioned adjacent the container of test gas for controlling the discharge of test gas from the container of test gas.
15. The apparatus of claim 14, wherein a lever is attached to an arm of the linear actuator such that, when the linear actuator is energized, the lever causes a depressor to depress a trigger on the container of test gas and release test gas from the container of test gas.
16. The apparatus of claim 12, wherein when test gas is released from the container of test gas, the test gas passes through a chimney into the detector chamber.
17. The apparatus of claim 1, wherein when the contacting surface is pressed against a ceiling or wall, a contact switch is depressed which switches the apparatus to a ready mode of operation.

18. The apparatus of claim 16, wherein the test gas contains carbon monoxide.
19. The apparatus of claim 16, wherein the test gas contains smoke or synthetic smoke.
20. The apparatus of claim 1, wherein a container of compressed air is threadingly engaged to a manifold positioned within the housing.
21. The apparatus of claim 1, further comprising:
a container of test gas positioned within the housing; and
a passageway within the housing for test gas to enter the detector chamber;
wherein the fan positioned within the housing is operable to draw test gas from the detector chamber into the air filter that is positioned in the housing above the fan.
22. A method of cleaning a detector comprising the steps of:
providing an apparatus having a housing, a bowl positioned on an upper portion of the housing and having an open upper surface, said bowl connected to the housing having a detector chamber adapted for enclosing a detector to be cleaned, a contacting surface positioned on the bowl, one of more air nozzles positioned within the detector chamber for directing one or more bursts of compressed air at a detector when positioned within the detector chamber, a dust collector positioned in the housing for containing dirt or debris dislodged from a detector during a cleaning operation, an air filter positioned within the dust collector, a fan positioned within the housing and beneath the dust collector operable to draw air within the detector chamber into the air filter, and means for introducing test gas into the detector chamber;
positioning the detector chamber over a detector to be cleaned;
pressing the contacting surface positioned on the detector chamber against a surface to which the detector is positioned;
discharging one or more bursts of compressed air through the one or more nozzles positioned in the detector chamber towards the detector to clean dust or debris from the detector;
operating the fan to draw air from the detector chamber into the air filter;
collecting dust or debris dislodged from the detector in the dust collector.
23. The method of claim 22, wherein the step of discharging one or more bursts comprises discharging three bursts of compressed air for a duration of around a half second from each of the one or more nozzles.
24. The method of claim 22, wherein the step of discharging one or more bursts comprises discharging at least one burst of compressed air for a duration of one second or less from the one or more nozzles.
25. The method of claim 22, wherein the discharge of one or more bursts of compressed air is controlled by a valve that controls the flow of compressed air through one or more passageways of a manifold positioned on the container of compressed air.
26. The method of claim 25, wherein the manifold includes four passageways that direct air to four air nozzles positioned in the detector chamber.
27. The method of claim 26, wherein one of the four air nozzles is positioned directly beneath the detector in the detector chamber.
28. The method of claim 27, wherein the other three nozzles are positioned within the detector chamber to direct compressed air towards the detector at an angle.

11

29. The method of claim 28, wherein the angle is 45 degrees.

30. The method claim 28, wherein the three nozzles are spaced apart from each other 120 degrees.

31. The method of claim 25, wherein the valve is a solenoid valve.

32. The method of claim 23, further including the step of releasing a test gas into the detector chamber.

33. The method of claim 32, wherein the step of releasing the test gas includes operating a linear actuator to move a lever attached to the linear actuator into indirect or direct contact with an aerosol trigger positioned on a container of test gas positioned within the housing.

34. The method of claim 33, wherein a depressor is positioned between the lever and the aerosol trigger.

35. The method of claim 32, wherein the test gas contains carbon monoxide.

36. The method of claim 32, wherein the test gas contains smoke or synthetic smoke.

37. The method of claim 32, further including the step of operating a fan to remove test gas from the detection chamber and into the filter.

38. A method of cleaning and testing a detector comprising the steps of:

providing a housing, a bowl positioned on an upper portion of the housing and having an open upper surface, said bowl connected to the housing having a detector chamber adapted for enclosing a detector to be tested, a contacting surface positioned on the bowl, a passageway within the housing for test gas to enter the detector chamber, one of more air nozzles positioned within the detector chamber for directing one or more bursts of compressed air at a detector when positioned with the detector chamber, a fan positioned within the housing and beneath the dust collector operable to draw test gas from the detector chamber into an air filter that is positioned in the housing above the fan, said fan also operable to draw air within the detector chamber into the air filter

positioning the detector chamber over a detector to be cleaned;

discharging one or more bursts of compressed air through the one or more nozzles positioned in the detector chambers towards the detector to clean dust or debris from the detector;

operating the fan to draw air from the detector chamber into the air filter;

12

releasing test gas into the detector chamber; and operating fan to draw the test gas from the detector chamber into the air filter.

39. The method of claim 38 further including the step of collecting any dust or debris dislodged from the detector and particulates from the test gas in a dust bin positioned within the housing.

40. The method of claim 38, wherein the test gas contains carbon monoxide.

41. The method of claim 38, wherein the test gas contains smoke or synthetic smoke.

42. An apparatus for testing a detector comprising: a housing;

a bowl positioned on an upper portion of the housing and having an open upper surface, said bowl connected to the housing having a detector chamber adapted for enclosing a detector to be tested;

a contacting surface positioned on the bowl;

a passageway within the housing for test gas to enter the detector chamber;

one of more air nozzles positioned within the detector chamber for directing one or more bursts of compressed air at a detector when positioned within the detector chamber;

a fan positioned within the housing and beneath the dust collector operable to draw test gas from the detector chamber into an air filter that is positioned in the housing above the fan said fan also operable to draw air within the detector chamber into the air filter.

43. The apparatus of claim 42, wherein a container of test gas is positioned within the housing.

44. The apparatus of claim 43, including means for releasing test gas from the container of test gas.

45. The apparatus of claim 43, further including a test container receptor within the housing adapted for receiving the container of test gas.

46. The apparatus of claim 43, wherein a linear actuator is positioned adjacent the container of test gas for controlling the discharge of test gas from the container of test gas.

47. The apparatus of claim 46, wherein a lever is attached to an arm of the linear actuator such that, when the linear actuator is energized, the lever causes a depressor to depress a trigger on the container of test gas and release test gas from the container of test gas.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 8,973,211 B2
APPLICATION NO. : 13/366309
DATED : March 10, 2015
INVENTOR(S) : Scott Rote, Dan Johnson and Aaron B. Eiger

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

In the Claims

In claim 1, column 9, line 13, delete the word “removable” before the term “dust collector”

In claim 38, column 11, line 33, delete the word “with” after the word “positioned” and replace it with the word “within”

In claim 38, column 11, line 35, delete the word “the” before the term “dust collector” and replace it with the word “a”

In claim 38, column 12, line 2, insert the word --the-- between the word “operating” and the word “fan”

In claim 42, column 12, lines 16 and 17, delete the phrase “connected to the housing”

In claim 42, column 12, line 26, delete the word “the” after the word “beneath” and before the term “dust collector” and replace it with the word “a”

In claim 42, column 12, line 29, insert a --,-- after the phrase “above the fan”

Signed and Sealed this
Twenty-eighth Day of July, 2015



Michelle K. Lee
Director of the United States Patent and Trademark Office