



US008977108B2

(12) **United States Patent**
Haot et al.

(10) **Patent No.:** **US 8,977,108 B2**
(45) **Date of Patent:** ***Mar. 10, 2015**

(54) **DIGITAL MEDIA ASSET MANAGEMENT SYSTEM AND METHOD FOR SUPPORTING MULTIPLE USERS**

(75) Inventors: **Maxime G. G. Haot**, New York, NY (US); **Richard G. Moore**, Cedar Rapids, IA (US); **Sreenivas Rachamadugu**, Leesburg, VA (US)

(73) Assignees: **Verizon Patent and Licensing Inc.**, Basking Ridge, NJ (US); **Verizon UK Limited**, Berkshire (GB)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 518 days.
This patent is subject to a terminal disclaimer.

(21) Appl. No.: **13/113,463**

(22) Filed: **May 23, 2011**

(65) **Prior Publication Data**

US 2011/0217023 A1 Sep. 8, 2011

Related U.S. Application Data

(63) Continuation of application No. 11/517,016, filed on Sep. 7, 2006, now Pat. No. 7,970,260, which is a continuation-in-part of application No. 11/475,603, filed on Jun. 27, 2006, which is a continuation of

(Continued)

(51) **Int. Cl.**

H04N 5/76 (2006.01)

H04N 5/91 (2006.01)

G11B 27/034 (2006.01)

G06F 17/30 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **G11B 27/034** (2013.01); **G06F 17/30017** (2013.01); **G11B 27/11** (2013.01); **G11B 27/3027** (2013.01)

USPC **386/278**; **386/326**

(58) **Field of Classification Search**

USPC 386/278, 353, 200, 230, 290, 328
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,303,367 A 4/1994 Leenstra et al.
5,313,630 A 5/1994 Namioka et al.
5,499,371 A 3/1996 Henninger et al.

(Continued)

FOREIGN PATENT DOCUMENTS

EP 0764951 3/1997
EP 1463058 9/2004

(Continued)

OTHER PUBLICATIONS

“Advanced Systems Format (ASF) Specification,” Microsoft Corporation, Revision Jan. 20, 2002, http://download.microsoft.com/download/E/0/6/E06DB390-1E2A-4978-82B5-311810D8A28D/ASF_Specification.doc, 104 pages, Jun. 2004.

“Avipreview Frequently Asked Questions”, pp. 1-7, Retrieved from the internet: URL:<http://www.avipreview.com/faq.htm> [retrieved Jan. 21, 2009], Oct. 15, 2002.

Bolle, et al., “Video Libraries: From Ingest to Distribution,” IBM T. J. Watson Research Center, Lecture Notes in Computer Science vol. 1614, pp. 15-18, DOI:10.1007/3-540-48762-X_2, Dec. 1999.


(Continued)

Primary Examiner — Robert Chevalier

(57) **ABSTRACT**

An approach provides editing of digital media. A platform, as maintained by a service provider, provides a remote proxy editing capability of a plurality of media streams. A first one of the media streams is transmitted to a player of a first customer of the service provider. Further, the method comprises transmitting a second one of the media streams to a player of a second customer of the service provider.

20 Claims, 8 Drawing Sheets



Related U.S. Application Data

application No. 10/311,903, filed as application No. PCT/GB01/02857 on Jun. 27, 2001, now Pat. No. 7,096,226.

(60) Provisional application No. 60/714,674, filed on Sep. 7, 2005.

(51) **Int. Cl.**
G11B 27/11 (2006.01)
G11B 27/30 (2006.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,557,790	A	9/1996	Bingham et al.
5,611,076	A	3/1997	Durflinger et al.
5,612,715	A	3/1997	Karaki et al.
5,729,730	A	3/1998	Wlaschin et al.
5,790,176	A	8/1998	Craig
5,799,310	A	8/1998	Anderson et al.
5,831,669	A	11/1998	Adrain
5,845,073	A *	12/1998	Carlin et al. 709/217
5,852,435	A	12/1998	Vigneaux et al.
5,864,870	A	1/1999	Guck
5,892,900	A	4/1999	Ginter et al.
5,930,446	A	7/1999	Kanda
5,956,424	A	9/1999	Wootton et al.
5,980,044	A	11/1999	Cannon et al.
6,026,408	A	2/2000	Srinivasan et al.
6,047,291	A	4/2000	Anderson et al.
6,069,627	A	5/2000	Conrad et al.
6,092,154	A	7/2000	Curtis et al.
6,151,622	A	11/2000	Fraenkel et al.
6,211,869	B1	4/2001	Loveman et al.
6,222,549	B1	4/2001	Hoddie
6,226,038	B1	5/2001	Frink et al.
6,226,618	B1	5/2001	Downs et al.
6,246,803	B1	6/2001	Gauch
6,263,313	B1	7/2001	Milsted et al.
6,330,572	B1	12/2001	Sitka
6,404,446	B1	6/2002	Bates et al.
6,405,198	B1	6/2002	Bitar et al.
6,411,770	B1	6/2002	Ito et al.
6,519,571	B1	2/2003	Guheen et al.
6,522,418	B2	2/2003	Yokomizo et al.
6,573,907	B1	6/2003	Madrane
6,643,659	B1	11/2003	MacIssac et al.
6,658,568	B1	12/2003	Ginter et al.
6,678,002	B2	1/2004	Frink et al.
6,698,020	B1	2/2004	Zigmond et al.
6,714,594	B2	3/2004	Dimitrova et al.
6,721,490	B1	4/2004	Yao et al.
6,728,727	B2	4/2004	Komine et al.
6,732,183	B1	5/2004	Graham
6,795,506	B1	9/2004	Zhang et al.
6,865,540	B1	3/2005	Faber et al.
6,870,887	B2	3/2005	Kauffman et al.
6,917,979	B1	7/2005	Dutra et al.
6,934,339	B2	8/2005	Kato
6,947,959	B1	9/2005	Gill
6,961,445	B1	11/2005	Jensen et al.
6,970,510	B1	11/2005	Wee et al.
7,168,086	B1	1/2007	Carpenter et al.
7,177,520	B2	2/2007	Zetts
7,310,111	B2	12/2007	Ramirez-Diaz et al.
7,409,144	B2	8/2008	McGrath et al.
7,505,604	B2	3/2009	Zakrzewski et al.
7,522,163	B2	4/2009	Holmes
7,577,959	B2	8/2009	Nguyen et al.
7,629,995	B2	12/2009	Salivar et al.
7,650,625	B2	1/2010	Watkins
7,676,820	B2	3/2010	Snijder et al.
7,782,365	B2	8/2010	Levien et al.
7,783,154	B2	8/2010	Wilkins et al.
7,902,978	B2	3/2011	Pederson

7,952,609	B2	5/2011	Simerly et al.
8,135,852	B2	3/2012	Nilsson et al.
2001/0034250	A1	10/2001	Chadha
2001/0051927	A1	12/2001	London et al.
2002/0035732	A1	3/2002	Zetts
2002/0046292	A1	4/2002	Tennison et al.
2002/0052771	A1	5/2002	Bacon et al.
2002/0056123	A1	5/2002	Liwerant et al.
2002/0069218	A1	6/2002	Sull et al.
2002/0108115	A1	8/2002	Palmer
2002/0122659	A1	9/2002	McGrath et al.
2002/0145622	A1	10/2002	Kauffman et al.
2002/0194253	A1	12/2002	Cooper et al.
2003/0001885	A1	1/2003	Lin et al.
2003/0005034	A1	1/2003	Amin
2003/0018978	A1	1/2003	Singal et al.
2003/0025599	A1	2/2003	Monroe
2003/0044162	A1	3/2003	Angel
2003/0084451	A1	5/2003	Pierzga et al.
2003/0088877	A1	5/2003	Loveman et al.
2003/0135464	A1	7/2003	Mourad et al.
2003/0188019	A1	10/2003	Wesley
2003/0229900	A1	12/2003	Reisman
2004/0017471	A1	1/2004	Suga et al.
2004/0059996	A1	3/2004	Fasciano
2004/0098754	A1	5/2004	Vella et al.
2004/0131330	A1	7/2004	Wilkins et al.
2004/0133467	A1	7/2004	Siler
2004/0136590	A1	7/2004	Brouwer
2004/0153504	A1	8/2004	Hutchinson et al.
2004/0168184	A1	8/2004	Steenkamp et al.
2004/0210823	A1	10/2004	Miura et al.
2004/0216173	A1	10/2004	Horoszowski et al.
2004/0223606	A1	11/2004	Enete et al.
2004/0247284	A1	12/2004	Yamasaki
2004/0255329	A1	12/2004	Compton et al.
2004/0268222	A1	12/2004	Kawa et al.
2004/0268224	A1	12/2004	Balkus et al.
2005/0005000	A1	1/2005	Yoshimoto
2005/0019005	A1	1/2005	Kim et al.
2005/0049886	A1	3/2005	Grannan et al.
2005/0073585	A1	4/2005	Ettinger et al.
2005/0074100	A1	4/2005	Lederman
2005/0091311	A1	4/2005	Lund et al.
2005/0149940	A1	7/2005	Calinescu et al.
2005/0185634	A1	8/2005	Benco et al.
2005/0195823	A1	9/2005	Chen et al.
2005/0198125	A1	9/2005	Macleod Beck et al.
2005/0210520	A1	9/2005	Horvitz et al.
2005/0262535	A1	11/2005	Uchida et al.
2005/0262542	A1	11/2005	DeWeese et al.
2005/0278425	A1	12/2005	Wilsher et al.
2006/0047749	A1	3/2006	Davis et al.
2006/0056732	A1	3/2006	Holmes
2006/0143686	A1	6/2006	Maes
2006/0146184	A1	7/2006	Gillard et al.
2006/0156219	A1	7/2006	Haot et al.
2006/0161635	A1	7/2006	Lamkin et al.
2006/0205362	A1	9/2006	Chang et al.
2006/0236221	A1	10/2006	McCausland et al.
2006/0259589	A1	11/2006	Lerman et al.
2006/0263039	A1	11/2006	Chiang
2006/0274828	A1	12/2006	Siemens et al.
2007/0006177	A1	1/2007	Aiber et al.
2007/0022404	A1	1/2007	Zhang et al.
2007/0043860	A1	2/2007	Pabari
2007/0043875	A1	2/2007	Brannon
2007/0113184	A1	5/2007	Haot et al.
2008/0043106	A1	2/2008	Hassapis
2008/0320599	A1	12/2008	Raley et al.

FOREIGN PATENT DOCUMENTS

EP	1864229	12/2007
JP	2000-341635	12/2000
JP	2001-346164	12/2001
JP	2004-088384	3/2004

(56)

References Cited

FOREIGN PATENT DOCUMENTS

JP	2004-320667	11/2004
WO	WO-97/15018	4/1997
WO	WO-97/39411	10/1997
WO	WO-00/29980	5/2000
WO	WO-02/01384	1/2002
WO	WO-2005/027068	3/2005

OTHER PUBLICATIONS

David, "News Technology: The Cutting Edge," Appears in Capturing the Action: Changes in Newsgathering Technology, IEEE Colloquium, pp. 4/1-4/8, Oct. 27, 1995.

Gordon-Till, "My Opinion is, Opinions are Useful," Information World Review, Issue 184, four pages, Oct. 2002.

* cited by examiner




FIG. 1A




FIG. 1B

FIG. 2




FIG. 3





FIG. 4








FIG. 6





1

DIGITAL MEDIA ASSET MANAGEMENT SYSTEM AND METHOD FOR SUPPORTING MULTIPLE USERS

RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 11/517,016, filed Sep. 7, 2006, and claims the benefit of the earlier filing date under 35 U.S.C. §119(e) of U.S. Provisional Patent Application Ser. No. 60/714,674, filed Sep. 7, 2005, entitled “Method and System for Supporting Media Services,” and is a continuation-in-part of U.S. application Ser. No. 11/475,603, filed Jun. 27, 2006, entitled “Database System, Particularly For Multimedia Objects,” which is a continuation of U.S. patent application Ser. No. 10/311,903, filed Feb. 13, 2003, entitled “Database System, Particularly for Multimedia Objects,” which is a national stage application of PCT/GB01/02857 filed Jun. 27, 2001; the entireties of which are incorporated herein by reference.

BACKGROUND OF THE INVENTION

The media or broadcast industry has traditionally been confined to technologies that are expensive and an inflexible with respect to editing, production and delivery of media (e.g., video). By contrast, the communications affords great flexibility in terms of providing users with alternative networks and rich communication and entertainment services. In addition, the cost of equipment, from networking elements to end user equipment, follows a downward trend as advancements are made; for example, cellular phones are ubiquitous because of their affordability. The capabilities of these devices continue to evolve at a rapid pace; e.g., cellular phones are now equipped with high resolution displays and advanced processors to support sophisticated applications and services. Further, broadband data communications services have enabled transmission of bandwidth intensive applications, such as video broadcasts (e.g., web casts). The transformation of the communications industry has in turn influenced the media industry to rethink their business models and technological approaches.

However, in adopting these advances in communication technologies, the media industry faces a number of challenges. For instance, the issue of convergence of a broadband rich media experience and live television production and delivery needs to be addressed. Also, the demands of supporting real-time news, video on demand, user personalization, and continuing creative additions to initial systems pose additional engineering challenges. Further, delivery of interactive media (which describe real events in the real world in real-time) requires the capability to quickly acquire, store, edit, and composite live and other descriptive media by numerous users, e.g., editors, artists, and producers.

Based on the foregoing, there is a clear need for approaches that enable rapid processing and delivery of digital media.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention is illustrated by way of example, and not by way of limitation, in the figures of the accompanying drawings and in which like reference numerals refer to similar elements and in which:

FIGS. 1A and 1B are diagrams of a media services platform for supporting multi-tenancy, according to one embodiment of the present invention;

2

FIG. 2 is a diagram of a workflow process utilized in the system of FIG. 1A to edit digital media, according to one embodiment of the present invention;

FIG. 3 is a function diagram of a video server in the system of FIG. 1A, according to one embodiment of the present invention;

FIG. 4 is a diagram of virtual digital asset manager (VDAM) for storing digital media, according to an embodiment of the present invention;

FIG. 5 is a flowchart of an indexing process to enable distributed editing over a data network, according to an embodiment of the present invention;

FIG. 6 is a diagram of a cache architecture for storing media, according to an embodiment of the present invention; and

FIG. 7 is a diagram of a computer system that can be used to implement various embodiments of the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENT

An apparatus, method, and software for providing editing of digital media are described. In the following description, for the purposes of explanation, numerous specific details are set forth in order to provide a thorough understanding of the present invention. It is apparent, however, to one skilled in the art that the present invention may be practiced without these specific details or with an equivalent arrangement. In other instances, well-known structures and devices are shown in block diagram form in order to avoid unnecessarily obscuring the present invention.

Although the various embodiments of the present invention are described with respect to the Motion Picture Expert Group (MPEG) standards and Group of Pictures (GOP) technologies, it is contemplated that these embodiments have applicability to other equivalent video encoding standards and technologies.

FIG. 1A is a diagram of a media services platform for supporting distributed editing and storage of digital media, according to one embodiment of the present invention. The media services platform **101** provides an integrated media asset management platform with a fully modular architecture that enables users (e.g., customers, subscribers, etc.) to deploy the platform on a module-by-module basis as well as workflow-by-workflow. Media asset management functions include archiving, mastering of long-form content for video-on-demand (VOD) distribution, digital content aggregation and distribution. The platform **101** also supports remote proxy editing using a proxy editing application as executed by a proxy editor server **102**, thereby permitting fast-turnaround broadcast productions. The editing application utilizes low-resolution version of the video content for the purposes of editing; hence, the editing application is referred to as a “proxy editor.” To support the above features and functions, the media services platform **101** enables multi-channel distribution of digital content to any variety and number of devices and networks—e.g., wireless mobile devices, broadband, Internet Protocol Television (IPTV), and traditional TV platforms—thereby, reducing costs and increasing revenue over conventional systems. The architecture of the media services platform **101**, according to one embodiment of the present invention, supports compact to enterprise-scale deployments, and ensures that storage and processing capabilities are robust and scalable, suitable for mission-critical broadcast operations.

It is recognized that there is an increasing need for professional, cost-effective editing of video feeds, such as television

coverage of news or entertainment events, wherein the edited files can be provided over different alternative networks. For example, a user of a video enabled mobile cellular telephone might subscribe to a service that provides highlights of selected sporting events. Similarly, a user might subscribe to a sports headlines service, and receive files on a computer connected to a public data network, such as the global Internet. The real time delivery of events such as sports footage, interviews and edited highlights presents problems in such contexts, where it is necessary to produce compressed files to reduce the bandwidth for transmission over a cellular telephone network or a data network. Video files for such purposes need to be produced in an encoded format using, for instance, Group of Picture (GOP) technology, otherwise the raw digital stream would render timely transmissions and file storage impractical.

Thus, a video stream is created to include a sequence of sets of frames (i.e., GOP). By way of example, each group, typically 8 to 24 frames long, has only one complete frame represented in full. This complete frame is compressed using only intraframe compression, and thus is denoted as an I frame. Other frames are utilized and include temporally-compressed frames, representing only change data with respect to the complete frame. Specifically, during encoding, motion prediction techniques compare neighboring frames and pinpoint areas of movement, defining vectors for how each will move from one frame to the next. By recording only these vectors, the data which needs to be recorded can be substantially reduced. Predictive (P) frames refer to the previous frame, while Bi-directional (B) frames rely on previous and subsequent frames. This combination of compression techniques is highly effective in reducing the size of the video stream.

With GOP systems, an index is required to decode a given frame. Conventionally, the index is only written at the end of the file once the file has completed the encoding process. As a result, no index is available until the recording is completed. The implication is that the production of an edited version of the file, for example to transmit as highlights over a cellular phone network, cannot commence until the recording is completed and this index file produced. The media services platform **101** addresses this drawback by creating a separate index file, which can be supplemental to the routinely generated index file, during the recording and encoding process; this mechanism is detailed with respect to FIG. 5.

Accordingly, the platform **101**, in an exemplary embodiment, can provide remote editing over any data network (e.g., Internet Protocol (IP)-based) that can support connectivity to the proxy editor server **102**, whereby editing can commence without having to wait for completion of the recording. The proxy editor application resident on the server **102** enables developers to build professional-level desktop video editing applications using, for example, the Microsoft Windows Media 9 Series platform.

The platform **101** also provides significant scalability due to decoupled storage. Conventional editing systems required direct disk access to the video file. This poses a severe scalability issue, as every editing function (e.g., play, scrub, etc.) from the editing client creates disk traffic. If the storage cannot timely respond, a conventional editing application often freezes or crashes, such a scenario is unacceptable for real time feeds. With the media services platform **101**, the content is downloaded once on each client cache; thus, the centralized storage requirements are reduced by a very significant factor (depending on editing type).

As seen in FIG. 1A, the media services platform **101** utilizes a shared repository **103** that stores media (e.g., digitized

video) content ingested from one or more video servers **105**. Ingesting involves obtaining content into the media services platform **101**, and can be accomplished locally or from a remote location. In one embodiment of the present invention, the repository **103** is deployed as a shared Storage Area Network (SAN) or NAS (Network Area Storage), which has the capability for high-performance video ingest and playback. The shared SAN **103** can utilize scalable Fibre Channel switch fabric to interface with a Fibre Channel disk array and nearline tape libraries. The video servers **105**, as will be more fully described in FIG. 3, can interface any type of content sources, such as a media archive **107**, a live feed **109**, or a digital feed **111**.

The media services platform **101** includes a workflow system **113**, which comprises a workflow engine **115** and one or more resource servers **117** to support editing and distribution of digital media. The automated workflow provides the ability to automate and orchestrate repetitive workflows. In particular, the workflow system **113** offers users an overview of their work and associated events; that is, the system **113** supports an application that shows the status and progress of each job and links to relevant applications that enable the users to perform their tasks and advance the project towards completion. The workflow engine **115** controls workflow jobs and dispatches them to the resource servers **117**. Communication among the resource servers **117** is facilitated by, for example, Microsoft Message Queuing.

In addition to providing individual users a central point for managing their work, the workflow system **113** is also useful as a monitoring system. For example, the system **113** can support a graphical user interface (GUI) on the user side, such that users can quickly determine through visual indicators whether tasks have been completed or error conditions exist. The users (e.g., administrators) can “drill down” to view more detail. Also, jobs can be paused, restarted (from any stage), aborted and deleted from the workflow application. This capability provides users with full control over the priority of the jobs. Additionally, the system **113** can record timing information for every step of a task, thereby enabling generation of reports on delivery turnaround etc.—e.g., for Service Level Agreement (SLA) reporting.

According to one embodiment of the present invention, the media services platform **101** can be implemented with a pre-configured, standard set of common workflows. For instance, these workflows can support generic delivery of files, rendering of edits and delivery of content from the video server **105**. Moreover, customizable workflows are supported, wherein the users can integrate new services.

As shown, the media services platform **101** comprises core servers, such as an object store **119**, a media server **121**, and an application server **123**. In an exemplary embodiment, the object store **119** contains configuration information for the workflow system **113**. Configuration information include, in an exemplary embodiment, parameters of every service, the capabilities of every resource server **117**, the definition of workflows, and the real time status of every job. The object store **119** supports the various applications that interface with it through an object store Application Program Interface (API). According to one embodiment of the present invention, the object store **119** has an object-based database schema (e.g., Microsoft SQL (Structured Query Language) Server, for example. The media server **121** receives stream broadcasts and serves the stream on to individual user workstations using, for example, Microsoft Windows Media. The stream contains, for example, Society of Motion Picture and Television Engineers (SMPTE) timecode, enabling the stream to be used as a frame-accurate source for live logging.

The application server **123** provides dynamic web site creation and administration functions, such as a search engine, and database capabilities. In an exemplary embodiment, the application server **123** executes Microsoft Internet Information Server (IIS), and can be configured for high availability and load-balancing based on industry standard components.

The media server **121** and the application server **123** interface with the data network **125**, which can be a corporate network or the Internet. The application server **123** is thus accessible by a workstation **127**, which can be any type of computing device—e.g., laptop, web appliance, palm computer, personal digital assistant (PDA), etc. The workstation **127** can utilize a browser (e.g., web-based), generally, to communicate with the media services platform **101**, and a downloadable applet (e.g., ActiveX controls) to support distributed video editing functionality. The browser in conjunction with the applet is referred to an editing (or editor) interface—e.g., the proxy editor player **128**. The workstation **127** can also be equipped with voiceover microphone and headphones to facilitate the editing process. The proxy editor player **128** communicates with the proxy editor server **102** to enable the viewing and editing of content, including live video, remotely. Editing functionalities include immediate access to frame-accurate content, even while being recorded, full audio and video scrubbing of source clips and edit timelines over the network **125**, and generation of Advanced Authoring Format/Edit Decision List (AAF/EDL) files for craft edit integration.

To connect to the media services platform **101**, the workstation **127** need not require special hardware or software. As mentioned, the workstation **127** need only be configured to run a browser application, e.g., Internet Explorer, for communication over the data network **125**. With this user interface, changes or upgrades to the workstation **127** are not required, as all the applications are hosted centrally at the platform **101**.

In addition to the video server **105** within the media services platform **101**, a remote video server **129** can be deployed to ingest content for uploading to the platform **101** via the data network **125**. The video servers **105**, **129** include, in an exemplary embodiment, a longitudinal timecode (LTC) reader card as well as other video interfaces (e.g., RS-422 control card, Windows Media 9 Encoder and Matrox DigiServer video card). Video editing relies on the use of timecodes to ensure precise edits, capturing all in “in points” and “out points” of the edits. An edited video can be characterized by an edit decision list (EDL), which enumerates all the edits used to produce the edited video. LTC timecodes are recorded as a longitudinal track, analogous to audio tracks. With LTC, each frame time is divided into 80 bit cells. LTC timecodes are transmitted serially in four-bit nibbles, using Manchester codes.

The video servers **105**, **129** can be remotely controlled by the workstation **127**. Also, these servers **105**, **129** can connect to the shared SAN **103** via Fibre Channel and a file system by, e.g., ADIC™.

A syndication (or distribution) function **131** can then distribute content over various channels, such as a wireless network **133** (e.g., cellular, wireless local area network (WLAN)), a television network **135**, and a broadband Internet Service Provider (ISP) network **137**. Depending on the capabilities supported by the wireless or wired access network (e.g., networks **133** and **137**), rich services, such as presence, events, instant messaging (IM), voice telephony, video, games and entertainment services can be supported.

Although the video server **105**, the workflow engine **115**, the object store **119**, the media server **121**, and the application

server **123** are shown as separate components, it is recognized that the functions of these servers can be combined in a variety of ways within one or more physical component. For example, the object store **119**, the application server **123**, and the workflow engine **115** can reside within a single server; and the video server **105** and the media server **121** can be combined into a common server.

As mentioned above, the media services platform **101** enables media asset management, rapid production, and robust, cost-effective proxy editing capabilities. By way of illustration, management of media assets to support broadband video on demand (VOD) is described. One of the first tasks involved with VOD applications is ingesting full length movies into the video servers **105** for mastering and editing (e.g., removing black, stitching tapes together, adding legal notices etc). The masters are then stored on the shared SAN **103**. The content is then transcoded to a high quality media stream format, such as Microsoft Windows Media 9 Series, and delivered automatically with metadata to their broadband video pay-per-view portal (e.g., any one or more of the networks **133**, **135** and **137**).

Additionally, the media services platform **101** can offer video archiving services. For instance, customers can extend their online storage with nearline tape and manage content seamlessly across multiple storage devices using add-on archive modules. Online storage can be backed up and/or migrated to tape according to automated policies. Advantageously, this archival approach can be transparent to the users; that is, the users are never aware that the master video is no longer stored on expensive disk-based storage. In one embodiment, a library application can be implemented with the media services platform **103** to provide seamless integration with offline video and data tape archives. Further, the media services platform **101** provides high integration with existing production workflows through its capability to transcode and deliver any content contained in the archive to, for example, popular non-linear editors (e.g., AVID™ editor).

Furthermore, the media services platform **101** enables flexible, cost-effective content aggregation and distribution, which is suitable for content service providers. Typical workflows involve aggregation of content from owners in such formats as Motion Pictures Expert Group (MPEG)-2 or Windows Media 9, along with metadata in eXtensible Markup Language (XML) files, using pre-configured File Transfer Protocol (FTP) hot folders. “Hot folders” are predefined folders that trigger a workflow event (e.g., file conversion, compression, file transfer, etc.) upon movement of files into the folder. These owners can submit content directly to the workflow system **113** for automatic transcoding, Digital Rights Management (DRM) protection and syndication to multi-channel operators.

According to one embodiment of the present invention, the media services platform **101** utilizes a unified user interface (e.g., web browser) for accessing applications supported by the platform **101**. It is recognized that typical production and content delivery workflows often involve the use of multiple separate applications: one application for logging, a second application for encoding, a third one for editing, a fourth application for asset management, and so on. Consequently, the challenge of effectively managing workflows is difficult. The task is even more daunting in a multi-channel production and distribution environment, as greater elements need to be coordinated and more applications have to be learned over traditional television environments.

The media services platform **101** advantageously simplifies this task by permitting access to the multitude of applications via a single unified user interface as part of a coherent

workflow. In this manner, although various technologies are involved, the user experience is that of a single, user-friendly suite of tools, which shield non-technical users from the complex integration of applications and technologies.

The applications supported by the platform **101** include the following: media asset management and search, video editing, video server services, workflow, syndication, upload of media, library service, administration, quality assurance, copyright protection, music cue sheet services, and reporting. In addition, the users can develop their own applications within the unified user interface. Asset management permits users to manage the location of content within organized folder structures and categories. This capability is more fully described with respect to FIG. 4. The asset search function offers a generic search capability across the entire object store **119**.

The media services platform **101** also provides a flexible and cost-effective approach for proxy logging and editing of live and archive material. Such editing services can be in support of news and sport editing, archive browsing and editing, mobile, broadband and IPTV production and mastering, and promotion production. The editing application provides viewing and logging of live feeds, frame-accurate proxy logging and editing, and remote proxy editing (e.g., utilizing Windows Media 9 Series proxy format). In addition, the editing application can support instant logging and editing while the feed is recording, as well as audio and video scrubbing. This editing application includes the following capabilities: edit timeline with effects; voiceover (while editing remotely—which is ideal for translation workflows); save edit projects with versions; generate thumbnail and metadata from within the editing user interface; and export EDL's or render finished edits ready for transcoding and delivery. With this application, a user, through an inexpensive workstation **127**, can efficiently master a movie for VOD distribution, rough-cut a documentary, or create a fully-finished sports highlight video with voiceover and effects.

The media services platform **101**, in an exemplary embodiment, utilizes a Windows Media 9 Series codec, which allows high quality video (e.g., DVD-quality) to be logged and edited across the data network **125**. Further, the platform **101** employs intelligent caching to ensure that the applications are as responsive as editing on a local hard drive, even over low-bandwidth connections; the caching architecture is described below with respect to FIG. 6.

The syndication application automates the creation and delivery of content and metadata to very specific standards for a range of target systems without manual intervention.

The upload application allows users to ingest digital files into the media services platform **101** and submit them to any permitted workflow. The users (with administrative responsibilities) can control which file types are allowed, which workflows are compatible, and the way in which different types of content are processed. The upload application can facilitate submission of the files to automatic workflows for hands-off end-to-end processing as well as to manual workflows that require manual intervention.

The upload application is complemented by a hot folder system, wherein workflow activities are automatically initiated upon movement of files into and out of the hot folders. The file system folders can be pre-configured to behave like the upload application and pass files of particular types to the workflows. Metadata for each asset provided in accompanying XML files can be acquired and mapped directly into the object store **119**.

The reporting application enables users to create “printer-friendly” reports on any information stored in the object store

119. The reporting application is pre-configured with a number of default reports for reporting on content delivery. Users can filter each report by selecting a desired property of the data, e.g., subscription name, or start and end date. Through the API of the media services platform **101**, users (and system integrators) can create new report templates and queries.

The library application offers the ability to manage physical media that contain instances of assets managed in the media services platform **101**. Even with continuing expansion in the use of digital media, traditional media continue to play an important role. Typical production environments possess a number of video tapes, DVDs or other physical media for storing content and data. Some environments utilize large established archives.

In mixed media environments, it is beneficial to manage digital and physical instances of content in an integrated manner. Accordingly, the library application provides the following capabilities. For example, the application permits the user to generate and print barcodes for the physical media and shelves, with automatic naming as well as bulk naming (with configurable naming conventions). Also, barcodes are employed for common actions, thereby allowing completely keyboard-free operation for checking in/out and shelving of the physical media. The library application additionally can manage items across multiple physical locations, e.g., local and master libraries. Further, the application supports PDA-based applications with a barcode scanner for mobile checking in/out and shelving. The library application advantageously simplifies management of multiple copies of the same asset on several physical media and storage of multiple assets on the same tape or DVD. The library application can further be used in conjunction with robotic tape libraries to track tapes that have been removed and shelved.

Moreover, the media services platform **101** provides an administration function to tailor system configuration for different customers. It is recognized that a “one size fits all” configuration for all users is non-existent. That is, each user, department, organization and customer has its own set of requirements. Therefore, the media services platform **101** supports concurrent use of multiple configurations. For example, each deployment can configure to its own user groups, create new workflows, integrate new services, support new content types, and specify new output media formats. The customer can also change and add metadata structures and fields, and integrate existing web-based applications into the user interface. The above capabilities can be executed, via the administration application, with immediate effect without shutting down the platform **101**. Additionally, in a multi-department deployment scenario, multiple logical instances of the media services platform **101** can be configured with their own unique configurations.

According to one embodiment of the present invention, the media services platform **101** can be implemented as a turn-key system within a single box—e.g., in-a-box flight case. Under this configuration, there is no need for a costly and time-consuming IT (information technology) integration undertaking to rack the components or integrate them into the customer's network. Under this arrangement, the platform **101** is be configured as a plug-and-play system, connecting to the network automatically.

FIG. 1B shows a diagram of the media services platform configured to support multi-tenancy. Under this scenario, the platform **101** is implemented as a hosted environment, whereby the platform **101** is located and maintained within a service provider network **151**. The media services platform **101** can be configured to serve numerous customers of the service provider. Each of the customer networks **153**, **155** can

employ one or more proxy editor players **157**, **159**, respectively. Further, it is contemplated that this multi-tenancy capability can facilitate the ability to permit different customers to work on common editing projects.

With this multi-tenant arrangement, the service provider can better utilize system resources, and more cost effectively supply the remote editing service.

FIG. 2 is a diagram of a workflow process utilized in the system of FIG. 1A to edit digital media, according to one embodiment of the present invention. For the purposes of explanation, the workflow capability of the media services platform **101** is described with respect to the video editing application. In step **201**, the media that is to be edited is obtained; the media can undergo an ingest process or simply exist as a digital file that can be uploaded (using the upload application as earlier explained). Ingesting is the process of capturing content into the media services platform **101** and can occur locally or remotely with respect to the platform **101**. If uploaded, the user delivers the project to selected hot folders that automatically define categorization.

The media is then edited, per step **203**. By way of example, the user, utilizing the proxy editor player **128** (which is the counterpart software to the proxy editor supported by the media services platform **101**) on the workstation **127**, can select and log the feed (assuming a live feed which is always visible), either marking in and out points manually or using an auto-clip feature for rapid logging. The user can also insert commentary and assign a rating to the video for determining which segment of the content is the most compelling content, thereby providing an indication of the selected clips that should be edited. During or after logging, the user can select clips from the log and use the proxy editor player to trim the selection. For example, the user can jog and shuttle along a timeline, or utilize a mouse wheel to scroll frame by frame to the desired cut point. The user can then preview the selection before placing it on the edit timeline. Thereafter, the user can manipulate the clips on the timeline, reorder and trim the selections. The proxy editor player **128** can permit the user to apply zoom and crop effects to close in on areas of interest; this capability is particularly valuable for broadband or mobile outputs where detail is important. The user can record a voiceover directly onto the timeline, thereby completing the edit.

The edit is then rendered, as in step **205**, as part of a workflow. In an exemplary embodiment, the edit is rendered using a high-resolution MPEG-2 master. Alternatively, an associated EDL is delivered to an integrated craft edit for completion. The media services platform **101** can support various workflows for craft editor integration, such as, store and forward, and instant editing. As for the store and forward approach, the content can be viewed, logged and edited using the proxy editor into packages for automated transcoding (from master MPEG-2) and delivery to popular non-linear editing systems (e.g., AVID Unity and AVID Media Composer, Adobe Premiere, Apple Final Cut Pro, Media 100, iFinish, Pinnacle Liquid and Vortex). With respect to instant editing, using the proxy editor player **128**, the user can execute an ingest of a live feed, which can be viewed, logged and edited. The user can then export an EDL to a craft editor, which can be a third party craft editor (e.g., Incite Editor E3) that is integrated with the media services platform **101**. When imported into Incite, the timeline is rebuilt frame-accurately, pointing to the MPEG-2 master on the shared SAN **103**. Once the edit is complete, the craft editor creates a new MPEG-2 digital master, which is automatically re-ingested back into the platform **101** when dropped in an appropriate Hot Folder.

It is noted that the above process can occur while the video feeds are still being recorded, thus enabling the quickest possible turnaround of content for broadcast programs (e.g., sports and news).

In step **207**, metadata is added. The file is transcoded (per step **209**) and reviewed and/or approved (step **211**). Thereafter, the edited file is delivered, per step **213**. The last stage in the workflow is the delivery of content files and metadata to other systems (e.g., networks **133**, **135**, and **137**) that are responsible for delivery of content to consumers. The syndication application of the media services platform **101** provides the automated delivery of the content and metadata. The media services platform **101** operates on a “set it and forget it” principle. In other words, once a configuration is specified, no other input is required thereafter. For instance, a configuration of a new subscription is set to the required content categories, the technology used to create each file as well as the specific set of parameters are specified, and the file-naming conventions and delivery details are indicated. Every subsequent delivery from the workflow application simply implements the subscription when the correct criteria are met. Whenever the user requires a new output format, the user can specify the various configuration parameters, including the codec, frame rate, frame size, bit rate, and encoder complexity.

It is noted that any technology plugged into the workflow system **113** can be automated—e.g., for pre-processing, transcoding, DRM protection, watermarking, delivery, or any other purpose required.

The above workflow process can be illustrated in the following example involving a sports production. Under this scenario, a customer produces, on a weekly basis for instance, multiple fully-edited football match highlights every week for mobile operators (utilizing Third Generation/Universal Mobile Telecommunications System (3G/UMTS) technologies). The customer requires a two minute voiced highlight package be delivered to the operators within 4 minutes of the end of each game for these concurrent matches. This requirement can be achieved with the media services platform **101**, whereby live broadcast feeds are recorded using the video servers **105**. Producers edit and log the media using the proxy editor application (e.g., player **128**) during recording of the matches. Once the matches are over, they simply select a deliver button presented by the proxy editor player **128**. The workflow system **113** automatically renders the proxy edit using, for instance, a MPEG-2 50 Mbps I-frame master, before automatically transcoding the edit into the mobile formats requested by the operators and delivering the content and metadata XML to their content distribution networks. In this manner, the mobile subscribers can purchase and view the video clips on their mobile handsets within minutes of the end of each game.

According to one embodiment of the present invention, the media services platform **101** can be integrated with a newsroom computer system and playout video server. The video server **105** ingests content from live feeds or tape, and journalists and producers throughout the news organization can instantly start to log and edit the live feeds from their desktop using the proxy editor player **128**. Finished edits are rendered and transcoded direct from the proxy editor application to a gallery playout video server. Notification is automatically sent to the newsroom computer system and automation system when every new package is available.

FIG. 3 is a function diagram of a video server in the system of FIG. 1A, according to one embodiment of the present invention. As mentioned, the video server **105**, among other functions, is capable of handling live broadcast video in a

flexible, feature rich and cost-effective manner. In this example, the video server **105** can be slaved by a Video Disk Communications Protocol (VDCP)-compliant automation system. It is noted that the video server **105** can support both National Television System Committee (NTSC) and Phase Alternating Line (PAL) standards. The video server **105** is controllable from any user workstation (e.g., workstation **127**) without geographical constraint. The video server **105** can in turn control, for instance, an attached video tape recorder (VTR) over an RS-422 interface, thereby allowing frame-accurate recording and lay back to tape, and preserving timecode through the entire process.

In one embodiment, the video server **105** includes a live media stream module **301**, a media proxy file module **303**, and a video format module **305**. The live media stream module **301** communicates with the user interface **313** to provide logging and monitoring functions. The media proxy file module **303** supports the capability to perform editing functions during recording of the video. The video format module **305** converts a raw video stream into a standardized format—MPEG-2, for example. The modules **303** and **305** interface the repository **103** to store the ingested contents.

As shown, the server **105** can support various input sources: an LTC time code source **307**, a Serial Digital Interface (SDI) source **309**, and a VDCP slave source **311**. The video server **105** can generate multiple outputs in real-time from the SDI source **307**, in contrast to conventional video servers which generate only a single output. The modules **301**, **303**, **305** generate three types of outputs. One output is that of MPEG-2, in which the user can select between long-GOP and I-frame for each server, ranging from DVD-quality 5 Mbps long-GOP to 50 Mbps I-frame only. The audio is captured at 48 kHz, for instance. The live media stream module **301** can generate a live media stream (e.g., Windows Media 9 Series) for broadcast over a network (e.g., networks **133-137** of FIG. 1A) to one or more media servers (e.g., media server **121**), which serve the stream on to individual user workstations. The stream can include SMPTE timecode, thereby providing a frame-accurate source for live logging.

Finally, the media proxy file module **303** can produce a file (e.g., Windows Media proxy file) for storage in the SAN **103**. The proxy editor permits this file, according to one embodiment, to be opened for viewing and editing while the file is still being written. Thus, in conjunction with the proxy editor, the video server **105** supports fast-turnaround production of live events without the need for dedicated high-bandwidth networks and expensive edit suites, and without sacrificing quality or functionality.

In addition to the robust video editing functionality, the media services platform **101** provides management of the digital assets, as next explained.

FIG. 4 is a diagram of virtual digital asset manager (VDAM) for storing digital media, according to an embodiment of the present invention. The virtual asset manager **401** (e.g., object store **119**) ensures that the digital archive can be fully integrated into the production workflow, including desktop proxy viewing, logging and editing, craft editing, and delivery. For example, sections of an archive MPEG-2 master can be selected using a low-resolution proxy and exported to an AVID editor or AVID Unity (the files can be transcoded and delivered automatically via Telestream FlipFactory).

The library application, as earlier described, provides physical asset management (e.g., tape check-in, check-out, shelving and barcode printing, etc.) to connect physical tape content with its digital equivalent stored in the repository **103**.

The asset manager **401** enables frame-accurate remote browsing, logging and selection of thousands of hours of

archive content from anywhere on the Internet or a private corporate WAN (e.g., data network **125**). The asset manager **401** allows users to manage the location of content within organized folder structures and categories. Content can be modified, deleted, copied, pasted and added through this application. Folders can store any asset type configured by administrators, from audio and video to ringtones, images and documents.

The asset manager **401** also offers a flexible search capability for the object store **119**. Users can search across their own work and that of others, thus facilitating sharing and simple retrieval of content. Further, other applications within the media services platform **101** can utilize this asset search capability, as to provide a consistent and recognizable function (i.e., common dialog) across these applications.

The object store **119** enables the asset management capability of the media services platform **101**, permitting users (e.g., administrators) to change the fields and forms associated with an asset at any point by utilizing the proxy editor player **128**. Under this approach, adapting the platform **101** to satisfy changing user requirements does not require expensive database administrators.

In this example, the virtual digital asset manager **401** accumulates content from a variety of content databases **403** and **405**, and thus is considered “virtual.” A customer can generate its own content, which can be stored in the original content database **403**. In addition, the content of one or more third party content providers can be offered by the asset manager **401**. Accordingly, the VDAM **401** enables tying of business partners (e.g., third party content providers), thereby enhancing the distribution of digitized assets. In an exemplary embodiment, the content owner can push content into the virtual digital asset manager **401** over the world wide web (e.g., network **125**). The virtual digital asset manager **401** can also provide private storage of asset data, and facilitate publishing of the content. In addition to being configured as an asset manager, the VDAM can act as a directory server of all the assets provided by users.

Furthermore, it is contemplated that the virtual digital asset manager **401** can provide advertisement and transaction support. That is, a user can produce a video file that includes the stored content as well as advertisements; the manager **401** then tracks transactions relating to the retrieval and/or viewing of the edited video file. In this manner, the customer has the capability to charge or otherwise account for such services.

Effectively, the VDAM supports a “most needed” based approach, rather than a “most requested” based approach of convention systems. In accordance with one embodiment of the present invention, the virtual digital asset manager **401** can be implemented external to the media services platform **101** as an independent system.

FIG. 5 is a flowchart of an indexing process to enable distributed editing over a data network, according to an embodiment of the present invention. Conventionally, to support editing, an index file is generated for addition to the end of the video file. The media services platform **101** provides a mechanism, whereby during recording and encoding of a video file, editing can be concurrently performed. This is enabled by created of a supplemental index file that is separate from the conventional index file. The separate index file is updated dynamically at intervals during recording and encoding. This index can be added to the video file when recording and encoding has been completed; optionally, the separate index file can then be deleted. Video frames for use in the editing process are created using data in the video file and the separate index file.

In step **501**, video signals are received by the platform **101**; namely, through the video server **105**. The video signals are then recorded and encoded, as in step **503**. In step **505**, the first index file is generated during the recording. This first index file is updated during the encoding process (step **507**). In other words, while the video file is being recorded and subjected to encoding (e.g., GOP encoding), a separate index file is created and updated at regular intervals during the encoding process. Typically, the updating of the index file can occur every half a second. If the encoding process is complete (as determined in step **509**), then a second index file (i.e., conventional index file) is generated, as in step **511**. Otherwise, the update of the first index file is continued.

If the editing application attempts to connect to a video file and cannot locate the index at the end of the file, the application will look automatically for the separate index file. The index file could be assigned the same name as the basic video (or media) file, but with a different extension—although mapping to any name of file could be used. If an appropriate index file (which can indicate a different file extension than the video file) is found, the editor uses this external index to play/render the file, which is still being recorded. This results in the editor being able to access content rapidly (e.g., within a one second maximum of the content being recorded). Once recording stops and the conventional index is added to the end of the video file, the external index file can be deleted as no longer necessary.

The above process can be applied to any GOP based video format (including Windows Media).

FIG. **6** is a diagram of a cache architecture for storing and manipulating media, according to an embodiment of the present invention. To offer the flexible, robust editing functions, a software-based, intelligent video cache system **601** is utilized. The system **601** enables frame accurate scrubbing and editing of GOP based content. Due to the processor demand in decoding GOP based content, GOP based editing has been implemented conventionally as hardware based functionality. This aspect of the present invention provides a caching architecture which removes this requirement and enables software based real-time long GOP editing. This architecture is implemented by the editing application of the media services platform **101**.

The architecture of the intelligent video cache system **601** has a number of layers: a video file content layer **603**; a non-sequential, compressed video file cache **605**; and a decompressed frame cache **607**. The video file content layer **603** provides for locally hosted video file content. The second layer **605** provides for a compressed video file cache within a client player. This cache **605** is non-sequential so that only parts of the video file (at GOP resolution) can be cached. In one embodiment, the cache **605** is maintained in main memory (e.g., Random Access Memory (RAM)) of the workstation **127**, but can be aged by the player software to local disk. Also, within the client player, the decompressed frame cache **607** is provided in video memory (VRAM).

In this example, the cache **601** is filled by asynchronous proactive caching threads **609**, which follow and predict user behavior patterns as well as fill the different layers **603**, **605** and **607** of the cache **601** as required to provide the best editing experience (within the constraints of the local workstation resources in terms of Central Processing Unit (CPU), RAM, disk and VRAM). The asynchronous aspect of the system is significant, and provides the user with an immediate response when scrubbing throughout a file or editing. If the system has not yet cached the desired frame, the player software can show the closest cached/decompressed frame and display a status symbol indicating to the user that the current

frame is not the correct frame. If the user waits, eventually that frame will render into the correct frame. The user interface is not locked by the caching mechanism—i.e., the user can always choose to scrub somewhere else, play, etc. Furthermore, cache requests can be configured to have an expiry timeout, enabling cancellation to avoid building long queues of caching requests (which could no longer be relevant).

The following modes of operation of the editor player **128** are considered: idle, scrubbing, and playing. In idle mode, when the player has not changed state within a predetermined period of time (e.g., such as in the last 2 seconds), a playback caching thread first ensures that it has cached the next few seconds forward and backward from the playback head position. The thread ensures that the content is cached in decompressed VRAM cache **607**. In this manner, if the user suddenly decides to play, the system can respond immediately. Once the playback caching thread is satisfied that the content is cached for immediate playback, the riddling thread is started.

The job of the riddling thread is to proactively download frames throughout the video in case the user starts scrubbing. The thread first downloads a GOP in the middle of the file, then every third of the file, then every ninth of the file, etc. This continues until the VRAM is full (it always leave the playback thread immediate playback content, but can replace other frames which have been cached and are no longer relevant). Once the VRAM is full, the thread continues—but only to the compressed RAM cache and disk cache. If enough resources exist on the workstation **127** and time is left in idle mode, the full video can be cached in the compressed cache.

The scrubbing mode is triggered by fast “playback head” movement, by a user operating an on screen editing tool (when not in play mode). The playback caching thread is disabled and all resources are given to the riddling thread to provide the best scrubbing experience.

When a play “button” is selected by a user within the proxy editor player **128**, the playing mode is triggered. In this mode, the playback caching thread, and the riddling thread are disabled. A look-ahead caching thread is started which decompresses into VRAM the content ahead, and faster (if there are sufficient system resources) than the playback head.

The processes described herein for supporting distributed editing may be implemented via software, hardware (e.g., general processor, Digital Signal Processing (DSP) chip, an Application Specific Integrated Circuit (ASIC), Field Programmable Gate Arrays (FPGAs), etc.), firmware or a combination thereof. Such exemplary hardware for performing the described functions is detailed below.

FIG. **7** illustrates a computer system **700** upon which an embodiment according to the present invention can be implemented. For example, the processes described herein can be implemented using the computer system **700**. The computer system **700** includes a bus **701** or other communication mechanism for communicating information and a processor **703** coupled to the bus **701** for processing information. The computer system **700** also includes main memory **705**, such as a random access memory (RAM) or other dynamic storage device, coupled to the bus **701** for storing information and instructions to be executed by the processor **703**. Main memory **705** can also be used for storing temporary variables or other intermediate information during execution of instructions by the processor **703**. The computer system **700** may further include a read only memory (ROM) **707** or other static storage device coupled to the bus **701** for storing static information and instructions for the processor **703**. A storage

device 709, such as a magnetic disk or optical disk, is coupled to the bus 701 for persistently storing information and instructions.

The computer system 700 may be coupled via the bus 701 to a display 711, such as a cathode ray tube (CRT), liquid crystal display, active matrix display, or plasma display, for displaying information to a computer user. An input device 713, such as a keyboard including alphanumeric and other keys, is coupled to the bus 701 for communicating information and command selections to the processor 703. Another type of user input device is a cursor control 715, such as a mouse, a trackball, or cursor direction keys, for communicating direction information and command selections to the processor 703 and for controlling cursor movement on the display 711.

According to one embodiment of the invention, the processes described herein are performed by the computer system 700, in response to the processor 703 executing an arrangement of instructions contained in main memory 705. Such instructions can be read into main memory 705 from another computer-readable medium, such as the storage device 709. Execution of the arrangement of instructions contained in main memory 705 causes the processor 703 to perform the process steps described herein. One or more processors in a multi-processing arrangement may also be employed to execute the instructions contained in main memory 705. In alternative embodiments, hard-wired circuitry may be used in place of or in combination with software instructions to implement the embodiment of the present invention. Thus, embodiments of the present invention are not limited to any specific combination of hardware circuitry and software.

The computer system 700 also includes a communication interface 717 coupled to bus 701. The communication interface 717 provides a two-way data communication coupling to a network link 719 connected to a local network 721. For example, the communication interface 717 may be a digital subscriber line (DSL) card or modem, an integrated services digital network (ISDN) card, a cable modem, a telephone modem, or any other communication interface to provide a data communication connection to a corresponding type of communication line. As another example, communication interface 717 may be a local area network (LAN) card (e.g. for Ethernet™ or an Asynchronous Transfer Model (ATM) network) to provide a data communication connection to a compatible LAN. Wireless links can also be implemented. In any such implementation, communication interface 717 sends and receives electrical, electromagnetic, or optical signals that carry digital data streams representing various types of information. Further, the communication interface 717 can include peripheral interface devices, such as a Universal Serial Bus (USB) interface, a PCMCIA (Personal Computer Memory Card International Association) interface, etc. Although a single communication interface 717 is depicted in FIG. 7, multiple communication interfaces can also be employed.

The network link 719 typically provides data communication through one or more networks to other data devices. For example, the network link 719 may provide a connection through local network 721 to a host computer 723, which has connectivity to a network 725 (e.g. a wide area network (WAN) or the global packet data communication network now commonly referred to as the “Internet”) or to data equipment operated by a service provider. The local network 721 and the network 725 both use electrical, electromagnetic, or optical signals to convey information and instructions. The signals through the various networks and the signals on the

network link 719 and through the communication interface 717, which communicate digital data with the computer system 700, are exemplary forms of carrier waves bearing the information and instructions.

The computer system 700 can send messages and receive data, including program code, through the network(s), the network link 719, and the communication interface 717. In the Internet example, a server (not shown) might transmit requested code belonging to an application program for implementing an embodiment of the present invention through the network 725, the local network 721 and the communication interface 717. The processor 703 may execute the transmitted code while being received and/or store the code in the storage device 709, or other non-volatile storage for later execution. In this manner, the computer system 700 may obtain application code in the form of a carrier wave.

The term “computer-readable medium” as used herein refers to any medium that participates in providing instructions to the processor 703 for execution. Such a medium may take many forms, including but not limited to non-volatile media, volatile media, and transmission media. Non-volatile media include, for example, optical or magnetic disks, such as the storage device 709. Volatile media include dynamic memory, such as main memory 705. Transmission media include coaxial cables, copper wire and fiber optics, including the wires that comprise the bus 701. Transmission media can also take the form of acoustic, optical, or electromagnetic waves, such as those generated during radio frequency (RF) and infrared (IR) data communications. Common forms of computer-readable media include, for example, a floppy disk, a flexible disk, hard disk, magnetic tape, any other magnetic medium, a CD-ROM, CDRW, DVD, any other optical medium, punch cards, paper tape, optical mark sheets, any other physical medium with patterns of holes or other optically recognizable indicia, a RAM, a PROM, and EPROM, a FLASH-EPROM, any other memory chip or cartridge, a carrier wave, or any other medium from which a computer can read.

Various forms of computer-readable media may be involved in providing instructions to a processor for execution. For example, the instructions for carrying out at least part of the present invention may initially be borne on a magnetic disk of a remote computer. In such a scenario, the remote computer loads the instructions into main memory and sends the instructions over a telephone line using a modem. A modem of a local computer system receives the data on the telephone line and uses an infrared transmitter to convert the data to an infrared signal and transmit the infrared signal to a portable computing device, such as a personal digital assistant (PDA) or a laptop. An infrared detector on the portable computing device receives the information and instructions borne by the infrared signal and places the data on a bus. The bus conveys the data to main memory, from which a processor retrieves and executes the instructions. The instructions received by main memory can optionally be stored on storage device either before or after execution by processor.

While the present invention has been described in connection with a number of embodiments and implementations, the present invention is not so limited but covers various obvious modifications and equivalent arrangements, which fall within the purview of the appended claims.

The following patent applications are incorporated herein by reference in their entireties: co-pending U.S. patent application Ser. No. 11/368,750, filed Mar. 6, 2006, entitled “Method and System for Providing Distributed Editing and Storage of Digital Media Over a Network”; co-pending U.S.

patent application filed Sep. 7, 2006, entitled "Method and System for Providing a Personal Video Recorder Utilizing Network-Based Digital Media Content"; co-pending U.S. patent application filed Sep. 7, 2006, entitled "Method and System for Providing Remote Digital Media Ingest with Centralized Editorial Control"; co-pending U.S. patent application Ser. No. 11/452,851, filed Jun. 14, 2006, entitled "Method and System for Providing Digital Media Management Using Templates and Profiles"; co-pending U.S. patent application Ser. No. 11/479,715, filed Jun. 30, 2006, entitled "Method and System for Providing End User Community Functionality for Publication and Delivery of Digital Media Content"; co-pending U.S. Patent Application filed Sep. 7, 2006, entitled "Method and System for Dynamic Control of Digital Media Content Playback and Advertisement Delivery"; co-pending U.S. patent application filed Sep. 7, 2006, entitled "Method and System for Delivery of Digital Media Experience via Common Instant Communication Clients"; and co-pending U.S. patent application filed Sep. 7, 2006, entitled "Providing End User Community Functionality for Publication and Delivery of Digital Media Content."

APPENDIX

3G 3rd Generation
 AAF Advanced Authoring Format
 API Application Programming Interface
 ASIC Application Specific Integrated Circuit
 CD Compact Disc
 CPU Central Processing Unit
 CRT Cathode Ray Tube
 DSL Digital Subscriber Line
 DRM Digital Rights Management
 DVD Digital Versatile Disc (formerly Digital Video Disc)
 EDL Edit Decision List
 EPROM Erasable Programmable Read Only Memory
 FPGA Field Programmable Gate Array
 GOP Group of Pictures
 GUI Graphical User Interface
 IIS Internet Information Services
 IM Instant Messaging
 IP Internet Protocol
 IPTV IP Television
 ISDN Integrated Digital Services Network
 ISP Internet Service Provider
 LAN Local Area Network
 LTC Longitudinal TimeCode
 MPEG Motion Picture Expert Group
 NAS Network Area Storage
 NTSC National Television System Committee
 NIC Network Interface Card
 PAL Phase Alternating Line
 PCMCIA Personal Computer Memory Card International Association
 PDA Personal Digital Assistant
 PROM Programmable Read Only Memory
 RAM Random Access Memory
 ROM Read Only Memory
 RFC Request For Comment
 RPID Rich Presence Information Data Format
 SAN Storage Area Network
 SDI Serial Digital Interface
 SLA Service Level Agreement
 SMPTE Society of Motion Picture and Television Engineers
 SQL Structured Query Language
 TV Television

UMTS Universal Mobile Telecommunications System
 VDAM Virtual Digital Asset Manager
 VDCP Video Disk Communications Protocol
 VOD Video On Demand
 WAN Wide Area Network
 WLAN Wireless Local Area Network
 XML Extensible Markup Language

What is claimed is:

1. A method comprising:
 receiving, at a service provider platform, a plurality of media streams;
 permitting access by a player of a first subscriber to the service provider platform to perform remote proxy editing of one or more of the media streams; and
 permitting access by a player of a second subscriber to the service provider platform to perform remote proxy editing of the one or more of the media streams.
2. A method according to claim 1, further comprising:
 generating an index file for one of the media streams during a recording of a corresponding digital media, wherein the index file includes indices for decoding the corresponding digital media; and
 periodically updating the index file throughout the recording of the corresponding digital media.
3. A method according to claim 2, wherein the corresponding digital media represents video information that is encoded according to a Group of Pictures (GOP) format.
4. A method according to claim 1, further comprising:
 executing a workflow application that includes proxy viewing, logging and editing, craft editing, and delivery of digital media, wherein the digital media is received from a plurality of content sources that include either a media archive, a live feed, a digital feed, or a combination thereof.
5. A method according to claim 1, wherein the one or more of the media streams are transmitted to a plurality of players of the first subscriber.
6. An apparatus comprising:
 at least one processor; and
 at least one memory including computer program code for one or more programs,
 the at least one memory and the computer program code configured to, with the at least one processor, cause the apparatus to perform at least the following,
 receive a plurality of media streams,
 permit access by a player of a first subscriber to perform remote proxy editing of one or more of the media streams, and
 permit access by a player of a second subscriber to perform remote proxy editing of the one or more of the media streams,
 wherein the first subscriber and the second subscriber are subscribers to an editing service maintained by a service provider.
7. An apparatus according to claim 6, wherein the apparatus is further caused to:
 generate an index file for one of the media streams during a recording of a corresponding digital media, wherein the index file includes indices for decoding the corresponding digital media; and
 periodically update the index file throughout the recording of the corresponding digital media.
8. An apparatus according to claim 7, wherein the corresponding digital media represents video information that is encoded according to a Group of Pictures (GOP) format.

19

9. An apparatus according to claim 6, further comprising: execute a workflow application that includes proxy viewing, logging and editing, craft editing, and delivery of digital media, wherein the digital media is received from a plurality of content sources that include either a media archive, a live feed, a digital feed, or a combination thereof. 5
10. An apparatus according to claim 6, wherein the one or more of the media streams are transmitted to a plurality of players of the first subscriber. 10
11. A method comprising:
 executing a proxy editor player;
 accessing a service provider platform to edit one or more of a plurality of media streams as part of a remote editing service; and 15
 selecting, via the proxy editor player, one of the media streams to edit at the service provider platform, wherein the service provider platform is configured to provide the remote editing service to a plurality of subscribers. 20
12. A method according to claim 11, further comprising: previewing, via the proxy editor player, the selected media stream before the editing.
13. A method according to claim 11, further comprising: applying, via the proxy editor player, a zoom or a crop effect on the selected media stream. 25
14. A method according to claim 11, further comprising: recording, via the proxy editor player, a voiceover with respect to the selected media stream.
15. A method according to claim 11, further comprising: receiving, via the proxy editor player, the edited media stream. 30

20

16. An apparatus comprising:
 at least one processor; and
 at least one memory including computer program code for one or more programs,
 the at least one memory and the computer program code configured to, with the at least one processor, cause the apparatus to perform at least the following,
 execute a proxy editor player,
 access a service provider platform to edit one or more of a plurality of media streams as part of a remote editing service, and
 select, via the proxy editor player, one of the media streams to edit at the service provider platform,
 wherein the service provider platform is configured to provide the remote editing service to a plurality of subscribers.
17. An apparatus according to claim 16, wherein the apparatus is further caused to:
 preview, via the proxy editor player, the selected media stream before the editing.
18. An apparatus according to claim 16, wherein the apparatus is further caused to:
 apply, via the proxy editor player, a zoom or a crop effect on the selected media stream.
19. An apparatus according to claim 16, wherein the apparatus is further caused to:
 record, via the proxy editor player, a voiceover with respect to the selected media stream.
20. An apparatus according to claim 16, wherein the apparatus is further caused to:
 receive, via the proxy editor player, the edited media stream.

* * * * *