



US008978275B2

(12) **United States Patent**
James

(10) **Patent No.:** **US 8,978,275 B2**
(45) **Date of Patent:** **Mar. 17, 2015**

(54) **FOOTWEAR WITH PLURALITY OF
INTERLOCKING MIDSOLE AND OUTSOLE
ELEMENTS**

USPC 36/103, 25 R, 35 R, 15, 31, 20, 102
See application file for complete search history.

(75) Inventor: **Dervin A. James**, Hillsboro, OR (US)

(73) Assignee: **NIKE, Inc.**, Beaverton, OR (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 528 days.

(21) Appl. No.: **13/494,120**

(22) Filed: **Jun. 12, 2012**

(65) **Prior Publication Data**

US 2012/0278999 A1 Nov. 8, 2012

Related U.S. Application Data

(63) Continuation-in-part of application No. 12/365,583,
filed on Feb. 4, 2009, now Pat. No. 8,215,037.

(51) **Int. Cl.**

A43B 13/14 (2006.01)

A43B 13/16 (2006.01)

A43B 13/00 (2006.01)

A43B 13/12 (2006.01)

A43B 1/00 (2006.01)

A43B 13/18 (2006.01)

(52) **U.S. Cl.**

CPC **A43B 13/16** (2013.01); **A43B 13/12**
(2013.01); **A43B 1/0027** (2013.01); **A43B**
1/0072 (2013.01); **A43B 13/188** (2013.01)

USPC **36/103**; 36/15; 36/31

(58) **Field of Classification Search**

CPC **A43B 13/16**; **A43B 13/188**; **A43B 13/18**;
A43B 13/187; **A43B 13/28**; **A43B 13/12**;
A43B 13/122; **A43B 13/125**

(56) **References Cited**

U.S. PATENT DOCUMENTS

190,113 A	5/1877	Arnold
500,385 A	6/1893	Hall
1,148,584 A	8/1915	Gerrish
1,575,813 A	3/1926	Burke
1,741,419 A	12/1927	Jones
1,907,136 A	8/1931	Weitsen
2,046,732 A	1/1936	Fein
2,088,902 A	7/1936	Fein
2,237,892 A	4/1941	Jacob

(Continued)

OTHER PUBLICATIONS

Office action dated Oct. 21, 2011, U.S. Appl. No. 12/365,583, filed
Feb. 4, 2009.


Primary Examiner — Jila M Mohandesi

(74) *Attorney, Agent, or Firm* — Honigman Miller Schwartz
and Cohn LLP; Matthew H. Szalach

(57) **ABSTRACT**

A method of manufacturing an article of footwear includes
providing an outsole and a midsole. The outsole and the
midsole are secured together such that a bottom surface of a
first midsole element overlaps and directly secures to an
upper surface of a first outsole element to define a first ele-
ment assembly, such that a bottom surface of a second mid-
sole element overlaps and directly secures to an upper surface
of a second outsole element to define a second element assem-
bly, and such that an outsole groove and a midsole groove are
substantially aligned and in communication with each other
in the thickness direction of the outsole and the thickness
direction of the midsole. Moreover, the method includes
interlocking the first and second element assemblies with
each other.

20 Claims, 3 Drawing Sheets





(56)

References Cited

U.S. PATENT DOCUMENTS

2,928,193	A	2/1958	Kristan	6,092,305	A	7/2000	Troy et al.	
3,517,928	A	6/1970	Shanahan	6,453,578	B1 *	9/2002	Yung et al.	36/43
3,594,929	A	7/1971	Stohr	6,519,876	B1	2/2003	Geer et al.	
3,952,429	A	4/1976	Thomas	6,701,643	B2	3/2004	Geer et al.	
4,128,950	A	12/1978	Bowerman et al.	7,059,067	B2	6/2006	Geer et al.	
4,237,626	A	12/1980	Brown	7,210,250	B2	5/2007	Gallegos	
4,364,188	A	12/1982	Turner et al.	7,334,350	B2	2/2008	Ellis, III	
4,408,402	A	10/1983	Looney	7,334,352	B2	2/2008	Lacey	
4,557,060	A	12/1985	Kawashima	7,434,335	B2 *	10/2008	Feldstein	36/8.3
4,608,768	A	9/1986	Cavanagh	D581,643	S *	12/2008	Bauerfeind et al.	D2/961
4,624,061	A	11/1986	Wezel et al.	D627,550	S *	11/2010	Zhang	D2/961
4,930,231	A	6/1990	Liu	8,230,619	B2 *	7/2012	Salvatelli et al.	36/88
5,729,912	A	3/1998	Gutkowski et al.	8,402,678	B1 *	3/2013	Kopelman	36/140
5,813,146	A	9/1998	Gutkowski et al.	2006/0213081	A1	9/2006	Geer et al.	
				2007/0271817	A1	11/2007	Ellis, III	
				2008/0000108	A1	1/2008	Ellis, III	
				2008/0005931	A1	1/2008	Ellis, III	

* cited by examiner






FIG. 1B




FIG. 3




FIG. 4

1

FOOTWEAR WITH PLURALITY OF INTERLOCKING MIDSOLE AND OUTSOLE ELEMENTS

CROSS-REFERENCE TO RELATED APPLICATION

This application is a continuation-in-part of U.S. patent application Ser. No. 12/365,583, filed on Feb. 4, 2009, now U.S. Pat. No. 8,215,037. The entire disclosure of the above application is incorporated herein by reference.

FIELD

The present disclosure relates to footwear and, more particularly, relates to an article of footwear with a plurality of interlocking midsole and outsole elements.

BACKGROUND

Articles of footwear usually include an upper, a midsole, and an outsole. The upper can include sections of thin material, straps, or the like for securing the footwear to the wearer's foot. The outsole is typically a unitary piece of relatively high-friction material that provides traction for the footwear. Also, the midsole can be a unitary piece of foam or other similar material disposed between the upper and the outsole for providing cushioned support for the wearer.

SUMMARY

A method of manufacturing an article of footwear is disclosed. The method includes providing an outsole and a midsole. The outsole including an outsole groove that extends generally in a thickness direction through the outsole to separate the outsole into first and second outsole elements. The first and second outsole elements each include a respective upper surface. The midsole includes a midsole groove that extends generally in a thickness direction through the midsole to separate the midsole into first and second midsole elements. The first and second midsole elements each include a respective bottom surface. The outsole and the midsole are secured together such that the bottom surface of the first midsole element overlaps and directly secures to the upper surface of the first outsole element to define a first element assembly, such that the bottom surface of the second midsole element overlaps and directly secures to the upper surface of the second outsole element to define a second element assembly, and such that the outsole groove and the midsole groove are substantially aligned and in communication with each other in the thickness direction of the outsole and the thickness direction of the midsole. Moreover, the method includes interlocking the first and second element assemblies with each other.

Additionally, a method of customizing an article of footwear is also disclosed. The method includes selecting an outsole including an outsole groove that extends generally in a thickness direction through the outsole to separate the outsole into first and second outsole elements. The first and second outsole elements each include a respective upper surface. The method also includes selecting a midsole including a midsole groove that extends generally in a thickness direction through the midsole to separate the midsole into first and second midsole elements. The first and second midsole elements each include a respective bottom surface. The midsole and the outsole are secured together such that the bottom surface of the first midsole element overlaps and directly

2

secures to the upper surface of the first outsole element to define a first element assembly, such that the bottom surface of the second midsole element overlaps and directly secures to the upper surface of the second outsole element to define a second element assembly, such that the outsole groove and the midsole groove are substantially aligned and in communication with each other in the thickness direction of the outsole and the thickness direction of the midsole, and such that the first and second element assemblies interlock with each other. The first midsole element differs from the second midsole element by a different material, a different color, a different durometer, and/or a different resistance to resilient deformation.

Still further, a method of customizing an article of footwear is disclosed that includes selecting an outsole including an outsole groove that extends generally in a thickness direction through the outsole to separate the outsole into first and second outsole elements. The first and second outsole elements each include a respective upper surface. The method also includes selecting a midsole including a midsole groove that extends generally in a thickness direction through the midsole to separate the midsole into first and second midsole elements. The first and second midsole elements each include a respective bottom surface. The midsole and the outsole are secured together such that the bottom surface of the first midsole element overlaps and directly secures to the upper surface of the first outsole element to define a first element assembly, such that the bottom surface of the second midsole element overlaps and directly secures to the upper surface of the second outsole element to define a second element assembly, such that the outsole groove and the midsole groove are substantially aligned and in communication with each other in the thickness direction of the outsole and the thickness direction of the midsole, and such that the first and second element assemblies interlock with each other. The first outsole element differs from the second outsole element by a different coefficient of friction, a different material, a different thickness, and/or a different color.

This section provides a general summary of the disclosure, and is not a comprehensive disclosure of its full scope or all of its features. Further areas of applicability will become apparent from the description provided herein. The description and specific examples in this summary are intended for purposes of illustration only and are not intended to limit the scope of the present disclosure.

DRAWINGS

The drawings described herein are for illustrative purposes only of selected embodiments and not all possible implementations, and are not intended to limit the scope of the present disclosure.

FIG. 1A is an isometric view of an exemplary embodiment of an article of footwear according to various teachings of the present disclosure;

FIG. 1B is an exploded view of the article of footwear of FIG. 1A;

FIG. 2 is a bottom plan view of the article of footwear of FIG. 1A;

FIG. 3 is a sectional view of the article of footwear of FIG. 1A; and

FIG. 4 is an exemplary embodiment of a pressure map illustrating a pressure distribution for the article of footwear of FIG. 1A.

Corresponding reference numerals indicate corresponding parts throughout the several views of the drawings.

DETAILED DESCRIPTION

Example embodiments will now be described more fully with reference to the accompanying drawings.

Referring initially to FIGS. 1A and 2, an exemplary embodiment of an article of footwear 10 is illustrated according to various teachings of the present disclosure. For purposes of discussion, the footwear 10 will be discussed using a reference coordinate system X, Y, Z (FIG. 1).

Generally, the article of footwear 10 includes an upper 12, an outsole 14, and a midsole 16. As will be discussed, the midsole 16 is operably secured to both the upper 12 and the outsole 14, and the midsole 16 is disposed between the upper 12 and the outsole 14. The midsole 16 and the outsole 14 generally extend in transverse directions (i.e., within the X-Y plane) (FIG. 1A), and the midsole 16 and the outsole 14 each have a thickness defined along a thickness direction (i.e., along the Z-axis).

In some embodiments, the upper 12 includes various thin sections of material that partially overlap each other and that are operably secured to each other, for example, by stitching, adhesives, and the like. The upper 12 defines a cavity in which the wearer's foot is received. The upper 12 can also include a fastening structure, such as laces, buckles, and/or other features for tightly securing the upper 12 to the foot of the wearer. It will also be appreciated that the upper 12 can include various decorative features. In addition, the upper 12 can have any suitable shape and/or features that adapt the article of footwear 10 for its intended use.

As shown in FIGS. 1A, 1B, and 2, the outsole 14 can include a layer of material that extends in the transverse directions (i.e., within the X-Y plane). The outsole 14 can also have any suitable curvature along the transverse directions. Additionally, the outsole 14 can have any suitable thickness (i.e., along the Z-axis), and the thickness of the outsole 14 can vary in any suitable fashion. Moreover, the outsole 14 can include various grooves, projections or other features for increasing traction of the footwear 10.

In addition, the outsole 14 includes a plurality of outsole grooves 18. As shown in FIG. 3, the outsole grooves 18 extend entirely through the thickness of the outsole 14 (i.e., along the Z-axis); however, the outsole grooves 18 can extend only partially through the thickness of the outsole 14 in some embodiments. Also, the outsole grooves 18 extend in the transverse directions (i.e., within the X-Y plane) (FIGS. 1A and 2). As such, the outsole grooves 18 separate the outsole 14 into a plurality of separate outsole elements 20a-20t (FIG. 1B). The outsole elements 20a-20t can have any suitable shape and size. In the embodiment shown, the outsole elements 20a-20t each have a plurality of generally planar sides 22 that extend in the thickness direction. The planar sides 22 of adjacent outsole elements 20a-20t face each other. In some embodiments, the outsole grooves 18 are wide enough in the transverse directions to space the outsole elements 20a-20t apart slightly (e.g., 1-2 millimeters). However, the grooves 18 can have a relatively small width, allowing the outsole elements 20a-20t to abut each other in some embodiments. As will be discussed, the outsole grooves 18 increase flexibility of the outsole 14 and can make the outsole 14 more versatile.

Furthermore, in some embodiments, the outsole grooves 18 are shaped such that the outsole elements 20a-20t interlock with each other. In the embodiment shown, the outsole elements 20a-20t are shaped in a fashion similar to interlocking jigsaw puzzle pieces (FIG. 2). For instance, the outsole

element 20k includes a projection 24 that projects from the respective planar side 22 (FIG. 2). Moreover, an adjacent outsole element (e.g., element 20j) includes a recess 30 that receives the projection 24 to interlock elements 20k and 20j. As shown, the other outsole elements 20a-20t can also include respective interlocking pairs of projections 24 and recesses 30.

The projections 24 and recesses 30 can have any suitable shape. For instance, in the embodiments shown, the projection 24 includes an enlarged head 26 and a neck portion 28, which is narrower than the enlarged head 26. The neck portion 28 is disposed between the head 26 and the respective planar side 22 of the outsole element 20a-20t. Furthermore, the recess 30 includes an enlarged portion 31 and a narrow portion 32. The enlarged portion 31 of the recess 30 receives the enlarged head 26 of the projection 24 such that the narrow portion 32 of the recess 30 limits movement of the enlarged head 26 out of the enlarged portion 31 of the recess 30. Accordingly, as will be discussed, the outsole elements 20a-20t can shift slightly relative to each other for added flexibility of the footwear 10. However, the outsole elements 20a-20t interlock with each other to maintain sufficient union of the outsole 14.

Furthermore, in some embodiments, the outsole 14 includes an outer periphery 34 that is entirely continuous (FIGS. 1A, 1B, 2). More specifically, as shown in FIG. 1B, the outsole elements 20a, 20d, 20g, 20j, 20m, 20p, 20s, 20r, 20o, 20l, 20i, 20f, 20c, and 20t ("the peripheral outsole elements") cooperate to define the outer periphery 34 of the outsole 14. The remaining outsole elements 20b, 20e, 20h, 20k, 20n, and 20q ("the interior outsole elements") are spaced apart from the outer periphery 34 of the outsole 14.

The peripheral outsole elements 20a, 20d, 20g, 20j, 20m, 20p, 20s, 20r, 20o, 20l, 20i, 20f, 20c, and 20t are each integrally coupled to adjacent ones of the peripheral outsole elements 20a, 20d, 20g, 20j, 20m, 20p, 20s, 20r, 20o, 20l, 20i, 20f, 20c, and 20t such that the outer periphery 34 is entirely continuous. For instance, the outsole groove 18 separating outsole elements 20f and 20i (FIG. 1B) does not extend in the transverse direction to the outer periphery 34, and elements 20f and 20i are integrally coupled to each other adjacent the outer periphery 34. In some embodiments, the outsole groove 18 separating outsole elements 20f and 20i (FIG. 1B) tapers and terminates immediately adjacent the outer periphery 34 to maintain the continuous outer periphery 34 of the outsole 14. Accordingly, because the outer periphery 34 is entirely continuous, the outsole 14 holds together to limit excessive relative movement of the outsole elements 20a-20t. In addition, the entirely continuous outer periphery 34 can aid in handling of the outsole 14, for instance, during manufacture of the footwear 10.

It will be appreciated that the outsole 14 can be made out of any suitable material. For instance, the outsole 14 can be made out of a high-friction polymeric material, such as rubber. Also, in some embodiments, the outsole 14 can be made out of a transparent material so that the midsole 16 is visible through the outsole 14. Also, it will be appreciated that the outsole elements 20a-20t can vary in material, thickness, function, aesthetics, and the like. Accordingly, the outsole elements 20a-20t can be selected according to the respective transverse location of the outsole element 20a-20t on the footwear 10, making the outsole 14 more versatile and adaptable as will be discussed in greater detail below.

Additionally, as shown in FIGS. 1A, 1B, and 3, the midsole 16 can include a layer of material that extends in the transverse directions (i.e., within the X-Y plane). The midsole 16

5

can also have any suitable curvature along the transverse directions. Furthermore, the midsole **16** can have any suitable thickness (i.e., along the Z-axis), and the thickness of the midsole **16** can vary in any suitable fashion.

In addition, the midsole **16** includes a plurality of midsole grooves **38** (FIG. 1B and 3). As shown in FIG. 3, the midsole grooves **38** extend entirely through the thickness of the midsole **16** (i.e., along the Z-axis); however, the midsole grooves **38** can extend only partially through the thickness of the midsole **16** in some embodiments. Also, the midsole grooves **38** extend in the transverse directions (i.e., within the X-Y plane) (FIG. 1B). As such, the midsole grooves **38** separate the midsole **16** into a plurality of separate midsole elements **40a-40t** (FIG. 1B). The midsole elements **40a-40t** can have any suitable shape and size. In the embodiments shown, the midsole elements **40a-40t** each have a plurality of generally planar sides **42** that extend in the thickness direction. The planar sides **42** of adjacent midsole elements **40a-40t** face each other. In some embodiments, the midsole grooves **38** are wide enough in the transverse directions to space the midsole elements **40a-40t** apart slightly (e.g., 1-2 millimeters). However, the grooves **38** can have a relatively small width, allowing the midsole elements **40a-40t** to abut each other in some embodiments. As will be discussed, the midsole grooves **38** increase flexibility of the midsole **16** and can make the midsole **16** more versatile.

Furthermore, in some embodiments, the midsole grooves **38** are shaped such that the midsole elements **40a-40t** interlock with each other. In the embodiment shown, the midsole elements **40a-40t** are shaped in a fashion similar to interlocking jigsaw puzzle pieces (FIG. 1B). For instance, the midsole element **40k** includes a projection **44** that projects from the respective planar side **42**. Moreover, an adjacent midsole element (e.g., element **40j**) includes a recess **50** that recesses into the respective planar side **42**. The recess **50** receives the projection **44** to interlock elements **40k** and **40j**. As shown, the other midsole elements **40a-40t** can also include respective interlocking pairs of projections **44** and recesses **50**.

The projections **44** and recesses **50** can have any suitable shape. For instance, in the embodiment shown in FIG. 1B, the projection **44** includes an enlarged head **46** and a neck portion **48**, which is narrower than the enlarged head **46**. The neck portion **48** is disposed between the head **46** and the respective planar side **42** of the respective midsole element **40a-40t**. Furthermore, the recess **50** includes an enlarged portion **51** and a narrow portion **52**. The enlarged portion **51** of the recess **50** receives the enlarged head **46** of the projection **44** such that the narrow portion **52** of the recess **50** limits movement of the enlarged head **46** out of the enlarged portion **51** of the recess **50**. Accordingly, as will be discussed, the midsole elements **40a-40t** can shift slightly relative to each other for added flexibility of the footwear **10**. However, the midsole elements **40a-40t** interlock with each other to maintain sufficient union of the midsole **16**.

Furthermore, in some embodiments, the midsole **16** includes an outer periphery **54** that is entirely continuous (FIGS. 1A and 1B). More specifically, as shown in FIG. 1B, the midsole elements **40a**, **40d**, **40g**, **40j**, **40m**, **40p**, **40s**, **40r**, **40o**, **40l**, **40i**, **40f**, **40c**, and **40t** ("the peripheral midsole elements") cooperate to define the outer periphery **54** of the midsole **16**. The remaining midsole elements **40b**, **40e**, **40h**, **40k**, **40n**, and **40q** ("the interior midsole elements") are spaced apart from the outer periphery **54** of the midsole **16**.

The peripheral midsole elements **40a**, **40d**, **40g**, **40j**, **40m**, **40p**, **40s**, **40r**, **40o**, **40l**, **40i**, **40f**, **40c**, and **40t** are each integrally coupled to adjacent ones of the peripheral midsole elements **40a**, **40d**, **40g**, **40j**, **40m**, **40p**, **40s**, **40r**, **40o**, **40l**, **40i**,

6

40f, **40c**, and **40t** such that the outer periphery **54** is entirely continuous. For instance, the midsole groove **38** separating midsole elements **40f** and **40i** (FIG. 1B) does not extend in the transverse direction to the outer periphery **54**, and elements **40f** and **40i** are integrally coupled to each other adjacent the outer periphery **54**. In some embodiments, the midsole groove **38** separating midsole elements **40f** and **40i** (FIG. 1B) tapers and terminates immediately adjacent the outer periphery **54** to maintain the continuous outer periphery **54** of the midsole **16**. Accordingly, because the outer periphery **54** is entirely continuous, the midsole **16** holds together to limit excessive relative movement of the midsole elements **40a-40t**. In addition, the entirely continuous outer periphery **54** can aid in handling of the midsole **16**, for instance, during manufacture of the footwear **10**.

It will be appreciated that the midsole **16** can be made out of any suitable material. For instance, the midsole **16** can be made out of any suitable foam material, such as Ethylene Vinyl Acetate (EVA) foam and/or Thermoplastic Polyurethane (TPU). The midsole **16** can also include a material with air pockets or fluid-filled bladders included therein, such as materials disclosed in U.S. Pat. No. 7,386,946, issued Jun. 17, 2008 to Goodwin, U.S. Pat. No. 7,070,845, issued Jul. 4, 2006 to Thomas et al., and/or U.S. Patent Publication No. 2006/0230636, published Oct. 19, 2006 to Kokstis et al., each of which is incorporated herein by reference in its entirety. Also, it will be appreciated that the individual midsole elements **40a-40t** can vary in material, thickness, function, aesthetics, and the like. Accordingly, the midsole elements **40a-40t** can be selected according to the respective transverse location of the midsole element **40a-40t** on the footwear **10**, making the midsole **16** more versatile and adaptable as will be discussed in greater detail below.

As shown in FIGS. 1B and 3, the outsole grooves **18** can be substantially aligned with the midsole grooves **38** so that the midsole and outsole grooves **38**, **18** substantially overlap in plan view (FIG. 2). Accordingly, the midsole and outsole grooves **38**, **18** are in communication with each other in the thickness direction (i.e., along the Z-axis) as shown in FIG. 3. It will be appreciated, however, that the outsole grooves **18** can be misaligned with the midsole grooves **38** in some embodiments. Furthermore, it will be appreciated that the outsole **14** can be a continuous sheet of material while the midsole **16** includes the individual midsole elements **40a-40t**. Likewise, it will be appreciated that the midsole **16** can be a continuous sheet of material while the outsole **14** can include the individual outsole elements **20a-20t**.

Furthermore, in the embodiment shown in FIG. 3, individual ones of the outsole elements **20a-20t** are operably secured to corresponding ones of the midsole elements **40a-40t**. Accordingly, each outsole element **20a-20t** pairs with a respective midsole element **40a-40t** to define an element assembly **60a-60t** (FIG. 3). In some embodiments shown in FIG. 3, an upper surface **52** of the outsole element **20e** is fixed to a bottom surface **54** of the midsole element **40e** such that the elements **20e**, **40e** collectively define an element assembly **60e**. It will be appreciated that the outsole elements **20a-20t** can be operably secured to the respective midsole elements **40a-40t** in any suitable fashion. In some embodiments, the outsole elements **20a-20t** are fixed to corresponding ones of the midsole elements **40a-40t**, such as by adhesive or other bonding. Also, in some embodiments, the outsole elements **20a-20t** are removably coupled to corresponding ones of the midsole elements **40a-40t**.

Because the outsole elements **20a-20t** and midsole elements **40a-40t** are separate from other ones of the outsole elements **20a-20t** and midsole elements **40a-40t**, the foot-

wear **10** can be adapted, adjusted, and customized in a variety of ways. For instance, different outsole elements **20a-20t** varying in thickness, coefficient of friction, material, color, etc. can be interlocked and integrated in the footwear **10**. Likewise, different midsole elements **40a-40t** varying in thickness, resistance to resilient deformation, material, color, etc. can be interlocked and integrated in the footwear **10**.

More specifically, as shown in FIG. 3, the thickness of the individual midsole elements **40a-40t** can vary. More specifically, in the embodiments shown, the midsole element **40b** has a thickness of t_1 , the midsole element **40e** has a thickness t_2 , and the midsole element **40k** has a thickness t_3 . As shown, the thickness t_1 of element **40b** is greater than the thickness t_2 of element **40e**, but the thickness t_1 of element **40b** is less than the thickness t_3 of element **40k**. Furthermore, the resistance to resilient deformation of the midsole elements **40t**, **40b**, **40e**, **40h**, **40k**, and **40n** can vary as shown in FIG. 3. For instance, element **40t** can have a lower density, durometer, etc. than elements **40b**, **40k**, and **40n** (as represented by cross hatching in FIG. 3), and element **40h** can have a lower density, durometer, etc. than element **40t**. As such, the elements **40b**, **40k**, and **40n** can provide higher resistance to resilient deformation than that of elements **40t** and **40h**, and element **40h** can provide higher resistance to resilient deformation than element **40t**.

FIG. 4 illustrates a pressure “map” of the footwear **10** to represent the location of the highest and lowest pressure on the midsole **16** during use of the footwear **10**. For instance, loading can be highest near the center of the heel of the wearer. Thus, midsole element **40b** can have a preselected thickness, durometer, material, or any other characteristic to handle the increased pressure loading. Other midsole elements **40a**, **40c-40t** can be similarly selected. For instance, loads near the arch of the foot are relatively low, and thus, midsole element **40e** can have a preselected thickness, durometer, material, or any other characteristic to handle the decreased pressure loading. Accordingly, the midsole **16** is very versatile.

The outsole elements **20a-20t** can be preselected in a similar fashion. For instance, the individual outsole elements **20a-20t** can be selected to provide higher friction in some areas of the outsole **14** as compared to other areas. Also, in the embodiment shown in FIG. 3, the thickness of each outsole element **20a-20t** is such that the outsole elements **20a-20t** are flush with each other on a side opposite from the midsole elements **40a-40t**; however, it will be appreciated that the outsole elements **20a-20t** can have any suitable thickness.

Manufacture of the footwear **10** can be accomplished in any suitable fashion. For instance, in some embodiments, the outsole elements **20a-20t** are individually selected and assembled, and the individual midsole elements **40a-40t** are individually selected and assembled in a similar fashion. Then, the outsole **14** is bonded to the midsole **16** (e.g., in a molding process), and the midsole **16** is bonded to the upper **12**. Alternatively, the outsole **14** can be removably secured to the midsole **16** and/or the midsole **16** can be removably secured to the upper **12**.

In another embodiment, the peripheral midsole elements **40a**, **40d**, **40g**, **40j**, **40m**, **40p**, **40s**, **40r**, **40o**, **40l**, **40i**, **40f**, **40c**, and **40t** are integrally coupled, leaving an opening for the remaining midsole elements **40b**, **40e**, **40h**, **40k**, **40n**, and **40q**. The midsole elements **40b**, **40e**, **40h**, **40k**, **40n**, and **40q** are selected and arranged between the peripheral midsole elements **40a**, **40d**, **40g**, **40j**, **40m**, **40p**, **40s**, **40r**, **40o**, **40l**, **40i**, **40f**, **40c**, and **40t**. The outsole elements **20a-20t** of the outsole

14 are assembled in a similar fashion. Then, the midsole **16** is operably secured to the outsole **14**, and the upper **12** is operably secured.

In another embodiment, the outsole **14** and the midsole **16** are initially monolithic layers of material. The outsole **14** and midsole **16** are operably secured together, and then the outsole grooves **18** and the midsole grooves **38** are subsequently formed therein. For instance, a laser cutting process can be used to form the grooves **18**, **38**.

It will be appreciated that the grooves **18**, **38** increase the flexibility of the outsole **14** and the midsole **16**, and yet the continuous outer peripheries **34**, **54** of the outsole **14** and the midsole **16** serve to hold the outsole **14** and the midsole **16** together for added durability and uniform flexion of the footwear **10**. Moreover, because the element assemblies **60a-60t** interlock, the element assemblies **60a-60t** can distribute loads to each other to improve performance of the footwear **10**.

Moreover, the footwear **10** can facilitate recycling. For instance, because of the outsole and midsole grooves **18**, **38**, the element assemblies **60a-60t** can be easily separated from each other for recycling purposes.

The foregoing description of the embodiments has been provided for purposes of illustration and description. It is not intended to be exhaustive or to limit the invention. Individual elements or features of a particular embodiment are generally not limited to that particular embodiment, but, where applicable, are interchangeable and can be used in a selected embodiment, even if not specifically shown or described. The same may also be varied in many ways. Such variations are not to be regarded as a departure from the invention, and all such modifications are intended to be included within the scope of the invention.

What is claimed is:

1. A method of manufacturing an article of footwear comprising:

providing an outsole and a midsole, the outsole including an outsole groove that extends generally in a thickness direction through the outsole to separate the outsole into first and second outsole elements, the first and second outsole elements each including a respective upper surface, the midsole including a midsole groove that extends generally in a thickness direction through the midsole to separate the midsole into first and second midsole elements, the first and second midsole elements each including a respective bottom surface, the outsole and the midsole secured together such that the bottom surface of the first midsole element overlaps and directly secures to the upper surface of the first outsole element to define a first element assembly, such that the bottom surface of the second midsole element overlaps and directly secures to the upper surface of the second outsole element to define a second element assembly, and such that the outsole groove and the midsole groove are substantially aligned and in communication with each other in the thickness direction of the outsole and the thickness direction of the midsole; and

interlocking the first and second element assemblies with each other.

2. The method of claim 1, wherein providing the midsole includes providing the first midsole element having a higher resistance to resilient deformation than the second midsole element.

3. The method of claim 1, wherein providing the midsole includes providing the first midsole element that is made of a different material than the second midsole element.

9

4. The method of claim 1, wherein interlocking the first and second element assemblies includes receiving a projection of the first element assembly in a recess of the second element assembly.

5. The method of claim 4, wherein the projection includes an enlarged head and a neck, and the recess includes an enlarged portion and a narrow portion, and wherein interlocking the first and second element assemblies includes the enlarged portion receiving the enlarged head and the narrow portion limiting movement of the enlarged head out of the enlarged portion of the recess.

6. The method of claim 1, wherein the midsole groove extends entirely through the midsole in the thickness direction.

7. The method of claim 1, wherein the outsole groove extends entirely through the outsole in the thickness direction.

8. The method of claim 1, wherein the midsole includes an entirely continuous outer periphery.

9. The method of claim 1, wherein the outsole includes an entirely continuous outer periphery.

10. The method of claim 1, further comprising securing the midsole and the outsole together such that the bottom surface of the first midsole element overlaps and directly secures to the upper surface of the first outsole element to define a first element assembly, such that the bottom surface of the second midsole element overlaps and directly secures to the upper surface of the second outsole element to define a second element assembly, and such that the outsole groove and the midsole groove are substantially aligned and in communication with each other in the thickness direction of the outsole and the thickness direction of the midsole.

11. A method of customizing an article of footwear comprising:

selecting an outsole including an outsole groove that extends generally in a thickness direction through the outsole to separate the outsole into first and second outsole elements, the first and second outsole elements each including a respective upper surface; and

selecting a midsole including a midsole groove that extends generally in a thickness direction through the midsole to separate the midsole into first and second midsole elements, the first and second midsole elements each including a respective bottom surface,

the midsole and the outsole secured together such that the bottom surface of the first midsole element overlaps and directly secures to the upper surface of the first outsole element to define a first element assembly, such that the bottom surface of the second midsole element overlaps and directly secures to the upper surface of the second outsole element to define a second element assembly, such that the outsole groove and the midsole groove are substantially aligned and in communication with each other in the thickness direction of the outsole and the thickness direction of the midsole, and such that the first and second element assemblies interlock with each other,

the first midsole element differing from the second midsole element by at least one of a different material, a different color, a different durometer, and a different resistance to resilient deformation.

10

12. The method of claim 11, wherein selecting the midsole includes selecting the at least one of the different material, the different color, the different durometer, and the different resistance to resilient deformation of the first midsole element based on a respective location of the first midsole element and the second midsole element within the midsole.

13. The method of claim 11, wherein the midsole groove extends entirely through the midsole in the thickness direction.

14. The method of claim 11, wherein the midsole includes an entirely continuous outer periphery.

15. The method of claim 11, further comprising securing the midsole and the outsole together and interlocking the first and second element assemblies together.

16. A method of customizing an article of footwear comprising:

selecting an outsole including an outsole groove that extends generally in a thickness direction through the outsole to separate the outsole into first and second outsole elements, the first and second outsole elements each including a respective upper surface; and

selecting a midsole including a midsole groove that extends generally in a thickness direction through the midsole to separate the midsole into first and second midsole elements, the first and second midsole elements each including a respective bottom surface,

the midsole and the outsole secured together such that the bottom surface of the first midsole element overlaps and directly secures to the upper surface of the first outsole element to define a first element assembly, such that the bottom surface of the second midsole element overlaps and directly secures to the upper surface of the second outsole element to define a second element assembly, such that the outsole groove and the midsole groove are substantially aligned and in communication with each other in the thickness direction of the outsole and the thickness direction of the midsole, and such that the first and second element assemblies interlock with each other,

the first outsole element differing from the second outsole element by at least one of a different coefficient of friction, a different material, a different thickness, and a different color.

17. The method of claim 16, wherein selecting the outsole includes selecting the at least one of the different coefficient of friction, the different material, the different thickness, and the different color based on a respective location of the first outsole element and the second outsole element within the outsole.

18. The method of claim 16, wherein the outsole groove extends entirely through the outsole in the thickness direction.

19. The method of claim 16, wherein the outsole includes an entirely continuous outer periphery.

20. The method of claim 16, further comprising securing the midsole and the outsole together and interlocking the first and second element assemblies together.

* * * * *