



US008985604B2

(12) **United States Patent**  
**Hopson et al.**

(10) **Patent No.:** **US 8,985,604 B2**  
(45) **Date of Patent:** **Mar. 24, 2015**

(54) **CROSS AXIS JOINT WITH ELASTOMERIC ISOLATION**

(75) Inventors: **Steven C Hopson**, Saline, MI (US);  
**Steve S Allen**, Saline, MI (US); **Kanak Soundrapandian**, Canton, MI (US)

(73) Assignee: **Ford Global Technologies, LLC**,  
Dearborn, MI (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 127 days.

(21) Appl. No.: **12/831,797**

(22) Filed: **Jul. 7, 2010**

(65) **Prior Publication Data**

US 2012/0007329 A1 Jan. 12, 2012

(51) **Int. Cl.**

**B60G 7/00** (2006.01)

**F16C 11/06** (2006.01)

(52) **U.S. Cl.**

CPC ..... **F16C 11/0614** (2013.01); **B60G 7/005** (2013.01); **B60G 2204/416** (2013.01)

USPC ..... **280/124.134**; 403/132; 403/133

(58) **Field of Classification Search**

USPC ..... 280/124.134, 124.15; 403/26, 76, 114, 403/127, 132, 133

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

3,467,421	A *	9/1969	Bentley	403/203
3,843,272	A *	10/1974	Jorn	403/132
4,034,996	A *	7/1977	Manita et al.	280/80.1
4,430,016	A *	2/1984	Matsuoka et al.	403/40
4,765,650	A *	8/1988	Kameshima et al.	280/124.116

5,058,867	A	10/1991	Hadano et al.	267/141.3
5,295,670	A *	3/1994	Tsukamoto et al.	267/140.5
5,318,373	A *	6/1994	Buhl et al.	403/134
5,362,093	A *	11/1994	Klosterhuber et al.	280/124.136
5,374,038	A *	12/1994	Hein	267/140.5
5,556,119	A	9/1996	Buchner et al.	280/96.1
5,845,926	A	12/1998	Davis et al.	280/690
5,902,050	A	5/1999	Balczun et al.	384/206
6,056,498	A *	5/2000	Velinsky et al.	414/555
6,113,302	A *	9/2000	Buhl	403/133
6,145,858	A *	11/2000	Foulquier	280/124.13
6,216,833	B1 *	4/2001	Lefferts et al.	188/380
6,231,062	B1 *	5/2001	Sutton	280/124.146
6,341,915	B1 *	1/2002	Kammel	403/135
6,386,553	B2 *	5/2002	Zetterstrom	280/5.51
6,435,491	B1 *	8/2002	Blondelet et al.	267/279
6,446,993	B1	9/2002	Huszarik et al.	280/124.177
6,575,441	B2 *	6/2003	Lefebvre	267/281
6,845,994	B2 *	1/2005	Cai et al.	280/124.107
6,854,750	B2 *	2/2005	Carlstedt et al.	280/124.169
7,017,890	B2 *	3/2006	Rechtien	267/141.3
7,052,002	B2 *	5/2006	Imaeda et al.	267/140.12
7,165,909	B2 *	1/2007	Buhl et al.	403/132
7,168,879	B2 *	1/2007	Bertram et al.	403/135
7,438,493	B2	10/2008	Holmes et al.	403/134

(Continued)

**FOREIGN PATENT DOCUMENTS**

DE	3906079	2/1989	F16C 11/08
WO	WO 2008/074063 A1	12/2007	F16C 11/06
WO	WO 2010/085934 A1	1/2010	B60G 7/00

*Primary Examiner* — Paul N Dickson



*Assistant Examiner* — Barry Gooden, Jr.

(74) *Attorney, Agent, or Firm* — L.C. Begin & Associates, PLLC

(57) **ABSTRACT**

A front lower control arm assembly includes a front lower control arm and a bushing attached to the arm. The bushing has a first central axis. A ball joint is also attached to the arm. The ball joint has a second central axis oriented substantially perpendicularly to a plane including the first central axis.

**9 Claims, 3 Drawing Sheets**



(56)

**References Cited**

U.S. PATENT DOCUMENTS

8,033,557 B2 \* 10/2011 Dundon ..... 280/124.134  
8,770,884 B2 \* 7/2014 Erdogan et al. .... 403/147  
2002/0076268 A1 \* 6/2002 Paduano ..... 403/149  
2003/0111818 A1 \* 6/2003 Carlstedt et al. .... 280/124.169  
2003/0152420 A1 \* 8/2003 Broker ..... 403/135

2004/0075234 A1 \* 4/2004 Seksaria et al. .... 280/124.134  
2004/0113337 A1 \* 6/2004 Landry, Jr. .... 267/141  
2004/0201196 A1 \* 10/2004 Katagiri et al. .... 280/124.134  
2005/0051987 A1 \* 3/2005 Saitoh et al. .... 280/124.134  
2005/0191120 A1 \* 9/2005 Oellers ..... 403/133  
2006/0151970 A1 \* 7/2006 Kaminski et al. .... 280/124.134  
2006/0171775 A1 \* 8/2006 McLaughlin et al. .... 403/122  
2008/0084043 A1 \* 4/2008 Dundon ..... 280/124.125

\* cited by examiner




FIG - 1






FIG-2

FIG-5



## CROSS AXIS JOINT WITH ELASTOMERIC ISOLATION

### BACKGROUND OF THE INVENTION

The embodiments of the present invention relate to ball joints usable for connecting a lower control arm to a sub-frame of a vehicle.

### SUMMARY OF THE INVENTION

In one aspect of the embodiments of the present invention, a front lower control arm assembly is provided including a front lower control arm and a bushing attached to the arm. The bushing has a first central axis. A ball joint is also attached to the arm. The ball joint has a second central axis oriented substantially perpendicularly to a plane including the first central axis.

In another aspect of the embodiments of the present invention, a vehicle is provided including a front lower control arm coupled to a vehicle sub-frame. The arm has a portion configured for attachment to a vehicle knuckle. A ball joint couples the arm to the sub-frame. The ball joint is positioned substantially laterally of the knuckle attachment portion. The joint has a central axis oriented substantially perpendicularly to an axis of rotation of the arm with respect to the sub-frame.

In another aspect of the embodiments of the present invention, a ball joint is provided including a mounting portion defining an opening therein, and a central portion positioned within the opening. An elastomeric portion is interposed between the mounting portion and the central portion to secure the central portion within the opening. At least one void is formed in the elastomeric portion.

### BRIEF DESCRIPTION OF THE DRAWINGS

In the drawings illustrating embodiments of the present invention:

FIG. 1 is a cross-sectional side view of a ball joint in accordance with one embodiment of the present invention.

FIG. 2 is an exploded view of a sub-assembly including a vehicle sub-frame and a front lower control arm sub-assembly incorporating a ball joint in accordance with one embodiment of the present invention.

FIG. 3 is a plan view of the lower control arm sub-assembly shown in FIG. 2.

FIG. 4 is a magnified view of a portion of the lower control arm sub-assembly shown in FIG. 3 showing the ball joint of FIG. 1.

FIG. 5 is a cross-sectional side view of a ball joint in accordance with another embodiment of the present invention.

### DETAILED DESCRIPTION

FIGS. 1-4 show a ball joint 10 and a front lower control arm sub-assembly incorporating a ball joint in accordance with one embodiment of the present invention.

In the embodiment shown in FIGS. 1-4, ball joint 10 is mounted on a front lower control arm 14 of an independent suspension of a vehicle. The joint 10 is mounted substantially laterally of the portion 14k of the control arm at which the wheel knuckle (not shown) is attached, and connects the front lower control arm 14 to the vehicle sub-frame 16. In the attachment position shown in FIG. 1, joint 10 is configured so as to have a relatively high stiffness responsive to lateral loads. This enhances vehicle handling characteristics.

In this embodiment, ball joint 10 is employed as a cross axis joint designed to carry loads in a radial direction and to transfer the loads from the front lower control arm 14 to the vehicle sub-frame 16. Ball joint 10 is secured in an opening 20 formed in the lower control arm 14. Sub-frame 16 has an opening 22 formed therein for receiving a bolt or other suitable member (not shown) therethrough for connecting the ball joint 10 to the sub-frame. The connecting member passes through an opening 24 of the ball joint 10. A bushing 100 or other suitable mechanism may be used to connect another portion of the front lower control arm to another portion of the sub-frame.

In the embodiment shown in FIGS. 1-4, the ball joint 10 has central portion (generally designated 60), an elastomeric portion 52, and a mounting portion 50. Central portion 60 may comprise (or be constructed as) a conventional ball joint or swivel joint. The following description sets forth an exemplary structure for the central portion 60 that is not intended to be limiting. However, any alternative construction of central portion 60 should be adaptable to elastomeric isolation from and within a mounting portion as described herein.

Referring to FIG. 1, central portion 60 includes an annular housing 18. Housing 18 may be metallic or may be formed from any suitable material. Housing 18 supports a bearing shell 30 in a cavity formed in the housing. The bearing shell 30 is secured in place within housing 18 by a first ring 32 positioned on a first side of the bearing shell and a second ring 36 positioned on a second side of the bearing shell opposite the first side. The rings 36 and 38 are held in position by deformation of the material forming the ends of housing 18. The housing material is deformed over flanges 32a and 36a formed along respective ones of rings 32 and 36, so as to enclose the flanges and secure the rings to the housing 18.

A ball sleeve 40 is secured within the bearing shell 30. Ball sleeve 40 has a generally spherical center 40a and a pair of projecting portions 40b and 40c extending from opposite sides of center 40a. Center 40a has a ball sleeve bearing surface 46 in contact with the bearing shell 30. Inner through opening 24 extends through projecting portion 40b, center 40a, and projecting portion 40c. The ball sleeve 40 also has a first end face 41 and a second end face 43.

As shown in FIG. 1, the rings 32 and 36 each define a seat to receive an end of a respective sealing member 54 or 52. Sealing member 52 has an end 56 seated in the seat formed in ring 32. End 56 is secured in this seat by a clamping element 59. Sealing member 52 has an end 58 seated in the seat formed in ring 36. End 58 is secured in this seat by a clamping element 57.

All of the components described above may be formed from any material or materials suitable for their intended uses.

In the embodiment shown in FIGS. 1-4, mounting portion 50 comprises a ring radially spaced apart from housing 18. Mounting portion 50 is used for mounting the ball joint 10 in an opening formed in front lower control arm 14, using an interference fit or any other suitable mounting method. Mounting portion 50 may be metallic or may be formed from any suitable material.

Referring to FIGS. 1-4, elastomeric portion 52 comprises an elastomeric material interposed between central portion 60 and mounting portion 50, to provide a resilient interface between the central portion and the mounting portion. In a particular embodiment, the elastomeric material joins an outer surface 18a of housing 18 to an inner surface 50a of mounting portion 50. Elastomeric material 52 may be a rubber compound or any other material suitable for the uses described herein. In a particular embodiment, elastomeric

portion **52** comprises an elastomeric bushing seated and secured between central portion **60** and mounting portion **50**.

In the embodiment shown in FIG. 2, a front lower control arm assembly is formed in which the ball joint **10** has a cross-axis orientation wherein the central axis X of the joint **10** is oriented substantially perpendicularly to a plane including a central axis Y of bushing **100**, rather than substantially parallel to the central axis of the bushing **100**. Central axis X is also oriented substantially perpendicularly to an axis of rotation of the front lower control arm **14** with respect to vehicle sub-frame **16** during up and down motion of a vehicle wheel (not shown) attached to the control arm. In the embodiment shown in FIG. 2, axis X is also oriented substantially vertically or substantially perpendicular to a horizontal plane. Central axis X is also oriented substantially perpendicularly to a plane including a longitudinal or fore-aft axis of the vehicle (not shown).

Compared to a conventional bushing having an axis oriented substantially parallel to the axis of bushing **100**, the orientation of ball joint **10** shown in FIG. 2 provides a very low joint rotational rate in response to up-and-down wheel motion. This low rotational rate enhances ride quality. In addition, the elastomeric material interposed between central portion **60** and mounting portion **50** provides a relatively high lateral stiffness responsive to loading, which enhances vehicle handling characteristics. The elastomeric material also attenuates the transmission of noise, vibration, and harshness from the vehicle wheel to the vehicle frame.

The orientation of the joint central axis X described above also provides a package that is relatively compact and which can be nested in the sub-frame and attached thereto.

In a particular embodiment, gaps or voids **56a** and **56b** are provided in the elastomeric material **52** along opposite sides of the housing **18**. In one embodiment, the voids **56a** and **56b** are positioned generally along an axis T extending substantially parallel with a longitudinal or fore-aft axis of the vehicle. This positioning enables central portion **60** to shift slightly responsive to loads or load components acting along or parallel to the vehicle fore-aft axis. For example, when a force acting in the general direction indicated by arrow A (FIG. 4) acts on ball joint **10**, void **56a** provides less resistance to motion of central portion **60** in direction A than the elastomeric material would. Similarly, due to void **56b**, elastomeric material that would otherwise resist motion of central portion **60** in direction A is not present. The principle just described applies equally to forces acting in the general direction of arrow B of FIG. 4. Thus, voids **56a** and **56b** provide relatively lower stiffness regions which permit central portion **60** to move slightly into voids **56a** and **56b** toward mounting portion **50** responsive to longitudinal loading (i.e., loading acting along or substantially parallel to the vehicle fore-aft axis). As seen in FIG. 4, each of voids **56a** and **56b** extends along a predetermined arc length  $\alpha$ . In one particular embodiment, voids **56a** and **56b** have substantially equal arc lengths. Each of voids **56a** and **56b** has an arc length in the range of about 45 degrees to about 90 degrees. In a particular embodiment, voids **56a** and **56b** have arc lengths equal to about 60 degrees.

In one embodiment, one or more of the voids **56a** and **56b** extend from the mounting portion to the central portion.

It is believed that the relative stiffness and response to loading of ball joint **10** may be affected by controlling the amount of elastomeric material, the type of elastomeric material, and the arrangement of elastomeric material in the annular region between central portion **60** and mounting portion **50**. For example, if the positions of voids **56a** and **56b** are shifted approximately 90 degrees (as shown in FIG. 5), voids

**56a** and **56b** would provide relatively lower stiffness regions which permit central portion **60** to move slightly into the voids toward mounting portion **50** responsive to lateral loading (i.e., loading acting substantially perpendicular to the vehicle fore-aft axis), rather than longitudinal loading.

Also, the relative stiffness of the ball joint may be increased by reducing the void size or the arc length of the void. This has the effect of adding more elastomeric material, thus increasing the resistance to motion of central portion **60** relative to mounting portion **50**. Conversely, the relative stiffness of the ball joint may be decreased by increasing the void size or the arc length of the void. This has the effect of removing elastomeric material, thus decreasing the resistance to motion of central portion **60** relative to mounting portion **50**.

Also, the relative stiffness of the ball joint may be increased by substituting an elastomeric material having a relatively higher elastic modulus, which provides relatively greater resistance to forces acting on the central portion **60**. Conversely, the relative stiffness of the ball joint may be decreased by substituting an elastomeric material having a relatively lower elastic modulus, which provides relatively lower resistance to forces acting on the central portion **60**.

Also, the amount of elastomeric material, the type of elastomeric material, and the arrangement of elastomeric material in the annular region between central portion **60** and mounting portion **50** may be varied to affect the relative stiffness and response of the joint to up and down motion of the vehicle wheels. For example, it is believed that the positioning of elastomeric material **52** along an axis W extending from the ball joint center to the vehicle wheel (as shown in FIGS. 3 and 4) will provide a greater relative stiffness of the ball joint responsive to up and down motion of the wheels than a distribution of elastomeric material in which voids **56a** and **56b** are disposed along axis W (as shown in FIG. 5). It is also believed that varying the total amount of elastomeric material and the pertinent elastomeric material properties as previously described will affect the stiffness and response of the ball joint to up and down motion of the vehicle wheels.

In the manner described above, suitable variation of the amount of elastomeric material, the type of elastomeric material, and the arrangement of elastomeric material provides a method of "tuning" the dynamic response of the ball joint to applied loads.

It will be understood that the foregoing descriptions of various embodiments of the present invention is for illustrative purposes only. As such, the various structural and operational features herein disclosed are susceptible to a number of modifications, none of which departs from the scope of the present invention as defined in the appended claims.

What is claimed is:

1. A ball joint structure comprising:

- a mounting portion defining an opening therein;
  - a central portion positioned within the opening;
  - a first quantity of elastomeric material extending uninterrupted from the mounting portion to the central portion;
  - a second quantity of elastomeric material extending uninterrupted from the mounting portion to the central portion;
  - a first void separating the first and second quantities of elastomeric material and extending uninterrupted from the mounting portion to the central portion; and
  - a second void separating the first and second quantities of elastomeric material and extending uninterrupted from the mounting portion to the central portion,
- wherein the first void is in direct contact with both the first and second quantities of elastomeric material, and the

second void is in direct contact with both the first and second quantities of elastomeric material.

2. The ball joint structure of claim 1 wherein the first and second voids are positioned on a single axis extending through a central axis of the central portion, and wherein the single axis is structured to extend substantially parallel with a fore-aft axis of a vehicle when the ball joint structure is installed in the vehicle. 5

3. The ball joint structure of claim 1 wherein the first void is positioned along a first side of the central portion and the second void is positioned diametrically opposite the first void along a second side of the central portion opposite the first side. 10

4. A vehicle including a ball joint structure in accordance with claim 1. 15

5. The ball joint structure of claim 1 wherein the first void extends along an arc length of 60 degrees.

6. The ball joint structure of claim 5 wherein the second void extends along an arc length of 60 degrees.

7. A control arm assembly comprising: 20  
a front lower control arm; and  
a ball joint structure in accordance with claim 1 attached to the arm.

8. A vehicle including a control arm assembly in accordance with claim 7. 25

9. The vehicle of claim 8 wherein the first and second voids are positioned on a single axis extending through a central axis of the central portion, and wherein the single axis extends substantially parallel with a fore-aft axis of the vehicle. 30

\* \* \* \* \*