

US008997395B2

(12) **United States Patent**  
**Browne**

(10) **Patent No.:** **US 8,997,395 B2**  
(45) **Date of Patent:** **Apr. 7, 2015**

(54) **FISHING POLE HOLDER MOUNT**

(76) Inventor: **Scott Browne**, Marion, MI (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 389 days.

(21) Appl. No.: **13/537,124**

(22) Filed: **Jun. 29, 2012**

(65) **Prior Publication Data**

US 2013/0008074 A1 Jan. 10, 2013

**Related U.S. Application Data**

(60) Provisional application No. 61/504,350, filed on Jul. 5, 2011.

(51) **Int. Cl.**  
**A01K 97/10** (2006.01)

(52) **U.S. Cl.**  
CPC ..... **A01K 97/10** (2013.01)

(58) **Field of Classification Search**  
USPC ..... 43/21.2; 248/512, 513  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

1,719,695 A \* 7/1929 Ferguson ..... 248/515  
2,607,398 A 8/1952 Andrews  
D179,525 S 1/1957 Porter  
4,485,579 A \* 12/1984 Hawie ..... 43/21.2

4,650,146 A \* 3/1987 Duke ..... 248/512  
4,823,723 A \* 4/1989 Brooks ..... 114/343  
5,058,308 A 10/1991 Girard  
5,383,299 A 1/1995 Smelker  
5,438,789 A \* 8/1995 Emory ..... 43/21.2  
D393,690 S 4/1998 Lovelady et al.  
5,778,592 A \* 7/1998 Malmberg ..... 43/21.2  
5,979,102 A \* 11/1999 Sagryn ..... 43/21.2  
5,987,803 A \* 11/1999 White ..... 43/21.2  
6,289,627 B1 \* 9/2001 Gibbs et al. .... 43/21.2  
6,490,823 B1 \* 12/2002 Ibarra ..... 43/21.2  
7,296,377 B2 \* 11/2007 Wilcox et al. .... 43/21.2  
7,331,139 B2 2/2008 Moses  
7,650,713 B1 \* 1/2010 Peede ..... 43/21.2  
7,937,883 B2 \* 5/2011 Roemer et al. .... 43/21.2  
2005/0102881 A1 \* 5/2005 Legendziewicz ..... 43/21.2

**FOREIGN PATENT DOCUMENTS**

FR 2639183 A1 \* 5/1990

\* cited by examiner


*Primary Examiner* — Christopher P Ellis


(74) *Attorney, Agent, or Firm* — Buckingham Doolittle & Burroughs, LLC

(57) **ABSTRACT**

A fishing pole holder mount for mounting to a watercraft or other structure that is capable of holding more than one fishing pole at the same time, wherein the fishing pole holders are horizontally and vertically repositionable relative to one another and the base of the fishing pole holder mount. The fishing pole holder mount of the present invention also allows a user to specify the number of fishing pole holders removably attached thereto.

**18 Claims, 5 Drawing Sheets**








FIG. 2





FIG. 3








FIG. 5

**FISHING POLE HOLDER MOUNT****CROSS-REFERENCE**

This application claims priority from Provisional Patent Application Ser. No. 61/504,350 filed on Jul. 5, 2011.

**FIELD OF THE INVENTION**

This invention relates to a mounting device for holding multiple fishing poles in a removably secured and repositionable manner.

**BACKGROUND**

Oftentimes, fisherman desire to use more than one fishing pole or rod at the same time. Using more than one fishing pole at a time increases the fisherman's likelihood of catching fish and having a successful outing. However, holding and/or operating multiple fishing poles at the same time can be a challenging task for even the most accomplished or experienced fisherman.

Fishing pole holders are known in the art and are useful for holding and/or permitting a fisherman to operate more than one fishing pole at the same time. Most known fishing pole holders hold a single pole and are either inserted into the ground or attached to a pier, a boat or other watercraft. However, the use of single fishing pole holders require a fisherman to purchase multiple fishing pole holders (i.e., one for each fishing pole), which can be expensive and take up a lot of space on a pier, a boat or other watercraft, where space is typically limited. The use of single pole holders, which are oftentimes spread out in a boat to avoid the tangling of various fishing lines, also make it difficult for the fisherman to readily access any one of his or her fishing poles should the need arise (e.g., if the fisherman catches a fish).

Other fishing pole holders known in the art, such as that which is disclosed in U.S. Pat. No. 5,383,299 to Smelker, are capable of holding two fishing poles in a side by side, fixed position and are inserted into the ground. However, these fishing pole holders are not repositionable relative to one another and the surface to which they are mounted. These prior art fishing pole holders are also not capable of supporting a user specified number of additional fishing poles.

Consequently, there exists in the art a long-felt need for a fishing pole holder mount that is capable of holding more than one fishing pole at the same time, wherein the fishing pole holders are horizontally and vertically repositionable relative to one another and the surface to which they are mounted. There also exists in the art a long felt need for a fishing pole holder mount that enables a user to specify the number of fishing pole holders attached thereto. Finally, there is a long-felt need for a fishing pole holder mount that accomplishes all of the forgoing objectives and that is relatively inexpensive to manufacture, and easy to use.

**SUMMARY**

The following presents a simplified summary in order to provide a basic understanding of some aspects of the disclosed innovation. This summary is not an extensive overview, and it is not intended to identify key/critical elements or to delineate the scope thereof. Its sole purpose is to present some concepts in a simplified form as a prelude to the more detailed description that is presented later.

The subject matter disclosed and claimed herein, in one aspect thereof, is a fishing pole holder mount comprised of a

base, a support attached to and extending outwardly from said base, and more than one fishing pole holder attached to and repositionable about said support, wherein the user can specify the number of fishing pole holders attached to the support. More specifically, the fishing pole holders are stacked along said support such that the various fishing pole holders employed along said support are at differing elevations relative to the base.

The fishing pole holder mount of the present invention enables a user to easily and securely employ and manage a user specified number of fishing poles at the same time. The fishing pole holder mount also enables a user to horizontally and vertically reposition the various fishing pole holders relative to one another and the base. Finally, the fishing pole holder mount of the present invention is relatively inexpensive to manufacture, and easy to use.

To the accomplishment of the foregoing and related ends, certain illustrative aspects of the disclosed innovation are described herein in connection with the following description and the annexed drawings. These aspects are indicative, however, of but a few of the various ways in which the principles disclosed herein can be employed and is intended to include all such aspects and their equivalents. Other advantages and novel features will become apparent from the following detailed description when considered in conjunction with the drawings.

**BRIEF DESCRIPTION OF THE DRAWINGS**

FIG. 1 illustrates a perspective view of one embodiment of the fishing pole holder mount of the present invention with two fishing pole holders removably attached thereto.

FIG. 2 illustrates a perspective view of the fishing pole holder mount depicted in FIG. 1 with fishing poles installed thereon.

FIG. 3 illustrates a perspective view of the fishing pole holder mount depicted in FIG. 1 as the first and second fishing pole holders are being installed thereon.

FIG. 4 illustrates a perspective view of another embodiment of the fishing pole holder mount of the present invention which employs three fishing pole holders.

FIG. 5 illustrates a perspective view of another embodiment of the fishing pole holder mount of the present invention which is capable of being used in conjunction with an existing fishing pole holder.

**DETAILED DESCRIPTION**

The innovation is now described with reference to the drawings, wherein like reference numerals are used to refer to like elements throughout. In the following description, for purposes of explanation, numerous specific details are set forth in order to provide a thorough understanding thereof. It may be evident, however, that the innovation can be practiced without these specific details.

The fishing pole holder mount of the present invention enables a user to easily and securely employ and manage a user specified number of fishing poles at the same time. The fishing pole holder mount also enables a user to horizontally and vertically reposition the various fishing pole holders relative to one another and the base. Finally, the fishing pole holder mount of the present invention is relatively inexpensive to manufacture and easy to use.

Referring initially to the drawings, FIG. 1 illustrates a perspective view of one embodiment of the fishing pole holder mount 100 of the present invention, which comprises a base 110, a support 120, a first fishing pole holder 140 and



3

a second fishing pole holder **160**. Unless otherwise stated herein, the various components of fishing pole holder mount **100** are preferably constructed of a metal, such as steel, iron or aluminum, though it is contemplated that base **110** can also be constructed of other durable materials, such as wood, plastic and the like, without affecting the overall concept of the present invention.

Base **110** is preferably a plate-like structure that can be used to attach fishing pole holder mount **100** to a relatively flat surface such as the ground, a watercraft (e.g. a boat), a deck, railing or the like. More specifically, base **110** is preferably comprised of a top surface **112**, a bottom surface **114** and a plurality of spaced apart openings **116** extending through said base **110** for receipt of fasteners **118** for attaching the base to an object or surface. Fasteners **118** can be any fastener commonly known in the art for securing a structure to a surface, including nails, screws, rivets and the like. For a more permanent solution, it is also contemplated that base **110** can be glued or welded to the desired object or surface.

While the materials used and the dimensions of base **110** can vary to suit user preference and the particular application, a base **110** comprised of aluminum and measuring approximately 4 inches in length by 4 inches in width with an approximate thickness of  $\frac{1}{4}$  inch is suitable for most applications and environments. Notwithstanding any of the foregoing, it is also contemplated that base **110** can be in the form of a prior art clamp or band, as opposed to a plate, provided that base **110** can function to securely attach support **120** to a desired surface.

As illustrated in FIG. 1, support **120** is preferably an elongated member, such as a length of pipe, comprised of a first end **122**, a second end **124** and an outer surface **126**. First end **122** of support **120** can be attached to the top surface **112** of base **110** by any common means known in the art such as welding, glue, etc., and extends outwardly from base **110** as shown in the FIGS. Nonetheless, it is also contemplated that support **120** could be fixedly or removably attached to base **110** by other means commonly known in the art including, without limitation, fasteners, clamps, press-fit, threading, etc.

Support **120** is preferably cylindrical in shape and between 12 and 20 inches in length, measured from first end **122** to second end **124**, with an outside diameter of between  $\frac{3}{4}$  and 2 inches. However, it is also contemplated that other shapes and dimensions can be used to suit user preference. The outer surface **126** of support **120** can be relatively smooth or threaded (not shown) to mate with the interior surface of a fishing pole holder in a male-female relationship, as further described below.

As depicted in the FIG. 1, first fishing pole holder **140** is preferably a generally y-shaped section of pipe comprised of a relatively straight body portion **141** with a continuous opening **142** formed therein for receipt of support **120**, and a holder portion **144** with an opening **146** formed therein for receipt of a handle **202** of a fishing pole **200**. The interior surface of continuous opening **142** can be relatively smooth or threaded (not shown) for removable attachment to a support **120** with a corresponding relatively smooth or threaded outer surface **126**. The length of straight body portion **141** is preferably between 3 and 7 inches and the inside diameter of continuous opening **142** should be sized to correspond to the outside diameter of support **120** so that first fishing pole holder **140** can be placed or threaded over support **120**, as best illustrated in FIGS. 1-4.

The length of holder portion **144**, measured from body portion **141** to the end of holder portion **144** is preferably between 9 and 10 inches, though it is contemplated that other dimensions could also be used within the scope of the present

4

invention. The inside diameter of holder opening **146** should be approximately between 1 and 3 inches to receive most sizes of fishing pole handles **202**, though other diameter sizes are also contemplated. The angle of holder portion **144** relative to body portion **141** is preferably between 30 and 45 degrees, though it is contemplated that other angles could also be used. In a preferred embodiment of the present invention, body portion **141** may further comprise a fastening means **148**, such as a set screw, winged screw (as shown in the FIGS.) or other fastener, for securing first fishing pole holder **140** in a desired position along support **120**, as described more fully below. Similarly, an additional fastening means **148** could also be included along holder portion **144** to secure fishing pole handle **202** within holder opening **146** of first fishing pole holder **140**.

Second fishing pole holder **160** is also preferably a generally y-shaped section of pipe comprised of a relatively straight body portion **161** with a continuous opening **162** formed therein for receipt of support **120**, and a holder portion **164** with an opening **166** formed therein for receipt of a handle **202** of a fishing pole **200**. The interior surface of continuous opening **162** can be relatively smooth or threaded (not shown) for removable attachment to a support **120** with a corresponding relatively smooth or threaded outer surface **126**. The length of straight body portion **161** is preferably between 3 and 7 inches and the inside diameter of continuous opening **162** should be sized to correspond to the outside diameter of support **120** so that second fishing pole holder **160** can be placed or threaded over support **120**, as best illustrated in FIG. 3 and explained more fully below.

The length of holder portion **164**, measured from body portion **161** to the end of holder portion **164** is preferably between 9 and 10 inches, though it is contemplated that other dimensions could also be used within the scope of the present invention. The inside diameter of holder opening **166** should be approximately between 1 and 2 inches to receive most sizes of fishing pole handles **202**, though other diameter sizes are also contemplated. The angle of holder portion **164** relative to body portion **161** is preferably between 30 and 45 degrees, though it is contemplated that other angles could also be used. In a preferred embodiment of the present invention, body portion **161** may further comprise a fastening means **168**, such as a set screw, winged screw (as shown in the FIGS.) or other fastener, for securing second fishing pole holder **160** in a desired position along support **120** above first fishing pole holder **140**, as described more fully below. Similarly, an additional fastening means **168** could also be included along holder portion **164** to secure fishing pole handle **202** within holder opening **166** of second fishing pole holder **160**.

As depicted in the FIG. 4, fishing pole holder mount **100** can be further comprised of additional first fishing pole holders **180** to suit user preference. Each of additional fishing pole holders **180** is preferably a generally y-shaped section of pipe comprised of a relatively straight body portion **181** with a continuous opening **182** formed therein for receipt of support **120**, and a holder portion **184** with an opening **186** formed therein for receipt of a handle **202** of a fishing pole **200**. The interior surface of continuous opening **182** can be relatively smooth or threaded (not shown) for removable attachment to a support **120** with a corresponding relatively smooth or threaded outer surface **126**. The length of straight body portion **181** is preferably between 3 and 7 inches and the inside diameter of continuous opening **182** should be sized to correspond to the outside diameter of support **120** so that the additional fishing pole holder(s) **180** can be placed or



## 5

threaded over support **120** above first fishing pole holder **140** and second fishing pole holder **160**, as best illustrated in FIG. 4.

The length of holder portion **184**, measured from body portion **181** to the end of holder portion **184** is preferably between 9 and 10 inches, though it is contemplated that other dimensions could also be used within the scope of the present invention. The inside diameter of holder opening **186** should be approximately between 1 and 2 inches to receive most sizes of fishing pole handles **202**, though other diameter sizes are also contemplated. The angle of holder portion **184** relative to body portion **181** is preferably between 30 and 45 degrees, though it is contemplated that other angles could also be used. In a preferred embodiment of the present invention, body portion **181** may further comprise a fastening means **188**, such as a set screw, winged screw (as shown in FIG. 4) or other fastener, for securing the additional fishing pole holder **180** in a desired position along support **120**, as described more fully below. Similarly, an additional fastening means **188** could also be included along holder portion **184** to secure fishing pole handle **202** within holder opening **186** of additional fishing pole holder **180**.

FIG. 5 illustrates yet another potential embodiment of the device of the present invention, and further includes a converter device **190** that can be used to attach fishing pole holder mount **100**, less base **110**, to an existing prior art fishing pole holder (not shown), thereby allowing the user to easily and quickly convert an existing single fishing pole holder into a multi-fishing pole holder. More specifically, converter device **190** can be securely and removably attached to an existing fishing pole holder by inserting the same into an opening in an existing fishing pole holder (not shown) similar to the way that a fishing pole handle would be inserted into the holder. Once inserted, support **120** can be placed over top of converter device **190** as shown in FIG. 5.

Converter device **190** preferably comprises a body portion **192**, a plurality of washers **194**, a compression portion **196** and a tightening means **198**, such as a threaded bolt. Each of bolt **198**, body portion **192** and washers **194** are preferably comprised of a durable materials such as a metal, plastic, etc., and compression portion **196** is preferably comprised of a compressible material such as rubber, though other materials could also be used.

Each of body portion **192**, washers **194**, and compression portion **196** have a continuous opening therein (not shown) for receipt of bolt **198**, and the continuous opening in the outermost washer **194** that is adjacent to compression portion is preferably threaded to match the thread pattern of bolt **198**. In this manner, as bolt **198** is threaded into said outermost washer **194** said outermost washer **194** is drawn closer to the head of bolt **198** which, in turn will cause compression portion **196** to compress and its outside diameter to expand against the interior portion of the existing fishing pole holder.

Having now described the preferred and alternative embodiments of fishing pole holder mount **100**, the use and usefulness of the preferred embodiment will now be described. A user (not shown) desiring to use the mount **100** would first use fasteners **118** to removably attach base **110** to a desired structure (e.g., a watercraft, a deck, railing, the ground, etc.). Once attached, the user would install the desired number of fishing pole holders along support **120**. For example, a user desiring to use mount **100** in conjunction with three fishing poles **200** would install first fishing pole holder **140**, second fishing pole holder **160** and third fishing pole holder **180** on support **120** in stacked relationship as shown in FIG. 4. If the outer surface **126** of support **120** is relatively smooth, the user would simply insert the second end **124** of

## 6

support **120** through opening **142** of first fishing pole holder **140** and slide first fishing pole holder **140** along support **120** into the desired position above base **110**. It should also be appreciated that holder portion **144** can be rotated about support **120** so that the user can also select the direction in which his or her fishing pole **200** will extend from support **120**. Once the desired position and direction are achieved, the user can use the fastening means **148** to removably secure first fishing pole holder **140** to the support **120**. Once secured, the user can insert fishing pole handle **202** into holder opening **146** and use the fastening means **148** located along holder portion **144** to secure the fishing pole **200** to the first fishing pole holder **140**. Second fishing pole holder **160** and additional fishing pole holder(s) **180** can be attached to support **120** in the same manner and in a stacked fashion as depicted in FIG. 4. It should be appreciated that each of fishing pole holders **140**, **160** and **180** can be positioned to extend outwardly from support **120** in different directions, as best illustrated in FIG. 4.

By comparison, if the outer surface **126** of support **120** and the inner surfaces of body portions **141**, **161**, **181** are threaded, the user would simply thread each of fishing pole holders **140**, **160** and **180** onto support **120** in stacked relationship. Similar to the unthreaded embodiment of the present invention, it should be appreciated that each of fishing pole holders **140**, **160** and **180** can be positioned to extend outwardly from support **120** in different directions, as best illustrated in FIG. 4.

Additionally, other variations are within the spirit of the present invention. Thus, while the invention is susceptible to various modifications and alternative constructions, a certain illustrated embodiment thereof is shown in the drawings and has been described above in detail. It should be understood, however, that there is no intention to limit the invention to the specific form or forms disclosed, but on the contrary, the intention is to cover all modifications, alternative constructions, and equivalents falling within the spirit and scope of the invention, as defined in the appended claims.

The use of the terms “a” and “an” and “the” and similar referents in the context of describing the invention (especially in the context of the following claims) are to be construed to cover both the singular and the plural, unless otherwise indicated herein or clearly contradicted by context. The terms “comprising,” “having,” “including,” and “containing” are to be construed as open-ended terms (i.e., meaning “including, but not limited to,”) unless otherwise noted. The term “connected” is to be construed as partly or wholly contained within, attached to, or joined together, even if there is something intervening. Recitation of ranges of values herein are merely intended to serve as a shorthand method of referring individually to each separate value falling within the range, unless otherwise indicated herein, and each separate value is incorporated into the specification as if it were individually recited herein. All methods described herein can be performed in any suitable order unless otherwise indicated herein or otherwise clearly contradicted by context. The use of any and all examples, or exemplary language (e.g., “such as”) provided herein, is intended merely to better illuminate embodiments of the invention and does not pose a limitation on the scope of the invention unless otherwise claimed. No language in the specification should be construed as indicating any non-claimed element as essential to the practice of the invention.

Preferred embodiments of this invention are described herein. Variations of those preferred embodiments may become apparent to those of ordinary skill in the art upon reading the foregoing description. The inventor expects



7

skilled artisans to employ such variations as appropriate, and the inventor intends for the invention to be practiced otherwise than as specifically described herein. Accordingly, this invention includes all modifications and equivalents of the subject matter recited in the claims appended hereto as permitted by applicable law. Moreover, any combination of the above-described elements in all possible variations thereof is encompassed by the invention unless otherwise indicated herein or otherwise clearly contradicted by context.

What is claimed is:

1. A fishing pole holder mount comprising:  
a base;  
a first fishing pole holder attached to said base, wherein said first fishing pole holder is generally y-shaped and comprised of a body portion, a holder portion with an opening therein and a fastening means for adjusting the size of said opening; and  
a second fishing pole holder attached to said base, wherein a portion of said second fishing pole holder is positioned above said first fishing pole holder.
2. The fishing pole holder mount of claim 1 wherein said fishing pole holder mount further comprises at least one additional fishing pole holder.
3. The fishing pole holder mount of claim 1 wherein said base is mounted to a watercraft.
4. The fishing pole holder mount of claim 1 wherein said first fishing pole holder is repositionable relative to said second fishing pole holder.
5. The fishing pole holder mount of claim 1 wherein each of said first fishing pole holder and said second fishing pole holder further comprise an opening therein for receipt of a fishing pole.
6. The fishing pole holder mount of claim 1 further comprising a user specified number of additional fishing pole holders attached to said base.
7. The fishing pole holder mount of claim 1 wherein at least one of said first fishing pole holder and said second fishing pole holder is comprised of aluminum.
8. A fishing pole holder mount comprising:  
a base;  
a support;  
a first fishing pole holder attached to and repositionable about said support; and  
a second fishing pole holder attached to and repositionable about said support, wherein a portion of said second fishing pole holder is positioned above said first fishing

8

pole holder and further wherein said second fishing pole holder is generally y-shaped and comprised of a body portion, a holder portion with an opening therein and a set screw for adjusting the size of said opening.

9. The fishing pole holder mount of claim 8 wherein said first fishing pole holder is rotationally and vertically repositionable along said support.

10. The fishing pole holder mount of claim 8 wherein said base is mounted to a watercraft.

11. The fishing pole holder mount of claim 8 further comprising a user specified number of additional fishing pole holders attached to and repositionable about said support.

12. The fishing pole holder mount of claim 8 wherein each of said first fishing pole holder and said second fishing pole holder further comprise an opening therein for receipt of a fishing pole.

13. The fishing pole holder mount of claim 8 wherein at least one of said first fishing pole holder and said second fishing pole holder is comprised of aluminum.

14. The fishing pole holder mount of claim 11 wherein at least one of said user specified number of additional fishing pole holders is positioned above both the first fishing pole holder and the second fishing pole holder relative to the base.

15. A fishing pole holder mount comprising:  
a base;

- 25 a support comprised of a threaded outer surface;

- a first fishing pole holder attached to and repositionable about said support, wherein said first fishing pole holder is further comprised of a threaded interior surface for mating with said threaded outer surface; and

- 30 a second fishing pole holder attached to and repositionable about said support, wherein a portion of said second fishing pole holder is positioned above said first fishing pole holder and further wherein said second fishing pole holder is generally y-shaped and comprised of a body portion, a holder portion with an opening therein and a set screw for adjusting the size of said opening.

- 35 16. The fishing pole holder mount of claim 15 wherein said first fishing pole holder is rotationally and vertically repositionable along said support.

- 40 17. The fishing pole holder mount of claim 15 wherein said base is mounted to a watercraft.

- 45 18. The fishing pole holder mount of claim 15 further comprising a user specified number of additional fishing pole holders attached to and repositionable about said support.

\* \* \* \* \*