



US008997715B2

(12) **United States Patent**
Worthington et al.

(10) **Patent No.:** **US 8,997,715 B2**
(45) **Date of Patent:** **Apr. 7, 2015**

(54) **COMMON RAIL SYSTEM WITH LEAK CONTAINMENT AND DETECTION**

USPC 73/40; 123/198 D, 456, 468, 514, 469, 123/445, 447
See application file for complete search history.

(75) Inventors: **Joseph Worthington**, Seymour, IN (US); **Thomas O. Hahn**, Columbus, IN (US); **Vijay Sonawane**, Pune (IN); **Prasad Khedekar**, Pune (IN); **Dave Richter**, Columbus, IN (US); **Josh Knight**, Columbus, IN (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,149,568	A	4/1979	Kuntz et al.	
6,286,556	B1	9/2001	Kato	
6,827,065	B2 *	12/2004	Gottmoller et al.	123/456
7,337,652	B2	3/2008	Shamine	
2005/0166899	A1 *	8/2005	Shamine et al.	123/456
2005/0235964	A1 *	10/2005	Shibata	123/458
2006/0130560	A1 *	6/2006	Shamine	73/40
2010/0192910	A1 *	8/2010	Toyoshima	123/456

(73) Assignee: **Cummins Intellectual Properties, Inc.**, Minneapolis, MN (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 971 days.

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **13/103,066**

EP 2011996 A1 1/2009

(22) Filed: **May 8, 2011**

* cited by examiner

(65) **Prior Publication Data**

US 2012/0006297 A1 Jan. 12, 2012

Primary Examiner — Mahmoud Gimie

Assistant Examiner — Sizo Vilakazi

(74) *Attorney, Agent, or Firm* — Faegre Baker Daniels LLP

Related U.S. Application Data

(57) **ABSTRACT**

(60) Provisional application No. 61/332,524, filed on May 7, 2010.

This disclosure provides a fuel system for supplying fuel to an internal combustion engine, an internal combustion engine that includes such a fuel system, a connector for connecting a single-walled high pressure common rail to a double-walled fuel line segment, and a fluid containment system. Each embodiment includes drain plumbing having a leakage drain connector that can be used to provide an interface between a single-walled high pressure common rail and a double-walled high pressure fuel line segment, and also provide part of a low pressure passage fluidly connected with a low pressure passage of the double-walled high pressure fuel line segment. The drain plumbing also can provide an interface with a low pressure fuel drain line fluidly coupled to a leakage detector.

(51) **Int. Cl.**

F02M 69/46	(2006.01)
F02M 55/02	(2006.01)
F02M 37/00	(2006.01)
F02M 55/00	(2006.01)
F02M 65/00	(2006.01)


(52) **U.S. Cl.**

CPC **F02M 55/025** (2013.01); **F02M 37/0052** (2013.01); **F02M 55/00** (2013.01); **F02M 65/006** (2013.01)

(58) **Field of Classification Search**

CPC B67D 7/3209; B67D 7/78

26 Claims, 3 Drawing Sheets






FIG. 1A




FIG. 1B




FIG.2A




FIG. 2B

COMMON RAIL SYSTEM WITH LEAK CONTAINMENT AND DETECTION

RELATED APPLICATIONS

This application claims benefit of priority to Provisional Patent Application No. 61/332,524, filed on May 7, 2010, the entire contents of which are hereby incorporated by reference.

FIELD OF THE INVENTION

The inventions relate to fluid leak containment plumbing, and more particularly, to a high pressure fluid system, such as a fuel system of an internal combustion engine, and a fluid system component, that can contain and detect leaking fluid.

BACKGROUND

To safely deliver fuel in high pressure systems, modern fuel systems include measures to contain fuel leaks that may occur. For example, marine agency requirements such as the International Convention for the Safety of Life at Sea (SOLAS) treaty require double-walled fuel lines to prevent the likelihood of fire on a commercial marine vessel. These double-walled fuel lines must include a gap between the inner and outer walls to allow any fuel leaked from the inner wall to be detected by a fuel sensor while being contained by the outer wall.

SUMMARY

This disclosure provides a fuel system for use with an internal combustion engine and an internal combustion engine including such a fuel system, each of which include a single-walled high pressure common rail, plural double-walled high pressure fuel lines that include a low pressure leak containment passage, and drain plumbing that includes leakage drain connectors forming interfaces between the single-walled high pressure common rail and respective ones of the double-walled high pressure fuel lines and forming part of the low pressure containment passage. This disclosure also provides a connector for interfacing a single-walled high pressure common rail with a double-walled fuel line, and a leak containment system for containing fuel or other types of fluids delivered from one place to another under high pressure.

In an embodiment, a fuel system for supplying fuel to an internal combustion engine includes a single-walled high pressure common rail including a main body and plural members extending from the main body, where each member has a high pressure passage leading to the main body. The system includes plural double-walled fuel line segments adapted to fluidly connect the high pressure passages of the single-walled high pressure common rail to respective plural fuel injectors, where each segment includes a high pressure fuel line, a jacket surrounding the high pressure fuel line, a low pressure passage between the high pressure fuel line and the jacket, and a fuel line connector. The fuel line connector includes a main body housing a portion of the high pressure fuel line such that an end portion of the high pressure fuel line protrudes from a first end of the main body and a second end of the main body is sealingly connected to the jacket to thereby extend the low pressure passage into the fuel line connector. The system includes plural leakage drain connectors, where each of the leakage drain connectors is sealingly connected at a first end portion thereof to one of the members,

and sealingly connected at a second end portion thereof to one of the plural fuel line connectors. In this way, the protruding end portion of the high pressure fuel line sealingly engages with the high pressure passage of the member, and the low pressure passage of the fuel line connector extends through the leakage drain connector to an opening at an outer surface of the leakage drain connector. A fuel drain line fluidly is coupled to each of the openings of the plural leakage drain connectors.

In another embodiment, an internal combustion engine includes a plurality of cylinders and plural fuel injectors, where each of the cylinders is associated with one of the fuel injectors. The engine includes a single-walled high pressure common rail including a main body and plural members extending from the main body, where each member has a high pressure passage leading to the main body. The engine includes plural double-walled fuel line segments, where each of the segments has a high pressure fuel line, a jacket surrounding the high pressure fuel line portion, a low pressure passage between the high pressure fuel line and the jacket, a first end fluidly connected to a respective one of the fuel injectors, and a fuel line connector including a main body. The fuel line connector houses a portion of the high pressure fuel line such that an end portion of the high pressure fuel line protrudes from a first end of the main body and a second end of the main body is sealingly connected to the jacket to thereby extend the low pressure passage into the fuel line connector. The engine includes plural leakage drain connectors, where each leakage drain connector is sealingly connected at a first end portion thereof to one of the members, and is sealingly connected at a second end portion thereof to one of the plural fuel line connectors. In this way, the protruding end portion of the high pressure fuel line sealingly engages with the high pressure passage of the member, and the low pressure passage of the fuel line connector extends through the leakage drain connector to an opening at an outer surface of the leakage drain connector. A fuel drain line fluidly coupled to each of the openings of the plural leakage drain connectors.

In another embodiment, a connector for connecting a single-walled high pressure common rail to a double-walled fuel line includes a main body having a first opening substantially aligned along a longitudinal axis of the main body and is configured to sealingly attach to a member extending from a single-walled high pressure common rail, and a second opening opposite the first opening and configured to sealingly attach to a connector of a double-walled high pressure fuel line such that the high pressure portion of the double-walled fuel line seals with the member to form a continuous high pressure passage. The at least one third opening provided along a direction substantially orthogonal to the longitudinal axis. A fuel collection manifold is around the main body and has a channel between the third opening and an outer surface of the fuel collection manifold such that a low pressure passage for fuel leaking from the double-walled fuel line extends from the channel through the third opening.

In yet another embodiment of the disclosure, a leak containment system includes a single-walled high pressure accumulator including a high pressure cavity, a double-walled line including a high pressure line, a jacket surrounding the high pressure line, an annular region between the high pressure line and the jacket, and a line connector housing a portion of the double-walled line and configured to fluidly attach the double-walled line to the single-walled high pressure accumulator, a drain line, and a leakage drain connector having a first end sealingly attached to the single-walled high pressure accumulator, a second end sealingly attached to the line con-

necter, and a side portion fluidly connected to the leakage drain line. The leakage drain connector houses a portion of the high pressure line. A leakage detector is fluidly coupled to the drain line. In the system, a continuous high pressure passage is formed that includes the high pressure cavity fluidly connected to the high pressure line, and a continuous low pressure passage is formed that includes the annular region, the drain line, and interior regions of the leakage drain connector and the line connector outside the housed high pressure line.

BRIEF DESCRIPTION OF THE DRAWINGS

FIGS. 1A and 1B are perspective diagrams of a fuel system according to an exemplary embodiment.

FIG. 2A is a more detailed perspective diagram of a portion of the fuel system shown in FIGS. 1A and 1B including a single-walled high pressure common rail, drain plumbing and high pressure double-walled fuel lines.

FIG. 2B is a diagram showing a cross section of the high pressure common rail, drain plumbing and the high pressure double-walled fuel lines shown in FIG. 2A.

DETAILED DESCRIPTION

The inventors have realized that known single-walled high pressure common rails (i.e., accumulators) and/or designs of high pressure common rails that would be commonly available can be made to interface with a bank of double-walled fuel injection lines and meet marine agency safety requirements. More specifically, drain plumbing described herein provides an interface between a single-walled high pressure common rail and a double-walled high pressure line (e.g., a fuel injector line) that avoids complicated and expensive designs that would require developing a double-walled high pressure common rail, while also providing a structure that can contain and detect fluid leaks.

FIGS. 1A and 1B show perspective diagrams of a fuel system according to an exemplary embodiment. As shown in FIGS. 1A and 1B, the fuel system includes plural double-walled fuel line segments **10** that fluidly couple with a high pressure cavity of a single-walled common rail **12** (i.e., accumulator). The high pressure cavity of the common rail **12** receives fuel at high pressure from a high pressure fuel pump and temporarily stores fuel at high pressure so it is available to injectors (not shown) attached to the double-walled fuel line segments. The fuel system includes drain plumbing **14** positioned between the common rail **12** and the fuel line segments **10**. The drain plumbing **14** provides an interface between the double-walled fuel line segments **10** and the high pressure common rail **12** that allows containment, collection and/or detection of fuel leaked from high pressure elements of the fuel system.

More specifically, the drain plumbing **14** includes a fuel drain line **16** into which fuel leaking from any of the double-walled fuel injector lines **10** flows. Leaking fuel in the fuel drain line **16** is directed to a leakage detector (not shown) that detects the leaking fuel. For example, one end **18** of the fuel drain line **16** can be provided with or fluidly coupled to a fuel leakage detector, such as a tell tale sensor element, flow meter, pressure or vacuum sensor, float switch, or a low pressure fuel sensor, and the other end **20** of the fuel drain line **16** can be capped or connected to a fuel drain line of another bank of plural double-walled fuel line segments **10**, drain plumbing **14** and injectors.

The fuel drain line **16** is part of a low pressure circuit also including the outer walls of the plural double-walled fuel line segments **10** and the outer walls of the drain plumbing **14**,

which contains the leaking fluid so it can be directed back in one or more conduits to the fuel tank, the fuel pump, and/or another storage tank or container (not shown). A detected leak can trigger activation of a visual and/or audible alarm, a message (e.g., email, text) or another indication or notification mechanism. For example, a leakage detector can be monitored by an ECM (engine control module), which upon receiving a signal indicating a leakage event, triggers an audible alarm or visual alarm on a display to alert an operator of the engine.

Although the fuel system embodiment of FIGS. 1A and 1B is shown as including a combination of six pairs of double-walled fuel line segments **10** and corresponding drain plumbing **14** elements, other applications can include embodiments that group these pairs in various configurations. For example, embodiments can include as little as one pair corresponding to a single fuel injector and engine cylinder, a group of pairs corresponding to all of the cylinders an engine, an entire bank of an engine's cylinders, or any predetermined number of pairs in any predetermined number of groups where each group corresponds to a subgroup of an engine's cylinders. Further, each group can include a fuel drain line that fluidly communicates with a detection element shared by plural groups or with detection element corresponding to only that group.

FIGS. 2A and 2B show a more detailed view of a portion of the fuel system configuration depicted in FIGS. 1A and 1B. As shown in FIG. 2A, each drain plumbing **14** is provided at an end of a respective double-walled fuel line segment **10** of a bank of the fuel injector lines to fluidly couple the single-walled common rail **12** to a respective double-walled fuel line segment **10**, each of which includes a fuel line connector **24**, or sometimes called a high pressure fuel line nut **24** housing a portion of the double-walled fuel line segment **10**. Each drain plumbing **14** includes a leakage drain connector **22** sealingly connected to the single-walled common rail **12** and to a fuel line connector **24**, and a fuel collection manifold **26** housing a portion of the high pressure fuel line and sealingly engaged with the leakage drain connector **22** to collect and contain any fuel leaked from high pressure lines of the double-walled fuel line segments **10**. Each fuel collection manifold **26** is fluidly connected to the fuel drain line **16** that can include, for example, banjo connectors **28** that for interfaces with surfaces of the fuel collection manifold to provide a path for fuel leaking from high pressure fuel line of the double-walled fuel line segments **10** to a leakage detector (not shown) fluidly coupled with the fuel drain line **16**, although fuel leaking from the injector also can be channeled into the low pressure circuit. The single-walled common rail **12** can include one or more mounting structures **30** to secure the single-walled common rail **12** and other fuel system elements attached to the single-walled common rail **12** to an internal combustion engine or other supporting structure (not shown).

FIG. 2B is a cross sectional view of the single-walled common rail **12**, a leakage drain connector **22** sealingly attached to one of plural members (e.g., a nipple) extending from the single-walled common rail **12**, a fuel collection manifold **26**, and a double walled fuel injection line. In the embodiment shown in FIG. 2B, the leakage drain connector **22** includes a main body including a threaded opening at each end of the main body along the longitudinal axis of the main body. Each fuel collection manifold **26** can include a surface **29** at which a banjo fitting **28** of the fuel drain line **16** (not shown in FIG. 2B) is sealingly engaged.

The fuel collection manifold **26** is retained at a predetermined longitudinal position on the leakage drain connector **22** by a bump out portion forming a nut head at one end of the

5

leakage drain connector **22**, which provides a stop preventing insertion of the main body of the leakage drain connector **22** into the fuel collection manifold **26** beyond the predetermined longitudinal position along the direction of the longitudinal axis of the connector **22**. The leakage drain connector **22** is retained on its other end by a retaining clip element **29** (e.g., a c-clip) engaged with a profile feature on the leakage drain connector **22**, which is shown as slot formed in a surface of the outer wall of the leakage drain connector **22**. It is to be appreciated that a configuration for retaining the fuel collection manifold **26** different from one having a retaining clip can be used, such as a retaining nut, pin etc. used in combination with a profile feature such as a slot, hole threads, or another profile element positioned on an outer surface of the main body to secure the leakage drain connector **22** at the predetermined position. In a preferred embodiment, the fuel collection manifold **26** is rotatable about and relative to the leakage drain connector **22** to facilitate aligning plural fuel collection manifolds **26** to be connected to a single fuel drain line **16**.

In another embodiment, the fuel collection manifold **26** may be an integrally formed portion of the leakage drain connector **22**. In another embodiment, no manifold is provided, and the drain line **16** is connected to a surface of the leakage drain connector **22**.

FIG. 2B also shows details of an embodiment of a double-walled fuel line segment **10**, which has a configuration that contains fuel leaking from a high pressure fuel line of the double-walled fuel line. More specifically, the double-walled fuel line segment **10** includes a high pressure fuel line **38** forming an inner wall, and a low pressure fuel line or jacket **40** forming an outer wall surrounding the inner wall of the double-walled fuel line structure. The inner surface of the jacket **40** and the outer surface of the high pressure fuel line **38** can be tubular such that they define an annular area or passage therebetween. Although not shown, the double-walled fuel line segments **10** also can include one or more spacers between the high pressure fuel line **38** and the jacket **40**, which are periodically spaced from another to maintain some uniformity to the annular area. Additionally, the spacers can include passages therethrough that allow leaking fuel to pass. The annular passage thus formed provides a low pressure passage relative to a high pressure passage formed by the high pressure fuel line **38** (i.e., when fuel is present in that line portion) and defines an area into which fuel leaking from the high pressure fuel line **38** can enter to be contained and detected. The low pressure region extending through the double-walled fuel line segment **10** is a portion of the larger continuous low pressure circuit that includes low pressure passages in the interior of the high pressure nut **24**, in the interior of the leakage drain connector **22**, in a channel of the fuel collection manifold **26**, and in the fuel drain line **16**. However, because the single-walled high pressure common rail **12** does not include an enclosed low pressure region surrounding its high pressure cavity, the low pressure circuit is terminated in the direction of the high pressure common rail **12** by the sealing engagement of the leakage drain connector **22** with a member of the high pressure common rail **12**.

Each leakage drain connector **22** can include at least one opening **23** that opens in a direction substantially orthogonal to the longitudinal axis of the main body of the connector **22** to allow the low pressure passage in the leakage drain connector **22** to fluidly communicate with a low pressure channel **41** provided in the fuel collection manifold **26**. For each double-walled fuel line segment **10**, fuel leaking from a high pressure inner wall portion **38** can enter the channel **41** of the corresponding fuel collection manifold **26**, and the channels

6

41 of all the fuel collection manifolds **26** in a bank of double-walled fuel lines **10** are fluidly connected to a low pressure passage in fuel drain line **16**. Because fuel leaks from any of the high pressure fuel lines **38** of the plural double-walled fuel line segments **10** are directed to a single fuel drain line **16** in this embodiment, a single fuel leakage detector (e.g., a single sensor) can be used to detect any fuel leaked from any one of the high pressure fuel lines **38**.

As shown in FIG. 2B, a mechanical, conical seal **48** can be used to seal fuel between the high pressure line **38** of the double-walled fuel line segment **10** by compressing an end portion of the high pressure fuel line **38** protruding from an end of the main body of the high pressure nut **24** with a complementary surface formed in a nipple of the single-walled common rail (accumulator) **12**. The high pressure fuel line **38** can use a high pressure fuel line sleeve **44** and high pressure fuel line spacer **46** to transfer force to the conical end of the protruding portion of the high pressure inner wall as the high pressure fuel line nut **24** in threaded engagement with the leakage drain connector **22** is tightened, to allow mechanical sealing of the high pressure fuel line **38** to the member single-walled common rail (accumulator) **12**. With the conical seal **48** in sealing engagement, a high pressure circuit includes the cavity of the single-walled high pressure common rail, a high pressure passage in the member leading to the cavity, and the high pressure fuel line **38**. The high pressure fuel line spacer **46** includes passages, for example, holes drilled through the spacer, that allow leaked fuel at low pressure present in an annular passage between the high pressure fuel line **38** and inner wall of the jacket portion **40** to pass between a low pressure passage in the high pressure fuel line nut **24** and a low pressure passage in the leakage drain connector **22**. From the low pressure passage in the leakage drain connector **22**, the leaked fuel can pass through opening **24** to the channel **41** and thereafter to the fuel drain line **16**.

In the exemplary embodiment shown in FIG. 2B, O-ring seals are used to seal interfaces in the low pressure system circuit, although other gasket or sealing elements can be used to provide sealing engagement between elements of the fuel system. For example, O-ring seals **32** can be used to seal any leaking fuel between the single-walled common rail **12** and leakage drain connector **22** to seal fuel from the common rail (accumulator) **12**; O-ring seals **34** can be used between the fuel collection manifold **26** and leakage drain connector **22** to seal fuel from outside of the fuel collection manifold **26** while preferably allowing rotation of the fuel collection manifold **26**; O-ring seals **36** can be used between the leakage drain connector **22** and high pressure fuel line nut **24** to seal fuel from the outer diameter of the high pressure fuel line nut **24**; and O-ring seals **42** can be used between the jacket portion **40** of the high pressure fuel line **10** and high pressure fuel line nut **24** to seal any leaking fuel in the low pressure passage formed by the high pressure fuel line nut **24** and the annular area between the jacket portion **40** and the high pressure fuel line **38** of the fuel injection line **10**.

Embodiments consistent with the disclosure allow the common rail (accumulator) **12** to remain single-walled, which simplifies design and facilitates cost savings. For example, without plural fuel collection manifolds **26** being plumbed together using a single fuel drain line **16** and a single fuel sensor (not shown), a more complicated, expensive design of a unique double-walled common rail (accumulator) would be required to allow for use of a single fuel sensor. Furthermore, the single-walled common rail **12** is compliant with requirements such as SOLAS, because a common rail is considered by marine agencies to be substantial fuel system component (i.e., not a fuel line), and thus it is not required for

the common rail **12** to be double-walled. Additionally, embodiments consistent with the disclosure allow use of a single fuel sensor to detect a fuel leak from any of the inner walls of the bank of plural fuel injection lines.

In an exemplary embodiment described above, the fuel drain line **16** is a single tube structure including banjo connectors. However, the low pressure nature of the leaking fuel allows for embodiments having another configuration. For example, a fuel drain line can include plural sections (not shown) attached by compression fittings, for example, between a tee plumbing fitting or flexible lines having compression fitting at each end that mate with complementary fittings on one of opposite sides of a fuel collection manifold **26**.

While an exemplary embodiment is described in the context of a marine internal combustion engine, for example, high horsepower diesel fuel systems, the same concepts can be applied to other applications of internal combustion engines, such as those used in wheeled vehicles, construction equipment, standby generators etc. Further, embodiments of the fuel system described herein can be used in applications including any type of internal combustion engine cylinder bank configuration, such as in-line, v-type or horizontally opposed. Additionally, the system described herein can be used to contain and detect leaks of fluids in applications using fluids other than fuels, where the fluids are stored at high pressure in an accumulator to be distributed to double walled lines.

Although a limited number of embodiments is described herein, one of ordinary skill in the art will readily recognize that there could be variations to any of these embodiments and those variations would be within the scope of the appended claims. Thus, it will be apparent to those skilled in the art that various changes and modifications can be made to the common rail fuel system with leak containment and detection described herein without departing from the scope of any appended claim and its equivalents.

What is claimed is:

1. A fuel system for supplying fuel to an internal combustion engine, comprising:

a single-walled high pressure common rail including a main body and plural members extending from the main body, each member having a high pressure passage leading to the main body;

plural double-walled fuel line segments adapted to fluidly connect the high pressure passages of the single-walled high pressure common rail to respective plural fuel injectors, each said segment including a high pressure fuel line, a jacket surrounding the high pressure fuel line, a low pressure passage between the high pressure fuel line and the jacket, and a fuel line connector housing a portion of the high pressure fuel line such that an end portion of the high pressure fuel line protrudes from a first end of the fuel line connector and a second end of the fuel line connector is sealingly connected to the jacket to thereby extend the low pressure passage into the fuel line connector;

plural leakage drain connectors coupled to an outer surface of the fuel line connector, each said leakage drain connector sealingly connected at a first end portion thereof to one of the members and sealingly connected at a second end portion thereof to one of the plural fuel line connectors, such that the protruding end portion of the high pressure fuel line sealingly engages with the high pressure passage of the member and the low pressure passage of the fuel line connector extends through the

leakage drain connector to an opening at an outer surface of the leakage drain connector; and
a fuel drain line fluidly coupled to each of said openings of the plural leakage drain connectors.

2. The internal combustion engine of claim **1**, further comprising plural fuel collection manifolds, each said fuel collection manifold provided around a respective one of the leakage drain connectors and comprising: an outer surface; and a channel fluidly connecting the opening at an outer surface of the leakage drain connector to the outer surface of the fuel collection manifold such that the low pressure passage in the leakage drain connector extends to the outer surface of the fuel collection manifold.

3. The internal combustion engine of claim **2**, wherein each said fuel collection manifold is detachably and sealingly engaged with the respective leakage drain connector.

4. The fuel system of claim **3**, wherein each said fuel collection manifold is rotatable about the leakage drain connector to which it is sealingly engaged.

5. The fuel system of claim **1**, wherein the fuel drain line extends the low pressure passage from the plural leakage drain connectors and is fluidly coupled to a fuel leakage detector.

6. The fuel system of claim **5**, further comprising an alarm triggerable with detection of a fuel leak in the low pressure passage by the fuel detector.

7. The fuel system of claim **1**, wherein each fuel line connector includes a spacer supporting a portion of the high pressure fuel line including the protruding end, said spacer including at least one passage through which the low pressure passage in the fuel line connector extends into the leakage drain connector.

8. An internal combustion engine, comprising:

a plurality of cylinders;

plural fuel injectors, each said cylinder associated with one of the fuel injectors;

a single-walled high pressure common rail including a main body and plural members extending from the main body, each member having a high pressure passage leading to the main body;

plural double-walled fuel line segments, each said segment having a high pressure fuel line, a jacket surrounding the high pressure fuel line portion, a low pressure passage between the high pressure fuel line and the jacket, a first end fluidly connected to a respective one of the fuel injectors, and a fuel line connector including a main body housing a portion of the high pressure fuel line such that an end portion of the high pressure fuel line protrudes from a first end of the main body and a second end of the main body is sealingly connected to the jacket to thereby extend the low pressure passage into the fuel line connector;

plural leakage drain connectors, a portion of each leakage drain connector being positioned longitudinally intermediate a respective one of the fuel line connectors and a respective one of the plural members of the single-walled high pressure common rail, and each said leakage drain connector sealingly connected at a first end portion thereof to one of the members and sealingly connected at a second end portion thereof to one of the plural fuel line connectors, such that the protruding end portion of the high pressure fuel line sealingly engages with the high pressure passage of the member and the low pressure passage of the fuel line connector extends through the leakage drain connector to an opening at an outer surface of the leakage drain connector; and

9

a fuel drain line fluidly coupled to each of said openings of the plural leakage drain connectors.

9. The internal combustion engine of claim 8, further comprising plural fuel collection manifolds, each said fuel collection manifold is provided around a respective one of the leakage drain connectors and comprising: an outer surface; and a channel connecting the opening at the outer surface of the leakage drain connector to the outer surface of the fuel collection manifold such that the low pressure passage in the leakage drain connector extends to the outer surface of the fuel collection manifold.

10. The internal combustion engine of claim 9, wherein each said fuel collection manifold is detachably and sealingly engaged with the respective leakage drain connector.

11. The internal combustion engine of claim 10, wherein each said fuel collection manifold is rotatable about the leakage drain connector to which it is sealingly engaged.

12. The internal combustion engine of claim 8, wherein the fuel drain line forms an extension of low pressure passage from the plural leakage drain connectors and is fluidly coupled to a fuel leakage detector.

13. The internal combustion engine of claim 12, further comprising an alarm triggerable with detection of a fuel leak in the low pressure passage by the fuel detector.

14. The fuel system of claim 8, wherein each fuel line connector includes a spacer supporting the protruding end portion of the high pressure fuel line, said spacer including at least one passage through which the low pressure passage in the fuel line connector extends into the leakage drain connector.

15. A connector for connecting a single-walled high pressure common rail to a double-walled fuel line, said connector comprising:

a main body comprising:

a first opening substantially aligned along a longitudinal axis of the main body and configured to sealingly attach to a member extending from a single-walled high pressure common rail;

a second opening opposite the first opening and configured to sealingly attach to a connector of a double-walled high pressure fuel line such that the high pressure portion of the double-walled fuel line seals with the member to form a continuous high pressure passage; and

at least one third opening that opens toward a direction substantially orthogonal to the longitudinal axis; and a fuel collection manifold around the main body and having a channel between the third opening and an outer surface of the fuel collection manifold such that a low pressure passage for fuel leaking from the double-walled fuel line extends from the channel through the third opening.

16. The connector of claim 15, wherein the fuel collection manifold is integrally formed with the main body.

17. The connector of claim 15, wherein the fuel collection manifold is rotatable about the longitudinal axis.

18. The connector of claim 15, wherein the fuel collection manifold is detachably connected to the main body and has an inner surface, said inner surface sealingly positioned about an outer surface of the main body.

10

19. The connector of claim 18, wherein the fuel collection manifold is attachable to the main body by inserting the main body into an opening in the fuel collection manifold, said main body including a stop preventing insertion of the main body beyond a predetermined position, and the fuel collection manifold including a profile feature positioned on an outer surface of the main body for attaching a retaining mechanism that locks the fuel collection manifold substantially at said predetermined position.

20. A leak containment system, comprising:

a single-walled high pressure accumulator including a high pressure cavity;

a double-walled line including a high pressure line, a jacket surrounding the high pressure line, an annular region between the high pressure line and the jacket, and a line connector housing a portion of the double-walled line and configured to fluidly attach the double-walled line to the single-walled high pressure accumulator;

a drain line;

a leakage drain connector having a first end sealingly attached to the single-walled high pressure accumulator, a second end sealingly attached to the line connector, and a side portion fluidly connected to the leakage drain line, said leakage drain connector housing a portion of the high pressure line;

a leakage detector fluidly coupled to the drain line;

a continuous high pressure passage including the high pressure cavity fluidly connected to the high pressure line; and

a continuous low pressure passage including the annular region, the drain line, and interior regions of the leakage drain connector and the line connector outside the housed high pressure line.

21. The fuel system of claim 1, wherein each of the fuel line connectors of the double-walled fuel line segments is spaced apart from each of the plural members of the single-walled high pressure common rail.

22. The fuel system of claim 20, wherein the leakage drain connector is coupled to an outer surface of the line connector.

23. The fuel system of claim 1, wherein the plural members are integral with the main body of the single-walled high pressure common rail.

24. The fuel system of claim 1, further comprising plural fuel collection manifolds coupled to an outer surface of respective leakage drain connectors, and a first end of each leakage drain connector is coupled to a respective one of the plural members and extends outwardly from a respective one of the fuel collection manifolds, and a second end of each leakage drain connector is coupled to a respective one of the fuel line connectors and extends outwardly from the respective one of the fuel collection manifolds.

25. The fuel system of claim 1, wherein each leakage drain connector has a first opening at a first end to receive a respective one of the plural members, a second opening at a second end to receive a respective one of the fuel line segments, and a third opening intermediate the first and second openings.

26. The fuel system of claim 25, wherein the third opening of each leakage drain connector is fluidly coupled to the fuel drain line.

* * * * *