



US009055649B2

(12) **United States Patent**
Chen et al.

(10) **Patent No.:** **US 9,055,649 B2**
(45) **Date of Patent:** **Jun. 9, 2015**

(54) **CONTROL CIRCUIT AND CONTROL METHOD OF LIGHT EMITTING DEVICE CIRCUIT**

(52) **U.S. Cl.**
CPC *H05B 33/089* (2013.01); *H05B 33/0803* (2013.01)

(71) Applicants: **Pei-Yuan Chen**, Taoyuan (TW); **Yu-Min Chen**, Taoyuan (TW); **Leng-Nien Hsiu**, Zhubei (TW)

(58) **Field of Classification Search**
None
See application file for complete search history.

(72) Inventors: **Pei-Yuan Chen**, Taoyuan (TW); **Yu-Min Chen**, Taoyuan (TW); **Leng-Nien Hsiu**, Zhubei (TW)

(56) **References Cited**

U.S. PATENT DOCUMENTS

(73) Assignee: **Richtek Technology Corporation**, Chupei, HsinChu (TW)

8,836,241 B2 * 9/2014 Shiu et al. 315/307
2011/0080110 A1 * 4/2011 Nuhfer et al. 315/291
2011/0248637 A1 * 10/2011 Mitsuyasu et al. 315/178
2014/0091714 A1 * 4/2014 Sutardja et al. 315/122

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 182 days.

* cited by examiner

Primary Examiner — Cassandra Cox
(74) *Attorney, Agent, or Firm* — Tung & Associates

(21) Appl. No.: **13/974,914**

(57) **ABSTRACT**

(22) Filed: **Aug. 23, 2013**

The present invention discloses a control circuit and a control method of a light emitting device circuit. When the light emitting device circuit is normally connected in normal operation, an output current is regulated to a predetermined current. When the light emitting device circuit is removed, an output voltage is regulated to a predetermined voltage. When the light emitting device circuit is reconnected, the output current is regulated to the predetermined current. The output voltage is at or above a level when the light emitting device circuit is normally connected in normal operation, and the predetermined voltage is lower than this level.

(65) **Prior Publication Data**


US 2014/0077703 A1 Mar. 20, 2014

Related U.S. Application Data

(60) Provisional application No. 61/703,208, filed on Sep. 19, 2012.

(51) **Int. Cl.**
H05B 37/00 (2006.01)
H05B 33/08 (2006.01)

12 Claims, 6 Drawing Sheets






Fig. 1 (Prior Art)




Fig. 2A




Fig. 2B




Fig. 2C




Fig. 2D




Fig. 2E




Fig. 2F




Fig. 2G




Fig. 2H




Fig. 2I




Fig. 2J




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10

1

CONTROL CIRCUIT AND CONTROL METHOD OF LIGHT EMITTING DEVICE CIRCUIT

CROSS REFERENCE

The present invention claims priority to U.S. 61/703208, filed on Sep. 19, 2012.

BACKGROUND OF THE INVENTION

1. Field of Invention

The present invention relates to a control circuit and a control method of a light emitting device circuit; particularly, it relates to such control circuit and control method with a hot swapping protection function.

2. Description of Related Art

FIG. 1 shows a schematic diagram of a prior art light emitting diode (LED) power control circuit **100**. As shown in FIG. 1, the LED power control circuit **100** controls an LED circuit **10**. The LED power control circuit **100** includes a control circuit **110**, a power stage circuit **120**, and a current sense circuit **130**. The control circuit **110** is connected to the current sense circuit **130** to receive a current feedback signal FB. The control circuit **110** generates a control signal GATE according to the current feedback signal FB, to control a power switch of the power stage circuit **120** accordingly such that an input voltage V_{in} is converted to an output voltage V_{out} , and an output current is provided to the LED circuit **10**. VCC is a power supply voltage of the control circuit **110**, and GND is a ground level of the circuitry. The power stage circuit **120** may be a synchronous or asynchronous buck, boost, inverting, buck-boost, or inverting-boost power stage circuit as shown in FIGS. 2A-2J.

In normal operation, the LED power control circuit **100** regulates the output current at a fixed predetermined current. When the LED circuit **10** is suddenly removed during the normal operation without shutting down the LED power control circuit **100**, the control circuit **110** will continue trying to regulate the output current at the fixed determined current, causing not only unnecessary power consumption but also serious danger because the output voltage V_{out} may rise to a dangerous level. At such dangerous level of the output voltage V_{out} , if the LED circuit **10** is reconnected to the power stage circuit **120**, an instant surge current may be generated, which may damage circuit devices and shorten lifetime of the circuitry.

In view of above, the present invention proposes a control circuit and a control method of a light emitting device circuit with hot swapping protection function ("hot swapping" meaning to remove and/or reconnect an LED circuit while power ON).

SUMMARY OF THE INVENTION

From one perspective, the present invention provides a control method of a light emitting device circuit, wherein the light emitting device circuit is coupled to a power stage circuit in normal operation, and the power stage circuit converts an input voltage to an output voltage according to a control signal, to provide an output current to the light emitting device circuit when the light emitting device circuit is in normal operation, the control method comprising: when the light emitting device circuit is normally connected in normal operation, performing current regulation to regulate the output current to a predetermined current, wherein the output current is a controlled object; when the light emitting device

2

circuit is removed (a removal condition) during normal operation, generating a hot swapping signal indicating the removal condition; after generating the hot swapping signal indicating the removal condition, switching the controlled object to the output voltage, and performing voltage regulation to regulate the output voltage to a predetermined voltage, wherein the output voltage is the controlled object; when the light emitting device circuit is reconnected (a reconnection condition) in the removal condition, generating a hot swapping signal indicating the reconnection condition; and after generating the hot swapping signal indicating the reconnection condition, switching the controlled object to the output current, and performing current regulation to regulate the output voltage to the predetermined current, wherein the output current is the controlled object.

In one preferable embodiment, the hot swapping signal indicating the reconnection condition is generated when the output current is not zero for a predetermined period of time after the light emitting device circuit is reconnected.

In one preferable embodiment, the hot swapping signal indicating the removal condition and the hot swapping signal indicating the reconnection condition are generated according to a signal related to the output voltage and/or a signal related to the output current.

In one preferable embodiment, the step of generating the hot swapping signal indicating the removal condition includes: comparing the output voltage with a removal reference signal; and the step of generating the hot swapping signal indicating the reconnection condition includes: comparing the output voltage with a reconnection reference signal.

In one preferable embodiment, the step of generating the hot swapping signal indicating the removal condition includes: determining whether to generate the hot swapping signal indicating the removal condition according to whether the output current is zero; and the step of generating the hot swapping signal indicating the reconnection condition includes: determining whether to generate the hot swapping signal indicating the reconnection condition according to whether the output current is no longer zero after the output current is zero.

In one preferable embodiment, the predetermined voltage is lower than a normal operating level of the output voltage when the light emitting device circuit is in the normal operation and normally connected.

From another perspective, the present invention provides a control circuit of a light emitting device circuit for generating a control signal to control a power stage circuit such that an input voltage is converted to an output voltage, and in normal operation, an output current is provided to the light emitting device circuit, the control circuit comprising: a determination circuit, for determining whether the light emitting device circuit is normally connected or is removed in normal operation, and for generating a hot swapping signal indicating whether the light emitting device circuit is normally connected or is removed; and a control signal generation circuit, which is coupled to the determination circuit, wherein when the hot swapping signal indicates that the light emitting device circuit is normally connected, the control signal generation circuit generates the control signal according to a voltage feedback signal related to the output voltage, so as to regulate the output voltage at a predetermined voltage, and when the hot swapping signal indicates that the light emitting device circuit is removed, the control signal generation circuit generates the control signal according to a current feedback signal related to the output current, so as to regulate the output current at a predetermined current.

In one preferable embodiment, the determination circuit generates the hot swapping signal according to a signal related to the output voltage and/or a signal related to the output current.

In another preferable embodiment, the determination circuit includes: a first comparator circuit for comparing the signal related to the output voltage with a removal reference signal; and a second comparator circuit for comparing the signal related to the output voltage with a reconnection reference signal.

In another preferable embodiment, the control signal generation circuit includes: a first error amplifier circuit, for comparing the current feedback signal with a current reference signal to generate a first output; a second error amplifier circuit, for comparing the voltage feedback signal with a voltage reference signal to generate a second output; and a pulse signal generation circuit, which is coupled to the first error amplifier circuit and the second error amplifier circuit, for comparing the first output or the second output with a saw-tooth waveform signal, to generate a pulse width modulation signal with a fixed frequency or a fixed pulse width signal with a variable frequency as the control signal.

In another preferable embodiment, the first output of the first error amplifier circuit and the second output of the second error amplifier circuit are coupled to a common node and the pulse signal generation circuit is coupled to the common node, wherein the voltage of the common node is determined by a higher one of the first output and the second output.

In another preferable embodiment, the predetermined voltage is lower than a normal operating level of the output voltage when the light emitting device circuit is in the normal operation and normally connected.

The objectives, technical details, features, and effects of the present invention will be better understood with regard to the detailed description of the embodiments below.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 shows a schematic diagram of a prior art light emitting diode (LED) power control circuit 100.

FIGS. 2A-2J show synchronous and asynchronous buck, boost, inverting, buck-boost, and inverting-boost power stage circuits.

FIG. 3 shows a first embodiment of the present invention.

FIG. 4 shows a second embodiment of the present invention.

FIG. 5 shows a third embodiment of the present invention.

FIG. 6 shows a fourth embodiment of the present invention.

FIG. 7 shows signal waveforms of the input voltage V_{in} , the output voltage V_{out} , and the output current I_{out} .

FIG. 8 shows a fifth embodiment of the present invention.

FIG. 9 shows a sixth embodiment of the present invention.

FIG. 10 shows a seventh embodiment of the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Please refer to FIG. 3 for a first embodiment according to the present invention. As shown in FIG. 3, in an LED power control circuit 200, a control circuit 210 generates a control signal GATE according to a current feedback signal FB in normal operation to feedback control the power stage circuit 220. A power switch Q1 of the power stage circuit 220 operates according to the control signal GATE to convert an input voltage V_{in} to an output voltage V_{out} , and to provide an output current I_{out} to the LED circuit 10. The power stage circuit 220

is for example but not limited to the buck power stage circuit as shown in FIG. 3. The power stage circuit 220 may also be the synchronous or asynchronous buck, boost, inverting, buck-boost, or inverting-boost power stage circuit as shown in FIGS. 2A-2J. The LED circuit 10 is not limited to a single LED string as shown in the figure, but may include plural light emitting device strings connected in parallel. The current feedback signal FB is generated by for example but not limited to a current sense circuit 230 which is coupled to the LED circuit 10. In this embodiment, because the current feedback signal FB is relative to the input voltage V_{in} , the control circuit 210 needs to obtain information related to the input voltage. In one preferable embodiment, the power supply VCC of the control circuit 210 is the input voltage V_{in} , such that the control circuit may obtain both electric power and information related to the input voltage. The output current I_{out} is regulated at for example but not limited to a predetermined current, such that a stable current may be provided to the LED circuit 10. This embodiment is different from the prior art LED power control circuit 100 in that, the LED power control circuit 200 further includes an output voltage sense circuit 250 for generating an over voltage protection signal OVP which is received by the control circuit 210, to determine whether the LED circuit 10 is normally connected or is removed during normal operation. When the LED circuit 10 is removed during normal operation, the LED power control circuit 200 adjusts the control signal GATE according to the over voltage protection signal (OVP), such that the LED power control circuit 200 enters a constant voltage control mode wherein the output voltage V_{out} is regulated at a predetermined relatively lower level. Therefore, after the LED circuit 10 is removed in the normal operation, the power consumption can be reduced, and the surge current caused by the reconnection of the LED circuit 10 can also be reduced because of the relatively lower voltage level. More specific embodiments of the control circuit 210 will be described in details later.

FIG. 4 shows a second embodiment of the present invention. As shown in FIG. 4, the control circuit 210 of an LED power control circuit 300 generates the control signal GATE according to the current feedback signal FB, and feedback controls a power stage circuit 320. The control circuit 210 generates the control signal GATE, controlling a power switch Q2 of the power stage circuit 320 to convert an input voltage V_{in} to an output voltage V_{out} , and provide an output current I_{out} to the LED circuit 10. This embodiment is different from the first embodiment in that, the power stage circuit 320 is for example the boost power stage circuit as shown in the figure, which shows that the present invention is not limited to the power stage circuit 220 as the first embodiment. The power stage circuit 320 may also be the synchronous or asynchronous buck, boost, inverting, buck-boost, or inverting-boost power stage circuit as shown in FIGS. 2A-2J. Besides, in this embodiment, the current feedback signal FB may be generated by for example a current sense circuit 330 which is connected to a reverse terminal of the LED circuit 10 in series, instead of the current sense circuit 230 which is connected to a forward terminal of the LED circuit 10 in series. Because the current sense signal FB in this embodiment is relative to ground level, the control circuit 210 does not need to obtain information related to the input voltage, and the power supply VCC of the control circuit 310 does not need to be the input voltage V_{in} , but may be another power source.

FIG. 5 shows a third embodiment of the present invention. This embodiment shows a specific embodiment of the control circuit 210. As shown in FIG. 5, the control circuit 210

5

includes a determination circuit **2101**, a selection circuit **2102**, and a control signal generation circuit **2103**. When the LED circuit **10** is normally connected during normal operation, the control signal generation circuit **2103** generates the control signal GATE according to the current feedback signal, i.e., in this condition, the LED power control circuit **200** or **300** enters a constant current control mode and performs current feedback control to regulate the output current at the predetermined current. The current feedback signal may be the current feedback signal FB or its related signal. When the LED circuit **10** is removed during normal operation, referring to FIGS. **3** and **4**, because the output current I_{out} can not flow through the LED circuit **10** and charges are accumulated at the output terminal, the output voltage V_{out} keeps increasing. The over voltage protection signal OVP is a signal related to the output voltage V_{out} , and the determination circuit **2101** determines whether the output voltage V_{out} is too high according to the over voltage protection signal OVP. When the determination circuit **2101** determines that the output voltage V_{out} is too high according to the over voltage protection signal OVP, the determination circuit **2101** generates a hot swapping signal to indicate a removal condition of the LED circuit **10**, such that the selection circuit **2102** selects the voltage feedback signal instead of the current feedback signal, and the control signal generation circuit **2103** generates the control signal GATE according to the voltage feedback signal instead of the current feedback signal, i.e., in this condition, the LED power control circuit **200** or **300** enters the constant voltage control mode and performs voltage feedback control to regulate the output voltage at a predetermined voltage. The predetermined voltage may be a safe level which will not endanger a human body and the circuitry, and at such level the LED power control circuit **200** or **300** will not consume high power but only maintains its basic operation, such that when the LED circuit **10** is reconnected, the LED power control circuit **200** or **300** can resume normal operation quickly. The voltage feedback signal for example may be the over voltage protection signal OVP or its related signal. The safety level for example may be a level lower than the normal operating level of the output voltage (i.e., the level of the output voltage when the light emitting device circuit is normally connected in normal operation (to be discussed later with reference to FIG. **7**)).

When the LED circuit **10** is reconnected after it is removed, the hot swapping signal generated by the determination circuit **2101** indicates the connection. Because the output voltage V_{out} is regulated at a safe predetermined level (the predetermined voltage) in the LED removal condition, the instant surge current will not be too large when the LED circuit **10** is reconnected. Besides, the LED power control circuit can resume normal operation quickly when the LED circuit **10** is reconnected because the circuit keeps operating in the LED removal condition. A current path is formed when the LED circuit **10** is reconnected, such that the output voltage V_{out} decreases because of the current flowing through the LED circuit **10**. The determination circuit **2101** determines that the LED circuit **10** is reconnected according to the over voltage protection signal OVP, and generates the hot swapping signal indicating such reconnection such that the selection circuit **2102** selects the current feedback signal as the input to the control signal generation circuit **2103**. The control signal generation circuit **2103** generates the control signal GATE according to the current feedback signal, i.e., the operation mode is changed to the constant current control mode (normal operation) from the constant voltage control mode (LED removal condition), and the output current I_{out} is regulated at the predetermined current.

6

FIG. **6** shows a fourth embodiment of the present invention. This embodiment shows a more specific embodiment of the determination circuit **2101**. As shown in FIG. **6**, in this embodiment, the determination circuit **2101** includes comparator circuits **2104** and **2105**, and a logic circuit **2106**. The comparator circuit **2104** compares the over voltage protection signal OVP with a removal reference signal V_{ref1} , to determine whether the output voltage V_{out} exceeds a high level, which indicates that the LED circuit **10** is removed. The comparator circuit **2105** compares the over voltage protection signal OVP with a reconnection reference signal V_{ref2} , to determine whether the output voltage V_{out} is below a low level, which indicates that the LED circuit **10** is reconnected. The logic circuit **2106** may be designed accordingly. In another embodiment, the logic circuit **2106** may be omitted, and the hot swapping signal can be a multi-digit signal.

FIG. **7** shows signal waveforms of the input voltage V_{in} , the output voltage V_{out} , and the output current I_{out} . As shown in FIG. **7**, when the circuitry starts operation, the input voltage V_{in} and the output voltage V_{out} increase, and the LED power control circuit regulates the output current I_{out} at the predetermined current; in this period, the output current is the controlled object. At time point T_1 , the LED circuit is removed and the output current I_{out} drops to zero; the output voltage V_{out} begins increasing from this time point. At time point T_2 , the output voltage V_{out} exceeds a threshold (referring to FIG. **6** of the fourth embodiment, the over voltage protection signal OVP exceeds the removal reference signal V_{ref1}), such that the hot swapping signal indicating the LED removal condition is generated. The LED power control circuit enters the constant voltage control mode at time point T_2 , and it is the output voltage V_{out} instead of the output current I_{out} that is to be regulated (i.e., in the period after time point T_2 , the output voltage is the controlled object). At time point T_3 , the output voltage V_{out} is controlled and stabilized at the predetermined voltage which has a relatively lower level.

The LED circuit is reconnected at time point T_4 . When the LED circuit is reconnected, the output voltage V_{out} drops (referring to FIG. **6** of the fourth embodiment, the over voltage protection signal OVP is lower than the reconnection reference signal V_{ref2}), and the output current I_{out} increases because of the instant surge current. In one embodiment, the hot swapping signal indicating the reconnection may be generated at this time point T_4 . In the present embodiment, the hot swapping signal is generated after it is confirmed that the output current I_{out} is not zero for a predetermined period of time after the light emitting device circuit is reconnected (i.e., after time point T_4 , there is a predetermined period of time for confirmation, so the hot swapping signal indicating reconnection is generated at time point T_5). For confirming that the output current I_{out} is not zero, the determination circuit **2101** needs to obtain information related to the output current I_{out} , and in this case the determination circuit **2101** can be embodied as shown in FIG. **9**. The LED power control circuit then enters the constant current control mode at time point T_5 , and it is the output current I_{out} instead of the output voltage V_{out} that is to be regulated (i.e., in the period after time point T_5 , the output current is the controlled object). At time point T_6 , the output current I_{out} is controlled and stabilized at the predetermined current.

In the aforementioned embodiments, the hot swapping signal is generated according to the over voltage protection signal, but the present invention is not limited to that. Note that, according to the present invention, the hot swapping signal can be generated according to any signal related to the output voltage (including but not limited to the output voltage itself) and/or any signal related to the output current (includ-

ing but not limited to the output current itself). For example, the hot swapping signal indicating the LED removal condition may be generated when the output current drops to zero during normal operation (but not so during the start-up stage, i.e., such determination may be disregarded in the start-up stage), and the hot swapping signal indicating reconnection may be generated when the output current is no more zero in the LED removal condition. In this example, the determination circuit **2101** needs to obtain information related to the output current instead of the information related to the output voltage, as shown by the embodiment in FIG. **8**.

In the third embodiment shown in FIG. **5**, the selection circuit **2102** is shown for explaining the concept of the present invention; in actual implementation of the concept, the selection circuit **2102** may be omitted, or does not need to be a physical circuit or device. For example, FIG. **10** shows a seventh embodiment of the present invention. In this embodiment, the control signal generation circuit **2103** includes an error amplifier circuits **2107** and **2108**, and a pulse signal generation circuit **2109**. The error amplifier circuit **2107** compares the current feedback signal FB with a current reference signal Vref3, and the error amplifier circuit **2108** compares the over voltage protection signal OVP with a voltage reference signal Vref4. By proper arrangement of the current reference signal Vref3, the voltage reference signal Vref4, the ratio of the current feedback signal FB to the output current Iout, and the ratio of the over voltage protection signal OVP to the output voltage Vout, it can be thus arranged that the output of the error amplifier circuit **2107** is higher than the output of the error amplifier circuit **2108** when the LED circuit **10** is normally connected in normal operation, and the output of the error amplifier circuit **2108** is higher than the output of the error amplifier circuit **2107** when the LED circuit **10** removed. Thus, the voltage at the node N is determined by a higher one between the outputs of the error amplifier circuits **2107** and **2108**, or from another perspective, the node N may be considered as an embodiment of the selection circuit, because it provides a function of selection (selecting the higher voltage).

There are various embodiments of the pulse signal generation circuit **2109**. For example, the pulse signal generation circuit **2109** can compare a signal at the node N with a sawtooth waveform, to generate a pulse width modulation signal with a fixed frequency or a fixed pulse width signal with a variable frequency as the control signal GATE. The control signal GATE, which is generated by the pulse signal generation circuit **2109**, maybe adjusted according to the hot swapping signal. For example, the pulse signal generation may stop for a period of time according to the hot swapping signal indicating the LED removal condition, such that the output voltage Vout decreases rapidly.

The present invention has been described in considerable detail with reference to certain preferred embodiments thereof. It should be understood that the description is for illustrative purpose, not for limiting the scope of the present invention. Those skilled in this art can readily conceive variations and modifications within the spirit of the present invention. For example, a device or circuit which does not substantially influence the primary function of a signal can be inserted between any two devices or circuits in the shown embodiments, such as a switch or the like, so the term. "couple" should include direct and indirect connections. For another example, a light emitting device is not limited to the LED as shown in the embodiments of the present, but the light emitting device may be any light emitting device driven by current. For another example, the meanings of the high and low levels of a digital signal are interchangeable, with corre-

sponding amendment of the circuits processing these signals. For another example, the positive and negative input terminals of the comparator circuits are interchangeable, with corresponding amendment of the circuits processing these signals. In view of the foregoing, the spirit of the present invention should cover all such and other modifications and variations, which should be interpreted to fall within the scope of the following claims and their equivalents.

What is claimed is:

1. A control method of a light emitting device circuit, wherein the light emitting device circuit is coupled to a power stage circuit in normal operation, and the power stage circuit converts an input voltage to an output voltage according to a control signal, to provide an output current to the light emitting device circuit when the light emitting device circuit is in normal operation, the control method comprising:

when the light emitting device circuit is normally connected in normal operation, performing current regulation to regulate the output current to a predetermined current, wherein the output current is a controlled object; when the light emitting device circuit is removed (a removal condition) during normal operation, generating a hot swapping signal indicating the removal condition; after generating the hot swapping signal indicating the removal condition, switching the controlled object to the output voltage, and performing voltage regulation to regulate the output voltage to a predetermined voltage, wherein the output voltage is the controlled object;

when the light emitting device circuit is reconnected (a reconnection condition) in the removal condition, generating a hot swapping signal indicating the reconnection condition; and

after generating the hot swapping signal indicating the reconnection condition, switching the controlled object to the output current, and performing current regulation to regulate the output voltage to the predetermined current, wherein the output current is the controlled object.

2. The control method of claim **1**, wherein the hot swapping signal indicating the reconnection condition is generated when the output current is not zero for a predetermined period of time after the light emitting device circuit is reconnected.

3. The control method of claim **1**, wherein the hot swapping signal indicating the removal condition and the hot swapping signal indicating the reconnection condition are generated according to a signal related to the output voltage and/or a signal related to the output current.

4. The control method of claim **1**, wherein the step of generating the hot swapping signal indicating the removal condition includes: comparing the output voltage with a removal reference signal; and the step of generating the hot swapping signal indicating the reconnection condition includes: comparing the output voltage with a reconnection reference signal.

5. The control method of claim **1**, wherein the step of generating the hot swapping signal indicating the removal condition includes: determining whether to generate the hot swapping signal indicating the removal condition according to whether the output current is zero; and the step of generating the hot swapping signal indicating the reconnection condition includes: determining whether to generate the hot swapping signal indicating the reconnection condition according to whether the output current is no longer zero after the output current is zero.

6. The control method of claim **1**, wherein the predetermined voltage is lower than a normal operating level of the output voltage when the light emitting device circuit is in the normal operation and normally connected.

9

7. A control circuit of a light emitting device circuit, for generating a control signal to control a power stage circuit such that an input voltage is converted to an output voltage, and in normal operation, an output current is provided to the light emitting device circuit, the control circuit comprising:

a determination circuit, for determining whether the light emitting device circuit is normally connected or is removed in normal operation, and for generating a hot swapping signal indicating whether the light emitting device circuit is normally connected or is removed; and
 a control signal generation circuit, which is coupled to the determination circuit, wherein when the hot swapping signal indicates that the light emitting device circuit is normally connected, the control signal generation circuit generates the control signal according to a voltage feedback signal related to the output voltage, so as to regulate the output voltage at a predetermined voltage, and when the hot swapping signal indicates that the light emitting device circuit is removed, the control signal generation circuit generates the control signal according to a current feedback signal related to the output current, so as to regulate the output current at a predetermined current.

8. The control circuit of claim 7, wherein the determination circuit generates the hot swapping signal according to a signal related to the output voltage and/or a signal related to the output current.

9. The control circuit of claim 8, wherein the determination circuit includes:

a first comparator circuit for comparing the signal related to the output voltage with a removal reference signal; and

10

a second comparator circuit for comparing the signal related to the output voltage with a reconnection reference signal.

10. The control circuit of claim 7, wherein the control signal generation circuit includes:

a first error amplifier circuit, for comparing the current feedback signal with a current reference signal to generate a first output;

a second error amplifier circuit, for comparing the voltage feedback signal with a voltage reference signal to generate a second output; and

a pulse signal generation circuit, which is coupled to the first error amplifier circuit and the second error amplifier circuit, for comparing the first output or the second output with a saw-tooth waveform signal, to generate a pulse width modulation signal with a fixed frequency or a fixed pulse width signal with a variable frequency as the control signal.

11. The control circuit of claim 10, wherein the first output of the first error amplifier circuit and the second output of the second error amplifier circuit are coupled to a common node and the pulse signal generation circuit is coupled to the common node, wherein the voltage of the common node is determined by a higher one of the first output and the second output.

12. The control circuit of claim 7, wherein the predetermined voltage is lower than a normal operating level of the output voltage when the light emitting device circuit is in the normal operation and normally connected.

* * * * *