

US009066783B2

(12) United States Patent

Euteneuer et al.

(54) METHODS AND APPARATUS FOR TREATING GLAUCOMA

(71) Applicant: Ivantis, Inc., Irvine, CA (US)

(72) Inventors: Charles L. Euteneuer, St. Michael, MN

(US); Thomas R. Hektner, Medina, MN (US); Andrew T. Schieber, Irvine, CA

(US); John Wardle, San Clemente, CA

(US)

(73) Assignee: IVANTIS, INC., Irvine, CA (US)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

(21) Appl. No.: 13/968,051

(22) Filed: Aug. 15, 2013

(65) Prior Publication Data

US 2013/0331761 A1 Dec. 12, 2013

Related U.S. Application Data

- (60) Division of application No. 13/610,769, filed on Sep. 11, 2012, now Pat. No. 8,529,494, which is a continuation of application No. 12/398,847, filed on Mar. 5, 2009, now Pat. No. 8,267,882.
- (60) Provisional application No. 61/034,059, filed on Mar. 5, 2008.
- (51) Int. Cl.

 A61F 9/007 (2006.01)

 A61F 9/00 (2006.01)

 (Continued)
- (52) **U.S. Cl.**CPC ... *A61F 9/00781* (2013.01); *A61F 2009/00885* (2013.01); *A61F 9/0017* (2013.01); (Continued)
- (58) Field of Classification Search

 CPC A61F 9/00781; A61F 2/14; A61F 2/16;

 A61F 11/00; A61F 9/0017; A61F 2009/00891;

(10) Patent No.: US 9,066,783 B2 (45) Date of Patent: Jun. 30, 2015

See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

703,296 A 6/1902 Arnold 1,601,709 A 10/1926 Windom (Continued)

FOREIGN PATENT DOCUMENTS

AU 1998/76197 B2 2/1999 CN 1950091 A 4/2007 (Continued)

OTHER PUBLICATIONS

Bahler, et al.; Trabecular bypass stents decrease intraocular pressure in cultured human anterior segments; Amer. Journal of Ophthalmology; vol. 138, No. 6; pp. 988-994.e2; Dec. 2004.


(Continued)

Primary Examiner — Adam Marcetich (74) Attorney, Agent, or Firm — Shay Glenn LLP

(57) ABSTRACT

An ocular implant for treating glaucoma is provided, which may include any number of features. More particularly, the present invention relates to implants that facilitate the transfer of fluid from within one area of the eye to another area of the eye. One feature of the implant is that it includes a proximal inlet portion and a distal inlet portion adapted to be inserted into the anterior chamber of the eye, and an intermediate portion adapted to be inserted into Schlemm's canal. Another feature of the implant is that it can be biased to assume a predetermined shape to aid in placement within the eye.

18 Claims, 17 Drawing Sheets



US 9,066,783 B2 Page 2

(51)	Int. Cl.			6,328,747	R1	12/2001	Nun
(51)	A61F 9/008		(2006.01)	6,375,642			Grieshaber et al.
	A61K 9/00		(2006.01)	6,409,752			Boatman et al.
	A61M 27/00		(2006.01)	6,450,984			Lynch et al.
(52)	U.S. Cl.		(2000.01)	6,464,724 6,471,666		10/2002 10/2002	Lynch et al.
(52)		161K 0	/0051 (2013.01); Y10S 623/906	6,494,857			Neuhann
			A61M 27/002 (2013.01); Y10S	6,508,779		1/2003	
	`	7.	13.01); A61F 9/007 (2013.01);	6,517,523			Kaneko et al.
		`	91 (2013.01); A61M 2210/0612	6,524,275 6,533,764			Lynch et al. Haffner et al.
	21011 2	00270002	(2013.01), 1101111 2210, 0012 (2013.01)	6,533,768		3/2003	
			(2015.01)	6,544,208			Ethier et al.
(56)		Referen	ces Cited	6,544,249			Yu et al.
` /				6,551,289 6,626,858			Higuchi et al. Lynch et al.
	U.S.	PATENT	DOCUMENTS	6,638,239			Bergheim et al.
	2,716,983 A	0/1055	George et al.	6,666,841			Gharib et al.
	3,071,135 A		Baldwin et al.	6,699,210			Williams et al.
	3,788,327 A		Donowitz et al.	6,699,211 6,726,676			Savage Stegmann et al.
	3,811,442 A		Maroth	D490,152			Myall et al.
	3,948,271 A 4,037,604 A		Akiyama Newkirk	6,730,056			Ghaem et al.
	4,428,746 A		Mendez	6,736,791 6,780,164			Tu et al. Bergheim et al.
	4,457,757 A		Molteno	6,783,544			Lynch et al.
	4,601,713 A	7/1986	•	6,827,699			Lynch et al.
	4,689,040 A 4,699,140 A		Thompson Holmes et al.	6,827,700			Lynch et al.
	4,706,669 A		Schlegel	6,881,198 6,899,717		4/2005 5/2005	Brown Weber et al.
	4,722,724 A		Schocket	6,939,298			Brown et al.
	4,733,665 A 4,750,901 A		Palmaz Molteno	6,955,656	B2		Bergheim et al.
	4,730,901 A 4,826,478 A		Schocket	6,962,573		11/2005	
	4,861,341 A		Woodburn	6,981,958 6,989,007			Gharib et al. Shadduck
	4,880,000 A		Holmes et al.	7,094,225			Tu et al.
	4,886,488 A 4,919,130 A	12/1989 4/1990	Stoy et al.	7,135,009		11/2006	
	4,934,363 A		Smith et al.	7,147,650 7,163,543			Lee Smedley et al.
	4,934,809 A	6/1990		7,186,232			Smedley et al.
	4,936,825 A		Ungerleider	7,192,412			Zhou et al.
	4,946,436 A 4,968,296 A	8/1990 11/1990	Ritch et al.	7,207,965		4/2007	
	5,092,837 A		Ritch et al.	7,207,980 7,220,238			Christian et al. Lynch et al.
	5,127,901 A		Odrich	7,273,475			Tu et al.
	5,178,604 A 5,180,362 A	1/1993	Baerveldt et al. Worst	7,297,130			Bergheim et al.
	5,190,552 A		Kelman	7,331,984 7,699,882			Tu et al.
	5,213,569 A	5/1993		7,099,882			Stamper et al. Schieber et al.
	5,246,452 A		Sinnott Zimmermann	7,931,596			Rachlin et al.
	5,290,267 A 5,360,399 A		Stegmann	7,967,772			McKenzie et al.
	5,372,577 A		Ungerleider	8,012,115 8,034,105		_	Karageozian Stegmann et al.
	5,445,637 A	8/1995		8,123,729			Yamamoto et al.
	5,454,796 A 5,458,615 A	10/1995	Krupin Klemm et al.	8,172,899			Silvestrini et al.
	5,536,259 A		Utterberg	8,267,882 8,282,592			Euteneuer et al. Schieber et al.
	5,575,780 A	11/1996		8,337,509			Schieber et al.
	5,591,223 A 5,613,972 A		Lock et al. Lee et al.	8,372,026		2/2013	Schieber et al.
	5,626,558 A	5/1997		8,414,518			Schieber et al.
	5,653,753 A		Brady et al.	8,425,449 8,512,404			Wardle et al. Frion et al.
	5,676,669 A		Colvard	8,529,494			Euteneuer et al.
	5,792,099 A 5,807,302 A		DeCamp et al. Wandel	8,551,166			Schieber et al.
	5,865,831 A		Cozean et al.	8,945,038			Yablonski Stoomann et al
	5,868,697 A	2/1999	Richter et al.	2001/0002438			Stegmann et al. Sepetka et al.
	5,879,319 A		Pynson et al.	2002/0003546			Mochimaru et al.
	5,893,837 A 5,919,171 A *		Eagles et al. Kira et al 604/264	2002/0013546			Grieshaber et al.
	5,948,427 A		Yamamoto et al.	2002/0013572		1/2002	
	5,968,058 A	10/1999	Richter et al.	2002/0052653 2002/0072673			Durgin Yamamoto et al.
	6,007,511 A			2002/0072073			Smedley et al.
	6,050,970 A 6,102,045 A		Baerveldt Nordquist et al.	2002/0143284			Tu et al.
	, ,		Allan et al.	2002/0165504			Sharp et al.
	6,217,584 B1	4/2001	-	2002/0193805			Ott et al.
	6,221,078 B1 6,238,409 B1		Bylsma Hojeibane	2003/0004457 2003/0055372			Andersson Lynch et al.
	D444,874 S		Haffner et al.	2003/0053372			Baikoff
	,				-	- -	

US 9,066,783 B2 Page 3

(56)		Referen	ces Cited	2006/0173397			Tu et al.
	U.S.	PATENT	DOCUMENTS	2006/0178674 2006/0189915			McIntyre Camras et al.
	0.0.		DOCOMENTO	2006/0189916	A1	8/2006	Bas et al.
2003/0060752	2 A1	3/2003	Bergheim et al.	2006/0189917			Mayr et al.
2003/0060784			Hilgers et al.	2006/0195055			Bergheim et al.
2003/0093084			Nissan et al.	2006/0195056 2006/0195187			Bergheim et al. Stegmann et al.
2003/0097151 2003/0181848			Smedley et al. Bergheim et al.	2006/0200113			Haffner et al.
2003/0187384			Bergheim et al.	2006/0241749		10/2006	
2003/0229303			Haffner et al.	2006/0264971			Akahoshi
2003/0236483		12/2003		2006/0276759 2007/0010827			Kinast et al. Tu et al.
2003/0236484 2004/0024345			Lynch et al. Gharib et al.	2007/0010327			Varner et al.
2004/0024343			Castillejos	2007/0073275			Conston et al.
2004/0030302			Kamata et al.	2007/0088432			Solovay et al.
2004/0082939		4/2004		2007/0106200 2007/0106236		5/2007 5/2007	Levy Coroneo
2004/0088048 2004/0098124		_ ,	Richter et al. Freeman et al.	2007/0100230			Tu et al.
2004/009812-			Haffner et al.	2007/0118147			Smedley et al.
2004/0106975			Solovay et al.	2007/0135681			Chin et al.
2004/0111050			Smedley et al.	2007/0179520 2007/0191863		8/2007	West De Juan, Jr. et al.
2004/0122380			Utterberg Tuest of	2007/0191803			Yamamoto et al.
2004/0127843 2004/0147870			Tu et al. Burns et al.	2007/0219509			Tashiro et al.
2004/0193095			Shadduck	2007/0265582		11/2007	-
2004/0193262			Shadduck	2007/0270945			Kobayashi et al.
2004/0199171			Akahoshi	2007/0276315 2007/0276316			Haffner et al. Haffner et al.
2004/0210181 2004/0210185		10/2004	Vass et al.	2007/0270310		12/2007	_
2004/0210103		11/2004		2007/0282245	A1	12/2007	
2004/0225357			Worst et al.	2007/0293807			Lynch et al.
2004/0249333			Bergheim et al.	2007/0293872 2007/0298068		12/2007	Peyman Badawi et al.
2004/0254517 2004/0254519			Quiroz-Mercado et al. Tu et al.	2008/0015488			Tu et al.
2004/0254519			Porteous et al.	2008/0045878			Bergheim et al.
2004/0260228			Lynch et al.	2008/0058704			Hee et al.
2005/0041200		2/2005		2008/0228127 2008/0288082		9/2008 11/2008	Burns et al.
2005/0049578 2005/0090806			Tu et al.	2008/0288082			Downer et al.
2005/0090800			Lynch et al. Lynch et al.	2009/0005852			Gittings et al.
2005/0101967			Weber et al.	2009/0028953			Yamamoto et al.
2005/0107734			Coroneo	2009/0030363 2009/0030381			Gellman Lind et al.
2005/0119601 2005/0119636			Lynch et al. Haffner et al.	2009/0030381			Erskine
2005/0119030			Pinchuk et al.	2009/0043321			Conston et al.
2005/0131514			Hijlkema et al.	2009/0054723			Khairkhahan et al
2005/0149114			Cartledge et al.	2009/0069786 2009/0082860			Vesely et al. Schieber et al.
2005/0154443 2005/0165385		7/2005 7/2005	Linder et al.	2009/0082860			Schieber et al.
2005/0103583			Gharib et al.	2009/0104248			Rapacki et al.
2005/0197667			Chan et al.	2009/0138081			Bergheim et al.
2005/0203542			Weber et al.	2009/0182421 2009/0198248			Silvestrini et al.
2005/0209549 2005/0209550			Bergheim et al.	2009/0198248			Yeung et al. Nissan et al.
2005/0209350		11/2005	Bergheim et al. Hughes	2009/0247955			Yamamoto et al.
2005/0250788		11/2005	· .	2009/0259126			Saal et al.
2005/0260186			Bookbinder et al.	2009/0281520 2010/0004580			Highley et al. Lynch et al.
2005/0266047 2005/0271704		12/2005 12/2005		2010/0004380			Roman et al.
2005/0271702			Grahn et al.	2010/0114309			De Juan et al.
2005/0277864			Haffner et al.	2010/0137981			Silvestrini et al.
2005/0288619			Gharib et al.	2010/0173866 2010/0191176			Hee et al. Ho et al.
2005/0288745 2006/0020247			Andersen et al.	2010/0191170			Chang et al.
2006/0020247		2/2006	Kagan et al. Tu	2010/0234726			Sirimanne et al.
2006/0052879		3/2006		2010/0234790			Tu et al.
2006/0069340		3/2006		2011/0009874 2011/0098809			Wardle et al. Wardle et al.
2006/0074375 2006/0079828		4/2006 4/2006	Bergheim et al.	2011/0098809		12/2011	
2006/00/9828			Brown Bergheim et al.	2012/0010702			Stegmann et al.
2006/0106370			Baerveldt et al.	2012/0323159			Wardle et al.
2006/0116626			Smedley et al.	2013/0150959			Schieber et al.
2006/0149194			Conston et al.	2013/0158462			Wardle et al.
2006/0154981 2006/0155238			Klimko et al. Shields	2013/0172804 2013/0182223			Schieber et al. Wardle et al.
2006/0133230			Stamper et al.	2013/0182223			Wardle et al.
2006/0153300		7/2006	-	2013/0281907			Wardle et al.
2006/0167466	5 A1	7/2006	~	2014/0066821	A1	3/2014	Friedland et al.

(56) References Cited

U.S. PATENT DOCUMENTS

2014/0066831 A1 3/2014 Silvestrini et al. 2014/0249463 A1 9/2014 Wardle et al. 2014/0323944 A1 10/2014 Scheiber et al.

FOREIGN PATENT DOCUMENTS

	40004=004	04000
DE	4226476 C1	8/1993
EP	1615604 B1	8/2009
EP	2193821 A1	6/2010
EP	1715827 B1	12/2010
EP	2380622 A1	10/2011
EP	2468327 A1	6/2012
EP	2471563 A1	7/2012
EP	1833440 B1	8/2012
JP	H10-504978 A	5/1998
JP	11123205	5/1999
JP	2002542872	12/2002
JP	2006517848	8/2006
JP	2006289075 A	10/2006
JP	2010509003	3/2010
JP	2011502649	1/2011
WO	WO 00/07525 A1	2/2000
WO	WO 00/64389 A1	11/2000
WO	WO 00/64393 A1	11/2000
WO	WO 01/97727 A1	12/2001
WO	WO 02/36052 A1	5/2002
WO	WO 02/074052 A2	9/2002
WO	WO 02/080811 A2	10/2002
WO	WO 03/015659 A2	2/2003
WO	WO 03/045290 A1	6/2003
WO	WO 2004/054643 A1	7/2004
WO	WO 2004/093761 A1	11/2004
WO	WO 2005/105197 A2	11/2005
WO	WO 2006/066103 A2	6/2006
WO	WO 2007/035356 A2	3/2007
WO	WO 2007/047744 A2	4/2007
WO	WO 2007/087061 A2	8/2007
WO	WO 2008/002377 A1	1/2008
WO	WO 2008/005873 A2	1/2008
WO	WO 2009/120960 A2	10/2009
,,, 🔾	11 0 2007/120700 /12	10/2007

OTHER PUBLICATIONS

D'Ermo, et al.; Our results with the operation of ab externo trabeculotomy; Ophthalmologica; vol. 163; pp. 347-355; Feb. 1971.

Ellingsen et al.; Trabeculotomy and sinusotomy in enucleated human eyes; Investigative Ophthalmology; vol. 11; pp. 21-28; Jan. 1972. Grant; Experimental aqueous perfusion in enucleated human eyes; Archives of Ophthalmology; vol. 69; pp. 783-801; Jun. 1963.

Johnstone et al.; "Microsurgery of Schlemm's Canal and the Human Aqueous Outflow System;" American Journal of Ophthalmology, vol. 76 (6): 906-917; Dec. 1973.

Lee et al.; Aqueous-venous shunt and intraocular pressure. Preliminary report of animal studies; Investigative Ophthalmology; vol. 5; No. 1; pp. 59-64; Feb. 1966.

Moses, Robert; The effect of intraocular pressure on resistance to outflow; Survey of Ophthalmology; vol. 22; No. 2; pp. 88-100; Sep.-Oct. 1977.

Mäepea et al.; The pressures in the episcleral veins, schlemm's canal and the trabecular meshwork in monkeys: effects of changes in intraocular pressure; Exp. Eye Res.; vol. 49; pp. 645-663; Oct. 1989. Rosenquist et al.; Outflow resistance of enucleated human eyes at two different perfusion pressures and different extents of trabeculotomy; Current Eyes Res.; vol. 8; No. 12; pp. 1233-1240; Dec. 1989.

Savage, James; Gonioscopy in the management of glaucoma; Am. Academy of Ophthalmology; Focal Points; vol. XXIV; No. 3; pp. 1-14; Mar. 2006.

Schultz, Jared; Canaloplasty procedure shows promise for openangle glaucoma in European study; Ocular Surgery News; vol. 34; Mar. 1, 2007.

Smit et al.; Effects of viscoelastic injection into schlemm's canal in primate and human eyes; J. Am. Academy of Ophthalmology; vol. 109; No. 4; pp. 786-792; Apr. 2002.

Spiegel et al.; Schlermm's canal implant: a new method to lower intraocular pressure in patients with POAG?; Ophthalmic Surgery and Lasers; vol. 30; No. 6; pp. 492-494; Jun. 1999.

Lynch, Mary G.; U.S. Appl. No. 60/131,030 entitled "Devices and methods for treating glaucoma by enhancing aqueous outflow through schlemm's canal and anterior chamber angle," filed Apr. 26, 1999.

Scheiber et al.; U.S. Appl. No. 13/973,864 entitled Methods and Apparatus for Delivering Ocular Implants Into the Eye; filed Aug. 22, 2013.


Schieber et al.; U.S. Appl. No. 14/246,363 entitled "Ocular implants with asymmetric flexibility," filed Apr. 7, 2014.


Wardle et al.; U.S. Appl. No. 14/139,403 entitled "Ocular implants for delivery into the eye," filed Dec. 23, 2013.

Wardle et al.; U.S. Appl. No. 14/146,587 entitled "Delivering Ocular Implants Into the Eye," filed Jan. 2, 2014.

Wardle et al.; U.S. Appl. No. 14/363,409 entitled "Delivering ocular implants into the eye," filed Jun. 6, 2014.

^{*} cited by examiner








FIG. 3A




FIG. 3B




FIG. 3C




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8A




FIG. 8B




FIG. 8C




FIG. 8D




FIG. 8E




FIG. 8F




FIG. 8G





FIG. 8H







FIG. 8J








FIG. 9





METHODS AND APPARATUS FOR TREATING GLAUCOMA

CROSS REFERENCE TO RELATED APPLICATIONS

This application is a divisional of U.S. application Ser. No. 13/610,769, filed Sep. 11, 2012; which application is a continuation of U.S. application Ser. No. 12/398,847, filed Mar. 5, 2009, now U.S. Pat. No. 8,267,882; which application claims the benefit under 35 U.S.C. 119 of U.S. Provisional Patent Application No. 61/034,059, filed Mar. 5, 2008, titled "METHODS AND APPARATUS FOR TREATING GLAUCOMA." These applications are herein incorporated by reference.

INCORPORATION BY REFERENCE

All publications and patent applications mentioned in this specification are herein incorporated by reference to the same extent as if each individual publication or patent application was specifically and individually indicated to be incorporated by reference.

FIELD

The present invention relates generally to devices that are implanted within the eye. More particularly, the present invention relates to devices that facilitate the transfer of fluid ³⁰ from within one area of the eye to another area of the eye.

BACKGROUND

According to a draft report by The National Eye Institute (NEI) at The United States National Institutes of Health (NIH), glaucoma is now the leading cause of irreversible blindness worldwide and the second leading cause of blindness, behind cataract, in the world. Thus, the NEI draft report concludes, "it is critical that significant emphasis and 40 resources continue to be devoted to determining the pathophysiology and management of this disease." Glaucoma researchers have found a strong correlation between high intraocular pressure and glaucoma. For this reason, eye care professionals routinely screen patients for glaucoma by measuring intraocular pressure using a device known as a tonometer. Many modern tonometers make this measurement by blowing a sudden puff of air against the outer surface of the eye.

The eye can be conceptualized as a ball filled with fluid. 50 There are two types of fluid inside the eye. The cavity behind the lens is filled with a viscous fluid known as vitreous humor. The cavities in front of the lens are filled with a fluid know as aqueous humor. Whenever a person views an object, he or she is viewing that object through both the vitreous humor and the 55 aqueous humor.

Whenever a person views an object, he or she is also viewing that object through the cornea and the lens of the eye. In order to be transparent, the cornea and the lens can include no blood vessels. Accordingly, no blood flows through the 60 cornea and the lens to provide nutrition to these tissues and to remove wastes from these tissues. Instead, these functions are performed by the aqueous humor. A continuous flow of aqueous humor through the eye provides nutrition to portions of the eye (e.g., the cornea and the lens) that have no blood 65 vessels. This flow of aqueous humor also removes waste from these tissues.

2

Aqueous humor is produced by an organ known as the ciliary body. The ciliary body includes epithelial cells that continuously secrete aqueous humor. In a healthy eye, a stream of aqueous humor flows out of the anterior chamber of the eye through the trabecular meshwork and into Schlemm's canal as new aqueous humor is secreted by the epithelial cells of the ciliary body. This excess aqueous humor enters the venous blood stream from Schlemm's canal and is carried along with the venous blood leaving the eye.

When the natural drainage mechanisms of the eye stop functioning properly, the pressure inside the eye begins to rise. Researchers have theorized prolonged exposure to high intraocular pressure causes damage to the optic nerve that transmits sensory information from the eye to the brain. This damage to the optic nerve results in loss of peripheral vision. As glaucoma progresses, more and more of the visual field is lost until the patient is completely blind.

In addition to drug treatments, a variety of surgical treatments for glaucoma have been performed. For example, shunts were implanted to direct aqueous humor from the anterior chamber to the extraocular vein (Lee and Scheppens, "Aqueous-venous shunt and intraocular pressure," Investigative Ophthalmology (February 1966)). Other early glaucoma treatment implants led from the anterior chamber to a subconjunctival bleb (e.g., U.S. Pat. Nos. 4,968,296 and 5,180, 362). Still others were shunts leading from the anterior chamber to a point just inside Schlemm's canal (Spiegel et al., "Schlemm's canal implant: a new method to lower intraocular pressure in patients with POAG?" Ophthalmic Surgery and Lasers (June 1999); U.S. Pat. Nos. 6,450,984; 6,450, 984).

SUMMARY OF THE DISCLOSURE

The present invention relates to devices implanted within the eye. In one embodiment, an ocular implant defines a generally cylindrical volume and comprises a proximal inlet portion at a proximal end of the implant, a distal inlet portion at a distal end of the implant, the distal inlet portion being biased to bend at a first radius of curvature, an intermediate portion positioned between the proximal inlet portion and the distal inlet portion, and a plurality of openings in the implant to facilitate fluidic flow laterally across the elongate implant. The implant can also define a lumen to facilitate fluidic flow longitudinally along the implant.

In some embodiments, an intermediate portion of the implant is biased to bend at a second radius of curvature. In one embodiment, the first radius of curvature is smaller than the second radius of curvature. In other embodiments, the second radius of curvature can approximate the curvature of Schlemm's canal.

In one embodiment, the proximal portion of the implant is biased to bend at a third radius of curvature. The third radius of curvature can be generally smaller than the second radius of curvature. In another embodiment, the third radius of curvature can be generally equal to the first radius of curvature.

In some embodiments, the plurality of openings in the implant extend over more than about 50% of an outer surface area of the implant.

Yet another embodiment includes an ocular implant defining a generally cylindrical volume, comprising a proximal inlet portion at a proximal end of the implant, the proximal inlet portion adapted to be positioned in an anterior chamber of the eye, a distal inlet portion at a distal end of the implant, the distal inlet portion adapted to be positioned in the anterior chamber of the eye, an intermediate portion positioned between the proximal and distal inlet portions, the interme-

diate portion adapted to be positioned in Schlemm's canal, and a plurality of openings in the implant to facilitate fluidic flow laterally across the implant. The implant can also define a lumen to facilitate fluidic flow longitudinally along the implant.

One embodiment includes an assembly, comprising an ocular implant defining an implant lumen, a core disposed in the implant lumen, a guide wire disposed in a guide wire lumen defined by the core, wherein the guide wire is biased to assume a predetermined at rest shape, the guide wire having a distal radius of curvature and a proximal radius of curvature when the guide wire is assuming the predetermined at rest shape, and wherein the proximal radius of curvature is greater than the distal radius of curvature.

In one embodiment, the assembly further comprises a cannula disposed about the ocular implant. In yet another embodiment, the assembly further comprises a luer fitting disposed in fluid communication with a lumen defined by the cannula.

In some embodiments, the proximal radius of curvature 20 approximates the curvature of Schlemm's canal. In other embodiments, an intermediate portion of the ocular implant is biased to bend at a second radius of curvature. In one embodiment, the proximal radius of curvature of the guide wire can be generally equal to the second radius of curvature of the 25 ocular implant.

In other embodiments, the ocular implant and the core urge the guide wire to assume a stressed shape that is different from the predetermined at rest shape. The stressed shape is generally straighter than the predetermined at rest shape.

In some embodiments, the implant comprises a first material and the core comprises a second material different from the first material. The first material and the second material typically comprise materials which provide a relatively low friction interface when placed in sliding contact with one 35 another. The first material and the second material also typically comprise materials which are unlikely to gall when placed in sliding contact with one another. In one embodiment, the first material comprises a metallic material and the second material comprises a polymeric material.

In one embodiment, the guide wire comprises a first material and the core comprises a second material different from the first material. In another embodiment, the first material and the second material comprise materials which provide a relatively low friction interface when placed in sliding contact with one another. The first material and the second material typically comprise materials which are unlikely to gall when placed in sliding contact with one another. In one embodiment, the first material comprises a metallic material and the second material comprises a polymeric material.

In another embodiment, a device comprises an ocular implant comprising a body and a hatch, the body defining a body lumen and a longitudinal axis, the hatch defining a hatch lumen having a hatch axis, the hatch comprising an arm hingedly connecting the hatch to the body, the hatch having a second position in which the hatch axis is skewed relative to the longitudinal axis of the body, and wherein the hatch is biased to assume the second position.

between of opening a cross the can also implant.

The program of opening a cross the can also implant.

The program of opening a cross the can also implant.

The program of opening a cross the can also implant.

The program of opening a cross the can also implant.

The program of opening a cross the can also implant.

The program of opening a cross the can also implant.

The program of opening a cross the can also implant.

The program of opening a cross the can also implant.

The program of opening a cross the can also implant.

The program of opening a cross the can also implant.

The program of opening a cross the can also implant.

The program of opening a cross the can also implant.

The program of opening a cross the can also implant.

The program of opening a cross the can also implant.

The program of opening a cross the can also implant.

The program of opening a cross the can also implant.

The program of opening a cross the can also implant a cross the can also implant a cross the can also implant.

The program of opening a cross the can also implant a cross the cross the c

In one embodiment, the hatch is disposed in the first position, and the device further includes a core extending through the body lumen and the hatch lumen. In another embodiment, at least a portion of the hatch extends around a portion of the core across a radial span of more than 180 degrees. In one embodiment, the core causes the hatch to remain in the first position. In another embodiment, the hatch assumes the first position when the core is withdrawn from the hatch lumen.

4

Another embodiment of the invention includes an ocular implant comprising a proximal locking portion at a proximal end of the implant, a distal locking portion at a distal end of the implant, an intermediate portion extending between the proximal locking portion and the distal locking portion, the intermediate portion having a longitudinal axis that follows an arcuate path when the implant is assuming a relaxed shape, wherein the proximal locking portion is biased to extend in a first radially inward direction relative to the arcuate path of the longitudinal axis of the intermediate portion, and wherein the distal locking portion is biased to extend in a second radially inward direction relative to the arcuate path of the longitudinal axis of the intermediate portion.

In one embodiment, the first radially inward direction and the second radially inward direction intersect one another. In another embodiment, the first radially inward direction and the second radially both lead out of Schlemm's canal of an eye when the intermediate portion of the implant is disposed in Schlemm's canal of the eye.

In some embodiments, the implant is dimensioned so that the proximal locking portion and the distal locking portion will both extend through a wall of Schlemm's canal of an eye when the intermediate portion of the implant is disposed in Schlemm's canal of the eye.

The implant described can reduce the likelihood that the intermediate portion of the implant will migrate within Schlemm's canal of an eye when the proximal locking portion and the distal locking portion both extend through a wall of Schlemm's canal.

In some embodiments, the first radially inward direction and the second radially both lead out of Schlemm's canal of an eye when the longitudinal axis of the intermediate portion is coaxial with a longitudinal axis of Schlemm's canal. In another embodiment, a radius of curvature of the longitudinal axis of the intermediate portion approximates the curvature of Schlemm's canal when the implant is assuming the relaxed shape.

In yet another embodiment, a wall of the implant defines a plurality of openings in the implant to facilitate fluidic flow laterally across the implant. The implant can also define a lumen to facilitate fluidic flow longitudinally along the implant.

In one embodiment of the invention, an ocular implant defining a generally cylindrical volume comprises a proximal inlet portion at a proximal end of the implant, the proximal inlet portion adapted to be positioned in an anterior chamber of the eye, a distal inlet portion at a distal end of the implant, the distal inlet portion adapted to be positioned in a suprachoroidal space of the eye, an intermediate portion positioned between the proximal and distal inlet portions, and a plurality of openings in the implant to facilitate fluidic flow laterally across the implant. The plurality of openings in the implant can also facilitate fluidic flow longitudinally along the implant.

The present invention also relates to a method of treating glaucoma in an eye of a patient, comprising positioning a proximal inlet portion of an implant in an anterior chamber of the eye, positioning an intermediate portion of the implant in Schlemm's canal, positioning a distal inlet portion of the implant in the anterior chamber of the eye, allowing aqueous humor to flow from the anterior chamber through the implant into Schlemm's canal.

The allowing step can further comprise allowing aqueous humor to flow from the anterior chamber into the proximal and distal inlet portions, through the intermediate portion, and into Schlemm's canal.

In one embodiment, aqueous humor flows into Schlemm's canal through a plurality of openings in the implant.

In another embodiment, the proximal inlet portion of the implant can be spaced approximately 60 to 180 degrees from the distal inlet portion.

In yet another embodiment, aqueous humor can flow longitudinally along the implant. Aqueous humor can also flow laterally across the implant.

Yet another method of the present invention relates to a method of implanting a dual inlet ocular implant into an eye of a patient, comprising, inserting a cannula into an anterior chamber of the eye so that a distal tip of the cannula is in communication with Schlemm's canal, inserting a distal inlet portion of the implant through the cannula into Schlemm's canal, advancing the implant distally along Schlemm's canal until only a proximal inlet portion of the implant remains in the cannula, introducing the distal inlet portion of the implant into the anterior chamber of the eye from Schlemm's canal.

In one embodiment, the method further comprises removing the cannula from the anterior chamber of the eye leaving the proximal inlet portion of the implant in the anterior chamber of the eye.

In another embodiment, the introducing step comprises, advancing a tissue penetrating guide wire distally from the implant to penetrate into the anterior chamber of the eye from 25 Schlemm's canal, advancing the implant over the guide wire to introduce the distal inlet portion of the implant into the anterior chamber of the eye from Schlemm's canal.

In an alternative embodiment, the introducing step comprises, making an incision from the anterior chamber of the 30 eye into Schlemm's canal at a position near the distal inlet portion of the implant, allowing the distal inlet portion of the implant to assume a predetermined at rest shape which results in the distal inlet portion bending through the incision into the anterior chamber of the eye from Schlemm's canal.

In another embodiment, the proximal inlet portion is spaced approximately 60 to 180 degrees from the distal inlet portion.

In one embodiment, the method comprises inserting a core into a lumen defined by the implant, and inserting a guide 40 wire into a guide wire lumen defined by the core. Sometimes the core is disposed in the lumen defined by the implant while the implant is advanced distally along Schlemm's canal. Other times the guide wire is disposed in the guide wire lumen defined by the core while the implant is advanced distally 45 along Schlemm's canal.

In one embodiment, the introducing step comprises advancing a distal portion of the guide wire distally from the core to penetrate into the anterior chamber of the eye from Schlemm's canal, and advancing the implant off of the core 50 and over the guide wire to introduce the distal inlet portion of the implant into the anterior chamber of the eye from Schlemm's canal.

In some embodiments, the distal portion of the guide wire is urged to assume a stressed shape when the distal portion of the guide wire is disposed in the guidewire lumen and the distal portion of the guide wire is free to assume a predetermined at rest shape when the distal portion of the guide wire is advanced distally from the core.

In other embodiments, the distal portion of the guide wire 60 has a distal radius of curvature when the distal portion of the guide wire is free to assume a predetermined at rest shape.

In yet other embodiments, a proximal portion of the guide wire has a proximal radius of curvature and the proximal radius of curvature is generally greater than the distal radius of curvature. In some embodiments the proximal radius of curvature approximates the curvature of Schlemm's canal.

6

In some embodiments, the cannula can be flushed with a fluid. The flushing can be performed prior inserting a distal end of the cannula into the anterior chamber for preventing the introduction of air bubbles into the anterior chamber of the eye.

In other embodiments, a bolus of viscoelastic material can be injected proximate a target location in the anterior chamber of the eye. The method can further comprise piercing a wall of Schlemm's canal or a trabecular mesh with a distal end of the cannula at the target location. Alternatively, the bolus of viscoelastic material can be injected prior to piercing the wall of Schlemm's canal for precluding the formation of a pool of blood near the target location.

In one embodiment, the introducing step comprises advancing a self-piercing distal inlet in a distal direction to cause the distal inlet to cut through Schlemm's canal into the anterior chamber. The self-piercing distal inlet can be advanced while the distal inlet portion is biased inwards.

BRIEF DESCRIPTION OF THE DRAWINGS

The foregoing aspects and many of the attendant advantages of this invention will become more readily appreciated as the same become better understood by reference to the following detailed description, when taken in conjunction with the accompanying drawings, wherein:

FIG. 1 is a schematic drawing of an ocular implant.

FIG. 2 is another drawing of the implant having a predetermined at rest shape.

FIG. 3A is a drawing showing a delivery system for the ocular implant.

FIG. 3B is an enlarged view of a distal end of the implant mounted on a core.

FIG. 3C is an enlarged view of the distal end of the implant mounted on a core further illustrating a tissue piercing guide wire.

FIG. 4 is a simplified view showing a human face including a pair of eyes.

FIG. 5 is an additional view of the eye shown in the FIG. 4 further illustrating a cannula inserted into the eye.

FIG. 6 is an enlarged view of the eye shown in FIG. 5 further showing the cannula piercing the trabecular mesh and Schlemm's canal.

FIG. 7 is a further enlarged view of an eye further illustrating an implant partially inserted into Schlemm's canal.

FIG. 8A is an additional view of the eye shown in FIG. 7 further illustrating a guide wire penetrating the tissues of the eye into the anterior chamber.

FIG. 8B is a view of the eye shown in FIG. 7 further illustrating a proximal inlet of an implant in the anterior chamber and a distal inlet of the implant in Schlemm's canal.

FIG. **8**C is a view of the eye shown in FIG. **8**B further illustrating making an incision near the distal inlet of the implant.

FIGS. 8D-8K are some embodiments of implants comprising a self-piercing distal inlet.

FIG. 9 is a view of an eye with an implant having two inlets positioned in the anterior chamber and the remaining portion of the implant positioned in Schlemm's canal.

FIG. 10 is a view of an ocular implant with a distal end positioned in the suprachoroidal space of the eye.

FIG. 11 is another view of the ocular implant with a distal end positioned in the suprachoroidal space of the eye.

DETAILED DESCRIPTION

The following detailed description should be read with reference to the drawings, in which like elements in different

drawings are numbered identically. The drawings, which are not necessarily to scale, depict exemplary embodiments and are not intended to limit the scope of the invention. Examples of constructions, materials, dimensions, and manufacturing processes are provided for selected elements. All other elements employ that which is known to those of skill in the field of the invention. Those skilled in the art will recognize that many of the examples provided have suitable alternatives that can be utilized.

FIG. 1 is a schematic view of an implant 100 that may be used, for example, to facilitate the flow of aqueous humor within the eye of a patient. Implant 100 comprises spines 102 and 104 and a frame 106 disposed between the spines. In FIG. 1, frame 106 comprises a first strut 120 and a second strut 122. 15 between any pockets or compartments formed within The struts extend between the spines. First strut 120 comprises a first edge 124A and a second edge 126A. Second strut **122** has a shape that is a mirror image of the shape of the first strut. Thus, the second strut comprises a first edge 124B and a second edge 126B. In FIG. 1, a first opening 128 is defined by the space between first edge 124A of first strut 120 and first edge 124B of second strut 122. Similarly, a second opening 130 is defined by the space between second edge 126A of first strut 120 and second edge 126B of second strut 122. The second opening generally divides the frame 106 into a first 25 strut and a second strut. The openings defined by implant 100, such as first opening 128 and second opening 130, allow aqueous humor to flow laterally across and/or laterally through the implant.

Implant 100 typically comprises a plurality of spines and a 30 plurality of frames. These spines and frames are arranged in an "ABAB" pattern. As shown in FIG. 1, implant 100 includes four spines and three frames, wherein each frame is positioned between adjacent spines. In other embodiments, the implant can have more or fewer spines and frames depending 35 on the desired length and/or size of the implant. Implant 100 can be shaped to have an outer surface 138 defining a generally cylindrical volume. An inner surface 140 of the implant defines an elongate channel **142** or lumen to facilitate fluidic flow longitudinally along the implant. The plurality of spines 40 and plurality of frames can be defined as an intermediate portion of the implant.

Implant 100 of FIG. 1 further comprises a proximal inlet portion 101A and a distal inlet portion 101B. Each inlet portion includes a plurality of apertures 105, to allow for fluid 45 to flow into each inlet portion. The elongate channel **142** of implant 100 can fluidly communicate with the first and second inlet portions as well as first opening 128 and second opening 130 of the implant. As shown in FIG. 1, the intermediate portion of the implant can be positioned between the 50 proximal and distal inlet portions.

Implant 100 may be inserted into Schlemm's canal of a human eye, for example, to facilitate the flow of aqueous humor out of the anterior chamber of the eye. Aqueous humor may flow, for example, into the proximal and distal inlet 55 portions, through the intermediate portion of the implant, and into Schlemm's canal. Aqueous humor may exit Schlemm's canal via natural outlets communicating with the canal. The flow of aqueous humor may include axial flow along Schlemm's canal, flow from the anterior chamber into 60 Schlemm's canal, flow leaving Schlemm's canal via natural outlets communicating with the canal, and flow through openings in the implant. When in place within the eye, the implant can support trabecular mesh tissue and Schlemm's canal tissue and can provide for improved communication 65 between the anterior chamber and Schlemm's canal (via the trabecular meshwork) and between pockets or compartments

along Schlemm's canal. The implant can facilitate flow of aqueous humor longitudinally along the implant, as well as laterally across the implant.

The outer diameter of the implant is selected to support the tissue of Schlemm's canal without undue stretching and is typically in the range of 0.005 inches to 0.04 inches, and preferably in the range of 0.005 inches to 0.02 inches. The arrangement of frames, spines, and openings along implant 100 support the tissue of Schlemm's canal with a minimum amount of material. In the embodiment shown in FIG. 1, for example, the openings (such as openings 128 and 130) extend over more than 50% of a tubular surface covering the volume of the portion of the implant lying within Schlemm's canal. This combination of features helps aqueous humor flow Schlemm's canal and, therefore, between the anterior chamber of the eye and the outlets from Schlemm's canal to the venous system.

The implant 100 may be biased to assume a predetermined at rest shape. This predetermined shape may include one or more bends or curves along the length of the implant. The predetermined shape can generally model the anatomy of the human eye, and in particular, the anatomy of Schlemm's canal into which it is to be implanted. FIG. 2 is a view of implant 100 assuming a predetermined at rest shape. As shown, the implant has an at rest shape that is generally curved. This at rest shape can be established, for example, using a heat-setting process. The shape of the implant in FIG. 2 can include a distal radius of curvature RA corresponding to each of the proximal and distal inlets 101A and 101B, and an intermediate or proximal radius of curvature RB corresponding to the intermediate portion of the implant between the inlets. The radius of curvature RB can approximate the curvature of Schlemm's canal, for example. In the embodiment of FIG. 2, the distal radii of curvature RA are smaller than the intermediate radius of curvature RB. For example, the distal radii of curvature RA can be approximately 0.105 inches and the intermediate radius of curvature RB can be approximately 0.215 inches. In the exemplary embodiment of FIG. 2, the distal radius of curvature RA corresponding to distal inlet **101**A is approximately the same as the distal radius of curvature RA corresponding to inlet 101B. In some embodiments, however, the radius of curvature corresponding to distal inlet 101A can be different from the radius of curvature corresponding to inlet 101B.

As shown in FIG. 2, each of the proximal and distal inlets of the implant follow a radius of curvature RA along an arc extending across an angle AA. Similarly, an intermediate portion of the implant (i.e., the portion of the implant disposed between the distal and proximal inlets) follows a radius of curvature RB along an arc extending across an angle AB. In one embodiment, angle AA can be approximately 0-45 degrees and angle AB can be between approximately 60-180 degrees.

Various fabrication techniques may be used to fabricate the implant. For example, implant 100 can be fabricated by providing a generally flat sheet of material and laser cutting the material. The material may then be formed into a generally tubular shape as shown in FIG. 1. Any adjoining edges (such as edges 103) may be attached, such as by welding or other techniques known in the art. In another embodiment, the implant may be fabricated by providing a tube and laser cutting openings in the tube to form the shape shown in FIG.

Implant 100 can be fabricated from various biocompatible materials possessing the necessary structural and mechanical attributes. Both metallic and non-metallic materials may be

suitable. Examples of metallic materials include stainless steel, tantalum, gold, titanium, and nickel-titanium alloys known in the art as Nitinol. Nitinol is commercially available from Memry Technologies (Brookfield, Conn.), TiNi Alloy Company (San Leandro, Calif.), and Shape Memory Applications (Sunnyvale, Calif.).

The implant may include one or more therapeutic agents. One or more therapeutic agents may, for example, be incorporated into a polymeric coating that is deposited onto the outer surfaces of the struts and spines of the ocular implant. The therapeutic agent may comprise, for example, an antiglaucoma drug. Examples of anti-glaucoma drugs include prostaglandin analogs. Examples of prostaglandin analogs include latanprost.

FIG. 3A is a partial view of a delivery system 300 used to deliver an implant 100 into the eye of a patient. The delivery system can comprise core 302, a push tube 304, cannula 306, handle 308, and guide wire 314. In some embodiments, the delivery system may optionally include a fluid source or syringe 310 in fluid communication with handle 308. In some exemplary methods, a syringe or other fluid source is used for flushing implant 100 with fluid to remove air bubbles and prevent the introduction of air bubbles into the anterior chamber of the eye. In some additional exemplary methods, a syringe or other fluid source may be used for injecting a 25 viscoelastic into the eye for precluding the formation of a pool of blood near a target location.

Cannula 306 can be coupled to a distal end of handle 308. The cannula can be relatively straight, or as shown in FIG. 3A, can have a curved distal tip to aid in implanting implant 100 30 into an eye of a patient. In the embodiment of FIG. 3A, the distal end of cannula 306 is curved so as to pierce the trabecular mesh of a patient to gain access to Schlemm's canal. It should be noted that in FIG. 3A, illustration of the distal end of cannula 306 has been enlarged for ease of visualization and 35 description.

Delivery system 300 may also include a mechanism (not shown in FIG. 3A), such as a thumb wheel, lever, or button on or near the handle 308 adapted to advance and retract core 302, push tube 304, and/or guide wire 314. This mechanism 40 may also be used to retract core 302 relative to push tube 304 and/or guide wire 314. The implant may be moved in distal and proximal directions by moving core 302 and push tube 304 with the mechanism.

As shown in FIG. 3B, implant 100 can be mounted on core 302. Core 302 can extend through a lumen defined by a push tube to extend through implant 100. In a preferred embodiment, core 302 extends beyond the distal end of the implant with a tapered finish. In another embodiment, the core extends only to the distal end of the implant. In a preferred embodiment, core 302 comprises polymeric tubing. In other embodiments, core 302 can be fabricated from similar materials to that of the implant, as described above. In general, the implant and core will comprise materials which provide a relatively low friction interface when placed in sliding contact with one another. Additionally, the materials are unlike to gall when placed in sliding contact with one another.

Among other features, one particular function of core 302 is to block the openings formed in implant 100 so as to minimize interference between the implant and tissue within 60 Schlemm's canal as the implant is advanced during implantation. With reference to FIGS. 3A-3B, it can be seen that core 302 substantially fills implant 100. Together, core 302 and implant 100 form an assembly that presents a relatively smooth outer surface.

Another function of core 302 is to aid in the insertion of implant 100 into the eye of a patient. FIG. 3B shows a close up

10

view of the distal tip of core 302 with implant 100 mounted on the core. As shown in FIG. 3B, the distal tip of core 302 is tapered and includes a guide wire lumen 312 which runs along the length of the core. The core can also be biased to assume a predetermined at rest shape corresponding to the predetermined shape of the implant 100 or any other desired predetermined shape. For example, an intermediate portion of core 302 can be biased to curve at a radius of curvature RB, which corresponds to radius of curvature RB of the intermediate portion of the implant in FIG. 2 as described above. Similarly, a distal or proximal portion of the core can be biased to curve at a radius of curvature RA, which corresponds to radius of curvature RA of the distal and proximal inlet portions of the implant. Despite the biased at rest shape of core 302, the core can be flexible enough to assume a generally straightened configuration when inserted into a delivery system or cannula for implantation into a patient, for example. If the core is biased to assume a predetermined at rest shape, then a portion of the core may be urged to assume a stressed shape when it is disposed in the implant.

FIG. 3C shows a close-up view of implant 100 mounted on core 302 and further including tissue piercing guide wire 314 adapted to advance and retract through the guide wire lumen of the core and extend out beyond the core. The guide wire can also include a tissue penetrating tip to allow the guide wire to cut through and penetrate tissue when desired. The guide wire can be a metallic wire, such as stainless steel, nitinol, MP-35N alloy or other appropriate materials. In one embodiment, the guide wire can have an approximate diameter of 0.004 inches. In general, the guide wire and core will comprise materials which provide a relatively low friction interface when placed in sliding contact with one another. Additionally, the materials are unlike to gall when placed in sliding contact with one another.

The distal end of guide wire **314** can also be biased to assume a predetermined at rest shape or curvature corresponding to the at rest shape of implant 100 or another desired at rest shape. For example, the distal tip of guide wire 314 can be biased to curve at a radius of curvature RA, which corresponds to radius of curvature RA of the distal and proximal inlet portions of the implant as shown in FIG. 2, and an intermediate portion of the guide wire can be biased to curve at a radius of curvature RB, which corresponds to radius of curvature RB of the intermediate portion of the implant, as described above. The radius of curvature RA can be smaller than the radius of curvature RB. In another embodiment, only the distal end of the guide wire can be biased to assume a predetermined at rest shape or curvature. Despite the biased at rest shape of guide wire 314, the guide wire is relatively flexible and can assume a generally straightened or slightly curved configuration when inserted into guide wire lumen 312 of core 302, for example. This could cause a portion of the guide wire to be urged to assume a stressed shape when it is disposed in the core, such as when a distal portion of the guide wire is disposed in an intermediate portion of the core, and cause the portion of the guide wire to assume the predetermined at rest shape when it is advanced distally from the core, such as when the distal portion is advanced distally from the core, for example. The stressed shape is generally straighter than the predetermined at rest shape. It should be noted that the guide wire can be correctly oriented relative to the anterior chamber because the predetermined shape of the guide wire can self align to Schlemm's canal creating an automatic alignment of the distal radius of curvature of the guide wire.

In some useful embodiments, the relaxed shape of the guide wire is selected so that so that a distal portion of the guide wire extends into the anterior chamber when a longi-

tudinal axis of the proximal portion of the guide wire is generally coaxial with a longitudinal axis of Schlemm's canal and the distal radius of curvature of the guide wire is free to assume its relaxed shape. The guide wire tends to orient itself within the core so that a plane defined by a longitudinal axis of the guide wire is coplanar with a plane defined by the longitudinal axis of Schlemm's canal.

A method of implanting implant 100 into a patient will now be described with reference to FIGS. 4-9. The implant described herein is adapted to be implanted into a patient's 10 eye so that both the distal and proximal inlets are positioned in the anterior chamber of the eye while the remaining portion of the implant is positioned in Schlemm's canal. This facilitates the flow of aqueous humor out of the anterior chamber of the eye through both inlets into Schlemm's canal, and then 15 out of Schlemm's canal via natural outlets communicating with the canal. An implant as described herein advantageously provides for multiple fluid inlets, allowing the implant to facilitate flow of aqueous humor into Schlemm's canal even if one of the inlets fails to function or becomes 20 clogged.

FIG. 4 is a simplified drawing showing a human face including an eye 40. In FIG. 4, a surgeon can use a scalpel or knife 402 to make an incision 404 through the cornea of the eye. FIG. 5 is an additional view of the eye shown in the 25 previous figure. In FIG. 5, the distal tip of cannula 306 can be inserted through the incision in the cornea.

FIG. 6 is a further enlarged view of eye 40. In FIG. 6, the distal tip of cannula 306 has pierced through trabecular mesh 50 and through the wall of Schlemm's canal 60. When the 30 distal tip of cannula 306 pierces through these tissues, it places Schlemm's canal in fluid communication with the anterior chamber 70 of eye 40. As shown, the distal tip of cannula 306 can be curved to achieve tangential entry into Schlemm's canal. However, in other embodiments the can-35 nula can be relatively straight.

When the distal tip of the cannula pierces the tissues separating Schlemm's canal from the anterior chamber, a small amount of blood may flow from the venous system into Schlemm's canal. This blood will typically cause Schlemm's canal to turn a red/pink color which can enhance the visibility of Schlemm's canal for a short time (i.e., until the blood in Schlemm's canal dissipates). It may be desirable to advance an implant into Schlemm's canal while the presence of blood in the canal is enhancing the visibility of the canal.

In some cases, however, blood will leak out of the puncture made by the distal end of the cannula. When this is the case, the blood may pool around the opening of the puncture and interfere with the physician's ability to see the opening. Methods described herein may be used to displace any blood 50 that is pooled around the opening of the puncture. Methods described herein may also be used to preclude blood from pooling around the opening of a puncture.

Blood can be precluded from pooling near an anticipated puncture by injecting a bolus of viscoelastic near the place 55 where the puncture will be made. Blood that has entered the anterior chamber may be displaced, for example, by injecting a bolus of viscoelastic near the place where the cannula has punctured the trabecular mesh. Various fluids may be used in conjunction with the methods described in this document. 60 Examples of fluids that may be suitable in some applications include water, saline, hyaluronic acid and/or viscoelastic. The term "viscoelastic" is sometimes used to describe various viscoelastic materials that are injected into the eye as part of a surgical procedure. Viscoelastics for use in ophthalmic surgery are commercially available from Bausch and Lomb Incorporated (Rochester, N.Y., U.S.A.) and Alcon, Incorpo-

12

rated (Hünenberg, Switzerland). Viscoelastics may comprise, for example, hyaluronic acid. Hyaluronic acid is a material that is naturally found in the vitreous humor that fills the posterior chamber of the eye. Accordingly, this material is well suited for use in ophthalmic surgery. Hyaluronic acid is also known as hyaluronan and hyaluronate.

FIG. 7 is a further enlarged view of the eye shown in FIG. 6 with an implant partially inserted into the eye. During delivery, implant 100 can be mounted on core 302 which is movable with implant 100, as described above. Among other features, one particular function of core 302 is to block the openings in implant 100 so as to minimize interference between the implant and tissue within Schlemm's canal as the implant is advanced. As described above, distal inlet portion 101B is situated at the distal end of implant 100, and core 302 extends beyond the distal inlet a small distance to a tapered finish. In a preferred embodiment, the entire length of the tapered end of core 302 extends distally beyond implant 100. The tapered finish of the core can be provided to facilitate dilation of tissue in Schlemm's canal while minimizing the compressive forces necessary to advance the implant in the canal.

A push tube can be engaged with a proximal end of implant 100. The push tube may be used to apply distally directed force to the proximal end of the implant 100 to advance the implant into Schlemm's canal. Core 302 can extend proximally into the push tube during implantation. A handheld actuator or mechanism (not shown) may be used to provide relative motion to the push tube, the core, and or the guide wire. When the implant is being inserted into Schlemm's canal, the tissue piercing guide wire can be positioned within the guide wire lumen, but should not extend out beyond the core to avoid cutting or penetrating tissue.

As shown in FIG. 7, the implant can be inserted into Schlemm's canal with the push tube until the distal inlet portion 101B of implant 100 is in a desired position with respect to the proximal inlet or proximal portion of the implant. In FIG. 7, the distal inlet is positioned approximately 180 degrees from the proximal inlet of the implant, which at this point in the procedure is still positioned within cannula 306. In other embodiments, the distal inlet may be positioned at different positions with respect to the proximal inlet depending on the length of the implant, typically anywhere from 60 to 180 or more degrees apart.

At this point in the implantation procedure the distal inlet 101B can be re-inserted into the anterior chamber of the eye using one of several methods. A first method is illustrated in FIG. 8A. As shown in FIG. 8A, tissue piercing guide wire 314 can be extended distally from core 302. In some useful embodiments, the relaxed shape of the guide wire is selected so that so that a distal portion of the guide wire extends into the anterior chamber when a longitudinal axis of the proximal portion of the guide wire is generally coaxial with a longitudinal axis of Schlemm's canal and the distal radius of curvature of the guide wire is free to assume its relaxed shape. The guide wire tends to orient itself within the core so that a plane defined by a longitudinal axis of the guide wire is coplanar with a plane defined by the longitudinal axis of Schlemm's canal.

As described above, the distal end of the guide wire 314 can have a pre-biased radius of curvature RA, which can be smaller than the radius of curvature RB of the portion of implant 100 within Schlemm's canal. Thus, when the guide wire is extended beyond the core, the guide wire will be biased to curve inwards back into the anterior chamber of the eye. The tissue piercing distal tip of the guide wire can allow the guide wire to penetrate the tissues of Schlemm's canal and

the trabecular meshwork to gain access to the anterior chamber. Once access to the anterior chamber has been achieved with the guide wire, the implant and core can be advanced together over the guide wire to position distal inlet 101B properly within the anterior chamber. The taper of the core will facilitate placement of the implant by dilating an opening through the meshwork. The implant can then be advanced into the anterior chamber and location can be achieved which allows both inlets to extend equally and uniformly from the canal. Next, the guide wire 314 can be removed from the core 10302, the core can be removed from implant 100, and cannula 306 can be removed from over the implant and out of the eye, leaving proximal inlet 101 A and distal inlet 101 B in the anterior chamber, and the remaining portion of implant 100 in Schlemm's canal, as shown in FIG. 9.

When the proximal and distal inlets are positioned in the anterior chamber, they effectively serve as anchors or locks to reduce the likelihood that the intermediate portion of the implant will migrate or move within Schlemm's canal or that the inlets will become dislodged or removed from the anterior 20 chamber. This is because the proximal and distal inlets extend at a radially inward direction relative to the arcuate path of the longitudinal axis of the intermediate portion, which can be shaped to fit the contours of Schlemm's canal.

Other methods of inserting distal inlet **101** B into the ante- 25 rior chamber are illustrated in reference to FIGS. 8B and 8C. It should be noted that this method may be performed with or without the use of guide wire 314. If guide wire 314 is used, it can be removed from the core 302, the core can be removed from implant 100, and cannula 306 can be removed from over 30 the implant and out of the eye, leaving proximal inlet portion **101A** in the anterior chamber, and distal inlet **101B** and the remaining portion of implant 100 in Schlemm's canal. Removing the core from the implant can cause the distal inlet to bias inwards to the predetermined at rest shape, as 35 described above. In some applications, the distal inlet may push through the tissues of Schlemm's canal and the trebecular meshwork to enter the anterior chamber when the implant assumes its at rest shape. In some cases, it may be desirable to make an incision in the tissues proximate the 40 distal inlet. When this is the case, the incision may be made, for example, with a scalpel. In some embodiments, the implant may include a cutter that is capable of making the incision. In one embodiment, the distal inlet 101B can have a self-piercing distal tip. Advancing the self-piercing distal tip 45 in a distal direction when the distal inlet is biased inwards can cause the distal inlet to cut through the tissues of Schlemm's canal and the trabecular meshwork to gain entry into the anterior chamber.

In another embodiment, as shown in FIG. 8C, instead of 50 having a self-piercing distal tip, a surgeon can make an incision near the distal inlet portion with scalpel 402. As described above, the portion of implant 100 near distal inlet 101B is biased to assume a predetermined at rest shape or curvature with a radius of curvature RA, as shown in FIG. 2. 55 Thus, when the incision is made near the distal inlet, the distal portion of the implant comprising the distal inlet will bend inwards to assume the predetermined at rest shape, which results in the distal inlet 101B positioning itself within the anterior chamber of the eye. As a result, the distal and proxi- 60 mal inlets will be positioned in the anterior chamber of the eye, and the remaining portion of the implant will be positioned in Schlemm's canal, as shown in FIG. 9. In yet another embodiment, a surgeon can reach through the trabecular meshwork to grab the implant with a surgical device, such as 65 forceps, to pull the implant from Schlemm's canal back into the anterior chamber.

14

Other embodiments of a self-piercing distal inlet are illustrated in FIGS. 8D-8K. FIG. 8D illustrates a distal inlet 101B with a cutter 802 extending radially from the distal inlet. The cutter can be configured to swing or "spring" outwards from hole 804, such as with a heat-set or shape-set design. For example, the cutter can be shape set with a predetermined body transition temperature which would cause the cutter to spring outwards from the hole when the implant is heated to the predetermined body transition temperature. However, it should be understood that the cutter can be designed to swing outwards without requiring the implant to be heated.

FIG. 8E is a top down view of distal inlet 101B further showing another view of cutter 802 and hole 804. In one embodiment, as shown in FIG. 8F, the cutter 802 can be tucked inside and held in place within the distal inlet when core 302 is inserted into the implant. Upon removal of the core, the cutter can swing outwards into the position shown in FIG. 8D.

As shown in FIG. 8E, cutter 802 can be a triangular shape. Other variations on the design can also be used, such as a serrated edge cutter 806, as shown in FIG. 8G, a rectangular cutter, a semicircular shaped cutter 808, as shown in FIG. 8H, or any other appropriately shaped cutter as long as the cutter is sharp enough to penetrate through tissue. In the embodiment of a serrated cutter, the trabecular meshwork and Schlemm's canal can be cut by moving the implant back and forth to slice through tissue and introduce the implant into the anterior chamber, for example.

FIGS. 8I-8K show an alternative embodiment of a self-piercing distal inlet having a hatch 810 that engages the core 302. The hatch comprises an arm that hingedly connects the hatch to the implant. In FIG. 81, when core 302 is disposed within the implant, it engages hatch 810 to cause the hatch to be flush with the body of the implant, so that the hatch is generally coaxial with the implant. FIG. 8J illustrates a cross section of hatch 810 being flush with the implant while core 302 is disposed in the implant. It can be seen that at least a portion of the hatch extends around a portion of the core across a radial span of more than 180 degrees. When the core is removed from the implant, the hatch can be heat set or shape set to assume a predetermined shape, as shown in FIG. 8K.

In FIG. 8K, hatch 810 is shown in a fully extended or "swung out" position due to removal of the core from the implant. This extended position causes the hatch to be skewed relative to the longitudinal axis of the implant. The hatch can be biased to assume this extended position, for example. The hatch can have a sharp tip or edge to slice through tissue, such as Schlemm's canal and/or the trabecular meshwork, to gain access to the anterior chamber of the eye.

In FIG. 10, a cannula 306 is shown extending through an incision 404 in the cornea of an eye. In the embodiment of FIG. 10, an implant 100 has been advanced into the eye so that a distal end of the implant is disposed in the suprachoroidal space 1002 of the eye. FIG. 10 also includes a view of sclera 90, ciliary body 92, and choroid 94 of the eye. The distal end of the implant can be distal inlet 101B, as described above. In another embodiment, the distal end of the implant does not have to be distal inlet 101B, but rather can share the same structural design as an intermediate portion of the implant, as described above. A method associated with inserting implant 100 into the suprachoroidal space 1002 of the eye can include the various delivery system components described herein, including core 302, cannula 306, and guide wire 314, for example.

FIG. 11 is an additional partial cross-sectional view of the eye shown in the previous figure. In the embodiment of FIG.

and incision 404 in the cornea has closed. Implant 100 is positioned so that its distal end is disposed in suprachoroidal space 1002 of the eye and the proximal end of implant 100 is disposed in the anterior chamber. When this is the case, aqueous humor can flow along the surface of implant 100. In this way, implant 100 allows aqueous humor to leave anterior chamber 70 and enter suprachoroidal space 1002. Numerous veins and arteries are located in suprachoroidal space. Accordingly, aqueous humor entering the suprachoroidal space can be absorbed into the bloodstream by passing through the walls of small blood vessels. This excess aqueous humor can then be carried away be venous blood leaving the eye.

In the methods described above, the predetermined shape of the implant, core, and/or guide wire will typically self align the implant in Schlemm's canal. However, the implant may additionally be rotated within Schlemm's canal to attain the appropriate orientation.

While exemplary embodiments of the present invention 20 have been shown and described, modifications may be made, and it is therefore intended in the appended claims to cover all such changes and modifications which fall within the true spirit and scope of the invention.

What is claimed is:

- 1. An ocular implant defining a generally cylindrical volume, comprising:
 - a proximal inlet portion at a proximal end of the implant adapted to be positioned in an anterior chamber of an eye;
 - a distal inlet portion at a distal end of the implant, the distal inlet portion being biased to bend at a first radius of curvature in a first plane;
 - an intermediate portion positioned between the proximal inlet portion and the distal inlet portion, the intermediate 35 portion being biased to bend at a second radius of curvature in the first plane; and
 - a plurality of openings in the implant to facilitate fluidic flow laterally across the elongate implant.
- 2. The implant of claim 1 wherein the implant defines a 40 lumen to facilitate fluidic flow longitudinally along the implant.
- 3. The implant of claim 1 wherein the first radius of curvature is smaller than the second radius of curvature.
- 4. The implant of claim 1 wherein the second radius of 45 curvature approximates the curvature of Schlemm's canal.
- 5. The implant of claim 1 wherein the proximal portion is biased to bend at a third radius of curvature.
- 6. The implant of claim 5 wherein the third radius of curvature is generally smaller than the second radius of curvature.
- 7. The implant of claim 5 wherein the third radius of curvature is generally equal to the first radius of curvature.
- 8. The implant of claim 1 wherein the plurality of openings extend over more than about 50% of an outer surface area of 55 the implant.
- 9. An ocular implant defining a generally cylindrical volume, comprising:
 - a proximal inlet portion at a proximal end of the implant, the proximal inlet portion adapted to be positioned in an 60 anterior chamber of the eye;
 - a distal inlet portion at a distal end of the implant, the distal inlet portion adapted to be positioned in the anterior

16

chamber of the eye, the distal inlet portion being biased to bend at a first radius of curvature in a first plane;

- an intermediate portion positioned between the proximal and distal inlet portions, the intermediate portion adapted to be positioned in Schlemm's canal, the intermediate portion being biased to bend at a second radius of curvature in the first plane; and
- a plurality of openings in the implant to facilitate fluidic flow laterally across the implant.
- 10. The implant of claim 9 wherein the implant defines a lumen to facilitate fluidic flow longitudinally along the implant.
 - 11. An ocular implant, comprising:
 - a proximal locking portion at a proximal end of the implant, the proximal end of the implant including a proximal inlet portion adapted to be positioned in an anterior chamber of an eye;
 - a distal locking portion at a distal end of the implant;
 - an intermediate portion extending between the proximal locking portion and the distal locking portion;
 - the intermediate portion having a longitudinal axis that follows an arcuate path in a first plane when the implant is assuming a relaxed shape;
 - wherein the proximal locking portion is biased to extend in a first radially inward direction relative to the arcuate path of the longitudinal axis of the intermediate portion; and
 - wherein the distal locking portion is biased to extend in a second radially inward direction in the first plane relative to the arcuate path of the longitudinal axis of the intermediate portion.
- 12. The implant of claim 11 wherein the first radially inward direction and the second radially inward direction both lead out of Schlemm's canal of an eye when the intermediate portion of the implant is disposed in Schlemm's canal of the eye.
- 13. The implant of claim 11 wherein the implant is dimensioned so that the proximal locking portion and the distal locking portion will both extend through a wall of Schlemm's canal of an eye when the intermediate portion of the implant is disposed in Schlemm's canal of the eye.
- 14. The implant of claim 11 wherein the likelihood that the intermediate portion of the implant will migrate within Schlemm's canal of an eye is reduced when the proximal locking portion and the distal locking portion both extend through a wall of Schlemm's canal.
- 15. The implant of claim 11 wherein the first radially inward direction and the second radially inward direction both lead out of Schlemm's canal of an eye when the longitudinal axis of the intermediate portion is coaxial with a longitudinal axis of Schlemm's canal.
- 16. The implant of claim 11 wherein a radius of curvature of the longitudinal axis of the intermediate portion approximates the curvature of Schlemm's canal when the implant is assuming the relaxed shape.
- 17. The implant of claim 11 wherein a wall of the implant defines a plurality of openings in the implant to facilitate fluidic flow laterally across the implant.
- 18. The implant of claim 11 wherein the implant defines a lumen to facilitate fluidic flow longitudinally along the implant.

* * * * *