

US009077230B2

(12) **United States Patent**
Lau et al.

(10) **Patent No.:** **US 9,077,230 B2**
(45) **Date of Patent:** **Jul. 7, 2015**

(54) **ELECTRIC MOTOR WITH HEAT DISSIPATING DEVICE**
(75) Inventors: **James Ching Sik Lau**, Hong Kong (CN); **Xiao Jun Yang**, Shenzhen (CN)
(73) Assignee: **JOHNSON ELECTRIC S.A.**, Murten (CH)

3,226,580 A * 12/1965 Oehlich et al. 310/57
3,809,935 A * 5/1974 Kristen et al. 310/68 R
6,177,740 B1 * 1/2001 Burns 310/68 R
6,891,292 B2 5/2005 Raster et al.
2003/0184172 A1 * 10/2003 Ghiotto 310/89
2004/0164625 A1 * 8/2004 Grundl et al. 310/16
2007/0241630 A1 * 10/2007 Holmes et al. 310/217

(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 140 days.

FOREIGN PATENT DOCUMENTS

CN 1477758 A 2/2004
DE 19723664 A1 * 12/1997

(Continued)

(21) Appl. No.: **13/106,976**

(22) Filed: **May 13, 2011**

(65) **Prior Publication Data**
US 2011/0278970 A1 Nov. 17, 2011

OTHER PUBLICATIONS

Machine Translation JP06169554 (1994).*
(Continued)

(30) **Foreign Application Priority Data**
May 13, 2010 (CN) 2010 1 0175604

Primary Examiner — Jose Gonzalez Quinone
(74) *Attorney, Agent, or Firm* — Muncy, Geissler, Olds & Lowe, P.C.

(51) **Int. Cl.**
H02K 9/00 (2006.01)
H02K 9/06 (2006.01)
H02K 11/00 (2006.01)
H02K 5/18 (2006.01)

(57) **ABSTRACT**

An electric motor has a stator and a rotor rotatably mounted in the stator. The stator includes a stator core and stator windings. A heat dissipating device is mounted around an outer surface of the stator core and configured to absorb heat therefrom. The heat dissipating device includes a base mounted around the stator core and a plurality of fins extending outwardly from the base in the radial direction. Electronic components are mounted on the heat dissipating device. A fan is mounted on a shaft of the rotor for generating a flow of air inside the stator and through slots between the fins to thereby cool the rotor, stator core, stator windings and electronic components.


(52) **U.S. Cl.**
CPC **H02K 11/0073** (2013.01); **H02K 5/18** (2013.01); **H02K 9/06** (2013.01)

(58) **Field of Classification Search**
CPC H02K 9/00; H02K 9/06; H02K 5/18
USPC 310/58, 60 R, 64, 67 R, 68 B, 68 C, 68 D, 310/62, 63
See application file for complete search history.

(56) **References Cited**
U.S. PATENT DOCUMENTS

2,845,694 A * 8/1958 Le Tourneau 242/445.1
3,200,275 A * 8/1965 Lindgren 310/90

16 Claims, 2 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2007/0284157 A1 * 12/2007 Heller et al. 180/54.1
2009/0230792 A1 * 9/2009 Goetze et al. 310/71

FOREIGN PATENT DOCUMENTS

JP 58-212343 A 12/1983
JP 04087547 A * 3/1992
JP 06169554 A * 6/1994

JP 8-205461 A 8/1996
JP 09093865 A * 4/1997
JP 09252563 A * 9/1997
JP 2002281698 A * 9/2002
JP 2004-222428 A 8/2004
WO WO 2009143946 A1 * 12/2009

OTHER PUBLICATIONS

Machine Translation JP09093865 (1997) and WO2009143946 (2009).*

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4

1**ELECTRIC MOTOR WITH HEAT
DISSIPATING DEVICE****CROSS REFERENCE TO RELATED
APPLICATIONS**

This non-provisional patent application claims priority under 35 U.S.C. §119(a) from Patent Application No. 201010175604.1 filed in The People's Republic of China on May 13, 2010.

FIELD OF THE INVENTION

This invention relates to an electric motor and in particular, to an electric motor with a heat dissipating device.

BACKGROUND OF THE INVENTION

Generally, small electric motors, such as PMDC motors and electronically commutated DC motors, comprise a stator, a rotor disposed within the stator and a circuit board on which a plurality of electronic components is mounted. The electronic components such as power transistors generate heat during operation of the motor. Usually, an additional heat dissipating device for the electronic components is provided inside the stator. However, the internal space of the motor is limited which limits the size and cooling efficiency of the heat dissipating device.

Hence there is a desire for an electric motor with an improved heat dissipating device for electronic components thereof.

SUMMARY OF THE INVENTION

Accordingly, in one aspect thereof, the present invention provides an electric motor comprising: a stator comprising a stator core and stator windings; a rotor rotatably mounted in the stator and having a shaft; a heat dissipating device mounted around an outer surface of the stator core and configured to absorb heat there from; and electronic components mounted to the heat dissipating device.

Preferably, the heat dissipating device comprises a base mounted around the stator core and a plurality of fins extending radially outwardly from the base.

Preferably, a fan is mounted on the shaft and arranged to generate a flow of air through the inside of the stator core and through slots between the fins.

Preferably, the motor comprises a first end cap located at an axial end of the stator, and the fan is located adjacent an outer side of the first end cap.

Preferably, ends of the fins adjacent the fan axially extend beyond the first end cap to form a receiving space between the ends of the fins and the first end cap, and the fan is located in the receiving space.

Alternatively, the diameter of the fan is larger than the diameter of the base of the heat dissipating device, and the fan is axially spaced from the fins.

Preferably, the motor comprises a second end cap and a plurality of locking members for fixing the end caps to the stator core, the locking members extending through the interior of the stator core.

Preferably, the motor comprises a circuit board to which the electronic components are connected.

Preferably, the electronic components comprise transistors mounted on the heat dissipating device, leads of the transistors being connected to the circuit board.

2

Preferably, the motor comprises a housing mounted on the outer surface of the stator core and the heat dissipating device is mounted on the housing.

BRIEF DESCRIPTION OF THE DRAWINGS

A preferred embodiment of the invention will now be described, by way of example only, with reference to figures of the accompanying drawings. In the figures, identical structures, elements or parts that appear in more than one figure are generally labeled with a same reference numeral in all the figures in which they appear. Dimensions of components and features shown in the figures are generally chosen for convenience and clarity of presentation and are not necessarily shown to scale. The figures are listed below.

FIG. 1 is an isometric view of a small electronically commutated electric motor in accordance with a first preferred embodiment of the present invention;

FIG. 2 is an axial sectional view of the motor of FIG. 1;

FIG. 3 is an isometric view of a similar motor in accordance with a second preferred embodiment of the present invention; and

FIG. 4 is an axial sectional view of a similar motor in accordance with a third preferred embodiment of the present invention.

**DETAILED DESCRIPTION OF THE PREFERRED
EMBODIMENTS**

FIGS. 1 and 2 illustrate a small electronically commutated electric motor, also known as a brushless DC motor, according to a preferred embodiment of the present invention. The term brushless DC motor refers to a motor which has no commutator and is designed to be operated by DC power through the use of electronics to electronically commutate the power supplied to the motor windings. The electronics power the windings with a chopped DC waveform. Recently, the term brushless AC motor has been coined to refer to a brushless DC motor in which the power supplied to the motor windings by the electronics more closely resembles a sinusoidal waveform than a chopped DC waveform. However, the term electronically commutated motor encompass both AC and DC brushless motors while the term brushless AC motor generally covers a special type or subset of brushless DC motors.

The motor comprises a stator **10** and a rotor **40** rotatable relative to and accommodated within the stator **10**. The rotor **40** comprises a shaft **42**, a rotor core **44** fixed to the shaft **42**, and magnets **46** fixed to the radially outer surface of the rotor core **44**. The stator **10** comprises a stator core **12** made of magnetic material such as iron. The stator core **12** comprises a yoke **16** and a plurality of teeth extending inwardly from the yoke. Stator windings **14** are wound around the teeth.

A heat dissipating device **18** is provided at the outer surface of the yoke **16**. Preferably, the heat dissipating device **18** comprises a cylindrical base **182** and a plurality of spaced fins **184** extending radially and axially from the outer surface of the base **182**. The base **182** is mounted on the outer surface of the yoke **16** and has a pair of axial projections **186** formed at one end thereof. Preferably, the base **182** is a press fit on the yoke **16**.

The stator **10** further comprises two end caps **20**, **22** and several locking members **24** for fixing the end caps **20**, **22**. The locking members **24** extend through the interior of the stator. Preferably, the locking members **24** extend through respective slots formed between adjacent teeth of the stator core.

3

The motor further comprises a circuit board **32** and a plurality of electronic components such as power transistors **33** connected to the circuit board **32**. The circuit board **32** is located adjacent to and fixed relative to one end cap **20**. The transistors **33** are mounted to the outer surface of the projections **186** of the base **182** of the heat dissipating device **18** and leads **34** of the transistors **33** are fixed to the circuit board **32**. The transistors may be any suitable power transistors such as MOSFETs.

Ends of the fins **184** remote from the axial projections **186** extend beyond the other end cap **22** in the axial direction. A receiving space is formed between the ends of the fins **184** and the end cap **22**. A fan **48** is mounted on one end of the shaft **42** and located in the receiving space. Preferably, the fan **48** is a centrifugal fan comprising several vanes **49** extending radially. When the motor is in operation, airflow generated by the fan **48** flows into the slots formed between adjacent teeth of the stator and the space between the stator and the rotor, then flows out from the end of the motor adjacent to the fan **48** and through the airflow passage formed between the vanes **49** of the fan **48** to thereby cool the rotor core **44**, magnets **46**, and the stator windings **14**. The air exiting from the fan **48** flows through slots formed between the ends of the fins **184** and carries heat away from the fins **184**. Thus, heat generated by the transistors **33** is rapidly conducted to the heat dissipating device **18** and then dissipated to the environment. The heat generated within the stator core is partially dissipated through the heat dissipating device **18**.

Alternatively, the air may flow in the opposite direction.

FIG. **3** shows an electric motor in accordance with a second embodiment of the present invention. The electric motor is similar to the one shown in FIG. **1**. However, in this embodiment, the circuit board **32** and the axial projections **186** of the heat dissipating device **18** are located adjacent the fan **48**. Also, the diameter of the fan **48** is larger than that of the base **182** of the heat dissipating device **18**. The fan **48** is mounted on the end of the shaft **42** and is located outside of the fins **184**. When the motor is in operation, airflow generated by the fan **48** flows through the slots formed between adjacent teeth of the stator and the space between the stator and the rotor, and then flows out from the end of the motor through the fan **48**. The fan also induces air to flow between the fins **184**, thereby cooling the rotor core **44**, magnets **46**, stator core **12**, stator windings **14** and transistors **33**.

In the above-mentioned embodiments, the base **182** of the heat dissipating device **18** is mounted on the outer surface of the stator core **12** directly.

FIG. **4** illustrates an alternative arrangement in which a housing **19** is mounted on the outer surface of the stator core **12** and the heat dissipating device **18** is mounted on the housing **19**. The motor of this third preferred embodiment is similar to the motor of FIG. **1** with the exception of the additional housing **19**. The housing **19** may be considered as an additional part of the stator core **12**. Preferably, the housing **19** is thermally and magnetically conductive and forms a part of the heat path between the stator core and the heat dissipating device as well as a part of the magnetic flux path of the stator. This is specially useful when the stator core is a segmented stator core.

The electric motor of the present invention is suitable for power tools such as drills.

In the description and claims of the present application, each of the verbs “comprise”, “include”, “contain” and “have”, and variations thereof, are used in an inclusive sense, to specify the presence of the stated item but not to exclude the presence of additional items.

4

Although the invention is described with reference to one or more preferred embodiments, it should be appreciated by those skilled in the art that various modifications are possible. Therefore, the scope of the invention is to be determined by reference to the claims that follow.

For example, although the present invention has been described with reference to a small electronically commutated motors, the invention is also applicable to servo motors, stepper motors and other types of electric motors having heat generating electronic components.

The invention claimed is:

1. An electric motor comprising:

a stator comprising a stator core and stator windings;
a rotor rotatably mounted in the stator and having a shaft;
a heat dissipating device mounted around an outer surface of the stator core and configured to absorb heat therefrom, the heat dissipating device comprising a substantially cylindrical base mounted around the stator core, and a plurality of fins extending radially outwardly from an outer periphery of the base, wherein the base has a first axial end and a second axial end opposite to the first axial end, the base has an opening at the second axial end, and the plurality of fins define a plurality of air passages extending from positions adjacent to the first axial end towards the second axial end of the base;
a circuit board located at the opening of the base, the circuit board having a through hole at a central portion thereof;
an end cap located at an outer side of the circuit board such that the circuit board is located between the end cap and the stator, the end cap fixed to the stator and having a bearing supporting the shaft of the rotor;
at least one electronic component mounted to a radially outer surface of the base of the heat dissipating device adjacent to the second axial end of the base, and aligned to at least one air passage of the heat dissipating device in an axial direction of the stator; and
a fan mounted on the shaft and arranged to generate a flow of air through an interior of the stator core and the air passages between the fins,
wherein the at least one electronic component is electrically connected to the circuit board, and
wherein the plurality of fins have first ends extend axially beyond the end cap, defining a receiving space between the first ends of the plurality of fins and the end cap, and wherein the fan is completely located in the receiving space.

2. The motor of claim **1**, wherein the fan is located adjacent to an outer side of the end cap.

3. The motor of claim **2**, wherein the diameter of the fan is larger than the diameter of the base of the heat dissipating device, and the fan is axially spaced from the fins.

4. The motor of claim **1**, further comprising a housing mounted on the outer surface of the stator core and the base of the heat dissipating device is mounted on the housing.

5. The motor of claim **1**, wherein the base comprises at least one projection at an lateral periphery thereof, and the at least one electronic component is mounted to an outer surface of the at least one projection of the base.

6. The motor of claim **1**, wherein the first ends of the plurality of fins extend radially inward at an end surface of the axial end of the base, and each fin has an increased radial width at the first end with respect to the remaining portions.

7. An electric motor comprising:

a stator comprising a stator core and stator windings wound on the stator core;
a rotor rotatably mounted in the stator and having a shaft;

5

a heat dissipating device mounted around an outer surface of the stator core and having a substantially cylindrical base surrounding the stator core and a plurality of fins extending radially outwardly from an outer periphery of the base, wherein the base has an axial end;

a circuit board located at the axial end of the base;

a fan arranged to generate an airflow flows between the plurality of fins; and

at least one electronic component mounted to and thermally contacting an outer surface of the base of the heat dissipating device adjacent to the circuit board, wherein the at least one electronic component has conductive portions extending over a circumferential surface of the circuit board and electrically connected to the circuit board, the circumferential surface is parallel to the shaft, wherein at least one of the plurality of fins has a first axial end adjacent to the electronic component and a second axial end located farther from the electronic component than the first axial end, and

wherein the fan and the plurality of fins are located at two axial ends of the at least one electronic component, respectively.

8. The motor of claim 7, wherein the base has an another axial end opposite to the axial end, the plurality of fins have first ends extending axially beyond the another axial end of the base.

9. The motor of claim 7, further comprising a housing mounted on the outer surface of the stator core and the base of the heat dissipating device is mounted on the housing.

6

10. The motor of claim 7, wherein the base comprises at least one projection at an lateral periphery thereof, and the at least one electronic component is mounted to an outer surface of the at least one projection of the base.

11. The motor of claim 7, wherein the at least one of the plurality of fins is axially aligned with the at least one electronic component.

12. The motor of claim 1, wherein at least one of the fins has a radially outmost end which is located farther from the stator core than a radially outmost end of the at least one electronic component.

13. The motor of claim 1, wherein the at least one electronic component and the fan are located at two axial ends of the plurality of fins, respectively.

14. The motor of claim 1, wherein the fan and the fins are located at two axial ends of the at least one electronic component, respectively.

15. The motor of claim 1, further comprising an another end cap and a plurality of locking members, wherein the stator core has a plurality of teeth spaced from each other with a plurality of slots defined between the plurality of teeth, the locking members extend through respective slots and connect the end cap and the another end cap together.

16. The motor of claim 4, wherein the outer surface of the stator core forms a plurality of ribs extending in axial direction of the stator core, the ribs are spaced along a circumferential direction of the stator core, and the base is press fitted on the ribs of the stator core.

* * * * *