



US009082141B2

(12) **United States Patent**
Meyerhofer et al.

(10) **Patent No.:** **US 9,082,141 B2**
(45) **Date of Patent:** **Jul. 14, 2015**

- (54) **SYSTEMS AND METHODS TO IMPLEMENT DEMAND RESPONSE EVENTS**
- (75) Inventors: **Mark Joseph Meyerhofer**, Acworth, GA (US); **James Joseph Schmid**, Acworth, GA (US); **Jerry Steven Massey**, Lawrenceville, GA (US); **Jaime Alberto Sierra**, Atlanta, GA (US)
- (73) Assignee: **General Electric Company**, Schenectady, NY (US)
- (*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 927 days.

3,906,242 A	9/1975	Stevenson
3,925,680 A	12/1975	Dixon
3,995,686 A	12/1976	Laube
4,031,406 A	6/1977	Leyde et al.
4,059,747 A	11/1977	Brody
4,100,426 A	7/1978	Baranowski et al.
4,117,537 A	9/1978	Muench
4,125,782 A	11/1978	Pollnow, Jr.
4,197,468 A	4/1980	Reid, Jr.
4,310,770 A	1/1982	Keener et al.
4,804,938 A	2/1989	Rouse et al.
4,847,781 A	7/1989	Brown, III et al.
5,381,462 A	1/1995	Larson et al.
5,687,139 A	11/1997	Budney
6,018,690 A	1/2000	Saito et al.
6,064,420 A	5/2000	Harrison et al.
6,078,785 A	6/2000	Bush

(Continued)

- (21) Appl. No.: **13/283,390**
- (22) Filed: **Oct. 27, 2011**

OTHER PUBLICATIONS

Tsikalakakis et al., "Centralized Control for Optimizing Microgrids Operation", IEEE, Jul. 24-29, 2011, pp. 1-8.

(Continued)

- (65) **Prior Publication Data**
US 2013/0110305 A1 May 2, 2013

Primary Examiner — Sean Shechtman
(74) *Attorney, Agent, or Firm* — Armstrong Teasdale LLP

- (51) **Int. Cl.**
G05D 17/00 (2006.01)
G06Q 30/06 (2012.01)
G06Q 50/06 (2012.01)

(57) **ABSTRACT**

A computing device for use with a demand response system is provided. The computing device includes a communication interface for receiving customer data of a plurality of customers, wherein the customer data includes at least a location, a policy limitation, a participation history, and an enrollment status for each customer. A processor is coupled to the communication interface and programmed to select at least one participant from the plurality of customers, based on the customer data, to participate in at least one demand response event. The processor is further programmed to verify that the selected participant, based on the customer data, satisfies at least one precondition to receive at least one signal representative of the demand response event.


- (52) **U.S. Cl.**
CPC **G06Q 30/06** (2013.01); **G06Q 50/06** (2013.01)

- (58) **Field of Classification Search**
CPC . H02J 3/14; H02J 2003/146; H02J 2003/143; Y02B 70/3225; Y02B 70/3266; Y02B 90/245; Y04S 20/222; Y04S 20/242; Y04S 10/126; Y04S 20/224; Y04S 30/12; G06F 1/26; G06F 1/3203; G06F 1/3234
See application file for complete search history.

- (56) **References Cited**
U.S. PATENT DOCUMENTS

3,678,284 A	7/1972	Peters
3,872,286 A	3/1975	Putman

17 Claims, 3 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

6,098,050 A 8/2000 Knoblock et al.
 6,138,461 A 10/2000 Park et al.
 6,528,957 B1 3/2003 Luchaco
 6,697,951 B1 2/2004 Sinha et al.
 6,900,738 B2 5/2005 Crichlow
 6,909,942 B2 6/2005 Andarawis et al.
 7,019,496 B1 3/2006 Garretson
 7,039,532 B2 5/2006 Hunter
 7,123,994 B2 10/2006 Weik et al.
 7,181,320 B2 2/2007 Whiffen et al.
 7,206,670 B2 4/2007 Pimputkar et al.
 7,274,305 B1 9/2007 Luttrell
 7,310,620 B2 12/2007 Moore et al.
 7,333,982 B2 2/2008 Bakalash et al.
 7,373,221 B2 5/2008 Lal
 7,373,222 B1 5/2008 Wright et al.
 7,392,115 B2 6/2008 Schindler
 7,561,681 B2 7/2009 Booth et al.
 7,565,227 B2 7/2009 Richard et al.
 7,653,443 B2 1/2010 Flohr
 7,660,649 B1 2/2010 Hope et al.
 7,715,951 B2 5/2010 Forbes, Jr. et al.
 7,743,001 B1 6/2010 Vermeulen et al.
 7,778,738 B2 8/2010 Taft
 7,885,917 B2 2/2011 Kuhns et al.
 7,945,466 B2 5/2011 Klett et al.
 7,962,248 B2 6/2011 Flohr
 8,219,258 B1 7/2012 Almeida et al.
 2001/0010032 A1 7/2001 Ehlers et al.
 2001/0014976 A1 8/2001 Roop et al.
 2001/0034236 A1 10/2001 Tong et al.
 2002/0072868 A1 6/2002 Bartone et al.
 2003/0125843 A1 7/2003 Prasad
 2003/0167178 A1 9/2003 Jarman et al.
 2004/0075343 A1 4/2004 Wareham et al.
 2004/0088083 A1 5/2004 Davis et al.
 2004/0107259 A1 6/2004 Wallace et al.
 2005/0165511 A1 7/2005 Fairlie
 2005/0240668 A1 10/2005 Rolia et al.
 2006/0143483 A1 6/2006 Liebenow

2007/0177319 A1 8/2007 Hirst
 2007/0260359 A1 11/2007 Benson et al.
 2008/0167756 A1 7/2008 Golden et al.
 2008/0177678 A1 7/2008 Di Martini et al.
 2009/0018706 A1 1/2009 Wittner
 2009/0187499 A1 7/2009 Mulder et al.
 2009/0194601 A1 8/2009 Flohr
 2009/0240964 A1 9/2009 Pfeiffer
 2009/0256686 A1 10/2009 Abbot et al.
 2009/0295594 A1 12/2009 Yoon
 2009/0326726 A1 12/2009 Ippolito et al.
 2010/0017045 A1 1/2010 Nesler et al.
 2010/0088261 A1 4/2010 Montalvo
 2010/0107173 A1 4/2010 Chassin
 2010/0138065 A1 6/2010 Taft
 2010/0145540 A1 6/2010 Mckenna
 2010/0179704 A1 7/2010 Ozog
 2010/0179862 A1 7/2010 Chassin et al.
 2010/0217550 A1 8/2010 Crabtree et al.
 2010/0286937 A1 11/2010 Hedley et al.
 2010/0332373 A1 12/2010 Crabtree et al.
 2011/0125542 A1 5/2011 Koch
 2011/0196546 A1 8/2011 Muller et al.
 2011/0202217 A1 8/2011 Kempton
 2011/0258018 A1 10/2011 Tyagi et al.
 2012/0004786 A1 1/2012 Lo et al.
 2012/0022709 A1 1/2012 Taylor
 2012/0116600 A1 5/2012 Schmid et al.
 2012/0130556 A1 5/2012 Marhoefer
 2012/0136496 A1 5/2012 Black et al.
 2012/0310860 A1 12/2012 Kim et al.
 2012/0323393 A1 12/2012 Imhof et al.
 2013/0035883 A1 2/2013 San Andreas et al.
 2013/0254151 A1 9/2013 Mohagheghi et al.
 2014/0062195 A1* 3/2014 Bruschi et al. 307/38

OTHER PUBLICATIONS

Kok et al., "PowerMatcher: Multiagent Control in the Electricity Infrastructure", AAMAS, 2005, pp. 75-82.
 Ilic, M.D., "From Hierarchical to Open Access Electric Power System", IEEE, 2007, pp. 1060-1084.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3

SYSTEMS AND METHODS TO IMPLEMENT DEMAND RESPONSE EVENTS

BACKGROUND OF THE INVENTION

The field of the invention relates generally to demand response systems and, more particularly, to a computing device for use with a demand response system that enables a utility to implement demand response events.

As the human population increases around the world and with an increase in the use of electric vehicles by customers, energy demand will also likely increase. More specifically, energy demand will likely increase in the form of electrical energy used to power buildings, homes, and/or to charge batteries or other energy sources used in electric vehicles. Moreover, the demand on the power grid is likely to increase while the demand for fuel decreases. Such demands will likely cause an increase in the price of energy from the power grid. In particular, the price of energy is likely to increase during peak times, such as a time of day and/or a day of the week, when demand for energy is high.

Currently, at least some known utilities use demand response systems that enable customers to enroll in at least one demand response program to manage the consumption of energy by their customers in response to supply conditions. Examples of demand response programs include a direct control program, a peak pricing program, such as a critical peak pricing program, and a time of use program. The initiation and/or implementation of a demand response program by a utility is known as a demand response event. A demand response event is initiated by a utility transmitting a plurality of signals to its customers. For example, a demand response event representative of a direct load control program, is initiated when the utility transmits a signal to a device within a building, such as an in-home smart device and/or smart thermostat, such that the utility is enabled to directly control the usage of energy consuming machines within the building. A demand response event representative of a critical peak pricing program occurs when the utility transmits pricing signals to its customers during peak demand times. The pricing signals enable the utility to apprise customers of heightened energy prices during peak demand time periods such that customers may limit their energy consumption during such peak demand time periods. A demand response event representative of a time of use program occurs when the utility transmits a signal to a customer that is representative of energy prices that correspond to a time range such that the customer may identify an optimal time of day and/or day of the week to consume energy to ensure a low energy price rate.

Such demand response systems enable the utility to manage peak load conditions and to reduce energy demand and/or consumption among its customers. More specifically, utilities manage peak load conditions by scheduling a fixed number of demand response events per day, week, and/or month for their customers. However, current demand response systems are unable to target specific customers for participating in a scheduled demand response event and, as a result, all the customers may receive signals from the utility that are representative of a demand response event. For example, current demand response systems are unable to select and/or identify customers based on various factors, such as an enrollment status in various demand response programs and/or a geographic location for each customer. As a result, some of the customers may be unnecessarily burdened with receiving the signal, as they may not have agreed to participate in the scheduled event and/or they may not reside in an appropriate location for participating in the scheduled event. Even if

specific customers may be selected to receive the signals from the utility, current demand response systems are unable to validate or verify whether such customers are appropriate for receiving the signals. For example, some of the selected customers may have a policy limitation in their agreements with the utility in which each customer may only receive a signal once a day that is representative of a demand response event. As such, if the utility transmits more than one signal to such customers, the utility would be in violation of the agreements. Without validating or verifying the customers, the utility also cannot take into account any changes in a participation history for each customer for participating in demand response events, changes in an enrollment status, and/or changes in a policy limitation.

BRIEF DESCRIPTION OF THE INVENTION

In one embodiment, a computing device for use with a demand response system is provided. The computing device includes a communication interface for receiving customer data of a plurality of customers, wherein the customer data includes at least a location, a policy limitation, a participation history, and an enrollment status for each customer. A processor is coupled to the communication interface and programmed to select at least one participant from the plurality of customers, based on the customer data, to participate in at least one demand response event. The processor is further programmed to verify that the selected participant, based on the customer data, satisfies at least one precondition to receive at least one signal representative of the demand response event.

In another embodiment, a demand response system is provided. The demand response system includes a data management system that includes a database that includes customer data of a plurality of customers. The customer data includes at least a location, a policy limitation, a participation history, and an enrollment status for each customer. A computing device is coupled to the data management system. The computing device includes a communication interface for receiving the customer data. A processor is coupled to the communication interface and programmed to select at least one participant from the plurality of customers, based on the customer data, to participate in at least one demand response event. The processor is further programmed to verify that the selected participant, based on the customer data, satisfies at least one precondition to receive at least one signal representative of the demand response event.

In yet another embodiment, a method for determining participants for participating in demand response events is provided. Customer data of a plurality of customers is received, wherein the customer data includes at least a location, a policy limitation, a participation history, and an enrollment status for each customer. At least one participant of the plurality of customers is selected, based on the customer data, to participate in at least one demand response event. The method includes verifying, based on the customer data, that the selected participant has satisfied at least one precondition to receive at least one signal representative of the demand response event.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram of an exemplary demand response system;

FIG. 2 is a block diagram of an exemplary computing device that may be used with the demand response system shown in FIG. 1; and

FIG. 3 is a flow chart of an exemplary method that may be used for implementing demand response events using the computing device shown in FIG. 2.

DETAILED DESCRIPTION OF THE INVENTION

The exemplary systems and methods described herein overcome at least some known disadvantages of known demand response systems by enabling a utility to determine participants for demand response events. The embodiments described herein include a demand response system that includes a computing device, wherein the computing device includes a communication interface for receiving customer data of a plurality of customers, wherein the customer data includes at least a location, a policy limitation, a participation history, and an enrollment status for each customer. A processor is coupled to the communication interface and programmed to select at least one participant from the plurality of customers, based on the customer data, to participate in at least one demand response event. The processor is further programmed to verify that the selected participant, based on the customer data, satisfies at least one precondition to receive at least one signal representative of the demand response event. By selecting participants of the customers for participating in a demand response event and by verifying whether each participant is appropriate for receiving a signal representative of the demand response event, the burden on every customer may be substantially reduced. By verifying each of the participants, the utility is also enabled to prevent any violations of any agreements and/or policy limitations they have with their customers.

FIG. 1 illustrates a demand response system 100. In the exemplary embodiment, demand response system 100 includes a utility 104 and a computing device 106 positioned within utility 104, wherein computing device 106 enables utility 104 to communicate with customers. Alternatively, computing device 106 may be positioned at another location with respect to utility 104. Moreover, in the exemplary embodiment, computing device 106 is communicatively coupled to a plurality of buildings 108, wherein a plurality of customers may reside. It should be noted that, as used herein, the term “couple” is not limited to a direct mechanical, electrical, and/or communication connection between components, but may also include an indirect mechanical, electrical, and/or communication connection between multiple components.

More specifically, in the exemplary embodiment, computing device 106 is communicatively coupled to at least one user notification device 110 within each building 108 via a network 112 such that computing device 106 may communicate with user notification device 110. In the exemplary embodiment, user notification device 110 may be a computer, a cellular phone, and/or a smart device, including a smart box and/or smart thermostat. Alternatively, user notification device 110 may be any other device that is configured to communicate with computing device 106. In the exemplary embodiment, each user notification device 110 is connected to network 112 and thus, each customer of utility 104 who is the owner and/or user of user notification device 110, has the same network location. Alternatively, each user notification device 110 may be connected to different networks.

Each user notification device 110 includes a user interface 114 that receives at least one input from a user, such as a customer of utility 104. In the exemplary embodiment, user interface 114 may include, for example, a keyboard, a pointing device, a mouse, a stylus, a touch sensitive panel (e.g., a touch pad or a touch screen), a gyroscope, an accelerometer,

a position detector, and/or an audio input interface (e.g., including a microphone) that enables the user to input pertinent information.

Moreover, in the exemplary embodiment, each user notification device 110 includes a presentation interface 116 that presents information, such as information regarding demand response programs and/or demand response events that are received from utility 104, input events and/or validation results, to the user. In the exemplary embodiment, presentation interface 116 includes a display adapter (not shown) that is coupled to at least one display device (not shown). More specifically, in the exemplary embodiment, the display device is a visual display device, such as a cathode ray tube (CRT), a liquid crystal display (LCD), an organic LED (OLED) display, and/or an “electronic ink” display. Alternatively, presentation interface 116 may include an audio output device (e.g., an audio adapter and/or a speaker) and/or a printer.

In the exemplary embodiment, computing device 106 may communicate with each user notification device 110 using a wired network connection (e.g., Ethernet or an optical fiber), a wireless communication means, such as radio frequency (RF), e.g., FM radio and/or digital audio broadcasting, an Institute of Electrical and Electronics Engineers (IEEE®) 802.11 standard (e.g., 802.11(g) or 802.11(n)), the Worldwide Interoperability for Microwave Access (WiMAX®) standard, a cellular phone technology (e.g., the Global Standard for Mobile communication (GSM)), a satellite communication link, and/or any other suitable communication means. WiMAX is a registered trademark of WiMax Forum, of Beaverton, Oregon. IEEE is a registered trademark of the Institute of Electrical and Electronics Engineers, Inc., of New York, N.Y.

In the exemplary embodiment, user notification device 110 is configured to receive at least one signal from computing device 106 that may be representative of, for example, information related to at least one demand response program that a customer is enrolled in and/or that may be representative of a demand response event initiating and/or implementing the demand response program that the customer is enrolled in. In the exemplary embodiment, the demand response programs may include a direct load control program, a peak pricing program, such as a critical peak pricing program, and/or a time of use program.

In the exemplary embodiment, each building 108 also includes at least one machine 118. Each machine 118, in the exemplary embodiment, consumes energy, such as an appliance and/or a computer. User notification device 110 may or may not be coupled to machine 118. For example, if user notification device 110 is a smart device, then user notification device 110 may be coupled to machine 118, such as an appliance. Moreover, in the exemplary embodiment, each building 108 is coupled to a power distribution substation 120 via a plurality of conduits 121. In the exemplary embodiment, conduits 121 are fabricated from a metallic wire. Alternatively, conduits 121 may be fabricated from any other substance or compound that enables the distribution of electrical energy to each building 108.

More specifically, in the exemplary embodiment, substation 120 includes a grid 122 that is coupled to each building 108 and provides power to each building 108. In the exemplary embodiment, grid 122 is coupled to a generator 123 within a power generation system 124 that is operated by utility 104. In the exemplary embodiment, power generation system 124 includes a machine 130. Machine 130, in the exemplary embodiment, is a variable speed machine, such as a wind turbine, a hydroelectric steam turbine, a gas turbine, and/or any other machine that operates with a variable speed.

Alternatively, machine **130** may be a synchronous speed machine. In the exemplary embodiment, machine **130** includes a rotating device **132**, such as a rotor or other device. Moreover, in the exemplary embodiment, rotating device **132** rotates a drive shaft **134** that is coupled to generator **123**.

In the exemplary embodiment, utility **104** also includes a data management system **140** that is coupled to computing device **106** via network **112**. Alternatively, data management system **140** may be separate from utility **104**. Data management system **140** may be any device capable of accessing network **112** including, without limitation, a desktop computer, a laptop computer, or other web-based connectable equipment. More specifically, in the exemplary embodiment, data management system **140** includes a database **142** that includes customer data for each of the customers of utility **104**. In the exemplary embodiment, database **142** can be fully or partially implemented in a cloud computing environment such that data from the database is received from one or more computers (not shown) within utility **104** or remote from utility **104**. The customer data may include a location for each customer, such as a geographic location for each customer. The location may include a location on network **112** for each customer, and/or a location for a substation, such as substation **120**, for each customer. The customer data may also include an enrollment status for each customer for participating in at least one demand response program. For example, the data may include a selection made by each customer for at least one demand response program to participate in. The customer data may also include at least one demand response program selected by each customer for each machine **118** to participate in. The customer data may include a participation history for each customer as well. The participation history may include, for example, the previous demand response events that each customer has participated in and the actual reduction in energy consumption that resulted from the participation in each of the events. In the exemplary embodiment, the customer data may also include a policy limitation that each customer may have included in any agreement with utility **104** regarding their participation in a demand response program and/or a demand response event. For example, in a policy limitation, a customer may have agreed to participate in only one demand response event per day. Customers, for example, may have also agreed to participate in a maximum number or a minimum number of total demand response programs and/or demand response events. As such, if the utility transmits more signals to such customers than was agreed to, the utility would be in violation of the policy limitation and/or agreement.

In the exemplary embodiment, data management system **140** includes a user interface **144** that receives at least one input from a user, such as an operator and/or employee of utility **104**. In the exemplary embodiment, data management system user interface **144** may include, for example, a keyboard, a pointing device, a mouse, a stylus, a touch sensitive panel (e.g., a touch pad or a touch screen), a gyroscope, an accelerometer, a position detector, and/or an audio input interface (e.g., including a microphone) that enables the user to input pertinent information.

Data management system **140** may communicate with computing device **106** using a wired network connection (e.g., Ethernet or an optical fiber), a wireless communication means, such as radio frequency (RF), e.g., FM radio and/or digital audio broadcasting, an Institute of Electrical and Electronics Engineers (IEEE®) 802.11 standard (e.g., 802.11(g) or 802.11(n)), the Worldwide Interoperability for Microwave Access (WIMAX®) standard, a cellular phone technology (e.g., the Global Standard for Mobile communication

(GSM)), a satellite communication link, and/or any other suitable communication means. More specifically, in the exemplary embodiment, data management system **140** transmits the customer data to computing device **106**. While the customer data is shown as being stored in database **142** within data management system **140** in the exemplary embodiment, it should be noted that the customer data may be stored in another system and/or device. For example, computing device **106** may store the customer data therein.

During operation, utility **104** may transmit, for example, a questionnaire to its customers via computing device **106**. The questionnaire provides questions to each customer to answer regarding the customer and the questionnaire provides various demand response programs that each customer may elect to participate in. More specifically, in the exemplary embodiment, the questionnaire is transmitted to user notification device **110**. Each customer may input various responses to the questionnaire via user interface **114** within user notification device **110**, including selecting at least one demand response program to participate in and/or selecting at least one demand response program for machine **118** to participate in. Alternatively, utility **104** may provide such a questionnaire to its customers via other means. For example, utility **104** may send the questionnaire via mail. Moreover, customers may provide responses for the questionnaire to utility **104** via other means, as opposed to via user notification device **110**.

In the exemplary embodiment, if a customer provides his or her responses via user notification device **110**, then the information that the customer provides is transmitted to computing device **106** via network **112**. Computing device **106** then transmits the information to data management system **140**, wherein the data is stored in database **142**. If a customer provides his or her responses via other means, utility **104** may receive the information and a user, such as an employee of utility **104**, may input the data to data management system **140** via data management system user interface **144**, wherein the data may be stored in database **142**.

When utility **104** needs to initiate and/or implement a demand response program, the user may manually input the initiation and/or implementation of a demand response event that corresponds to a demand response program to computing device **106** at a particular time. The user may also manually input the names of the customers such that computing device **106** may transmit at least one signal representative of at least one demand response event to the customers that are identified by the user.

Alternatively, computing device **106** may be programmed to select at least one participant from a plurality of customers of utility **104** to participate in at least one demand response event that results in reduction of energy consumption. More specifically, as explained in more detail below, computing device **106** receives the customer data from database **142** and selects the participants based on the customer data received. When the participants have been selected, computing device **106** will then verify, based on the customer data, that each of the selected participants satisfy at least one precondition to receive at least one signal representative of the demand response event.

Computing device **106** will then schedule the demand response event for the selected participants. More specifically, in the exemplary embodiment, computing device **106** schedules a start time and/or a duration of time for the demand response event to occur on a particular day of the week. When the demand response event has been scheduled, computing device **106** will then transmit at least one signal to each selected participant that is representative of the scheduled demand response event at the scheduled time. The signals

may be transmitted to user notification device **110** such that each participant may receive the signal via presentation interface **116**. Each participant may then choose whether to participate in the demand response event via user interface **114**. By selectively targeting the participants for participating in a demand response event that is to be scheduled, the burden on every customer may be substantially reduced. By verifying each of the participants, utility **104** is also enabled to prevent any violations of any agreements and/or policy limitations they have with their customers.

In the exemplary embodiment, the customer data is frequently updated. For example, each time a participant participates in the demand response event, at least one signal representative of the participation and the actual reduction in energy consumption that resulted from the participation is transmitted to data management system **140** such that the participation history for each customer may be updated in database **142**. Alternatively, the participation history for each customer may be updated in database **142** by a user via user interface **144**. Similarly, changes in a customer's location, enrollment status, and/or policy limitation are also updated. Such information may be changed via user notification device **110** and/or provided to utility **104** via other means and manually updated in database **142** by a user via user interface **144**.

FIG. **2** is a block diagram of computing device **106**. In the exemplary embodiment, computing device **106** includes a user interface **204** that receives at least one input from a user, such as an operator and/or employee of utility **104** (shown in FIG. **1**). In the exemplary embodiment, user interface **204** includes a keyboard **206** that enables the user to input pertinent information. Alternatively, user interface **204** may include, for example, a pointing device, a mouse, a stylus, a touch sensitive panel (e.g., a touch pad or a touch screen), a gyroscope, an accelerometer, a position detector, and/or an audio input interface (e.g., including a microphone).

Moreover, in the exemplary embodiment, computing device **106** includes a presentation interface **207** that presents information, such as input events and/or validation results, to the user. In the exemplary embodiment, presentation interface **207** includes a display adapter **208** that is coupled to at least one display device **210**. More specifically, in the exemplary embodiment, display device **210** is a visual display device, such as a cathode ray tube (CRT), a liquid crystal display (LCD), an organic LED (OLED) display, and/or an "electronic ink" display. Alternatively, presentation interface **207** may include an audio output device (e.g., an audio adapter and/or a speaker) and/or a printer.

Computing device **106** also includes a processor **214** and a memory device **218**. In the exemplary embodiment, processor **214** is coupled to user interface **204**, presentation interface **207**, and to memory device **218** via a system bus **220**. In the exemplary embodiment, processor **214** communicates with the user, such as by prompting the user via presentation interface **207** and/or by receiving user inputs via user interface **204**.

Moreover, in the exemplary embodiment, processor **214** is programmed by encoding an operation using one or more executable instructions and providing the executable instructions in memory device **218**. In the exemplary embodiment, processor **214** is programmed to select at least one participant from the customers of utility **104** to participate in at least one demand response event that results in a reduction of energy consumption. More specifically, in the exemplary embodiment, processor **214** is programmed to select the participants based on the customer data. For example, processor **214** may be programmed to select the participants by considering the location of each of the customers, such as a geographic loca-

tion for each customer, a location on network **112** (shown in FIG. **1**) for each customer, and/or a location for a substation, such as substation **120** (shown in FIG. **1**), for each customer. Processor **214** may also be programmed to consider the enrollment status for each customer for participating in at least one demand response program. For example, processor **214** may consider the selection made by each customer for at least one demand response program to participate in. Processor **214** may also consider at least one demand response program selected by each customer for each machine **118** (shown in FIG. **1**) to participate in. Processor **214** may also consider the participation history for each customer, such as the previous demand response events each customer has participated in. Processor **214** may also be programmed to select the participants by considering unwanted criteria. Alternatively, processor **214** may select the participants by considering any other information about each customer that enables computing device **106** and/or demand response system **100** (shown in FIG. **1**) to function as described herein.

In the exemplary embodiment, processor **214** is also programmed to verify that the selected participants satisfy at least one precondition to receive at least one signal representative of the demand response event. Processor may be programmed with the various preconditions for the selected participants. For example, processor **214** may consider any policy limitations that the selected participants may have in any agreements with utility **104**. Processor **214** may also consider the participation history of each of the selected participants, such as participating in similar demand response events in the past. Processor **214** may also consider the enrollment status for each of the selected participants for participating in at least one demand response program, such as a selection made by each participant for at least one demand response program to participate in and/or at least one demand response program selected by each participant for each machine **118** to participate in.

Processor **214**, in the exemplary embodiment, is also programmed to schedule the demand response event when the selected participants have been verified. More specifically, processor **214** is programmed to schedule a start time for the demand response event to commence on a particular day of the week and/or processor is programmed to schedule a duration of time for the demand response event to take place on the day of the week. When the demand response event has been scheduled, processor **214** is programmed to transmit at least one signal representative of the demand response event at the scheduled time.

The term "processor" refers generally to any programmable system including systems and microcontrollers, reduced instruction set circuits (RISC), application specific integrated circuits (ASIC), programmable logic circuits (PLC), and any other circuit or processor capable of executing the functions described herein. The above examples are exemplary only, and thus are not intended to limit in any way the definition and/or meaning of the term "processor."

In the exemplary embodiment, memory device **218** includes one or more devices that enable information, such as executable instructions and/or other data, to be stored and retrieved. Moreover, in the exemplary embodiment, memory device **218** includes one or more computer readable media, such as, without limitation, dynamic random access memory (DRAM), static random access memory (SRAM), a solid state disk, and/or a hard disk. In the exemplary embodiment, memory device **218** stores, without limitation, application source code, application object code, configuration data, additional input events, application states, assertion statements, validation results, and/or any other type of data. More

specifically, in the exemplary embodiment, memory device **218** stores input data received by a user via user interface **204**, and/or information received from other components of demand response system **100**, such as from user notification device **110** (shown in FIG. 1) and/or data management system **140** (shown in FIG. 1).

Computing device **106**, in the exemplary embodiment, also includes a communication interface **230** that is coupled to processor **214** via system bus **220**. Moreover, in the exemplary embodiment, communication interface **230** is communicatively coupled to user notification device **110** and data management system **140** via network **112** (shown in FIG. 1). In the exemplary embodiment, communication interface **230** communicates with user notification device **110**, data management system **140**, and/or other components within system **100**.

During operation, when utility **104** needs to initiate and/or implement a demand response program, the user may manually input the initiation and/or implementation of a demand response event to computing device **106** at a particular time. The user may also manually input the names of the customers such that computing device **106** may transmit at least one signal representative of at least one demand response event to the customers that are identified by the user.

Alternatively, computing device **106** may be programmed to select at least one participant from the plurality of customers of utility **104** to participate in at least one demand response event that results in a reduction of energy consumption. More specifically, in the exemplary embodiment, processor **214** transmits a signal via communication interface **230** to data management system **140** to retrieve customer data from database **142**. Customer data is transmitted from database **142** to computing device **106**, wherein communication interface **230** receives the data and transmits the data to processor **214**. Processor **214** selects at least one participant of the customers, based on the customer data, for participating in at least one demand response event. More specifically, in the exemplary embodiment, processor **214** selects the participants by considering the location of each of the customers, such as a geographic location for each customer, a location on network **112** for each customer, and/or a location for a substation, such as substation **120**, for each customer. For example, the participants selected may be the customers who have the same geographic location and/or the same substation location, such as substation **120**. Processor **214** may also select the participants by considering, for example, the enrollment status for each customer for participating in at least one demand response program. For example, processor **214** may consider the selection made by each customer for at least one demand response program to participate in. Processor **214** may also consider at least one demand response program selected by each customer for each machine **118** to participate in. Processor **214** may also consider the participation history for each customer, such as the previous demand response events each customer has participated in. For example, a customer who has participated in similar demand response events in the past will likely be selected. Alternatively, processor **214** may select the participants by considering any other information about each customer that enables computing device **106** and demand response system **100** to function as described herein.

Processor **214** then verifies that the selected participants satisfy at least one precondition to receive at least one signal representative of the demand response event. In the exemplary embodiment, processor **214** may verify the selected participants by considering any policy limitations that the selected participants may have in any agreements with utility **104**. For example, a selected participant may have a policy

limitation with utility **104** for participating in only one demand response event per day. If the selected participant has already received a signal for one demand response event for that day, then the selected participant would not receive another signal. Processor **214** may also consider the participation history of each of the selected participants, such as whether the participant participated in similar demand response events in the past. For example, a selected participant who has participated in similar demand response events will likely receive a signal for the instant demand response event as opposed to participants who have never participated in similar demand response events in the past. Processor **214** may also consider the enrollment status for each of the selected participants for participating in at least one demand response program, such as a selection made by each participant for at least one demand response program to participate in and/or at least one demand response program selected by each participant for each machine **118** to participate in.

In the exemplary embodiment, the selected participants and/or the verified participants for the demand response event are presented to the user via display device **210** within presentation interface **207**. The user may accept the selected participants and/or the verified participants via user interface **204**. Alternatively, the user may make any additional changes via user interface **204**.

After the selected participants have each been verified for receiving a signal representative of the demand response event, processor **214** then schedules the demand response event. In the exemplary embodiment, processor **214** schedules a start time for the demand response event to commence on a particular day of the week and schedules the demand response event for a specific duration of time. For example, processor **214** may schedule the demand response event to start at 10:00 a.m. on Monday and to occur for a period of thirty minutes. When the demand response event has been scheduled, computing device **106** will then transmit at least one signal to each selected participant that is representative of the scheduled demand response event at the scheduled time. The signals may be transmitted to user notification device **110** such that each participant may receive the signal via presentation interface **116**. Each participant may then choose whether to participate in the demand response event via user interface **114**.

FIG. 3 is a flow chart of a method **300** that may be used for implementing demand response events using a computing device, such as computing device **106** (shown in FIGS. 1 and 2). Customer data of a plurality of customers of a utility **104** (shown in FIG. 1) is received **302**, via a communication interface **230** (shown in FIG. 2). The customer data includes at least a location, a policy limitation, a participation history, and an enrollment status for each customer. At least one participant from the plurality of customers to participate in at least one demand response event is selected **304**, via a processor **214** (shown in FIG. 2), by considering the customer data. In the exemplary embodiment, when the participant is selected **304**, the location of each customer is considered **306**.

Whether the selected participant satisfies at least one precondition to receive at least one signal representative of the demand response event is verified **308**, via processor **214**, by considering the customer data. When the participant is verified **308**, the policy limitation, the participation history, and/or the enrollment status for the selected participant are considered **310**. The demand response event is then scheduled **312** via processor **214**. A signal representative of the demand response event is then transmitted **314** to the participant at a scheduled time.

As compared to known demand response systems that are used to enable utilities to manage energy consumption, the exemplary systems and methods described herein provide a demand response system that enables a utility to effectively implement demand response events. The embodiments described herein include a demand response system that includes a computing device, wherein the computing device includes a communication interface for receiving customer data of a plurality of customers of a utility, wherein the customer data includes at least a location, a policy limitation, a participation history, and an enrollment status for each customer. A processor is coupled to the communication interface and programmed select at least one participant from the plurality of customers, based on the customer data, to participate in at least one demand response event. The processor is further programmed to verify that the selected participant, based on the customer data, satisfies at least one precondition to receive at least one signal representative of the demand response event. By selecting participants of the customers for participating in a demand response event and by verifying whether each participant is appropriate for receiving a signal representative of the demand response event, the burden on every customer may be substantially reduced. By verifying each of the participants, the utility is also enabled to prevent any violations of any agreements and/or policy limitations they have with their customers.

A technical effect of the systems and methods described herein includes at least one of: (a) receiving customer data of a plurality of customers of a utility, wherein the customer data includes at least a location, a policy limitation, a participation history, and an enrollment status for each customer; (b) selecting at least one participant from a plurality of customers to participate in at least one demand response event based on customer data; and (c) verifying, based on customer data, that at least one selected participant satisfies at least one precondition to receive at least one signal representative of at least one demand response event.

Exemplary embodiments of the systems and methods are described above in detail. The systems and methods are not limited to the specific embodiments described herein, but rather, components of the systems and/or steps of the methods may be utilized independently and separately from other components and/or steps described herein. For example, the systems may also be used in combination with other systems and methods, and is not limited to practice with only the systems as described herein. Rather, the exemplary embodiment can be implemented and utilized in connection with many other applications.

Although specific features of various embodiments of the invention may be shown in some drawings and not in others, this is for convenience only. In accordance with the principles of the invention, any feature of a drawing may be referenced and/or claimed in combination with any feature of any other drawing.

This written description uses examples to disclose the invention, including the best mode, and also to enable any person skilled in the art to practice the invention, including making and using any devices or systems and performing any incorporated methods. The patentable scope of the invention is defined by the claims, and may include other examples that occur to those skilled in the art. Such other examples are intended to be within the scope of the claims if they have structural elements that do not differ from the literal language of the claims, or if they include equivalent structural elements with insubstantial differences from the literal language of the claims.

What is claimed is:

1. A computing device for use with a demand response system, said computing device comprising:
 - a communication interface for receiving customer data of a plurality of customers, wherein the customer data includes at least a location, a policy limitation, a participation history, and an enrollment status for each customer;
 - a processor coupled to said communication interface and programmed to:
 - select at least one participant from the plurality of customers, based on the customer data and a substation location for each customer, to participate in at least one demand response event; and
 - verify that the at least one selected participant satisfies at least one precondition to receive at least one signal representative of the at least one demand response event by considering at least the policy limitation, the participation history, and the enrollment status of the at least one selected participant.
2. A computing device in accordance with claim 1, wherein said processor is further programmed to schedule at least one of a start time and a duration of time for the at least one demand response event after the at least one selected participant has been verified.
3. A computing device in accordance with claim 2, wherein said processor is further programmed to transmit the at least one signal to the at least one selected participant at the scheduled start time.
4. A computing device in accordance with claim 1, wherein said communication interface receives updated customer data of the plurality of customers.
5. A computing device in accordance with claim 1, wherein said processor is programmed to select the at least one participant based at least in part on the location of each customer.
6. A computing device in accordance with claim 1, wherein said processor is programmed to select the least one participant based at least in part on at least one of a geographic location for each customer and a location on a network for each customer.
7. A demand response system comprising:
 - a data management system comprising a database that includes customer data of a plurality of customers, wherein the customer data includes at least a location, a policy limitation, a participation history, and an enrollment status for each customer;
 - a computing device coupled to said data management system, said computing device comprising:
 - a communication interface for receiving the customer data;
 - a processor coupled to said communication interface and programmed to:
 - select at least one participant from the plurality of customers, based on the customer data and a substation location for each customer, to participate in at least one demand response event; and
 - verify that the at least one selected participant satisfies at least one precondition to receive at least one signal representative of the at least one demand response event by considering at least the policy limitation, the participation history, and the enrollment status of the at least one selected participant.
8. A demand response system in accordance with claim 7, wherein said processor is further programmed to schedule at least one of a start time and a duration of time for the at least one demand response event after the at least one selected participant has been verified.

13

9. A demand response system in accordance with claim 8, wherein said processor is further programmed to transmit the at least one signal to the at least one selected participant at the scheduled start time.

10. A demand response system in accordance with claim 7, wherein said communication interface receives updated customer data of the plurality of customers.

11. A demand response system in accordance with claim 7, wherein said processor is programmed to select the at least one participant based at least in part on the location of each customer.

12. A demand response system in accordance with claim 7, wherein said processor is programmed to select the least one participant based at least in part on at least one of a geographic location for each customer and a location on a network for each customer.

13. A method of implementing demand response events, via a computing device coupled to a data management system, the computing device including a processor programmed to perform said method, said method comprising:

receiving, via the computing device, customer data of a plurality of customers, wherein the customer data includes at least a location, a policy limitation, a participation history, and an enrollment status for each customer;

selecting, via the computing device, at least one participant from the plurality of customers to participate in at least

14

one demand response event based on the customer data and a substation location for each customer; and verifying via the computing device, that the at least one selected participant satisfies at least one precondition to receive at least one signal representative of the at least one demand response event by considering at least the policy limitation, the participation history, and the enrollment status of the at least one selected participant.

14. A method in accordance with claim 13, further comprising scheduling at least one of a start time and a duration of time for the at least one demand response event after the at least one selected participant has been verified.

15. A method in accordance with claim 14, further comprising transmitting the at least one signal to the at least one selected participant at the scheduled time.

16. A method in accordance with claim 13, wherein selecting at least one participant further comprises selecting at least one participant from the plurality of customers to participate in at least one demand response event based at least in part on the location for each customer.

17. A method in accordance with claim 13, wherein selecting at least one participant further comprises selecting at least one participant from the plurality of customers to participate in at least one demand response event based at least in part on at least one of a geographic location for each customer and a location on a network for each customer.

* * * * *