



US009082282B1

(12) **United States Patent**  
**Landefeld et al.**

(10) **Patent No.:** **US 9,082,282 B1**  
(45) **Date of Patent:** **Jul. 14, 2015**

(54) **DETERMINING USEFULNESS OF A DATA ALERT**

USPC ..... 340/506, 500  
See application file for complete search history.

(71) Applicant: **Domo, Inc.**, American Fork, UT (US)

(56) **References Cited**

(72) Inventors: **Adam Landefeld**, Lehi, UT (US); **Chris Willis**, Heber City, UT (US); **Alan Adams Winters**, Lindon, UT (US); **Dana Stott**, Pleasant Grove, UT (US)

U.S. PATENT DOCUMENTS

7,107,339 B1 \* 9/2006 Wolters ..... 709/224  
7,836,175 B2 \* 11/2010 Bronoel et al. .... 709/224  
2010/0318487 A1 \* 12/2010 Marvasti ..... 706/47

(73) Assignee: **Domo, Inc.**, American Fork, UT (US)

\* cited by examiner

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

*Primary Examiner* — Kerri McNally

(74) *Attorney, Agent, or Firm* — Raubvogel Law Office

(21) Appl. No.: **14/607,427**

(57) **ABSTRACT**

(22) Filed: **Jan. 28, 2015**

An alert may provide a user with notification when a trigger condition regarding the operation of an enterprise is satisfied. Prior to setting the alert, a proposed alert with the trigger condition may be received. The trigger condition may be compared with a database of operational data related to operation of the enterprise over a period of time to obtain historical trigger data. The historical trigger data may indicate how the proposed alert would have functioned if applied to the operational data for the period of time, for example, by indicating how many times the alert would have been triggered during the period of time. The historical trigger data may be provided to a user, and may facilitate user determination of whether the proposed alert will perform as desired. Once the desired proposed alert has been entered, the user may set the proposed alert as an actual alert.

**Related U.S. Application Data**


(60) Provisional application No. 61/932,622, filed on Jan. 28, 2014.


(51) **Int. Cl.**  
**G08B 23/00** (2006.01)  
**G08B 25/00** (2006.01)

(52) **U.S. Cl.**  
CPC ..... **G08B 25/008** (2013.01)


(58) **Field of Classification Search**  
CPC ..... G08B 25/008

**30 Claims, 12 Drawing Sheets**





**Fig. 1A**



**Fig. 1B**




Fig. 2A




Fig. 2B




Fig. 2C




Fig. 3





Fig. 4






FIG. 6






FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12

The diagram shows a table with three columns. Above the first column is the label '1310', above the second is '1320', and above the third is '1330'. A reference numeral '1300' with a curved arrow points to the table. The table has a header row and 28 data rows.

| Order Dat | Customer Seg   | Sales     |
|-----------|----------------|-----------|
| 1/2/2011  | Consumer       | 18544.67  |
| 1/2/2011  | Corporate      | 1244.19   |
| 1/2/2011  | Home Office    | 914.16    |
| 1/3/2011  | Home Office    | 872.48    |
| 1/3/2011  | Small Business | 180.36    |
| 1/4/2011  | Consumer       | 877.24    |
| 1/4/2011  | Corporate      | 10224.63  |
| 1/5/2011  | Corporate      | 30742.36  |
| 1/5/2011  | Home Office    | 1255.5    |
| 1/6/2011  | Corporate      | 214.69    |
| 1/6/2011  | Home Office    | 1039.56   |
| 1/7/2011  | Corporate      | 257.41    |
| 1/7/2011  | Home Office    | 700.73    |
| 1/7/2011  | Small Business | 7404.22   |
| 1/8/2011  | Consumer       | 6475.15   |
| 1/8/2011  | Corporate      | 458.02    |
| 1/8/2011  | Home Office    | 26235.16  |
| 1/8/2011  | Small Business | 2357.45   |
| 1/9/2011  | Consumer       | 1505.94   |
| 1/9/2011  | Corporate      | 11.57     |
| 1/9/2011  | Home Office    | 2569.39   |
| 1/9/2011  | Small Business | 1961.7915 |
| 1/10/2011 | Corporate      | 21752.01  |
| 1/10/2011 | Home Office    | 464.34    |

**Fig. 13**

**1****DETERMINING USEFULNESS OF A DATA  
ALERT****CROSS-REFERENCE TO RELATED  
APPLICATION**

The present application claims priority from U.S. Provisional Application Ser. No. 61/932,622 for "Determining Usefulness of a Data Alert," filed Jan. 28, 2014, which is incorporated by reference herein in its entirety.

**TECHNICAL FIELD**

The present document relates to mechanisms for setting alerts to notify users of the satisfaction of certain trigger conditions in the operational data of an enterprise.

**DESCRIPTION OF THE RELATED ART**

In the context of a software system, an alert is a trigger condition that can be automatically monitored so that notification can be provided to the user when the trigger condition is satisfied. The notification may be any form of output that presents information to a user at a given time or in response to satisfaction of a given trigger event, rather than output that is presented immediately in response to a user request. Possible forms of output may include emails, SMS messages, visual cues, audible tones, combinations thereof, and the like.

Many existing systems allow users to configure alerts that will notify them when some change takes place with regard to stored data. Conventionally, when a user sets a data-driven threshold or change-based alert, it may be challenging to determine an appropriate threshold or change value for the alert. Too low a threshold can result in information fatigue; too high a threshold can result in important information and events being missed. Often a user must be subscribed to an alert for several iterations before he or she can understand what causes the alert to trigger and how frequently it triggers. This makes the process of setting a useful alert relatively time consuming.

**SUMMARY**

Various embodiments of the present disclosure provide the user with an indication of how a proposed alert is likely to function on the basis of prior operational data related to an enterprise. The present disclosure may facilitate a determination of the usefulness of a data alert by examining the settings and thresholds a user may set to trigger the proposed alert, and then examining historical patterns of the data being alerted on and historical events related to the data.

More specifically, prior to setting an alert, the user may provide the proposed alert with a trigger that defines how the proposed alert is triggered. The trigger condition may include a metric, which may be a piece of data stored on a periodic basis in the operational data. Further, the trigger condition may include a threshold value and an operator such as greater than the threshold, less than the threshold, equal to the threshold, or other comparative value, such as standard deviations from the norm. The threshold may be provided as text by the user, selected on a data visualization such as a chart or graph, or by other means.

The trigger condition may be compared with a database of the operational data, relative to a period of time, to obtain historical trigger data. The historical trigger data may indicate how the proposed alert would have functioned if applied to the operational data for the period of time, for example, by

**2**

indicating how many times the alert would have been triggered during the period of time.

The historical trigger data may be provided to a user. The historical trigger data may be provided, for example, as text and/or a data visualization displayed on a display screen. The historical trigger data may be displayed as an activity indicator proximate an alert entry module. The historical trigger data may optionally include historical values for the metric. Examples of historical trigger data may include, but are not limited to:

How many times the alert would trigger.

How frequently it would trigger.

Whether it would trigger at all.

Whether the change shown would be meaningful.

Historical values such as high, low, and mean.

The system may be able to simulate the value of any given alert for the user. In at least one embodiment, the system may present a reasonable default recent period of time for an alert, but may also provide the ability for users to set this time period themselves or to override the default suggestion.

The user may determine whether the historical trigger data indicates that the proposed alert will perform as desired. Once the desired proposed alert has been entered, the user may provide input to set the proposed alert as an actual alert.

Further details and variations are described herein.

**BRIEF DESCRIPTION OF THE DRAWINGS**

The accompanying drawings, together with the description, illustrate several embodiments. One skilled in the art will recognize that the particular embodiments illustrated in the drawings are merely exemplary, and are not intended to limit scope.

FIG. 1A is a block diagram depicting a hardware architecture according to one embodiment.

FIG. 1B is a block diagram depicting a hardware architecture in a client/server environment, according to one embodiment.

FIGS. 2A to 2C are block diagrams depicting trigger conditions of various alerts, according to selected embodiments.

FIG. 3 is a block diagram depicting a system for setting alerts, according to one embodiment.

FIG. 4 is a flowchart depicting a method of setting alerts, according to one embodiment.

FIG. 5 is a screenshot depicting entry of a proposed alert via text entry, and provision of historical trigger data, according to one embodiment.

FIG. 6 is a screenshot depicting entry of a different proposed alert, and provision of historical trigger data, according to the embodiment of FIG. 5.

FIG. 7 is a screenshot depicting entry of a proposed alert via text entry, and provision of historical trigger data, according to another embodiment.

FIG. 8 is a screenshot depicting entry of a proposed alert via indication on a data visualization, and provision of historical trigger data, according to another embodiment.

FIG. 9 is a screenshot depicting a further step in the entry of a proposed alert via indication on a data visualization, and provision of historical trigger data, according to the embodiment of FIG. 8.

FIG. 10 is a screenshot depicting an additional step in the entry of a proposed alert via indication on a data visualization, and provision of historical trigger data, according to the embodiment of FIG. 8.

FIG. 11 is a screenshot depicting entry of a proposed alert via indication on a data visualization, and provision of historical trigger data, according to another embodiment.

FIG. 12 is a screenshot depicting entry of a proposed alert via indication on a data visualization, and provision of historical trigger data, according to another embodiment.

FIG. 13 is a table illustrating a portion of an aggregated operational data set, according to one embodiment.

#### DETAILED DESCRIPTION OF THE EMBODIMENTS

In at least one embodiment, the system and method described herein facilitate the configuration of alerts regarding the operation of an enterprise by providing the user with historical trigger data that indicate how a proposed alert would have functioned historically. Based on the historical trigger data, the user may decide to set the proposed alert as an alert, or modify it before setting it. Thus, the alert may have a stronger likelihood of triggering at the appropriate frequency.

In this application, an “alert” is a trigger condition that, if satisfied, will trigger transmission of notification to a user. A “proposed alert” is a set of trigger conditions that have been entered but have not yet been set as an actual alert. An “enterprise” is any entity that exists for the purpose accomplishing a one or more tasks or objectives, including but not limited to for-profit entities, governmental bodies, and non-profit organizations. “Operational data” is any data indicative of the operation of an enterprise. “Historical trigger data” is data that indicate how an alert or proposed alert would have functioned if applied to the prior operation of an enterprise. A “data visualization” is a graphical representation of data, such as a chart, graph, table of summarized data, or the like.

#### System Architecture

According to various embodiments, the system can be implemented on any electronic device equipped to receive, store, and present information. Such an electronic device may be, for example, a desktop computer, laptop computer, smartphone, tablet computer, or the like.

Although the system is described herein in connection with an implementation in a computer, one skilled in the art will recognize that the techniques described herein can be implemented in other contexts, and indeed in any suitable device capable of receiving and/or processing user input. Accordingly, the following description is intended to illustrate various embodiments by way of example, rather than to limit scope.

Referring now to FIG. 1A, there is shown a block diagram depicting a hardware architecture for practicing the described system, according to one embodiment. Such an architecture can be used, for example, for implementing the techniques of the system in a computer or other device 101. Device 101 may be any electronic device equipped to receive, store, and/or present information, and to receive user input in connect with such information.

In at least one embodiment, device 101 has a number of hardware components well known to those skilled in the art. Input device 102 can be any element that receives input from user 100, including, for example, a keyboard, mouse, stylus, touch-sensitive screen (touchscreen), touchpad, trackball, accelerometer, five-way switch, microphone, or the like. Input can be provided via any suitable mode, including for example, one or more of: pointing, tapping, typing, dragging, and/or speech.

Data store 106 can be any magnetic, optical, or electronic storage device for data in digital form; examples include flash memory, magnetic hard drive, CD-ROM, DVD-ROM, or the like. In at least one embodiment, data store 106 stores information which may include one or more databases, referred to collectively as a database 107, that can be utilized and/or

displayed according to the techniques described below. In another embodiment, database 107 can be stored elsewhere, and retrieved by device 101 when needed for presentation to user 100. Database 107 may include one or more data sets, which may be used for a variety of purposes and may include a wide variety of files, metadata, and/or other data. In at least one embodiment, database 107 may include alerts 111 and operational data 112.

Display screen 103 can be any element that graphically displays information such as items from database 107 and/or the results of steps performed on such items to provide information useful to a user. Such output may include, for example, raw data, data visualizations, navigational elements, queries requesting confirmation and/or parameters for information identification, display, or presentation, or the like. In at least one embodiment where only some of the desired output is presented at a time, a dynamic control, such as a scrolling mechanism, may be available via input device 102 to change which information is currently displayed, and/or to alter the manner in which the information is displayed.

In at least one embodiment, the information displayed on display screen 103 may include data in text and/or graphical form. Such data may comprise visual cues, such as height, distance, and/or area, to convey the value of each data entry. In at least one embodiment, labels accompany data entries on display screen 103, or can be displayed when user 100 taps on or clicks on a data entry, or causes an onscreen cursor to hover over a data entry.

Processor 104 can be a conventional microprocessor for performing operations on data under the direction of software, according to well-known techniques. Memory 105 can be random-access memory, having a structure and architecture as are known in the art, for use by processor 104 in the course of running software.

Data store 106 can be local or remote with respect to the other components of device 101. In at least one embodiment, device 101 is configured to retrieve data from a remote data storage device when needed. Such communication between device 101 and other components can take place wirelessly, by Ethernet connection, via a computing network such as the Internet, via a cellular network, or by any other appropriate means. This communication with other electronic devices is provided as an example and is not necessary.

In at least one embodiment, data store 106 is detachable in the form of a CD-ROM, DVD, flash drive, USB hard drive, or the like. Database 107 can be entered from a source outside of device 101 into a data store 106 that is detachable, and later displayed after the data store 106 is connected to device 101. In another embodiment, data store 106 is fixed within device 101.

Referring now to FIG. 1B, there is shown a block diagram depicting a hardware architecture in a client/server environment, according to one embodiment. Such an implementation may use a “black box” approach, whereby data storage and processing are done completely independently from user input/output. An example of such a client/server environment is a web-based implementation, wherein client device 108 runs a browser that provides a user interface for interacting with web pages and/or other web-based resources from server 110. Items from the database 107, reports, and/or other data derived from the database 107 can be presented as part of such web pages and/or other web-based resources, using known protocols and languages such as Hypertext Markup Language (HTML), Java, JavaScript, and the like.

Client device 108 can be any electronic device incorporating the input device 102 and/or display screen 103, such as a desktop computer, laptop computer, personal digital assistant

(PDA), cellular telephone, smartphone, music player, hand-held computer, tablet computer, kiosk, game system, or the like. Any suitable type of communications network **109**, such as the Internet, can be used as the mechanism for transmitting data between client device **108** and server **110**, according to any suitable protocols and techniques. In addition to the Internet, other examples include cellular telephone networks, EDGE, 3G, 4G, long term evolution (LTE), Session Initiation Protocol (SIP), Short Message Peer-to-Peer protocol (SMPP), SS7, Wi-Fi, Bluetooth, ZigBee, Hypertext Transfer Protocol (HTTP), Secure Hypertext Transfer Protocol (SH-TTP), Transmission Control Protocol/Internet Protocol (TCP/IP), and/or the like, and/or any combination thereof. In at least one embodiment, client device **108** transmits requests for data via communications network **109**, and receives responses from server **110** containing the requested data.

In this implementation, server **110** is responsible for data storage and processing, and incorporates data store **106** for storing database **107**. Server **110** may include additional components as needed for retrieving data and/or database **107** from data store **106** in response to requests from client device **108**.

In at least one embodiment, data store **106** may be organized into one or more well-ordered data sets, with one or more data entries in each set. Data store **106**, however, can have any suitable structure. Accordingly, the particular organization of data store **106** need not resemble the form in which information from data store **106** is displayed to user **100**. In at least one embodiment, an identifying label is also stored along with each data entry, to be displayed along with each data entry.

In at least one embodiment, database **107** is organized in a file system within data store **106**. Appropriate indexing can be provided to associate particular documents with particular quantitative data elements, reports, other documents, and/or the like. Database **107** may include any of a wide variety of data structures known in the database arts. As in FIG. 1A, database **107** may include one or more data sets, which may include alerts **111**, operational data **112**, and/or other data (not shown).

Alerts **111** and/or operational data **112** can be retrieved from the data store **106**, or from any other source. Data store **106** may be client-based and/or server-based. In at least one embodiment, input device **102** is configured to receive data entries from user **100**, to be added to data store **106**. User **100** may provide such data entries via the hardware and software components described above according to means that are well known to those skilled in the art. Server **110** may be connected to several client devices **108** that are used by various individuals of the enterprise, and may thus store alerts **111** and/or operational data **112** from multiple users and/or multiple client devices **108**. Alerts **111** and/or operational data **112** may be used to generate notifications to the user **100**, which may be transmitted via the display screen **103** and/or one or more other output devices.

Display screen **103** can be any element that graphically displays information such as items from database **107** and/or the results of steps performed on such items to provide information useful to a user. Such output may include, for example, raw data, data visualizations, navigational elements, queries requesting confirmation and/or parameters for information identification, display, or presentation, or the like. In at least one embodiment where only some of the desired output is presented at a time, a dynamic control, such as a scrolling mechanism, may be available via input device **102** to change which information is currently displayed, and/or to alter the manner in which the information is displayed.

In at least one embodiment, the information displayed on display screen **103** may include data in text and/or graphical form. Such data may comprise visual cues, such as height, distance, and/or area, to convey the value of each data entry.

In at least one embodiment, labels accompany data entries on display screen **103**, or can be displayed when user **100** taps on or clicks on a data entry, or causes an onscreen cursor to hover over a data entry.

Processor **104** can be a conventional microprocessor for use in an electronic device to perform operations on data under the direction of software, according to well-known techniques. Memory **105** can be random-access memory, having a structure and architecture as are known in the art, for use by processor **104** in the course of running software.

In one embodiment, the system can be implemented as software written in any suitable computer programming language, whether in a standalone or client/server architecture. Alternatively, it may be implemented and/or embedded in hardware.

#### Alert Structure

In general, the data stored within data store **106** of FIG. 1A or FIG. 1B may include one or more pieces of data, each of which may be of any desired length and format. Thus, each piece of data may be a character string, integer, floating point number, or any other type of data, and may thus represent any information such as names, times, dates, currency amounts, percentages, fractions, physical dimensions, or any other data that may desirably be stored in a computer. As mentioned previously, data store **106** may include alerts **111**, operational data **112**, and/or other data (not shown).

Referring to FIG. 2A, a block diagram depicts the structure of an alert **200**, which is shown by way of example according to one embodiment. The alert **200** may have a set of trigger conditions **210** which, when satisfied, will trigger transmission of a notification to the user **100**. The trigger condition **210** of FIG. 2A is shown as menu selections and/or text entry boxes as may be present in a user interface; however, in alternative embodiments, they may be entered via manipulation of data visualizations, widgets, or via other user input methods.

In the exemplary embodiment of FIG. 2A, the trigger condition **210** may include a metric **212**, which is the item to be measured as a basis of the alert **200**. The metric **212** may be selected, for example, through the use of a dropdown menu accessible via an arrow **214**. The dropdown menu may show a list of the metrics **212** stored in the operational data **112**. Thus, the user **100** may click or tap the arrow **214** to reveal the dropdown menu and select the desired metric on which the alert **200** is to be based.

The trigger condition **210** may also include an operator **216** and a threshold **218**. The operator **216** may be the type of comparison to be performed between the threshold **218** and the metric **212**. Thus, the trigger condition **210** may be satisfied when the metric **212** meets the condition specified by the operator **216**, relative to the threshold **218**.

Like the metric **212**, the operator **216** may be displayed alongside an arrow **214** that can be clicked or tapped by a user to display a dropdown menu listing the various operators that are available for use in alerts. For a threshold **218** in the form of a number, such operators may include, but are not limited to, greater than, less than, and equal to. Other operators may be used with different threshold types, as will be shown and described in connection with other embodiments.

The alert **200** may further include a date grain **220** and a date range **222**. The date grain **220** may indicate the period of time over which the metric **212** is to be measured to determine whether the trigger condition **210** is satisfied. The date range



**222** may be the dates over which the trigger condition **210** is to be applied. Thus, in the example of FIG. 2A, the trigger condition **210** may be satisfied if the total revenue in a day is greater than \$1,000,000, any time within the last thirty days. The date grain **220** and the date range may be user-adjustable, or may not be adjustable.

When the trigger condition **210** is satisfied, notification may be transmitted to the user **100** in a variety of ways. Such ways may include, but are not limited to, e-mails, instant messages, text messages, auditory signals, speech, graphical displays, and/or messages from within various computer programs. According to one embodiment, the alert **200** may specify the manner(s) in which the notification is to be transmitted to the user **100**. This notification method may be user-selectable via various menus (not shown), radio buttons (not shown), and/or other user interface elements (not shown).

Referring to FIG. 2B, a block diagram depicts the structure of an alert **230**, which is shown by way of example according to another embodiment. The alert **230** may have a set of trigger conditions **240** which, when satisfied, will trigger transmission of a notification to the user **100**. The trigger condition **240** of FIG. 2B is shown as menu selections and/or text entry boxes as may be present in a user interface; however, in alternative embodiments, they may be entered via manipulation of data visualizations, widgets, or via other user input methods.

As in the alert **200** of FIG. 2A, the trigger condition **240** of the alert **230** of FIG. 2B may have a metric **242**, an operator **246**, a date grain **250**, and a date range **252**. The operator **246** may be “breaks a record high.” This requires comparison to, not a single numerical threshold, but rather, to a threshold in the form of the highest previous total revenue. Thus, a blank field **248** may be used for the threshold of the trigger condition **240**, because no user input is required for the threshold. The threshold already exists in the data to be compared.

Per the date grain **250**, the revenue to be assessed is, again, daily revenue. In alternative embodiments, any date grain may be used, including but not limited to seconds, minutes, hours, work days, weeks, months, and years.

However, per the date range **252**, rather than reviewing a period of thirty days as in the trigger condition **210** of FIG. 2A, total daily revenue for each day of the current quarter is reviewed. Notably, while the date range **222** of FIG. 2A is a rolling time period that remains the same size (thirty days) regardless of the date, the date range **252** is a definite beginning date (the first date of the current quarter), and will grow longer as the current quarter progresses, until the end of the quarter is reached.

Referring to FIG. 2C, a block diagram depicts the structure of an alert **260**, which is shown by way of example according to another embodiment. The alert **260** may have a set of trigger conditions **270** which, when satisfied, will trigger transmission of a notification to the user **100**. The trigger condition **270** of FIG. 2C is shown as menu selections and/or text entry boxes as may be present in a user interface; however, in alternative embodiments, they may be entered via manipulation of data visualizations, widgets, or via other user input methods.

As in the alert **200** of FIG. 2A and the alert **230** of FIG. 2B, the trigger condition **270** of the alert **260** of FIG. 2C may have a metric **272**, an operator **276**, a date grain **250**, and a date range **252**. The metric **272** may be the “top selling person,” and the operator **246** may be “changes.” As in the alert **230** of FIG. 2B, this requires comparison to, not a single numerical threshold, but rather, to values that are tracked and stored by the system. For example, the top selling person may be recorded each day as a character string. When a new top

selling person is entered, the trigger condition **270** may be satisfied, and the alert **260** may be triggered. In other embodiments, sales revenue, sales units, or other metrics may be tracked for various individuals, and the system may automatically determine which individual has the highest sales in any given day. Again, when the identity of this individual changes, the alert **260** may be triggered. As in the trigger condition **240** of FIG. 2B, a blank field **278** may be used for the threshold of the trigger condition **270**, because no user input is required for the threshold. The threshold already exists in the data to be compared.

As in FIG. 2A and FIG. 2B, the alert **260** may have a date grain **280**, which may be daily. The alert **260** may also have a date range **282**, which may be the entire history, i.e., all dates for which the operational data **112** needed to determine the top selling person exists.

FIGS. 2A, 2B, and 2C are merely exemplary. Those of skill in the art will recognize that alerts may be generated using a wide variety of metrics, operators, and thresholds (whether user-defined or found in recorded data), aside from those shown and described in these exemplary embodiments.

#### Automatic Provision of Historical Trigger Data

Alerts may be implemented in a variety of ways. According to some embodiments, alerts may be implemented on enterprise management software that performs multiple functions. For example, such software may facilitate communications among employees of an enterprise, performance tracking through the use of key performance indicators or other tools, and/or the like. Thus, the setting alerts and/or receiving notification may be carried out in conjunction with other activities that can be performed on the software platform. Alternatively, alerts may be carried out through the use of more specialized software that only provides the alert and/or notification functionality. In either case, the methods set forth herein may be performed with the aid of a computing system, such as the device **101** of FIG. 1A and/or the client device **108** and/or server **110** of FIG. 1B.

Referring to FIG. 3, a block diagram illustrates a system **300** according to one embodiment. The system **300** may be designed to facilitate alert setting by automatically providing historical trigger data that indicates how a proposed alert would have functioned if applied to the operational data **112** previously generated for the enterprise. As indicated previously, alert functionality may be carried out in a system that performs other functions pertinent to the management of an enterprise. However, only the architecture pertinent to alerts is shown in FIG. 3.

As shown, the system **300** may have an alert history module **310** and an alert setting module **320**. In general, the alert history module **310** may provide the historical trigger data referenced above, and the alert setting module **320** may be used to set the alert when it has been properly formulated.

More specifically, the user may provide a proposed alert **330**, for example via the input device **102**. The proposed alert **330** may be structured, for example, in a manner similar to that of the alert **200** of FIG. 2A, the alert **230** of FIG. 2B, and/or the alert **260** of FIG. 2C. The proposed alert **330** may be received via text entry, manipulation of a data visualization, or through other methods, as will be set forth in greater detail subsequently.

The alert history module **310** may receive the proposed alert **330**, and may query the database **107** to determine how the proposed alert **330** would have functioned if applied to the operational data **112**. This information may be presented to the user **100** as historical trigger data **370**. The operational data **112** may include various data structures that may facilitate and/or expedite this comparison. For example, the opera-

tional data **112** may include one or more data visualizations **340**, one or more aggregated operational data sets **350**, and/or one or more data differentials **360**. These will be described in greater detail below.

The data visualizations **340** may include any graphical representations of the data of the operational data **112**, such as charts, graphs, and the like. The data visualizations **340** may be viewed by the user **100** in order to facilitate entry of the proposed alert **330**. Additionally or alternatively, the data visualizations **340** may be used as part of the historical trigger data **370**.

Each of the aggregated operational data sets **350** may include the operational data **112**, or a subset of the operational data **112**, organized according to various schemas. In some examples, each of the aggregated operational data sets **350** may be organized according to the date grain that will be used for the proposed alert **330** (or if the date grain is adjustable in the proposed alert **330**, the most likely date grain to be used). Thus, for example, the operational data sets **350** may each have data broken down by date, with individual days listed separately to facilitate calculations based on a “daily” date grain.

The aggregated operational data sets **350** may each include a subset of the operational data **112**, if desired. Thus, the alert **200** of FIG. 2A, for which the metric **212** is “total revenue,” may only require that the alert history module **310** reference the one or more aggregated operational data sets **350** that include “total revenue,” broken down by date. This may expedite the data transfer processes and/or calculations required to obtain the historical trigger data **370** because only a subset of the operational data **112** may need to be retrieved and/or compared.

Each of the aggregated operational data sets **350** may optionally be stored in multiple versions in the operational data **112**. Thus, for example, one aggregated operational data set **350** may store only current data, such as the “top selling person,” as referenced in the metric **272** of FIG. 2C. Since this data may change from one time period to the next, multiple versions of such an aggregated operational data set **350** may be stored in the operational data **112**. A new version of such an aggregated operational data set **350** may be stored periodically, without overwriting the previous version. Thus, any given aggregated operational data set **350** may include a first version **352** and, optionally, one or more additional versions up to an nth version **354**. In the case of the aggregated operational data sets **350** for the “top selling person,” any two adjacent versions of the aggregated operational data set may be compared with each other to determine how many times the trigger condition **270** of the alert **260** of FIG. 2C would have been satisfied over a specified period of time (such as the date range **282** of FIG. 2C).

The data differentials **360** may include comparisons of various data that can be referenced to facilitate the calculations needed to obtain the historical trigger data **370**. For example, some alerts may be based on the change of a metric from one time period to another. More specifically, an alert may be triggered when the sales from one day to the next change by more than a predetermined amount. In order to expedite determination of how many times such an alert would have been triggered over a given time period, it may be advantageous to record data differentials **360** that include the change in daily sales between each day and the previous day. Then, in order to obtain the historical trigger data **370**, subtractions need not be carried out. Rather, the change in daily sales, stored previously in the data differentials **360**, may simply be compared with the threshold for each day.

In alternative embodiments, the data visualizations **340**, aggregated operational data sets **350**, and/or the data differentials **360** may be generated on-the-fly based on the operational data **112**, as it exists in raw form. However, generation of these elements may be somewhat time-consuming, depending on the scope of the operational data **112**. Accordingly, generating them prior to receipt of the proposed alert **330** from the user **100** may help to minimize the amount of time the user **100** has to wait between entry of the proposed alert **330** and provision, to the user **100**, of the historical trigger data **370**. The system **300** may be customizable to determine whether the data visualizations **340**, the aggregated operational data sets **350**, and/or the data differentials **360** are generated before they are needed by the user **100**, and if so, which of each are generated and stored in the operational data **112**.

After the alert history module **310** has compared the proposed alert **330** with the operational data **112**, the historical trigger data **370** may be obtained and provided to the user **100**. This may be done, for example, by displaying text and/or one or more data visualizations on the display screen **103**. The historical trigger data **370** may provide various data, such as:

- Whether the proposed alert **330** would have been triggered within the applicable date range;

- How many times, within the applicable date range, the proposed alert **330** would have been triggered;

- The frequency at which the proposed alert **330** would have been triggered within the applicable date range (for example, how many times per month);

- The significance of triggering of the proposed alert **330** (for example, by assuming that an alert that would be triggered more frequently would be less significant than an alert that triggers more rarely); and

- Historical values and/or statistics of the metric of the proposed alert **330** (for example, high, low, mean, median, standard deviation, and the like).

After the user **100** has had the opportunity to review the historical trigger data **370**, he or she may desire to set the proposed alert **330** as an alert in the system **300**, or to make changes to the proposed alert **330** before the corresponding alert is set. Once the proposed alert **330** is ready to be set as an alert in the system **300**, the user **100** may provide an alert confirmation **380**.

The alert confirmation **380** may be received by the alert setting module **320**. The alert setting module **320** may store a new alert in the alerts **111** of the database **107**. The new alert may have the trigger condition and/or other parameters of the proposed alert **330**. The system **300** may provide notifications to the user **100** on the basis of the alerts **111**; accordingly, the new alert may also be used to transmit a notification to the user **100** when the trigger condition of the new alert has been satisfied.

Referring to FIG. 4, a flowchart diagram illustrates a method **400** of setting an alert according to one embodiment. The method **400** may be carried out through the use of a system such as the system **300** of FIG. 3, as will be described by way of example below. Additionally or alternatively, other systems may be used to carry out the method **400**. Further, a system such as the system **300** of FIG. 3 may be used to carry out other methods besides the method **400** of FIG. 4.

As shown, the method **400** may start **410** with a step **420** in which the operational data **112** is recorded. This may be done automatically or manually, by various individuals of the enterprise. The operational data **112** may be stored in the database **107** in the data store **106**, as indicated previously.

The method **400** may proceed to a step **425** in which the one or more data visualizations **340** are generated, a step **430** in

## 11

which the aggregated operational data set **350** are generated, and a step **435** in which the data differentials are generated. As mentioned previously, performance of the step **425**, the step **430**, and/or the step **435** may be optional; any of these steps, if desired, may be replaced with calculations and/or data manipulations performed on-the-fly after the proposed alert **330** is received.

The method **400** may proceed to a query **440** in which a determination is made as to whether a proposed alert **330** has been received. If the proposed alert **330** has not been received, the steps **420**, **425**, **430**, and **435** may be repeated until a proposed alert **330** is received. Thus, the operational data **112** may be continuously updated until the proposed alert **330** is received. This updating process may optionally entail updating the one or more data visualizations **340**, the one or more aggregated operational data set **350**, and/or the one or more data differentials **360**.

Pursuant to the query **440**, if a determination is made that the proposed alert **330** has been received, the method **400** may proceed to a step **445** in which the proposed alert **330** is compared with the operational data **112**. This may be done as set forth in the description of FIG. 3. Thus, the step **445** may entail comparison of the proposed alert **330** with the data visualization **340**, the aggregated operational data set **350**, and/or the data differential **360**, as applicable. This comparison may yield the historical trigger data **370**, as described previously.

The method **400** may proceed to a step **450** in which the historical trigger data **370** are provided to the user **100**. As indicated previously, this may entail display of text and or data visualizations on the display screen **103** of the device **101** and/or the client device **108**.

In a query **455**, a determination may be made as to whether the proposed alert **330** is to be set as an alert in the system **300**. For example, the user **100** may make a selection to confirm a proposed alert **330** to set the proposed alert **330** as an alert **111** to be stored in the database **107** and used to provide notification per the trigger condition of the alert **111**.

If no such confirmation is received, the method **400** may return to the query **440**, in which a determination is made as to whether a proposed alert **330** has been received. If no proposed alert **330** is received, the method **400** may return to the step **420**, in which operational data **112** is recorded by updating the operational data **112** previously recorded.

Pursuant to the query **440**, if the proposed alert **330** has been received, this proposed alert **330** may be a revised version of the one previously entered. The system **300** may again compare the proposed alert **330**, in its revised form, with the operational data **112** to obtain the historical trigger data **370** for the proposed alert **330**, and provide the resulting historical trigger data **370** to the user **100**.

Once the user **100** confirms an intention to set a proposed alert **330** as an alert **111**, pursuant to the query **455**, the method **400** may proceed to a step **460** in which the alert **111** is set. The alert **111** may then be periodically compared with the operational data **112** in a manner similar to the comparison performed with the proposed alert **330** in the step **445**.

The system **300** may, in a step **465**, detect that the trigger condition of the alert **111** have been satisfied. In response, the method **400** may proceed to a step **465** in which notification of triggering of the alert **111** is transmitted to the user **100**. As indicated previously, this may be done in a variety of ways, which may optionally be user-configurable. The method **400** may then end **490**.

The method **400** of FIG. 4 is only one of many methods included within the scope of the present disclosure. Several examples will be presented in FIGS. 5-12, as follows. FIGS.

## 12

5-12 illustrate various user interfaces, methods, and alert structures, which are merely exemplary.

## EXAMPLES

Referring to FIG. 5, a screenshot **500** illustrates entry of a proposed alert **330** via text entry, and provision of historical trigger data **370**, according to one embodiment. The screenshot **500** illustrates software that may be used to facilitate multiple aspects of the management of an enterprise. As shown, the screenshot **500** may include an alert entry section **510**, an activity indicator **520**, an organizational alert listing **530**, an organizational activity listing **540**, and an individual alert summary **550**.

The alert entry section **510** may be used by the user **100** to enter the proposed alert **330** via text entry. The alert entry section **510** may have a format similar to that of the alert **200** of FIG. 2A, the alert **230** of FIG. 2B, and the alert **260** of FIG. 2C. Thus, the alert entry section **510** may have a metric **560**, an operator **562**, and a threshold **564**, which may be entered by the user through the use of dropdown menus and/or text entry, as appropriate. More specifically, arrows **566** adjacent to the metric **560** and the operator **562** may enable the metric **560** and the operator **562** to be selected from dropdown menus. The threshold **564** may be entered via text entry.

Optionally, the proposed alert **330** in FIG. 5 may also include a condition selection **568**, which may be used to allow the user to select different options, such as transmission of a notification if the trigger condition is satisfied, and transmission of a notification if the trigger condition is not satisfied. In FIG. 5, the condition selection **568** is set to transmit notification if the trigger condition is satisfied.

In the example of FIG. 5, the metric **560** is “30-Day Average” (as applied to account balance), the operator **562** is “falls below,” and the threshold **564** is “4,800,000.” Thus, the proposed alert **330** entered in the alert entry section **510** will notify the user **100** if the 30-day average account balance of the enterprise’s account falls below \$4,800,000.

A follow alert button **570** may be displayed, and may be selected by the user **100**, for example, by clicking or tapping, to apply the proposed alert **330** to the user **100** by causing the user **100** to “follow” an alert **111**, already in existence, that is identical to the proposed alert **330**.

The activity indicator **520** may provide the historical trigger data **370** to the user **100** by indicating that the proposed alert **330** would have been triggered seven times within the last ninety days. This may help the user **100** to determine whether the proposed alert **330** is appropriately tuned. As shown, the activity indicator **520** may include a data visualization in the form of a trigger log **580**, which graphically indicates when the proposed alert **330** would have been triggered within the past 90 days. Further, the activity indicator **520** may include text **522** that indicates the number of times the proposed alert **330** would have been triggered within the past 90 days. A historical value section **584** may provide additional helpful information regarding the historical values of the metric **560**.

The organizational alert listing **530** may list alerts created and/or followed by others within the enterprise. The organizational alert listing **530** may have options for the user **100** to follow alerts **111** created and/or followed by other users so that the user **100** will also receive notification when those alerts **111** are triggered. Accordingly, the user **100** may easily set an alert **111** without entering a proposed alert **330** at all; the user **100** may simply browse the alerts **111** being followed by others in the enterprise and select to follow any that are satisfactory for his or her own informational needs.

The organizational activity listing **540** may list various activities within the enterprise. Some of these items may be KPI's (key performance indicators) being followed by the user, comments made by others at the enterprise, news pertinent to the enterprise, or the like.

The individual alert summary **550** may include a summary of alerts set by and/or followed by the user **100**. As shown, the individual alert summary **550** may indicate how many alerts for the user **100** have been triggered recently, and how many alerts for the user **100** are close to triggering.

In some embodiments, the information in the activity indicator **520**, the organizational alert listing **530**, the organizational activity listing **540**, and/or the individual alert summary **550** may include links so that the user **100** can select a pertinent piece of information to bring up additional information. For example, clicking on one of the alerts **111** shown in the organizational alert listing **530** may cause a more detailed description of the alert **111** to be displayed.

In at least one embodiment, the follow alert button **570** may only be active when the proposed alert **330** entered by the user **100** matches an alert **111** that has already been set. For example, the second alert **111** in the organizational alert listing **530** reads "Alert me if 30-day Average value of Cash balance falls below \$4,800,000." This is identical to the proposed alert **330**. Thus, the user **100** need not set a new alert. It may be advantageous for the user **100** to see other users that are also following the alert **111** in which he or she is interested. Further, preventing duplicative alerts **111** may help reduce the storage and/or processing loads on the system **300**. Hence, the follow alert button **570** may replace a button that ordinarily permits the user **100** to set a new alert, but only when the proposed alert **330** is identical to one of the alert **111** that has already been set within the system **300**.

Referring to FIG. 6, a screenshot **600** depicts entry of a different proposed alert **330**, and provision of historical trigger data **370**, according to the embodiment of FIG. 5. In FIG. 6, the threshold **564** has been adjusted to \$4,975,000. This proposed alert **330** is no longer identical to the alert **111** in the organizational alert listing **530** regarding cash balances; accordingly, the follow alert button **570** has been changed to a save alert button **670** that can be activated to save the proposed alert **330** as an alert **111** distinct from those in the organizational alert listing **530**.

In some embodiments, the proposed alert **330** may not need to be identical to an alert **111** in order for the user **100** to be offered the option to follow the alert **111** rather than setting the proposed alert **330** as a new and separate alert **111**. For example, various algorithms may be applied to the proposed alert **330** to determine whether it is close enough to an alert **111** to offer the user **100** the option to follow the existing alert **111**. For example, if the metric **560** and the operator **562** of the proposed alert **330** are identical to those of an existing alert **111**, the system **300** may determine whether the threshold **564** for the proposed alert **330** is within 5% (i.e., within the range of 5% under to 5% over) the threshold **564** of the existing alert **111**. If the threshold **564** of the proposed alert **330** falls within this range, but is not identical to the threshold **564** of the existing alert, the user **100** may be offered both options, i.e., the option to follow the existing alert **111** and the option to set the proposed alert **330** as a new alert **111**.

As also shown in FIG. 6, the activity indicator **520** now indicates that the proposed alert **330** would have been triggered forty-two times within the past ninety days. This is because the threshold **564** is more liberal than in the proposed alert **330** entered in FIG. 5.

Referring to FIG. 7, a screenshot **700** depicts entry of a proposed alert **330** via text entry, and provision of historical

trigger data **370**, according to another embodiment. As shown, the alert entry section **510** of the screenshot **700** may have a proposed alert **330** with a different format than those of FIGS. 5 and 6.

More specifically, the proposed alert **330** of FIG. 7 may be a compound alert, with multiple trigger conditions that all have to be satisfied in order for the alert to be triggered. Thus, the proposed alert **330** of FIG. 7 may have a metric **560**, an operator **562**, and a threshold **564**. These may be similar to previous embodiments, except that the threshold **564** may have an arrow **566** that permits it to be selected from a drop-down menu rather than via entry of text. The metric **560** may be "account name," the operator **562** may be "equals," and the threshold **564** may be "Zillow, Inc." Thus, this first portion of the proposed alert **330** may be satisfied if the account is for Zillow, Inc.

Further, the proposed alert **330** of FIG. 7 may have a second portion with a second metric **760**, a second operator **762**, and a second threshold **764**. The second metric **760** may be "close date," the second operator **762** may be "falls below," and the second threshold **764** may be 9/1/2012. Thus, this portion of the proposed alert **330** may be satisfied if the account was closed prior to 9/1/2012. Inclusion of this second portion with the first portion may indicate that the account in question is the one specified in the first portion (i.e., Zillow, Inc.). Thus, the proposed alert **330** may be satisfied only if an account for Zillow, Inc. has been closed prior to 9/1/2012.

The activity indicator **520** indicates that this alert has never been triggered within the past ninety days. Such compound alerts may be beneficial for setting alerts based on more specific sets of circumstances. In alternative embodiments, various operators may be applied between portions of an alert; for example, a proposed alert **330** may be satisfied if either a first portion or a second portion of the proposed alert **330** has been satisfied, rather than requiring satisfaction of both portions to trigger the proposed alert **330**. Various buttons, widgets, and/or other user interface items may be used to facilitate the entry of compound alerts.

Referring to FIG. 8, a screenshot **800** depicts entry of a proposed alert **330** via indication on a data visualization **805**, and provision of historical trigger data **370**, according to another embodiment. More specifically, the data visualization **805** may be a bar graph regarding customer issues, with a first bar **810** representing open issues, a second bar **820** representing resolved issues, and a third bar **830** representing closed issues. Rather than entering text and/or making a selection from a menu as in FIGS. 5, 6, and 7, FIG. 8 may allow the user **100** to enter a proposed alert **330** directly on the data visualization **805**.

A threshold indicator **840** may be applied to the data visualization **805** in the form of a horizontal line. The threshold indicator **840** may be positioned with the aid of a pointer **850**, which may be moved via motion of a mouse, finger, or other input device **102**. The proposed alert **330** is shown in the form of a current alert section **860**, which indicates that the proposed alert **330** will trigger notification of the user **100** when the number of closed customer issues represented by the third bar **830** exceeds 20 (the position at which the threshold indicator **840** currently resides). The threshold indicator **840** may be moved vertically to change the threshold of the proposed alert **330** to a number greater or less than 20. Additionally or alternatively, the threshold indicator **840** may be moved horizontally to change the metric of the proposed alert **330** to instead compare the threshold with a different quantity, such as the number of open customer issues represented by the first bar **810**, or the number of resolved customer issues represented by the second bar **820**.

If desired, the operator of the proposed alert **330** may be automatically set based on the context. For example, placing the threshold indicator **840** above the top of the third bar **830** may cause the proposed alert **330** to have a “higher than” operator. On the other hand, placing the threshold indicator **840** below the top of the third bar **830** may cause the proposed alert **330** to have a “lower than” operator. Placing the threshold indicator **840** at the top of the third bar **830** may cause the proposed alert **330** to have an “equals” operator. Alternatively, the operator of the proposed alert **330** may be user-selected, as shown in FIG. 9.

The historical trigger data **370** may be provided in the form of a trigger indicator **870**, which indicates that the proposed alert **330** would have been triggered six times within the last thirty days. The trigger indicator **870** may update in real-time as the threshold indicator **840** is moved by the user. This may facilitate rapid selection of the appropriate threshold for the new alert **111** to be set by the user **100**.

Referring to FIG. 9, a screenshot **900** depicts a further step in the entry of a proposed alert **330** via indication on the data visualization **805**, and provision of historical trigger data **370**, according to the embodiment of FIG. 8. More specifically, in FIG. 9, an operator window **910** may be displayed, for example, in response to a change in the position of the threshold indicator **840**.

The operator window **910** may display multiple operators that the user **100** can select from to formulate the different proposed alert **330**. The options in the operator window **910** shown in FIG. 9 are “higher than,” “lower than,” and “equal to.”

Referring to FIG. 10, a screenshot **1000** depicts an additional step in the entry of a proposed alert **330** via indication on the data visualization **805**, and provision of historical trigger data **370**, according to the embodiment of FIG. 8. As shown, the user **100** may click and drag the threshold indicator **840** with the pointer **850**, and move the threshold indicator **840** vertically from 20 to 19.

This may cause the current alert section **860** to reflect that the different proposed alert **330** now has a threshold of 19. The trigger indicator **870** may also update to indicate that this new proposed alert **330** would have been triggered seven times within the past thirty days. Thus, the user **100** may easily tune the different proposed alert **330** to obtain the desired trigger frequency.

Referring to FIG. 11, a screenshot **1100** depicts entry of a proposed alert **330** via indication on a data visualization **1105**, and provision of historical trigger data **370**, according to another embodiment. The data visualization **1105** may be a histogram indicating the number of visits to a related group of web sites. The data visualization **1105** may have a first bar **1110**, a second bar **1112**, a third bar **1114**, a fourth bar **1116**, a fifth bar **1118**, a sixth bar **1120**, and a seventh bar **1122**.

As shown, the different proposed alert **330** may be set to trigger when any of the bars **1110**, **1112**, **1114**, **1116**, **1118**, **1120**, or **1122** has a value greater than seven. Any of a variety of menus, indicators, widgets, or other devices may be used to establish this proposed alert **330**. In some examples, a threshold indicator (not shown) similar to the threshold indicator **840** may be used, but may take the form of a vertical, rather than horizontal, line. A wide variety of threshold indicators may be used to facilitate entry of a proposed alert **330** on a variety of data visualization types.

This may be shown in a current alert section **1160**. A trigger indicator **1170** may display the historical trigger data **370** by showing that this proposed alert **330** would have been triggered six times within the past ninety days. As in previous

embodiments, the trigger indicator **1170** may be updated in real-time as the proposed alert **330** is adjusted.

Referring to FIG. 12, a screenshot **1200** depicts entry of a proposed alert **330** via indication on the data visualization **805**, and provision of historical trigger data **370**, according to the embodiment. The data visualization **805** may be the same as in FIG. 8. However, in the screenshot **1200**, a threshold indicator **1240** may function in a manner similar to that of the threshold indicator **840** of FIG. 8, but may extend horizontally across the entire data visualization **805**. This may facilitate entry of a proposed alert **330** that will be triggered in the event that any of the first bar **810**, the second bar **820**, and the third bar **830** exceeds the threshold value at which the threshold indicator **1240** is positioned (i.e., twenty).

Thus, the current alert section **860** may indicate that proposed alert **330** will provide notification when any series is higher than twenty. The trigger indicator **870** may indicate that this proposed alert **330** would have been triggered six times within the last thirty days. The threshold indicator **1240** may be moved horizontally to update the trigger indicator **870** in real-time, as in previous embodiments. However, in the embodiment of FIG. 12, the threshold indicator **1240** may not be moved horizontally. Various menus, widgets, or other tools may be used to select the type of threshold indicator to be used, facilitating the entry of different proposed alert types on any given data visualization.

As mentioned previously, the aggregated operational data sets **350** may help to expedite provision of the historical trigger data **370**, thereby enabling the user **100** to see the effects of adjustment of a proposed alert **330**, substantially in real-time. One exemplary aggregated operational data set **350** will be shown and described in connection with FIG. 13.

Referring to FIG. 13, a table illustrates a portion **1300** of an aggregated operational data set, according to one embodiment. The portion **1300** of an aggregated operational data set **350** may have multiple columns, each of which contains a different data field. As shown, the portion **1300** may include order dates **1310**, customer segments **1320**, and sales **1330**. The customer segment **1320** and the sales **1330** may be indexed according to the order date **1310**. This may facilitate rapid lookup of date-based information in order to expedite provision of the historical trigger data **370**, as described above.

As also described previously, multiple aggregated operational data sets **350** may optionally be used. Thus, for example, in addition to the aggregated operational data set **350** shown in FIG. 13, the operational data **112** may include other aggregated operational data sets **350**, which may index other data (for example, salesperson, items purchased, payment terms, and the like). Such other data may advantageously also be indexed according to the order date **1310**. However, this is only one exemplary aggregation scheme; according to alternative embodiments, other aggregation schema may be used.

One skilled in the art will recognize that the examples depicted and described herein are merely illustrative, and that other arrangements of user interface elements can be used. In addition, some of the depicted elements can be omitted or changed, and additional elements depicted, without departing from the essential characteristics.

The present system and method have been described in particular detail with respect to possible embodiments. Those of skill in the art will appreciate that the system and method may be practiced in other embodiments. First, the particular naming of the components, capitalization of terms, the attributes, data structures, or any other programming or structural aspect is not mandatory or significant, and the mecha-

nisms and/or features may have different names, formats, or protocols. Further, the system may be implemented via a combination of hardware and software, or entirely in hardware elements, or entirely in software elements. Also, the particular division of functionality between the various system components described herein is merely exemplary, and not mandatory; functions performed by a single system component may instead be performed by multiple components, and functions performed by multiple components may instead be performed by a single component.

Reference in the specification to “one embodiment” or to “an embodiment” means that a particular feature, structure, or characteristic described in connection with the embodiments is included in at least one embodiment. The appearances of the phrases “in one embodiment” or “in at least one embodiment” in various places in the specification are not necessarily all referring to the same embodiment.

Various embodiments may include any number of systems and/or methods for performing the above-described techniques, either singly or in any combination. Another embodiment includes a computer program product comprising a non-transitory computer-readable storage medium and computer program code, encoded on the medium, for causing a processor in a computing device or other electronic device to perform the above-described techniques.

Some portions of the above are presented in terms of algorithms and symbolic representations of operations on data bits within a memory of a computing device. These algorithmic descriptions and representations are the means used by those skilled in the data processing arts to most effectively convey the substance of their work to others skilled in the art. An algorithm is here, and generally, conceived to be a self-consistent sequence of steps (instructions) leading to a desired result. The steps are those requiring physical manipulations of physical quantities. Usually, though not necessarily, these quantities take the form of electrical, magnetic or optical signals capable of being stored, transferred, combined, compared and otherwise manipulated. It is convenient at times, principally for reasons of common usage, to refer to these signals as bits, values, elements, symbols, characters, terms, numbers, or the like. Furthermore, it is also convenient at times, to refer to certain arrangements of steps requiring physical manipulations of physical quantities as modules or code devices, without loss of generality.

It should be borne in mind, however, that all of these and similar terms are to be associated with the appropriate physical quantities and are merely convenient labels applied to these quantities. Unless specifically stated otherwise as apparent from the following discussion, it is appreciated that throughout the description, discussions utilizing terms such as “processing” or “computing” or “calculating” or “displaying” or “determining” or the like, refer to the action and processes of a computer system, or similar electronic computing module and/or device, that manipulates and transforms data represented as physical (electronic) quantities within the computer system memories or registers or other such information storage, transmission or display devices.

Certain aspects include process steps and instructions described herein in the form of an algorithm. It should be noted that the process steps and instructions can be embodied in software, firmware and/or hardware, and when embodied in software, can be downloaded to reside on and be operated from different platforms used by a variety of operating systems.

The present document also relates to an apparatus for performing the operations herein. This apparatus may be specially constructed for the required purposes, or it may com-

prise a general-purpose computing device selectively activated or reconfigured by a computer program stored in the computing device. Such a computer program may be stored in a computer readable storage medium, such as, but is not limited to, any type of disk including floppy disks, optical disks, CD-ROMs, DVD-ROMs, magnetic-optical disks, read-only memories (ROMs), random access memories (RAMs), EPROMs, EEPROMs, flash memory, solid state drives, magnetic or optical cards, application specific integrated circuits (ASICs), or any type of media suitable for storing electronic instructions, and each coupled to a computer system bus. Further, the computing devices referred to herein may include a single processor or may be architectures employing multiple processor designs for increased computing capability.

The algorithms and displays presented herein are not inherently related to any particular computing device, virtualized system, or other apparatus. Various general-purpose systems may also be used with programs in accordance with the teachings herein, or it may prove convenient to construct more specialized apparatus to perform the required method steps. The required structure for a variety of these systems will be apparent from the description provided herein. In addition, the system and method are not described with reference to any particular programming language. It will be appreciated that a variety of programming languages may be used to implement the teachings described herein, and any references above to specific languages are provided for disclosure of enablement and best mode.

Accordingly, various embodiments include software, hardware, and/or other elements for controlling a computer system, computing device, or other electronic device, or any combination or plurality thereof. Such an electronic device can include, for example, a processor, an input device (such as a keyboard, mouse, touchpad, track pad, joystick, trackball, microphone, and/or any combination thereof), an output device (such as a screen, speaker, and/or the like), memory, long-term storage (such as magnetic storage, optical storage, and/or the like), and/or network connectivity, according to techniques that are well known in the art. Such an electronic device may be portable or nonportable. Examples of electronic devices that may be used for implementing the described system and method include: a mobile phone, personal digital assistant, smartphone, kiosk, server computer, enterprise computing device, desktop computer, laptop computer, tablet computer, consumer electronic device, or the like. An electronic device may use any operating system such as, for example and without limitation: Linux; Microsoft Windows, available from Microsoft Corporation of Redmond, Wash.; Mac OS X, available from Apple Inc. of Cupertino, Calif.; iOS, available from Apple Inc. of Cupertino, Calif.; Android, available from Google, Inc. of Mountain View, Calif.; and/or any other operating system that is adapted for use on the device.

While a limited number of embodiments have been described herein, those skilled in the art, having benefit of the above description, will appreciate that other embodiments may be devised. In addition, it should be noted that the language used in the specification has been principally selected for readability and instructional purposes, and may not have been selected to delineate or circumscribe the subject matter. Accordingly, the disclosure is intended to be illustrative, but not limiting, of scope.

What is claimed is:

1. A method for setting an alert pertinent to operation of an enterprise, the method comprising:

19

at a processor, receiving a proposed alert comprising a trigger condition;

at the processor, comparing the trigger condition with a database of operational data related to operation of the enterprise over a period of time to obtain historical trigger data indicative of how the proposed alert would have functioned if applied to the operational data for the period of time;

at an output device, providing the historical trigger data to a user;

at an input device, receiving user input; and

at the processor, responsive to receipt of the user input, setting an alert that specifies that, when the operational data satisfy the trigger condition, user notification of satisfaction of the trigger condition is provided.

2. The method of claim 1, wherein the trigger condition comprises a metric, stored on a periodic basis in the operational data, a threshold value, and an operator selected from the group consisting of the metric being greater than the threshold, the metric being less than the threshold, and the metric being equal to the threshold.

3. The method of claim 2, wherein receiving the proposed alert comprises receiving the threshold by receiving text from the user via the input device.

4. The method of claim 2, wherein the output device comprises a display screen, the method further comprising displaying a data visualization of at least a portion of the operational data on the display screen, wherein receiving the proposed alert comprises receiving the threshold by receiving user indication of a portion of the data visualization corresponding to the threshold via the input device.

5. The method of claim 1, wherein the output device comprises a display screen, wherein providing the historical trigger data to the user comprises indicating to the user, via text displayed on the display screen, a number of times the trigger condition was met within the period of time.

6. The method of claim 1, wherein the output device comprises a display screen, wherein providing the historical trigger data to the user comprises indicating to the user, via a data visualization displayed on the display screen, a number of times the trigger condition was met within the period of time.

7. The method of claim 1, wherein receiving the user input comprises receiving a user selection to set the proposed alert as the alert.

8. The method of claim 1, further comprising, prior to receiving the proposed alert:

at the processor, receiving a previous proposed alert comprising a previous trigger condition comprising a previous threshold;

at the processor, comparing the previous trigger condition with the database of operational data to obtain previous historical trigger data indicative of how the previous proposed alert would have functioned if applied to the operational data for the period of time;

at the output device, providing the previous historical data to the user; and

at the input device, receiving, from the user, a threshold different from the previous threshold;

wherein the trigger condition comprises the threshold.

9. The method of claim 1, further comprising:

at the processor, detecting that the operational data satisfy the trigger condition; and

at the processor, responsive to detection of satisfaction of the trigger condition, initiating transmission of the user notification of satisfaction of the trigger condition.

20

10. The method of claim 1, wherein receiving the proposed alert comprises receiving the proposed alert from a first user, the method further comprising:

at the processor, comparing the proposed alert with a previous alert previously set by a second user different from the first user;

at the processor, responsive to comparison of the proposed alert with the previous alert, detecting that the proposed alert is similar to the previous alert; and

at the output device, responsive to detection that the proposed alert is similar to the previous alert, providing a user-selectable option to follow the previous alert.

11. The method of claim 1, further comprising, prior to receiving the proposed alert:

at the processor, aggregating the operational data from the database of operational data to generate one or more aggregated operational data sets; and

at a data store, storing the one or more aggregated operational data sets in the database of operational data;

wherein comparing the trigger condition with the database of operational data comprises comparing the trigger condition with the one or more aggregated operational data sets.

12. The method of claim 11, wherein aggregating the operational data from the database of operational data to generate the one or more aggregated operational data sets comprises:

aggregating the operational data from the database of operational data to generate a first version of a first aggregated operational data set;

at a data store, storing the first version of the first aggregated operational data set;

after generation of the first version of the first aggregated operational data set and after updating of the operational data to store updated operational data in the database of operational data, aggregating the updated operational data from the database of operational data to generate a second version of the first operational data set; and

at the data store, storing the second version of the first aggregated operational data set without deleting the first version of the first aggregated data set.

13. The method of claim 12, further comprising:

at the processor, comparing the first version of the first operational data set with the second version of the first operational data set to obtain trending data indicative of how the operational data changed; and

at the output device, providing the trending data to the user.

14. The method of claim 1, further comprising, prior to receiving the proposed alert:

at the processor, comparing the operational data from the database of operational data to generate one or more data differentials; and

at a data store, storing the one or more data differentials in the database of operational data;

wherein comparing the trigger condition with the database of operational data comprises comparing the trigger condition with the one or more data differentials.

15. A computer program product for setting an alert pertinent to operation of an enterprise, the computer program product comprising:

a non-transitory storage medium; and

computer program code, encoded on the medium, configured to cause at least one processor to perform the steps of:

receiving a proposed alert comprising a trigger condition; comparing the trigger condition with a database of operational data related to operation of the enterprise over a

## 21

period of time to obtain historical trigger data indicative of how the proposed alert would have functioned if applied to the operational data for the period of time; causing an output device to provide the historical trigger data to a user;

causing an input device to receive user input; and responsive to receipt of the user input, setting an alert that specifies that, when the operational data satisfy the trigger condition, user notification of satisfaction of the trigger condition is provided.

16. The computer program product of claim 15, wherein the trigger condition comprises a metric, stored on a periodic basis in the operational data, a threshold value, and an operator selected from the group consisting of the metric being greater than the threshold, the metric being less than the threshold, and the metric being equal to the threshold;

and wherein the computer program code configured to cause the at least one processor to receive the proposed alert comprises computer program code configured to cause the at least one processor to cause the input device to receive the threshold by receiving text from the user.

17. The computer program product of claim 15, wherein: the trigger condition comprises a metric, stored on a periodic basis in the operational data, a threshold value, and an operator selected from the group consisting of the metric being greater than the threshold, the metric being less than the threshold, and the metric being equal to the threshold;

the output device comprises a display screen;

the computer program code is further configured to cause the at least one processor to cause the display screen to display a data visualization of at least a portion of the operational data; and

the computer program code configured to cause the at least one processor to receive the proposed alert comprises computer program code configured to cause the at least one processor to receive the threshold by causing the input device to receive user indication of a portion of the data visualization corresponding to the threshold.

18. The computer program product of claim 15, wherein the output device comprises a display screen;

and wherein the computer program code configured to cause the at least one processor to provide the historical trigger data to the user comprises computer program code configured to cause the at least one processor to perform at least one step from the group consisting of:

causing the display screen to display text that indicates how many times the trigger condition was met within the period of time; and

causing the display screen to display a data visualization that indicates how many times the trigger condition was met within the period of time.

19. The computer program product of claim 15, wherein the computer program code is further configured to cause the at least one processor, prior to receiving the proposed alert, to perform the steps of:

receiving a previous proposed alert comprising a previous trigger condition comprising a previous threshold;

comparing the previous trigger condition with the database of operational data to obtain previous historical trigger data indicative of how the previous proposed alert would have functioned if applied to the operational data for the period of time;

causing the output device to provide the previous historical data to the user; and

causing the input device to receive, from the user, a threshold different from the previous threshold;

## 22

wherein the trigger condition comprises the threshold.

20. The computer program product of claim 15, wherein the computer program code is further configured to cause the at least one processor to perform the steps of:

detecting that the operational data satisfy the trigger condition; and

responsive to detection of satisfaction of the trigger condition, initiating transmission of the user notification of satisfaction of the trigger condition.

21. The computer program product of claim 15, wherein the computer program code is further configured to cause the at least one processor to receive the proposed alert by causing the at least one processor to receive the proposed alert from a first user;

and wherein the computer program code is further configured to cause the at least one processor to perform the steps of:

comparing the proposed alert with a previous alert previously set by a second user different from the first user;

responsive to comparison of the proposed alert with the previous alert, detecting that the proposed alert is similar to the previous alert; and

responsive to detection that the proposed alert is similar to the previous alert, causing the output device to provide a user-selectable option to follow the previous alert.

22. The computer program product of claim 15, wherein the computer program code is further configured to cause the at least one processor, prior to receiving the proposed alert, to perform the steps of:

aggregating the operational data from the database of operational data to generate one or more aggregated operational data sets; and

causing a data store to store the one or more aggregated operational data sets in the database of operational data;

wherein the computer program code configured to cause the at least one processor to compare the trigger condition with the database of operational data comprises computer program code configured to cause the at least one processor to compare the trigger condition with the one or more aggregated operational data sets;

and wherein the computer program code configured to cause the at least one processor to aggregate the operational data from the database of operational data to generate the one or more aggregated operational data sets comprises computer program code configured to cause the at least one processor to perform the steps of:

aggregating the operational data from the database of operational data to generate a first version of a first aggregated operational data set;

causing the data store to store the first version of the first aggregated operational data set;

after generation of the first version of the first aggregated operational data set and after updating of the operational data to store updated operational data in the database of operational data, aggregating the updated operational data from the database of operational data to generate a second version of the first operational data set; and

causing the data store to store the second version of the first aggregated operational data set without deleting the first version of the first aggregated data set;

and wherein the computer program code is further configured to cause the at least one processor to perform the steps of:

comparing the first version of the first operational data set with the second version of the first operational data set to obtain trending data indicative of how the operational data changed; and



## 23

causing the output device to provide the trending data to the user.

**23.** A system for setting an alert pertinent to operation of an enterprise, the system comprising:

a processor, configured to:  
 receive a proposed alert comprising a trigger condition;  
 and

compare the trigger condition with a database of operational data related to operation of the enterprise over a period of time to obtain historical trigger data indicative of how the proposed alert would have functioned if applied to the operational data for the period of time;

an output device, communicatively coupled to the processor, configured to:

provide the historical trigger data to a user; and

an input device, communicatively coupled to the processor, configured to:

receive user input;

and wherein the processor is further configured, responsive to receipt of the user input, to set an alert that specifies that, when the operational data satisfy the trigger condition, user notification of satisfaction of the trigger condition is provided.

**24.** The system of claim **23**, wherein the trigger condition comprises a metric, stored on a periodic basis in the operational data, a threshold value, and an operator selected from the group consisting of the metric being greater than the threshold, the metric being less than the threshold, and the metric being equal to the threshold;

and wherein the input device is further configured to receive the proposed alert by receiving the threshold by receiving text from the user.

**25.** The system of claim **23**, wherein:

the trigger condition comprises a metric, stored on a periodic basis in the operational data, a threshold value, and an operator selected from the group consisting of the metric being greater than the threshold, the metric being less than the threshold, and the metric being equal to the threshold;

the output device comprises a display screen configured to displaying a data visualization of at least a portion of the operational data on the display screen; and

the input device is further configured to receive the proposed alert by receiving the threshold by receiving user indication of a portion of the data visualization corresponding to the threshold.

**26.** The system of claim **23**, wherein:

the output device comprises a display screen; and

the output device is further configured to provide the historical trigger data to the user by displaying, on the display screen, a selection from the group consisting of: text that indicates, to the user, how many times the trigger condition was met within the period of time; and

a data visualization that indicates, to the user, how many times the trigger condition was met within the period of time.

**27.** The system of claim **23**, wherein the processor is further configured, prior to receiving the proposed alert, to:

receive a previous proposed alert comprising a previous trigger condition comprising a previous threshold; and compare the previous trigger condition with the database of operational data to obtain previous historical trigger data indicative of how the previous proposed alert would have functioned if applied to the operational data for the period of time;

## 24

and wherein:

the output device is further configured to provide the previous historical data to the user;

the input device is further configured to receive, from the user, a threshold different from the previous threshold; and the trigger condition comprises the threshold.

**28.** The system of claim **23**, wherein the processor is further configured to:

detect that the operational data satisfy the trigger condition; and

responsive to detection of satisfaction of the trigger condition, initiate transmission of the user notification of satisfaction of the trigger condition.

**29.** The system of claim **23**, wherein the processor is further configured to:

receive the proposed alert by receiving the proposed alert from a first user;

compare the proposed alert with a previous alert previously set by a second user different from the first user; and

responsive to comparison of the proposed alert with the previous alert, detecting that the proposed alert is similar to the previous alert;

and wherein the output device is further configured, responsive to detection that the proposed alert is similar to the previous alert, to provide a user-selectable option to follow the previous alert.

**30.** The system of claim **23**, wherein the processor is further configured, prior to receiving the proposed alert, to:

aggregate the operational data from the database of operational data to generate one or more aggregated operational data sets;

and wherein:

the system further comprises a data store configured to store the one or more aggregated operational data sets in the database of operational data;

the processor is further configured to compare the trigger condition with the database of operational data by comparing the trigger condition with the one or more aggregated operational data sets;

the processor is further configured to aggregate the operational data from the database of operational data to generate the one or more aggregated operational data sets by aggregating the operational data from the database of operational data to generate a first version of a first aggregated operational data set;

the data store is further configured to store the first version of the first aggregated operational data set;

the processor is further configured to aggregate the operational data from the database of operational data to generate the one or more aggregated operational data sets by, after generation of the first version of the first aggregated operational data set and after updating of the operational data to store updated operational data in the database of operational data, aggregating the updated operational data from the database of operational data to generate a second version of the first operational data set;

the data store is further configured to store the second version of the first aggregated operational data set without deleting the first version of the first aggregated data set;

the processor is further configured to compare the first version of the first operational data set with the second version of the first operational data set to obtain trending data indicative of how the operational data changed;

and the output device is further configured to provide the trending data to the user.

\* \* \* \* \*