

US009097436B1

(12) **United States Patent**
Smelcer et al.

(10) **Patent No.:** US 9,097,436 B1
(45) **Date of Patent:** Aug. 4, 2015

(54) **INTEGRATED DUAL CHAMBER BURNER WITH REMOTE COMMUNICATING FLAME STRIP**

(75) Inventors: **Jim C. Smelcer**, Hermitage, TN (US);
Brian J. Iske, Murfreesboro, TN (US);
Neil W. Rolph, Lebanon, TN (US);
Mohamed M. Doura, Mount Juliet, TN (US)

(73) Assignee: **Lochinvar, LLC**, Lebanon, TN (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 1157 days.

(21) Appl. No.: **12/978,681**

(22) Filed: **Dec. 27, 2010**

(51) **Int. Cl.**

F24H 1/28 (2006.01)
F23N 1/02 (2006.01)
F22B 5/00 (2006.01)
F23D 14/02 (2006.01)
F22B 5/02 (2006.01)
F22D 5/00 (2006.01)
F23D 14/08 (2006.01)
F23D 14/12 (2006.01)
F23L 9/00 (2006.01)
F23N 3/00 (2006.01)
F24H 1/10 (2006.01)
F24H 9/20 (2006.01)

(52) **U.S. Cl.**

CPC ... **F24H 1/28** (2013.01); **F22B 5/00** (2013.01);
F22B 5/02 (2013.01); **F22D 5/00** (2013.01);
F23D 14/02 (2013.01); **F23D 14/08** (2013.01);
F23D 14/12 (2013.01); **F23L 9/00** (2013.01);
F23N 1/02 (2013.01); **F23N 3/00** (2013.01);
F24H 1/10 (2013.01); **F24H 9/20** (2013.01)

(58) **Field of Classification Search**

None

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

108,050 A	10/1870	Raisbeck et al.
D14,883 S	3/1884	Arci et al.
469,731 A	3/1892	Althouse
514,338 A	2/1894	Row
629,245 A	7/1899	Frank
691,978 A	1/1902	Smith et al.
770,599 A	9/1904	Monteagle
811,016 A	1/1906	Whyte et al.
910,192 A	1/1909	Grouvelle et al.
951,215 A	3/1910	Millan
1,391,871 A	9/1921	Volk

(Continued)

FOREIGN PATENT DOCUMENTS

JP	57207719	12/1982
JP	58052905	3/1983

(Continued)

OTHER PUBLICATIONS

Exhibit A: Aerco Benchmark literature. (undated but admitted to be prior art).

(Continued)

Primary Examiner — Gregory Huson


Assistant Examiner — Eric Gorman

(74) *Attorney, Agent, or Firm* — Lucian Wayne Beavers;
Patterson Intellectual Property Law, PC

(57) **ABSTRACT**

A dual chamber burner assembly provides a header, a first burner chamber adjacent the header, and a second burner chamber on an opposite side of the first burner chamber from the header. The second burner chamber is provided with a flame sensor portion extending back through the first burner chamber toward the header so that first and second flame sensors may be utilized to detect flame in the first and second chambers, respectively.

21 Claims, 13 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

1,448,075 A 3/1923 Melville
 1,780,110 A 10/1930 Bliss
 1,780,319 A 11/1930 Sonneborn
 1,881,610 A 10/1932 Hyde
 1,951,063 A 3/1934 Reimann et al.
 1,979,859 A 11/1934 Brown
 1,991,788 A * 2/1935 Cartter 138/38
 2,162,620 A * 6/1939 Larsen 122/19.1
 2,205,893 A 6/1940 Unger
 2,335,687 A 11/1943 Modine
 2,365,688 A 12/1944 Dewey
 2,506,120 A 5/1950 Turner et al.
 2,621,721 A 12/1952 Manteria
 3,002,519 A 10/1961 Wright et al.
 3,004,330 A 10/1961 Wilkins
 3,177,936 A 4/1965 Walter
 3,407,025 A * 10/1968 Hardison 431/329
 3,486,834 A 12/1969 Frey et al.
 3,516,773 A 6/1970 Rosenberg et al.
 3,698,429 A 10/1972 Lowe et al.
 3,724,523 A 4/1973 Mattern
 3,763,849 A * 10/1973 Pfluger et al. 126/101
 3,870,585 A * 3/1975 Kearns et al. 159/4.02
 3,875,997 A 4/1975 Newson et al.
 3,903,846 A * 9/1975 Elliott et al. 122/4 R
 3,964,873 A 6/1976 Aramaki et al.
 4,014,962 A 3/1977 del Notario
 4,029,451 A * 6/1977 Farnia 122/18.4
 4,095,929 A 6/1978 McCartney
 4,190,105 A 2/1980 Dankowski
 4,206,806 A 6/1980 Togashi
 4,270,470 A 6/1981 Barnett et al.
 4,271,789 A * 6/1981 Black 122/14.22
 4,293,315 A * 10/1981 Sederquist 48/94
 4,393,926 A 7/1983 Appel
 4,434,112 A 2/1984 Pollock
 4,462,342 A * 7/1984 Welden 122/448.1
 4,466,479 A 8/1984 MacLean
 4,511,327 A 4/1985 Ogino et al.
 4,548,138 A 10/1985 Korenberg
 4,599,066 A 7/1986 Granberg
 4,632,090 A 12/1986 York
 4,678,116 A * 7/1987 Krishnakumar et al. ... 236/25 A
 4,688,521 A 8/1987 Korenberg
 4,723,513 A * 2/1988 Vallett et al. 122/18.4
 4,725,224 A 2/1988 Kanter
 4,793,798 A 12/1988 Sabin
 4,793,800 A * 12/1988 Vallett et al. 431/328
 4,852,524 A * 8/1989 Cohen 122/448.1
 4,959,009 A 9/1990 Hemsath
 5,024,379 A * 6/1991 Dempsey 237/16
 5,080,577 A 1/1992 Bell et al.
 5,099,576 A 3/1992 Shinmura
 5,131,836 A * 7/1992 Coppin 431/12
 5,161,739 A * 11/1992 Saito et al. 237/9 R
 5,190,454 A 3/1993 Murray et al.
 5,251,693 A 10/1993 Zifferer
 5,311,661 A 5/1994 Zifferer
 5,409,057 A 4/1995 Zifferer
 5,437,249 A * 8/1995 Adams et al. 122/18.3
 5,443,040 A 8/1995 Kaji et al.
 5,470,224 A * 11/1995 Bortz 431/182
 5,488,942 A * 2/1996 Maughan 126/39 E
 5,551,504 A 9/1996 Zifferer
 5,579,832 A 12/1996 Le Gauyer
 5,590,711 A 1/1997 Ishida et al.
 5,644,842 A 7/1997 Coleman
 5,662,467 A * 9/1997 Jones 431/175
 5,697,330 A * 12/1997 Yetman et al. 122/14.21
 5,839,505 A 11/1998 Ludwig et al.
 5,881,681 A * 3/1999 Stuart 122/18.31
 5,915,952 A 6/1999 Manning et al.
 5,915,960 A 6/1999 Check et al.

5,960,870 A 10/1999 Takahashi et al.
 5,989,020 A * 11/1999 Glass et al. 432/161
 6,003,477 A * 12/1999 Valcic 122/14.21
 6,044,803 A * 4/2000 Hamos et al. 122/18.4
 6,082,310 A * 7/2000 Valcic et al. 122/13.01
 6,082,993 A * 7/2000 O'Leary et al. 431/18
 6,085,699 A * 7/2000 Valcic et al. 122/13.01
 6,113,386 A * 9/2000 Shannon et al. 432/59
 6,206,687 B1 * 3/2001 Redington 431/90
 6,253,834 B1 * 7/2001 Sterner 165/80.3
 6,269,755 B1 8/2001 Boswell et al.
 6,273,141 B1 8/2001 DeSelle
 6,283,159 B1 9/2001 Tada
 6,363,868 B1 * 4/2002 Boswell et al. 110/213
 6,397,927 B1 * 6/2002 Sterner 165/80.3
 6,397,929 B1 * 6/2002 Sterner 165/80.3
 6,428,312 B1 * 8/2002 Smelcer et al. 431/329
 6,435,267 B1 * 8/2002 Sterner 165/96
 6,435,862 B1 * 8/2002 Fioriti et al. 431/354
 6,474,409 B1 * 11/2002 Sterner 165/96
 6,485,289 B1 11/2002 Kelly et al.
 6,488,079 B2 12/2002 Zifferer
 6,553,946 B1 * 4/2003 Abraham et al. 122/14.22
 6,565,361 B2 * 5/2003 Jones et al. 438/6
 6,619,951 B2 * 9/2003 Bodnar et al. 431/329
 6,629,523 B2 10/2003 Saltzman et al.
 6,659,026 B1 12/2003 Hendricks et al.
 6,685,462 B2 * 2/2004 Jones et al. 431/8
 6,694,926 B2 * 2/2004 Baese et al. 122/14.2
 6,780,008 B2 * 8/2004 Koch et al. 431/354
 6,923,035 B2 8/2005 Zifferer et al.
 6,941,754 B2 * 9/2005 Aldridge et al. 60/524
 6,945,197 B2 * 9/2005 Ryoo 122/15.1
 6,969,250 B1 * 11/2005 Kawamura et al. 431/185
 7,044,123 B2 5/2006 Rigamonti
 7,188,481 B2 3/2007 DeYoe et al.
 7,614,366 B2 * 11/2009 Arnold et al. 122/18.1
 7,703,705 B2 4/2010 Ganzer
 7,748,684 B2 7/2010 Ito et al.
 8,100,381 B2 1/2012 Roschke et al.
 8,167,610 B2 * 5/2012 Raleigh et al. 431/171
 8,366,014 B2 * 2/2013 Ene et al. 237/19
 8,402,927 B2 * 3/2013 Home 122/18.3
 8,418,753 B2 * 4/2013 Hirokawa et al. 165/177
 2006/0194160 A1 8/2006 Kokuo et al.
 2007/0044787 A1 3/2007 Brice
 2007/0209788 A1 9/2007 Jing et al.
 2007/0215225 A1 9/2007 Koch et al.
 2008/0076079 A1 3/2008 Eggebrecht et al.
 2008/0105176 A1 5/2008 Chang et al.
 2008/0197205 A1 * 8/2008 Ene et al. 237/19
 2008/0216771 A1 * 9/2008 Paine 122/14.2
 2010/0095905 A1 * 4/2010 Smelcer 122/14.2
 2010/0116225 A1 * 5/2010 Smelcer 122/17.1
 2010/0154778 A1 * 6/2010 Sun 126/39 E
 2010/0269766 A1 * 10/2010 Home 122/18.3
 2010/0310998 A1 * 12/2010 Raleigh et al. 431/8
 2011/0083593 A1 * 4/2011 Hunter et al. 110/346
 2011/0146594 A1 * 6/2011 Smelcer 122/18.3
 2012/0111434 A1 5/2012 Cadeau et al.
 2012/0132836 A1 5/2012 Cadeau et al.
 2012/0153200 A1 6/2012 Turrin et al.
 2014/0113238 A1 * 4/2014 Kiarostami et al. 431/2
 2014/0199643 A1 * 7/2014 Smelcer 431/12

FOREIGN PATENT DOCUMENTS

JP 61079914 A 4/1986
 JP 1314809 12/1989
 JP 3263508 A 11/1991
 JP 07190484 A 7/1995
 JP 2002174420 A 6/2002
 JP 2006038418 A 2/2006
 SE 518478 C2 10/2002
 WO 2004097274 A1 11/2004

(56)

References Cited

FOREIGN PATENT DOCUMENTS

WO 2011009793 A1 1/2011
WO 2012079167 A1 6/2012

OTHER PUBLICATIONS

Exhibit B: Lochinvar COPPER-FIN literature. (undated but admitted to be prior art).

Exhibit C: "Notification of Transmittal of the International Search Report and the Written Opinion of the International Searching Authority, or the Declaration" mailing date Dec. 16, 2009.

Co-pending U.S. Appl. No. 12/252,841 for "Gas Fired Modulating Water Heating Appliance With Dual Combustion Air Premix Blowers" filed Oct. 16, 2008, to Jim C. Smelcer.

Co-pending U.S. Appl. No. 12/691,108 for "Integrated Dual Chamber Burner" filed Jan. 21, 2010, to Jim C. Smelcer.

* cited by examiner




FIG. 1





FIG. 2






FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17

1

INTEGRATED DUAL CHAMBER BURNER WITH REMOTE COMMUNICATING FLAME STRIP

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates generally to a single burner assembly with separate integrated chambers, and more particularly, but not by way of limitation, to such a burner which is especially suited for use with high capacity water heating appliances wherein it is desired to obtain high turndown ratios with respect to burner modulation.

2. Description of the Prior Art

Most conventional water heating appliance technologies utilize a single chamber burner designed to operate at a fixed flow rate of combustion air and fuel gas to the burner. Such technologies require that the appliance cycles on and off in response to a control system which monitors the temperature of heated water in a storage tank or elsewhere in various conduits of the water supply system. One example of such a typical prior art system which is presently being marketed by the assignee of the present invention is that shown in U.S. Pat. Nos. 4,723,513 and 4,793,800 to Vallett et al., the details of which are incorporated herein by reference.

It has been recognized that, in circumstances where there is a substantially varying demand for heat input to the water supply system, greater energy efficiencies can be achieved through the use of a water heating appliance which is capable of operating at load matching input strategies wherein the appliance is permitted to control independent manifolds of groups of fixed input single chamber burners to turn on and off based on a predetermined load matching control strategy such that operation at different energy inputs is obtainable. One example of such a system is that sold by Lochinvar Corporation, the assignee of the present invention, under the trademark COPPER-FIN II®. The Lochinvar COPPER-FIN II® system utilizes a plurality of staged burners which can be brought on line or taken off line as the demand for heat energy changes. The COPPER-FIN II® appliance includes multiple banks, for example, first, second, third and fourth stages. It initially turns on all four stages of burners, and as it approaches the desired temperature, it sequentially shuts off units to decrease input energy. This type of system provides variable input, but it is not continuously variable. Instead the input can be changed only in substantial increments corresponding to the heat input of one burner stage.

The prior art has also included proposals for water heaters with predominately single chamber burners having continuously variable input over a limited range of inputs. Two such systems are shown in U.S. Pat. No. 4,852,524 to Cohen and U.S. Pat. No. 5,881,681 to Stuart. These systems, which have been marketed by AERCO International, Inc. under the Benchmark name, utilize a nozzle mix burner which receives independent streams of combustion air and fuel gas. A fuel/air valve is utilized to electronically and simultaneously control the flow of air through the air line and fuel through the fuel line so as to provide a varying input of fuel and air while maintaining a constant fuel to air ratio. The blower speed remains constant on these systems. The Stuart U.S. Pat. No. 5,881,681 suggests that the system described therein can achieve turndown ratios as high as 15:1. AERCO's advertising literature for its Benchmark model water heaters suggests that they achieve turndown ratios as high as 20:1.

More recently the assignee of the present invention has developed a continuously variable water heating appliance with variable air and fuel input, as shown in U.S. Pat. No.

2

6,694,926 to Baese et al. In the Baese apparatus a variable flow blower provides premix combustion air and fuel to a single chamber burner at a controlled blower flow rate within a blower flow rate range. This allows the heat input of the water heating appliance to be continuously varied within a substantial flow range having a turndown ratio of as much as 4:1.

Inherent physical limitations on the turndown ratio which can be achieved with a single chamber burner heating apparatus of prior designs makes it difficult to achieve a continuous range of heat input over a large operating range from a very low low end for low heat demand situations to a very high high end for high heat demand situations. One prior solution to this difficulty is to utilize a plurality of commonly controlled heat exchangers such as those of the Baese et al. patent described above. One such system is described for example in U.S. Patent Application Publication No. 2008/0216771 of Paine et al., and assigned to the assignee of the present invention. While such multiple single chamber burner modulating systems do solve the problem of providing continuous modulation over a wide range of heat demands, they do so at the cost of increased complexity of plumbing to connect the multiple units and increased complexity of control systems to coordinate the operation of the units.

Thus there is a continuing need for a relatively large capacity single unit heating apparatus which can provide continuous modulation of heat input over a wide range of heat demands, and specifically, for burner assemblies that can operate reliably over a much wider range of heat demands within the heating apparatus.

SUMMARY OF THE INVENTION

In one aspect of the invention a burner assembly includes a header including a first fuel and air inlet and a second fuel and air inlet. A first burner chamber is located adjacent the header. The first fuel and air inlet are communicated with the first burner chamber. A second burner chamber is located on an opposite side of the first burner chamber from the header. The second fuel and air inlet are communicated with the second burner chamber. The second burner chamber has a flame sensor portion extending into the first burner chamber back toward the header. The flame sensor portion includes a flame indicating burner surface of the second burner chamber located adjacent the header, so that a flame sensor located adjacent the flame sensor portion of the second burner chamber need not be exposed to flame from the first burner chamber.

In another aspect of the invention a burner chamber includes a first foraminous outer wall portion being partially cylindrical in shape and having a cylindrical gap. The burner assembly includes a second foraminous outer wall portion including a finger extending into the circumferential gap. At least one interior wall separates the burner chamber into first and second interior zones, the first and second interior zones being adjacent the first and second foraminous outer wall portions respectively. The at least one interior wall includes a duct communicating the second interior zone with the finger of the second foraminous outer wall portion. A first fuel and air inlet passage is communicated with the first interior zone. A second fuel and air inlet passage is communicated with the second interior zone. A header including a header wall is spaced from the at least one interior wall. The first interior zone is cylindrical in shape and has first and second ends closed by the header wall and the at least one interior wall, respectively. The second interior zone is cylindrical in shape and has a first end enclosed by the at least one interior wall and

3

a second end covered by foraminous material comprising part of the second foraminous outer wall portion.

In another aspect of the invention a water heating apparatus includes a multi-stage burner including a header having first and second inlets. First and second internal zones are separated by an internal barrier, the first and second internal zones being communicated with the first and second inlets, respectively. First and second external foraminous burner wall portions at least partially define the first and second interior internal zones, respectively. The water heating apparatus further includes a first blower communicated with the first internal zone of the burner for providing premixed fuel and air to the first internal zone to provide a first burner stage. A second blower is communicated with the second internal zone of the burner for providing premixed fuel and air to the second internal zone to provide a second burner stage. A first flame sensor is located adjacent the first external foraminous burner wall portion. A second flame sensor is located adjacent the second foraminous burner wall portion. An automated control system is connected to the first and second blowers, the control system operable to provide air without fuel to the second internal zone when the second burner stage is not burning, so that air flowing through the second internal zone prevents flame from the first burner stage from being detected by the second flame sensor when the second burner stage is not burning.

In another aspect of the invention a burner assembly includes a header including a first fuel and air inlet and a second fuel and air inlet. A first burner chamber is located adjacent the header. The first fuel and air inlet are communicated with the first burner chamber. A second burner chamber is located on an opposite side of the first burner chamber from the header. The second fuel and air inlet are communicated with the second burner chamber. The second burner chamber has an extension portion extending into the first burner chamber back toward the header. The extension portion includes a remote communicating flame strip of the second burner chamber.

Accordingly it is an object of the present invention to provide a burner for a water heating apparatus having a high turndown ratio.

Another object of the present invention is the provision of a burner for a high capacity water heating apparatus which is continuously modulated over a large range of inputs.

Another object of the present invention is to apply multiples of already existing smaller capacity blowers and gas valves in a manner such that very large inputs can be achieved without the need for a single large customized blower and/or large gas valve train components that may not exist today, or are impractical to apply due to size and cost within the desired footprint of the appliance.

Another object of the present invention is the provision of a multiple chamber burner for a water heating apparatus having a burner assembly and having one or more low range blower assemblies providing fuel and air to the individual burner chambers within the burner assembly within a low flow rate range, and having a high range blower assembly providing fuel and air to the burner assembly within a high flow rate range.

Another object of the present invention is to provide a multiple chamber burner for a water heating apparatus having the ability to supply supplemental air to the combustion chamber and venting system independently for purposes of preventing the formation of condensation of combustion gases within the venting system.

Another object of the present invention is the provision of a burner for a water heating apparatus having two or more

4

blowers feeding as many independent chambers within a single burner assembly such that the aggregate firing inputs of each independent chamber provides the total desired input of the appliance, with safety systems for preventing backflow of combustion gases into either one of the blower assemblies.

Another object of the present invention is the provision of a multiple chamber burner for a single water heating apparatus having a turndown ratio of at least 25:1 theoretically with no limit in turndown ratio provided the makeup of multiple chamber burners achieves the range of specific inputs desired.

And another object of the present invention is the provision of a multiple chamber burner assembly for use with a multiple blower system supplying combustion air and fuel independently to each independent chamber within the burner.

And another object of the present invention is the provision of a multiple chamber burner for use in methods of operating water heating apparatus utilizing multiple blower assemblies supplying combustion air and fuel independently to each independent chamber within the burner.

And another object of the present invention is the provision of a multiple chamber burner for a limitless input capacity water heating apparatus capable of utilizing direct spark ignition.

Another object of the present invention is the provision of a dual chamber burner having flame sensors for both chambers.

Another object of the present invention is the provision of a dual chamber burner providing for a flame sensor for a distalmost burner portion without having that flame sensor exposed to flame from the other burner portions.

And another object of the present invention is the provision of a water heating apparatus utilizing a multi-stage burner and a multi-blower system wherein air without fuel can be provided to non-operating burner stages.

Another object of the present invention is the provision of a multiple chamber burner with improved carry-over lighting of second and subsequent burner stages.

And another object of the present invention is the elimination/reduction of resonant burner noise in a multiple chamber burner as a result of the lack of ability for either burner to set up a resonant wave form around the total perimeter of the burner.

Other and further objects, features and advantages of the present invention will be readily apparent to those skilled in the art upon a reading of the following disclosure when taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic illustration of a water heating apparatus having a dual blower system including a low range blower assembly and a high range blower assembly.

FIG. 2 is a schematic illustration of the control system for the heating apparatus of FIG. 1.

FIG. 3 is an elevation cross-section view of the water heating apparatus of FIG. 1.

FIG. 4 is an enlarged elevation cross-section view of one embodiment of the burner assembly and surrounding heat exchanger structure of the apparatus of FIG. 3.

FIG. 5 is a cross-section view taken along line 5-5 of FIG. 3 showing internal details of a blower transition manifold.

FIG. 6 is a perspective view of another embodiment of a burner assembly for use in a heater apparatus like that of FIG. 1.

FIG. 7 is a top plan view of the burner of FIG. 6.

FIG. 8 is an elevation section schematic view of the burner of FIG. 6 taken along line 8-8 of FIG. 7.

5

FIG. 9 is a top plan view of the burner of FIG. 6 assembled with a transition manifold.

FIG. 10 is a side elevation view of the burner and transition manifold of FIG. 9.

FIG. 11 is a schematic side elevation view of another embodiment of a burner assembly having three cylindrical chambers.

FIG. 12 is a schematic plan view of another embodiment of a burner assembly having three pie-shape chambers.

FIG. 13 is a schematic side elevation view of another embodiment of a burner assembly providing for a flame sensor for the lower burner chamber.

FIG. 14 is a schematic section view taken along line 14-14 of FIG. 13.

FIG. 15 is a schematic plan view of the burner assembly of FIG. 13.

FIG. 16 is a perspective schematic view of the interior divider separating the first and second burner chambers of the burner apparatus of FIG. 13.

FIG. 17 is a perspective schematic view of a three chamber burner with remote communicating flame strips on the second and third chambers.

DETAILED DESCRIPTION OF THE INVENTION

Referring now to the drawings, and particularly to FIG. 1, a water heating apparatus is shown and generally designated by the numeral 10. As used herein, the terms water heating apparatus or water heating appliance or water heater apparatus or water heater all are used interchangeably and all refer to an apparatus for heating water, including both hot water boilers and water heaters that do not actually "boil" the water. Such apparatus are used in a wide variety of commercial and residential applications including potable water systems, space heating systems, pool heaters, process water heaters, and the like. Also, the water being heated can include various additives such as antifreeze or the like.

The water heating apparatus 10 illustrated in FIG. 1 is a fire tube heater. A fire tube heater is one in which the hot combustion gases from the burner flow through the interior of a plurality of tubes. Water which is to be heated flows around the exterior of the tubes. The operating principles of the apparatus 10 are equally applicable, however, to water heaters having the water flowing through the interior of the tubes and having the hot combustion gases on the exterior of the tubes, such as for example the design shown in U.S. Pat. No. 6,694,926 to Baese et al. discussed above.

The water heating apparatus 10 shown in FIG. 1 is connected to a heat demand load in a manner sometimes referred to as full flow heating wherein a water inlet 12 and water outlet 14 of the heating apparatus 10 are directly connected to a flow loop 16 which carries the heated water to a plurality of loads 18A, 18B, 18C and 18D. The loads 18A-18D may, for example, represent the various heating loads of heat radiators contained in different areas of a building. Heat to a given area of the building may be turned on or off by controlling zone valves 20A-20D. Thus as a radiator is turned on and off or as the desired heat is regulated in various zones of the building, the water flow permitted to that zone by zone valve 20 will vary, thus providing a varying water flow through the flow loop 16 and a varying heat load on the heating apparatus 10. A supply pump 22 in the flow loop 16 circulates the water through the system. The operating principles of the apparatus 10 are, however, also applicable to heating apparatus connected to other types of water supply systems, such as for example a system using a primary flow loop for the heat loads, with the water heating apparatus being in a secondary flow

6

loop so that not all of the water circulating through the system necessarily flows back through the water heater. An example of such a primary and secondary flow loop system is seen in U.S. Patent Application Publication No. 2008/0216771 of Paine et al., filed Mar. 9, 2007 and entitled "Control System for Modulating Water Heater", and assigned to the assignee of the present invention, the details of which are incorporated herein by reference.

The apparatus 10 includes an outer jacket 24. The water inlet 12 and water outlet 14 communicate through the jacket 24 with a water chamber 26 or water side 26 of the heat exchanger. In an upper or primary heat exchanger portion 28, an inner heat exchange wall or inner jacket 30 has a combustion chamber or combustion zone 32 defined therein. The lower end of the combustion chamber 32 is closed by an upper tube sheet 34. A plurality of fire tubes 36 have their upper ends connected to upper tube sheet 34 and their lower ends connected to a lower tube sheet 38. The fire tubes extend through a secondary heat exchanger portion 40 of the heat exchanger apparatus 10.

A burner assembly or burner apparatus 42 is located within the combustion chamber 32. The burner assembly 42 burns premixed fuel and air within the combustion chamber 32. The hot gases from the combustion chamber 32 flow down through the fire tubes 36 to an exhaust collector 44 and out an exhaust flue 46.

Water from flow loop 16 to be heated flows in the water inlet 12, then around the exterior of the fire tubes 36 and up through a secondary heat exchanger water side portion 48 of water side 26, and continues up through a primary heat exchanger water side portion 50 of water side 26, and then out through water outlet 14. It will be appreciated that the interior of the apparatus 10 includes various baffles for directing the water flow in such a manner that it generally uniformly flows around all of the fire tubes 36 and through the water chamber 50 of primary heat exchanger 28 between the outer jacket 24 and inner jacket 30. As the water flows upward around the fire tubes 36 of the secondary heat exchanger 40 the water is heated by heat transfer from the hot combustion gases inside of the fire tubes 36 through the walls of the fire tubes 36 into the water flowing around the fire tubes 36. As the heated water continues to flow upward through the water side 50 of primary heat exchanger 28 additional heat is transferred from the combustion chamber 32 through the inner jacket 30 into the water contained in water side 50.

The Dual Blower Assemblies

Referring again to FIG. 1, first and second blower assemblies 52 and 54, respectively, are connected to the burner apparatus 42 for supplying premixed fuel and air to the burner assembly 42. Each of the blower assemblies is a variable flow premix blower assembly.

The first blower assembly 52 includes a variable flow blower 56 driven by a variable frequency drive motor. A venturi 58 is provided for mixing combustion air and fuel gas. An air supply duct 60 provides combustion air to the venturi 58. A gas supply line 62 provides fuel gas to the venturi 58. A gas control valve 64 is disposed in supply line 62 for regulating the amount of gas entering the venturi 58. The gas control valve 64 includes an integral shutoff valve. In some embodiments the gas control valve and the venturi may be combined into a single integral unit. The gas control valve is preferably a ratio gas valve for providing fuel gas to the venturi 58 at a variable gas rate which is proportional to the negative air pressure within the venturi caused by the speed of the blower, hence varying the flow rate entering the venturi 58, in order to maintain a predetermined air to fuel ratio over the flow rate range within which the blower 56 operates. In order to pro-

vide the variable input operation of the burner assembly **42**, the variable flow blower **56** delivers the premixed combustion air and fuel gas to the burner assembly **42** at a controlled blower flow rate within a first blower flow rate range extending from a first range low end to a first range high end. Thus the first blower assembly **52** has a first turndown ratio at least equal to the first range high end divided by the first range low end.

Similarly, the second blower assembly **54** includes variable speed blower **66**, venturi **68**, air supply duct **70**, gas supply line **72** and gas valve **74**. The second blower assembly **54** supplies premixed fuel and air to the burner assembly **42** and has a second flow rate range extending from a second range low end to a second range high end so that the second blower assembly has a second turndown ratio equal to the second range high end divided by the second range low end.

Although in the embodiment illustrated the first and second blower assemblies **52** and **54** include completely separate fuel air mixing devices, namely their venturis **58** and **68**, it is conceivable to develop a system in which the two blower assemblies would draw premixed fuel and air from a common mixing device.

In one embodiment the first and second blower assemblies **52** and **54** are low range and high range blower assemblies, respectively, with the second range low end being substantially equal to the first range high end. With that arrangement the continuous combined turndown ratio of the two blower assemblies is at least as great as the product of the first turndown ratio multiplied times the second turndown ratio. For example, if the first or low range blower assembly **52** has a low range low end corresponding to an 80,000 BTU/hr heat input and a low range high end corresponding to a 400,000 BTU/hr heat input, it has a first turndown ratio of 5:1. And if the second or high range blower assembly **54** has a high range low end corresponding to a 400,000 BTU/hr heat input and a high range high end corresponding to a 2,000,000 BTU/hr heat input, then the second turndown ratio is also 5:1. Thus in the example just given the continuous combined turndown ratio from 80,000 BTU/hr to 2,000,000 BTU/hr is 25:1 which is at least as great as the product of the first turndown ratio multiplied times the second turndown ratio. As noted in the example just given, it is conventional in the heater industry to describe the input of a heating apparatus in terms of heat energy per unit time consumed by the burner, i.e. the heat energy of the combustion gas burned in the burner. Thus it is conventional to also describe the volumetric output per unit time or flow rate range of the blower as corresponding to the heat input rating of the heating apparatus.

The benefits of the dual blower system can also be achieved to a lesser degree, however, with first and second blower assemblies whose flow rate ranges to some degree or even entirely overlap.

Thus for example the first and second blower assemblies **52** and **54** could have substantially equal flow rate ranges in which case the continuous combined turndown ratio is substantially equal to the sum of the first and second turndown ratios.

Or, more generally, if there is partial but incomplete overlap of the first and second flow rate ranges the continuous combined turndown ratio will be something less than the product of the first turndown ratio multiplied times the second turndown ratio, and something greater than the sum of the first and second turndown ratios.

It is desirable, however, that there be no substantial gap between the first and second flow rate ranges. Thus the second range low end should be substantially equal to or less than the first range high end.

As schematically illustrated in FIG. 2, the apparatus **10** includes a control system **76** operably associated with the first and second blower assemblies **52** and **54** to selectively operate one or both of the blower assemblies as needed in response to heat demand on the heating apparatus **10**. The control system **76** causes the first and second blower assemblies **52** and **54** to supply premixed fuel and air to the burner assembly **42** in a continuously variable combined flow rate range extending from the first range low end to at least the second range high end. In the embodiment where the first blower assembly **52** is a low range blower assembly **52** and the second blower assembly **54** is a high range blower assembly **54**, the control system supplies fuel and air in a continuously variable combined flow rate range extending from the low range low end to at least the high range high end. Preferably the high range high end is at least 25 times the low range low end thus providing a 25:1 turndown ratio. This can be accomplished by choosing low and high range blower assemblies **52** and **54** having contiguous but substantially non-overlapping flow rate ranges wherein each of the blower assemblies has a 5:1 turndown ratio.

For example, an apparatus **10** having a maximum heat input of approximately 2,000,000 BTU/hr may utilize the following components. In the low range blower assembly **52** the variable speed blower **56** may be a model RG148 or its redesigned enhanced equivalent RG137 blower available from EBM Industries. The venturi and gas valve may be a combination venturi/gas valve model VR8615V available from Honeywell. In this series of components the first blower assembly **52** can provide a low flow rate range from a low range low end corresponding to a heater input of approximately 80,000 BTU/hr to a low range high end corresponding to a heater input of approximately 400,000 BTU/hr. In this example, the high range blower assembly **54** may include a variable speed blower **66** which is a model G3G200 blower available from EBM Industries. The venturi **68** may be a model VMU680A available from Honeywell. The gas valve **74** may be a model VR4734C available from Honeywell. With this combination of components the second blower assembly **54** can provide a high flow rate range extending from a high range low end corresponding to a heater input of approximately 400,000 BTU/hr to a high range high end corresponding to a heater input of approximately 2,000,000 BTU/hr.

It is noted that in the example just described the high range blower assembly includes one and only one blower **66**. It is also possible for the high range blower assembly to be made up of a plurality of smaller blowers connected in parallel to provide the desired blower output. Such an arrangement of smaller blowers manifolded together may in some situations be desirable from a practical standpoint due to the availability and lower cost of the smaller variable speed blowers. The Burner Assembly Embodiment of FIGS. 3-5

Referring now to FIG. 4 the details of construction of one embodiment of the burner assembly **42** are best seen. The burner assembly **42** is generally cylindrical in shape and extends into the combustion chamber **32** of the primary heat exchanger section **28**. Burner assembly **42** includes a header wall **78** and an interior wall **80** spaced from the header wall **78**. The interior wall **80** may also be referred to as a divider wall **80**. The interior wall separates first and second or upper and lower interior zones or plenums **82** and **84**.

A blower transition manifold **79** is attached to the header wall **78** and connects the outlets of blower assemblies **52** and **54** to the burner assembly **42**. As best seen in FIG. 5, first and second passageways **81** and **83**, respectively, are defined in the transition manifold **79**.

The outlet of first blower **56** is connected to inlet **85** of first passage **81**. The outlet of second blower **66** is connected to second inlet **87**. Check valves such as **104** (see FIG. 1) may be placed between the blowers and their respective manifold inlets.

First passage **81** has a passage outlet **89** which aligns with an opening **90** in header wall **78**, so that the output of first blower **56** is communicated to first zone **82**. It is noted that FIG. 4 is shown somewhat schematically and that the opening **90** is rotated 90° from its actual position in header wall **78**.

A duct **91** extends between divider wall **80** and header wall **78** and extends upward into the second passage **83**. Duct **91** is welded or otherwise attached to header wall **78** and divider wall **80**. The lower end of duct **91** communicates through opening **93** in divider wall **80** with the second zone **84**, and defines a passage communicating second blower **66** with second zone **84**.

The burner apparatus **42** further includes an upper neck or collar **95** attached to and extending downward from header wall **78**. A perforated cylindrical support screen **97** is attached to collar **95** and divider wall **80**. A lower support ring **99** is received in the lower end of support screen **97**. A flat lower burner screen **101** is attached to and spans across ring **99**. The header wall **78**, neck **95**, duct **91**, divider wall **80**, support screen **97**, support ring **99**, and bottom screen **101** are all preferably constructed of metal and welded together to form a structural skeleton of the burner assembly **42**.

A foraminous outer sock **103** is received about the cylindrical screen **97** and bottom screen **101** and held in place by a retaining band **105**.

First and second foraminous outer wall portions **86** and **88** of sock **103** are located adjacent the first and second interior zones **82** and **84**, respectively. The second foraminous outer wall portion **88** includes both a cylindrical portion **94** and an end portion **96** which spans the bottom screen **101**. The foraminous material from which the sock **103** is constructed may for example be a ceramic fiber weave material manufactured by 3M Company. The cylindrical portion **94** of second foraminous outer wall portion **88** and the first foraminous outer wall portion **86** may comprise a continuous cylindrical foraminous burner wall.

As is further described below, it is preferable to design the burner assembly **42** to match the capacities of the first and second blower assemblies **52** and **54** so as to provide a substantially uniform surface loading on the burner. That is, the amount of heat energy being generated per square inch of surface area of the burner should be uniform for uniform heating. Thus, if at maximum output the high range high end of the high range blower assembly is to be five times the low range high end of the low range blower assembly, then the surface area of the second foraminous outer wall portion **88** including both portions **94** and **96** thereof should be approximately five times the external surface area of the first foraminous outer wall portion **86**. More generally, it can be stated that the external surface area of the second foraminous outer wall portion **88** in that example should be in the range of from four to six times the external surface area of the first foraminous outer wall portion **86**.

The combustion chamber **32** is a relatively tight combustion chamber in that it relatively closely confines the burner assembly **42** as compared to many other types of prior art burner arrangements. The design of the burner assembly **42** and its tightly confined combustion chamber **32** allows the foraminous outer walls of the burner assembly **42** to carry very high specific loadings for high energy input. As used herein the term "specific loading" is referring to the power per unit of surface area of the foraminous outer wall portions.

Where typical prior art burner devices might have a specific loading of 2,500 BTU/in² hr to 3,600 BTU/in² hr, the burner assembly **42** of the present invention may utilize specific loadings as high as 5,600 BTU/in² hr.

The apparatus **10** preferably utilizes a direct spark ignition element **98** extending downward into the combustion chamber **32** to a location adjacent the exterior of the first foraminous outer wall portion **86** so that when the operation of the apparatus **10** is first initiated, and premixed fuel and air are flowing only from the low range blower assembly **52**, the fuel and air mixture exiting the first foraminous outer wall portion **86** can be ignited by the direct spark ignition element **98** located adjacent thereto.

In the construction illustrated in FIG. 4, the first and second foraminous outer wall portions **86** and **88** are separated only by the thickness of the interior wall **80** and are sufficiently close to each other so that flame from the first foraminous burner wall portion **86** will subsequently ignite fuel and air mixture exiting the second foraminous burner wall portion **88**. Thus only a single direct spark ignition device **98** is needed. Also only a single flame detector **120** is needed, although as explained below with regard to FIGS. 13-16, dual flame detectors may optionally be provided.

It will be appreciated that due to the presence of the interior wall **80** there will be a small gap between the exterior burner surfaces associated with the first zone **82** and second zone **84** of the burner assembly **42**. When the heating apparatus **10** is first fired up, with only the low range blower assembly **52** providing fuel to the burner assembly **42**, there will only be flame on the exterior surface **86** of the first zone **82**. Hot combustion gases will be flowing downward past the outer surface **94** of second zone **84** and upon actuation of the second blower assembly **54** those hot gases will ignite fuel being provided by high range blower assembly **54**. Although the physical gap created by divider wall **80** is preferably kept to a minimum, it will be appreciated that so long as the foraminous outer surface **94** is sufficiently close to foraminous outer surface **86** that the gases exiting the second zone **84** can be ignited, then the apparatus **10** can operate with only the single direct spark ignition element **98** initially igniting the flame from first zone **82**. Although in the embodiment illustrated in FIG. 4 the physical gap created by interior wall **80** is on the order of one inch, it is expected that a gap of several inches, perhaps as much as six inches, could be accommodated and the fuel exiting second zone **84** could still be ignited by hot gases flowing downward from the flames exiting first zone **82**. Although it is preferred for practical reasons that the burner assembly **42** be an integrally constructed burner assembly, it is conceivable to completely physically separate the burner surfaces associated with the first and second blower assemblies **52** and **54** so long as they are feeding a common combustion zone **32** and are sufficiently close that second burner surface **88** can take ignition from flame from first burner surface **86**, and so long as the design prevents physical damage from occurring to the neighboring burner.

It will be appreciated by those skilled in the art that in accordance with various industry design standards, the use of direct spark ignition elements are typically limited to relatively small heating apparatus having relatively low fuel flow rates. This is because typical standards require that there be a "trial for ignition period" of for example 4 seconds during which fuel must flow before ignition. In larger heating apparatus, particularly those providing over, for example, 400,000 BTU/hr, a 4 second flow period prior to ignition involves a substantial amount of fuel and can result in a "hard start" due to the volume of gas present upon ignition. With the heating apparatus **10**, however, utilizing a low range blower assembly

and a high range blower assembly, the advantages of the use of direct spark ignition can be enjoyed since the low range blower assembly will ignite like a typical lower range water heating apparatus, and then the high range blower assembly **54** can take its ignition from the previously ignited low range blower assembly without going through a “trial for ignition period” on the high range blower assembly.

As can be seen in FIGS. **3** and **4** the inner jacket or heat exchanger wall **30** which defines the combustion chamber **32** therewithin is made up of a first smaller diameter portion **100** and a second larger diameter portion **102**. The first zone **82** of burner assembly **42** is located within the smaller diameter portion **100**, and the second zone **84** is located within the larger diameter portion **102**. Thus the radial spacing from the first foraminous outer wall portion **86** to smaller diameter heat exchanger wall portion **100** is less than the radial spacing between the second cylindrical foraminous outer wall portion **94** and the larger diameter heat exchanger wall portion **102**. This provides improved heat transfer for the burner assembly **42** when it is operating in its low range with just the low range blower assembly **52** providing fuel air mixture to the burner assembly **42** through the first zone **82**. The flame from the first foraminous outer wall portion **86** is relatively close to the smaller diameter heat exchanger wall portion **100** and thus transfers heat relatively directly thereto. Thus the flame from the first zone **82** fed by the low range flow assembly **52** has a shorter standoff from the reduced diameter portion **100** of heat exchanger wall **30** than does flame from the second zone **84** fed by the high range flow assembly **54** which has a greater standoff distance from the larger diameter portion **102** of heat exchanger wall **30**.

Also, this staggered construction of the inner jacket **30** increases the radial width of an uppermost portion **104** of the water chamber **26** adjacent to the water outlet **14**. This aids in providing uniform upward flow of water through the water zone **50** around the entire circumference of the inner jacket **30**.

Safety Features

The use of dual blower assemblies each feeding premixed fuel and air to a common burner assembly in a common combustion chamber requires that precautions be taken to prevent the occurrence of backflow of hot combustion gases from the combustion chamber **32** into one of the blower assemblies.

This is particularly important with regard to the small blower assembly **52** which due to its relatively small size could be easily overcome and destroyed by the high volume of hot combustion gases which could backflow from the operation of the large blower assembly **54**. Three different safety features may be provided to prevent such backflow with regard to the small blower assembly **52**. The same three features may also be provided on the large blower assembly **54**.

One manner of preventing backflow into the low range blower assembly **52** is the provision of a mechanical check valve **104** on the discharge of the blower **56**. The mechanical check valve can be a flapper type valve that when properly operating will mechanically prevent flow back into the blower **56** while permitting flow out of the blower **56**. Although not shown in FIG. **1**, a similar mechanical check valve could be provided on the discharge of the large blower **66**.

A second means for preventing such backflow is the provision of a temperature sensor **106** in the ducting between blower **56** and burner assembly **42**, which temperature sensor can detect the increased heat if hot combustion gases were to backflow toward the blower **56**. As is schematically illustrated in FIG. **2**, the temperature sensor **106** is communicated

with the control system **76**, and the control system **76** is operable to shut down the heating apparatus **10** in response to detection of backflow into the low range blower assembly **52** via the temperature sensor **106**. A similar temperature sensor **108** can be provided between the high range blower assembly **54** and the burner assembly **42**.

Still another means for detecting and preventing backflow into either of the blower assemblies is the provision of speed sensors **110** and **112** associated with the blowers **56** and **66**, respectively, so as to detect blower fan speed. It will be appreciated that during normal operation of the water heating apparatus **10** the control system **76** is sending operating signals to the variable speed drive motors of the blowers **56** and **66**, and thus the control system **76** is instructing each of the blowers **56** and **66** to operate at a programmed speed dependent upon the heat demand and the control scenario being utilized by the control system **76**. Thus the control system **76** knows what the blower fan speed of each blower **56** and **66** should be at any given point in time. If the controller **76** detects an aberration in the actual blower fan speed of either blower via speed sensors **110** and **112**, the controller **76** can shut down the heating apparatus **10**. Such an unexpected blower fan speed may be either an overspeed or an under-speed dependent upon various forms of malfunction of the system, but in any event if the blower fan speed differs substantially from what speed is programmed, then the control system **76** can shut down the heating apparatus **10**, or can send an appropriate warning signal to call an operator to determine what action should be taken.

Supplemental Air Feature

The water heating apparatus **10** may be designed such that the primary heat exchanger portion **28** is a non-condensing heat exchanger, i.e. the water vapor in the hot combustion gases should not condense within the confines of the combustion chamber **32**. The secondary heat exchanger portion **40** is designed to be a condensing heat exchanger and thus the moisture contained in the hot combustion gases may condense on the inside of the fire tubes **36**. As will be appreciated by those skilled in the art, a condensing heat exchanger section in which condensation of moisture is expected mandates that that portion of the heat exchanger be made of material such as stainless steel which will not corrode due to the presence of moisture.

Thus according to the intended operating parameters of the apparatus **10**, the operating temperatures at various points within the apparatus **10** should be such that there is no condensation of water from the hot combustion gases within the combustion chamber **32**. Condensation of water can occur in the interior of the fire tubes **36**.

So long as it can be insured that there is no condensation within the combustion chamber **32**, the inner heat exchange jacket **30** can be made of carbon steel, whereas the fire tubes **36** should be made from stainless steel. As will be understood by those skilled in the art, stainless steel is much more corrosion resistant when exposed to condensed water. The carbon steel, on the other hand, will corrode if exposed to water, but has many preferable characteristics such as reduced cost and increased heat transfer capacity as compared to stainless steel. Thus, where operating conditions allow, the use of carbon steel may be preferable.

The circumstance which must be monitored to prevent condensation in primary heat exchanger **28** is to make certain that the walls of the inner jacket or heat exchange wall **30** stay at a temperature above the dew point of the condensate water vapor in the hot combustion gases in combustion chamber **32**. This can be insured by making certain that the water temperature of the water flowing upward through water side **26** just

13

prior to the time it enters the upper portion **50** remains above the dew point of the condensate water vapor in the hot combustion gases. Thus a temperature sensor **114** may be placed in the water side **26** right below the inner jacket **30** as shown in FIGS. **3** and **4**.

The temperature sensor **114** may be more generally described as a sensor **114** for detecting a parameter related to possible condensation of combustion gases within the heating apparatus **10**, the sensor **114** providing an input to the control system **76**.

The unique operating scenarios which are provided by the use of the dual blower assemblies described herein, provide a unique means for addressing condensation problems. As will be understood by those skilled in the art, the dew point of the water vapor contained in the hot combustion gases within combustion chamber **32** can be modified by adding increased amounts of air to be mixed with the hot combustion gases within the combustion chamber **32**. This addition of supplemental air without accompanying fuel results in an overall drier gas mixture thus having a lower dew point.

Because the heating apparatus **10** has the advantage of having two blower assemblies present and having control over the fuel air mixture provided from each blower, the control system **76** can instruct one of the blowers to provide air without fuel while the fuel air mixture being burned comes from the other blower assembly.

This is particularly significant at operating conditions within the lower portion of the range over which the heating apparatus **10** operates. It is at low load operating conditions where condensation problems typically occur. Thus, for example, if while operating based upon fuel and air mixture coming from the first blower assembly **52**, the control system **76** detects an impending condensation problem due to the temperature at sensor **114** dropping below a predetermined condensation point of the combustion gases, the control system **76** can direct the second blower assembly **54** to provide supplemental air without fuel to the burner assembly **42** thus lowering the dew point of the combustion gases within combustion chamber **32** and avoiding the creation of condensation within the primary heat exchanger **28**.

Similarly, it is also possible for the first blower assembly **52** to be the source of supplemental air when the primary fuel and air load is coming from the secondary blower assembly **54**. In the context of the supplemental air just described, the blower assembly which is being tapped for that supplemental air may be generally referred to as a supplemental blower.

It is also noted however that even if the primary heat exchanger **28** is intended to be non-condensing, the inner jacket **30** can be made of stainless steel if desired. If such a stainless steel inner jacket **30** is provided, then it is not necessary to provide the supplemental air feature just described.

Methods of Operation
A typical operating scenario for the water heating apparatus **10** is as follows. This scenario begins with the assumption that the water heating apparatus **10** is idle, with its control system on but with the burner assembly **32** off.

Upon receiving a call for heat from the control system **76**, the control system **76** will first check the apparatus **10** for various safety preconditions such as a switch indicating that the check valve **104** is in its closed position, and the various temperature sensors being in a proper range indicating that there is no flame, no backflow, etc.

The control system **76** will then engage the blowers in both the low range blower assembly **52** and the high range blower assembly **54**. The control system **76** will run through a trial for ignition routine including the following:

14

1. Confirm the check valve **104** has opened when the blower fan **56** comes on.
2. Confirm that the blower fan **66** of high range blower assembly **54** is on at a minimal speed, for example 1250 rpm, to prevent any backflow through the high range blower assembly **54**.
3. An air pressure switch should detect a pressure differential across the large blower **54** providing further confirmation that the large blower **54** is on.
4. The various flame and temperature sensors should confirm that there is no flame in the combustion chamber **32** and no heat being produced.

Once the trial for ignition routine confirms that all systems are go for ignition, the controller **76** will run through a purge gas routine to provide fuel to the low range blower assembly **52** and an ignition signal will be sent to direct spark ignition element **98** to light the flame of fuel and gas exiting from the first zone **82** of blower assembly **42**. A flame sensor will confirm ignition.

Then, depending upon the amount of heat being called for by the system the output of the low range blower assembly **52** will be increased as needed. If the call for heat is relatively low and the demand can be met by the low range blower **52** alone, then the blower **56** of low range blower assembly **52** will increase in speed to a level sufficient to meet the heat demand, and the blower **66** of high range blower assembly **54** will continue to operate only at a minimal speed to prevent backflow and no fuel will be provided to the burner assembly **42** from the high range blower assembly **54**.

On the other hand, if the heat demand is high the control system **76** can bring on the high range blower assembly **54** to provide additional fuel and air to the burner assembly **42** through the second zone **84** of burner assembly **42** as needed.

Throughout the operation of the heating apparatus **10**, the control system **76** will continuously monitor the various safety systems for malfunction. Typical malfunctions could for example be a restriction in the flue causing excessive back pressure on the heating apparatus **10** potentially causing overheating and backflow; failure of check valve **104** potentially causing backflow; loss of a blower fan motor, or the like. Upon detection of any malfunction the control system **76** can shut down the heating apparatus **10** by de-energizing the gas valves **64** and **74** thus preventing the flow of fuel to the burner assembly **42**.

The control system **76** also continuously monitors various other operating parameters of the heating apparatus **10**. Water temperature into inlet **12** is monitored by temperature sensor **116**. Water temperature out from outlet **14** is monitored by temperature sensor **118**. Flame sensor **120** detects whether there is flame in combustion chamber **32**. An exhaust flue temperature sensor **122** senses the temperature of exhaust gases going out flue **46**; that for example can be used to detect if the apparatus **10** is being fired without sufficient water flow therethrough.

One issue which must be dealt with in the heating apparatus **10** utilizing the two blower assemblies **52** and **54** is how to deal with providing for heat demands slightly in excess of that which can be provided by the low range blower assembly **52**. For example, if the low range blower assembly can only operate at heat inputs between 80,000 BTU/hr and 400,000 BTU/hr and if the high range blower assembly **54** can only operate between 400,000 BTU/hr and 2,000,000 BTU/hr, then no combination of those two blower assemblies can provide exact heat demands in the range of 400,000 to 480,000 BTU/hr, unless one chooses to completely shut off fuel flow to the low range boiler assembly which can be done. This transition zone can be dealt with in several ways.

One way to deal with the transition zone is to select the blower assemblies **52** and **54** so that they have an overlap in capability at least equal to the minimum operating capacity of the low range blower assembly **52**. Thus if the low range blower assembly **52** is selected so that it can operate between 80,000 and 480,000 BTU/hr and if the high range blower assembly **54** can operate between 400,000 BTU/hr and 2,000,000 BTU/hr, then the low range blower assembly **52** can provide for heat demands from 80,000 to 480,000 BTU/hr, and upon a heat demand in excess of 480,000 BTU/hr, the high range blower assembly **54** can be brought on at 400,000 BTU/hr and the low range blower assembly **52** can be throttled back to provide the remainder of the necessary heat input. Of course the overlap can be greater than that just described and the low range and the high range blower assemblies **52** and **54** can be brought on in any suitable combination to provide for the necessary heat demand.

Of course the overlap of operating ranges between the low range blower assembly **52** and the high range blower assembly **54** can be provided in any manner. For example, the high range blower assembly **54** could be selected so that it was capable of operating somewhat below the nominal low end of its operating range.

Additionally, if the selected low range and high range blower assemblies **52** and **54** are such that there is not sufficient overlap in their operating ranges to allow provision of every single point of heat demand, thus resulting in a small gap in the available heat demands, the control system can be operated in such a fashion as to minimize the cycling on and off of the heating apparatus **10**. For example, an operating routine can be used like that described in U.S. patent application Ser. No. 12/112,179 of Paine filed Apr. 30, 2008, and assigned to the assignee of the present invention, the details of which are incorporated herein by reference.

At maximum operating conditions, it is noted that even with both the low range blower assembly **52** and high range blower assembly **54** operating at maximum output, it is generally not expected that the combined output would reach a total of the maximum individual outputs of those blower assemblies. That is, in the example given it is not expected that the low range blower assembly **52** would be providing 400,000 BTU/hr and the high range blower assembly **54** would be providing 2,000,000 BTU/hr for a total of 2,400,000 BTU/hr. The reason is that at maximum operating capacities the back pressures within the system are such that neither the low range or high range blower assembly would be able to reach its maximum operating condition. Thus it is expected that at maximum operating conditions the combined output of the two blower assemblies will correspond to a heater input of approximately the 2,000,000 BTU/hr which is desired for the example given.

It is also noted that for fuel efficiency reasons it is preferable at maximum operating conditions to be providing fuel through both the low range blower assembly **52** and the high range blower assembly **54**. Although it is conceivable to provide the maximum desired input of 2,000,000 BTU/hr by simply operating the high range blower assembly **54** at its maximum output, it must be remembered that in order to prevent backflow through the smaller low range blower assembly **52**, the blower **56** will typically remain in operation thus providing some air flow without fuel. That air flow without fuel in effect cools the combustion gases, and thus reduces operating efficiency. Accordingly, the maximum operating efficiency occurs when both blower assemblies **52** and **54** are operating to provide fuel and combustion air to the burner assembly **42**.

During that operation it will be appreciated that in order to avoid backflow into either blower assembly, the pressures in each of the inner zones **82** and **84** of burner assembly **42** must be greater than the pressure within the combustion chamber **32**.

The Burner Assembly Embodiment of FIGS. **6-10**

In FIGS. **6-10** a somewhat modified version of the burner assembly is shown along with a modified blower transition manifold which corresponds to the changes in construction of the burner assembly. In FIGS. **6-10**, components identical to or analogous to those previously described with regard to the burner assembly **42** of FIG. **4** and the blower transition manifold **79** of FIGS. **4** and **5** are identified by like numerals with the suffix A. It will be understood that the burner assembly **42A** and the blower transition manifold **79A** of FIGS. **6-10** may be substituted within the apparatus **10** of FIG. **1** for the burner assembly **42** and the blower transition manifold **79**.

Thus the burner assembly **42A** is generally cylindrical in shape and extends into the combustion chamber **32** of primary heat exchanger section **28**. Burner assembly **42A** includes a header wall **78A** and an interior wall **80A** spaced from the header wall **78A**. The interior wall separates first and second or upper and lower interior zones or plenums **82A** and **84A**.

The blower transition manifold **79A** is attached to the header wall **78A** and connects the outlets of blower assemblies **52** and **54** to the burner assembly **42A**. As best seen in FIGS. **9** and **10**, first and second passageways **81A** and **83A**, respectively, are defined in the transition manifold **79A**.

The outlet of first blower **56** is connected to the inlet **85A** of first passage **81A**. The outlet of second blower **66** is connected to second inlet **87A**. Check valves such as **104A** may be placed in the manifold **79A** between the blowers **56** and **66** and their respective plenums **82A** and **84A**.

First passage **81A** has a passage outlet **89A** which aligns with a plurality of openings **90A** (see FIG. **7**) defined in the header wall **78A**, so that the output of first blower **56** is communicated to first plenum zone **82A**.

A duct **91A** extends between divider wall **80A** and header wall **78A**. Duct **91A** is welded or otherwise attached to the header wall **78A** and divider wall **80A**. The lower end of duct **91A** communicates through opening **93A** in divider wall **80A** with the second zone **84A**, and defines a passage communicating second blower **66** with second zone **84A**.

The burner apparatus **42A** further includes an upper neck or collar **95A** attached to and extending downward from the header wall **78A**.

The burner assembly **42A** as illustrated in the cross section view of FIG. **8** is shown somewhat schematically. It includes a structural skeleton like the structural skeleton described with regard to the burner assembly **42** of FIG. **4**, but certain of the components analogous to the perforated cylindrical support screen **97**, the lower support ring **99**, the flat blower burner screen **101**, and the foraminous outer sock **103** are not illustrated in the schematic view of FIG. **8**.

The burner assembly **42A** similarly includes first and second foraminous outer wall portions **86A** and **88A** located adjacent the first and second interior zones **82A** and **84A**, respectively. The cylindrical burner wall portions **86A** and **88A** may be described as comprising a peripheral side wall **86A**, **88A**. The second foraminous outer wall portion **88A** includes both a cylindrical portion **94A** and an end portion **96A**. The lower end burner wall portion **96A** may be described as a distal end wall **96A**. The foraminous material from which the foraminous outer wall portions are constructed may for example be a ceramic fiber weave material manufactured by 3M Company. The cylindrical portion **94A** of second foraminous outer wall portion **88A** and the first

foraminous outer wall portion **86A** may comprise a continuous cylindrical foraminous burner wall.

As has been previously noted, it is preferable to design the burner assembly **42A** to match the capacities of the first and second blower assemblies **52** and **54** so as to provide a substantially uniform surface loading on the burner. The following Table I provides exemplary dimensions for five different sizes of the burner assembly **42A**.

TABLE I

Total Burner Output (1000 BTU/hr)	Low Range Output (1000 BTU/hr)	High Range Output (1000 BTU/hr)	L1 (Inches)	L2 (Inches)	L3	D (Inches)	L3/D	A2/A1	Burner Output Ratios
1,500	60-300	240-1,200	2.438	5.250	11.5	11.375	1.01	3.32	4.0
2,000	80-400	320-1,600	2.438	5.250	11.5	14.000	0.82	3.59	4.0
2,500	100-500	400-2,000	2.438	5.250	11.5	16.375	0.70	3.83	4.0
3,000	120-600	480-2,400	2.688	5.000	11.5	19.000	0.61	3.63	4.0
3,500	200,1,000	500-2,500	4.855	4.830	12.25	20.500	0.60	2.05	2.5

The first column of Table I identifies the total burner output for the burner assembly in thousands of BTU/hr. Thus, the example shown in the first row of Table I is for a burner assembly **42A** having a total burner output of approximately 1,500,000 BTU/hr.

The second and third columns of Table I provide the output range for the first and second burner zones associated with the low range and high range blowers, respectively.

The next four columns provide the appropriate dimensions **L1**, **L2**, **L3** and **D**, for each of the examples, as identified on FIG. **8**. **L1** is the axial length of the cylindrical portion of the first outer burner surface **86A**. **L2** is the axial length of the cylindrical burner surface of the second burner portion **88A**. **L3** is the assembly length which is defined from the header wall **78A** to the second end of the second interior zone **84A**. **D2** is the diameter of the cylindrical burner portions **86A** and **88A**. The diameter **D** may also be described as a maximum burner width transverse to the assembly length **L3**.

The next column provides the ratio of **L3/D**.

The next column provides the ratio of the surface area for the second burner **88A** (identified as **A2**) divided by the surface area of the first burner zone **86A**.

The final column provides the burner output ratios which are the ratio of the high end of the high range output to the high end of the low range output.

It is noted that the ratio **A2/A1** approximates and typically is slightly lower than the burner output ratio so as to maintain the desired substantially uniform surface loading on both the first and second burner surfaces **86A** and **88A**.

A number of generalizations can be derived from the five examples set forth in Table I. First, it is noted that in all examples the assembly length **L3** is less than about 13.0 inches. The assembly length **L3** may also be described as being in a range from about 10.0 to about 13.0 inches. It is noted from a comparison of the assembly length **L3** to the diameter **D**, which is set forth as the ratio **L3/D** in Table I that a ratio of the assembly length to the maximum burner width is in a range of from about 0.4 to about 1.2, for all of the examples given. Thus these relatively short, relatively wide burner assemblies, which may be described as low profile burner assemblies, allow relatively high burner outputs to be created from a burner assembly that can fit in a relatively short vertical space. This allows the heater apparatus **10** to be designed to fit within a footprint which allows it to be placed within buildings with conventional door sizes and under conventional ceiling heights.

One significant contributor to the ability to attain the external outer burner surface areas necessary to achieve these relatively high burner outputs in such a short low profile burner is the use of the distal end surface area **96A** as burner surface.

These relatively high output burner assemblies may be described as having a burner output capacity of at least about 1.5 MM BTU/hr, which may alternatively be stated as

1,500,000 BTU/hr. The larger burner assemblies may be described as having a burner output capacity of at least about 3.0 MM BTU/hr.

As previously noted, the burner output ratios set forth in the last column of Table I provide the ratio of the high end of the high output range to the high end of the low output range. That ratio can also be described by stating that the cylindrical portion **94A** of the second foraminous outer wall portion **88A** plus the foraminous distal end wall **96A** have a total outer burner surface area in the range of from 1 to 6 times an outer burner surface area of the first foraminous outer wall portion **86A**.

Although in all of the examples illustrated the first and second foraminous wall portions **86A** and **88A** are of equal diameters, they need not be so. They can be of different diameters.

The Burner Assembly Embodiment of FIGS. **11-12**

The burner assemblies previously described with regard to FIGS. **4** and **6-10** have all been dual chamber burners. But it will be understood that the multiple chamber burners may have more than two chambers. For example in FIGS. **11** and **12** two embodiments are shown of burners each having three chambers. More than three chambers could also be used.

One advantage provided by dividing the interior of the burner into multiple segregated chambers is that the capacity of those chambers may be matched to available sizes of blowers and gas valves to allow a burner assembly of any desired capacity to be constructed from components of a size that are readily or economically available.

In FIGS. **11** and **12**, components identical to or analogous to those previously described with regard to the burner assembly **42** of FIG. **4** and the blower transition manifold **79** of FIGS. **4** and **5** are identified by like numerals with the suffix **B** or **C**, respectively. It will be understood that the burner assemblies **42B** or **42C** may be substituted within the apparatus **10** of FIG. **1** for the blower assembly **42**.

The burner assembly **42B** of FIG. **11** is generally cylindrical in shape and has a header wall **78B**, first divider wall **80B'**, second divider wall **80B''**, distal end wall **96B**, and a peripheral side wall including peripheral wall portions **86B**, **202** and **94B**. The divider walls **80B'** and **80B''** divide the interior of the assembly into three zones **82B**, **84B** and **200**. Manifold passages **81B**, **83B** and **204** communicate three blowers with the three zones. Manifold passages **83B** and **204** communi-

cate with ducts 91B and 206 extending through the header wall 78B and one or both divider walls 80B' and 80B".

The interior of the burner assembly may also be divided in ways other than the axial division shown for FIGS. 4, 6-10 and 11. For example as schematically shown in the plan view of FIG. 12 a burner assembly 42C may utilize radially extending interior walls 80C', 80C" and 80C'. Thus the interior of burner assembly 42C includes three zones 208, 210 and 212 which will extend the entire axial length of the burner. Each zone is communicated with a separate blower by appropriate manifolding. Any other suitable geometric arrangement of burner chambers may be used.

Thus any of the burner assemblies described above can be described as having at least one interior divider wall dividing the interior into at least a first zone and a second zone. In the embodiments of FIGS. 11 and 12, the at least one interior divider wall comprises at least two interior divider walls dividing the interior into at least three zones.

The Burner Assembly Embodiment Of FIGS. 13-16

In FIGS. 13-16 a further somewhat modified version of the burner assembly is shown. In FIGS. 13-16, components identical to or analogous to those previously described with regard to the burner assembly 42 of FIG. 4 or the burner assembly 42A of FIGS. 6-10 are identified by like numerals with the suffix D. It will be understood that the burner assembly 42D shown in FIGS. 13-16 may be substituted within the apparatus 10 of FIG. 1 for the burner assembly 42.

Thus the burner assembly 42D of FIGS. 13-16 is generally cylindrical in shape and extends into the combustion chamber 32 of primary heat exchanger 28. Burner assembly 42D includes a header wall 78D and an interior wall or internal barrier 80D spaced from the header wall 78D. The interior wall 80D separates first and second or upper and lower interior zones or plenums 82D and 84D. A ring or collar 95D extends downwardly from the header wall 78D. The header wall 78D and the collar 95D may collectively be referred to as a header 300.

As best seen in FIG. 15, the header wall 78D includes a plurality of inlet openings 90D for communicating a blower transition manifold (not shown) similar to the manifold 79 and/or 79A described above, with the first interior zone 82D.

A duct 91D extends between the header wall 78D and the divider wall 80D to communicate the transition manifold with the second interior zone 84D.

The burner assembly 42D shown in FIGS. 13-16 illustrates two optional features for the burner assembly, and it will be understood that either or both of these features may be utilized with the other burner assembly designs shown above. The first feature illustrated in FIGS. 13-16 is a modification of the lower burner chamber 84D which provides a flame sensor portion 302 of the lower burner chamber 84D which extends back through the area of the first burner chamber 82D toward or to the header 300 so as to provide a location for a second flame sensor to detect flame in the second burner chamber 84D. The flame sensor portion 302 may also be referred to as an extension 302 or finger 302 of the lower burner chamber 84D.

The second new feature illustrated with regard to the embodiment of FIGS. 13-16 is a different manner of construction of the burner assembly utilizing a foraminous stainless steel metering sleeve 304 supporting a woven metal fabric layer 306 to collectively form the foraminous outer wall portions of the burner assembly. That construction is contrasted to that described above for some of the other embodiments which utilize a foraminous ceramic outer layer of the wall. It is noted that while a burner assembly as shown in FIGS. 13-16 having the flame sensor portion 302 could be

constructed utilizing a ceramic outer wall layer, there are advantages with this construction to utilize a metal fabric layer 306 supported by a metering sleeve 304 due to the weldability of the metal fabric 306 and metering sleeve 304.

A metal fabric construction can also be used for the foraminous outer walls of the previously shown embodiments.

FIG. 16 schematically illustrates the manner in which the interior divider 80D has been modified to provide the flame sensor portion 302 of the lower interior zone or burner chamber 84D. The interior wall 80D in addition to including a generally circular flat planar wall portion 308 includes a duct 310 which creates an extension of the second interior zone 84D which extends back toward the header wall 78D through the area that would otherwise be occupied by the outer burner wall 86D of the first interior zone 82D.

The duct 310 is formed by an inner wall 312 and two side walls 314 and 316 which are all welded at their lower ends to the flat planar wall portion 308 and which define a peripheral edge 318 along all three of the walls of the duct 310. The peripheral edge 318 abuts and is welded to an inner cylindrical surface of the stainless steel metering sleeve 304 thus defining the flame sensor portion 302 of the second interior zone 84D, which may also be referred to as an extension 302 of the second interior zone 84D.

The stainless steel metering sleeve 304 may be an integral extension of the neck 95D of header 300. The neck 95D is a solid cylindrical structure with no perforations therethrough, but the metering sleeve 304 adjacent the outer metal fabric layer 306 contains a large number of small perforations, for example narrow slits, such as schematically illustrated and designated by the numeral 322 in FIG. 14.

The perforated stainless steel metering sleeve 304 serves to maintain a back pressure within the interior zones 82D and 84D of burner assembly 42D such that an adequate gas velocity exiting the perforations 322 is maintained so that a flame front defined on the outer burner surfaces 86D and 88D cannot flash back into the interior of the burner assembly 42D. The stainless steel metering sleeve 304 also provides a structural support for the outer metal fabric layer 306 which provides a flame support surface for the burning fuel flowing out through the perforations 322 of the metering sleeve 304.

A lower end wall 324 closes the lower end of metering sleeve 304 and is formed of the same slitted or perforated stainless steel material as just described for the metering sleeve 304. The metal fabric layer 306 also covers the lower end wall 324.

The metal fabric layer 306 may be formed in a socklike shape as shown in FIG. 14, or it may be formed of various segments placed about the metering sleeve 304 and lower end wall 324. Due to its metallic construction, the metal fabric layer 306 may be attached to the metering sleeve 304 and/or lower end wall 324 by welding. The metal fabric outer layer 306 may be welded to the neck 95D at the upper edge 326 of fabric layer 306 as illustrated in FIG. 13.

Additionally, as best seen in FIG. 13, the metal fabric 306 may be welded to the outer surface of the metering sleeve 304 along a border 328 superimposed upon the location of the peripheral edge 318 of duct 310, and also superimposed upon an outer peripheral edge 330 of the planar portion 308 of interior divider 80D, as schematically illustrated by the welded border 328 in FIG. 13.

Thus the structure described provides a burner assembly 42D having the header 300 including the first and second fuel and air inlets 90D and 91D. The first burner chamber or interior zone 82D is located adjacent the header 300, with the first fuel and air inlets 90D being communicated with the first burner chamber 82D. The second burner chamber or interior

zone 84D is located on an opposite side of the first burner chamber 82D from the header 300. The second fuel and air inlet 91D is communicated with the second burner chamber 84D. The second burner chamber 84D has the flame sensor portion 302 extending into the first burner chamber 82D back toward the header 300. The flame sensor portion 302 includes a flame indicating burner surface 320 of the second burner chamber 84D located adjacent the header 300, so that a second flame sensor 120D (see FIG. 15) located adjacent the flame sensor portion 302 of the second burner chamber 84D need not be exposed to flame from the first burner chamber 82D. The flame indicating burner surface 320 may also be referred to more generally as a remote communicating flame strip 320.

As best seen in FIG. 13, the first burner chamber 82D has a partially cylindrical foraminous outer burner surface 332 having a circumferential gap 334, with the flame sensor portion 302 and its flame indicating burner surface 320 of the second burner chamber 84D extending into the circumferential gap 334. The circumferential gap 334 preferably has a sufficient circumferential width so that the flame sensor 120D located adjacent thereto will not be too close to flames exiting from the partially cylindrical outer burner surface 332 of first burner chamber 84D. The circumferential gap 334 preferably has a circumferential width of at least 1.5 inches and more preferably has a circumferential width of at least about 2.0 inches.

As shown schematically in FIG. 14 the flame sensor 120D may have its sensor element offset from the surface of the burner by a spacing 338 which preferably is approximately 1/2 inch or less.

FIG. 15 schematically illustrates the position of the second flame sensor 120D adjacent the extension 302 of second burner chamber 84D for detecting whether a flame is present in the second burner chamber 84D. FIG. 15 also shows the first flame sensor 120 associated with first burner chamber 82D and FIG. 15 shows the direct spark ignition element 98. Preferably, those components are spaced away from each other around the periphery of the burner assembly 42D as shown in FIG. 15, and in any event the first flame sensor 120 and second flame sensor 120D should be adequately separated, for example by an angular separation of at least 90 degrees.

In order to ensure proper operation of the second flame sensor 120D associated with the second burner chamber 84D, the automated control system 76 controlling the first and second blowers which are associated with the first and second burner chambers 82D and 84D, respectively, should be operable to provide air without fuel to the second burner chamber 84D when the second burner chamber 84D is not burning. The air flowing out through the second burner chamber 84D and particularly through the extension portion 302 thereof will prevent flame from the first burner portion 82D from impinging upon the second flame sensor 120D located adjacent the flame indication burner surface 320 of the extension 302 of second burner chamber 84D thus preventing flame from the first burner stage 82D from being detected by the second flame sensor 120D when the second burner stage 84D is not burning.

The construction described above allows the second flame sensor 120D to be of conventional construction, and preferably it is substantially identical to the flame sensor 120 utilized with the first burner chamber 82D. The flame sensors 120 and 120D may be mounted from an appropriate structural portion of the burner apparatus 10 and may extend substantially equal distances 340 downward relative to the header wall 78D.

For example the flame sensors 120 and 120D may be constructed of flame sensing rods such as that available from SAPCO or from Precision Speed Equipment

Another advantage of the construction shown in FIGS. 13-16 is that the flame indicator burner surface or remote communicating flame strip 320 of the second burner chamber 84D interrupts the circumferential continuity of the outer burner surface 332 of the upper burner chamber 82D, thus preventing resonance and attenuating or reducing burner noise in the upper burner chamber 82D due to resonance patterns setting up in the burner flame circumferentially around the upper burner chamber 82D. The presence of the extension 302, and the pressure discontinuity it creates in the second burner chamber 84D also contributes to prevention of resonance and attenuation of burner noise in the second burner chamber 84D.

Another advantage provided by the construction shown in FIGS. 13-16 is that lighting of the second burner chamber 84D from flame exiting the first burner chamber 82D is improved due to the proximity of the extension 302 to flame exiting the first burner chamber 82D, thus providing faster ignition of the second burner chamber 84D. This may be described as the remote communicating flame strip 320 providing a carry-over ignition location for the second burner chamber 84D to ignite via flame from the first burner chamber 82D.

Another advantage of the construction shown in FIGS. 13-16 is that a flame sensor can be provided for the lower burner chamber 84D without having to extend the hardware of that flame sensor through a flame exiting the upper burner chamber 82D.

The Burner Assembly Embodiment of FIG. 17

It will also be appreciated that the benefits of the remote communicating flame strip 320 are applicable to burner assemblies having more than two burner chambers. For example, as shown in FIG. 17, a burner assembly 400 has a header 402 and first, second and third burner chambers 404, 406 and 408. The second burner chamber 406 has a remote communicating flame strip 410. The third burner chamber 408 has a remote communicating flame strip 412.

The header 402 has first, second and third inlets 414, 416 and 418, respectively, communicated with the first, second and third burner chambers.

The remote communicating flame strips 410 and 412 each individually provide all the same advantages as discussed above for the remote communicating flame strip 320 of FIG. 13. Furthermore, the construction of FIG. 17 allows the third burner chamber 408 to take carry-over ignition from either the first burner chamber 404 or the second burner chamber 406. Also it is possible to operate first and third burner chambers 404 and 408 while leaving the second burner chamber 406 idle.

Thus it is seen that the apparatus and methods of the present invention readily achieve the ends and advantages mentioned as well as those inherent therein. While certain preferred embodiments of the invention have been illustrated and described for purposes of the present disclosure, numerous changes in the arrangement and construction of parts and steps may be made by those skilled in the art, which changes are embodied with the scope and spirit of the present invention as defined by the following claims.

What is claimed is:

1. A burner assembly, comprising:

- a header including a first fuel and air inlet and a second fuel and air inlet;
- a first burner chamber adjacent the header, the first burner chamber including a first foraminous outer burner sur-

23

face, the first fuel and air inlet being communicated with the first burner chamber; and

a second burner chamber on an opposite side of the first burner chamber from the header, the second burner chamber including a second foraminous outer burner surface located on an opposite side of the first foraminous outer burner surface from the header, the second fuel and air inlet being communicated with the second burner chamber, the second burner chamber having a flame sensor portion extending into the first burner chamber back toward the header, the flame sensor portion including a flame indicating foraminous outer burner surface of the second burner chamber extending from the second foraminous outer burner surface back toward the header, so that a flame sensor located adjacent the flame sensor portion of the second burner chamber need not be exposed to flame from the first burner chamber.

2. The burner assembly of claim 1, wherein: the first foraminous outer burner surface of the first burner chamber is partially cylindrical and has a circumferential gap, the flame indicating foraminous outer burner surface of the flame sensor portion of the second burner chamber extending into the circumferential gap.

3. The burner assembly of claim 2, wherein: the flame sensor portion of the second burner chamber extends to the header.

4. The burner assembly of claim 2, wherein: the circumferential gap has a circumferential width of at least about 1.5 inches.

5. The burner assembly of claim 2, wherein: the circumferential gap has a circumferential width of at least about 2.0 inches.

6. The burner assembly of claim 1, further comprising: an interior divider separating the first and second burner chambers, the interior divider including a generally circular divider wall and a duct extending from the divider wall into the first burner chamber and communicating the second burner chamber with the flame indicating foraminous outer burner surface of the flame sensor portion of the second burner chamber.

7. The burner assembly of claim 6, wherein: the interior divider is made of metal; the first and second foraminous outer burner surfaces are made of metal fabric surrounding a foraminous metal sleeve; and the metal fabric, the sleeve and the duct of the interior divider are welded together form a seam to prevent flame from the first burner chamber from entering the duct.

8. A burner assembly, comprising: a first foraminous outer wall portion being partially cylindrical in shape and having a circumferential gap; a second foraminous outer wall portion including a finger shaped outer foraminous wall portion extending into the circumferential gap; at least one interior wall separating first and second interior zones, the first and second interior zones being adjacent the first and second foraminous outer wall portions, respectively, the at least one interior wall including a duct communicating the second interior zone with the finger shaped outer foraminous wall portion of the second foraminous outer wall portion; a first fuel and air inlet passage communicated with the first interior zone; a second fuel and air inlet passage communicated with the second interior zone; and

24

a header including a header wall spaced from the at least one interior wall;

wherein the first interior zone is cylindrical in shape and has first and second ends closed by the header wall and the at least one interior wall, respectively; and

wherein the second interior zone is cylindrical in shape and has a first end closed by the at least one interior wall and a second end covered by foraminous material comprising part of the second foraminous outer wall portion; and

wherein the second foraminous outer wall portion is located on an opposite side of the first foraminous outer wall portion from the header.

9. The burner assembly of claim 8, wherein: the header includes a header ring extending from the header wall toward the second interior zone.

10. The burner assembly of claim 8, wherein: the finger of the second foraminous outer wall portion extends to the header ring.

11. The burner assembly of claim 8, wherein: the circumferential gap has a circumferential width of at least about 1.5 inches.

12. The burner assembly of claim 8, wherein: the circumferential gap has a circumferential width of at least about 2.0 inches.

13. The burner assembly of claim 8, wherein: the at least one interior wall is a metal wall; the foraminous outer wall portions each include a foraminous metal sleeve surrounded by a metal fabric, the sleeve having inner and outer surfaces; and the duct of the interior wall has a peripheral edge adjacent to and welded to the inner surface of the sleeve, and the metal fabric is welded to an outer surface of the sleeve along a border superimposed upon the peripheral edge of the duct.

14. A water heating apparatus, comprising: a multi-stage burner including: a header having first and second inlets; first and second internal zones separated by an internal barrier, the first and second internal zones being communicated with the first and second inlets, respectively; first and second external foraminous burner wall portions at least partially defining the first and second internal zones, respectively; a first blower communicated with the first internal zone of the burner for providing premixed fuel and air to the first internal zone to provide a first burner stage; a second blower communicated with the second internal zone of the burner for providing premixed fuel and air to the second internal zone to provide a second burner stage; a first flame sensor adjacent the first external foraminous burner wall portion; a second flame sensor adjacent the second foraminous burner wall portion; and an automated control system connected to the first and second blowers, the control system operable to provide air without fuel to the second internal zone when the second burner stage is not burning, so that air flowing through the second internal zone prevents flame from the first burner stage from being detected by the second flame sensor when the second burner stage is not burning.

15. The apparatus of claim 14, further comprising: a direct spark ignition element adjacent the first external foraminous burner wall portion.

25

16. The apparatus of claim **14**, wherein:
the first external foraminous burner wall portion is partially
circular and defines a gap;
the second external foraminous burner wall portion
includes an extension through the gap to the header;
the second flame sensor is located adjacent the extension;
and
the first flame sensor is circumferentially spaced about the
burner at least 90 degrees from the second flame sensor.

17. The apparatus of claim **14**, wherein:
the first and second flame sensors are substantially identical.

18. The apparatus of claim **14**, wherein:
the first and second flame sensors extend substantially
equal distances from the header.

19. The burner assembly of claim **1**, wherein:
the flame indicating foraminous outer burner surface pro-
vides a carry-over ignition location for the second burner
chamber to ignite via flame from the first burner cham-
ber.

26

20. The burner assembly of claim **1**, wherein:
the flame indicating foraminous outer burner surface inter-
rupts the first foraminous outer burner surface of the first
burner chamber and thereby attenuates burner noise
from the first burner chamber.

21. The burner assembly of claim **1**, wherein:
the header further includes a third fuel and air inlet; and
the burner assembly further comprises:
a third burner chamber on an opposite side of the second
burner chamber from the header, the third fuel and air
inlet being communicated with the third burner cham-
ber, the third burner chamber having a second flame
sensor portion extending into the first and second burner
chambers back toward the header, the second flame sen-
sor portion including a remote communicating flame
strip of the third burner chamber.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 9,097,436 B1
APPLICATION NO. : 12/978681
DATED : August 4, 2015
INVENTOR(S) : Smelcer et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Claims

Column 23, line 49, claim 7, insert --to-- between --together-- and --form--.

Column 24, line 5, claim 8, delete "and" after --respectively;--.

Signed and Sealed this
Second Day of February, 2016



Michelle K. Lee
Director of the United States Patent and Trademark Office