

US009105112B2

(12) **United States Patent**  
**Holland et al.**

(10) **Patent No.:** **US 9,105,112 B2**  
(45) **Date of Patent:** **Aug. 11, 2015**

(54) **POWER MANAGEMENT FOR IMAGE SCALING CIRCUITRY**

(71) Applicant: **Apple Inc.**, Cupertino, CA (US)

(72) Inventors: **Peter Holland**, Los Gatos, CA (US);  
**Hao Chen**, San Ramon, CA (US);  
**Albert Kuo**, Mountain View, CA (US)

(73) Assignee: **Apple Inc.**, Cupertino, CA (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 211 days.

(21) Appl. No.: **13/773,522**

(22) Filed: **Feb. 21, 2013**

(65) **Prior Publication Data**

US 2014/0232731 A1 Aug. 21, 2014

(51) **Int. Cl.**

**G06T 3/40** (2006.01)  
**G06T 1/60** (2006.01)  
**G06F 1/32** (2006.01)

(52) **U.S. Cl.**

CPC ..... **G06T 1/60** (2013.01); **G06F 1/3228** (2013.01); **G06F 1/3265** (2013.01); **G06F 1/3287** (2013.01); **G06T 3/4007** (2013.01); **G09G 2330/021** (2013.01); **G09G 2340/0407** (2013.01); **Y02B 60/1242** (2013.01); **Y02B 60/1282** (2013.01); **Y02B 60/32** (2013.01)

(58) **Field of Classification Search**

None  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,469,223 A \* 11/1995 Kimura ..... 348/581  
5,886,689 A \* 3/1999 Chee et al. .... 345/212  
6,894,706 B1 \* 5/2005 Ward et al. .... 345/660  
7,418,606 B2 8/2008 Holmer

7,802,118 B1 \* 9/2010 Abdalla et al. .... 713/322  
2003/0081858 A1 \* 5/2003 Rathnam et al. .... 382/298  
2008/0084491 A1 4/2008 He et al.  
2012/0038822 A1 \* 2/2012 Hsu et al. .... 348/458

OTHER PUBLICATIONS

NVidia, "Whitepaper NVIDIA Tegra 4 Family GPU Architecture Table of Contents", Feb. 15, 2013, XP055113921, [http://www.nvidia.cn/content/PDF/tegra\\_white\\_papers/Tegra\\_4\\_GPU\\_Whitepaper\\_FINALv2.pdf](http://www.nvidia.cn/content/PDF/tegra_white_papers/Tegra_4_GPU_Whitepaper_FINALv2.pdf)\*

Shivajit Mohapatra, Nikil Dutt, Alex Nicolau, and Nalini Venkatasubramanian, "DYNAMO: A Cross-Layer Framework for End-to-End QoS and Energy Optimization in Mobile Handheld Devices," IEEE Journal on Selected Areas in Communications, vol. 25, No. 4, May 2007, pp. 722-737.

International Search Report and Written Opinion in PCT Application No. PCT/US2014/015979 mailed May 22, 2014, 15 pages.

Whitepaper NVIDIA Tegra 4 Family, GPU Architecture, V1.0, XP055113921, Feb. 2013, 26 pages.

\* cited by examiner

*Primary Examiner* — Jason M Repko


*Assistant Examiner* — Diane Wills

(74) *Attorney, Agent, or Firm* — Meyertons, Hood, Kivlin, Kowert & Goetzel, P.C.

(57) **ABSTRACT**

Techniques are disclosed relating to power management within an integrated circuit. In one embodiment, a display buffer receives image data through a data transfer interconnect. A data transfer interconnect is powered down based on the received image data being greater than a threshold amount of data. The display buffer transmits at least a portion of the image data to one or more outputs, and in response to the transmitting, the data transfer interconnect is powered up. In some embodiments, the display buffer includes a plurality of line buffers, each configured to store a respective image source line. In such an embodiment, a display pipe configured to render images to be displayed includes the display buffer, and the powering down is performed in response to the received image data including two or more image source lines.

**20 Claims, 6 Drawing Sheets**






FIG. 1




FIG. 2




FIG. 3






FIG. 4




FIG. 5




FIG. 6



## 1

POWER MANAGEMENT FOR IMAGE  
SCALING CIRCUITRY

## BACKGROUND

## 1. Technical Field

This disclosure relates to display pipelines, and, more specifically to power management associated with display pipelines.

## 2. Description of the Related Art

As the power and complexity of computer systems increase, graphics operations are increasingly being performed using dedicated graphics rendering hardware. Accordingly, a graphics processing unit (GPU) may include various built-in and configurable structures within a display pipe for rendering images of pixel data to be presented via a display. These structures may implement various pipeline stages corresponding to, for example, rasterisation, overlaying, blending, clipping, dithering, color space conversion, frame rotation, frame buffering, etc.

In some instances, a display pipeline may also include dedicated structures for scaling images, such as, to a native resolution of an output device. The structures may implement scaling operations that perform linear transformations to upscale or downscale image data. Such scaling may include horizontal and/or vertical scaling.

## SUMMARY

The present disclosure describes embodiments in which power management is performed based on the operation of a display buffer. In one embodiment, the display buffer stores image source lines (e.g., horizontal or vertical image lines) fetched from memory for a display pipeline that uses the source lines to render images for a display. In various embodiments, the image source lines may be fetched as individual lines or as blocks of multiple lines, based on operations being performed by the display pipe. For example, in one embodiment, the display pipe may fetch individual lines more frequently if it is scaling, and it may fetch blocks less frequently if it is not scaling.

In various embodiments, one or more circuits may be power managed depending on whether multiple or individual image source lines are being fetched for the display buffer. In some embodiments, these circuits may include a data transfer interconnect transmitting the image source lines from memory to the display buffer, a memory controller of the memory storing the image source lines, etc. Accordingly, in one embodiment, if blocks of image source lines are being fetched, these circuits may be powered down (i.e., their power may be reduced) when they are idle between the fetching of source lines. They may then be powered up once a request to fetch additional source lines is received. In many instances, power managing circuits in this manner can achieve power savings without sufficiently compromising performance.

## BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram illustrating one embodiment of a computer system.

FIG. 2 is a block diagram illustrating one embodiment of a display pipe within the computer system.

FIG. 3 is a block diagram illustrating one embodiment of components within a display pipe.

FIG. 4 is a flow diagram illustrating one embodiment of a method for receiving image data.

## 2

FIG. 5 is a flow diagram illustrating one embodiment of a method for powering down a data transfer interconnect.

FIG. 6 is a flow diagram illustrating one embodiment of a method for operating the display pipe in different modes.

This specification includes references to “one embodiment” or “an embodiment.” The appearances of the phrases “in one embodiment” or “in an embodiment” do not necessarily refer to the same embodiment. Particular features, structures, or characteristics may be combined in any suitable manner consistent with this disclosure.

Various units, circuits, or other components in this disclosure may be described or claimed as “configured to” perform a task or tasks. In such contexts, “configured to” is used to connote structure by indicating that the units/circuits/components include structure (e.g., circuitry) that performs those task or tasks during operation. As such, the unit/circuit/component can be said to be configured to perform the task even when the specified unit/circuit/component is not currently operational (e.g., is not on). The units/circuits/components used with the “configured to” language include hardware—for example, circuits, memory storing program instructions executable to implement the operation, etc. Reciting that a unit/circuit/component is “configured to” perform one or more tasks is expressly intended not to invoke 35 U.S.C. §112, sixth paragraph, for that unit/circuit/component.

## DETAILED DESCRIPTION

Turning now to FIG. 1, a block diagram of one embodiment of a system **100** is shown. As illustrated, system **100** includes various components such as a processor unit **108**, memory **106**, solid state device **112**, display unit **110** and fabric **102**. System **100** may correspond to any suitable computer system. Accordingly, in some embodiments, system **100** may be a mobile device (e.g., a mobile phone, a tablet, personal data assistant (PDA), etc.), desktop computer system, server system, network device (e.g., router, gateway, etc.), microcontroller, etc. In one embodiment, multiple components of system **100** may be included together within a system on a chip (i.e., an integrated circuit which integrates components of a computer into a single integrated circuit).

In certain embodiments, system **100** is configured to render video and images on a screen coupled to system **100**. Accordingly, in various embodiments, system **100** comprises specialized circuitry dedicated to processing and manipulating graphics data prior to rendering a display.

Additionally, system **100** is configured to be power-managed. Accordingly, in various embodiments, system **100** may disable power and/or cause one or more circuits or the fabric (i.e., fabric **102**) to enter a power-managed state. As used here, the terms “power-manage,” “power down,” “put to sleep,” and the like refer to reducing a circuit’s power consumption. This reduction may be achieved, for example, through clock gating (i.e., disabling a circuit’s reception of a clock signal), power gating (i.e., disabling a circuit’s voltage supply), etc. In certain cases, power gating a circuit may result in greater power savings than if the circuit were clock-gated. Powering down a circuit or standardized bus may result in the functionality of the circuit being disabled.

In some embodiments, a power-managed state may be applicable to multiple ones of components **102-114** or system **100** as a whole. For example, in one embodiment in which system **100** is a mobile phone or tablet, system **100** is configured to enter a power-managed state when the mobile phone or tablet is idle (e.g., in a user’s pocket or when the user has stepped away from the tablet). While system **100** is in a low-power state, it may clock gate or power gate fabric **102**,



memory controller **104** and memory **106** as is further discussed below. Power management for system **100** may be desired for many reasons. In some embodiments, power management of system **100** may reduce overall energy consumption, prolong battery life, reduce cooling requirements, and reduce operating costs for energy and cooling.

As illustrated, components of system **100** are coupled via fabric **102**. The term “fabric” (or “data transfer interconnect”) refers generally to a set of physical connections that are shared among two or more structures (e.g. display processing unit **110** and memory **106**). These physical connections provide pathways for transferring information within devices, components or units that may be present on system **100**. Accordingly, in some embodiments, fabric **102** may include one or more buses, controllers, interconnects, and/or bridges. In some embodiments, fabric **102** may implement a single communication protocol and elements coupled to fabric **102** may convert from the single communication protocol to other communication protocols internally. For example, in one embodiment, fabric **102** includes a Northbridge and a Southbridge. As discussed further below, in various embodiments, fabric **102** may be configured to power down if left idle and power back up upon receiving a communication.

In various embodiments, processor unit **108** may execute program instructions (e.g., drivers) that control the operation of display processing unit **110**, memory controller **104**, memory **106** and storage device **112**. In such an embodiment, processor unit **108** may also execute program instructions (e.g., applications) that may provide data to be communicated to one or more components within system **100**. Processor unit **108** may implement any instruction set architecture, and may be configured to execute instructions defined in that instruction set architecture. Processor unit **108** may employ any microarchitecture, including scalar, superscalar, pipelines, superpipelined, out of order, in order, speculative, non-speculative, etc., or combinations thereof. Processor unit **108** may include circuitry, and optionally may implement microcoding techniques. Furthermore, processor unit **108** may include one or more cache levels. In some embodiment, processor unit **108** may be a plurality of processors.

In one embodiment, memory **106** stores image data that may be used to render an image display. Image data may comprise bits of data that specify an image value for each specific pixel on a display unit. Image data may include raster graphics which may also be referred to herein as bitmaps. Raster graphics data may be stored and manipulated as a grid of individual pixels viewable through a display medium. A bitmap may be characterized by its width and height in pixels. Commonly a color bitmap may be defined in RGB (i.e., red, green, blue) color space and it may further comprise an alpha channel used to store additional data such as per-pixel transparency values. In other embodiments, the image data may be defined using other color spaces such as sRGB, Adobe RGB (ARGB), cyan magenta yellow key (CMYK),  $YC_B C_R$ , CIE 1931 XYZ, etc. In some embodiments, image data may include subsampled chroma. For example, in the case of  $YC_B C_R$  4:2:2 color space, two horizontally adjacent pixels may include their own respective Y components related to the luminance (i.e., light intensity) and share  $C_B$  and  $C_R$  chroma components. Memory **106** may store various types of image data such as videos, pictures, and other types of graphics images that may be displayed on a display unit.

The image data may be rendered to a display unit such as a computer monitor, television or phone monitor. Any imaging device that is configured to display digital image data may be used. An image device may be configured to display data read by display processing unit **110**, discussed further below.

Memory **106** may be any type of memory, such as dynamic random access memory (DRAM), synchronous DRAM (SDRAM), double data rate (DDR, DDR2, DDR3, etc.). SRAM (including mobile versions of the SDRAMs such as mDDR2, etc., and/or low-power versions of the SDRAMs such as LPDDR2, etc.), RAMBUS DRAM (RDRAM), static RAM (SRAM), etc. One or more memory devices may be coupled onto a circuit board to form memory modules such as single inline memory modules (SIMMs), dual inline memory modules (DIMMs), etc. In some embodiments, memory **106** may be mounted with an integrated circuit in a chip-on-chip configuration, a package-on-package configuration, or a multi-chip module configuration.

In various embodiments, memory **106** may be controlled by memory controller **104**. Accordingly, memory controller **104** may facilitate the performance of read and write operations responsive to data requests received via fabric **102** from units **108** and **110**. Memory controller **104** may perform various memory physical interface (PHY) functions such as memory refreshing, memory row-address and column-address strobe operations, etc. As discussed below, memory controller **104** may also be used to power-manage memory **106**. The image data may be accessed via fabric **102** and transferred to display processing unit **110** as discussed further below.

In various embodiments, storage device **112** may store program instructions (e.g., applications) executable by processor unit **108**. In certain embodiments, storage device **112** may store a plurality of image data that may be transferred to memory **106** (i.e., so that future requests for that data can be served faster) or transferred to display processing unit **110** directly. Storage device **112** may be any suitable type of non-volatile memory hard disk drive (e.g., Small Computer System Interface (SCSI) drives, Serial AT Attachment (SATA) drives, etc.), tape drives, optical drives (e.g., CD drives, DVD drives, Blu-Ray drives, etc.), etc. Storage device **112** may also be a solid-state device (SSD) such as one including NAND flash memory, NOR flash memory, nano RAM (“NRAM”), etc.

In various embodiments, display processing unit **110** is configured to process image data such that system **100** can render the data on a display unit. Display processing unit **110** may include a display pipe that includes various pipeline stages such as rasterisation, overlaying, blending, clipping, dithering, color space conversion, frame rotation, and frame buffering. Display processing unit **110** also includes one or more display buffers **114** to buffer image data used by one or more of these stages. In various embodiments, data may be buffered as image source lines. As used herein, an “image source line” refers to image data corresponding to either a vertical or horizontal line of an image (i.e., data corresponding to a horizontal or vertical line of pixels). For the sake of this disclosure, this term may refer to an entire line (e.g., a horizontal line spanning the entire width of an image) or a portion of line (e.g., nine pixels within a horizontal line). Accordingly, in various embodiments, the source lines stored in display buffer **114** may correspond to a partial line in an image as opposed to a full line.

In various embodiments, the display processing unit **110** fetches image data to store in buffer **114** by sending requests for image data via fabric **102** to memory **106**. In certain embodiments, circuitry within system **100** may be power-managed based on the fetching of image data by display processing unit **110**. In one embodiment, this circuitry includes fabric **102**. Accordingly, fabric **102** may be power managed by reducing power to one or more bus controllers, control lines, data lines, and/or clock signal lines. In some



embodiments, power may be reduced to the entirety of fabric **102**; in other embodiments, power may be reduced to merely a portion—e.g., the interconnecting controllers and lines between display processing unit **110** and memory controller **104**. In one embodiment, memory controller **104** may also be power managed—e.g., unit **104** may be clock gated and/or power gated.

In some embodiments, units **110** and **104** may be power managed based on the fetching of image data. In one embodiment, the rate at which data is fetched is a factor in determining whether to power down units. For example, in various embodiments, display processing unit **110** may fetch individual image source lines frequently (e.g., an individual line may be fetched every 10 ms) or blocks of multiple image source lines less frequently (e.g., a block may be fetched every 100 ms) depending on the operations being performed by display processing unit **110**. (For example, as will be discussed with respect to FIGS. **2** and **3**, in one embodiment, individual image source lines or blocks of lines may be fetched based on whether display processing unit **110** is scaling the image data.) In various embodiments, when display processing unit **110** fetches blocks of multiple image source lines, fabric **102** and memory controller **104** may be idle for some time before another block of data is fetched. As a result, in such an embodiment, fabric **102** and memory controller **104** may be powered down.

In certain embodiments, the determination to power down fabric **102** and/or memory controller **104** may be based on a timer that tracks how long a certain unit has been idle. In one embodiment, once the timer indicates that a unit (e.g., fabric **102** or memory controller **104**) has been idle for an allotted amount of time, control logic may cause the unit to be powered down. As such, when display processing unit **110** fetches data in bursts, leaving the fabric **102** and memory controller **104** idle in between fetches, units **102** and **104** may be powered down responsive to the timer satisfying a particular threshold. For example, control logic may power down fabric **102** after the timer indicates an idle period of 100 ms or greater. In one embodiment, once power has been reduced to fabric **102** and/or memory controller **104**, power may be restored responsive to a subsequent request for data (e.g., read or write request) from any unit (e.g., display processing unit **110** or processor unit **108**).

Turning now to FIG. **2**, a block diagram of display processing unit **110** is shown. As discussed above, in various embodiments, display processing unit **110** may be configured to fetch and process image data such that system **100** can render the data on a display unit. In the illustrated embodiment, display processing unit **110** includes a display pipe **200** to facilitate image rendering. Display pipe **200** in turn includes display buffers **114** and **115**, scaling units **210** and **211**, and blending unit **230**. In some embodiments, display buffer **114** and scaling unit **210** is identical to display buffer **115** and scaling unit **211**, respectively. (As such, any description applicable to units **114** and **210** is similarly applicable to units **115** and **211**.) Although not shown, display pipe **200** may include multiple additional pipeline stages in various embodiments.

As noted above, in one embodiment, display buffer **114** is configured to store image data **202** fetched from memory **106**. In certain embodiments, image data **202** may be fetched alternatively from storage device **112**. As will be described with respect to FIG. **3**, in various embodiments, image data **202** is stored as image source lines within line buffers of display buffer **114**. As used herein, the term “line buffer” refers to circuitry configured to store an individual image source line (or portion of a source line). As also discussed, display buffer **114** may fetch one image source line at a time

or blocks of multiple image source lines depending on the mode in which display processing unit **110** is operating (e.g., scale or non-scale mode).

In the illustrated embodiment, scaling unit **210** is configured to scale image data **202** received from buffer **114**. In general, scaling may refer to changing the pixel resolution of an image. Scaling performed by scaling unit **210** may include downscaling, upscaling, vertical scaling and/or horizontal scaling. For example, an image having a resolution of 200 pixels wide by 100 pixels high may be downscaled horizontally and vertically to have a resolution of 100 pixels wide by 75 pixels high. In one embodiment, scaling unit **210** may reduce the resolution of such an image by generating output pixel components (e.g., R, G, B components) for the scaled image based on the components of nearby pixels in the original image. As but one example, scaling may be performed when an application generates image data that does not coincide with the native resolution of the display unit (e.g. a web browser originally formatted to display web content on a computer screen, viewed instead on a phone).

In some cases, not all image source lines are scaled, however (e.g., when an application is formatted in the native resolution). Accordingly, in various embodiments, display pipe **200** may be configured such that it operates in a “scale mode” or a “non-scale mode.” In one embodiment, when display pipe **200** is operating in a scale mode, image source lines are scaled by scaling unit **210** prior to being transmitted to blending unit **230**. While in scale mode, display buffer **114** may also fetch individual image source lines one at a time from memory. In a non-scale mode, the image source lines are not scaled prior to being transmitted to blending unit **230**. In certain embodiments, when operating in a non-scale mode, display buffer **114** may fetch image source lines in a block. (i.e., two or more image source lines at a time).

In the illustrated embodiment, image source lines (scaled and not scaled) may be transmitted to blending unit **230** (or, in other embodiments, to a different stage in the pipeline). The additional image data may include information (e.g., related to transparency or positioning) regarding another image to be displayed along with image data **202**. The image source lines and additional image data may be combined in a variety of ways by blending unit **230** to render a final image (e.g., icons combined with a desktop background).

Turning now to FIG. **3**, a block diagram of display buffer **114** and scaling unit **210** is shown in further detail. As shown, display pipe **200** includes circuitry related to scaling (i.e., scaling unit **210**), display buffer **114**, scale mode register **340** and mux **350**. In the illustrated embodiment, display buffer **114** also includes a plurality of line buffers **310a-x** (nine (9) buffers **310**, in one embodiment), each configured to store a respective image source line, and buffer read logic **320**. As will be discussed, in various embodiments, circuits **310-350** may be used to implement support for scale and non-scale modes.

In the illustrated embodiment, the mode in which display pipe **200** operates may be controlled by the value of scale mode register **340** as indicated by one or more bits. In various embodiments, an operating system may set the value in register **340** (i.e., control which mode display pipe **200** should operate in). In various embodiments, while in a non-scale mode, buffer read logic **320** may be configured such that it selectively reads one line buffer **310a-x** at a time. As such, display buffer **114** may be configured to retain all the image source lines in line buffers **310a-x** until each one has been read by buffer read logic **320**. Subsequently, display buffer **114** may fetch another block of image source lines to be read by buffer read logic **320**.



In scale mode, buffer read logic **320** may be configured to read all line buffers **310a-x** simultaneously. After each reading, display buffer **114** may be configured to shift down each image source line to the adjacent line buffer (e.g. transfer image source line from line buffer **310a** to **310b**) and fetch a new image source line (e.g. fill line buffer **310a** with new image source line). Accordingly, display buffer **114** may be configured to fetch a new image source line after each reading performed by buffer read logic **320**.

In scale mode, the image source lines are transferred via scaling path **322** to scaling unit **210**. As illustrated, scaling unit **210** includes horizontal scaler **332** and vertical scaler **334**. Horizontal scaler **332** may be configured to process horizontal lines of pixels; similarly, vertical scaler **334** may be configured to process vertical lines of pixels. As illustrated, scaling unit **210** may be configured to generate output pixel components in a scaled image based on characteristics of nearby pixels in the original image. For example, in the case where scaling path **322** transmits nine image source lines (i.e., from line buffers **312a-x**), these source lines represent 9 lines of pixels that are adjacent to each other. As such, horizontal scaler **332** and vertical scaler **334** may apply any combination of formulas to the nine image source lines to output scaled line **335**.

In non-scale mode, the image source lines are transferred via bypass path **324** to mux **350**. As such, the image source lines are not scaled. As illustrated, scale mode register **340** may indicate to mux **350**, which mode display pipe **200** is configured to operate in. Mux **350** may select scaled line **335** or bypass path **324** accordingly and output the image data to blending unit **230** or another stage in the pipeline.

In certain embodiments in which display pipe **200** is operating on image data that is encoded using subsampled chroma, display pipe **200** may operate in a hybrid mode that incorporates functionality of scale mode and non-scale mode. In this hybrid mode, image data may be scaled in one dimension (e.g., horizontal dimension) but not the other. In one embodiment, when operating in such a mode, display pipe **200** may transmit image data via scaling path **322**. As with non-scaling mode, individual source image lines may be read (i.e., one at a time) from line buffers **310**, enabling blocks of multiple image source lines to be read from memory **106**. Upon arrival at scaling unit, image source lines may be processed by the relevant scaler (e.g., horizontal scaler **332** or vertical scaler **334**) and may bypass the non-relevant scaler. For example, in the case of the  $YC_B C_R$  4:2:2 color space, horizontal upscaling may be performed if the data is being converted to an RGB color space since two horizontally adjacent pixels share  $C_B$  and  $C_R$  chroma components. In such a situation, the horizontal scaler **332** may perform upscaling while vertical scaler **334** is bypassed. In various embodiments, bypassing one of scalers **332** or **334** may afford additional power saving as the bypassed scaler may be power gated and/or clock gated.

As discussed previously, in a non-scale mode, buffer read logic **320** may be configured to selectively read each line buffer **310a-x** one at a time. In this mode, display buffer **114** may fetch blocks of image source line data in bursts (as opposed to continuously fetching an image source line). This leaves fabric **102** and memory controller **104** idle in between fetches. As such, fabric **102** and memory controller **104** may be powered down responsive to the idle time satisfying a particular threshold. This results in significant power savings. Additionally, by bypassing scaling unit **210** via bypass path **324** (e.g., in non-scale mode) or individual scalers **332** and **334** (e.g., in a hybrid mode), further power savings may be achieved (e.g., scaling unit **210** or individual scalers **332** and

**334** may be powered-down when not in use). In certain embodiments, fabric **102** may also be powered down in scale mode in between fetch operations, however, fabric **102** may be powered down for shorter intervals than when operating in a non-scale mode.

Turning now to FIG. **4**, a flow diagram illustrating one embodiment of a method for implementing a non-scale mode within a system is shown. Method **400** may be performed by any suitable system that supports power managing one or more circuits such as system **100**. In various embodiments, some of the blocks shown in FIG. **4** may be performed concurrently, in a different order than shown, or omitted. Additional method elements may also be performed as desired.

Method **400** begins at step **402**, at the beginning of a frame a determination is made at decision block **404** regarding whether to operate in a scale mode. If yes, flow proceeds to operate in a scale mode. If no, flow proceeds to operate in non-scale mode beginning at step **410**. At step **410**, a unit (e.g., display pipe **200**) receives data (e.g., image data **202**) through a data transfer interconnect (e.g., fabric **102**). In certain embodiments, step **410** may occur while display pipe **200** is operating in a non-scale or hybrid mode. The display pipe may receive an indication (e.g., from a bit set in scale mode register **340**) accordingly and proceed to fetch image source lines in blocks. At decision block **415**, a determination is made as to whether the amount of received image data is greater than a threshold amount of data (e.g., two or more source lines are fetched). As display pipe is configured to operate in a non-scale (or hybrid) mode, as discussed above, once the threshold amount of image data is received, the display pipe proceeds to selectively read each line buffer (e.g., **310a-x**). If a threshold amount of data is not received, flow proceeds back to step **410** at which point, the display pipe may continue to fetch image data until a threshold amount is received.

As explained above, at decision block **415**, if a threshold amount of data is received, the data transfer interconnect and other units (e.g., memory controller **104**) may remain idle while the display pipe reads the image data. As discussed previously, in some embodiments, step **415** entails checking a timer to determine whether the data transfer interconnect has been idle for a threshold amount of time. In other embodiments, an indication that a threshold amount of data has been received may be sent by display pipe **200**. Accordingly, once an indication or determination is made that the data transfer interconnect should be powered down, at step **420** the data transfer interconnect is powered down. Step **420** may also include powering down or reducing power to other circuitry such as memory controller **104**. In other embodiments, a portion of the data transfer interconnect (as opposed to all of it) may be powered down.

At step **425** the display pipe transmits the received data to an output. In certain embodiments, this may be a blending unit (e.g., blending unit **230**) or to any other stage in the pipeline. At this point, the display pipe may fetch more data. As such, in response to transmitting the image data, at step **430**, the data transfer interconnect is powered up so more data may be fetched. At step **435** a determination is made regarding whether the end of the frame has been reached. If yes, flow proceeds back to step **402**. If no, flow proceeds back to step **410** in which more data is received through data transfer interconnect **410**. As discussed previously, in certain embodiments, operating in a scale mode prevents the fabric from being powered down between fetches due to the display pipe successively fetching one image source line at a time. In other embodiments, however, the fabric may still be powered down



in a scale mode but for a significantly smaller amount of time than what occurs in a non-scale mode.

Turning now to FIG. 5, a flow diagram illustrating one embodiment of a method for powering down a data transfer interconnect is shown. Similar to method 400, method 500 may be performed by any suitable system that supports power management. In various embodiments, method 500 may be used by any system that performs method 400 to fetch image data. In various embodiments, some of the blocks shown in FIG. 5 may be performed concurrently, in a different order than shown, or omitted. Additional method elements may also be performed as desired.

Method 500 begins at step 502 in which image data (e.g., image data 202) is transmitted through a data transfer interconnect (e.g., fabric 102). As discussed previously, in various embodiments, image data may be transferred from memory (e.g., memory 106) to a display pipe (e.g., display pipe 200). At decision block 504, a determination is made as to whether the interconnect is idle. As mentioned above, in certain embodiments, this determination may be made by a timer. If the interconnect is not idle, flow proceeds back to step 502. If the interconnect is idle, flow proceeds to step 516 at which point a determination is made as to whether the interconnect has been idle for a threshold amount of time. If the idle time is below the threshold amount of time, flow proceeds through back to decision block 504. Otherwise, flow proceeds through to step 522. At step 522, the data transfer interconnect is power gated. At step 524, the data transfer interconnect is powered back up upon receiving a data request (e.g., display pipe 200 requests to fetch another block of data from memory 106).

Turning now to FIG. 6, a flow diagram illustrating one embodiment of a method for operating a display pipe in two different modes is shown. In various embodiments, method 600 is performed within a display processing unit (e.g., display processing unit 110). In various embodiments, some of the blocks shown in FIG. 6 may be performed concurrently, in a different order than shown, or omitted. Additional method elements may also be performed as desired.

Method 600 begins at step 602 in which line buffers (e.g., line buffers 310a-x) within a display buffer (e.g., display buffer 114) are filled with data (e.g., image data 202). At decision block 604, a determination is made as to whether the display pipe is operating in a non-scale mode (e.g., in one embodiment this may be indicated by a register such as scale mode register 340). If a scale mode is indicated, flow proceeds to step 608. At step 608, read logic (e.g., buffer read logic 320), reads all line buffers. As discussed above, subsequent to reading all the line buffers, the display pipe successively fetches a new image source line. Accordingly, at step 610, as the fabric does not remain idle, the system continues to power the fabric. Flow proceeds through back to step 602.

At decision block 604, if a non-scale mode is indicated flow proceeds to step 614. At step 614 the data transfer interconnect is powered down (i.e., in certain embodiments a timer controls this; in other embodiments the display pipe may control this). At step 616, read logic selectively reads each line buffer one at a time. After reading all the buffers, at step 618, the fabric is powered up. Flow proceeds back to step 602.

Although specific embodiments have been described above, these embodiments are not intended to limit the scope of the present disclosure, even where only a single embodiment is described with respect to a particular feature. Examples of features provided in the disclosure are intended to be illustrative rather than restrictive unless stated otherwise. The above description is intended to cover such alter-

natives, modifications, and equivalents as would be apparent to a person skilled in the art having the benefit of this disclosure.

The scope of the present disclosure includes any feature or combination of features disclosed herein (either explicitly or implicitly), or any generalization thereof, whether or not it mitigates any or all of the problems addressed herein. Accordingly, new claims may be formulated during prosecution of this application (or an application claiming priority thereto) to any such combination of features. In particular, with reference to the appended claims, features from dependent claims may be combined with those of the independent claims and features from respective independent claims may be combined in any appropriate manner and not merely in the specific combinations enumerated in the appended claims.

What is claimed is:

1. A method, comprising:

operating a display unit in a first mode of operation, including:

a display buffer receiving sets of image data, each set having a first size, through a data transfer interconnect; scaling circuitry scaling image data from the display buffer in at least two dimensions; and

operating the display unit in a second mode of operation, including:

the display buffer receiving sets of image data, each set having a second size that is greater than the first size, through the data transfer interconnect;

the scaling circuitry scaling image data from the display buffer in at most one dimension; and

powering down the data transfer interconnect during one or more time intervals between the display buffer receiving the sets of image data.

2. The method of claim 1, wherein the display buffer includes a plurality of line buffers, each configured to store a respective image source line, wherein a display pipe configured to render images to be displayed includes the display buffer; and

wherein said powering down is performed in response to the received image data including two or more image source lines.

3. The method of claim 2, wherein the operating in the second mode of operation includes:

selectively reading one or more of the image source lines from the plurality of line buffers, wherein the selectively reading is performed multiple times during the time interval.

4. The method of claim 1, wherein the second mode is a non-scale mode, wherein the operating in the second mode of operation includes the scaling circuitry transmitting the image data from the display buffer via a bypass path without scaling the image data from the display buffer.

5. The method of claim 1, further comprising:

determining whether to use the first mode or the second mode based on a programmable setting stored in a register of a display pipe.

6. The method of claim 1, further comprising:

wherein the powering down the data transfer interconnect is based on a timer that maintains a value indicative of an amount of time that the data transfer interconnect has been idle.



## 11

7. An apparatus, comprising:  
 a data transfer interconnect;  
 a display buffer; and  
 a display pipe configured to:  
 operate in a first mode in which the display pipe is config- 5  
 ured to:  
 receive sets of image data, each set having a first size, via  
 the data transfer interconnect and store the sets of image  
 data in the display buffer; and  
 scale image data from the display buffer in at least two 10  
 dimensions; and  
 operate in a second mode in which the display pipe is  
 configured to:  
 receive sets of image data, each set having a second size 15  
 that is greater than the first size, via the data transfer  
 interconnect and store the sets of image data in the  
 display buffer; and  
 scale image data from the display buffer in at most one 20  
 dimension,  
 wherein the apparatus is configured, in the second mode, to  
 reduce power to the data transfer interconnect during  
 one or more time intervals between receiving sets of  
 image data.

8. The apparatus of claim 7, wherein the apparatus is con- 25  
 figured to reduce power to the data transfer interconnect in  
 response to an interval between fetching the sets of image  
 data, each set having the second size, wherein the length of  
 the interval exceeds a threshold value.

9. The apparatus of claim 8, wherein the apparatus is con- 30  
 figured to maintain a timer indicative of an amount of time  
 that the data transfer interconnect has remained idle, and  
 wherein the apparatus is configured to reduce power to the  
 data transfer interconnect based on the timer.

10. The apparatus of claim 7, wherein the apparatus is 35  
 configured, in the second mode, to reduce power to a memory  
 controller between fetching sets of image data, wherein the  
 memory controller is configured to retrieve data from the  
 memory.

11. The apparatus of claim 7, wherein the display buffer 40  
 includes a plurality of line buffers configured to store lines of  
 image data, wherein the first size corresponds to a single line  
 of image data and wherein the second size corresponds to  
 multiple lines of image data.

12. The apparatus of claim 7, wherein the second mode is 45  
 a non-scale mode, wherein the display pipe is configured to,  
 in the second mode, scale image data from the display buffer  
 in at most one dimension by causing the sets of image data  
 stored in the display buffer to bypass scaling circuitry without  
 scaling the sets of image data. 50

13. The apparatus of claim 11, wherein the display pipe is  
 configured to perform both horizontal and vertical scaling of  
 the image data in the display buffer in the first mode.

14. The apparatus of claim 11, wherein the display pipe is 55  
 configured to fetch image source lines having subsampled  
 chroma, and wherein the display pipe is configured, in the  
 second mode, to cause the image source lines having sub-  
 sampled chroma to bypass a vertical scaler or a horizontal  
 scaler.

## 12

15. An apparatus, comprising:  
 a plurality of line buffers configured to receive image data  
 from a memory via a data transfer interconnect;  
 scaling circuitry configured to scale image data from the  
 line buffers in a plurality of dimensions; and  
 display circuitry configured to:

operate in a scaling mode to use the scaling circuitry to  
 produce an output line of image data by performing  
 one or more scaling operations in at least two dimen-  
 sions on at least a portion of the image data, wherein  
 the at least a portion of the image data is read from a  
 first set of line buffers that includes two or more of the  
 plurality of line buffers; and

operate in a non-scaling mode or a hybrid mode in which  
 the apparatus is configured to produce an output line  
 of image data by selectively reading a portion of the  
 image data from a second set of line buffers that  
 includes a smaller number of line buffers than the first  
 set of line buffers and bypass the image data from the  
 second set of line buffers or perform one or more  
 scaling operations in at most one dimension on the  
 image data from the second set of line buffers; and

reduce power to the data transfer interconnect, in the  
 non-scaling mode or the hybrid mode, during one or  
 more time intervals between fetching image data for  
 the line buffers.

16. The apparatus of claim 15, wherein the apparatus is  
 configured to

maintain power to the data transfer interconnect while  
 operating in the scaling mode.

17. The apparatus of claim 15, wherein the display circuitry  
 is configured to:

in the non-scaling mode or the hybrid mode, perform a first  
 set of read operations from the memory, wherein each  
 read operation in the first set are of a plurality of image  
 source lines; and

in response to operating in the scaling mode, perform a  
 second set of read operations from the memory, wherein  
 one read operation in the second set are of a single image  
 source line;

wherein the display circuitry is configured to perform the  
 second set at a higher rate than the first set.

18. The apparatus of claim 15, further comprising:  
 a register configured to store a value indicative of whether  
 the apparatus is to operate the scaling mode, the non-  
 scaling mode, or the hybrid mode.

19. The apparatus of claim 15, wherein the apparatus is  
 configured to:

identify a set of image data as having subsampled chroma;  
 and

cause the set of image data to bypass one of a horizontal  
 scaler and a vertical scaler of the scaling circuitry in  
 response to the identification.

20. The apparatus of claim 15, wherein the apparatus is  
 configured to:

reduce power to a memory controller of the memory while  
 operating in the non-scaling mode; and

maintain power to the memory controller while operating  
 in the scaling mode.

\* \* \* \* \*