

US009113828B2

(12) **United States Patent**  
**Budiman**

(10) **Patent No.:** **US 9,113,828 B2**  
(45) **Date of Patent:** **\*Aug. 25, 2015**

(54) **METHOD AND SYSTEM FOR PROVIDING ANALYTE MONITORING**

(2013.01); *A61B 5/1468* (2013.01); *G06F 19/3406* (2013.01); *G06F 19/3456* (2013.01)

(75) Inventor: **Erwin S. Budiman**, Fremont, CA (US)

(58) **Field of Classification Search**

CPC ..... *A61B 5/002*; *A61B 5/14532*; *A61B 5/14546*; *A61B 5/1486*; *A61B 5/145*; *A61B 5/14503*; *A61B 5/1468*; *A61B 5/1473*; *A61B 5/14735*; *A61B 5/14865*; *A61B 5/1495*; *G06F 19/3406*; *G06F 19/3456*; *G06Q 50/24*  
See application file for complete search history.

(73) Assignee: **Abbott Diabetes Care Inc.**, Alameda, CA (US)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 598 days.

This patent is subject to a terminal disclaimer.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,581,062 A 5/1971 Aston  
3,926,760 A 12/1975 Allen et al.  
3,949,388 A 4/1976 Fuller  
3,960,497 A 6/1976 Acord et al.  
3,978,856 A 9/1976 Michel  
4,036,749 A 7/1977 Anderson

(Continued)

(21) Appl. No.: **13/544,946**

(22) Filed: **Jul. 9, 2012**

(65) **Prior Publication Data**

US 2012/0277565 A1 Nov. 1, 2012

**Related U.S. Application Data**

(63) Continuation of application No. 12/506,227, filed on Jul. 20, 2009, now Pat. No. 8,216,137, which is a continuation of application No. 11/552,935, filed on Oct. 25, 2006, now Pat. No. 7,630,748.

FOREIGN PATENT DOCUMENTS

CA 2667930 C 4/2011  
DE 4401400 7/1995

(Continued)

OTHER PUBLICATIONS

Armour, J. C., et al., "Application of Chronic Intravascular Blood Glucose Sensor in Dogs", *Diabetes*, vol. 39, 1990, pp. 1519-1526.

(Continued)

*Primary Examiner* — Navin Natnithithadha

(74) *Attorney, Agent, or Firm* — Jackson & Co., LLP

(51) **Int. Cl.**

*A61B 5/1473* (2006.01)  
*A61B 5/1468* (2006.01)  
*A61B 5/145* (2006.01)  
*A61B 5/1486* (2006.01)  
*G06Q 50/24* (2012.01)  
*A61B 5/00* (2006.01)  
*G06F 19/00* (2011.01)


(52) **U.S. Cl.**

CPC ..... *A61B 5/14532* (2013.01); *A61B 5/002* (2013.01); *A61B 5/1473* (2013.01); *A61B 5/1486* (2013.01); *A61B 5/14503* (2013.01); *A61B 5/14546* (2013.01); *G06Q 50/24*

(57) **ABSTRACT**

Methods and apparatuses for determining an analyte value are disclosed.

**12 Claims, 9 Drawing Sheets**



(56)

## References Cited

## U.S. PATENT DOCUMENTS

|             |         |                 |             |         |                      |
|-------------|---------|-----------------|-------------|---------|----------------------|
| 4,055,175 A | 10/1977 | Clemens et al.  | 5,365,426 A | 11/1994 | Siegel et al.        |
| 4,129,128 A | 12/1978 | McFarlane       | 5,372,427 A | 12/1994 | Padovani et al.      |
| 4,245,634 A | 1/1981  | Albisser et al. | 5,376,070 A | 12/1994 | Purvis et al.        |
| 4,327,725 A | 5/1982  | Cortese et al.  | 5,379,238 A | 1/1995  | Stark                |
| 4,344,438 A | 8/1982  | Schultz         | 5,384,547 A | 1/1995  | Lynk et al.          |
| 4,349,728 A | 9/1982  | Phillips et al. | 5,390,671 A | 2/1995  | Lord et al.          |
| 4,373,527 A | 2/1983  | Fischell        | 5,391,250 A | 2/1995  | Cheney, II et al.    |
| 4,392,849 A | 7/1983  | Petre et al.    | 5,400,795 A | 3/1995  | Murphy et al.        |
| 4,425,920 A | 1/1984  | Bourland et al. | 5,408,999 A | 4/1995  | Singh et al.         |
| 4,441,968 A | 4/1984  | Emmer et al.    | 5,411,647 A | 5/1995  | Johnson et al.       |
| 4,462,048 A | 7/1984  | Ross            | 5,425,749 A | 6/1995  | Adams                |
| 4,478,976 A | 10/1984 | Goertz et al.   | 5,425,868 A | 6/1995  | Pedersen             |
| 4,494,950 A | 1/1985  | Fischell        | 5,431,160 A | 7/1995  | Wilkins              |
| 4,509,531 A | 4/1985  | Ward            | 5,431,921 A | 7/1995  | Thombre              |
| 4,527,240 A | 7/1985  | Kvitash         | 5,438,983 A | 8/1995  | Falcone              |
| 4,538,616 A | 9/1985  | Rogoff          | 5,462,645 A | 10/1995 | Albery et al.        |
| 4,545,382 A | 10/1985 | Higgins et al.  | 5,472,317 A | 12/1995 | Field et al.         |
| 4,619,793 A | 10/1986 | Lee             | 5,489,414 A | 2/1996  | Schreiber et al.     |
| 4,671,288 A | 6/1987  | Gough           | 5,497,772 A | 3/1996  | Schulman et al.      |
| 4,703,756 A | 11/1987 | Gough et al.    | 5,505,828 A | 4/1996  | Wong et al.          |
| 4,711,245 A | 12/1987 | Higgins et al.  | 5,507,288 A | 4/1996  | Bocker et al.        |
| 4,731,051 A | 3/1988  | Fischell        | 5,509,410 A | 4/1996  | Hill et al.          |
| 4,731,726 A | 3/1988  | Allen, III      | 5,514,718 A | 5/1996  | Lewis et al.         |
| 4,749,985 A | 6/1988  | Corsberg        | 5,520,191 A | 5/1996  | Karlsson et al.      |
| 4,757,022 A | 7/1988  | Shults et al.   | 5,520,191 A | 5/1996  | Karlsson et al.      |
| 4,759,366 A | 7/1988  | Callaghan       | 5,531,878 A | 7/1996  | Vadgama et al.       |
| 4,777,953 A | 10/1988 | Ash et al.      | 5,543,326 A | 8/1996  | Heller et al.        |
| 4,779,618 A | 10/1988 | Mund et al.     | 5,552,997 A | 9/1996  | Massart              |
| 4,854,322 A | 8/1989  | Ash et al.      | 5,568,400 A | 10/1996 | Stark et al.         |
| 4,871,351 A | 10/1989 | Feingold        | 5,568,806 A | 10/1996 | Cheney, II et al.    |
| 4,890,620 A | 1/1990  | Gough           | 5,569,186 A | 10/1996 | Lord et al.          |
| 4,925,268 A | 5/1990  | Iyer et al.     | 5,582,184 A | 12/1996 | Erickson et al.      |
| 4,947,845 A | 8/1990  | Davis           | 5,586,553 A | 12/1996 | Halili et al.        |
| 4,953,552 A | 9/1990  | DeMarzo         | 5,593,852 A | 1/1997  | Heller et al.        |
| 4,986,271 A | 1/1991  | Wilkins         | 5,601,435 A | 2/1997  | Quy                  |
| 4,995,402 A | 2/1991  | Smith et al.    | 5,609,575 A | 3/1997  | Larson et al.        |
| 5,000,180 A | 3/1991  | Kuypers et al.  | 5,628,310 A | 5/1997  | Rao et al.           |
| 5,002,054 A | 3/1991  | Ash et al.      | 5,628,890 A | 5/1997  | Carter et al.        |
| 5,019,974 A | 5/1991  | Beckers         | 5,640,954 A | 6/1997  | Pfeiffer et al.      |
| 5,050,612 A | 9/1991  | Matsumura       | 5,653,239 A | 8/1997  | Pompei et al.        |
| 5,055,171 A | 10/1991 | Peck            | 5,660,163 A | 8/1997  | Schulman et al.      |
| 5,068,536 A | 11/1991 | Rosenthal       | 5,665,222 A | 9/1997  | Heller et al.        |
| 5,077,476 A | 12/1991 | Rosenthal       | 5,711,001 A | 1/1998  | Bussan et al.        |
| 5,082,550 A | 1/1992  | Rishpon et al.  | 5,711,861 A | 1/1998  | Ward et al.          |
| 5,106,365 A | 4/1992  | Hernandez       | 5,720,295 A | 2/1998  | Greenhut et al.      |
| 5,113,869 A | 5/1992  | Nappholz et al. | 5,733,259 A | 3/1998  | Valcke et al.        |
| 5,122,925 A | 6/1992  | Inpyun          | 5,735,285 A | 4/1998  | Albert et al.        |
| 5,135,004 A | 8/1992  | Adams et al.    | 5,741,211 A | 4/1998  | Renirie et al.       |
| 5,148,812 A | 9/1992  | Verrier et al.  | 5,772,586 A | 6/1998  | Heinonen et al.      |
| 5,165,407 A | 11/1992 | Wilson et al.   | 5,785,660 A | 7/1998  | van Lake et al.      |
| 5,199,428 A | 4/1993  | Obel et al.     | 5,791,344 A | 8/1998  | Schulman et al.      |
| 5,202,261 A | 4/1993  | Musho et al.    | 5,792,065 A | 8/1998  | Xue et al.           |
| 5,203,326 A | 4/1993  | Collins         | 5,820,551 A | 10/1998 | Hill et al.          |
| 5,204,264 A | 4/1993  | Kaminer et al.  | 5,822,715 A | 10/1998 | Worthington et al.   |
| 5,210,778 A | 5/1993  | Massart         | 5,891,047 A | 4/1999  | Lander et al.        |
| 5,231,988 A | 8/1993  | Wernicke et al. | 5,899,855 A | 5/1999  | Brown                |
| 5,246,867 A | 9/1993  | Lakowicz et al. | 5,914,026 A | 6/1999  | Blubaugh, Jr. et al. |
| 5,262,035 A | 11/1993 | Gregg et al.    | 5,918,603 A | 7/1999  | Brown                |
| 5,262,305 A | 11/1993 | Heller et al.   | 5,925,021 A | 7/1999  | Castellano et al.    |
| 5,264,104 A | 11/1993 | Gregg et al.    | 5,935,224 A | 8/1999  | Svancarek et al.     |
| 5,264,105 A | 11/1993 | Gregg et al.    | 5,942,979 A | 8/1999  | Luppino              |
| 5,279,294 A | 1/1994  | Anderson et al. | 5,957,854 A | 9/1999  | Besson et al.        |
| 5,285,792 A | 2/1994  | Sjoquist et al. | 5,960,797 A | 10/1999 | Kramer et al.        |
| 5,293,877 A | 3/1994  | O'Hara et al.   | 5,961,451 A | 10/1999 | Reber et al.         |
| 5,299,571 A | 4/1994  | Mastrototaro    | 5,964,993 A | 10/1999 | Blubaugh, Jr. et al. |
| 5,313,953 A | 5/1994  | Yomtov et al.   | 5,965,380 A | 10/1999 | Heller et al.        |
| 5,320,715 A | 6/1994  | Berg            | 5,971,922 A | 10/1999 | Arita et al.         |
| 5,320,725 A | 6/1994  | Gregg et al.    | 5,995,860 A | 11/1999 | Sun et al.           |
| 5,322,063 A | 6/1994  | Allen et al.    | 6,001,067 A | 12/1999 | Shults et al.        |
| 5,328,460 A | 7/1994  | Lord et al.     | 6,016,443 A | 1/2000  | Ekwall et al.        |
| 5,330,634 A | 7/1994  | Wong et al.     | 6,021,350 A | 2/2000  | Mathson              |
| 5,340,722 A | 8/1994  | Wolfbeis et al. | 6,024,699 A | 2/2000  | Surwit et al.        |
| 5,342,789 A | 8/1994  | Chick et al.    | 6,038,469 A | 3/2000  | Karlsson et al.      |
| 5,356,786 A | 10/1994 | Heller et al.   | 6,049,727 A | 4/2000  | Crothall             |
| 5,360,404 A | 11/1994 | Novacek et al.  | 6,071,391 A | 6/2000  | Gotoh et al.         |
|             |         |                 | 6,073,031 A | 6/2000  | Helstab et al.       |
|             |         |                 | 6,083,710 A | 7/2000  | Heller et al.        |
|             |         |                 | 6,088,608 A | 7/2000  | Schulman et al.      |
|             |         |                 | 6,091,976 A | 7/2000  | Pfeiffer et al.      |
|             |         |                 | 6,093,172 A | 7/2000  | Funderburk et al.    |

(56)

## References Cited

## U.S. PATENT DOCUMENTS

|           |    |         |                       |           |    |         |                     |
|-----------|----|---------|-----------------------|-----------|----|---------|---------------------|
| 6,103,033 | A  | 8/2000  | Say et al.            | 6,564,105 | B2 | 5/2003  | Starkweather et al. |
| 6,108,577 | A  | 8/2000  | Benser                | 6,565,509 | B1 | 5/2003  | Say et al.          |
| 6,112,116 | A  | 8/2000  | Fischell              | 6,571,128 | B2 | 5/2003  | Lebel et al.        |
| 6,115,628 | A  | 9/2000  | Stadler et al.        | 6,572,542 | B1 | 6/2003  | Houben et al.       |
| 6,117,290 | A  | 9/2000  | Say et al.            | 6,574,490 | B2 | 6/2003  | Abbink et al.       |
| 6,119,028 | A  | 9/2000  | Schulman et al.       | 6,576,101 | B1 | 6/2003  | Heller et al.       |
| 6,120,676 | A  | 9/2000  | Heller et al.         | 6,577,899 | B2 | 6/2003  | Lebel et al.        |
| 6,121,009 | A  | 9/2000  | Heller et al.         | 6,579,690 | B1 | 6/2003  | Bonnecaze et al.    |
| 6,121,611 | A  | 9/2000  | Lindsay et al.        | 6,585,644 | B2 | 7/2003  | Lebel et al.        |
| 6,122,351 | A  | 9/2000  | Schlueter, Jr. et al. | 6,591,125 | B1 | 7/2003  | Buse et al.         |
| 6,128,526 | A  | 10/2000 | Stadler et al.        | 6,592,745 | B1 | 7/2003  | Feldman et al.      |
| 6,134,461 | A  | 10/2000 | Say et al.            | 6,595,919 | B2 | 7/2003  | Berner et al.       |
| 6,143,164 | A  | 11/2000 | Heller et al.         | 6,600,997 | B2 | 7/2003  | Deweese et al.      |
| 6,144,837 | A  | 11/2000 | Quy                   | 6,605,200 | B1 | 8/2003  | Mao et al.          |
| 6,159,147 | A  | 12/2000 | Lichter et al.        | 6,605,201 | B1 | 8/2003  | Mao et al.          |
| 6,161,095 | A  | 12/2000 | Brown                 | 6,607,509 | B2 | 8/2003  | Bobroff et al.      |
| 6,162,611 | A  | 12/2000 | Heller et al.         | 6,610,012 | B2 | 8/2003  | Mault               |
| 6,175,752 | B1 | 1/2001  | Say et al.            | 6,616,819 | B1 | 9/2003  | Liamos et al.       |
| 6,200,265 | B1 | 3/2001  | Walsh et al.          | 6,618,934 | B1 | 9/2003  | Feldman et al.      |
| 6,212,416 | B1 | 4/2001  | Ward et al.           | 6,622,045 | B2 | 9/2003  | Snell et al.        |
| 6,219,574 | B1 | 4/2001  | Cormier et al.        | 6,633,772 | B2 | 10/2003 | Ford et al.         |
| 6,223,283 | B1 | 4/2001  | Chaiken et al.        | 6,635,014 | B2 | 10/2003 | Starkweather et al. |
| 6,233,471 | B1 | 5/2001  | Berner et al.         | 6,641,533 | B2 | 11/2003 | Causey, III et al.  |
| 6,233,486 | B1 | 5/2001  | Ekwall et al.         | 6,648,821 | B2 | 11/2003 | Lebel et al.        |
| 6,248,067 | B1 | 6/2001  | Causey, III et al.    | 6,650,471 | B2 | 11/2003 | Doi                 |
| 6,249,705 | B1 | 6/2001  | Snell                 | 6,654,625 | B1 | 11/2003 | Say et al.          |
| 6,254,586 | B1 | 7/2001  | Mann et al.           | 6,656,114 | B1 | 12/2003 | Poulsen et al.      |
| 6,256,538 | B1 | 7/2001  | Ekwall                | 6,658,396 | B1 | 12/2003 | Tang et al.         |
| 6,264,606 | B1 | 7/2001  | Ekwall et al.         | 6,659,948 | B2 | 12/2003 | Lebel et al.        |
| 6,270,455 | B1 | 8/2001  | Brown                 | 6,668,196 | B1 | 12/2003 | Villegas et al.     |
| 6,272,379 | B1 | 8/2001  | Fischell et al.       | 6,675,030 | B2 | 1/2004  | Ciuczak et al.      |
| 6,275,717 | B1 | 8/2001  | Gross et al.          | 6,676,816 | B2 | 1/2004  | Mao et al.          |
| 6,283,761 | B1 | 9/2001  | Joao                  | 6,687,546 | B2 | 2/2004  | Lebel et al.        |
| 6,284,478 | B1 | 9/2001  | Heller et al.         | 6,689,056 | B1 | 2/2004  | Kilcoyne et al.     |
| 6,293,925 | B1 | 9/2001  | Safabash et al.       | 6,694,191 | B2 | 2/2004  | Starkweather et al. |
| 6,295,506 | B1 | 9/2001  | Heinonen et al.       | 6,695,860 | B1 | 2/2004  | Ward et al.         |
| 6,299,757 | B1 | 10/2001 | Feldman et al.        | 6,698,269 | B2 | 3/2004  | Baber et al.        |
| 6,306,104 | B1 | 10/2001 | Cunningham et al.     | 6,702,857 | B2 | 3/2004  | Brauker et al.      |
| 6,309,884 | B1 | 10/2001 | Cooper et al.         | 6,730,200 | B1 | 5/2004  | Stewart et al.      |
| 6,329,161 | B1 | 12/2001 | Heller et al.         | 6,731,985 | B2 | 5/2004  | Poore et al.        |
| 6,338,790 | B1 | 1/2002  | Feldman et al.        | 6,733,446 | B2 | 5/2004  | Lebel et al.        |
| 6,348,640 | B1 | 2/2002  | Navot et al.          | 6,736,957 | B1 | 5/2004  | Forrow et al.       |
| 6,359,444 | B1 | 3/2002  | Grimes                | 6,740,075 | B2 | 5/2004  | Lebel et al.        |
| 6,360,888 | B1 | 3/2002  | McIvor et al.         | 6,741,877 | B1 | 5/2004  | Shults et al.       |
| 6,361,503 | B1 | 3/2002  | Starobin et al.       | 6,746,582 | B2 | 6/2004  | Heller et al.       |
| 6,366,794 | B1 | 4/2002  | Moussy et al.         | 6,749,740 | B2 | 6/2004  | Liamos et al.       |
| 6,377,828 | B1 | 4/2002  | Chaiken et al.        | 6,758,810 | B2 | 7/2004  | Lebel et al.        |
| 6,377,852 | B1 | 4/2002  | Bornzin et al.        | 6,764,581 | B1 | 7/2004  | Forrow et al.       |
| 6,377,894 | B1 | 4/2002  | Deweese et al.        | 6,770,030 | B1 | 8/2004  | Schaupp et al.      |
| 6,379,301 | B1 | 4/2002  | Worthington et al.    | 6,773,671 | B1 | 8/2004  | Lewis et al.        |
| 6,381,493 | B1 | 4/2002  | Stadler et al.        | 6,790,178 | B1 | 9/2004  | Mault et al.        |
| 6,387,048 | B1 | 5/2002  | Schulman et al.       | 6,809,653 | B1 | 10/2004 | Mann et al.         |
| 6,405,066 | B1 | 6/2002  | Essenpreis et al.     | 6,810,290 | B2 | 10/2004 | Lebel et al.        |
| 6,413,393 | B1 | 7/2002  | Van Antwerp et al.    | 6,811,533 | B2 | 11/2004 | Lebel et al.        |
| 6,424,847 | B1 | 7/2002  | Mastrototaro et al.   | 6,811,534 | B2 | 11/2004 | Bowman, IV et al.   |
| 6,427,088 | B1 | 7/2002  | Bowman, IV et al.     | 6,813,519 | B2 | 11/2004 | Lebel et al.        |
| 6,440,068 | B1 | 8/2002  | Brown et al.          | 6,850,790 | B2 | 2/2005  | Berner et al.       |
| 6,461,496 | B1 | 10/2002 | Feldman et al.        | 6,862,465 | B2 | 3/2005  | Shults et al.       |
| 6,471,689 | B1 | 10/2002 | Joseph et al.         | 6,865,407 | B2 | 3/2005  | Kimball et al.      |
| 6,478,736 | B1 | 11/2002 | Mault                 | 6,873,268 | B2 | 3/2005  | Lebel et al.        |
| 6,484,046 | B1 | 11/2002 | Say et al.            | 6,881,551 | B2 | 4/2005  | Heller et al.       |
| 6,501,983 | B1 | 12/2002 | Natarajan et al.      | 6,882,940 | B2 | 4/2005  | Potts et al.        |
| 6,503,381 | B1 | 1/2003  | Gotoh et al.          | 6,892,085 | B2 | 5/2005  | McIvor et al.       |
| 6,514,460 | B1 | 2/2003  | Fendrock              | 6,893,545 | B2 | 5/2005  | Gotoh et al.        |
| 6,514,718 | B2 | 2/2003  | Heller et al.         | 6,895,263 | B2 | 5/2005  | Shin et al.         |
| 6,520,326 | B2 | 2/2003  | McIvor et al.         | 6,895,265 | B2 | 5/2005  | Silver              |
| 6,540,891 | B1 | 4/2003  | Stewart et al.        | 6,923,763 | B1 | 8/2005  | Kovatchev et al.    |
| 6,544,212 | B2 | 4/2003  | Galley et al.         | 6,931,327 | B2 | 8/2005  | Goode, Jr. et al.   |
| 6,551,494 | B1 | 4/2003  | Heller et al.         | 6,932,892 | B2 | 8/2005  | Chen et al.         |
| 6,558,320 | B1 | 5/2003  | Causey, III et al.    | 6,932,894 | B2 | 8/2005  | Mao et al.          |
| 6,558,321 | B1 | 5/2003  | Burd et al.           | 6,936,006 | B2 | 8/2005  | Sabra               |
| 6,558,351 | B1 | 5/2003  | Steil et al.          | 6,942,518 | B2 | 9/2005  | Liamos et al.       |
| 6,560,471 | B1 | 5/2003  | Heller et al.         | 6,950,708 | B2 | 9/2005  | Bowman, IV et al.   |
| 6,561,978 | B1 | 5/2003  | Conn et al.           | 6,958,705 | B2 | 10/2005 | Lebel et al.        |
| 6,562,001 | B2 | 5/2003  | Lebel et al.          | 6,968,294 | B2 | 11/2005 | Gutta et al.        |
|           |    |         |                       | 6,971,274 | B2 | 12/2005 | Olin                |
|           |    |         |                       | 6,974,437 | B2 | 12/2005 | Lebel et al.        |
|           |    |         |                       | 6,990,366 | B2 | 1/2006  | Say et al.          |
|           |    |         |                       | 6,997,907 | B2 | 2/2006  | Safabash et al.     |

(56)

## References Cited

## U.S. PATENT DOCUMENTS

|              |         |                     |                 |         |                       |
|--------------|---------|---------------------|-----------------|---------|-----------------------|
| 6,998,247 B2 | 2/2006  | Monfre et al.       | 7,613,491 B2    | 11/2009 | Boock et al.          |
| 7,003,336 B2 | 2/2006  | Holker et al.       | 7,615,007 B2    | 11/2009 | Shults et al.         |
| 7,003,340 B2 | 2/2006  | Say et al.          | 7,618,369 B2    | 11/2009 | Hayter et al.         |
| 7,003,341 B2 | 2/2006  | Say et al.          | 7,630,748 B2    | 12/2009 | Budiman               |
| 7,010,345 B2 | 3/2006  | Hill et al.         | 7,632,228 B2    | 12/2009 | Brauker et al.        |
| 7,016,713 B2 | 3/2006  | Gardner et al.      | 7,635,594 B2    | 12/2009 | Holmes et al.         |
| 7,016,720 B2 | 3/2006  | Kroll               | 7,637,868 B2    | 12/2009 | Saint et al.          |
| 7,022,072 B2 | 4/2006  | Fox et al.          | 7,640,048 B2    | 12/2009 | Dobbles et al.        |
| 7,022,219 B2 | 4/2006  | Mansouri et al.     | 7,699,775 B2    | 4/2010  | Desai et al.          |
| 7,024,245 B2 | 4/2006  | Lebel et al.        | 7,699,964 B2    | 4/2010  | Feldman et al.        |
| 7,025,425 B2 | 4/2006  | Kovatchev et al.    | 7,736,310 B2    | 6/2010  | Taub et al.           |
| 7,029,443 B2 | 4/2006  | Kroll               | 7,766,829 B2    | 8/2010  | Sloan et al.          |
| 7,029,444 B2 | 4/2006  | Shin et al.         | 7,771,352 B2    | 8/2010  | Shults et al.         |
| 7,041,068 B2 | 5/2006  | Freeman et al.      | 7,774,145 B2    | 8/2010  | Brauker et al.        |
| 7,041,468 B2 | 5/2006  | Drucker et al.      | 7,778,680 B2    | 8/2010  | Goode, Jr. et al.     |
| 7,043,287 B1 | 5/2006  | Khalil et al.       | 7,826,981 B2    | 11/2010 | Goode, Jr. et al.     |
| 7,052,483 B2 | 5/2006  | Wojcik              | 7,866,026 B1    | 1/2011  | Wang et al.           |
| 7,056,302 B2 | 6/2006  | Douglas             | 7,889,069 B2    | 2/2011  | Fifolt et al.         |
| 7,074,307 B2 | 7/2006  | Simpson et al.      | 7,899,511 B2    | 3/2011  | Shults et al.         |
| 7,076,300 B1 | 7/2006  | Kroll et al.        | 7,905,833 B2    | 3/2011  | Brister et al.        |
| 7,081,195 B2 | 7/2006  | Simpson et al.      | 7,914,450 B2    | 3/2011  | Goode, Jr. et al.     |
| 7,092,891 B2 | 8/2006  | Maus et al.         | 7,938,797 B2    | 5/2011  | Estes                 |
| 7,096,064 B2 | 8/2006  | Deno et al.         | 7,974,672 B2    | 7/2011  | Shults et al.         |
| 7,098,803 B2 | 8/2006  | Mann et al.         | 8,211,016 B2 *  | 7/2012  | Budiman ..... 600/309 |
| 7,103,412 B1 | 9/2006  | Kroll               | 8,216,137 B2 *  | 7/2012  | Budiman ..... 600/309 |
| 7,108,778 B2 | 9/2006  | Simpson et al.      | 8,216,138 B1    | 7/2012  | McGarraugh et al.     |
| 7,110,803 B2 | 9/2006  | Shults et al.       | 8,255,026 B1    | 8/2012  | Al-Ali                |
| 7,113,821 B1 | 9/2006  | Sun et al.          | 8,282,549 B2    | 10/2012 | Brauker et al.        |
| 7,118,667 B2 | 10/2006 | Lee                 | 2001/0041831 A1 | 11/2001 | Starkweather et al.   |
| 7,123,950 B2 | 10/2006 | Mannheimer          | 2002/0019022 A1 | 2/2002  | Dunn et al.           |
| 7,134,999 B2 | 11/2006 | Brauker et al.      | 2002/0042090 A1 | 4/2002  | Heller et al.         |
| 7,136,689 B2 | 11/2006 | Shults et al.       | 2002/0068860 A1 | 6/2002  | Clark                 |
| 7,142,911 B2 | 11/2006 | Boileau et al.      | 2002/0103499 A1 | 8/2002  | Perez et al.          |
| 7,153,265 B2 | 12/2006 | Vachon              | 2002/0106709 A1 | 8/2002  | Potts et al.          |
| 7,167,818 B2 | 1/2007  | Brown               | 2002/0120186 A1 | 8/2002  | Keimel                |
| 7,171,274 B2 | 1/2007  | Starkweather et al. | 2002/0128594 A1 | 9/2002  | Das et al.            |
| 7,190,988 B2 | 3/2007  | Say et al.          | 2002/0143266 A1 | 10/2002 | Bock                  |
| 7,192,450 B2 | 3/2007  | Brauker et al.      | 2002/0143372 A1 | 10/2002 | Snell et al.          |
| 7,198,606 B2 | 4/2007  | Boecker et al.      | 2002/0161288 A1 | 10/2002 | Shin et al.           |
| 7,225,535 B2 | 6/2007  | Feldman et al.      | 2002/0169635 A1 | 11/2002 | Shillingburg          |
| 7,226,978 B2 | 6/2007  | Tapsak et al.       | 2002/0193679 A1 | 12/2002 | Malave et al.         |
| 7,258,673 B2 | 8/2007  | Racchini et al.     | 2003/0004403 A1 | 1/2003  | Drinan et al.         |
| 7,267,665 B2 | 9/2007  | Steil et al.        | 2003/0023317 A1 | 1/2003  | Brauker et al.        |
| 7,272,436 B2 | 9/2007  | Gill et al.         | 2003/0023461 A1 | 1/2003  | Quintanilla et al.    |
| 7,276,029 B2 | 10/2007 | Goode, Jr. et al.   | 2003/0032867 A1 | 2/2003  | Crothall et al.       |
| 7,278,983 B2 | 10/2007 | Ireland et al.      | 2003/0032874 A1 | 2/2003  | Rhodes et al.         |
| 7,295,867 B2 | 11/2007 | Berner et al.       | 2003/0042137 A1 | 3/2003  | Mao et al.            |
| 7,297,114 B2 | 11/2007 | Gill et al.         | 2003/0050546 A1 | 3/2003  | Desai et al.          |
| 7,299,082 B2 | 11/2007 | Feldman et al.      | 2003/0065308 A1 | 4/2003  | Lebel et al.          |
| 7,310,544 B2 | 12/2007 | Brister et al.      | 2003/0100821 A1 | 5/2003  | Heller et al.         |
| 7,317,938 B2 | 1/2008  | Lorenz et al.       | 2003/0125612 A1 | 7/2003  | Fox et al.            |
| 7,335,294 B2 | 2/2008  | Heller et al.       | 2003/0130616 A1 | 7/2003  | Steil et al.          |
| 7,354,420 B2 | 4/2008  | Steil et al.        | 2003/0134347 A1 | 7/2003  | Heller et al.         |
| 7,364,592 B2 | 4/2008  | Carr-Brendel et al. | 2003/0168338 A1 | 9/2003  | Gao et al.            |
| 7,366,556 B2 | 4/2008  | Brister et al.      | 2003/0176933 A1 | 9/2003  | Lebel et al.          |
| 7,379,765 B2 | 5/2008  | Petisce et al.      | 2003/0187338 A1 | 10/2003 | Say et al.            |
| 7,402,153 B2 | 7/2008  | Steil et al.        | 2003/0191377 A1 | 10/2003 | Robinson et al.       |
| 7,404,796 B2 | 7/2008  | Ginsberg            | 2003/0199744 A1 | 10/2003 | Buse et al.           |
| 7,424,318 B2 | 9/2008  | Brister et al.      | 2003/0199790 A1 | 10/2003 | Boecker et al.        |
| 7,460,898 B2 | 12/2008 | Brister et al.      | 2003/0208113 A1 | 11/2003 | Mault et al.          |
| 7,467,003 B2 | 12/2008 | Brister et al.      | 2003/0212317 A1 | 11/2003 | Kovatchev et al.      |
| 7,468,125 B2 | 12/2008 | Kraft et al.        | 2003/0212379 A1 | 11/2003 | Bylund et al.         |
| 7,471,972 B2 | 12/2008 | Rhodes et al.       | 2003/0216630 A1 | 11/2003 | Jersey-Willuhn et al. |
| 7,474,992 B2 | 1/2009  | Ariyur              | 2003/0217966 A1 | 11/2003 | Tapsak et al.         |
| 7,494,465 B2 | 2/2009  | Brister et al.      | 2004/0010186 A1 | 1/2004  | Kimball et al.        |
| 7,497,827 B2 | 3/2009  | Brister et al.      | 2004/0010207 A1 | 1/2004  | Flaherty et al.       |
| 7,499,002 B2 | 3/2009  | Blasko et al.       | 2004/0011671 A1 | 1/2004  | Shults et al.         |
| 7,502,644 B2 | 3/2009  | Gill et al.         | 2004/0024553 A1 | 2/2004  | Monfre et al.         |
| 7,519,408 B2 | 4/2009  | Rasdal et al.       | 2004/0039298 A1 | 2/2004  | Abreu                 |
| 7,524,287 B2 | 4/2009  | Bharmi              | 2004/0040840 A1 | 3/2004  | Mao et al.            |
| 7,547,281 B2 | 6/2009  | Hayes et al.        | 2004/0045879 A1 | 3/2004  | Shults et al.         |
| 7,569,030 B2 | 8/2009  | Lebel et al.        | 2004/0054263 A1 | 3/2004  | Moerman et al.        |
| 7,583,990 B2 | 9/2009  | Goode, Jr. et al.   | 2004/0064068 A1 | 4/2004  | DeNuzzio et al.       |
| 7,591,801 B2 | 9/2009  | Brauker et al.      | 2004/0077962 A1 | 4/2004  | Kroll                 |
| 7,599,726 B2 | 10/2009 | Goode, Jr. et al.   | 2004/0078065 A1 | 4/2004  | Kroll                 |
|              |         |                     | 2004/0093167 A1 | 5/2004  | Braig et al.          |
|              |         |                     | 2004/0099529 A1 | 5/2004  | Mao et al.            |
|              |         |                     | 2004/0106858 A1 | 6/2004  | Say et al.            |
|              |         |                     | 2004/0122353 A1 | 6/2004  | Shahmirian et al.     |

(56)

## References Cited

## U.S. PATENT DOCUMENTS

|              |    |         |                    |              |    |         |                      |
|--------------|----|---------|--------------------|--------------|----|---------|----------------------|
| 2004/0133164 | A1 | 7/2004  | Funderburk et al.  | 2006/0001538 | A1 | 1/2006  | Kraft et al.         |
| 2004/0135684 | A1 | 7/2004  | Steinthal et al.   | 2006/0004270 | A1 | 1/2006  | Bedard et al.        |
| 2004/0138588 | A1 | 7/2004  | Saikley et al.     | 2006/0010098 | A1 | 1/2006  | Goodnow et al.       |
| 2004/0138716 | A1 | 7/2004  | Kon et al.         | 2006/0015020 | A1 | 1/2006  | Neale et al.         |
| 2004/0146909 | A1 | 7/2004  | Duong et al.       | 2006/0015024 | A1 | 1/2006  | Brister et al.       |
| 2004/0152622 | A1 | 8/2004  | Keith et al.       | 2006/0016700 | A1 | 1/2006  | Brister et al.       |
| 2004/0167801 | A1 | 8/2004  | Say et al.         | 2006/0017923 | A1 | 1/2006  | Ruchti et al.        |
| 2004/0171921 | A1 | 9/2004  | Say et al.         | 2006/0019327 | A1 | 1/2006  | Brister et al.       |
| 2004/0172307 | A1 | 9/2004  | Gruber             | 2006/0020186 | A1 | 1/2006  | Brister et al.       |
| 2004/0176672 | A1 | 9/2004  | Silver et al.      | 2006/0020187 | A1 | 1/2006  | Brister et al.       |
| 2004/0186362 | A1 | 9/2004  | Brauker et al.     | 2006/0020188 | A1 | 1/2006  | Kamath et al.        |
| 2004/0186365 | A1 | 9/2004  | Jin et al.         | 2006/0020189 | A1 | 1/2006  | Brister et al.       |
| 2004/0193025 | A1 | 9/2004  | Steil et al.       | 2006/0020190 | A1 | 1/2006  | Kamath et al.        |
| 2004/0193090 | A1 | 9/2004  | Lebel et al.       | 2006/0020191 | A1 | 1/2006  | Brister et al.       |
| 2004/0197846 | A1 | 10/2004 | Hockersmith et al. | 2006/0020192 | A1 | 1/2006  | Brister et al.       |
| 2004/0199059 | A1 | 10/2004 | Brauker et al.     | 2006/0025662 | A1 | 2/2006  | Buse et al.          |
| 2004/0204687 | A1 | 10/2004 | Mogensen et al.    | 2006/0025663 | A1 | 2/2006  | Talbot et al.        |
| 2004/0208780 | A1 | 10/2004 | Faries, Jr. et al. | 2006/0029177 | A1 | 2/2006  | Cranford, Jr. et al. |
| 2004/0225338 | A1 | 11/2004 | Lebel et al.       | 2006/0031094 | A1 | 2/2006  | Cohen et al.         |
| 2004/0236200 | A1 | 11/2004 | Say et al.         | 2006/0036139 | A1 | 2/2006  | Brister et al.       |
| 2004/0249253 | A1 | 12/2004 | Racchini et al.    | 2006/0036140 | A1 | 2/2006  | Brister et al.       |
| 2004/0249420 | A1 | 12/2004 | Olson et al.       | 2006/0036141 | A1 | 2/2006  | Kamath et al.        |
| 2004/0254433 | A1 | 12/2004 | Bandis et al.      | 2006/0036142 | A1 | 2/2006  | Brister et al.       |
| 2004/0254434 | A1 | 12/2004 | Goodnow et al.     | 2006/0036143 | A1 | 2/2006  | Brister et al.       |
| 2004/0260478 | A1 | 12/2004 | Schwamm            | 2006/0036144 | A1 | 2/2006  | Brister et al.       |
| 2004/0263354 | A1 | 12/2004 | Mann et al.        | 2006/0036145 | A1 | 2/2006  | Brister et al.       |
| 2004/0267300 | A1 | 12/2004 | Mace               | 2006/0091006 | A1 | 5/2006  | Wang et al.          |
| 2005/0003470 | A1 | 1/2005  | Nelson et al.      | 2006/0142651 | A1 | 6/2006  | Brister et al.       |
| 2005/0004439 | A1 | 1/2005  | Shin et al.        | 2006/0155180 | A1 | 7/2006  | Brister et al.       |
| 2005/0004494 | A1 | 1/2005  | Perez et al.       | 2006/0166629 | A1 | 7/2006  | Reggiardo            |
| 2005/0010087 | A1 | 1/2005  | Banet et al.       | 2006/0167365 | A1 | 7/2006  | Bharmi               |
| 2005/0010269 | A1 | 1/2005  | Lebel et al.       | 2006/0167517 | A1 | 7/2006  | Gill et al.          |
| 2005/0016276 | A1 | 1/2005  | Guan et al.        | 2006/0167518 | A1 | 7/2006  | Gill et al.          |
| 2005/0027177 | A1 | 2/2005  | Shin et al.        | 2006/0167519 | A1 | 7/2006  | Gill et al.          |
| 2005/0027180 | A1 | 2/2005  | Goode et al.       | 2006/0173260 | A1 | 8/2006  | Gaoni et al.         |
| 2005/0027181 | A1 | 2/2005  | Goode et al.       | 2006/0173406 | A1 | 8/2006  | Hayes et al.         |
| 2005/0027462 | A1 | 2/2005  | Goode et al.       | 2006/0173444 | A1 | 8/2006  | Choy et al.          |
| 2005/0027463 | A1 | 2/2005  | Goode et al.       | 2006/0183984 | A1 | 8/2006  | Dobbles et al.       |
| 2005/0031689 | A1 | 2/2005  | Shults et al.      | 2006/0183985 | A1 | 8/2006  | Brister et al.       |
| 2005/0038332 | A1 | 2/2005  | Saidara et al.     | 2006/0189863 | A1 | 8/2006  | Peysen et al.        |
| 2005/0043598 | A1 | 2/2005  | Goode, Jr. et al.  | 2006/0193375 | A1 | 8/2006  | Lee                  |
| 2005/0049179 | A1 | 3/2005  | Davidson et al.    | 2006/0222566 | A1 | 10/2006 | Brauker et al.       |
| 2005/0070774 | A1 | 3/2005  | Addison et al.     | 2006/0224109 | A1 | 10/2006 | Steil et al.         |
| 2005/0090607 | A1 | 4/2005  | Tapsak et al.      | 2006/0226985 | A1 | 10/2006 | Goodnow et al.       |
| 2005/0096511 | A1 | 5/2005  | Fox et al.         | 2006/0229512 | A1 | 10/2006 | Petisce et al.       |
| 2005/0096512 | A1 | 5/2005  | Fox et al.         | 2006/0247508 | A1 | 11/2006 | Fennell              |
| 2005/0112169 | A1 | 5/2005  | Brauker et al.     | 2006/0247685 | A1 | 11/2006 | Bharmi               |
| 2005/0113653 | A1 | 5/2005  | Fox et al.         | 2006/0247985 | A1 | 11/2006 | Liamos et al.        |
| 2005/0114068 | A1 | 5/2005  | Chey et al.        | 2006/0258929 | A1 | 11/2006 | Goode et al.         |
| 2005/0115832 | A1 | 6/2005  | Simpson et al.     | 2006/0264785 | A1 | 11/2006 | Dring et al.         |
| 2005/0121322 | A1 | 6/2005  | Say et al.         | 2006/0272652 | A1 | 12/2006 | Stocker et al.       |
| 2005/0131346 | A1 | 6/2005  | Douglas            | 2006/0281985 | A1 | 12/2006 | Ward et al.          |
| 2005/0143635 | A1 | 6/2005  | Kamath et al.      | 2007/0016381 | A1 | 1/2007  | Kamath et al.        |
| 2005/0154271 | A1 | 7/2005  | Rasdal et al.      | 2007/0027381 | A1 | 2/2007  | Stafford             |
| 2005/0176136 | A1 | 8/2005  | Burd et al.        | 2007/0032706 | A1 | 2/2007  | Kamath et al.        |
| 2005/0177398 | A1 | 8/2005  | Watanabe et al.    | 2007/0033074 | A1 | 2/2007  | Nitzan et al.        |
| 2005/0182306 | A1 | 8/2005  | Sloan              | 2007/0056858 | A1 | 3/2007  | Chen et al.          |
| 2005/0187720 | A1 | 8/2005  | Goode, Jr. et al.  | 2007/0060803 | A1 | 3/2007  | Liljeryd et al.      |
| 2005/0192494 | A1 | 9/2005  | Ginsberg           | 2007/0060814 | A1 | 3/2007  | Stafford             |
| 2005/0192557 | A1 | 9/2005  | Brauker et al.     | 2007/0066873 | A1 | 3/2007  | Kamath et al.        |
| 2005/0195930 | A1 | 9/2005  | Spital et al.      | 2007/0068807 | A1 | 3/2007  | Feldman et al.       |
| 2005/0199494 | A1 | 9/2005  | Say et al.         | 2007/0071681 | A1 | 3/2007  | Gadkar et al.        |
| 2005/0203360 | A1 | 9/2005  | Brauker et al.     | 2007/0073129 | A1 | 3/2007  | Shah et al.          |
| 2005/0214892 | A1 | 9/2005  | Kovatchev et al.   | 2007/0078320 | A1 | 4/2007  | Stafford             |
| 2005/0239154 | A1 | 10/2005 | Feldman et al.     | 2007/0078321 | A1 | 4/2007  | Mazza et al.         |
| 2005/0239156 | A1 | 10/2005 | Drucker et al.     | 2007/0078322 | A1 | 4/2007  | Stafford             |
| 2005/0241957 | A1 | 11/2005 | Mao et al.         | 2007/0078323 | A1 | 4/2007  | Reggiardo et al.     |
| 2005/0245795 | A1 | 11/2005 | Goode, Jr. et al.  | 2007/0095661 | A1 | 5/2007  | Wang et al.          |
| 2005/0245799 | A1 | 11/2005 | Brauker et al.     | 2007/0106135 | A1 | 5/2007  | Sloan et al.         |
| 2005/0245839 | A1 | 11/2005 | Stivoric et al.    | 2007/0108048 | A1 | 5/2007  | Wang et al.          |
| 2005/0245904 | A1 | 11/2005 | Estes et al.       | 2007/0118405 | A1 | 5/2007  | Campbell et al.      |
| 2005/0277164 | A1 | 12/2005 | Drucker et al.     | 2007/0124002 | A1 | 5/2007  | Estes et al.         |
| 2005/0277912 | A1 | 12/2005 | John               | 2007/0149875 | A1 | 6/2007  | Ouyang et al.        |
| 2005/0287620 | A1 | 12/2005 | Heller et al.      | 2007/0156033 | A1 | 7/2007  | Causey, III et al.   |
| 2005/0288725 | A1 | 12/2005 | Hettrick et al.    | 2007/0163880 | A1 | 7/2007  | Woo et al.           |
|              |    |         |                    | 2007/0168224 | A1 | 7/2007  | Letzt et al.         |
|              |    |         |                    | 2007/0173706 | A1 | 7/2007  | Neinast et al.       |
|              |    |         |                    | 2007/0173709 | A1 | 7/2007  | Petisce et al.       |
|              |    |         |                    | 2007/0173710 | A1 | 7/2007  | Petisce et al.       |

(56)

References Cited

U.S. PATENT DOCUMENTS

|                  |         |                       |                  |         |                       |
|------------------|---------|-----------------------|------------------|---------|-----------------------|
| 2007/0173761 A1  | 7/2007  | Kanderian et al.      | 2008/0242961 A1  | 10/2008 | Brister et al.        |
| 2007/0179349 A1  | 8/2007  | Hoyme et al.          | 2008/0242963 A1  | 10/2008 | Essenpreis et al.     |
| 2007/0179352 A1  | 8/2007  | Randlov et al.        | 2008/0255434 A1  | 10/2008 | Hayter et al.         |
| 2007/0179434 A1  | 8/2007  | Weinert et al.        | 2008/0255437 A1  | 10/2008 | Hayter                |
| 2007/0191701 A1  | 8/2007  | Feldman et al.        | 2008/0255808 A1  | 10/2008 | Hayter                |
| 2007/0199818 A1  | 8/2007  | Petyt et al.          | 2008/0256048 A1  | 10/2008 | Hayter                |
| 2007/0203407 A1  | 8/2007  | Hoss et al.           | 2008/0262469 A1  | 10/2008 | Hayter                |
| 2007/0203966 A1  | 8/2007  | Brauker et al.        | 2008/0262469 A1  | 10/2008 | Brister et al.        |
| 2007/0213657 A1  | 9/2007  | Jennewine et al.      | 2008/0275313 A1  | 11/2008 | Brister et al.        |
| 2007/0227911 A1  | 10/2007 | Wang et al.           | 2008/0287761 A1  | 11/2008 | Hayter                |
| 2007/0232877 A1  | 10/2007 | He                    | 2008/0287762 A1  | 11/2008 | Hayter                |
| 2007/0232878 A1  | 10/2007 | Kovatchev et al.      | 2008/0287763 A1  | 11/2008 | Hayter                |
| 2007/0232880 A1  | 10/2007 | Siddiqui et al.       | 2008/0287764 A1  | 11/2008 | Rasdal et al.         |
| 2007/0233013 A1  | 10/2007 | Schoenberg et al.     | 2008/0287765 A1  | 11/2008 | Rasdal et al.         |
| 2007/0235331 A1  | 10/2007 | Simpson et al.        | 2008/0287766 A1  | 11/2008 | Rasdal et al.         |
| 2007/0249922 A1  | 10/2007 | Peysner et al.        | 2008/0288180 A1  | 11/2008 | Hayter                |
| 2007/0255321 A1  | 11/2007 | Gerber et al.         | 2008/0288204 A1  | 11/2008 | Hayter et al.         |
| 2007/0282299 A1  | 12/2007 | Hellwig               | 2008/0296155 A1  | 12/2008 | Shults et al.         |
| 2007/0299617 A1  | 12/2007 | Willis                | 2008/0300572 A1  | 12/2008 | Rankers et al.        |
| 2008/0004515 A1  | 1/2008  | Jennewine et al.      | 2008/0306368 A1  | 12/2008 | Goode et al.          |
| 2008/0004601 A1  | 1/2008  | Jennewine et al.      | 2008/0306434 A1  | 12/2008 | Dobbles et al.        |
| 2008/0009692 A1  | 1/2008  | Stafford              | 2008/0306435 A1  | 12/2008 | Kamath et al.         |
| 2008/0017522 A1  | 1/2008  | Heller et al.         | 2008/0306444 A1  | 12/2008 | Brister et al.        |
| 2008/0021666 A1  | 1/2008  | Goode, Jr. et al.     | 2008/0312841 A1  | 12/2008 | Hayter                |
| 2008/0029391 A1  | 2/2008  | Mao et al.            | 2008/0312842 A1  | 12/2008 | Hayter                |
| 2008/0033254 A1  | 2/2008  | Kamath et al.         | 2008/0312844 A1  | 12/2008 | Hayter et al.         |
| 2008/0039702 A1  | 2/2008  | Hayter et al.         | 2008/0312845 A1  | 12/2008 | Hayter et al.         |
| 2008/0045824 A1  | 2/2008  | Tapsak et al.         | 2008/0314395 A1  | 12/2008 | Kovatchev et al.      |
| 2008/0058625 A1  | 3/2008  | McGarraugh et al.     | 2008/0319279 A1  | 12/2008 | Ramsay et al.         |
| 2008/0064937 A1  | 3/2008  | McGarraugh et al.     | 2009/0005665 A1  | 1/2009  | Hayter et al.         |
| 2008/0066305 A1  | 3/2008  | Wang et al.           | 2009/0005666 A1  | 1/2009  | Shin et al.           |
| 2008/0071156 A1  | 3/2008  | Brister et al.        | 2009/0006034 A1  | 1/2009  | Hayter et al.         |
| 2008/0071157 A1  | 3/2008  | McGarraugh et al.     | 2009/0006061 A1  | 1/2009  | Thukral et al.        |
| 2008/0071158 A1  | 3/2008  | McGarraugh et al.     | 2009/0006133 A1  | 1/2009  | Weinert et al.        |
| 2008/0081977 A1  | 4/2008  | Hayter et al.         | 2009/0012376 A1  | 1/2009  | Agus                  |
| 2008/0083617 A1  | 4/2008  | Simpson et al.        | 2009/0012379 A1  | 1/2009  | Goode et al.          |
| 2008/0086042 A1  | 4/2008  | Brister et al.        | 2009/0018424 A1  | 1/2009  | Kamath et al.         |
| 2008/0086044 A1  | 4/2008  | Brister et al.        | 2009/0018425 A1  | 1/2009  | Ouyang et al.         |
| 2008/0086273 A1  | 4/2008  | Shults et al.         | 2009/0030294 A1  | 1/2009  | Petisce et al.        |
| 2008/0097289 A1  | 4/2008  | Steil et al.          | 2009/0033482 A1  | 2/2009  | Hayter et al.         |
| 2008/0108942 A1  | 5/2008  | Brister et al.        | 2009/0036747 A1  | 2/2009  | Hayter et al.         |
| 2008/0119703 A1  | 5/2008  | Brister et al.        | 2009/0036758 A1  | 2/2009  | Brauker et al.        |
| 2008/0119708 A1* | 5/2008  | Budiman ..... 600/365 | 2009/0036760 A1  | 2/2009  | Hayter                |
| 2008/0139910 A1  | 6/2008  | Mastrototaro et al.   | 2009/0036763 A1  | 2/2009  | Brauker et al.        |
| 2008/0154513 A1  | 6/2008  | Kovatchev et al.      | 2009/0043181 A1  | 2/2009  | Brauker et al.        |
| 2008/0161666 A1  | 7/2008  | Feldman et al.        | 2009/0043182 A1  | 2/2009  | Brauker et al.        |
| 2008/0167543 A1  | 7/2008  | Say et al.            | 2009/0043525 A1  | 2/2009  | Brauker et al.        |
| 2008/0172205 A1  | 7/2008  | Breton et al.         | 2009/0043541 A1  | 2/2009  | Brauker et al.        |
| 2008/0177149 A1  | 7/2008  | Weinert et al.        | 2009/0043542 A1  | 2/2009  | Brauker et al.        |
| 2008/0177165 A1  | 7/2008  | Blomquist et al.      | 2009/0045055 A1  | 2/2009  | Rhodes et al.         |
| 2008/0183060 A1  | 7/2008  | Steil et al.          | 2009/0048503 A1  | 2/2009  | Dalal et al.          |
| 2008/0183061 A1  | 7/2008  | Goode et al.          | 2009/0054745 A1  | 2/2009  | Jennewine et al.      |
| 2008/0183399 A1  | 7/2008  | Goode et al.          | 2009/0054748 A1  | 2/2009  | Feldman et al.        |
| 2008/0188731 A1  | 8/2008  | Brister et al.        | 2009/0055149 A1  | 2/2009  | Hayter et al.         |
| 2008/0188796 A1  | 8/2008  | Steil et al.          | 2009/0062633 A1  | 3/2009  | Brauker et al.        |
| 2008/0189051 A1  | 8/2008  | Goode et al.          | 2009/0062635 A1  | 3/2009  | Brauker et al.        |
| 2008/0194934 A1  | 8/2008  | Ray et al.            | 2009/0062767 A1  | 3/2009  | VanAntwerp et al.     |
| 2008/0194935 A1  | 8/2008  | Brister et al.        | 2009/0063402 A1  | 3/2009  | Hayter                |
| 2008/0194936 A1  | 8/2008  | Goode et al.          | 2009/0069649 A1* | 3/2009  | Budiman ..... 600/309 |
| 2008/0194937 A1  | 8/2008  | Goode et al.          | 2009/0076356 A1  | 3/2009  | Simpson et al.        |
| 2008/0194938 A1  | 8/2008  | Brister et al.        | 2009/0076360 A1  | 3/2009  | Brister et al.        |
| 2008/0195232 A1  | 8/2008  | Carr-Brendel et al.   | 2009/0076361 A1  | 3/2009  | Kamath et al.         |
| 2008/0195967 A1  | 8/2008  | Goode et al.          | 2009/0082693 A1  | 3/2009  | Stafford              |
| 2008/0197024 A1  | 8/2008  | Simpson et al.        | 2009/0085768 A1  | 4/2009  | Patel et al.          |
| 2008/0200788 A1  | 8/2008  | Brister et al.        | 2009/0099436 A1  | 4/2009  | Brister et al.        |
| 2008/0200789 A1  | 8/2008  | Brister et al.        | 2009/0105560 A1  | 4/2009  | Solomon               |
| 2008/0200791 A1  | 8/2008  | Simpson et al.        | 2009/0105570 A1  | 4/2009  | Sloan et al.          |
| 2008/0201325 A1  | 8/2008  | Doniger et al.        | 2009/0105636 A1  | 4/2009  | Hayter et al.         |
| 2008/0208025 A1  | 8/2008  | Shults et al.         | 2009/0112478 A1  | 4/2009  | Mueller, Jr. et al.   |
| 2008/0208113 A1  | 8/2008  | Damiano et al.        | 2009/0118589 A1  | 5/2009  | Ueshima et al.        |
| 2008/0214915 A1  | 9/2008  | Brister et al.        | 2009/0124877 A1  | 5/2009  | Goode, Jr. et al.     |
| 2008/0214918 A1  | 9/2008  | Brister et al.        | 2009/0124878 A1  | 5/2009  | Goode et al.          |
| 2008/0228051 A1  | 9/2008  | Shults et al.         | 2009/0124879 A1  | 5/2009  | Brister et al.        |
| 2008/0228054 A1  | 9/2008  | Shults et al.         | 2009/0124964 A1  | 5/2009  | Leach et al.          |
| 2008/0234943 A1  | 9/2008  | Ray et al.            | 2009/0131768 A1  | 5/2009  | Simpson et al.        |
|                  |         |                       | 2009/0131769 A1  | 5/2009  | Leach et al.          |
|                  |         |                       | 2009/0131776 A1  | 5/2009  | Simpson et al.        |
|                  |         |                       | 2009/0131777 A1  | 5/2009  | Simpson et al.        |
|                  |         |                       | 2009/0137886 A1  | 5/2009  | Shariati et al.       |
|                  |         |                       | 2009/0137887 A1  | 5/2009  | Shariati et al.       |

(56)

References Cited

U.S. PATENT DOCUMENTS

2009/0143659 A1 6/2009 Li et al.  
 2009/0143660 A1 6/2009 Brister et al.  
 2009/0156919 A1 6/2009 Brister et al.  
 2009/0156924 A1 6/2009 Shariati et al.  
 2009/0163790 A1 6/2009 Brister et al.  
 2009/0163791 A1 6/2009 Brister et al.  
 2009/0164190 A1 6/2009 Hayter  
 2009/0164239 A1 6/2009 Hayter et al.  
 2009/0164251 A1 6/2009 Hayter  
 2009/0178459 A1 7/2009 Li et al.  
 2009/0182217 A1 7/2009 Li et al.  
 2009/0192366 A1 7/2009 Mensinger et al.  
 2009/0192380 A1 7/2009 Shariati et al.  
 2009/0192722 A1 7/2009 Shariati et al.  
 2009/0192724 A1 7/2009 Brauker et al.  
 2009/0192745 A1 7/2009 Kamath et al.  
 2009/0192751 A1 7/2009 Kamath et al.  
 2009/0198118 A1 8/2009 Hayter et al.  
 2009/0203981 A1 8/2009 Brauker et al.  
 2009/0204341 A1 8/2009 Brauker et al.  
 2009/0216103 A1 8/2009 Brister et al.  
 2009/0240120 A1 9/2009 Mensinger et al.  
 2009/0240128 A1 9/2009 Mensinger et al.  
 2009/0240193 A1 9/2009 Mensinger et al.  
 2009/0242399 A1 10/2009 Kamath et al.  
 2009/0242425 A1 10/2009 Kamath et al.  
 2009/0247855 A1 10/2009 Boock et al.  
 2009/0247856 A1 10/2009 Boock et al.  
 2009/0247857 A1 10/2009 Harper et al.  
 2009/0253973 A1 10/2009 Bashan et al.  
 2009/0281407 A1\* 11/2009 Budiman ..... 600/365  
 2009/0287073 A1 11/2009 Boock et al.  
 2009/0287074 A1 11/2009 Shults et al.  
 2009/0299155 A1 12/2009 Yang et al.  
 2009/0299156 A1 12/2009 Simpson et al.  
 2009/0299162 A1 12/2009 Brauker et al.  
 2009/0299276 A1 12/2009 Brauker et al.  
 2010/0010324 A1 1/2010 Brauker et al.  
 2010/0010331 A1 1/2010 Brauker et al.  
 2010/0010332 A1 1/2010 Brauker et al.  
 2010/0057040 A1 3/2010 Hayter  
 2010/0057041 A1 3/2010 Hayter  
 2010/0057042 A1 3/2010 Hayter  
 2010/0057044 A1 3/2010 Hayter  
 2010/0057057 A1 3/2010 Hayter et al.  
 2010/0063372 A1 3/2010 Potts et al.  
 2010/0141656 A1 6/2010 Krieffewirth  
 2010/0160759 A1 6/2010 Celentano et al.  
 2010/0168538 A1 7/2010 Keenan et al.  
 2010/0168546 A1 7/2010 Kamath et al.  
 2010/0174266 A1 7/2010 Estes  
 2010/0230285 A1 9/2010 Hoss et al.  
 2010/0280441 A1 11/2010 Willinska et al.  
 2010/0312176 A1 12/2010 Lauer et al.  
 2011/0024043 A1 2/2011 Boock et al.  
 2011/0024307 A1 2/2011 Simpson et al.  
 2011/0027127 A1 2/2011 Simpson et al.  
 2011/0027453 A1 2/2011 Boock et al.  
 2011/0027458 A1 2/2011 Boock et al.  
 2011/0028815 A1 2/2011 Simpson et al.  
 2011/0028816 A1 2/2011 Simpson et al.  
 2011/0077490 A1 3/2011 Simpson et al.  
 2011/0112696 A1 5/2011 Yodfat et al.  
 2011/0148905 A1 6/2011 Simmons et al.  
 2011/0208027 A1 8/2011 Wagner et al.  
 2011/0208155 A1 8/2011 Palerm et al.  
 2011/0257895 A1 10/2011 Brauker et al.  
 2011/0263958 A1 10/2011 Brauker et al.  
 2011/0320130 A1 12/2011 Valdes et al.  
 2012/0078071 A1 3/2012 Bohm et al.  
 2012/0108934 A1 5/2012 Valdes et al.

2012/0165626 A1 6/2012 Irina et al.  
 2012/0165640 A1 6/2012 Galley et al.  
 2012/0173200 A1 7/2012 Breton et al.  
 2012/0215462 A1 8/2012 Goode et al.  
 2013/0035575 A1 2/2013 Mayou et al.

FOREIGN PATENT DOCUMENTS

EP 0098592 1/1984  
 EP 0127958 12/1984  
 EP 0320109 6/1989  
 EP 0353328 2/1990  
 EP 0390390 10/1990  
 EP 0396788 11/1990  
 EP 0472411 2/1992  
 EP 0286118 1/1995  
 EP 0867146 9/1998  
 EP 1048264 11/2000  
 EP 1419731 5/2004  
 EP 0939602 9/2004  
 EP 1850909 4/2010  
 EP 1677668 7/2010  
 JP 2004-358261 12/2004  
 WO WO-96/25089 8/1996  
 WO WO-96/35370 11/1996  
 WO WO-97/15227 5/1997  
 WO WO-98/35053 8/1998  
 WO WO-99/56613 11/1999  
 WO WO-00/49940 8/2000  
 WO WO-00/59370 10/2000  
 WO WO-00/74753 12/2000  
 WO WO-00/78992 12/2000  
 WO WO-01/52935 7/2001  
 WO WO-01/54753 8/2001  
 WO WO-02/16905 2/2002  
 WO WO-02/058537 8/2002  
 WO WO-03/076893 9/2003  
 WO WO-03/082091 10/2003  
 WO WO-03/085372 10/2003  
 WO WO-2004/060455 7/2004  
 WO WO-2004/061420 7/2004  
 WO WO-2005/010756 2/2005  
 WO WO-2005/041766 5/2005  
 WO WO-2005/065542 7/2005  
 WO WO-2005/089103 9/2005  
 WO WO-2006/024671 3/2006  
 WO WO-2006/079114 7/2006  
 WO WO-2006/081336 8/2006  
 WO WO-2006/085087 8/2006  
 WO WO-2006/086423 8/2006  
 WO WO-2006/118947 11/2006  
 WO WO-2006/124099 11/2006  
 WO WO-2007/016399 2/2007  
 WO WO-2007/027788 3/2007  
 WO WO-2007/041069 4/2007  
 WO WO-2007/041070 4/2007  
 WO WO-2007/041072 4/2007  
 WO WO-2007/041248 4/2007  
 WO WO-2007/056638 5/2007  
 WO WO-2007/097754 8/2007  
 WO WO-2007/101223 9/2007  
 WO WO-2007/115094 10/2007  
 WO WO-2007/120363 10/2007  
 WO WO-2007/126444 11/2007  
 WO WO-2007/053832 12/2007  
 WO WO-2007/143225 12/2007  
 WO WO-2008/021913 2/2008  
 WO WO-2008/042760 4/2008  
 WO WO-2008/052057 5/2008  
 WO WO-2008/086541 7/2008  
 WO WO-2008/128210 10/2008  
 WO WO-2008/130896 10/2008  
 WO WO-2008/130897 10/2008  
 WO WO-2008/130898 10/2008  
 WO WO-2008/143943 11/2008  
 WO WO-2009/018058 2/2009  
 WO WO-2009/086216 7/2009

(56)

## References Cited

## FOREIGN PATENT DOCUMENTS

|    |                |        |
|----|----------------|--------|
| WO | WO-2009/096992 | 8/2009 |
| WO | WO-2009/097594 | 8/2009 |

## OTHER PUBLICATIONS

Bennion, N., et al., "Alternate Site Glucose Testing: A Crossover Design", *Diabetes Technology & Therapeutics*, vol. 4, No. 1, 2002, pp. 25-33.

Blendea, M. C., et al., "Heart Disease in Diabetic Patients", *Current Diabetes Reports*, vol. 3, 2003, pp. 223-229.

Brooks, S. L., et al., "Development of an On-Line Glucose Sensor for Fermentation Monitoring", *Biosensors*, vol. 3, 1987/88, pp. 45-56.

Cass, A. E., et al., "Ferrocene-Medicated Enzyme Electrode for Amperometric Determination of Glucose", *Analytical Chemistry*, vol. 56, No. 4, 1984, 667-671.

Csoregi, E., et al., "Design and Optimization of a Selective Subcutaneously Implantable Glucose Electrode Based on 'Wired' Glucose Oxidase", *Analytical Chemistry*, vol. 67, No. 7, 1995, pp. 1240-1244.

Diabetes Control and Complications Trial Research Group, "The Effect of Intensive Treatment of Diabetes on the Development and Progression of Long-Term Complications in Insulin-Dependent Diabetes Mellitus," *New England J. Med.* vol. 329, 1993, pp. 977-986.

Eckert, B. et al. "Hypoglycaemia Leads to an Increased QT Interval in Normal Men," *Clinical Physiology*, vol. 18, No. 6, 1998, pp. 570-575.

Feldman, B., et al., "A Continuous Glucose Sensor Based on Wired Enzyme™ Technology—Results from a 3-Day Trial in Patients with Type 1 Diabetes", *Diabetes Technology & Therapeutics*, vol. 5, No. 5, 2003, pp. 769-779.

Feldman, B., et al., "Correlation of Glucose Concentrations in Interstitial Fluid and Venous Blood During Periods of Rapid Glucose Change", *Abbott Diabetes Care, Inc. Freestyle Navigator Continuous Glucose Monitor Pamphlet*, 2004.

Georgescu, B., et al., "Real-Time Multimodel Tracking of Myocardium in Echocardiography Using Robust Information Fusion", *Medical Image Computing and Computer-Assisted Intervention*, 2004, pp. 777-785.

Goldman, J. M., et al., "Masimo Signal Extraction Pulse Oximetry", *Journal of Clinical Monitoring and Computing*, vol. 16, No. 7, 2000, pp. 475-483.

Harris, N.D., et al., "Can Changes in QT Interval be Used to Predict the Onset of Hypoglycemia in Type 1 Diabetes?", *Computers in Cardiology*, vol. 27, 2000, pp. 375-378.

Heller, S. R., "Abnormalities of the Electrocardiogram During Hypoglycemia: The Cause of the Dead in Bed Syndrome?" *International Journal of Clinical Practice*, Suppl. No. 129, 2002, pp. 27-32.

Isermann, R., "Supervision, Fault-Detection and Fault-Diagnosis Methods—An Introduction", *Control Engineering Practice*, vol. 5, No. 5, 1997, pp. 639-652.

Isermann, R., et al., "Trends in the Application of Model-Based Fault Detection and Diagnosis of Technical Processes", *Control Engineering Practice*, vol. 5, No. 5, 1997, pp. 709-719.

Johnson, P. C., "Peripheral Circulation", *John Wiley & Sons*, 1978, pp. 198.

Jones, T. W., et al., "Mild Hypoglycemia and Impairment of Brain Stem and Cortical Evoked Potentials in Healthy Subjects," *Diabetes* vol. 39, 1990, 1550-1555.

Jungheim, K., et al., "How Rapid Does Glucose Concentration Change in Daily Life of Patients with Type 1 Diabetes?", 2002, pp. 250.

Jungheim, K., et al., "Risky Delay of Hypoglycemia Detection by Glucose Monitoring at the Arm", *Diabetes Care*, vol. 24, No. 7, 2001, pp. 1303-1304.

Kaplan, S. M., "Wiley Electrical and Electronics Engineering Dictionary", *IEEE Press*, 2004, pp. 141, 142, 548, 549.

Landstedt-Hallin, L., et al., "Increased QT Dispersion During Hypoglycaemia in Patients with Type 2 Diabetes Mellitus," *Journal of Internal Medicine*, vol. 246, 1999, 299-307.

Lortz, J., et al., "What is Bluetooth? We Explain the Newest Short-Range Connectivity Technology", *Smart Computing Learning Series, Wireless Computing*, vol. 8, Issue 5, 2002, pp. 72-74.

Maher, "A Method for Extrapolation of Missing Digital Audio Data", *Preprints of Papers Presented at the AES Convention*, 1993, pp. 1-19.

Maher, "Audio Enhancement using Nonlinear Time-Frequency Filtering", *AES 26th International Conference*, 2005, pp. 1-9.

Malin, S. F., et al., "Noninvasive Prediction of Glucose by Near-Infrared Diffuse Reflectance Spectroscopy", *Clinical Chemistry*, vol. 45, No. 9, 1999, pp. 1651-1658.

Malmberg, K., "Prospective Randomised Study of Intensive Insulin Treatment on Long-Term Survival After Acute Myocardial Infarction in Patients with Diabetes Mellitus", *British Medical Journal*, vol. 314, 1997, pp. 1512-1515.

Markel, A. et al, "Hypoglycaemia-Induced Ischaemic ECG Changes", *Presse Medicale*, vol. 23, No. 2, 1994, pp. 78-79.

McGarraugh, G., et al., "Glucose Measurements Using Blood Extracted from the Forearm and the Finger", *TheraSense, Inc.*, 2001, 16 Pages.

McGarraugh, G., et al., "Physiological Influences on Off-Finger Glucose Testing", *Diabetes Technology & Therapeutics*, vol. 3, No. 3, 2001, pp. 367-376.

McKean, B. D., et al., "A Telemetry-Instrumentation System for Chronically Implanted Glucose and Oxygen Sensors", *IEEE Transactions on Biomedical Engineering*, vol. 35, No. 7, 1988, pp. 526-532.

Okin, P. M., et al, "Electrocardiographic Repolarization Complexity and Abnormality Predict All-Cause and Cardiovascular Mortality in Diabetes," *Diabetes*, vol. 53, 2004, pp. 434-440.

Peterson, K., et al., "Regulation of Serum Potassium During Insulin-Induced Hypoglycemia," *Diabetes*, vol. 31, 1982, pp. 615-617.

Pickup, J., et al., "Implantable Glucose Sensors: Choosing the Appropriate Sensing Strategy", *Biosensors*, vol. 3, 1987/88, pp. 335-346.

Pickup, J., et al., "In Vivo Molecular Sensing in Diabetes Mellitus: An Implantable Glucose Sensor with Direct Electron Transfer", *Diabetologia*, vol. 32, 1989, pp. 213-217.

Pishko, M. V., et al., "Amperometric Glucose Microelectrodes Prepared Through Immobilization of Glucose Oxidase in Redox Hydrogels", *Analytical Chemistry*, vol. 63, No. 20, 1991, pp. 2268-2272.

Quinn, C. P., et al., "Kinetics of Glucose Delivery to Subcutaneous Tissue in Rats Measured with 0.3-mm Amperometric Microsensors", *The American Physiological Society*, 1995, E155-E161.

Rana, B. S., et al., "Relation of QT Interval Dispersion to the Number of Different Cardiac Abnormalities in Diabetes Mellitus", *The American Journal of Cardiology*, vol. 90, 2002, pp. 483-487.

Robinson, R. T. C. E., et al. "Changes in Cardiac Repolarization During Clinical Episodes of Nocturnal Hypoglycaemia in Adults with Type 1 Diabetes," *Diabetologia*, vol. 47, 2004, pp. 312-315.

Roe, J. N., et al., "Bloodless Glucose Measurements", *Critical Review in Therapeutic Drug Carrier Systems*, vol. 15, Issue 3, 1998, pp. 199-241.

Sakakida, M., et al., "Development of Ferrocene-Mediated Needle-Type Glucose Sensor as a Measure of True Subcutaneous Tissue Glucose Concentrations", *Artificial Organs Today*, vol. 2, No. 2, 1992, pp. 145-158.

Sakakida, M., et al., "Ferrocene-Mediated Needle-Type Glucose Sensor Covered with Newly Designed Biocompatible Membrane", *Sensors and Actuators B*, vol. 13-14, 1993, pp. 319-322.

Salehi, C., et al., "A Telemetry-Instrumentation System for Long-Term Implantable Glucose and Oxygen Sensors", *Analytical Letters*, vol. 29, No. 13, 1996, pp. 2289-2308.

Schmidtke, D. W., et al., "Measurement and Modeling of the Transient Difference Between Blood and Subcutaneous Glucose Concentrations in the Rat After Injection of Insulin", *Proceedings of the National Academy of Sciences*, vol. 95, 1998, pp. 294-299.

Shaw, G. W., et al., "In Vitro Testing of a Simply Constructed, Highly Stable Glucose Sensor Suitable for Implantation in Diabetic Patients", *Biosensors & Bioelectronics*, vol. 6, 1991, pp. 401-406.

Shichiri, M., et al., "Glycaemic Control in Pancreatectomized Dogs with a Wearable Artificial Endocrine Pancreas", *Diabetologia*, vol. 24, 1983, pp. 179-184.




(56)

## References Cited

## OTHER PUBLICATIONS

- Shichiri, M., et al., "In Vivo Characteristics of Needle-Type Glucose Sensor—Measurements of Subcutaneous Glucose Concentrations in Human Volunteers", *Hormone and Metabolic Research Supplement Series*, vol. 20, 1988, pp. 17-20.
- Shichiri, M., et al., "Membrane Design for Extending the Long-Life of an Implantable Glucose Sensor", *Diabetes Nutrition and Metabolism*, vol. 2, 1989, pp. 309-313.
- Shichiri, M., et al., "Needle-type Glucose Sensor for Wearable Artificial Endocrine Pancreas", *Implantable Sensors for Closed-Loop Prosthetic Systems*, Chapter 15, 1985, pp. 197-210.
- Shichiri, M., et al., "Telemetry Glucose Monitoring Device With Needle-Type Glucose Sensor: A Useful Tool for Blood Glucose Monitoring in Diabetic Individuals", *Diabetes Care*, vol. 9, No. 3, 1986, pp. 298-301.
- Shichiri, M., et al., "Wearable Artificial Endocrine Pancreas With Needle-Type Glucose Sensor", *The Lancet*, 1982, pp. 1129-1131.
- Shults, M. C., et al., "A Telemetry-Instrumentation System for Monitoring Multiple Subcutaneously Implanted Glucose Sensors", *IEEE Transactions on Biomedical Engineering*, vol. 41, No. 10, 1994, pp. 937-942.
- Steinhaus, B. M., et al., "The Information Content of the Cardiac Electrogram at the Stimulus Site," *Annual International Conference of the IEEE Engineering in Medicine and Biology Society*, vol. 12, No. 2, 1990, 0607-0609.
- Sternberg, R., et al., "Study and Development of Multilayer Needle-Type Enzyme-Based Glucose Microsensors", *Biosensors*, vol. 4, 1988, pp. 27-40.
- Thompson, M., et al., "In Vivo Probes: Problems and Perspectives", *Clinical Biochemistry*, vol. 19, 1986, pp. 255-261.
- Turner, A., et al., "Diabetes Mellitus: Biosensors for Research and Management", *Biosensors*, vol. 1, 1985, pp. 85-115.
- Updike, S. J., et al., "Principles of Long-Term Fully Implanted Sensors with Emphasis on Radiotelemetric Monitoring of Blood Glucose from Inside a Subcutaneous Foreign Body Capsule (FBC)", *Biosensors in the Body: Continuous in vivo Monitoring*, Chapter 4, 1997, pp. 117-137.
- Velho, G., et al., "Strategies for Calibrating a Subcutaneous Glucose Sensor", *Biomedica Biochimica Acta*, vol. 48, 1989, pp. 957-964.
- Whipple, G., "Low Residual Noise Speech Enhancement Utilizing Time-Frequency", *Proceedings of the International Conference on Acoustics, Speech, and Signal Processing*, vol. 19, 1994, pp. I5-I8.
- Wilson, G. S., et al., "Progress Toward the Development of an Implantable Sensor for Glucose", *Clinical Chemistry*, vol. 38, No. 9, 1992, pp. 1613-1617.
- Wolfe, P. J., et al., "Interpolation of Missing Data Values for Audio Signal Restoration Using a Gabor Regression Model", *2005 IEEE International Conference on Acoustics, Speech, and Signal Processing*, vol. 5, 2005, pp. 517-520.
- Canadian Patent Application No. 2,667,930, Examiner's Report mailed Mar. 2, 2010.
- Canadian Patent Application No. 2,667,930, Notice of Allowance mailed Oct. 14, 2010.
- European Patent Application No. 07854382.4, Extended European Search Report mailed Dec. 23, 2009.
- PCT Application No. PCT/US2007/082382, International Preliminary Report on Patentability and Written Opinion of the International Searching Authority mailed May 7, 2009.
- PCT Application No. PCT/US2007/082382, International Search Report and Written Opinion of the International Searching Authority mailed Jun. 24, 2008.
- U.S. Appl. No. 11/552,935, Advisory Action mailed Jun. 26, 2009.
- U.S. Appl. No. 11/552,935, Notice of Allowance Aug. 20, 2009.
- U.S. Appl. No. 11/552,935, Office Action mailed Jun. 25, 2008.
- U.S. Appl. No. 11/552,935, Office Action mailed Mar. 17, 2009.
- U.S. Appl. No. 12/238,874, Office Action mailed Aug. 18, 2011.
- U.S. Appl. No. 12/238,874, Office Action mailed Feb. 6, 2012.
- U.S. Appl. No. 12/506,227, Office Action mailed Mar. 19, 2012.
- U.S. Appl. No. 12/506,227, Office Action mailed Oct. 7, 2011.
- U.S. Appl. No. 12/506,227, Notice of Allowance mailed May 15, 2012.
- U.S. Appl. No. 12/238,874, Notice of Allowance mailed May 15, 2012.
- Arnold, M. A., et al., "Selectivity Assessment of Noninvasive Glucose Measurements Based on Analysis of Multivariate Calibration Vectors", *Journal of Diabetes Science and Technology*, vol. 1, No. 4, 2007, pp. 454-462.
- Blank, T. B., et al., "Clinical Results From a Non-Invasive Blood Glucose Monitor", *Optical Diagnostics and Sensing of Biological Fluids and Glucose and Cholesterol Monitoring II, Proceedings of SPIE*, vol. 4624, 2002, pp. 1-10.
- Boyne, M. S., et al., "Timing of Changes in Interstitial and Venous Blood Glucose Measured With a Continuous Subcutaneous Glucose Sensor", *Diabetes*, vol. 52, Nov. 2003, pp. 2790-2794.
- Bremer, T. M., et al., "Benchmark Data from the Literature for Evaluation of New Glucose Sensing Technologies", *Diabetes Technology & Therapeutics*, vol. 3, No. 3, 2001, pp. 409-418.
- Cheyne, E. H., et al., "Performance of a Continuous Glucose Monitoring System During Controlled Hypoglycaemia in Healthy Volunteers", *Diabetes Technology & Therapeutics*, vol. 4, No. 5, 2002, pp. 607-613.
- Choleau, C., et al., "Calibration of a Subcutaneous Amperometric Glucose Sensor Implanted for 7 Days in Diabetic Patients Part 2. Superiority of the One-Point Calibration Method", *Biosensors and Bioelectronics*, vol. 17, No. 8, 2002, pp. 647-654.
- Eren-Oruklu, M., et al., "Estimation of Future Glucose Concentrations with Subject-Specific Recursive Linear Models", *Diabetes Technology & Therapeutics* vol. 11(4), 2009, pp. 243-253.
- Guerci, B., et al., "Clinical Performance of CGMS in Type 1 Diabetic Patients Treated by Continuous Subcutaneous Insulin Infusion Using Insulin Analogs", *Diabetes Care*, vol. 26, 2003, pp. 582-589.
- Kovatchev, B. P., et al., "Evaluating the Accuracy of Continuous Glucose-Monitoring Sensors", *Diabetes Care*, vol. 27, No. 8, 2004, pp. 1922-1928.
- Kuure-Kinsey, M., et al., "A Dual-Rate Kalman Filter for Continuous Glucose Monitoring", *Proceedings of the 28th IEEE, EMBS Annual International Conference*, New York City, 2006, pp. 63-66.
- Lodwig, V., et al., "Continuous Glucose Monitoring with Glucose Sensors: Calibration and Assessment Criteria", *Diabetes Technology & Therapeutics*, vol. 5, No. 4, 2003, pp. 573-587.
- Mougiakakou, et al., "A Real Time Simulation Model of Glucose-Insulin Metabolism for Type 1 Diabetes Patients", *Proceedings of the 2005 IEEE*, 2005, pp. 298-301.
- Panteleon, A. E., et al., "The Role of the Independent Variable to Glucose Sensor Calibration", *Diabetes Technology & Therapeutics*, vol. 5, No. 3, 2003, pp. 401-410.
- Parker, R., et al., "Robust H $\infty$  Glucose Control in Diabetes Using a Physiological Model", *AIChE Journal*, vol. 46, No. 12, 2000, pp. 2537-2549.

\* cited by examiner



**FIGURE 1**




FIGURE 2




FIGURE 3




FIGURE 4




FIGURE 5




FIGURE 6




FIGURE 7




FIGURE 8






FIGURE 9




FIGURE 10

**1****METHOD AND SYSTEM FOR PROVIDING  
ANALYTE MONITORING**

## RELATED APPLICATIONS

The present application is a continuation of U.S. patent application Ser. No. 12/506,227 filed Jul. 20, 2009, now U.S. Pat. No. 8,216,137, which is a continuation of U.S. patent application Ser. No. 11/552,935 filed Oct. 25, 2006, now U.S. Pat. No. 7,630,748, entitled "Method and System for Providing Analyte Monitoring," the disclosures of each of which are incorporated herein by reference for all purposes.

## BACKGROUND

Analyte, e.g., glucose monitoring systems including continuous and discrete monitoring systems generally include a small, lightweight battery powered and microprocessor controlled system which is configured to detect signals proportional to the corresponding measured glucose levels using an electrometer, and RF signals to transmit the collected data. One aspect of certain analyte monitoring systems include a transcutaneous or subcutaneous analyte sensor configuration which is, for example, partially mounted on the skin of a subject whose analyte level is to be monitored. The sensor cell may use a two or three-electrode (work, reference and counter electrodes) configuration driven by a controlled potential (potentiostat) analog circuit connected through a contact system.

The analyte sensor may be configured so that a portion thereof is placed under the skin of the patient so as to detect the analyte levels of the patient, and another segment of the analyte sensor that is in communication with the transmitter unit. The transmitter unit is configured to transmit the analyte levels detected by the sensor over a wireless communication link such as an RF (radio frequency) communication link to a receiver/monitor unit. The receiver/monitor unit performs data analysis, among others on the received analyte levels to generate information pertaining to the monitored analyte levels.

To obtain accurate data from the analyte sensor, calibration using capillary blood glucose measurements is necessary. Typically, blood glucose measurements are obtained using, for example, a blood glucose meter, and the measured blood glucose values are used to calibrate the sensors. Due to a lag factor between the monitored sensor data and the measured blood glucose values, an error, or signal noise such as signal dropouts, is typically introduced in calibration using the monitored data as well as in computing the displayed glucose value. While correcting for the lag factors can minimize the error due to lag in the presence of noise, in the presence of signal dropouts, such error compensation may reduce accuracy of the monitored sensor data.

In view of the foregoing, it would be desirable to have a method and system for providing noise filtering and signal dropout detection and/or compensation in data monitoring systems.

## SUMMARY OF THE INVENTION

In one embodiment, a method for minimizing the effect of noise and signal dropouts in a glucose sensor including monitoring a data stream, generating a noise-filtered signal associated with the data stream, determining a presence of a signal dropout based on the noise filtered signal, and estimating a noise filtered dropout compensated signal based on the noise filtered signal and the determination of the presence of the signal dropout are disclosed.

**2**

These and other objects, features and advantages of the present invention will become more fully apparent from the following detailed description of the embodiments, the appended claims and the accompanying drawings.

## BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates a block diagram of a data monitoring and management system for practicing one or more embodiments of the present invention;

FIG. 2 is a block diagram of the transmitter unit of the data monitoring and management system shown in FIG. 1 in accordance with one embodiment of the present invention;

FIG. 3 is a block diagram of the receiver/monitor unit of the data monitoring and management system shown in FIG. 1 in accordance with one embodiment of the present invention;

FIG. 4 is a functional diagram of the overall signal processing for noise filtering and signal dropout compensation in accordance with one embodiment of the present invention;

FIG. 5 is a flowchart illustrating the overall signal processing for noise filtering and signal dropout compensation in accordance with one embodiment of the present invention;

FIG. 6 is a flowchart illustrating the process input estimation in accordance with one embodiment of the present invention;

FIG. 7 is a flowchart illustrating the noise filtered estimation;

FIG. 8 is a flowchart illustrating signal dropout detection in accordance with one embodiment of the present invention;

FIG. 9 is a flowchart illustrating an overall signal dropout compensation in accordance with one embodiment of the present invention; and

FIG. 10 is flowchart illustrating a detailed signal dropout compensation determination of FIG. 9 in accordance with one embodiment of the present invention.

## DETAILED DESCRIPTION

As described in further detail below, in accordance with the various embodiments of the present invention, there is provided a method and system for providing noise filtered and/or signal dropout mitigated processes for signals in analyte monitoring systems. In particular, within the scope of the present invention, there are provided method and system for noise filtering, signal dropout detection, and signal dropout compensation to improve the accuracy of lag compensation.

FIG. 1 illustrates a data monitoring and management system such as, for example, analyte (e.g., glucose) monitoring system **100** in accordance with one embodiment of the present invention. The subject invention is further described primarily with respect to a glucose monitoring system for convenience and such description is in no way intended to limit the scope of the invention. It is to be understood that the analyte monitoring system may be configured to monitor a variety of analytes, e.g., lactate, and the like.

Analytes that may be monitored include, for example, acetyl choline, amylase, bilirubin, cholesterol, chorionic gonadotropin, creatine kinase (e.g., CK-MB), creatine, DNA, fructosamine, glucose, glutamine, growth hormones, hormones, ketones, lactate, peroxide, prostate-specific antigen, prothrombin, RNA, thyroid stimulating hormone, and tropinin. The concentration of drugs, such as, for example, antibiotics (e.g., gentamicin, vancomycin, and the like), digitoxin, digoxin, drugs of abuse, theophylline, and warfarin, may also be monitored.

The analyte monitoring system **100** includes a sensor **101**, a transmitter unit **102** coupled to the sensor **101**, and a pri-

mary receiver unit **104** which is configured to communicate with the transmitter unit **102** via a communication link **103**. The primary receiver unit **104** may be further configured to transmit data to a data processing terminal **105** for evaluating the data received by the primary receiver unit **104**. Moreover, the data processing terminal in one embodiment may be configured to receive data directly from the transmitter unit **102** via a communication link which may optionally be configured for bi-directional communication.

Also shown in FIG. **1** is a secondary receiver unit **106** which is operatively coupled to the communication link and configured to receive data transmitted from the transmitter unit **102**. Moreover, as shown in the Figure, the secondary receiver unit **106** is configured to communicate with the primary receiver unit **104** as well as the data processing terminal **105**. Indeed, the secondary receiver unit **106** may be configured for bi-directional wireless communication with each of the primary receiver unit **104** and the data processing terminal **105**. As discussed in further detail below, in one embodiment of the present invention, the secondary receiver unit **106** may be configured to include a limited number of functions and features as compared with the primary receiver unit **104**. As such, the secondary receiver unit **106** may be configured substantially in a smaller compact housing or embodied in a device such as a wrist watch, for example. Alternatively, the secondary receiver unit **106** may be configured with the same or substantially similar functionality as the primary receiver unit **104**, and may be configured to be used in conjunction with a docking cradle unit for placement by bedside, for night time monitoring, and/or bi-directional communication device.

Only one sensor **101**, transmitter unit **102**, communication link **103**, and data processing terminal **105** are shown in the embodiment of the analyte monitoring system **100** illustrated in FIG. **1**. However, it will be appreciated by one of ordinary skill in the art that the analyte monitoring system **100** may include one or more sensor **101**, transmitter unit **102**, communication link **103**, and data processing terminal **105**. Moreover, within the scope of the present invention, the analyte monitoring system **100** may be a continuous monitoring system, or semi-continuous, or a discrete monitoring system. In a multi-component environment, each device is configured to be uniquely identified by each of the other devices in the system so that communication conflict is readily resolved between the various components within the analyte monitoring system **100**.

In one embodiment of the present invention, the sensor **101** is physically positioned in or on the body of a user whose analyte level is being monitored. The sensor **101** may be configured to continuously sample the analyte level of the user and convert the sampled analyte level into a corresponding data signal for transmission by the transmitter unit **102**. In one embodiment, the transmitter unit **102** is mounted on the sensor **101** so that both devices are positioned on the user's body. The transmitter unit **102** performs data processing such as filtering and encoding on data signals, each of which corresponds to a sampled analyte level of the user, for transmission to the primary receiver unit **104** via the communication link **103**.

In one embodiment, the analyte monitoring system **100** is configured as a one-way RF communication path from the transmitter unit **102** to the primary receiver unit **104**. In such embodiment, the transmitter unit **102** transmits the sampled data signals received from the sensor **101** without acknowledgement from the primary receiver unit **104** that the transmitted sampled data signals have been received. For example, the transmitter unit **102** may be configured to transmit the

encoded sampled data signals at a fixed rate (e.g., at one minute intervals) after the completion of the initial power on procedure. Likewise, the primary receiver unit **104** may be configured to detect such transmitted encoded sampled data signals at predetermined time intervals. Alternatively, the analyte monitoring system **100** may be configured with a bi-directional RF (or otherwise) communication between the transmitter unit **102** and the primary receiver unit **104**.

Additionally, in one aspect, the primary receiver unit **104** may include two sections. The first section is an analog interface section that is configured to communicate with the transmitter unit **102** via the communication link **103**. In one embodiment, the analog interface section may include an RF receiver and an antenna for receiving and amplifying the data signals from the transmitter unit **102**, which are thereafter, demodulated with a local oscillator and filtered through a band-pass filter. The second section of the primary receiver unit **104** is a data processing section which is configured to process the data signals received from the transmitter unit **102** such as by performing data decoding, error detection and correction, data clock generation, and data bit recovery.

In operation, upon completing the power-on procedure, the primary receiver unit **104** is configured to detect the presence of the transmitter unit **102** within its range based on, for example, the strength of the detected data signals received from the transmitter unit **102** or a predetermined transmitter identification information. Upon successful synchronization with the corresponding transmitter unit **102**, the primary receiver unit **104** is configured to begin receiving from the transmitter unit **102** data signals corresponding to the user's detected analyte level. More specifically, the primary receiver unit **104** in one embodiment is configured to perform synchronized time hopping with the corresponding synchronized transmitter unit **102** via the communication link **103** to obtain the user's detected analyte level.

Referring again to FIG. **1**, the data processing terminal **105** may include a personal computer, a portable computer such as a laptop or a handheld device (e.g., personal digital assistants (PDAs)), and the like, each of which may be configured for data communication with the receiver via a wired or a wireless connection. Additionally, the data processing terminal **105** may further be connected to a data network (not shown) for storing, retrieving and updating data corresponding to the detected analyte level of the user.

Within the scope of the present invention, the data processing terminal **105** may include an infusion device such as an insulin infusion pump or the like, which may be configured to administer insulin to patients, and which may be configured to communicate with the receiver unit **104** for receiving, among others, the measured analyte level. Alternatively, the receiver unit **104** may be configured to integrate an infusion device therein so that the receiver unit **104** is configured to administer insulin therapy to patients, for example, for administering and modifying basal profiles, as well as for determining appropriate boluses for administration based on, among others, the detected analyte levels received from the transmitter unit **102**.

Additionally, the transmitter unit **102**, the primary receiver unit **104** and the data processing terminal **105** may each be configured for bi-directional wireless communication such that each of the transmitter unit **102**, the primary receiver unit **104** and the data processing terminal **105** may be configured to communicate (that is, transmit data to and receive data from) with each other via the wireless communication link **103**. More specifically, the data processing terminal **105** may in one embodiment be configured to receive data directly from the transmitter unit **102** via the communication link,

where the communication link, as described above, may be configured for bi-directional communication.

In this embodiment, the data processing terminal **105** which may include an insulin pump, may be configured to receive the analyte signals from the transmitter unit **102**, and thus, incorporate the functions of the receiver **104** including data processing for managing the patient's insulin therapy and analyte monitoring. In one embodiment, the communication link **103** may include one or more of an RF communication protocol, an infrared communication protocol, a Bluetooth® enabled communication protocol, an 802.11x wireless communication protocol, or an equivalent wireless communication protocol which would allow secure, wireless communication of several units (for example, per HIPAA requirements) while avoiding potential data collision and interference.

FIG. 2 is a block diagram of the transmitter of the data monitoring and detection system shown in FIG. 1 in accordance with one embodiment of the present invention.

Referring to the Figure, the transmitter unit **102** in one embodiment includes an analog interface **201** configured to communicate with the sensor **101** (FIG. 1), a user input **202**, and a temperature detection section **203**, each of which is operatively coupled to a transmitter processor **204** such as a central processing unit (CPU). As can be seen from FIG. 2, there are provided four contacts, three of which are electrodes—work electrode (W), guard contact (G), reference electrode (R), and counter electrode (C), each operatively coupled to the analog interface **201** of the transmitter unit **102** for connection to the sensor **101** (FIG. 1). In one embodiment, each of the work electrode (W), guard contact (G), reference electrode (R), and counter electrode (C) may be made using a conductive material that is either printed or etched, for example, such as carbon which may be printed, or metal foil (e.g., gold) which may be etched.

Further shown in FIG. 2 are a transmitter serial communication section **205** and an RF transmitter **206**, each of which is also operatively coupled to the transmitter processor **204**. Moreover, a power supply **207** such as a battery is also provided in the transmitter unit **102** to provide the necessary power for the transmitter unit **102**. Additionally, as can be seen from the Figure, clock **208** is provided to, among others, supply real time information to the transmitter processor **204**.

In one embodiment, a unidirectional input path is established from the sensor **101** (FIG. 1) and/or manufacturing and testing equipment to the analog interface **201** of the transmitter unit **102**, while a unidirectional output is established from the output of the RF transmitter **206** of the transmitter unit **102** for transmission to the primary receiver unit **104**. In this manner, a data path is shown in FIG. 2 between the aforementioned unidirectional input and output via a dedicated link **209** from the analog interface **201** to serial communication section **205**, thereafter to the processor **204**, and then to the RF transmitter **206**. As such, in one embodiment, via the data path described above, the transmitter unit **102** is configured to transmit to the primary receiver unit **104** (FIG. 1), via the communication link **103** (FIG. 1), processed and encoded data signals received from the sensor **101** (FIG. 1). Additionally, the unidirectional communication data path between the analog interface **201** and the RF transmitter **206** discussed above allows for the configuration of the transmitter unit **102** for operation upon completion of the manufacturing process as well as for direct communication for diagnostic and testing purposes.

As discussed above, the transmitter processor **204** is configured to transmit control signals to the various sections of the transmitter unit **102** during the operation of the transmitter

unit **102**. In one embodiment, the transmitter processor **204** also includes a memory (not shown) for storing data such as the identification information for the transmitter unit **102**, as well as the data signals received from the sensor **101**. The stored information may be retrieved and processed for transmission to the primary receiver unit **104** under the control of the transmitter processor **204**. Furthermore, the power supply **207** may include a commercially available battery.

The transmitter unit **102** is also configured such that the power supply section **207** is capable of providing power to the transmitter for a minimum of about three months of continuous operation after having been stored for about eighteen months in a low-power (non-operating) mode. In one embodiment, this may be achieved by the transmitter processor **204** operating in low power modes in the non-operating state, for example, drawing no more than approximately 1  $\mu$ A of current. Indeed, in one embodiment, the final step during the manufacturing process of the transmitter unit **102** may place the transmitter unit **102** in the lower power, non-operating state (i.e., post-manufacture sleep mode). In this manner, the shelf life of the transmitter unit **102** may be significantly improved. Moreover, as shown in FIG. 2, while the power supply unit **207** is shown as coupled to the processor **204**, and as such, the processor **204** is configured to provide control of the power supply unit **207**, it should be noted that within the scope of the present invention, the power supply unit **207** is configured to provide the necessary power to each of the components of the transmitter unit **102** shown in FIG. 2.

Referring back to FIG. 2, the power supply section **207** of the transmitter unit **102** in one embodiment may include a rechargeable battery unit that may be recharged by a separate power supply recharging unit (for example, provided in the receiver unit **104**) so that the transmitter unit **102** may be powered for a longer period of usage time. Moreover, in one embodiment, the transmitter unit **102** may be configured without a battery in the power supply section **207**, in which case the transmitter unit **102** may be configured to receive power from an external power supply source (for example, a battery) as discussed in further detail below.

Referring yet again to FIG. 2, the temperature detection section **203** of the transmitter unit **102** is configured to monitor the temperature of the skin near the sensor insertion site. The temperature reading is used to adjust the analyte readings obtained from the analog interface **201**. The RF transmitter **206** of the transmitter unit **102** may be configured for operation in the frequency band of 315 MHz to 322 MHz, for example, in the United States. Further, in one embodiment, the RF transmitter **206** is configured to modulate the carrier frequency by performing Frequency Shift Keying and Manchester encoding. In one embodiment, the data transmission rate is 19,200 symbols per second, with a minimum transmission range for communication with the primary receiver unit **104**.

Referring yet again to FIG. 2, also shown is a leak detection circuit **214** coupled to the guard contact (G) and the processor **204** in the transmitter unit **102** of the data monitoring and management system **100**. The leak detection circuit **214** in accordance with one embodiment of the present invention may be configured to detect leakage current in the sensor **101** to determine whether the measured sensor data are corrupt or whether the measured data from the sensor **101** is accurate.

Additional detailed description of the continuous analyte monitoring system, its various components including the functional descriptions of the transmitter are provided in U.S. Pat. No. 6,175,752 issued Jan. 16, 2001 entitled "Analyte Monitoring Device and Methods of Use", and in application

Ser. No. 10/745,878 filed Dec. 26, 2003, now U.S. Pat. No. 7,811,231, entitled "Continuous Glucose Monitoring System and Methods of Use", each assigned to the Assignee of the present application.

FIG. 3 is a block diagram of the receiver/monitor unit of the data monitoring and management system shown in FIG. 1 in accordance with one embodiment of the present invention. Referring to FIG. 3, the primary receiver unit 104 includes a blood glucose test strip interface 301, an RF receiver 302, an input 303, a temperature detection section 304, and a clock 305, each of which is operatively coupled to a receiver processor 307. As can be further seen from the Figure, the primary receiver unit 104 also includes a power supply 306 operatively coupled to a power conversion and monitoring section 308. Further, the power conversion and monitoring section 308 is also coupled to the receiver processor 307. Moreover, also shown are a receiver serial communication section 309, and an output 310, each operatively coupled to the receiver processor 307.

In one embodiment, the test strip interface 301 includes a glucose level testing portion to receive a manual insertion of a glucose test strip, and thereby determine and display the glucose level of the test strip on the output 310 of the primary receiver unit 104. This manual testing of glucose can be used to calibrate sensor 101. The RF receiver 302 is configured to communicate, via the communication link 103 (FIG. 1) with the RF transmitter 206 of the transmitter unit 102, to receive encoded data signals from the transmitter unit 102 for, among others, signal mixing, demodulation, and other data processing. The input 303 of the primary receiver unit 104 is configured to allow the user to enter information into the primary receiver unit 104 as needed. In one aspect, the input 303 may include one or more keys of a keypad, a touch-sensitive screen, or a voice-activated input command unit. The temperature detection section 304 is configured to provide temperature information of the primary receiver unit 104 to the receiver processor 307, while the clock 305 provides, among others, real time information to the receiver processor 307.

Each of the various components of the primary receiver unit 104 shown in FIG. 3 is powered by the power supply 306 which, in one embodiment, includes a battery. Furthermore, the power conversion and monitoring section 308 is configured to monitor the power usage by the various components in the primary receiver unit 104 for effective power management and to alert the user, for example, in the event of power usage which renders the primary receiver unit 104 in sub-optimal operating conditions. An example of such sub-optimal operating condition may include, for example, operating the vibration output mode (as discussed below) for a period of time thus substantially draining the power supply 306 while the processor 307 (thus, the primary receiver unit 104) is turned on. Moreover, the power conversion and monitoring section 308 may additionally be configured to include a reverse polarity protection circuit such as a field effect transistor (FET) configured as a battery activated switch.

The serial communication section 309 in the primary receiver unit 104 is configured to provide a bi-directional communication path from the testing and/or manufacturing equipment for, among others, initialization, testing, and configuration of the primary receiver unit 104. Serial communication section 309 can also be used to upload data to a computer, such as time-stamped blood glucose data. The communication link with an external device (not shown) can be made, for example, by cable, infrared (IR) or RF link. The output 310 of the primary receiver unit 104 is configured to provide, among others, a graphical user interface (GUI) such as a liquid crystal display (LCD) for displaying information.

Additionally, the output 310 may also include an integrated speaker for outputting audible signals as well as to provide vibration output as commonly found in handheld electronic devices, such as mobile telephones presently available. In a further embodiment, the primary receiver unit 104 also includes an electro-luminescent lamp configured to provide backlighting to the output 310 for output visual display in dark ambient surroundings.

Referring back to FIG. 3, the primary receiver unit 104 in one embodiment may also include a storage section such as a programmable, non-volatile memory device as part of the processor 307, or provided separately in the primary receiver unit 104, operatively coupled to the processor 307. The processor 307 is further configured to perform Manchester decoding as well as error detection and correction upon the encoded data signals received from the transmitter unit 102 via the communication link 103.

FIG. 4 is a functional diagram of the overall signal processing for noise filtering and signal dropout compensation, while FIG. 5 shows a flowchart illustrating the overall signal processing for noise filtering and signal dropout compensation in accordance with one embodiment of the present invention. Referring to the Figures, in one embodiment, signals measured are received from, for example, the analyte sensor 101 (FIG. 1) and are provided to the state observer 410 which in one embodiment may be configured to provide prior or past noise filtered estimate to a process input estimator 420.

In one embodiment, the process input estimator 420 may be configured to generate a process input estimate based on the prior or past noise filtered estimate of the received or measured signal (510), which is then provided to the state observer 410. In one aspect, and as described in further detail below in conjunction with FIG. 6, the process input estimate at a predetermined time  $t$  may be based on past noise filtered estimate of the signal.

Thereafter, in one embodiment, the state observer 410 may be configured to generate a noise filtered estimate of the measured or received signal based on the current measured or received signal and the process input estimate (520) received from the process input estimator 420. In one embodiment and as described in further detail below in conjunction with FIG. 7, using the real time process input and sensor measurement signals, a noise filtered estimate of the signal at the latest time  $t$  may be determined.

In one aspect, this routine of generating the process input estimate based on the past noise filtered estimate of the received or measured signal, and generating the noise filtered estimate of the signal based on the current received or measured signal and the current determined or generated process input estimate may be repeated for each measurement signal received, for example, from the analyte sensor 101 (FIG. 1). In this manner, in one aspect, the noise filtered signals corresponding to the measured or received sensor signals may be determined.

Referring back to FIGS. 4 and 5, in one embodiment, with the noise filtered estimate, the presence of signal dropouts are detected based on, for example, the current and past noise filtered estimate of the received or measured signal (530). More specifically, in one embodiment, a dropout detector 430 may be configured to detect signal dropouts, and thereafter, detection of signal dropouts are provided to dropout compensator 440. In one aspect, the dropout detector 430 may be configured to generate a signal or notification associated with the detection of a signal dropout (as shown in FIG. 4). That is, in one embodiment and as described in further detail below in conjunction with FIG. 8, the dropout detector 430 may be

configured to detect or estimate the presence or absence of signal dropouts at the predetermined time.

In one embodiment, the dropout compensator **440** may be configured to generate an estimate of the noise filtered, dropout compensated signal (**540**) when the signal dropout is detected (for example, by the dropout detector **430**), by subtracting the estimate of the current dropout signal source from the present noise filtered estimate of the signal. In this manner, and as described in further detail below in conjunction with FIGS. 9-10, in one embodiment of the present invention, the noise filtered signal dropout mitigated or compensated signal may be generated to improve accuracy of the measured or received signal from, for example, the analyte sensor **101** (FIG. 1).

FIG. 6 is a flowchart illustrating the process input estimation in accordance with one embodiment of the present invention. Referring to FIG. 6, a mean component of the process input estimate  $u_m(t)$  based on past noise filtered estimate of the signal is generated (**610**). For example, in one embodiment, a series of five past noise-filtered estimate of the signal,  $x_i(t-5)$ ,  $x_i(t-4)$ ,  $x_i(t-3)$ ,  $x_i(t-2)$ ,  $x_i(t-1)$ , the mean component of the process input estimate at time  $t$ ,  $u_m(t)$  may be determined by taking the unweighted average of these signals as shown by the following relationship:

$$u_m(t) = \frac{x_i(t-5) + x_i(t-4) + x_i(t-3) + x_i(t-2) + x_i(t-1)}{5} \quad (1)$$

Alternatively, the mean component of the process input estimate at time  $t$  may be determined by taking the weighted average of these signals as shown by the following relationship:

$$u_m(t) = \frac{a_5 x_i(t-5) + a_4 x_i(t-4) + a_3 x_i(t-3) + a_2 x_i(t-2) + a_1 x_i(t-1)}{a_5 + a_4 + a_3 + a_2 + a_1} \quad (2)$$

where the determination of the constants  $a_1$ ,  $a_2$ ,  $a_3$ ,  $a_4$ ,  $a_5$ , may be obtained based on empirical or analytical analysis of the analyte monitoring system.

In yet another embodiment, the mean component of the process input estimate at time  $t$  based on recent past data may be determined using filtering techniques, such as, but not limited to FIR filters.

Referring to FIG. 6, with the mean component of the process input estimate  $u_m(t)$  based on past noise filtered estimate of the signal determined, the difference component of the process input estimate at any time  $t$ ,  $u_d(t)$ , may be generated (**620**) by, for example, taking an averaged difference of a series of noise-filtered estimate of the signal from the recent past. In one aspect, an unweighted average of the last three past differences may be used in the following manner:

$$u_d(t) = \frac{(x_i(t-4) - x_i(t-3)) + (x_i(t-3) - x_i(t-2)) + (x_i(t-2) - x_i(t-1))}{3} \quad (3)$$

Within the scope of the present invention, other approaches such as the use of FIR filter to determine the proper number of recent past values of  $x_i$  as well as the weighting of each difference may be used.

Referring again to FIG. 6, after determining the difference component of the process input estimate at any time  $t$ ,  $u_d(t)$ , the difference gain at any time  $t$ ,  $K_d(t)$ , is determined (**630**), for example, by using past noise-filtered estimate of the signal,  $x_i$ , and/or the derived signals from  $x_i$ . For example, in one embodiment, a band-limited rate  $X_{i\_bandRate}$  and a band-limited acceleration  $x_{i\_bandAcc}$  may be determined at any time  $t$ , based solely on recent past values of  $x_i$ . Using the knowledge of how the amount of  $u_d$  would contribute to the total process input  $u$  at any time  $t$  relates to these two variables  $X_{i\_bandRate}$  and  $X_{i\_bandAcc}$ , a functional relationship may be determined to ascertain the value of the difference gain  $K_d$  at any time  $t$ .

Alternatively, a lookup table can be constructed that determines the value of the difference gain  $K_d$  given the values of  $X_{i\_bandRate}$  and  $X_{i\_bandAcc}$  as shown below:

$$K_d = \begin{cases} 2 & \text{if } (X_{i\_bandRate} > 0) \ \& \ (x_{i\_bandAcc} > 0) \\ 1 & \text{if } (x_{i\_bandRate} > 0) \ \& \ (x_{i\_bandAcc} \leq 0) \\ 1 & \text{if } (x_{i\_bandRate} \leq 0) \ \& \ (x_{i\_bandAcc} \leq 0) \\ 0.5 & \text{if } (x_{i\_bandRate} \leq 0) \ \& \ (x_{i\_bandAcc} > 0) \end{cases} \quad (4)$$

In one aspect, the difference gain  $K_d$  may be used to scale the contribution of the difference component of the process input estimate  $u_d$  in the value of the process input estimate at a given time. For example, a relatively larger value of the difference gain  $K_d$  may indicate a larger contribution of the difference component of the process input estimate  $u_d$  in the value of the process input estimate at the particular time, and so on. In this manner, in one aspect, the lookup table may show the relationship between factors such as the band-limited rate  $X_{i\_bandRate}$  and the band-limited acceleration  $x_{i\_bandAcc}$  upon how much the difference component of the process input estimate  $u_d$  should contribute to the process input estimate value.

Referring again to FIG. 6, with the mean component of the process input estimate  $u_m(t)$ , the difference component of the process input estimate at any time  $t$ ,  $u_d(t)$ , and the difference gain at any time  $t$ ,  $K_d(t)$ , the scaled difference component  $u_{ds}(t)$  of the process input estimate may be determined (**640**) by multiplying the difference component of the process input estimate at any time  $t$ ,  $u_d(t)$  by the difference gain at any time  $t$ ,  $K_d(t)$ . Thereafter, the scaled difference component  $u_{ds}(t)$  of the process input estimate may be added to the mean component of the process input estimate  $u_m(t)$  to determine the current process input estimate value  $u(t)$  (**650**).

FIG. 7 is a flowchart illustrating the noise filtered estimation. Referring to FIG. 7, with an estimate of process input signal at any time  $t$ ,  $u(t)$ , and based on the measured signals from the analyte sensor  $z(t)$ , in addition to past estimates of the noise-filtered signal  $x_i(t-1)$ ,  $x_i(t-2)$ , ..., the state observer **410** (FIG. 4) may be configured to determine the estimate of noise-filtered signal at any time  $t$ ,  $x_i(t)$ . In one aspect, the state observer **410** (FIG. 4) may be configured to reduce the contribution of noise without introducing excessive undesirable distortion based on the estimate of process input signal at any time  $t$ ,  $u(t)$ , and the measured signals from the sensor  $z(t)$ .

FIG. 8 is a flowchart illustrating signal dropout detection in accordance with one embodiment of the present invention. Referring to FIG. 8, a present "fast rate" estimate  $x_{df}(t)$  is determined based on present and past noise-filtered estimate of the signal (**810**). For example, a difference signal  $x_d(t)$  may be determined based on the following expression:

$$x_d(t) = x_i(t) - x_i(t-1) \quad (5)$$

## 11

Thereafter, a fast rate may be extracted from the difference signal  $x_d(t)$  by performing high pass filtering on the difference signal  $x_d(t)$ . In one embodiment, a discrete-time realization of a first order high pass filter function may be used to determine the present “fast rate” estimate  $x_{df}(t)$ :

$$x_{df}(t) = a_{hpfd}x_d(t-1) + x_d(t) - x_d(t-1) \quad (6)$$

where the value of  $a_{hpfd}$ , or the structure of the high pass filter may be determined in accordance with the suitable design configurations, for example, a value between zero and one.

Referring back to FIG. 8, after determining the “fast rate” estimate  $x_{df}(t)$ , a present “slow rate” estimate  $x_{ds}(t)$  is determined based on present and past noise-filtered estimate of the signal (820). For example, in one embodiment, the slow rate estimate  $x_{ds}(t)$  may be determined by passing the simple difference through a low-pass filter, or alternatively, by taking the difference between the simple difference and the fast difference signals as shown, for example, by the following expression:

$$x_{ds}(t) = x_d(t) - x_{df}(t) \quad (7)$$

After determining the slow rate estimate  $x_{ds}(t)$ , it is determined whether there is a beginning of a large negative spike in the fast rate estimate  $x_{df}(t)$  (830). That is, referring to FIG. 8, the start of a signal dropout state is determined which is correlated to a spike in the fast difference. The fast difference does not generate a spike larger than a predetermined value in response to signals generated in the absence of dropouts. For example, adjusted to the units of glucose concentration, this may correspond to a fast rate in excess of  $-3$  mg/(dL min). Although a rate of  $-3$  mg/(dL min) or faster may be ascertained, when band pass filtered, the fast rate estimate  $x_{df}(t)$  determined above does not occur in this range unless a signal dropout occurs.

Referring back to FIG. 8, if the beginning of a large negative spike in the fast rate estimate  $x_{df}(t)$  is detected, then the elapsed time period from the initial occurrence of the large negative spike is monitored (840), for example, by triggering a timer or a counter so as to monitor the elapsed time since the most recent signal dropout occurrence predicted estimate. In this manner, a safety check mechanism may be provided to determine situations where a signal dropout that was anticipated to have started has lasted in an undesirably long period of dropout time period. That is, as the signal dropouts are generally intermittent in nature, it is expected that the dropout does not last beyond the order of one hour, for example, and more commonly, in the order of five to 30 minutes.

Thereafter, it is determined whether a predetermined allowable time period has elapsed (850). As shown in FIG. 8, if it is determined the allowable time period has not elapsed, then the beginning or onset of the signal dropout is expected. On the other hand, if the predetermined allowable time period has elapsed, then the end of the signal dropout is expected. Referring again to FIG. 8, when the beginning of a large negative spike in the fast rate estimate  $x_{df}(t)$  is not detected, it is determined whether an end of a large positive spike (for example, in the order of  $+3$  mg/(dL min)) in the fast rate estimate  $x_{df}(t)$  is detected (860). If the end of the large positive spike in the fast rate estimate  $x_{df}(t)$  is detected, then the end of the signal dropout is expected. On the other hand, if the end of the large positive spike in the fast rate estimate  $x_{df}(t)$  is not detected, then no signal dropout is expected.

That is, a signal dropout is generally correlated to a large positive spike in the fast difference. Thus, in this case, the tail of the large positive spike is monitored and detected as the end

## 12

of the signal dropout. In one embodiment, this maximizes the likelihood of detecting most of the instances within a signal dropout.

In this manner, in one embodiment of the present invention, the presence of signal dropout may be monitored and detected based on, for example, present and past noise filtered estimate of the signals.

FIG. 9 is a flowchart illustrating an overall signal dropout compensation in accordance with one embodiment of the present invention. Referring to FIG. 9, a momentum-based estimate is determined based on the present slow difference and previous momentum-based estimate (910). That is, with the present and past noise filtered estimate of the signal, the present and past slow and fast rate estimates determined as described above, and with the signal dropout detection estimation determined above, the momentum-based estimate is determined based on the present slow difference and previous momentum-based estimate. That is, in one embodiment, a momentum-based estimate may factor in a signal without dropouts as being likely to project (e.g., extrapolate) based on its past signal and its prior trend.

Referring back to FIG. 9, after determining the momentum based estimate using the present slow difference and prior momentum-based estimate, an averaged value of the present or current momentum-based estimate and the present noise filtered estimate is determined (920). Thereafter, an inertial gain based on the present and past slow rate estimate is determined (930), and which may be configured to scale the contribution of the momentum-based estimate determined using the present slow different and the previous momentum based estimate above in the final dropout compensated gain. Referring again to FIG. 9, after determining the inertial gain, a tracking gain is determined based on the inertial gain (940). In one embodiment, the determined tracking gain may be configured to scale the impact of the determined average value of the present momentum-based estimate and the present noise-filtered estimate, in the determination of the final dropout compensated signal (950) as discussed below.

Referring to FIG. 9, after determining the tracking gain, the dropout compensated signal is determined (950). In one embodiment, the dropout-compensated signal equals the noise-filtered estimate of the signal  $x_i$ , when no dropout is estimated. Otherwise, the dropout compensated signal may be a weighted average of the momentum-based estimate ( $x_{momentum}$ ) as discussed above and the averaged momentum and noise-filtered estimate ( $x_{average}$ ) also discussed above. In one aspect, the weighing factors for the weighted average of the momentum-based estimate ( $x_{momentum}$ ) and the averaged momentum and noise-filtered estimate ( $x_{average}$ ) may be the inertial gain  $K_{inertial}$  and tracking gain  $K_{tracking}$ , respectively. For example, the dropout compensated signal at any time  $t$ ,  $x'_{dci}(t)$  in one embodiment may be determined in accordance with the following relationship:

$$x'_{dci}(t) = (K_{inertial}(t)x_{momentum}(t) + (K_{tracking}(t)x_{average}(t))) \quad (8)$$

In a further embodiment, the determination of the dropout compensated signal at any time  $t$ ,  $x'_{dci}(t)$  may be refined to ensure a smooth transition depending upon the underlying conditions, as described in further detail below in conjunction with FIG. 10.

Referring back to FIG. 9, after determining the dropout compensated signal, the dropout compensated signal may be clipped to be within a predetermined range (960), for example, such that the dropout compensated signal is not less than the noise-filtered signal, and further, that it is not greater than a specified safety ratio times the noise-filtered signal.



## 13

In certain cases, the resulting value of the dropout compensated signal  $x'_{dci}(t)$  may fall below the noise-filtered estimate  $x_i(t)$ . Since by definition, a dropout is a phenomena that can only reduce the true value of a signal, the relationship (8) above for determining the dropout compensated signal may be modified by ensuring that its value never goes below  $x_i(t)$  at any given time, and as shown by the following expression:

$$x_{dci}(t) = \begin{cases} x'_{dci}(t) & \text{for } x'_{dci}(t) \geq x_i(t) \\ x_i(t) & \text{for } x'_{dci}(t) < x_i(t) \end{cases} \quad (9)$$

FIG. 10 is flowchart illustrating a detailed signal dropout compensation determination of FIG. 9 in accordance with one embodiment of the present invention. Referring to FIG. 10, for example, in determining the drop-compensated signal, it is first determined whether signal dropout is detected. If signal dropout is not detected, then it is determined whether a preset time period has elapsed since the end of the last dropout occurrence. If it is determined that a preset time period has elapsed, then the dropout compensated signal may be based upon the present noise filtered signal. In one aspect, the preset time period may be a predetermined time period that may be considered a long period of time. On the other hand, if it is determined that the preset time period has not elapsed (that is, the end of the occurrence of a signal dropout has recently occurred), then the dropout compensated signal may be based upon a smooth transition using the previous dropout compensated signal and the present noise filtered signal.

Indeed, referring to FIG. 10, it can be seen that depending upon the determination of the timing of the signal dropout occurrence, in particular embodiments, the dropout compensated signal may be determined based on one or more factors as shown in the Figure and also described above.

Referring again to the Figures, in particular embodiments, the processings associated with the noise filtering, signal dropout detection estimation and compensation may be performed by one or more processing units of the one or more receiver unit (104, 106), the transmitter unit 102 or the data processing terminal/infusion section 105. In addition, the one or more of the transmitter unit 102, the primary receiver unit 104, secondary receiver unit 106, or the data processing terminal/infusion section 105 may also incorporate a blood glucose meter functionality, such that, the housing of the respective one or more of the transmitter unit 102, the primary receiver unit 104, secondary receiver unit 106, or the data processing terminal/infusion section 105 may include a test strip port configured to receive a blood sample for determining one or more blood glucose levels of the patient.

In a further embodiment, the one or more of the transmitter unit 102, the primary receiver unit 104, secondary receiver unit 106, or the data processing terminal/infusion section 105 may be configured to receive the blood glucose value wirelessly over a communication link from, for example, a glucose meter. In still a further embodiment, the user or patient manipulating or using the analyte monitoring system 100 (FIG. 1) may manually input the blood glucose value using, for example, a user interface (for example, a keyboard, keypad, and the like) incorporated in the one or more of the transmitter unit 102, the primary receiver unit 104, secondary receiver unit 106, or the data processing terminal/infusion section 105.

A method in one embodiment includes monitoring a data stream, generating a noise-filtered signal associated with the data stream, detecting a presence of a signal dropout based on the noise filtered signal, and estimating a noise filtered drop-

## 14

out compensated signal based on the noise filtered signal and the determination of the presence of the signal dropout.

In one aspect, generating the noise filtered signal may include generating one or more frequency-shaped signals based on the monitored data stream, and further, which may include high pass filtering the monitored data stream.

Also, generating the noise filtered signal in another aspect may be based on one or more previous noise filtered signals.

The method in a further embodiment may include outputting the noise filtered signal. The method in still another aspect may include outputting the noise filtered dropout compensated signal.

The method may also include generating a signal associated with detecting the presence of a signal dropout.

Moreover, the data stream in one embodiment may be associated with a monitored analyte level of a patient.

An apparatus in another embodiment includes one or more processors, and a memory for storing instructions which, when executed by the one or more processors, causes the one or more processors to monitor a data stream, generate a noise-filtered signal associated with the data stream, detect a presence of a signal dropout based on the noise filtered signal, and estimate a noise filtered dropout compensated signal based on the noise filtered signal and the determination of the presence of the signal dropout.

The memory may be further configured for storing instructions which, when executed by the one or more processors, causes the one or more processors to generate one or more frequency-shaped signals based on the monitored data stream.

In another aspect, the memory may be further configured for storing instructions which, when executed by the one or more processors, causes the one or more processors to generate the one or more frequency shaped signals by high pass filtering the monitored data stream.

In still another aspect, the memory may be further configured for storing instructions which, when executed by the one or more processors, causes the one or more processors to generate the noise filtered signal based on one or more previous noise filtered signals.

Moreover, the memory may be further configured for storing instructions which, when executed by the one or more processors, causes the one or more processors to output the noise filtered signal.

In yet another embodiment, the memory may be further configured for storing instructions which, when executed by the one or more processors, causes the one or more processors to output the noise filtered dropout compensated signal.

Additionally, the memory may be further configured for storing instructions which, when executed by the one or more processors, causes the one or more processors to generate a signal associated with detecting the presence of a signal dropout.

A system in accordance with still another embodiment may include an analyte sensor configured to monitor an analyte of a patient, a data processing section operatively coupled to the analyte sensor, the data processing section further including one or more processors, and a memory for storing instructions which, when executed by the one or more processors, causes the one or more processors to monitor a data stream, generate a noise-filtered signal associated with the data stream, detect a presence of a signal dropout based on the noise filtered signal, and estimate a noise filtered dropout compensated signal based on the noise filtered signal and the determination of the presence of the signal dropout.

The data processing section may include a data transmission unit operatively coupled to one or more processors con-

figured to transmit the data stream. In another aspect, the data processing section may include a data receiving unit operatively coupled to the one or more processors and configured to receive the data stream.

The analyte sensor may include a glucose sensor.

Moreover, the memory may be further configured for storing instructions which, when executed by the one or more processors, causes the one or more processors to store one or more of the data stream, the noise filtered signal, or the noise filtered dropout compensated signal.

The various processes described above including the processes performed by the receiver unit **104/106** or transmitter unit **102** in the software application execution environment in the analyte monitoring system **100** including the processes and routines described in conjunction with FIGS. **5-10**, may be embodied as computer programs developed using an object oriented language that allows the modeling of complex systems with modular objects to create abstractions that are representative of real world, physical objects and their interrelationships. The software required to carry out the inventive process, which may be stored in the memory or storage unit of the receiver unit **104/106** or transmitter unit **102** may be developed by a person of ordinary skill in the art and may include one or more computer program products.

Various other modifications and alterations in the structure and method of operation of this invention will be apparent to those skilled in the art without departing from the scope and spirit of the invention. Although the invention has been described in connection with specific preferred embodiments, it should be understood that the invention as claimed should not be unduly limited to such specific embodiments. It is intended that the following claims define the scope of the present invention and that structures and methods within the scope of these claims and their equivalents be covered thereby.

What is claimed is:

**1.** A glucose monitoring system, comprising:

an in vivo glucose sensor;

sensor electronics that generates glucose data corresponding to a monitored glucose level based on signals received from the in vivo glucose sensor; and

a glucose data processing unit that determines noise filtered glucose data based on stored noise filtered estimates of the glucose data received from the sensor electronics, that identifies dropouts in the noise filtered

glucose data over a predetermined time period, and that compensates for the identified dropouts in the noise filtered glucose data over the predetermined time period to increase accuracy of the generated glucose data, the glucose data processing unit further including an output unit to output information corresponding to the noise filtered glucose data over the predetermined time period.

**2.** The system of claim **1**, wherein the glucose data processing unit includes a filter that clips the dropout compensated noise filtered glucose signals to be within a predetermined range.

**3.** The system of claim **2**, wherein the clipped dropout compensated noise filtered glucose signals are not less than the noise filtered signals.

**4.** The system of claim **2**, wherein the clipped dropout compensated noise filtered glucose signals are not greater than a predetermined safety multiple of the noise filtered signals.

**5.** The system of claim **1**, wherein the glucose data processing unit identifies dropouts in the noise filtered glucose data over the predetermined time period based on a positive spike in the glucose data rate of change that exceeds a predetermined threshold.

**6.** The system of claim **1**, wherein the glucose data processing unit determines a fast rate estimate and a slow rate estimate based on the stored noise filtered estimates of the glucose data to identify dropouts in the noise filtered glucose data.

**7.** The system of claim **6**, wherein spikes in the fast rate estimate and the slow rate estimate are associated with dropouts in the noise filtered glucose data.

**8.** The system of claim **1**, wherein the glucose data processing unit includes an infusion device.

**9.** The system of claim **8**, wherein the infusion device determines a medication therapy profile based on the glucose data from the in vivo glucose sensor.

**10.** The system of claim **6**, wherein the glucose data processing unit includes a data computing device.

**11.** The system of claim **1**, wherein the sensor electronics communicates the generated glucose data to the glucose data processing unit over a wireless communication link.

**12.** The system of claim **1**, wherein the sensor electronics communicates the generated glucose data to the glucose data processing unit using Bluetooth communication protocol.

\* \* \* \* \*