



US009114782B2

(12) **United States Patent**
Warr

(10) **Patent No.:** **US 9,114,782 B2**
(45) **Date of Patent:** **Aug. 25, 2015**

(54) **LEVELING SYSTEM**

(56) **References Cited**

(71) Applicant: **Harnischfeger Technologies, Inc.**,
Wilmington, DE (US)

(72) Inventor: **Owen J. Warr**, Muskego, WI (US)

(73) Assignee: **Harnischfeger Technologies, Inc.**,
Wilmington, DE (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 22 days.

(21) Appl. No.: **13/691,930**

(22) Filed: **Dec. 3, 2012**

(65) **Prior Publication Data**

US 2013/0140802 A1 Jun. 6, 2013

Related U.S. Application Data

(60) Provisional application No. 61/565,800, filed on Dec.
1, 2011.

(51) **Int. Cl.**
B60S 9/10 (2006.01)
E21B 7/02 (2006.01)
E21B 15/00 (2006.01)

(52) **U.S. Cl.**
CPC . **B60S 9/10** (2013.01); **E21B 7/024** (2013.01);
E21B 15/003 (2013.01)

(58) **Field of Classification Search**
CPC E02F 9/085; B60S 9/10; B60S 9/12;
E21B 7/024; B66F 3/44; B66F 3/25; B66C
23/80
USPC 280/766.1; 254/423; 137/269, 884;
248/188.5

See application file for complete search history.

U.S. PATENT DOCUMENTS

2,443,209	A *	6/1948	Thornburg	254/423
3,181,630	A	5/1965	Coburn	
3,625,483	A *	12/1971	Stoner	254/423
4,109,733	A *	8/1978	Dummer	173/4
4,437,385	A *	3/1984	Kramer et al.	91/361
4,524,836	A *	6/1985	Pehrson	172/4.5
4,615,491	A	10/1986	Batch et al.	
4,872,275	A	10/1989	Beckett et al.	
6,050,573	A *	4/2000	Kunz	280/6.153
6,523,570	B2 *	2/2003	Weiss et al.	137/627.5
7,243,907	B2 *	7/2007	Singh et al.	254/423
8,177,193	B2	5/2012	Kooima et al.	
2011/0024706	A1	2/2011	Schwindaman et al.	
2011/0062399	A1	3/2011	Kooima et al.	

FOREIGN PATENT DOCUMENTS

GB 1432094 4/1976

OTHER PUBLICATIONS

First Office Action from the Australian Intellectual Property Office
for Application No. 2012258501 dated Jun. 13, 2014 (8 pages).

* cited by examiner

Primary Examiner — Brodie Follman


Assistant Examiner — Brian Cassidy

(74) *Attorney, Agent, or Firm* — Michael Best & Friedrich
LLP

(57) **ABSTRACT**

A leveling system for supporting a drill assembly includes at least one hydraulic actuator and a manifold coupled to the actuator. The hydraulic actuator supports the cab relative to a support surface, and includes a first end coupled to the cab and a second end that is extendable away from the first end. The manifold is coupled to the actuator and includes a directional flow control valve, a regenerative flow valve, and at least one counterbalance valve for controlling the extension of the actuator. The counterbalance valve is in direct fluid communication with the actuator.

16 Claims, 7 Drawing Sheets







FIG. 1






FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9

1

LEVELING SYSTEM

CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims the benefit of U.S. Provisional Patent Application No. 61/565,800, filed Dec. 1, 2011, the entire contents of which are incorporated herein by reference.

BACKGROUND OF THE INVENTION

The present invention relates to the field of blasthole drills. Specifically, the present invention discloses a leveling system for an operator cab and complete drill assembly.

Conventional drills often include a main platform for supporting an operator cab and the drilling mast/system; a leveling mechanism is then used for supporting the platform relative to the ground. The leveling mechanism may include hydraulic jacks that engage the ground. The fluid flow to each of the jacks is centrally controlled by a controller and valve manifold that are in fluid communication with each jack through a series of hoses. The hose connections can be cumbersome in part because each jack is subject to complex control inputs during operation. In addition, the hoses create pressure losses between the valve manifold and the individual jacks, causing the operation of the jacks to lag behind the controls. This causes the system to exhibit hysteresis and impairs the responsiveness of the leveling system.

SUMMARY OF THE INVENTION

In one embodiment, the invention provides a leveling system for supporting an operator cab. The leveling system includes at least one hydraulic actuator and a manifold coupled to the actuator. The hydraulic actuator supports the cab relative to a support surface, and includes a first end coupled to the cab and a second end that is extendable away from the first end. The manifold is coupled to the actuator and includes a directional flow control valve, a regenerative flow valve, and at least one counterbalance valve for controlling the extension of the actuator. The counterbalance valve is in direct fluid communication with the actuator.

In another embodiment, the invention provides a drill including a mainframe supporting an operator cab, a mast supporting a drill, and a plurality of hydraulic jacks supporting the mainframe and the mast relative to a support surface. Each jack includes an actuator extendable away from the mainframe and a valve manifold. The valve manifold is coupled to the actuator and includes a directional flow control valve, a regenerative flow valve, and a pair of counterbalance valves for controlling the extension of the actuator. The counterbalance valves are in direct fluid communication with the actuator.

In yet another embodiment, the invention provides a hydraulic jack for an excavation machine. The jack includes a shell, an actuator, and a valve manifold coupled to the shell. The shell includes a first end and a second end having an opening. The actuator includes a cylinder, a rod, a piston, a first conduit, and a second conduit. The cylinder is positioned at least partially within the shell and is moveable relative to the shell. The cylinder includes a first end and a second end for engaging a support surface. The rod is positioned at least partially within the cylinder and includes a first end coupled to the first end of the shell and a second end. The piston is coupled to the second end of the rod and divides the cylinder into a base side chamber and a rod side chamber. The first conduit extends at least partially through the rod and is in fluid

2

communication with the rod side chamber. The second conduit extends through the rod and is in fluid communication with the base side chamber. The valve manifold is coupled to the shell and includes at least one directional flow control valve, at least one regenerative flow valve, a first counterbalance valve in direct fluid communication with the first conduit, and a second counterbalance valve in direct fluid communication with the second conduit.

Other aspects of the invention will become apparent by consideration of the detailed description and accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of a blasthole drill.

FIG. 2 is a perspective view of a mainframe of the blasthole drill of FIG. 1 without associated equipment mounted thereon, but illustrating the location of leveling jacks on the mainframe.

FIG. 3 is a partial perspective view of a jack.

FIG. 4 is a side view of the jack of FIG. 3.

FIG. 5 is a cross sectional view of the jack of FIG. 3 taken along line 5-5.

FIG. 6 is a perspective view of a jack cylinder.

FIG. 7 is a cross sectional view of the jack cylinder of FIG. 6.

FIG. 8 is an enlarged cross sectional view of the jack cylinder of FIG. 6.

FIG. 9 is a schematic of a hydraulic control system.

Before any embodiments of the invention are explained in detail, it is to be understood that the invention is not limited in its application to the details of construction and the arrangement of components set forth in the following description or illustrated in the following drawings. The invention is capable of other embodiments and of being practiced or of being carried out in various ways. Also, it is to be understood that the phraseology and terminology used herein is for the purpose of description and should not be regarded as limiting.

DETAILED DESCRIPTION

As shown in FIG. 1, a blasthole drill 10 includes a base or lower works 14 for supporting and moving the drill 10 over a support surface, a platform or mainframe 18, a mast 22 for supporting a drill, an operator cab 26, and a leveling system 30 (FIG. 2) for supporting the mainframe 18 relative to the support surface. The mainframe 18 is coupled to the lower works 14 and supports the mast 22 and the cab 26. In the illustrated embodiment, the leveling system 30 includes four leveling jacks 34. In other embodiments, the leveling system may include fewer or more jacks 34.

As best shown in FIGS. 3-6, each jack 34 includes a shell 46, an electro-hydraulic control 50, and an actuator or leveling cylinder 54 (FIGS. 5 and 6). The shell 46 includes a first end 58 coupled to a flange cover 62, and a second end 66 (FIG. 2) that is open. The electro-hydraulic control 50 is positioned adjacent the shell 46 and is in direct fluid communication with the leveling cylinder 54. The electro-hydraulic control 50 includes a pressure sensor 74 (FIG. 9) and a valve manifold 78, and is described in greater detail below. The leveling cylinder 54 (FIGS. 5 and 6) is positioned within the shell 46 and extends outwardly from the second end 66 of the shell 46.

As shown in FIG. 7, the leveling cylinder 54 includes a barrel 86, a piston 90 positioned within the barrel 86, and a rod 94 positioned substantially within the barrel 86. The barrel 86 is moveable relative to the rod 94 and the piston 90. The barrel 86 includes a first end 102 and a second end 106.

The first end **102** of the barrel **86** includes a rod seal **110** extending circumferentially around an inside surface **114** of the barrel **86**. The rod seal **110** engages the rod **94** and is moveable relative to the rod **94**. The second end **106** of the barrel **86** may be coupled to a support member (not shown) for engaging the ground or support surface.

Referring to FIG. 8, the piston **90** includes a base side **122** and a rod side **126**. The piston **90** divides the cylinder **54** into a base side chamber **130** and a rod side chamber **134**. The base side chamber **130** is formed by the interior volume of the barrel **86** extending between the second end **106** of the barrel **86** and the base side **122** of the piston **90**. The rod side chamber **134** is defined by the interior volume of the barrel **86** located between the barrel **86** and the rod **94** and extends from the rod side **126** of the piston **90** to the rod seal **110**.

Referring to FIGS. 5 and 8, the rod **94** includes a first end **142** (FIG. 5) coupled to the shell **46** and a second end **146** (FIG. 8) coupled to the rod side **126** of the piston **90**. In the illustrated embodiment, the first end **142** of the rod **94** is coupled to the shell **46** by a tie rod **150** (FIG. 5). The rod **94** includes a first conduit **158**, a first port **162** (FIG. 8), a second conduit **166**, and a second port **170** (FIG. 8). The first conduit **158** is located within the rod **94** and is in direct fluid communication with the valve manifold **78** (FIG. 5). The term “direct fluid communication” refers to the fact that the valve manifold **78** directly interfaces with the conduit **158** without requiring hoses or other intermediate connections. The second conduit **166** is in direct fluid communication with the valve manifold **78** and extends through the rod **94**. In particular, the first conduit **158** and the second conduit **166** are each in direct fluid communication with a counterbalance valve **190a**, **190b** (FIG. 5), as described in more detail below. As shown in FIG. 8, the first port **162** is positioned on the rod **94** and provides fluid communication between the first conduit **158** and the rod side chamber **134**. The second conduit **166** is schematically parallel to the first conduit **158**, such that the first conduit **158** and the second conduit **166** are not in communication with one another. The second port **170** is positioned on the base side **122** of the piston **90** and provides fluid communication between the second conduit **166** and the base side chamber **130**.

When fluid is supplied to the base side chamber **130** via the second conduit **166** and drained from the rod side chamber **134** via the first conduit **158**, the second end **106** of the barrel **86** moves away from the piston **90** while the first end **102** of the barrel **86** moves toward the piston **90** to extend the cylinder **54**. Similarly, when fluid is supplied to the rod side chamber **134** via the first conduit **158** and drained from the base side chamber **130** via the second conduit **166**, the second end **106** of the barrel **86** moves away from the piston **90** to retract the cylinder **54**.

The electro-hydraulic control **50** is shown schematically in FIG. 9. The valve manifold **78** includes a pressure-compensated proportional flow control valve **178**, a pair of pilot valves **182**, a regenerative flow valve **186**, and a pair of counterbalance valves **190**. The flow control valve **178** is coupled to a pressure compensator valve **198**. One of the pilot valves **182** moves the flow control valve **186** to an “extend” phase to extend the leveling cylinder **54**, while the other pilot valve **182** moves the flow control valve to a “retract” phase. The regenerative flow valve **186** is operated by the pilot valves **182** and includes a cavity **206** for providing a pressure limitation on the regenerative fluid flow. The counterbalance valves **190** are also operated by the pilot valves **182** and sense a sudden pressure change in either the base side chamber **130** or the rod side chamber **134**. The electro-hydraulic controller **50** obtains pressure data for the cylinder **54** from the pressure sensor **74**.

During operation, the operator activates one of the pilot valves **182** to extend or retract each jack **34** to level the mainframe **18**. The operator may actuate all of the jacks **34** simultaneously or individually. When the pilot valve **182** associated with the extend phase is actuated, for instance, the flow control valve **178** is moved such that fluid is supplied through the second counterbalance valve **190b** to the second conduit **166**, and then to the base side chamber **130**. The counterbalance valves **190a**, **190b** are operated by pilot pressure, and the counterbalance valves **190a**, **190b** block fluid flow to both chambers **130**, **134** of the cylinder **54** if the pilot flow to either counterbalance valve **190** is interrupted. The counterbalance valves **190a**, **190b** control flow to the cylinder **54** and also lock the cylinder in case of a sudden drop in fluid flow or pressure. Therefore, the counterbalance valves **190a**, **190b** provide an additional measure of safety during operation of the drill **10**.

If the counterbalance valves **190** permit fluid flow in both directions, the regenerative flow valve **186** is actuated to allow some of the fluid that is pushed out of the rod side chamber **134** to flow into the base side chamber **130**, providing better response time for extending the cylinder **54**. The regenerative fluid flow may be limited by a maximum pressure.

The leveling system **30** include multiple jacks **34** for supporting the mainframe **18**, and each jack **34** includes an individual valve manifold **78** directly coupled to the jack **34** to provide direct fluid communication between the counterbalance valves **190a**, **190b** and the cylinder **54**. The flow control valve **178** is housed within the same valve manifold **78** as the regenerative flow valve **186** and the counterbalance valves **190a**, **190b**. The electro-hydraulic control **50** actuates the valves remotely. These features eliminate the need for hose connections between each valve and the cylinder **54**, thereby significantly reducing the hysteresis in the system and improving the response time of the controller **50**.

Thus, the invention provides, among other things, a leveling system. Various features and advantages of the invention are set forth in the following claims.

What is claimed is:

1. A leveling system for supporting a drill assembly, the leveling system comprising:
 - at least one hydraulic actuator supporting a cab relative to a support surface, the actuator including a first end coupled to the cab and a second end that is extendable away from the first end, the actuator further including a first fluid passageway and a second fluid passageway for providing fluid flow to extend and retract the second end; and
 - a manifold directly connected to the actuator, the manifold including a directional flow control valve, a regenerative flow valve, and at least one counterbalance valve for controlling the extension of the actuator, the at least one counterbalance valve being in direct fluid communication with at least one of the first fluid passageway and the second fluid passageway,
 - further comprising a shell including a first end and a second end having an opening,
 - wherein the hydraulic actuator includes
 - a barrel positioned at least partially within the shell and moveable relative to the shell, the barrel including a first end and a second end for engaging the support surface,
 - a rod positioned at least partially within the barrel, the rod including a first end coupled to the first end of the shell and a second end, and

5

a piston coupled to the second end of the rod, the piston dividing the barrel into a base side chamber and a rod side chamber, and
 wherein the first fluid passageway extends at least partially through the rod and is in fluid communication with the rod side chamber, and the second fluid passageway extends through the rod and is in fluid communication with the base side chamber.

2. The leveling system of claim 1, wherein the directional flow control valve is a pressure compensated proportional flow control valve.

3. The leveling system of claim 1, wherein the counterbalance valve blocks fluid flow to the rod side chamber and the base side chamber if fluid flow to the counterbalance valve is interrupted.

4. The leveling system of claim 1, wherein the regenerative flow valve is actuated to permit fluid flow from the rod side chamber to the base side chamber, and wherein the fluid flow is not permitted once the pressure in the base side chamber reaches a predetermined level.

5. The leveling system of claim 1, wherein the regenerative flow valve and the directional flow control valve are in direct fluid communication with the actuator.

6. A drill comprising:
 a mainframe supporting an operator cab;
 a mast supporting a drill; and
 a plurality of hydraulic jacks supporting the mainframe and the mast relative to a support surface, each jack including an actuator extendable away from the mainframe and a valve manifold, the valve manifold directly connected to the actuator and including a directional flow control valve, a regenerative flow valve, and a pair of counterbalance valves for controlling the extension of the actuator, the counterbalance valves being in direct fluid communication with the actuator,
 further comprising a shell including a first end and a second end having an opening,
 wherein the hydraulic actuator includes
 a barrel positioned at least partially within the shell and moveable relative to the shell, the barrel including a first end and a second end for engaging the support surface,
 a rod positioned at least partially within the barrel, the rod including a first end coupled to the first end of the shell and a second end, and
 a piston coupled to the second end of the rod, the piston dividing the barrel into a base side chamber and a rod side chamber,
 wherein the rod includes a first conduit and a second conduit, the first conduit extending at least partially through the rod and in fluid communication with the rod side chamber, the second conduit extending through the rod and in fluid communication with the base side chamber.

7. The drill of claim 6, wherein the directional flow control valve is a pressure compensated proportional flow control valve.

6

8. The drill of claim 6, wherein one of the counterbalance valves blocks fluid flow to the rod side chamber and the other counterbalance valve blocks fluid flow to the base side chamber if fluid flow to either counterbalance valve is interrupted.

9. The drill of claim 6, wherein the regenerative flow valve is actuated to permit fluid flow from the rod side chamber to the base side chamber, and wherein the fluid flow is not permitted once the pressure in the base side chamber reaches a predetermined level.

10. The drill of claim 6, wherein the regenerative flow valve and the directional flow control valve are in direct fluid communication with the actuator.

11. The drill of claim 6, wherein the plurality of hydraulic jacks includes at least three hydraulic jacks.

12. A hydraulic jack for an excavation machine, the jack comprising:

a shell including a first end and a second end having an opening;

an actuator including

a barrel positioned at least partially within the shell and moveable relative to the shell, the barrel including a first end and a second end for engaging a support surface;

a rod positioned at least partially within the barrel, the rod including a first end coupled to the first end of the shell and a second end,

a piston coupled to the second end of the rod, the piston dividing the barrel into a base side chamber and a rod side chamber,

a first conduit extending at least partially through the rod and being in fluid communication with the rod side chamber, and

a second conduit extending through the rod and being in fluid communication with the base side chamber; and

a valve manifold directly connected to the shell and including at least one directional flow control valve, at least one regenerative flow valve, a first counterbalance valve in direct fluid communication with the first conduit, and a second counterbalance valve in direct fluid communication with the second conduit.

13. The hydraulic jack of claim 12, wherein the directional flow control valve is a pressure-compensated proportional flow control valve.

14. The hydraulic jack of claim 12, wherein the first counterbalance valve blocks fluid flow to the rod side chamber if fluid flow to the first counterbalance valve is interrupted.

15. The hydraulic jack of claim 12, wherein the at least one regenerative flow valve is actuated to permit fluid flow from the rod side chamber to the base side chamber to assist in extending the barrel, and wherein the fluid flow is not permitted once the pressure in the base side chamber reaches a predetermined level.

16. The hydraulic jack of claim 12, wherein the at least one regenerative flow valve and the at least one directional flow control valve are in direct fluid communication with one of the first conduit and the second conduit.

* * * * *