



US009117611B2

(12) **United States Patent**
Naka et al.

(10) **Patent No.:** **US 9,117,611 B2**
(45) **Date of Patent:** **Aug. 25, 2015**

(54) **ELECTROMAGNETIC CONTACTOR**

(75) Inventors: **Yasuhiro Naka**, Kounosu (JP); **Kouetsu Takaya**, Kounosu (JP); **Kenji Suzuki**, Kounosu (JP); **Osamu Kashimura**, Hino (JP)

(73) Assignees: **FUJI ELECTRIC FA COMPONENTS & SYSTEMS CO., LTD.**, Tokyo (JP); **FUJI ELECTRIC CO., LTD.**, Kawasaki-Shi (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/116,226**

(22) PCT Filed: **Apr. 3, 2012**

(86) PCT No.: **PCT/JP2012/002333**

§ 371 (c)(1),
(2), (4) Date: **Nov. 22, 2013**

(87) PCT Pub. No.: **WO2012/157176**

PCT Pub. Date: **Nov. 22, 2012**

(65) **Prior Publication Data**

US 2014/0062627 A1 Mar. 6, 2014

(30) **Foreign Application Priority Data**

May 19, 2011 (JP) 2011-112907

(51) **Int. Cl.**

H01H 9/30 (2006.01)
H01H 50/54 (2006.01)
H01H 50/42 (2006.01)
H01H 9/34 (2006.01)
H01H 50/02 (2006.01)
H01H 1/54 (2006.01)
H01H 9/44 (2006.01)

(52) **U.S. Cl.**

CPC **H01H 50/54** (2013.01); **H01H 50/42** (2013.01); **H01H 50/546** (2013.01); **H01H 1/54** (2013.01); **H01H 9/34** (2013.01); **H01H 9/443** (2013.01); **H01H 2050/025** (2013.01)

(58) **Field of Classification Search**

CPC **H01H 50/42**; **H01H 50/546**; **H01H 50/54**; **H01H 9/34**; **H01H 1/54**; **H01H 9/443**; **H01H 2050/025**

USPC **335/78**, **128**, **189-191**, **201**, **202**, **203**
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,465,270 A 9/1969 Schattler
5,546,061 A * 8/1996 Okabayashi et al. 335/78

(Continued)

FOREIGN PATENT DOCUMENTS

JP H05-25644 U 4/1993
JP S62-140328 A 6/1997

OTHER PUBLICATIONS

Europe Patent Office, "Search Report for EP 12786354.6," Oct. 2, 2014.


Primary Examiner — Bernard Rojas

(74) *Attorney, Agent, or Firm* — Manabu Kanesaka

(57) **ABSTRACT**

An electromagnetic contactor has a contact device including a pair of fixed contacts disposed maintaining a predetermined distance and a movable contact disposed to be capable of contacting to and separating from the pair of fixed contacts. The pair of fixed contacts each includes a support conductor portion supported by an upper plate of a contact housing case, and a contact conductor portion connected to an end portion of the support conductor portion. The contact conductor portion includes a contact plate portion formed with a contact portion, and a connecting plate portion formed on an outer end portion of the contact plate portion and extending to the upper plate side. The movable contact is mounted onto a connecting shaft connected to a drive portion through a contact spring on an end portion on the upper plate side, and disposed to face the contact portion of the pair of fixed contacts.

6 Claims, 10 Drawing Sheets



US 9,117,611 B2

Page 2

(56)

References Cited

U.S. PATENT DOCUMENTS

5,892,194 A *	4/1999	Uotome et al.	218/68	2005/0148216 A1	7/2005	Nishida et al.	
8,823,472 B2 *	9/2014	Takaya et al.	335/133	2005/0151606 A1 *	7/2005	Nishida et al.	335/128
				2009/0237191 A1	9/2009	Yano et al.	

* cited by examiner




Fig. 2(b)







Fig. 2(a)






Fig. 4(a)




Fig. 4(b)




Fig. 4(c)




Fig. 5




Fig. 6(a)




Fig. 6(b)




Fig. 6(c)




Fig. 7(a)




Fig. 7(b)




Fig. 7(c)




Fig. 8




Fig. 9(a)




Fig. 9(b)




Fig. 10(a)




Fig. 10(b)

ELECTROMAGNETIC CONTACTOR

RELATED APPLICATION

The present application is a National Phase of International Application No. PCT/JP2012/002333 filed Apr. 3, 2012, and claims priority from Japanese Applications No. 2011112907 filed May 19, 2011.

TECHNICAL FIELD

The present invention relates to an electromagnetic contactor having a pair of fixed contacts disposed maintaining a predetermined interval and a movable contact disposed so as to be capable of contacting to and separating from the fixed contacts.

BACKGROUND ART

A fixed contact terminal support structure, having a fixed contact terminal support structure that supports a pair of fixed contact terminals, on free ends of which are provided fixed contacts, with a fixed contact stand and causes both end portions of a movable contact piece to be capable of contacting to and separating from the pair of fixed contacts, wherein the fixed contact terminals, to which a connection terminal is fixed by caulking, are formed in an approximate C-shape, and a permanent magnet is installed in a lower side corner portion of the fixed contact terminals, has been proposed as a contact structure that may be applied to an electromagnetic contactor that carries out switching of a current path (for example, refer to Patent Literature 1).

CITATION LIST

Patent Literature

PTL 1: JP-A-2005-183277

SUMMARY OF INVENTION

Technical Problem

However, the heretofore known example described in PTL 1 is such that, although the fixed contact terminals are formed in an approximate C-shape, the fixed contact terminals are formed in a C-shape in order to support a permanent magnet in a corner portion thereof, the height increases, and there is an unsolved problem in that it is not possible to reduce the size of the contact device when it is applied to an electromagnetic contactor.

Also, when adopting an engaged state wherein the movable contact contacts the fixed contacts and a current flows, an electromagnetic repulsion force is generated in a contact opening direction in portions in which the movable contact and fixed contacts are contacting when the current flowing is a large current, so that it is no longer possible to secure stable contact between the movable contact and fixed contacts, and there is an unsolved problem in that short circuit resistance performance decreases. There is also an unsolved problem in that there arises a need to increase the urging force of a contact spring that presses the movable contact to the fixed contact side in order to counter the electromagnetic repulsion force.

Therefore, the invention, having been contrived focusing on the heretofore described unsolved problems of the heretofore known example, has an object of providing an electromagnetic contactor such that it is possible to reduce the height

of a contact device, thus reducing the size of the electromagnetic contactor, while suppressing electromagnetic repulsion force generated between a movable contact and fixed contacts.

Solution to Problem

In order to achieve the heretofore described object, an electromagnetic contactor according to one aspect of the invention includes a contact device including a pair of fixed contacts disposed maintaining a predetermined distance and a movable contact disposed to be capable of contacting to and separating from the pair of fixed contacts. The pair of fixed contacts include support conductor portions maintaining a predetermined interval and supported by an upper plate of a contact housing case, and a contact conductor portion connected to an end portion of the support conductor portion inside the contact housing case. The contact conductor portion has a contact plate portion formed with at least a contact portion on an upper plate side and in parallel with the upper plate, and a connecting plate portion formed in proximity to the contact portion on an outer end portion of the contact plate portion and extending to the upper plate side. The movable contact is mounted onto a connecting shaft connected to a drive portion through a contact spring on an end portion on the upper plate side, and disposed to face the contact portion of the pair of fixed contacts from the upper plate side.

According to this configuration, because the pair of fixed contacts have an L-shaped or C-shaped contact conductor portion wherein a contact plate portion having at least a contact portion is disposed parallel with the upper plate and a connecting plate portion is formed in proximity to the contact portion on an outer end portion of the contact plate portion and extending to the upper plate side, when adopting a conductive state by bringing both ends of the movable contact into contact with the contact portions of the pair of fixed contacts when engaging the electromagnetic contactor, it is possible to cause a magnetic field generated by the current flowing through the connecting plate portion to act on the upper plate side of the movable contact. Because of this, a Lorentz force pressing the movable contact to the fixed contact portion side is generated, contact between the movable contact and the contact portions of the fixed contacts is maintained, and it is thus possible to realize a high short circuit resistance performance. Consequently, it is possible to reduce the urging force of the contact spring that urges the movable contact to the fixed contact portion side and thus possible to suppress the height of the contact device.

Also, it is good when the electromagnetic contactor is such that the contact conductor portion is formed in a C-shape having a second connecting plate portion in parallel to the contact plate portion and disposed between an end portion of the connecting plate portion on the upper plate side and the support conductor portion.

According to this configuration, because the fixed contacts are formed in a C-shape portion, it is also possible to form a magnetic field on the upper plate side of the movable contact with the current flowing through the second connecting plate portion, and thus possible to increase the magnetic flux density on the upper plate side of the movable contact, generating a bigger Lorentz force countering the electromagnetic repulsion force.

Also, it is good when the electromagnetic contactor is such that the movable contact is formed with a depressed portion protruding toward the side opposite to that of the upper plate in a portion in which the movable contact comes into contact with the contact spring.

According to this configuration, because the contact spring contacts the depressed portion of the movable contact, it is possible to reduce the height of the upper plate of the contact spring by an amount equivalent to the size of the depressed portion, and thus possible to reduce the height of the whole contact device.

Advantageous Effects of Invention

According to the invention, it is possible to generate a Lorentz force that counters the electromagnetic repulsion force in an engaged state by forming the contact conductor portions of the fixed contacts in an L-shape or C-shape, in accordance with which it is possible to set the urging force of the contact spring to be small, and thus possible to reduce the size of the contact device configuration. Moreover, as the contact conductor portion is such that it is necessary to bring a plate portion into close proximity in order to generate a Lorentz force that counters the electromagnetic repulsion force, it is possible to reduce the size of the contact conductor portion configuration by this amount.

Furthermore, as the contact conductor portions of the pair of fixed contacts and the contact spring are disposed in parallel, it is possible to reduce the height of the contact device considerably in comparison with a case wherein the movable contact is disposed on the side opposite to that of the upper plate, and the contact spring and contact conductor portions are disposed in series.

BRIEF DESCRIPTION OF DRAWINGS

FIG. 1 is a sectional view showing a first embodiment of an electromagnetic contactor according to the present invention.

FIGS. 2(a), 2(b) are exploded perspective views of a contact housing case.

FIGS. 3(a)-3(c) are diagrams showing an insulating cover of a contact device, wherein FIG. 3(a) is a perspective view, FIG. 3(b) is a plan view before mounting, and FIG. 3(c) is a plan view after mounting.

FIG. 4(a)-4(c) are illustrations showing an insulating cover mounting method.

FIG. 5 is a sectional view along the line A-A in FIG. 1.

FIGS. 6(a)-6(c) are illustrated accompanying a description of arc extinguishing by an arc extinguishing permanent magnet according to the invention.

FIGS. 7(a)-7(c) are illustrations accompanying a description of arc extinguishing when the arc extinguishing permanent magnet is disposed on the outer side of an insulating case.

FIG. 8 is a sectional view showing a second embodiment of an electromagnetic contactor according to the invention.

FIGS. 9(a), 9(b) are diagrams showing a modification example of a contact device of the invention, wherein FIG. 9(a) is a sectional view and FIG. 9(b) is a perspective view.

FIGS. 10(a), 10(b) are diagrams showing another modification example of a contact device of the invention, wherein FIG. 10(a) is a sectional view and FIG. 10(b) is a perspective view.

DESCRIPTION OF EMBODIMENTS

Hereafter, a description will be given, based on the drawings, of embodiments of the invention.

FIG. 1 is a sectional view showing one embodiment of an electromagnetic contactor according to the invention, while FIGS. 2(a), 2(b) are exploded perspective views of a contact housing case. In FIG. 1 and FIGS. 2(a), 2(b), numeral 10 is an

electromagnetic contactor, and the electromagnetic contactor 10 is configured of a contact device 100 in which is disposed a contact mechanism, and an electromagnet unit 200 that drives the contact device 100.

The contact device 100 has a contact housing case 102 that houses a contact mechanism 101, as is clear from FIG. 1 and FIGS. 2(a), 2(b). The contact housing case 102 includes a metal tubular body 104 having on a lower end portion a metal flange portion 103 protruding outward, and a fixed contact support insulating substrate 105 configured of a plate-like ceramic insulating substrate that closes off the upper end of the metal tubular body 104, as shown in FIG. 2(a).

The metal tubular body 104 is such that the flange portion 103 thereof is seal joined and fixed to an upper portion magnetic yoke 210 of the electromagnet unit 200, to be described hereafter.

Also, through holes 106 and 107 in which are inserted a pair of fixed contacts 111 and 112, to be described hereafter, are formed maintaining a predetermined interval in a central portion of the fixed contact support insulating substrate 105. A metalizing process is performed around the through holes 106 and 107 on the upper surface side of the fixed contact support insulating substrate 105, and in a position on the lower surface side that contacts the tubular body 104. In order to carry out the metalizing process, copper foil is formed around the through holes 106 and 107, and in the position that contacts the tubular body 104, in a state wherein a plurality of the fixed contact support insulating substrates 105 is arranged vertically and horizontally on a flat surface.

The contact mechanism 101, as shown in FIG. 1, includes the pair of fixed contacts 111 and 112 inserted into and fixed in the through holes 106 and 107 of the fixed contact support insulating substrate 105 of the contact housing case 102. Each of the fixed contacts 111 and 112 includes a support conductor portion 114, having on an upper end a flange portion protruding outward, inserted into the through holes 106 and 107 of the fixed contact support insulating substrate 105, and a contact conductor portion 115, the inner side of which is opened, linked to the support conductor portion 114 and disposed on the lower surface side of the fixed contact support insulating substrate 105.

The contact conductor portion 115 includes an upper plate portion 116 as a second connecting plate portion extending to the outer side along the line of the lower surface of the fixed contact support insulating substrate 105, an intermediate plate portion 117 as a connection plate portion extending downward from the outer side end portion of the upper plate portion 116, and a lower plate portion 118 as a contact plate portion extending from the lower end side of the intermediate plate portion 117, parallel with the upper plate portion 116, to the inner side, that is, in a direction facing the fixed contacts 111 and 112. Because of this, the contact conductor portion 115 is formed in a C-shape wherein the upper plate portion 116 is added to an L-shape formed by the intermediate plate portion 117 and lower plate portion 118.

Herein, the support conductor portion 114 and contact conductor portion 115 are fixed by, for example, brazing in a state in which a pin 114a formed protruding on the lower end surface of the support conductor portion 114 is inserted into a through hole 120 formed in the upper plate portion 116 of the contact conductor portion 115. The fixing of the support conductor portion 114 and contact conductor portion 115, not being limited to brazing, may be such that the pin 114a is fitted into the through hole 120, or an external thread is formed on the pin 114a and an internal thread formed in the through hole 120, and the two are screwed together.

Also, a magnetic plate **119** of a C-shape when seen in plan view is mounted so as to cover the inner side surface of the intermediate plate portion **117** in the C-shaped portion **115** of the fixed contacts **111** and **112**. By disposing the magnetic plate **119** so as to cover the inner side surface of the intermediate plate portion **117** in this way, it is possible to shield a magnetic field generated by current flowing through the intermediate plate portion **117**.

Because of this, in the event that an arc is generated when, from a state in which contact portions **130a** of a movable contact **130** are contacting contact portions **118a** of the fixed contacts **111** and **112**, the contact portions **130a** move away upward, as will be described hereafter, it is possible to prevent interference between a magnetic field caused by the current flowing through the intermediate plate portion **117** and a magnetic field caused by the arc generated between the contact portions **118a** of the fixed contacts **111** and **112** and the contact portions **130a** of the movable contact **130**. Consequently, it is possible to prevent the two magnetic fields from repelling each other, the arc being moved to the inner side along the line of the movable contact **130** by this electromagnetic repulsion force, and interruption of the arc becoming difficult. It being sufficient that it is possible to shield a magnetic field generated by current flowing through the intermediate plate portion **117**, the magnetic plate **119** may be formed so as to cover the periphery of the intermediate plate portion **117**.

Furthermore, an insulating cover **121**, made of a synthetic resin material, that regulates arc generation is mounted on the contact conductor portion **115** of each of the fixed contacts **111** and **112**. The insulating cover **121** covers the inner peripheral surfaces of the upper plate portion **116** and intermediate plate portion **117** of the contact conductor portion **115**, as shown in FIGS. **3(a)** and **3(b)**. The insulating cover **121** includes an L-shaped plate portion **122** that follows the inner peripheral surfaces of the upper plate portion **116** and intermediate plate portion **117**, side plate portions **123** and **124**, each extending upward and outward from front and rear end portions of the L-shaped plate portion **122**, that cover side surfaces of the upper plate portion **116** and intermediate plate portion **117** of the contact conductor portion **115**, and a fitting portion **125**, formed on the inward side from the upper end of the side plate portions **123** and **124**, that fits onto a small diameter portion **114b** formed on the support conductor portion **114** of the fixed contacts **111** and **112**.

Consequently, the insulating cover **121** is placed in a state in which the fitting portion **125** is facing the small diameter portion of the support conductor portion **114** of the fixed contacts **111** and **112**, as shown in FIGS. **3(a)** and **3(b)**, after which, the fitting portion **125** is fitted onto the small diameter portion **114b** of the support conductor portion **114** by pushing the insulating cover **121** onto the small diameter portion **114b**, as shown in FIG. **3(c)**.

Actually, with the contact housing case **102** after the fixed contacts **111** and **112** have been attached in a state wherein the fixed contact support insulating substrate **105** is on the lower side, the insulating cover **121** is inserted from an upper aperture portion between the fixed contacts **111** and **112** in a state vertically the reverse of that in FIGS. **3(a)** to **3(c)**, as shown in FIG. **4(a)**.

Next, in a state in which the fitting portion **125** is contacting the fixed contact support insulating substrate **105**, as shown in FIG. **4(b)**, the fitting portion **125** is engaged with and fixed to the small diameter portion **114b** of the support conductor portion **114** of the fixed contacts **111** and **112** by pushing the insulating cover **121** to the outer side, as shown in FIG. **4(c)**.

By mounting the insulating cover **121** on the contact conductor portion **115** of the fixed contacts **111** and **112** in this way, only the upper surface side of the lower plate portion **118** of the inner peripheral surface of the contact conductor portion **115** is exposed, and is taken to be the contact portion **118a**.

Further, the movable contact **130** is disposed in such a way that both end portions are disposed in the contact conductor portion **115** of the fixed contacts **111** and **112**. The movable contact **130** is supported by a connecting shaft **131** fixed to a movable plunger **215** of the electromagnet unit **200**, to be described hereafter. The movable contact **130** is such that, as shown in FIG. **1**, a central portion in the vicinity of the connecting shaft **131** protrudes downward, whereby a depressed portion **132** is formed, and a through hole **133** in which the connecting shaft **131** is inserted is formed in the depressed portion **132**.

A flange portion **131a** protruding outward is formed on the upper end of the connecting shaft **131**. The connecting shaft **131** is inserted from the lower end side into a contact spring **134**, then inserted into the through hole **133** of the movable contact **130**, bringing the upper end of the contact spring **134** into contact with the flange portion **131a**, and the moving contact **130** is positioned using, for example, a C-ring **135** so as to obtain a predetermined urging force from the contact spring **134**.

The movable contact **130**, in a released state, takes on a state wherein the contact portions **130a** at either end and the contact portions **118a** of the lower plate portions **118** of the contact conductor portions **115** of the fixed contacts **111** and **112** are separated from each other and maintaining a predetermined interval. Also, the movable contact **130** is set so that, in an engaged position, the contact portions at either end contact the contact portions **118a** of the lower plate portions **118** of the contact conductor portions **115** of the fixed contacts **111** and **112** at a predetermined contact pressure due to the contact spring **134**.

Furthermore, an insulating cylinder **140** formed in a bottomed tubular form of a bottom plate portion **140a** and a tubular body **140b** formed on the upper surface of the bottom plate portion **140a** is disposed on the inner peripheral surface of the tubular body **104** of the contact housing case **102**, as shown in FIG. **1**. The insulating cylinder **140** is made of, for example, a synthetic resin, and the bottom plate portion **140a** and tubular body **140b** are formed integrally. Magnet housing cylinders **141** and **142** are formed integrally as magnet housing portions in positions on the insulating cylinder **140** facing the side surfaces of the movable contact **130**. Arc extinguishing permanent magnets **143** and **144** are inserted into and fixed in the magnet housing cylinders **141** and **142**.

The arc extinguishing permanent magnets **143** and **144** are magnetized in a thickness direction so that mutually opposing faces thereof are homopolar, for example, N-poles. Also, the arc extinguishing permanent magnets **143** and **144** are set so that both end portions in a left-right direction are slightly inward of positions in which the contact portions **118a** of the fixed contacts **111** and **112** and the contact portions of the movable contact **130** are opposed, as shown in FIG. **5**. Further, arc extinguishing spaces **145** and **146** are formed on the outer sides in a left-right direction, that is, the longitudinal direction of the movable contact, of the magnet housing cylinders **141** and **142** respectively.

Also, movable contact guide members **148** and **149**, which regulate the turning of the movable contact **130**, are formed protruding, sliding against side edges of the magnet housing cylinders **141** and **142** toward either end of the movable contact **130**.

Consequently, the insulating cylinder **140** includes a function of positioning the arc extinguishing permanent magnets **143** and **144** using the magnet housing cylinders **141** and **142**, a protective function protecting the arc extinguishing permanent magnets **143** and **144** from an arc, and an insulating function preventing the arc from affecting the metal tubular body **104**, which increases external rigidity.

Further, by disposing the arc extinguishing permanent magnets **143** and **144** on the inner peripheral surface side of the insulating cylinder **140**, it is possible to bring the arc extinguishing permanent magnets **143** and **144** near to the movable contact **130**. Because of this, as shown in FIG. 6(a), magnetic flux ϕ emanating from the N-pole sides of the two arc extinguishing permanent magnets **143** and **144** crosses portions in which the contact portions **118a** of the fixed contacts **111** and **112** and the contact portions **130a** of the movable contact **130** are opposed in a left-right direction, from the inner side to the outer side, with a large flux density.

Consequently, assuming that the fixed contact **111** is connected to a current supply source and the fixed contact **112** is connected to a load side, the current direction in the engaged state is such that the current flows from the fixed contact **111** through the movable contact **130** to the fixed contact **112**, as shown in FIG. 6(b). Then, when changing from the engaged state to the released state by causing the movable contact **130** to move away upward from the fixed contacts **111** and **112**, an arc is generated between the contact portions **118a** of the fixed contacts **111** and **112** and the contact portions **130a** of the movable contact **130**.

The arc is extended to the arc extinguishing space **145** side on the arc extinguishing permanent magnet **143** side by the magnetic flux ϕ from the arc extinguishing permanent magnets **143** and **144**. At this time, as the arc extinguishing spaces **145** and **146** are formed as widely as the thickness of the arc extinguishing permanent magnets **143** and **144**, it is possible to obtain a long arc length, and thus possible to reliably extinguish the arc.

Incidentally, when the arc extinguishing permanent magnets **143** and **144** are disposed on the outer side of the insulating cylinder **140**, as shown in FIGS. 7(a) to 7(c), there is an increase in the distance to the positions in which the contact portions **118a** of the fixed contacts **111** and **112** and the contact portions **130a** of the movable contact **130** are opposed, and when the same permanent magnets as in this embodiment are applied, the density of the magnetic flux crossing the arc decreases.

Because of this, the Lorentz force acting on an arc generated when shifting from the engaged state to the released state decreases, and it is no longer possible to sufficiently extend the arc. In order to improve the arc extinguishing performance, it is necessary to increase the magnetic force of the arc extinguishing permanent magnets **143** and **144**. Moreover, in order to shorten the distance between the arc extinguishing permanent magnets **143** and **144** and the contact portions of the fixed contacts **111** and **112** and movable contact **130**, it is necessary to reduce the depth in a front-back direction of the insulating cylinder **140**, and there is a problem in that it is not possible to secure sufficient arc extinguishing space to extinguish the arc.

However, according to the heretofore described embodiment, the arc extinguishing permanent magnets **143** and **144** are disposed on the inner side of the insulating cylinder **140**, because of which the problems occurring when the arc extinguishing permanent magnets **143** and **144** are disposed on the outer side of the insulating cylinder **140** can all be solved.

The electromagnet unit **200**, as shown in FIG. 1, has a magnetic yoke **201** of a flattened U-shape when seen from the

side, and a cylindrical auxiliary yoke **203** is fixed in a central portion of a bottom plate portion **202** of the magnetic yoke **201**. A spool **204** is disposed on the outer side of the cylindrical auxiliary yoke **203**.

The spool **204** is configured of a central cylinder portion **205** in which the cylindrical auxiliary yoke **203** is inserted, a lower flange portion **206** protruding outward in a radial direction from a lower end portion of the central cylinder portion **205**, and an upper flange portion **207** protruding outward in a radial direction from slightly below the upper end of the central cylinder portion **205**. Further, an exciting coil **208** is mounted wound in a housing space configured of the central cylinder portion **205**, lower flange portion **206**, and upper flange portion **207**.

Further, an upper magnetic yoke **210** is fixed between upper ends forming an opened end of the magnetic yoke **201**. A through hole **210a** facing the central cylinder portion **205** of the spool **204** is formed in a central portion of the upper magnetic yoke **210**.

Further, the movable plunger **215**, in which is disposed a return spring **214** between a bottom portion and the bottom plate portion **202** of the magnetic yoke **201**, is disposed in the central cylinder portion **205** of the spool **204** so as to be able to slide up and down. A peripheral flange portion **216** protruding outward in a radial direction is formed on the movable plunger **215**, on an upper end portion protruding upward from the upper magnetic yoke **210**.

Also, a permanent magnet **220** formed in an annular shape, whose external form is, for example, rectangular and which has a circular central aperture **221** is fixed to the upper surface of the upper magnetic yoke **210** so as to enclose the peripheral flange portion **216** of the movable plunger **215**. The permanent magnet **220** is magnetized in an up-down direction, that is, a thickness direction, so that the upper end side is, for example, an N-pole while the lower end side is an S-pole.

Further, an auxiliary yoke **225** of the same external form as the permanent magnet **220**, and having a through hole **224** with an inner diameter smaller than the outer diameter of the peripheral flange portion **216** of the movable plunger **215**, is fixed to the upper end surface of the permanent magnet **220**. The peripheral flange portion **216** of the movable plunger **215** contacts the lower surface of the auxiliary yoke **225**.

The form of the permanent magnet **220** not being limited to that heretofore described, it can also be formed in a circular ring form, and in fact, the external form can be any form, such as circular or polygonal, provided that the inner peripheral surface is of a form tailored to the form of the peripheral flange portion **216**.

Also, the connecting shaft **131** that supports the movable contact **130** is screwed to the upper end surface of the movable plunger **215**.

Further, the movable plunger **215** is covered with a cap **230** formed in a bottomed tubular form made of a non-magnetic body, and a flange portion **231** formed extending outward in a radial direction on an opened end of the cap **230** is seal joined to the lower surface of the upper magnetic yoke **210**. By so doing, a hermetic receptacle, wherein the contact housing case **102** and cap **230** are in communication via the through hole **210a** of the upper magnetic yoke **210**, is formed. Further, a gas such as hydrogen gas, nitrogen gas, a mixed gas of hydrogen and nitrogen, air, or SF₆ is encapsulated inside the hermetic receptacle formed by the contact housing case **102** and cap **230**.

Next, a description will be given of an operation of the heretofore described embodiment.

For now, it is assumed that the fixed contact **111** is connected to, for example, a power supply source that supplies a large current, while the fixed contact **112** is connected to a load.

In this state, the exciting coil **208** in the electromagnet unit **200** is in a non-excited state, and there exists a released state wherein no exciting force causing the movable plunger **215** to descend is being generated in the electromagnet unit **200**. In this released state, the movable plunger **215** is urged in an upward direction away from the upper magnetic yoke **210** by the return spring **214**. Simultaneously with this, a suctioning force caused by the permanent magnet **220** acts on the auxiliary yoke **225**, and the peripheral flange portion **216** of the movable plunger **215** is suctioned. Because of this, the upper surface of the peripheral flange portion **216** of the movable plunger **215** contacts the lower surface of the auxiliary yoke **225**.

Because of this, the contact portions **130a** of the movable contact **130** in the contact mechanism **101** connected to the movable plunger **215** via the connecting shaft **131** are separated by a predetermined distance upward from the contact portions **118a** of the fixed contacts **111** and **112**. Because of this, the current path between the fixed contacts **111** and **112** is in an interrupted state, and the contact mechanism **101** is in a state wherein the contacts are opened.

In this way, as the urging force of the return spring **214** and the suctioning force of the annular permanent magnet **220** both act on the movable plunger **215** in the released state, there is no unplanned downward movement of the movable plunger **215** due to external vibration, shock, or the like, and it is thus possible to reliably prevent malfunction.

On the exciting coil **208** of the electromagnet unit **200** being excited in the released state, an exciting force is generated in the electromagnet unit **200**, and the movable plunger **215** is caused to descend against the urging force of the return spring **214** and the suctioning force of the annular permanent magnet **220**. The descent of the movable plunger **215** is stopped by the lower surface of the peripheral flange portion **216** contacting the upper surface of the upper magnetic yoke **210**.

By the movable plunger **215** descending in this way, the movable contact **130** connected to the movable plunger **215** via the connecting shaft **131** also descends, and the contact portions **130a** of the movable contact **130** contact the contact portions **118a** of the fixed contacts **111** and **112** with the contact pressure of the contact spring **134**.

Because of this, there exists a closed contact state wherein the large current of the external power supply source is supplied via the fixed contact **111**, movable contact **130**, and fixed contact **112** to the load.

At this time, an electromagnetic repulsion force is generated between the fixed contacts **111** and **112** and the movable contact **130** in a direction such as to cause the contacts of the movable contact **130** to open.

However, as the fixed contacts **111** and **112** are such that the contact conductor portion **115** is formed of the upper plate portion **116**, intermediate plate portion **117**, and lower plate portion **118**, as shown in FIG. 1, the current in the upper plate portion **116** and lower plate portion **118** and the current in the opposing movable contact **130** flow in opposite directions. Because of this, from the relationship between a magnetic field formed by the lower plate portions **118** of the fixed contacts **111** and **112** and the current flowing through the movable contact **130**, it is possible, in accordance with Fleming's left-hand rule, to generate a Lorentz force that presses

the movable contact **130** against the contact portions **118a** of the fixed contacts **111** and **112**.

Because of this Lorentz force, it is possible to oppose the electromagnetic repulsion force generated in the contact opening direction between the contact portions **118a** of the fixed contacts **111** and **112** and the contact portions **130a** of the movable contact **130**, and thus possible to reliably prevent the contact portions **130a** of the movable contact **130** from opening. Because of this, it is possible to reduce the pressing force of the contact spring **134** supporting the movable contact **130**, and possible to reduce the size of the contact spring **134**, and thus possible to reduce the size of the contact device **100**.

When interrupting the supply of current to the load in the closed contact state of the contact mechanism **101**, the exciting of the exciting coil **208** of the electromagnet unit **200** is stopped.

By so doing, the exciting force causing the movable plunger **215** to move downward in the electromagnet unit **200** stops, the movable plunger **215** is raised by the urging force of the return spring **214**, and the suctioning force of the annular permanent magnet **220** increases as the peripheral flange portion **216** nears the auxiliary yoke **225**.

As the movable plunger **215** rises, the movable contact **130** connected via the connecting shaft **131** rises. As a result of this, the movable contact **130** is contacting the fixed contacts **111** and **112** as long as contact pressure is applied by the contact spring **134**. Subsequently, it starts an opened contact state, wherein the movable contact **130** moves upward away from the fixed contacts **111** and **112** at the point at which the contact pressure of the contact spring **134** stops.

On the opened contact state starting, an arc is generated between the contact portions **118a** of the fixed contacts **111** and **112** and the contact portions **130a** of the movable contact **130**, and the state in which current is conducted continues due to the arc. At this time, as the insulating cover **121** is mounted covering the upper plate portion **116** and intermediate plate portion **117** of the contact conductor portion **115** of the fixed contacts **111** and **112**, it is possible to cause the arc to be generated only between the contact portions **118a** of the fixed contacts **111** and **112** and the contact portions **130a** of the movable contact **130**. Because of this, it is possible to reliably prevent the arc from moving above the contact conductor portion **115** of the fixed contacts **111** and **112**, thereby stabilizing the arc generation state, and thus possible to improve arc extinguishing performance. Moreover, as both side surfaces of the fixed contacts **111** and **112** are also covered by the insulating cover **121**, it is also possible to reliably prevent the leading edge of the arc from short circuiting.

Furthermore, as the surfaces of the fixed contacts **111** and **112** facing the upper plate portion **116** and intermediate plate portion **117** of the contact conductor portion **115** are covered by the insulating cover **121**, it is possible to bring the upper plate portion **116** and intermediate plate portion **117** and the movable contact **130** close together while maintaining the necessary insulating distance, and thus possible to reduce the height of the contact mechanism **101**, that is, the height in the direction in which the movable contact **130** can move.

Further, as the insulating cover **121** can be mounted on the fixed contacts **111** and **112** simply by the fitting portion **125** being fitted onto the small diameter portion **114h** of the fixed contacts **111** and **112**, it is possible to easily carry out the mounting of the insulating cover **121** on the fixed contacts **111** and **112**.

Furthermore, as the inner surface of the intermediate plate portion **117** of the fixed contacts **111** and **112** is covered by the magnetic plate **119**, a magnetic field generated by current

11

flowing through the intermediate plate portion 117 is shielded by the magnetic plate 119. Because of this, there is no interference between a magnetic field caused by the arc generated between the contact portions 118a of the fixed contacts 111 and 112 and the contact portions 130a of the movable contact 130 and the magnetic field caused by the current flowing through the intermediate plate portion 117, and it is thus possible to prevent the arc being affected by the magnetic field generated by the current flowing through the intermediate plate portion 117.

At this time, as the opposing magnetic pole faces of the arc extinguishing permanent magnets 143 and 144 are N-poles, and the outer sides thereof are S-poles, magnetic flux emanating from the N-poles, seen in plan view as shown in FIG. 6(a), crosses an arc generation portion of a portion in which the contact portion 118a of the arc extinguishing permanent magnets 143 and 144 fixed contact 111 and the contact portion 130a of the movable contact 130 are opposed, from the inner side to the outer side in the longitudinal direction of the movable contact 130, and reaches the S-pole, whereby a magnetic field is formed. In the same way, the magnetic flux crosses an arc generation portion of the contact portion 118a of the fixed contact 112 and the contact portion 130a of the movable contact 130, from the inner side to the outer side in the longitudinal direction of the movable contact 130, and reaches the S-pole, whereby a magnetic field is formed.

Consequently, the magnetic fluxes of the arc extinguishing magnets 143 and 144 both cross between the contact portion 118a of the fixed contact 111 and the contact portion 130a of the movable contact 130 and between the contact portion 118a of the fixed contact 112 and the contact portion 130a of the movable contact 130, in mutually opposite directions in the longitudinal direction of the movable contact 130.

Because of this, a current I flows from the fixed contact 111 side to the movable contact 130 side between the contact portion 118a of the fixed contact 111 and the contact portion 130a of the movable contact 130, and the orientation of the magnetic flux ϕ is in a direction from the inner side toward the outer side, as shown in FIG. 6(b). Because of this, in accordance with Fleming's left-hand rule, a large Lorentz force F acts toward the arc extinguishing space 145, perpendicular to the longitudinal direction of the movable contact 130 and perpendicular to the switching direction of the contact portion 118a of the fixed contact 111 and the movable contact 130, as shown in FIG. 6(c).

Due to the Lorentz force F, an arc generated between the contact portion 118a of the fixed contact 111 and the contact portion 130a of the movable contact 130 is greatly extended so as to pass from the side surface of the contact portion 118a of the fixed contact 111 through the inside of the arc extinguishing space 145, reaching the upper surface side of the movable contact 130, and is extinguished.

Also, at the lower side and upper side of the arc extinguishing space 145, magnetic flux inclines to the lower side and upper side with respect to the orientation of the magnetic flux between the contact portion 118a of the fixed contact 111 and the contact portion 130a of the movable contact 130. Because of this, the arc extended to the arc extinguishing space 145 is further extended by the inclined magnetic flux in the direction of the corner of the arc extinguishing space 145, it is possible to increase the arc length, and thus possible to obtain good interruption performance.

Meanwhile, the current I flows from the movable contact 130 side to the fixed contact 112 side between the contact portion 118a of the fixed contact 112 and the movable contact 130, and the orientation of the magnetic flux ϕ is in a rightward direction from the inner side toward the outer side, as

12

shown in FIG. 6(b). Because of this, in accordance with Fleming's left-hand rule, a large Lorentz force F acts toward the arc extinguishing space 145 side, perpendicular to the longitudinal direction of the movable contact 130 and perpendicular to the switching direction of the contact portion 118a of the fixed contact 112 and the movable contact 130.

Due to the Lorentz force F, an arc generated between the contact portion 118a of the fixed contact 112 and the movable contact 130 is greatly extended so as to pass from the upper surface side of the movable contact 130 through the inside of the arc extinguishing space 145, reaching the side surface side of the fixed contact 112, and is extinguished.

Also, at the lower side and upper side of the arc extinguishing space 145, as heretofore described, magnetic flux inclines to the lower side and upper side with respect to the orientation of the magnetic flux between the contact portion 118a of the fixed contact 112 and the contact portion 130a of the movable contact 130. Because of this, the arc extended to the arc extinguishing space 145 is further extended by the inclined magnetic flux in the direction of the corner of the arc extinguishing space 145, it is possible to increase the arc length, and thus possible to obtain good interruption performance.

Meanwhile, in the engaged state of the electromagnetic contactor 10, when adopting a released state in a state wherein a regenerative current flows from the load side to the direct current power source side, the direction of current in FIG. 6(b) is reversed, meaning that the Lorentz force F acts on the arc extinguishing space 146 side, and except that the arc is extended to the arc extinguishing space 146 side, the same arc extinguishing function is fulfilled.

At this time, as the arc extinguishing permanent magnets 143 and 144 are disposed in the magnet housing cylinders 141 and 142 formed in the insulating cylinder 140, the arc does not directly contact the arc extinguishing permanent magnets 143 and 144. Because of this, it is possible to stably maintain the magnetic characteristics of the arc extinguishing permanent magnets 143 and 144, and thus possible to stabilize interruption performance.

Also, as it is possible to cover and insulate the inner peripheral surface of the metal tubular body 104 with the insulating cylinder 140, there is no short circuiting of the arc when the current is interrupted, and it is thus possible to reliably carry out current interruption.

Furthermore, as it is possible to carry out the insulating function, the function of positioning the arc extinguishing permanent magnets 143 and 144, the function of protecting the arc extinguishing permanent magnets 143 and 144 from the arc, and the insulating function preventing the arc from reaching the external metal tubular body 104 with the one insulating cylinder 140, it is possible to reduce manufacturing cost.

Also, as the movable contact guide members 148 and 149 that slide against a side edge of the movable contact are formed protruding on the permanent magnet housing cylinders 141 and 142 housing the arc extinguishing permanent magnets 143 and 144 in positions facing the movable contact 130, it is possible to reliably prevent turning of the movable contact 130.

Also, as it is possible to increase the distance between the side edges of the movable contact 130 and the inner peripheral surface of the insulating cylinder 140 by the thickness of the arc extinguishing permanent magnets 143 and 144, it is possible to provide sufficient arc extinguishing spaces 145 and 146, and thus possible to reliably carry out arc extinguishing.

Furthermore, as the movable contact guide members 148 and 149 that slide against a side edge of the movable contact

13

are formed protruding on the magnet housing cylinders **141** and **142** housing the arc extinguishing permanent magnets **143** and **144** in positions opposing the movable contact **130**, it is possible to reliably prevent turning of the movable contact **130**.

In this way, according to the embodiment, a C-shape is adopted for the contact conductor portions **115** of the pair of fixed contacts **111** and **112**, the intermediate plate portion **117** and upper plate portion **116** are disposed in proximity to the contact portions **118a** so as to generate a Lorentz force opposing the electromagnetic repulsion force in the engaged state, and furthermore, the contact conductor portions **115** of the pair of fixed contacts **111** and **112** and the contact spring **134** are disposed in a parallel state in the extension direction of the movable contact **130**, because of which it is possible to reduce the height of the contact device **100**, and also possible to reduce the width, and thus possible to reduce the size of the whole contact device **100**. Moreover, it is possible to generate a Lorentz force opposing the electromagnetic repulsion force generated when engaging in the contact conductor portions **115** of the fixed contacts **111** and **112** between the contact portions **118a** of the fixed contacts **111** and **112** and the contact portions **130a** of the movable contact **130**. Because of this, it is possible to reduce the urging force of the contact spring **134**, thus reducing the size thereof, and possible to reduce the height of the contact device **100** by this amount. Furthermore, the depressed portion **132** protruding on the side opposite to that of the fixed contact support insulating substrate **105** forming an upper plate, that is, the lower side, is formed in the position in which the movable contact **130** contacts the contact spring **134**, because of which it is possible to further reduce the protruding height of the contact spring **134**.

Incidentally, when omitting the contact conductor portion **115**, forming a contact portion on the lower end of the support conductor portion **114**, and disposing the movable contact **130** so as to be capable of contacting to and separating from the contact portion from below, the contact spring, movable contact, and fixed contacts are disposed in series in a vertical direction, and the height of the contact device **100** increases.

Next, a description will be given of a second embodiment of the invention, based on FIG. 8.

In the second embodiment, the configuration of the contact housing case is changed.

That is, in the second embodiment, the contact housing case **102** is configured of a tubular portion **301** and an upper surface plate portion **302** closing off the upper end of the tubular portion **301** being formed integrally of a ceramic or a synthetic resin material, thereby forming a tub-form body **303**, a metal foil being formed on an opened end surface side of the tub-form body **303** by a metalizing process, and a metal connection member **304** being seal joined to the metal foil, as shown in FIG. 10 and FIG. 2(b).

Further, a bottom plate portion **305** formed of, for example, a synthetic resin, corresponding to the bottom plate portion **104b** in the first embodiment, is disposed on the inner peripheral surface on the bottom surface side of the tub-form body **303**.

Also, insertion holes **306** and **307** in which are inserted the fixed contacts **111** and **112** are formed in the upper surface plate portion **302**, in the same way as in the fixed contact support insulating substrate **105**, and the fixed contacts **111** and **112** are supported by the insertion holes **306** and **307**, in the same way as in the first embodiment.

Configurations other than this have the same configurations as in the first embodiment, the same reference signs are

14

given to portions corresponding to those in FIG. 1, and a detailed description thereof will be omitted.

According to the second embodiment, the contact housing case **102** is configured of the tub-form body **303** integrally molded of an insulating material, because of which it is possible to easily form the airtight contact housing case **102** in a small number of man-hours, and possible to reduce the number of parts.

In the first and second embodiments, a description has been given of a case wherein the opposing magnetic pole faces of the arc extinguishing permanent magnets **143** and **144** are N-poles but, not being limited to this, it is also possible to obtain the same advantages as in the heretofore described embodiments when arranging so that the opposing magnetic pole faces of the arc extinguishing permanent magnets **143** and **144** are S-poles, excepting that the direction in which the magnetic flux crosses the arc and the direction of the Lorentz force are reversed.

Also, in the first and second embodiments, a description has been given of a case wherein the contact housing case **102** is formed by brazing the metal tubular body **104** and the fixed contact support insulating substrate **105** that closes off the upper end of the tubular body **104**, but not being limited to this. That is, the contact housing case **102** may be integrally formed in a tub-form of an insulating material, such as a ceramic or a synthetic resin material.

Also, in the first and second embodiments, a description has been given of a case wherein the contact conductor portion **115** is formed in the fixed contacts **111** and **112** but, not being limited to this, an L-shaped portion **160**, of a form such that the upper plate portion **116** of the contact conductor portion **115** is omitted, may be connected to the support conductor portion **114**, as shown in FIGS. 9(a) and 9(b).

In this case too, in the closed contact state wherein the movable contact **130** contacts the fixed contacts **111** and **112**, it is possible to cause magnetic flux generated by the current flowing through a vertical plate portion of the L-shaped portion **160** to act on portions in which the fixed contacts **111** and **112** and the movable contact **130** are in contact. Because of this, it is possible to increase the magnetic flux density in the portions in which the fixed contacts **111** and **112** and the movable contact **130** are in contact, generating a Lorentz force that opposes the electromagnetic repulsion force.

Also, in the heretofore described embodiments, a description has been given of a case wherein the movable contact **130** has the depressed portion **132** in a central portion thereof but, not being limited to this, the depressed portion **132** may be omitted, forming a flat plate, as shown in FIGS. 10(a) and 10(b).

Also, in the first and second embodiments, a description has been given of a case wherein the connecting shaft **131** is screwed to the movable plunger **215**, but the movable plunger **215** and connecting shaft **131** may also be formed integrally.

Also, a description has been given of a case wherein the connection of the connecting shaft **131** and movable contact **130** is such that the flange portion **131a** is formed on the leading end portion of the connecting shaft **131**, and the lower end of the movable contact **130** is fixed with a C-ring after the connecting shaft **131** is inserted into the contact spring **134** and movable contact **130**, but not being limited to this. That is, a positioning large diameter portion may be formed protruding in a radial direction in the C-ring position of the connecting shaft **131**, the contact spring **134** disposed after the movable contact **130** contacts the large diameter portion, and the upper end of the contact spring **134** fixed with the C-ring.

Also, in the heretofore described embodiments, a description has been given of a case wherein a hermetic receptacle is

configured of the contact housing case **102** and cap **230**, and gas is encapsulated inside the hermetic receptacle but, this not being limiting, the gas encapsulation may be omitted when the interrupted current is small.

Reference Signs List

10 . . . Electromagnetic contactor, **11** . . . External insulating receptacle, **100** . . . Contact device, **101** . . . Contact mechanism, **102** . . . Contact housing case, **104** . . . Tubular body, **105** . . . Fixed contact support insulating substrate, **111**, **112** . . . Fixed contact, **114** . . . Support conductor portion, **115** . . . contact conductor portion, **116** . . . Upper plate portion, **117** . . . Intermediate plate portion, **118** . . . Lower plate portion, **118a** . . . Contact portion, **121** . . . Insulating cover, **122** . . . L-shaped plate portion, **123**, **124** . . . Side plate portion, **125** . . . Fitting portion, **130** . . . Movable contact, **130a** . . . Contact portion, **131** . . . Connecting shaft, **132** . . . Depressed portion, **134** . . . Contact spring, **140** . . . Insulating cylinder, **141**, **142** . . . Magnet housing cylinder, **143**, **144** . . . Arc extinguishing permanent magnet, **145**, **146** . . . Arc extinguishing space, **160** . . . L-shaped portion, **200** . . . Electromagnet unit, **201** . . . Magnetic yoke, **203** . . . Cylindrical auxiliary yoke, **204** . . . Spool, **208** . . . Exciting coil, **210** . . . Upper magnetic yoke, **214** . . . Return spring, **215** . . . Movable plunger, **216** . . . Peripheral flange portion, **220** . . . Permanent magnet, **225** . . . Auxiliary yoke, **301** . . . Tubular portion, **302** . . . Upper surface plate portion, **303** . . . Tub-form body, **304** . . . Connection member, **305** . . . Bottom plate portion

What is claimed is:

1. An electromagnetic contactor, comprising:

a contact device including a pair of fixed contacts spaced at a predetermined interval away from each other, each having a support conductor portion supported on an upper plate of a contact housing case, and a contact conductor portion connected to an end portion of the support conductor portion inside the contact housing case, the contact conductor portion being integrally formed in a C-shape and including a contact plate portion having at least a contact portion facing the upper plate and disposed in parallel with the upper plate, a first connecting plate portion formed in proximity to the contact portion on an outer end portion of the contact plate portion and extending toward the upper plate, and a second connecting plate portion disposed in parallel to the contact plate portion between an end portion of the first connecting plate portion on an upper plate side and the support conductor portion; and a movable contact mounted onto a connecting shaft connected to a drive portion through a contact spring on an end portion of the connecting shaft on the upper plate side, and disposed to

face the contact portion of each of the pair of fixed contacts from the upper plate side;
 a magnetic plate formed in a C-shape and disposed inside the first connecting plate portion to cover an inner side surface of the first connecting plate portion;
 an insulating cover including an L-shaped plate portion disposed to sandwich the magnetic plate with the first connecting plate portion and to cover an inner side surface of the first connecting plate portion through the magnetic plate and an inner side surface of the second connecting plate portion, and side plate portions protruding outwardly from two side portions of the L-shaped plate portion to cover side surfaces of the first and second connecting portions,
 wherein the contact conductor portion is formed in the C-shape to generate a Lorentz force opposing an electromagnetic repulsion force to separate the movable contact from the pair of fixed contacts when current is supplied to the pair of fixed contacts and the movable contact.

2. The electromagnetic contactor according to claim **1**, wherein the movable contact includes a depressed portion protruding toward a side opposite to the upper plate side in a portion where the movable contact contacts the contact spring.

3. The electromagnetic contactor according to claim **2**, wherein the movable contact includes a through hole formed at a center portion thereof, the connecting shaft is inserted into the through hole such that the contact spring is disposed between the end portion of the connecting shaft on the upper plate side and the depressed portion of the movable contact, and the drive portion is connected to the connecting shaft at another end portion thereof.

4. The electromagnetic contactor according to claim **1**, wherein the movable contact is formed in a flat plate shape parallel to the upper plate.

5. The electromagnetic contactor according to claim **1**, wherein the insulating cover includes a fitting portion protruding inwardly from each of the side plate portions, and an inner side surface of the fitting portion is curved to fit each of the pair of fixed contacts.

6. The electromagnetic contactor according to claim **1**, wherein the L-shaped plate portion and the side plate portions of the insulating cover are integrally formed to cover the inner side surfaces of the first and second connecting plate portions and the side surfaces of the first and second connecting portions all at once.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 9,117,611 B2
APPLICATION NO. : 14/116226
DATED : August 25, 2015
INVENTOR(S) : Yasuhiro Naka et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Specification

Please change column 3, line 42, from "... in FIG. L" to --... in FIG. 1.--.

Please change column 3, line 43, from "... are illustrated ..." to --... are illustrations ...--.

Please change column 7, line 4, from "... function protecting ..." to --... function of protecting ...--.

Please change column 10, line 61, from "... portion 114h of ..." to --... portion 114b of ...--.

Signed and Sealed this
Ninth Day of February, 2016



Michelle K. Lee
Director of the United States Patent and Trademark Office