

US009124879B2

(12) **United States Patent**
Beyabani

(10) **Patent No.:** **US 9,124,879 B2**
(45) **Date of Patent:** ***Sep. 1, 2015**

(54) **SYSTEM FOR PROACTIVELY TROUBLESHOOTING SET TOP BOX ISSUES**

(71) Applicant: **Verizon Patent and Licensing Inc.**,
Basking Ridge, NJ (US)

(72) Inventor: **Syed Z. Beyabani**, Irving, TX (US)

(73) Assignee: **Verizon Patent and Licensing Inc.**,
Basking Ridge, NJ (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 65 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **14/158,162**

(22) Filed: **Jan. 17, 2014**

(65) **Prior Publication Data**

US 2014/0132777 A1 May 15, 2014

Related U.S. Application Data

(63) Continuation of application No. 12/164,547, filed on Jun. 30, 2008, now Pat. No. 8,656,444.

(51) **Int. Cl.**
G06F 11/07 (2006.01)
H04N 17/04 (2006.01)

(52) **U.S. Cl.**
CPC **H04N 17/04** (2013.01); **G06F 11/0709** (2013.01); **G06F 11/0748** (2013.01); **G06F 11/0751** (2013.01); **G06F 11/0793** (2013.01)

(58) **Field of Classification Search**
CPC . H04N 17/04; G06F 11/0709; G06F 11/0748; G06F 11/0751; G06F 11/0793

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,606,669	A *	2/1997	Bertin et al.	709/223
7,032,016	B2 *	4/2006	Cerami et al.	709/223
7,467,067	B2	12/2008	Marvasti	
2003/0151621	A1 *	8/2003	McEvelly et al.	345/744
2004/0054771	A1	3/2004	Roe et al.	
2004/0088734	A1	5/2004	Donlan et al.	
2005/0183130	A1	8/2005	Sadja et al.	
2007/0136476	A1	6/2007	Rubinstein	
2007/0162932	A1 *	7/2007	Mickle et al.	725/37
2008/0077358	A1	3/2008	Marvasti	

FOREIGN PATENT DOCUMENTS

WO 02/082814 10/2002


* cited by examiner

Primary Examiner — Hai V Tran

(57) **ABSTRACT**

A system for proactively troubleshooting set top box issues may include a media distribution network with a remote requesting device and a programming guide server. The programming guide server may be configured to identify a guide data retrieval profile of the requesting device, compare the guide data retrieval profile to an expected profile, and flag the requesting device for troubleshooting based on a lack of correspondence between the retrieval profile and the expected profile. Additionally methods for discovering related devices, predicting that the related devices also require troubleshooting, and limiting restorative measures to only those devices that have been confirmed to be affected by a service issue may also be implemented by the system.

17 Claims, 4 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5

1

SYSTEM FOR PROACTIVELY TROUBLESHOOTING SET TOP BOX ISSUES

CROSS REFERENCE TO RELATED APPLICATIONS

This application is a continuation application of U.S. patent application Ser. No. 12/164,547, filed on Jun. 30, 2008, the content of which is hereby incorporated by reference in its entirety.

BACKGROUND

Customer service related expenses can impose significant costs for a subscriber based media and telecommunication system. Such expenses may include staffing a telephone support helpdesk to answer and address customer service issues. Additionally, issues that cannot be resolved by phone may require a technician to make an on-site visit to the subscriber or customer. Training support staff and technicians may further add to customer service expenses.

Many subscriber based media and telecommunication systems, or simply subscriber based systems, deliver media content to customers with a content processing device such as a set top box (STB). As the interface between the customer and the subscriber based system, the STB frequently may be the source of customer service issues. Accordingly, customer service expenses may be reduced by identifying and handling service issues involving STBs before the customer discovers the issue.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a system diagram of a system for proactively troubleshooting set top box issues;

FIG. 2 is an exemplary dataflow diagram depicting the delivery of programming guide data;

FIG. 3 is an illustrative representation of an exemplary device association hierarchy;

FIG. 4 is a flowchart depicting exemplary steps and decisions related to handling a request for programming guide data; and

FIG. 5 is a flowchart depicting exemplary steps and decisions related to proactively troubleshooting set top box issues.

DETAILED DESCRIPTION

Exemplary illustrations of a system for proactively troubleshooting set top box issues are described below. In the interest of clarity, not all features of an actual implementation are described in this specification. It will of course be appreciated that in the development of any such actual illustration, numerous implementation-specific decisions must be made to achieve the specific goals of the developer, such as compliance with system-related and business-related constraints that will vary from one implementation to another. Moreover, it will be appreciated that such a development effort might be complex and time-consuming, but would nevertheless be a routine undertaking for those having the benefit of this disclosure.

Referring now to the drawings wherein like numerals indicate like or corresponding parts throughout the several views, exemplary illustrations are provided.

FIG. 1 illustrates an exemplary system 100 for proactively troubleshooting set top box issues. Details of the elements depicted in the figures are included following a brief func-

2

tional overview of the system 100. Customer service issues for subscriber based systems, e.g., cable and fiber optic television systems, frequently relate to content processing devices, or so-called set top boxes (STB). The behavior and activities of the STB may be monitored to proactively detect service issues prior to receiving a service call from a customer. Moreover, the STB may communicate with other elements of the multimedia subscriber system in an anticipated and regular manner. Accordingly, by reviewing the communications of the STB, anomalies may be recognized as indicative of a service issue.

In one exemplary approach, communications between the STB and an interactive programming guide server may be logged and reviewed for anomalies. Comparisons between an expected set of communications and an actual set of communications may be made in order to recognize the anomalies and subsequently flag the STB for troubleshooting. The hierarchical network architecture of subscriber based systems may allow for a problem with one device to predict a problem with another device associated with common node of the network at a higher level in the hierarchy. Accordingly, the hierarchical relationships of the network devices, including the STBs, may be analyzed to discover other STBs that may be in need of troubleshooting and restorative measures. To confirm the prediction, logs of the communications between the discovered STB and the interactive programming guide server may be reviewed for anomalies. Confirming the prediction may allow troubleshooting and restorative measures to be limited to only those STBs actually affected by a service issue, which may improve customer service by avoiding unnecessary STB maintenance.

Turning now to FIG. 1, an exemplary system 100 for proactively troubleshooting set top box issues. The system 100 generally includes a customer premises network 101 in which media content 140 (e.g., media programming such as interactive or streamed media content), including any one or more of text, images, audio, video, multimedia, etc., may be provided to a media playback device 102 through a content processing device 104 attached to a customer premises network 101. The customer premises network 101 may receive media content 140 from a head end 116 via a media distribution network 114.

The customer premises network 101 may encompass one or more devices within a customer premises such as one or more content processing devices 104a-b. The content processing device 104 may be a set top box (STB) or similar device for receiving a media signal from a network and for providing media content programming, e.g., audio, video, interactive content, etc., to a media playback device 102. The content processing device 104 may be controlled by a user through any control mechanism, e.g., a remote control (not shown), thereby facilitating the selection and playing of content 140 through the media playback device 102. A control mechanism may include numeric keys for selecting channels of video programming, as well as other keys for making selections and requests according to menus displayed on the media playback device 102, in addition to arrow keys and the like for selecting channels and items in a menu, changing volume levels, etc. An example of the content processing device 104 is set top box model number QIP6400 made by Motorola, Inc. of Schaumburg, Ill.

A router 108 may establish and operate, or at least connect to, a network such as a home network or local area network (LAN), and may route certain communications within customer premises network 101. The router 108 may provide connections to one or more computing devices 110. For example the computing devices 110 may be connected to the

router **108** using a wireless connection, a network cable such as a “Cat5” cable, or the like. Further, the computing devices **110** are each uniquely addressable by the router **108** according to a networking protocol. For example, in one exemplary approach, Dynamic Host Configuration Protocol (DHCP) in combination with Network Address Translation (NAT) may dynamically assign Internet Protocol (IP) addresses to computing devices **110**. In one exemplary approach, the assigned IP addresses may only be accessible to devices such as devices **110** that are part of the customer premises network **101** via the router **108**.

The media playback devices **102a**, **102b** may include a variety of equipment alone or in combination, such as a video receiver, including a conventional television or a hi-definition television (HDTV), audio equipment including an amplifier and speakers, or devices that incorporate the capability to simultaneously, or near simultaneously, process different types of media content **140** such as video, audio, text data, etc. The media playback device **102** may be connected to, and receive media content from, the content processing device **104**.

In the illustrated exemplary system **100**, fiber optic cable may be used to provide both different data streams including at least on data stream representing media content **140** to the customer premises network **101**. An alternative data stream may be directed to router **108** for consumption by one or more devices **110**, the data stream also potentially including media content **140** and one or more of the features discussed below.

An optical line terminal (OLT) **126** may serve as a terminus for an optical network or an optical line. The OLT **126** may provide data, including media content **140**, to one or more optical network terminals (ONTs) **122**. The ONT **122** is generally situated adjacent to a customer premises, for the purpose of providing data received over an optical line to customer premises network **101**, including content processing device **104**. The ONT **122** may further bridge the network connection to a coaxial cable based network within the customer premises. One or more fiber distribution hubs (not shown) including an optical splitter may be positioned within the system **100**, e.g., between the OLT **126** and the ONT **122**. For example, the fiber distribution hub may split a main fiber feed going into a neighborhood, or like collection of customers, to provide individual fiber lines to the ONT **122** serving a particular customer premises **101**.

A gateway router **124** allows content processing device **104** to access the media distribution network **114** as well as a packet network **118**, e.g. the Internet. By communicating with router **124**, content processing device **104** is able to obtain a network address such as an internet protocol (IP) address, thereby enabling content processing device **104** to make requests to and to receive data from, an IPG server **142**, and VOD server **144**. The gateway router **124** may interconnect the customer premises network **101** with the media distribution network **114**, as well as with the packet network **118**. Accordingly, FIG. 1 illustrates a hybrid network system **100** in which media content **140** is transported over media distribution network **114** and alternative data is transported over the packet network **118**, both data streams being received by customer premises network **101** through a fiber optic line. However, it should be understood that other approaches are envisioned in which the content processing device **104** receives both data streams by way of media other than fiber optic cables to customer premises network **101**.

In an exemplary approach, the media distribution network **114** is a network for delivering media content **140** to the customer premises network **101**. For example, the network **114** may include hardware and software for providing media

content **140** via coaxial cable and/or fiber optic cable, and network equipment, e.g., routers, switches, etc., as described further below. The media content **140** may be provided to the media distribution network **114** from a head end **116**, which collects, aggregates, formats, and encodes the content according to the requirements of the media distribution network **114**.

Various elements may be included as part of media distribution network **114** to provide media or other information to content processing device **104**. A video distribution router (VDR) **148** may provide network connectivity to the elements of the media distribution network **114**, and may further connect with the gateway router **124**. For example, an interactive program guide (IPG) server **142** may selectively communicate through routers **124**, **148** to provide an interactive program guide to the content processing device **104**. A video on demand (VOD) server **144**, for providing telecommunications customers with video content “on demand,” may also be provided to selectively communicate with content processing device **104**, generally via media distribution network **114**. Additionally, an activation server **146** may be provided to generally authorize and provision content processing device **104**. For example, entitlement management data (EMM) may flow from activation server **146** when content processing device **104** is initially set up or placed in communication with system **100**. EMM data may be provided by a service provider to authorize certain video content, e.g., subscriptions or packages of channels, to be decoded by content processing device **104**, thereby generally preventing access from an unauthorized device. The IPG server **142**, VOD server **144**, and activation server **146** may selectively communicate with content processing device **104** via Video Distribution Router (VDR) **148**, which links servers **142**, **144**, **146** with media distribution network **114**.

A request module **112** may include software instructions, or the like, for controlling at least some aspects of the content processing device **104**. As illustrated, the request module **112** may be a software component implemented by the content processing device **104**. The request module may be configured to retrieve programming guide data **205** (FIG. 2) from the IPG server **142**. The request module **112** may communicate with an IPG module **150**. The IPG module may include software instructions, or the like, for controlling at least some aspects of the IPG server **142**. The request module **112** may be a software component implemented by the IPG server **142** and configured to receive and handle requests for programming guide data **205**. Exemplary interactions between the request module **112** and the IPG module **150** will be discussed below with respect to FIG. 2.

The media distribution network **114** and the packet network **118** are generally Internet protocol (IP) networks. As such, networks **114** and **118** generally use one or more inter-networking protocols for transporting data, such as user datagram protocol (UDP), transport control protocol (TCP), hypertext transfer protocol (HTTP), etc. Further, networks **114** and **118** may include a variety of networks such as a wide area network (WAN), e.g., the Internet, a local area network (LAN), etc. The networks **114** and **118** may be used to transport a variety of data, including multimedia data such as audio data and video data. Accordingly, it is to be understood that other approaches are envisioned in which networks **114** and **118** are in fact combined into a single network, or in which media distribution network **114** is simply omitted, wherein the packet network **118** is used to provide media content **140** to content processing device **104**.

FIG. 2 illustrates an exemplary dataflow **200** of the delivery of programming guide data **205** to a content processing device **104**. The dataflow **200** includes the request-response

cycle between the request module **112** and the IPG module **150**. As explained above, the IPG module **150** may receive and handle requests for programming guide data **205**. The request module **112**, operating on the content processing device **104** may initiate requests for the programming guide data **205** on a periodic basis. In one exemplary approach, the request for guide data **205** may occur on a daily basis. The particular timing of the request may be coordinated with requests from other content processing devices **104** to avoid over burdening the IPG server **142**.

Guide data **205** may be logically divided into portions related to a period of time. For example, a portion may contain all of the programming listings for a particular day. A request for guide data **205** may include sub-requests for a plurality of portions. For example, the request for guide data **205** may include sub-requests for fourteen portions, with each portion including the listings for a respective day of a fourteen day period. Notably, the request module **112** may request data **205** that includes listings for a plurality of days, e.g., two weeks worth of listings, despite making daily requests. Such a pattern of requests may serve a variety of purposes. For example, the pattern of requests allows a viewer to see programming listings for a multi-day period. Moreover, unlike a printed programming guide that also shows multiple days of programming listings, corrections and other changes may be reflected each time the data is refreshed, e.g., each day. Additionally, this scheme provides a failsafe for a day, or days, when fresh programming guide data **205** is unavailable for any reason.

Because of the regularity of the retrieval of the programming guide data **205**, any interruption thereof may be symptomatic of a partial or complete service issue affecting the content processing device **104**. However, given that guide data **205** may be retrieved for a number of days at a time, any problems developed by the content processing device **104**, such as a service issue that prevents the retrieval of fresh programming guide data **205**, may not become apparent to the subscribing customer until the conclusion of the time period for which guide data was previously retrieved, e.g., fourteen days. Accordingly, the system **100** may have a period of time, e.g., fourteen days, to proactively troubleshoot the device **104** for partial service issues prior to the issue being noticed by the subscribing customer.

The communications between the request module **112** and the IPG module **150** may be analyzed to recognize anomalies therein. In one exemplary approach, the communications may be analyzed in an on-the-fly manner, or as they occur. In another exemplary approach, the communications may be logged for later analysis. The pattern of communications between the request module **112** and the IPG module **150** for a particular content processing device **104** may be collectively referred to as a retrieval profile **210**. Moreover, a model pattern of communications that would occur if the content processing device **104** is functioning properly may be referred to as an expected retrieval profile **215**. Accordingly, the retrieval profile **210** may be compared to the expected retrieval profile **215** to detect anomalies. An anomaly may be detected from a lack of correspondence between the retrieval profile **210** and the expected retrieval profile **215**.

As noted above, the communications between the request module **112** and the IPG module **150** occur throughout a request-response cycle. Accordingly, some of the communications relate to requests made by the requests module **112**, and some of the communications relate to the responses sent by the IPG module **150**. Thus, the retrieval profile may be either a request profile **220** or a response profile **225**. Similarly, the expected retrieval profile **215** may be either an

expected request profile **230** or an expected response profile **225**. The request profile **220** may include an indication of what guide data **205** was requested by the content processing device **104**, e.g., guide data **205** for a particular time. The response profile **225** may include an indication of whether the retrieval request was fulfilled. For example, the content processing device **104** may send an acknowledgement that that requested guide data **205** was successfully retrieved. The acknowledgement may be recorded in the response profile **225**. The detection of anomalies may be based on a lack of correspondence between the request profile **220** and the expected request profile **230** or between the response profile **225** and the expected response profile **235**. The detection of an anomaly may result in the content processing device **104** being flagged for troubleshooting. Moreover, the device **104** may be flagged for troubleshooting without the knowledge of the subscribing customer.

The hierarchical nature of the media distribution network **114** and the customer premises network **101** may result in a service issue affecting more than one content processing device **104**. Moreover, the content processing devices **104** affected by a service issue may be related or associated based on the topography of the networks **114**, **101**. Turning now to FIG. **3**, an exemplary device association hierarchy **300** depicts the relationships between content processing devices **104**. In one exemplary approach, local franchising authorities (LFAs) may be represented at an LFA level **305** at the highest level of the hierarchy **300**. The LFA may be a municipality, or the like, and therefore segment the networks **114**, **101** across a geographic and political region. However, in some exemplary approaches, larger geographic regions, e.g., a state or other collection of LFAs, may be represented at an even higher level of the hierarchy **300**.

Each LFA may include a plurality of neighborhoods. Accordingly, a neighborhood level **310** may include any fragment of an LFA such as a residential subdivision or development, a street, a block, or a collection thereof. The neighborhood level **310** may be associated with a fiber distribution hub (not show) that splits a fiber into individual customer or subscriber connections. As noted above, the fiber distribution hub may be positioned in the networks **114**, **101** between the OLT **126** and the ONT **122**. A circuit level **315** of the hierarchy **300** may represent the connection to an individual customer premises network **101**, such as a residential or business location of a subscribing customer. In particular, the ONT **122** may define the circuit level **315**. A device level **320** may represent particular content processing devices **104** at the customer premises network **101** and connected to a common ONT **122**.

Family terminology may be useful in describing the relationships between devices of the hierarchy **300**. For example, devices **104** at the device level **320** that are associated with the same ONT **122** at the circuit level **315** may be referred to as sibling devices. Devices that are associated with the same fiber distribution hub at the neighborhood level **310** may be referred to as first cousins. Further, devices that are associated with the same franchising authority at the LFA level **305** may be referred to as second cousins.

Each level of the device association hierarchy **300** may represent a point of control and provide a troubleshooting intervention point. For example, at the LFA level **305**, a plurality of fiber distribution hubs (not show) at the neighborhood level **310** may be controllable. At the neighborhood level **310**, a plurality of ONTs **122** at the circuit level **315** may be controllable. At the circuit level **315**, a plurality of content processing devices **104** at the device level may be controllable.

To address a potential service issue that may cause an anomaly in the retrieval profile as discussed above, the device **104** may need to have restorative measures performed thereon, e.g., by being serviced, restarted, patched, upgraded, etc. Because each level of the hierarchy **300** provides a point of control, the affected device **104** could be serviced by servicing a device at a higher level of the hierarchy **300**. For example, a fiber distribution hub at the neighborhood level **310** could be serviced to address a problem at the device level **320**. However, servicing a device may be disruptive to any customer that is not already experiencing a service issue. Accordingly, a higher degree of customer service may be achieved by accurately targeting any restorative measures to the smallest possible set of devices **104**.

As explained above, an anomaly in the retrieval profile **210** associated with the content processing device **104** may be indicative of a service issue affecting not only the device but also other devices related according to the device association hierarchy **300**. Accordingly, after flagging a device **104** for troubleshooting based on a lack of correspondence between the retrieval profile **210** and the expected retrieval profile **215**, related or associated devices may be discovered using the device association hierarchy **300**. In one exemplary approach, the discovery may broadly identify a large number of associated devices, e.g., all devices associated with a particular LFA at the LFA level **305**. While restorative measures could be performed on all of the discovered devices, this may lead to less than optimal customer service.

Accordingly, it may be predicted that the associated devices also require troubleshooting based on the association with the flagged device. The prediction may narrow the set of associated devices that will receive restorative measures. The prediction may be based on empirical analysis of historical service issues. In one exemplary approach, the prediction may be based on the family relationships between devices in the hierarchy **300**. For example once flagged for troubleshooting, all second cousin devices may be discovered, e.g., all devices associated at the LFA level **305**. However, based on historical or other information, it may be predicted that only first cousin or sibling devices should be subjected to troubleshooting and restorative measures.

The device association hierarchy **300** is not the only source of data available to the system **100** for identifying service issues. As explained above, the communications between the IPG module **150** and the request module **112** may be logged for later analysis. Therefore, the prediction may be confirmed using this retrieval log of communications. For each device that has been predicted to require restorative measures, the retrieval log may be analyzed for an associated retrieval profile **210**. The prediction may be confirmed by recognizing a lack of correspondence between the retrieval profile **210** and the expected profile **215**. To improve customer service by reducing unnecessary troubleshooting and servicing, any restorative measures may be limited to the initially flagged device and any associated devices that have a confirmed lack of correspondence between the retrieval profile **210** and the expected profile **215**.

Servers **142**, **144**, and **146**, PCs **110a-b**, and content processing devices **104a-b** may be any general purpose computing device, such as a PC, server, or a specialized device. Servers **142**, **144**, and **146**, PCs **110a-b**, and content processing devices **104a-b** may have software, such as an operating system in addition to the instructions of module **112** of the content processing devices **104a-b**. The operating system may also include a network protocol stack, for establishing network connections, e.g., connections to media distribution network **114** and packet network **118**.

Servers **142**, **144**, and **146**, PCs **110a-b**, and content processing devices **104a-b** may employ any of a number of user-level and embedded operating systems known, including, but by no means limited to, known versions and/or varieties of the Microsoft Windows® operating system, the Unix operating system (e.g., the Solaris® operating system distributed by Sun Microsystems of Menlo Park, Calif.), the AIX UNIX operating system distributed by International Business Machines of Armonk, N.Y., the Apple Mac OS X operating system, the Linux operating system, the Symbian mobile device operating system, the Android mobile stack developed by Google, etc. Computing devices may include any one of a number of computing devices known to those skilled in the art, including, without limitation, a computer workstation, a desktop, notebook, laptop, or handheld computer, mobile phones, smart phones, PDAs, or some other computing device known.

Servers **142**, **144**, and **146**, PCs **110a-b**, and content processing devices **104a-b** may each include instructions executable by one or more processing elements such as those listed above. Computer-executable instructions may be compiled or interpreted from computer programs created using a variety of programming languages and/or technologies known, including, without limitation, and either alone or in combination, Java™, C, C++, Visual Basic, Java Script, Perl, etc. In general, a processor (e.g., a microprocessor) receives instructions, e.g., from a memory, a computer-readable medium, etc., and executes these instructions, thereby performing one or more processes, including one or more of the processes described herein. Such instructions and other data may be stored and transmitted using a variety of known computer-readable media.

A computer-readable medium includes any medium that participates in providing data (e.g., instructions), which may be read by a computer. Such a medium may take many forms, including, but not limited to, non-volatile media, and volatile media. Non-volatile media include, for example, optical or magnetic disks and other persistent memory. Volatile media include dynamic random access memory (DRAM), which typically constitutes a main memory. Common forms of computer-readable media include, for example, a floppy disk, a flexible disk, hard disk, magnetic tape, any other magnetic medium, a CD-ROM, DVD, any other optical medium, punch cards, paper tape, any other physical medium with patterns of holes, a RAM, a PROM, an EPROM, a FLASH-EEPROM, any other memory chip or cartridge, a carrier wave as described hereinafter, or any other medium from which a computer can read.

FIG. 4 illustrates a flowchart of an exemplary process **400** for handling a request for programming guide data **205**. The IPG server **142** may include a computer-readable medium having stored instructions for carrying out certain operations described herein, including some or all of the operations described with respect to process **400**. For example, some or all of such instructions may be included in the IPG module **150**.

The process **400** begins in step **405** in which a request for programming guide data **205** may be received. In one exemplary approach, the IPG module **150** provides a data retrieval interface for receiving the request from the request module **112**. The request may correspond to a standard data retrieval protocol, such as the File Transfer Protocol (FTP), the Hyper Text Transfer Protocol (HTTP), etc., or may correspond to a private or customized data interchange protocol. Because the guide data **205** may be arranged by date and time, the request may typically specify a particular day or date range for which data should be retrieved.

Next, in step **410**, request and response retrieval profiles **220**, **225** may be created. As explained above, the communications between the IPG module **150** and the request module **112** may be logged in a retrieval log for later analysis. The retrieval log may include a series of time stamped line items indicating the particular processing steps that occurred. For example, a line item might indicate the network address of the requesting device **104**, the time of the request, and identification the particular data **205** that was requested. In one exemplary approach, the line items may simply be recorded in a text file, or the like, in a time ordered arrangement. However, in another exemplary approach, the line items may be organized or structured according to a particular operation and requestor. For example, the requests and response line items may be structured as request and response profiles **220**, **225**. Accordingly, in step **410**, the request and response profiles **220**, **225** may be created or initialized for later filling in steps **415** and **425** as will be discussed below. Similarly, if the line items of the retrieval log are not structured, the step of creating the request and response profiles **220**, **225** may be an implicit aspect of respective steps **415** and **425**.

Next, in step **415**, the request may be logged to the request profile **220**. In one exemplary approach, the request may include a plurality of sub-requests for portions of the programming guide data **205**. Accordingly, the overall request may be logged in step **410** by creating the request profile **220**, and each sub-request may be logged in this step **415**.

Next, in step **420**, the requested guide data **205** may be sent to the requestor. The requested guide data **205** may be transmitted over the networks **114**, **101** to the requesting content processing device **104**.

Next, in step **425**, an indication of whether the request was successfully fulfilled may be logged to the response profile **225**. For example, upon receipt of the guide data **205**, the request module **112** may send an acknowledgment to the IPG module **150** which may be logged to the response profile **225**.

Next, in step **430**, it may be determined whether additional requests need to be processed. As explained above, the request may include sub-requests for portions of the guide data **205**. For example, a day of program listings may be grouped together as a portion. The portion may be requested along with other portions. For example, the request module **112** may be configured to request fourteen days of programming guide data **205**. If there are additional requests, the process may return to step **415**.

If there are no remaining requests, process **400** may end.

FIG. **5** illustrates a flowchart of an exemplary process **500** for proactively troubleshooting set top box issues. The IPG server **142** may include a computer-readable medium having stored instructions for carrying out certain operations described herein, including some or all of the operations described with respect to process **500**. For example, some or all of such instructions may be included in the IPG module **150**.

The process **500** begins in step **505** in which the guide data retrieval log may be reviewed. The review of the log may be scheduled to occur automatically at a set time. For example, the log may be reviewed once a day. In another exemplary approach, the review of the log may occur in an on-demand manner. For example, a service technician may initiate a review during a customer service call. In another exemplary approach, the review step may be omitted entirely and process **500** may begin in step **510** discussed below. For example, process **500** may be implemented concurrently with the request-response cycle discussed with respect to FIG. **2**.

Next, in step **510**, a retrieval profile **210** may be identified. In one exemplary approach, the identification may be made

from the retrieval log line items or profile structures discussed above with respect to process **400**. For example, the retrieval log may be searched for the request profile **220** for a particular device **104**. However, in another exemplary approach, the profile **210** may be identified on-the-fly during the guide data **205** request-response cycle. For example, the request for guide data **205** made by the request module **112** may be identified immediately as a request profile **220**. In such an approach, the logging steps, e.g., **410**, **415**, and **425**, of process **400** may be omitted.

Next, in step **515**, the retrieval profile **210** may be compared to the expected profile **215**. A lack of correspondence between the retrieval profile **210** and the expected profile **215** may be recognized as an anomaly indicative of a service issue. Moreover, because the retrieval profile may be either a request profile **220** or a response profile **235**, the recognition of an anomaly may be based on a lack of correspondence between the request profile **220** and the expected request profile **230** or between the response profile **225** and the expected response profile **235**. If the retrieval profile **210** corresponds to the expected profile **215**, the process may skip to step **555** to determine if there are any more profiles **210** to analyze.

In step **520**, the content processing device **104** associated with the retrieval profile **210** identified in step **510** may be flagged for troubleshooting, servicing, or other restorative measures. In one exemplary approach, the system **100** may interface with a customer service management system such as a helpdesk or trouble ticket management system for tracking customer service issues. In another exemplary approach, a service technician responsible for the device **104** may be contacted, e.g., by email, instant messaging, or the like.

Next, in step **525**, devices associated with the flagged device may be discovered. As explained above with respect to FIG. **3**, the device association hierarchy **300** provides the relationships between content processing devices **104**. In one exemplary approach, the discovery may broadly identify a large number of associated devices, e.g., all devices associated with a particular franchise authority at the LFA level **305**. The franchise authority at the LFA level **305** associated with the flagged device may be identified. Then the hierarchy **300** may be used to identify all associated devices **104** at the device level **320** that descend from the identified franchise authority.

Because it may be undesirable to perform restorative measures on all of the discovered devices, it may be predicted that only certain devices require restorative measures in step **530**. The prediction may narrow the set of associated devices that will receive restorative measures. In one exemplary approach, the prediction may be based on the family relationships between devices in the hierarchy **300**. For example, it may be predicted that only first cousin or sibling devices should be subjected to restorative measures.

In steps **535-550**, the prediction made in step **530** may be confirmed using the retrieval log. For each device that has been predicted to require restorative measures, the retrieval log may be analyzed for an associated retrieval profile **210**. In step **535**, the prediction may be confirmed by recognizing a lack of correspondence between the retrieval profile **210** and the expected profile **215**.

In step **540**, any restorative measures may be limited to the initially flagged device and any associated devices that have a confirmed lack of correspondence between the retrieval profile **210** and the expected profile **215**.

Similarly, in step **545**, devices whose prediction was not confirmed in step **535** may be omitted from the set of devices that require restorative measures.

11

In step 550, the process may return to step 535 if there are more predictions to confirm. However, if there are no more predictions to confirm, process 500 may end.

In step 555, the process may return to step 510 if there are more profiles 210 to analyze. However, if there are no more profiles 210 to analyze, process 500 may end.

Accordingly, exemplary a system for proactively troubleshooting set top box (STB) issue has been described. The behavior and activities of content processing devices 104 (e.g., STBs) may be monitored to proactively detect service issues prior to receiving a service call from a customer. Because the content processing device 104 may communicate with other elements of the multimedia subscriber system (e.g., the IPG server 142) in an anticipated and regular manner, logs of communications may be used to recognize anomalies indicative of service issues. Comparisons between an expected retrieval profile 215 of communications and an actual retrieval profile 210 of communications may be made in order to recognize the anomalies and subsequently flag the STB for troubleshooting. The hierarchical network architecture of the multimedia subscriber system may allow for a problem with one device 104 to predict a problem with another device associated with common node of the network at a higher level in the device association hierarchy 300. The device association hierarchy 300 may be analyzed to discover other devices 104 that may be in need of troubleshooting and restorative measures. In order to reduce the number of devices 104 subjected to restorative measures, a prediction of which devices are actually affected by a service issue may be made. To confirm the prediction, logs of the communications between the discovered devices 104 and the interactive programming guide server 142 may reviewed for anomalies. Confirming the prediction may allow restorative measures to be limited to only those devices with actual service issues, which may improve customer service by avoiding unnecessary, and potentially disruptive, device maintenance.

With regard to the processes, systems, methods, heuristics, etc. described herein, it should be understood that, although the steps of such processes, etc. have been described as occurring according to a certain ordered sequence, such processes could be practiced with the described steps performed in an order other than the order described herein. It further should be understood that certain steps could be performed simultaneously, that other steps could be added, or that certain steps described herein could be omitted. In other words, the descriptions of processes herein are provided for the purpose of illustrating certain systems, and should in no way be construed so as to limit the claims.

Accordingly, it is to be understood that the above description is intended to be illustrative and not restrictive. Many systems and applications other than the examples provided would be apparent upon reading the above description. The scope of the disclosure should be determined, not with reference to the above description, but should instead be determined with reference to the appended claims, along with the full scope of equivalents to which such claims are entitled. It is anticipated and intended that future developments will occur in the arts discussed herein, and that the disclosed systems and methods will be incorporated into such future systems. In sum, it should be understood that the disclosure is capable of modification and variation and is limited only by the following claims.

All terms used in the claims are intended to be given their broadest reasonable constructions and their ordinary meanings as understood by those skilled in the art unless an explicit indication to the contrary is made herein. In particular, use of the singular articles such as “a,” “the,” “said,” etc. should be

12

read to recite one or more of the indicated elements unless a claim recites explicitly to the contrary.

What is claimed is:

1. A method comprising:

identifying, by way of a computing device, a guide data retrieval profile of a first content processing device;
comparing the guide data retrieval profile to an expected profile;

flagging the first content processing device for troubleshooting based on a lack of correspondence between the guide data retrieval profile and the expected profile;

predicting at least one additional content processing device that requires troubleshooting based on a relationship between the at least one additional content processing device and the flagging of the first content processing device, the relationship including both the at least one additional content processing device and the first content processing device being associated with a common node at a higher level of a device association hierarchy;
determining after the predicting if the at least one additional content processing device actually requires troubleshooting including analyzing a guide data retrieval profile of the at least one additional content processing device, and recognizing a lack of correspondence between the guide data retrieval profile of the at least one additional content processing device and the expected profile;

if the at least one additional content processing device does require troubleshooting, then initiating restorative measures to both the first content processing device and the at least one additional content processing device; and

if the at least one additional content processing device does not require troubleshooting, then initiating restorative measures to just the first content processing device;

wherein the device association hierarchy is based on a location of the first content processing device, and includes a plurality of location levels, each level of the device association hierarchy representing a point of control and providing a troubleshooting intervention point.

2. The method according to claim 1, wherein the plurality of location levels includes a first location level that includes at least one other location level.

3. The method according to claim 2, wherein one of the first content processing device and the at least one additional content processing device is associated with the first location level, and the other of the first content processing device and the at least one additional content processing device is associated with the other location level.

4. The method according to claim 1, further comprising performing restorative measures at the location level associated with the first content processing device and the at least one additional content processing device.

5. The method according to claim 1, further comprising performing restorative measures on the at least one additional content processing device in response to the relationship with the first content processing device.

6. The method according to claim 1, further comprising:
receiving a request for guide data from the first content processing device; and
logging at least one of the retrieval request and an indication of whether the retrieval request was fulfilled.

7. The method according to claim 1, further comprising representing the guide data retrieval profile of the first content processing device as one of a request profile indicative of requested guide data and a response profile indicative of whether the requested guide data was successfully provided.

13

8. The method according to claim 1, further comprising including a plurality of sub-requests for portions of guide data.

9. The method according to claim 1, wherein initiating restorative measures includes at least one of:

initiating an interface between a customer service management system and at least one of the first content processing device and the at least one additional content processing device; and

contacting a service technician responsible for at least one of the first content processing device and the at least one additional content processing device.

10. A method comprising:

reviewing, by way of a computing device, a guide data retrieval profile of a first content processing device from a retrieval log of programming guide data;

recognizing at least one anomaly in the guide data retrieval profile of the first content processing device based on lack of correspondence between the guide data retrieval profile of the first content processing device and an expected profile;

flagging the first content processing device for troubleshooting based on the anomaly;

predicting at least one additional content processing device that requires troubleshooting based on a relationship between the at least one content processing device and the first content processing device associated with the flagging, the relationship including both the at least one additional content processing device and the first content processing device being associated with a common node at a higher level of a device association hierarchy;

determining if the at least one additional content processing device actually requires troubleshooting including analyzing a guide data retrieval profile of the at least one additional content processing device and recognizing a lack of correspondence between the guide data retrieval profile of the at least one additional content processing device and the expected profile;

if the at least one additional content processing device does require troubleshooting, then initiating restorative measures to both the first content processing device and the at least one additional content processing device; and

if the at least one additional content processing device does not require troubleshooting, then initiating restorative measures to just the first content processing device;

wherein the device association hierarchy is based on a location of the first content processing device, and includes a plurality of location levels, each level of the device association hierarchy representing a point of control and providing a troubleshooting intervention point.

11. The method according to claim 10, further comprising: receiving a request for guide data from the first content processing device; and

logging at least one of the retrieval request and an indication of whether the retrieval request was fulfilled.

12. The method according to claim 10, further comprising representing the guide data retrieval profile of the first content processing device as one of a request profile indicative of requested guide data and a response profile indicative of whether the requested guide data was successfully provided.

13. The method according to claim 10, further comprising including a plurality of sub-requests for portions of guide data.

14

14. A system comprising:

a media distribution network including a remote requesting device; and

a programming guide server configured to:

identify a guide data retrieval profile of the remote requesting device;

compare the guide data retrieval profile of the remote requesting device to an expected profile;

flag the remote requesting device for troubleshooting based on a lack of correspondence between the guide data retrieval profile of the remote requesting device and the expected profile;

predict at least one additional content processing device that requires troubleshooting based on a relationship between the at least one content processing device and the remote requesting device associated with the flagging, the relationship including both the at least one additional content processing device and the remote requesting device being associated with a common node at a higher level of a device association hierarchy;

determine if the at least one additional content processing device actually requires troubleshooting;

initiate restorative measures to both the remote requesting device and the at least one additional content processing device if the at least one additional content processing device does actually require troubleshooting; and

initiate restorative measures to just the remote requesting device if the at least one additional content processing device does not actually require troubleshooting;

wherein the device association hierarchy is based on a location of the remote requesting device, and includes a plurality of location levels, each level of the device association hierarchy representing a point of control and providing a troubleshooting intervention point; and

wherein the programming guide server is further configured to analyze a guide data retrieval profile of the at least one additional content processing device, and recognize a lack of correspondence between the guide data retrieval profile of the at least one additional content processing device and the expected profile to determine if the at least one additional content processing device actually requires troubleshooting.

15. The system according to claim 14, wherein the programming guide server is further configured to:

receive a request for guide data from the remote requesting device; and

log at least one of the retrieval request and an indication of whether the retrieval request was fulfilled.

16. The system according to claim 14, wherein the programming guide server is further configured to represent the guide data retrieval profile of the remote requesting device as one of a request profile indicative of requested guide data and a response profile indicative of whether the requested guide data was successfully provided to the remote requesting device.

17. The system according to claim 14, wherein the programming guide server is further configured to include a plurality of sub-requests for portions of the guide data retrieval and expected profiles.