

(12) **United States Patent**
Kondo et al.

(10) **Patent No.:** **US 9,124,896 B2**
(45) **Date of Patent:** ***Sep. 1, 2015**

(54) **MOTION VECTOR CODING METHOD AND
MOTION VECTOR DECODING METHOD**

(71) Applicant: **Panasonic Intellectual Property
Corporation of America**, Torrance, CA
(US)

(72) Inventors: **Satoshi Kondo**, Kyoto (JP); **Shinya
Kadono**, Fukuoka (JP); **Makoto Hagai**,
Osaka (JP); **Kiyofumi Abe**, Osaka (JP)

(73) Assignee: **PANASONIC INTELLECTUAL
PROPERTY CORPORATION OF
AMERICA**, Torrance, CA (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.
This patent is subject to a terminal dis-
claimer.

(21) Appl. No.: **14/533,318**

(22) Filed: **Nov. 5, 2014**

(65) **Prior Publication Data**

US 2015/0055714 A1 Feb. 26, 2015

Related U.S. Application Data

(60) Division of application No. 13/966,484, filed on Aug.
14, 2013, now Pat. No. 8,908,769, which is a division
of application No. 11/979,013, filed on Oct. 30, 2007,
now abandoned, which is a continuation of application
No. 10/468,203, filed as application No.
PCT/JP03/00055 on Jan. 8, 2003, now Pat. No.
7,362,807.

(30) **Foreign Application Priority Data**

Jan. 9, 2002 (JP) 2002-001983
Jul. 12, 2002 (JP) 2002-204714
Nov. 28, 2002 (JP) 2002-346062

(51) **Int. Cl.**

H04N 19/176 (2014.01)
H04N 19/52 (2014.01)

(Continued)

(52) **U.S. Cl.**

CPC **H04N 19/52** (2014.11); **H04N 19/137**
(2014.11); **H04N 19/139** (2014.11);

(Continued)

(58) **Field of Classification Search**

CPC . H04N 19/176; H04N 19/513; H04N 19/137;
H04N 19/139; H04N 19/50; H04N 19/51;
H04N 19/517; H04N 19/52; H04N 19/521;
H04N 19/533; H04N 19/537; H04N

- (51) **Int. Cl.**
H04N 19/56 (2014.01)
H04N 19/50 (2014.01)
H04N 19/51 (2014.01)
H04N 19/513 (2014.01)
H04N 19/61 (2014.01)
H04N 19/593 (2014.01)
H04N 19/517 (2014.01)
H04N 19/577 (2014.01)
H04N 19/137 (2014.01)
H04N 19/139 (2014.01)
H04N 19/537 (2014.01)
H04N 19/533 (2014.01)
- (52) **U.S. Cl.**
CPC *H04N 19/176* (2014.11); *H04N 19/50* (2014.11); *H04N 19/51* (2014.11); *H04N 19/513* (2014.11); *H04N 19/517* (2014.11); *H04N 19/521* (2014.11); *H04N 19/533* (2014.11); *H04N 19/537* (2014.11); *H04N 19/56* (2014.11); *H04N 19/577* (2014.11); *H04N 19/593* (2014.11); *H04N 19/61* (2014.11)

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,991,447	A	11/1999	Eifrig et al.	
6,005,980	A *	12/1999	Eifrig et al.	382/236
6,097,842	A	8/2000	Suzuki et al.	
6,272,179	B1	8/2001	Kadono	
6,654,420	B1	11/2003	Snook	
6,671,319	B1 *	12/2003	Chang et al.	375/240.16
6,842,483	B1	1/2005	Au et al.	
6,983,018	B1	1/2006	Lin et al.	
7,020,200	B2	3/2006	Winger	
8,111,754	B1	2/2012	Demos	
2002/0176505	A1	11/2002	Kim et al.	
2003/0206589	A1	11/2003	Jeon	

FOREIGN PATENT DOCUMENTS

EP	0 765 087	3/1997
EP	1 335 609	8/2003
JP	11-317961	11/1999
JP	2000-099864	4/2000
JP	2000-299864	10/2000
JP	2001-45498	2/2001
JP	2001-224036	8/2001
KR	1020020077630	10/2002
WO	94/22269	9/1994
WO	00/33581	6/2000
WO	01/33864	5/2001
WO	01/50770	7/2001

Fig. 1




Fig. 2




Fig. 3A




Fig. 3B




Fig. 3C




Fig. 3D




Fig. 4







Fig. 5










Fig. 9




Fig. 10




Fig. 11




Fig. 12







Fig. 13















Fig. 17











Fig. 19

Fig. 20







29

neighboring blocks, and (2) when it is judged in the second judging step that only one of the three neighboring blocks refer to the same reference picture as the current block, the predictive motion vector of the current block is set to be a motion vector of the only one neighboring block having the same reference picture as the current block.

2. A motion vector decoding apparatus for decoding a motion vector of a current block in a moving picture, the apparatus comprising:

- a non-transitory memory storing a program; and
- a hardware processor that executes the program and causes the motion vector decoding apparatus to operate as:
 - a neighboring block specification unit operable to specify three neighboring blocks, the three neighboring blocks being located in a neighborhood of the current block and have been already decoded;
 - a first judgment unit operable to judge whether or not each of the three neighboring blocks has been decoded using a motion vector of another block; a second judgment unit operable to judge whether or not a reference picture referred to in the decoding of the current block is the same as a reference picture referred to in the decoding of each of the three neighboring blocks;
 - a different motion vector determining unit operable to determine a different motion vector of each of the three neighboring blocks based on a result of the first judgment unit;
 - a prediction unit operable to derive a predictive motion vector of the current block using different motion vectors of the three neighboring blocks based on a result of the second judgment unit;

30

a decoding unit operable to decode a coded motion vector to obtain a decoded difference motion vector of the current block; and a motion vector recovering unit operable to recover the motion vector of the current block by adding the decoded difference motion vector and the predictive motion vector, wherein, the different motion vector determining unit is further operable to: (1) determine a motion vector, which is calculated from the motion vector of the other block and which is used in performing a decoding process on a neighboring block of the three neighboring blocks, as a different motion vector of the neighboring block when it is judged by the first judgment unit that the neighboring block has been decoded using the motion vector of the other block, and (2) determine a motion vector, which is detected for the neighboring block and which is used in performing a decoding process on the neighboring block, as a different motion vector of the neighboring block when it is judged by the first judgment unit that the neighboring block has not been decoded using the motion vector of the other block, wherein, the prediction unit is further operable to: (1) set the predictive motion vector of the current block to a median of three motion vectors of the three neighboring blocks when it is judged by the second judgment unit that the three neighboring blocks refer to the same reference picture as the current block, and (2) set the predictive motion vector of the current block to a motion vector of one neighboring block having the same reference picture as the current block when it is judged by the second judging unit that only one of the three neighboring blocks refer to the same reference picture as the current block.

* * * * *