

US009125498B2

(12) **United States Patent**
Flannery

(10) **Patent No.:** **US 9,125,498 B2**
(45) **Date of Patent:** ***Sep. 8, 2015**

(54) **HIDE AWAY BED RAIL**

(71) Applicant: **Regalo International, LLC**, Longboat Key, FL (US)

(72) Inventor: **Mark A. Flannery**, Longboat Key, FL (US)

(73) Assignee: **Regalo International, LLC**, Longboat Key, FL (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **14/159,269**

(22) Filed: **Jan. 20, 2014**

(65) **Prior Publication Data**

US 2014/0223663 A1 Aug. 14, 2014

Related U.S. Application Data

(63) Continuation of application No. 13/785,331, filed on Feb. 4, 2013, now Pat. No. 8,631,525, which is a continuation of application No. 13/345,700, filed on Jan. 7, 2012, now Pat. No. 8,365,324, which is a continuation of application No. 13/053,191, filed on Mar. 21, 2011, now Pat. No. 8,091,163, which is a continuation of application No. 11/352,100, filed on Feb. 9, 2006, now Pat. No. 7,908,689.

(60) Provisional application No. 60/652,663, filed on Feb. 10, 2005.

(51) **Int. Cl.**

A47C 21/08 (2006.01)
A61G 7/05 (2006.01)

(52) **U.S. Cl.**

CPC **A47C 21/08** (2013.01); **A61G 7/0507** (2013.01); **A61G 2007/051** (2013.01); **A61G 2007/0518** (2013.01)

(58) **Field of Classification Search**

CPC **A47C 21/08**
USPC **5/425-430**
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

329,663 A 11/1885 McMurray
1,066,976 A * 7/1913 Atkinson 5/426
2,594,926 A * 4/1952 Hoffman 5/430

(Continued)

FOREIGN PATENT DOCUMENTS

GB 2 070 921 A 9/1981
GB 2 225 716 A 6/1990

OTHER PUBLICATIONS

S. Heh, Log of Meeting, Directorate for Engineering Sciences, Dec. 15, 1999, U.S. Consumer Products Safety Commission, U.S.A.



(Continued)

Primary Examiner — Michael Trettel

(57) **ABSTRACT**

A bed rail having an operating position at one of the sides of a bed and a stored position between a mattress and box spring of the bed. To take down the bed rail, a guard frame portion is disengaged from a base frame portion, then the guard frame portion is pivoted and slid into the base frame portion. To set up the bed rail, the guard frame portion can be slid out of the base frame portion, pivoted relative to the base frame portion, then engaged to the base frame portion and into the operating position at a side of the bed.

4 Claims, 21 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2,611,909 A 9/1952 Dillon et al.
 2,649,594 A 8/1953 Herz et al.
 2,722,693 A 11/1955 Wolf
 2,750,605 A * 6/1956 Blevins 5/430
 2,751,608 A 6/1956 Lucas
 2,763,014 A 9/1956 Luger
 3,474,473 A 10/1969 Hannaberg
 4,811,436 A 3/1989 Schwartz
 4,833,743 A 5/1989 Howell et al.
 5,437,067 A 8/1995 Bernstein et al.
 5,519,905 A 5/1996 Bernstein et al.
 5,596,776 A 1/1997 Huang
 5,640,726 A * 6/1997 Fichner-Rathus 5/426
 5,671,490 A 9/1997 Wu
 5,761,756 A 6/1998 Nowak et al.
 5,781,945 A 7/1998 Scherer et al.
 5,845,349 A 12/1998 Tharalson et al.
 6,112,347 A 9/2000 Tharalson et al.
 6,134,731 A 10/2000 Thom et al.
 6,148,456 A 11/2000 Tharalson et al.
 6,202,228 B1 3/2001 Cox
 6,289,539 B1 9/2001 Alpern
 6,374,437 B1 * 4/2002 Voelker 5/600
 6,401,280 B1 6/2002 Baker
 6,453,490 B1 9/2002 Cardinale
 6,550,082 B2 4/2003 Tharalson et al.
 6,578,211 B2 6/2003 Tharalson et al.
 6,704,949 B2 3/2004 Waldman et al.
 6,725,476 B2 4/2004 Macari
 6,728,981 B1 5/2004 Gutierrez
 6,795,988 B2 * 9/2004 Hueppe 5/426
 6,862,757 B2 3/2005 Andriunas et al.
 6,877,173 B2 4/2005 Tharalson et al.
 6,931,677 B2 8/2005 Tharalson et al.
 6,934,981 B2 8/2005 Waldman et al.
 6,952,846 B2 10/2005 Flannery et al.
 6,952,847 B1 10/2005 Cleary
 6,959,463 B2 11/2005 Macari
 6,990,697 B1 1/2006 Clute
 7,013,508 B2 3/2006 Wu
 7,024,708 B2 4/2006 Tomas et al.
 7,028,353 B2 4/2006 Waldman et al.
 7,028,354 B2 4/2006 Nygren et al.
 7,055,193 B2 6/2006 Macari et al.
 7,080,419 B2 7/2006 Macari
 7,137,158 B2 11/2006 Flannery et al.
 7,178,184 B2 2/2007 Flannery et al.
 7,181,788 B2 2/2007 Flannery et al.
 7,237,285 B2 7/2007 Brewin et al.
 7,640,606 B2 1/2010 Flannery et al.
 7,908,689 B2 * 3/2011 Flannery 5/430

8,091,163 B2 1/2012 Flannery
 8,365,324 B2 2/2013 Flannery
 2002/0083524 A1 7/2002 Tharalson et al.
 2002/0152550 A1 10/2002 Tharalson et al.
 2003/0024047 A1 2/2003 Wu
 2003/0126681 A1 7/2003 Tharalson et al.
 2003/0177574 A1 9/2003 Waldman
 2003/0196264 A1 10/2003 Tharalson et al.
 2004/0040089 A1 3/2004 Flannery et al.
 2004/0049849 A1 3/2004 Macari
 2004/0154100 A1 8/2004 Macari
 2004/0168251 A1 9/2004 Waldman et al.
 2004/0181873 A1 9/2004 Waldman et al.
 2004/0187209 A1 9/2004 Flannery et al.
 2004/0250347 A1 12/2004 Brewin et al.
 2005/0034232 A1 2/2005 Martin
 2005/0198734 A1 9/2005 Macari
 2005/0229309 A1 10/2005 Nygren et al.
 2005/0229310 A1 10/2005 Flannery et al.
 2005/0235419 A1 10/2005 Macari
 2005/0246837 A1 11/2005 Macari et al.
 2005/0262632 A1 12/2005 Wu
 2006/0026759 A1 2/2006 Flannery et al.
 2006/0037140 A1 2/2006 Clute
 2006/0130233 A1 6/2006 Macari et al.
 2006/0150329 A1 7/2006 Nygren et al.
 2006/0162075 A1 7/2006 Waldman et al.
 2006/0174408 A1 8/2006 Flannery
 2011/0167560 A1 7/2011 Flannery

OTHER PUBLICATIONS

S. Heh, Log of Meeting, Directorate for Engineering Sciences, Apr. 12, 2000, U.S. Consumer Products Safety Commission, U.S.A.
 R. Medford et al., Memorandum, Options to Address Portable Bed Rail Hazards, Jun. 28, 2000, U.S. Consumer Product Safety Commission, U.S.A.
 Reexamination Application No. 90/009,498, filed Jun. 19, 2009 based on U.S. Patent No. 7,718,184.
 Reexamination Application No. 90/009,499, filed Jun. 19, 2009 based on U.S. Patent No. 7,137,158, with Reexamination Certificate attached.
 Reexamination Application No. 90/009,500, filed Jun. 19, 2009 based on U.S. Patent No. 6,952,846, with Reexamination Certificate attached.
 Regalo International, LLC, Hide Away Bed Rail, Model 4010 HD Instruction Manual, 13 pages, approximately 2010.
 Regalo International, LLC, Hide Away Bed Rail Instructions, Model: 4010 HD and 5010HD, 37 pages, approximately May 10, 2010.
 Regalo International, LLC, Hide Away Bed Rail, Model 4010 HD, 9 pages, approximately 2006.

* cited by examiner




Fig. 1A.




Fig. 1B.




Fig. 2A.

Fig. 2B.




Fig. 3.




Fig. 4.




Fig. 5.




Fig. 6.




Fig. 7.




Fig. 8.




Fig. 9.





Fig. 10.






Fig. 12B.




Fig. 12A.






Fig. 13C.

Fig. 13A.

Fig. 13B.






Fig. 15A.

Fig. 15B.




Fig. 16A.




Fig. 16B.




Fig. 17A.







Fig. 17B.






Fig. 19A.




Fig. 19B.




Fig. 20.




Fig. 21A.




Fig. 21B.

HIDE AWAY BED RAIL

This application is a continuation of U.S. patent application Ser. No. 13/758,331 filed Feb. 4, 2013 (U.S. Pat. No. 8,631,525) and claims the benefit thereof under 35 U.S.C. §120, which application is a continuation of U.S. patent application Ser. No. 13/345,700 filed Jan. 7, 2012 (U.S. Pat. No. 8,365,324) and claims the benefit thereof under 35 U.S.C. §120, which application is a continuation of U.S. patent application Ser. No. 13/053,191 filed Mar. 21, 2011 (U.S. Pat. No. 8,091,163) and claims the benefit thereof under 35 U.S.C. §120, which application is a continuation of U.S. patent application Ser. No. 11/352,100 filed Feb. 9, 2006 (U.S. Pat. No. 7,908,689) and claims the benefit thereof under 35 U.S.C. §120, which application is a nonprovisional of U.S. Provisional Patent Application No. 60/652,663 filed Feb. 10, 2005 and claims the benefit thereof under 35 U.S.C. 119(e). U.S. Provisional Patent Application No. 60/652,663 filed Feb. 10, 2005, U.S. patent application Ser. No. 11/352,100 filed Feb. 9, 2006, U.S. patent application Ser. No. 13/053,191 filed Mar. 21, 2011, U.S. patent application Ser. No. 13/345,700 filed Jan. 7, 2012 and U.S. patent application Ser. No. 13/758,331 filed Feb. 4, 2013 are hereby incorporated by reference in their entireties into this application.

FIELD OF THE INVENTION

The present invention relates generally to a bed rail, particularly to a bed rail having an operating position at a side of a bed and a stored position below a sleeping surface of the bed and between two sides of the bed, and specifically to a bed rail having a guard frame portion that is pivotable and slideable between the operating and stored positions.

BACKGROUND OF THE INVENTION

Some bed rails are fixed such that the bed rail is relatively permanently engaged to the frame of a bed. Other bed rails are on the bed at night, removed in the morning, and then placed on the bed again at night. Yet other bed rails swing out like a door for access to and from the bed. Still other bed rails swing from an operating position at the side of a mattress to a stored position at the side of a box spring. Most beds have no bed rails.

SUMMARY OF THE INVENTION

A feature of the present invention is the provision in a bed rail, of the bed rail having an operating position and a stored position, with the operating position being at a first side of a bed, with the stored position being under a sleeping surface of the bed, and of the bed rail having a guard frame portion that can be disposed in each of the operating and stored positions.

Another feature of the present invention is the provision in a bed rail, of the bed rail having a guard frame portion and a base frame portion, and of the guard frame portion being slideable into the base frame portion.

Another feature of the present invention is the provision in a bed rail, of the bed rail having a guard frame portion and a base frame portion, and of the guard frame portion being pivotable relative to the base frame portion.

Another feature of the present invention is the provision in a bed rail, of a bed rail that 1) is less than the length of an ordinary sized bed and preferably has a length between about 2.5 feet and 5.0 feet, more preferably between about 3.0 feet and 4.5 feet, and even more preferably between about 3.0 feet and 4.0 feet in length, 2) can be disassembled so as to be sold

and stored in an elongate bag or package, 3) meets safety regulations, 4) has sheeting that can be readily removed for washing, and 5) has a guard frame portion that can be easily put up at night and stored in an out-of-the-way position during the day. The embodiments of the present invention have all five such features.

Another feature of the present invention is the provision in a bed rail having a guard frame portion slideable into a base frame portion, of first and second locations or points of connection where the guard frame portion engages the base frame portion, of the first and second locations being spaced from each other in a depth direction and being generally in a first plane at a side of the bed, and, optionally, of at least one of the first and second locations being lockable such that the guard frame portion can be locked in the first plane.

Another feature of the present invention is the provision in a bed rail having a guard frame portion slideable into a base frame portion, of first and second locations or points of connection where the guard frame portion engages the base frame portion, of the first and second locations being spaced from each other in a depth direction and being generally in a first plane at a side of the bed, and of first and second counter members engaged to the base frame portion and being engageable to opposite sides of the bed such that the base frame portion hugs the bed.

Another feature of the present invention is the provision in a bed rail, of the bed rail having a guard portion and a base frame portion, and of the bed rail having at least one point of connection, or optionally a lock, to fix the guard frame portion relative to the base frame portion.

Another feature of the present invention is the provision in a bed rail having a guard portion and a base frame portion that are slideable and pivotable to each other, with such portions being slideable and pivotable at different times depending upon the position of the guard frame portion, and with such portions being slideable and pivotable at the same time depending upon the position of the guard frame portion.

Another feature of the present invention is the provision in a bed rail having a guard frame portion and a base frame portion that are slideable relative to each other, of the guard frame portion having one of a track and rider, of the base frame portion having one of a track and rider, and of the track engaging the rider such that the guard frame portion is slideable relative to the base frame portion.

Another feature of the present invention is the provision in a bed rail having a guard frame portion and a base frame portion that are slideable relative to each other, of a track and rider arrangement, with one of the guard frame portion and base frame portion having a track and a seat offset from the track such that the guard portion and base frame portions can be pivotable relative to each other when the rider is in the seat.

Another feature of the present invention is the provision in a bed rail having a guard frame portion and a base frame portion that are slideable relative to each other, of a method having the steps of fixing a guard frame portion in an operating position at a side of a bed, unlocking the guard frame portion relative to a base frame portion, pivoting the guard frame portion relative to the base frame portion, and then sliding the guard frame portion into the base frame portion.

Another feature of the present invention is the provision in a bed rail having a guard frame portion and a base frame portion that are slideable relative to each other, of a method having the steps of sliding the guard frame portion out of the base frame portion, swinging the guard frame portion relative to the base frame portion, and locking the guard frame portion into a fixed relationship with the base frame portion.

Another feature of the present invention is the provision in a bed rail having a guard frame portion and a base frame portion that are slideable relative to each other, of guard support receptors that do double duty by, on one side, engaging the guard frame portion and by, on the other side, acting as first side bed counter members for opposing the second side bed counter members.

An advantage is safety. One feature contributing to this advantage is that the present bed rail can be fixed or locked in its operating position at a side of the bed. Another feature contributing to this advantage is that the bed rail is manually unfastened or manually unlocked from its operating position. Another feature contributing to this advantage is that a relatively great portion of the bed rail is tucked away in an out-of-the-way position such that use of the bed rail as a toy or ladder is minimized.

Another advantage of the present invention is a quick take down and storage. The present bed rail can almost immediately be taken down from an operating position and put down into a stored position.

Another advantage of the present invention is a quick set up from storage. The present bed rail can almost immediately be taken out of a stored position and put up into an operating position.

Another advantage of the present invention is cost. The present bed rail is inexpensive to manufacture.

Another advantage of the present invention is simplicity. Merely fixing or locking, pivoting and sliding operations are utilized. There is no disassembly of tubing.

Another advantage of the present invention is ease of operation. The points of connection are readily unfastened, or the locks are readily unlockable, when the bed rail is being taken down. The points of connection are easily engaged, or the locks are easily locked, when the bed rail is being set up.

Another advantage is that the base frame portion can be readily set up to hug the bed so as to serve as a support for the guard frame portion. One feature contributing to this advantage is a rigid counter member, namely the guard support receptor, that is rigidly engaged to the base frame portion and confronts or is generally in a first plane at a first side of the bed in which the guard frame member is disposed in its operating position. Another feature contributing to this advantage is an adjustable counter member that is engaged to the base frame portion at a position confronting the first side of the bed, that is engagable to the second side of the bed, and that is operable from the first side of the bed such that the adjustable counter member can be adjusted or tightened and locked from a position close to or at the first side of the bed.

Another advantage of the present invention is that the guard frame portion is rigid and sturdy in its operating position. One feature contributing to this advantage is the fast and secure fixing of the base frame portion to the opposite sides of the bed by the first and second counter members such that the base frame portion is a true base for the guard frame portion. Another feature contributing to this advantage is a two point or two location connection where the two points or two locations are spaced from each other in the depth direction. At each of the points or locations, the guard frame portion engages the base frame portion. Each of the locations may include a seat for a rider or pin, a connection or lock such as a retractable pin, a connection or lock such as a wrap around hinged piece, or some other structure that effectively engages the base frame portion to the guard frame portion. Since two points or two locations are utilized, movement of the guard

frame portion when the guard frame portion is in the operating position is minimized or effectively eliminated.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1A is a side view of one embodiment of the present hide away bed rail in an operating position on a bed having a mattress and a box spring, with a guard frame portion disposed on the side of the bed and with a base frame portion tucked between the mattress and box spring.

FIG. 1B is a side view of the embodiment of FIG. 1A in a stored position wherein the guard frame portion has been slid into the base frame portion tucked between the mattress and box spring.

FIG. 2A is a top view of the embodiment of FIG. 1A, in the operating position of FIG. 1A, with the mattress of the bed removed.

FIG. 2B is a top view of the embodiment of FIG. 1A, in the stored position of FIG. 1B, with the mattress of the bed removed.

FIG. 3 is a perspective view of a right side portion of the bed rail embodiment of FIG. 1A in the stored position.

FIG. 4 is a perspective view of a left side portion of the bed rail embodiment of FIG. 1A in the stored position.

FIG. 5 is a perspective detail view of the bed rail embodiment of FIG. 1A and shows a fixed or locked position of the guard frame portion relative to the base frame portion where a first lock is locked and where a second lock is locked in a two point connection relationship.

FIG. 6 is a perspective detail view of the bed rail embodiment of FIG. 1A, shows the first lock of FIG. 5 in the process of being unlocked and shows the second lock locked.

FIG. 7 is a perspective detail view of the bed rail embodiment of FIG. 1A, shows the first lock of FIG. 5 unlocked, shows the guard frame portion being pivoted relative to the base frame portion, and shows the second lock locked.

FIG. 8 is a perspective detail view of the bed rail embodiment of FIG. 1A, shows the first lock of FIG. 5 unlocked, shows the guard frame portion having been pivoted relative to the base frame portion, and shows the second lock locked.

FIG. 9 is a perspective detail view of the bed rail embodiment of FIG. 1A, shows the first lock of FIG. 5 unlocked, shows the guard frame portion having been pivoted relative to the base frame portion, and shows the second lock of FIG. 5 unlocked for sliding the guard frame portion into the base frame portion.

FIG. 10 is a perspective detail view of the bed rail embodiment of FIG. 1A, shows the second lock unlocked, and shows the guard frame portion being slid into the base frame portion.

FIG. 11A is a diagrammatic view of a rider of the guard frame portion engaging a track of the base frame portion and shows the second lock of FIG. 5 locked.

FIG. 11B is a diagrammatic view of a rider of the guard frame portion engaging a track of the base frame portion and shows the second lock of FIG. 5 unlocked.

FIG. 11C is an isolated view of the handle of the second lock of FIG. 11A where the handle is rotated ninety degrees relative to the view in FIG. 11A.

FIG. 11D is an isolated view of the rider of the second lock of FIG. 11A.

FIG. 12A is a diagrammatic view of a portion of the first lock of FIG. 5, with the first lock in a locked position, and with the coil spring of the first lock in an extended position.

FIG. 12B is a diagrammatic view of a portion of the first lock of FIG. 5, with the first lock in an unlocked position biased toward the locked position, and with the coil spring of the first lock in a retracted and compressed position.

5

FIG. 13A is a diagrammatic view of a rider of the guard frame portion engaging a track of the base frame portion and shows another embodiment of the second lock of FIG. 5 locked, where the second lock includes a pin that threadingly engages the base frame portion.

FIG. 13B is a diagrammatic view of a rider of the guard frame portion engaging a track of the base frame portion and shows the embodiment of the second lock of FIG. 13A unlocked where the pin is turned out to disengage the rider.

FIG. 13C is a diagrammatic view of a handle of the second lock shown in FIG. 13B.

FIG. 14A shows another embodiment of the guard frame portion of FIG. 1A.

FIG. 14B shows still another embodiment of the guard frame portion of FIG. 1A.

FIG. 15A shows the embodiment of the guard frame portion of FIG. 1A.

FIG. 15B shows yet another embodiment of the guard frame portion of FIG. 1A.

FIG. 16A is a perspective view of an alternate embodiment of the present bed rail with the base frame portion engaged between the box spring and mattress of a bed and with the guard frame portion in the upright, locked and operating position at a first side of the bed.

FIG. 16B is a perspective view of the bed rail of FIG. 16A, with the guard rail portion in a stored position within the base frame portion.

FIG. 17A is a perspective view of the bed rail of FIG. 16A, showing the guard frame portion in the process of being swung up to the upright, locked and operating position.

FIG. 17B is a detail perspective view of a two point or two location connection between the guard frame portion and the base frame portion when the guard frame portion is in the upright, locked and operating position of FIG. 16A.

FIG. 18A is a detail perspective view of the connection of FIG. 17B after the guard frame portion has been fully slid out of the base frame portion.

FIG. 18B is a detail perspective view of the two point or two location connection of FIG. 17B while the guard frame portion is in the process of being swung up to the upright, locked and operating position.

FIG. 18C is a detail perspective view of the two point or two location connection of FIG. 17B when the guard frame portion is in the upright, locked and operating position.

FIG. 19A is a detail perspective view of the two point or two location connection of FIG. 17B while the guard frame portion is being slid into the base frame portion.

FIG. 19B is a detail front view of the two point connection of FIG. 17B while the guard frame portion is in the upright, locked and operating position.

FIG. 20 is a perspective view of an alternate embodiment of the invention, where two bed rails of FIG. 16A are set back to back and interconnected so as to guard both sides of the bed.

FIG. 21A shows a section view of an alternate embodiment of one of the two point or two location connections shown in FIG. 17B, where the alternate connection replaces the pin of FIG. 17B.

FIG. 21B shows a strap and counter member engaged to the bed rail of FIG. 16A.

DESCRIPTION

One embodiment of the present bed rail is a bed rail 10 shown in FIGS. 1A, 1B, 3 and 4. Bed rail 10 includes a guard frame portion or first frame portion 12 and a base frame portion or second frame portion 14.

6

Bed rail 10 is preferably engaged to a bed 16. Bed 16 includes a headboard 18, a footboard 20, a box spring 22, and a mattress 24. Bed 10 can further include a box spring frame 26 having casters or feet 28. Mattress 24 includes a sleeping surface 30 and first and second sides 32. Box spring 22 includes first and second sides 34 that are generally coplanar with respective first and second sides 32 of mattress 24. Mattress 24 further includes an underside or under face 36 and box spring 22 further includes an upper side or upper face 38. The underside 36 of the mattress 24 confronts the upper face 38 of the box spring 22.

Guard frame portion 12 includes a pair of side support members 40, 42, an upper or outer support member 44 engaged between the side support members 40, 42, a lower support member 46 engaged between the side support members 40, 42, and an intermediate support member 48 engaged between the side support members 40, 42. When the guard frame portion 12 is in the operating position, intermediate support member 48 lies coplanar with, or confronts, a plane of a sleeping surface 30 to maximize the closing off of any gaps that may form between side 32 and guard frame portion 12. The guard frame portion 12 further includes a sheeting or wall 50 in the interior of the guard frame portion 12. Sheeting or wall 50 extends between upper support member 44, intermediate support member 48, and side support members 40, 42. Sheeting or wall 50 further extends between intermediate support member 48, lower support member 46, and side support members 40, 42. Sheeting or wall 50 can, within a sleeve, envelope a portion of intermediate support member 48, a portion of upper support member 44, and a portion of lower support member 46. Sheeting or wall 50 can be a flexible sheet element such as a mesh or a fabric. Sheeting or wall 50 can be a rigid or semi-rigid wall formed of a wood, metal or composite material. Side support members 40, 42, upper support member 44, intermediate support member 48 and lower support member 46 can be or include tubing.

The guard frame portion 12 further includes a corner support or corner connection 52 for connecting lower support member 46 to each of the side support members 40, 42. Corner connection 52 includes a receptor for one end portion of lower support member 46. Corner connection 52 further includes another receptor for one end portion of one of the respective side support members 40, 42. Within the corner connection 52, an end portion of lower support member 46 confronts an end portion of one of the side support members 40, 42, as shown in FIGS. 11A, 11B.

As also shown in FIGS. 11A, 11B, guard frame portion 12 further includes a rider 54 on an axle 56. Axle 56 is engaged to one of the side support members 40, 42. Axle 56 has one closed end and one open end. Rider 54 is preferably a wheel. Axle 56 and the open end of the axle can be referred to as a lock or locking portion, and is one part of a two point or two location connection.

As shown in FIGS. 8, 12A and 12B, guard frame portion 12 further includes a lock portion 58 in each of the side support members 40, 42, and this lock portion 58 is the other part of the two point or two location connection. Lock portion 58 includes a slot 60 formed longitudinally in the respective side support member 40 or 42. A pin 62 slides longitudinally in the slot 60 and includes a pair of riders 64 on each of the end portions of the pin 62. Lock portion 58 further includes, as shown in FIGS. 12A, 12B, a coil spring 66 or other bias member that is pinched between an internal tube support 68 and the pin 62. FIG. 12A shows a locked position for the locking portion 58 and FIG. 12B shows an unlocked position for the locking portion 58. The coil spring 66 biases the locking portion 58 towards the locking position shown in

FIG. 12A, whereupon the pin 62 comes to rest at one of the ends of the slot 60. In the unlocked position shown in FIG. 12B, pin 62 is spaced from the other end of the slot 60.

Base frame portion 14 includes, as shown in FIGS. 2A, 2B, a pair of tracks 70, 72. Tracks 70, 72 are preferably joined at end portions for support via a support member or cross tube 74, shown in FIGS. 2A, 2B whereupon, if support member 74 is included, base frame portion 14 is generally U-shaped when viewed from the top as in FIGS. 2A and 2B. Each of the tracks 70, 72 can be about 22 inches in length. In the event that support member 74 is not included, tracks 70, 72 are spaced apart in a supported manner by guard frame portion 12. Cross tube 74 can be a two part piece that is assembled when the bed rail 10 is assembled.

With or without support member 74, base frame portion 14 can include members 76 having counters 78. Members 76 can be flexible and formed in the nature of straps, where the straps may be flexible metal or fabric or fabric like straps. Members 76 can be rigid or relatively rigid, such as in the nature of metal tubes or rails such as U-shaped rails. Members 76 engage, at one respective end, a portion of base frame portion 14 such as end portions of tracks 70, 72. Members 76 engage, at the other respective end, one respective counter member 78. Counter member 78 can engage mattress side 32 only or box spring side 34 only or can engage sides 32, 34 at the same time. Counter member 78 can be an L-shaped end tube for engaging one of the mattress side 32 or box spring side 34 or a T-shaped end tube for engaging each of the sides 32, 34. Members 76 can be adjustable in length so as to draw guard frame portion 12 to a hugging position against mattress side 32 and so as to draw intermediate tube 48 against the upper edge of side 32, which upper edge lies in the plane of the sleeping surface 30. Members 76 can include a buckle for such length adjustment at or near the counter members 78 such that such buckle is accessible relative to the side of the bed that the counter members 78 engage. It should be noted that locking portions 82 and 84, which are rigidly affixed to the base frame portion 14, act as counters on the first side of the bed 16, opposite the second side that counter 78 is acting upon. This counter action by locking portions 82 and 84 can be seen in FIGS. 1A, 1B, 2A, and 2B and is specifically applied by the rear face of hook section 90.

Each of the tracks 70, 72 is preferably, in section or when viewed from an end, generally U-shaped or generally C-shaped. Riders 54, 64 ride within the U-shaped or C-shaped interior and on a track portion 80 of said track 70 or 72, as shown in FIG. 8.

The base frame portion 14 further includes a pair of locking portions 82, 84 fixed at respective end portions of the tracks 70, 72. Each of the locking portions 82, 84 is a relatively rigid piece formed of metal or plastic. Each of the locking portions 82, 84 includes a U-shaped base section 86 fixed via pins 88 to said respective end portions of the tracks 70, 72. Extending from the U-shaped base 86 and integral and one-piece with the U-shaped base 86, is a hook section 90 having a pair of hooks 92. Hook section 90 is offset from U-shaped base section 86 such that hook section 90 is generally coplanar with side member 40 or 42 and such that U-shaped base section 86 is coplanar with track 70 or 72. Side support member 40 or 42 is received within one respective pair of hooks 92. Hooks 92 engage one of the pins 62 of one of the lock portions 58 of one respective side member 40, 42. Each of the hooks 92 includes a curved edge or sloping edge 94 leading into an open ended slot 98 for reception of pin 62. Curved edges 94 provide, along with coil spring 66, an auto-

matic locking of pin 62 into hooks 92 when guard frame portion 12 is pivoted into an operating position with base frame portion 14.

Base frame portion 14 further includes locking portions 98, one for each of the tracks 70, 72. As shown in FIGS. 11A, 11B, locking portion 98 includes a handle 100 that is integral and one-piece with a pin 102. Pin 102 is integral and one-piece with a disk 104 and a pin head 106. In one embodiment, as shown in FIG. 11C, pin head 106 includes a curved or sloping surface 108. Locking portion 98 further includes a U-shaped coil spring housing 110 for housing a coil spring 112, which is pinched between one face of the disk 104 and an inner surface of the U-shaped coil spring housing 110. Pin head 106 is received in a slot 114 formed in an end portion of each of tracks 70, 72 and is further received in the open end of axle 56. The sloping surface 108 of pin head 106 permits passage of rider 64 when the guard frame portion 12 is being rolled out of the base frame portion 14.

It can be noted that rider 64 can have a flat face 116 or a spherical face 118, as shown in phantom in FIG. 11D. A rider 64 having a spherical face 118 may more readily pass by and push in pin head 106 when the guard frame portion 12 is being slid out of the base frame portion 14.

It should be noted that rider 64, when having a spherical face 118, may obviate any need for the curved edge 108 of pin head 106, such that curved edge 108 may be deleted and pin head 106 can have a cylindrical shape and such that slot 114 can be of a circular shape rather than of a slotted or elongate shape.

It should be noted that rider 54 too can have the flat face 116 or the spherical face 118. If rider 54 includes the spherical face 118, then curved edge 108 may be eliminated and a cylindrical pin head 106 may be utilized.

In operation, to initially engage the bed rail 10 to the bed 16, the mattress 24 may (or may not) be removed from the box spring 22. Then the bed rail 10 as a whole, preferably in the operating position with the guard frame portion 12 locked in a fixed and upright position relative to the base frame portion 14, is placed on the upper side of the box spring 22. Then the outer ends of the adjustable members 76 and the counters 78 can be placed over the side 34 of the box spring 22 to be accessible once the mattress 24 is placed back on the box spring 22. Then, if the mattress 24 has been removed from the box spring 22, the mattress 24 can be laid back on top of the box spring 22. Then the adjustable members 76 and counters 78 are engaged to one or more of the mattress side 32 and box spring side 34 such that guard frame portion 12 is brought into a hugging relationship with the mattress 24 and such that upper support member 44 confronts or abuts the upper edge of the mattress side 32 to lie in or confront the plane of the sleeping surface 30. At the same time, locking portions 82, 84, functioning as counter members, engage the first side of the bed 16.

As shown in FIGS. 1A and 5, bed rail 10 is in an operating position. That is, guard frame portion 12 is in a generally upright and locked position with intermediate support member 48 abutting or at least confronting the upper edge or an upper edge portion of the side 32 of the mattress so as to close any gaps that otherwise may be present.

In the operating position, as shown in FIG. 5, both of first and second locks are locked. A first lock is an engagement between locking portion 58 (which includes pin 60) and locking portion 82 (which includes hooks 92). A second lock is an engagement between locking portion 56 (which includes axle 56) and locking portion 98 (which includes pin 102), as shown in FIG. 11A.

To begin the process to take down the bed rail 10, as shown in FIG. 6, the first lock is disengaged. That is, riders 64 are lifted upwardly, to in turn lift pin 62 upwardly and compress coil spring 66. After pin 62 clears the upper ends of the hooks 92, the guard frame portion 12 is pivoted such that the upper support member 44 swings downwardly and outwardly, as shown in FIG. 7.

The pivoting of the guard frame portion 12 relative to the base frame portion 14 continues until the guard frame portion 12 lies in substantially the same plane as the tracks 70, 72, as shown in FIG. 8. At such a point, the riders 64 have been released such that the coil spring 66 expands to place pin 62 against an end of slot 60 and to thereby stabilize the pin 62 to in turn stabilize the rider 64 that runs on the track portion 80 and that utilizes pin 62 as an axle. At such a point, an upper surface of connection 52 can make contact with a lower surface of hook section 90, such as a lower surface of hooks 92, to stop a pivoting of guard frame portion 12 relative to base frame portion 14.

Then, as shown in FIG. 9, handle 100 is pulled out (or turned out as shown in FIGS. 13A, 13B and 13C), to pull pin head 106 out of the open end of axle 56 of rider 54, thereby unlocking the second lock and permitting the guard frame portion 12 to slide relative to the base frame portion 14. Handle 100 may be maintained in the pulled out position until guard frame portion 12 is partially pushed into base frame portion 14 such that rider 64 passes beyond pin head 106. However, in the case where rider 64 includes spherical head 118, handle 100 may be maintained in the pulled out position only to dislodge pin head 106 from the open end of axle 56 whereupon handle 100 may be released, whereupon coil spring 112 pushes pin head 106 back into track 72, and whereupon rider 64 can automatically pass by pin head 106 by momentarily pushing pin head 106 out of the way and momentarily compressing coil spring 112.

Then, as shown in FIG. 10, guard frame portion 12 is yet further pushed or rolled into base frame portion 14 by virtue of the riders or rollers 54, 64 rolling on track portion 80 of the tracks 70, 72. FIGS. 2 and 3 show the guard frame portion 12 completely pushed into base frame portion 14, whereupon upper support member 44 is disposed inwardly of lock section 90, as shown in FIGS. 2 and 3 and as further shown in FIG. 2B, such that upper support member 44 has an outer edge generally flush with mattress side 32 and box spring side 34. Such is a stored position of the bed rail 10.

To take the bed rail 10 out of the stored position and to put up the bed rail 10, upper support member 44 is pulled out such that riders or rollers 54, 64 begin to run or roll on the track portions 80 such that guard frame portion 12 begins to slide out of base frame portion 14. As the riders 64 abut the pin heads 106, the pin heads 106 automatically retract (by virtue of the curved edge 108 and/or the spherical face 118 of rider 64). After the riders 64 pass the pin heads 106, the riders 54 confront the pin heads 106. Each of the pin heads 106 is initially automatically pushed out and then automatically snap into its respective open end of its respective axle 56, thereby completing a locking of the second lock and whereupon the guard frame portion 12 is fixed in a pivoting relationship relative to base frame portion 14. (It should be noted that pin heads 106 may be manually controlled by the embodiment of FIGS. 13A, 13B and 13C.) Then the upper support member 44 is swung upwardly and inwardly. As the upper support member 44 is swinging upwardly and inwardly, the pins 62 meet the curved edges 94 of the hooks 92 and automatically begin to compress their respective coil springs 66. When the pins 62 automatically pass over the ends of the hooks 92, the pins 62 automatically snap into their

respective open ended slots 96, thereby completing a locking of the first lock. As the pins snap into their respective open ended slots 96, upper support member 44 confronts and may abut the upper edge of the side 32 of mattress 24. As the pins snap into their respective open ended slots 96, the first and second locks are locked and the bed rail 10 is back in an operating position.

Bed rail 10 has an operating position at the mattress side 32 of the bed 16 in generally a first plane and a stored position below sleeping surface 30 in generally a second plane. The stored position is between the underside 36 of the mattress 24 and the upper side 38 of the box spring 22. The stored position is further generally between the two sides of the bed 16, where one side of the bed 10 is defined as a combination of mattress side 32 and box spring side 34. It should be noted that such first and second planes are generally normal to each other, though the first plane may be set at an angle slightly less than ninety degrees such that upper support member 44 can abut the upper edge of mattress 24. Bed 10 includes a lateral direction (defined as the direction between two mattress sides 32) a longitudinal direction (defined as the direction between headboard 18 and footboard 20) and a depth direction (defined as the direction between the sleeping surface 30 and the underside 36 of the mattress 24).

It should be noted that the second lock (having locking portions 56 and 98) is spaced from the first lock (having locking portions 58 and 82) in the depth direction of bed 10 to maximize a stable fixing of the guard rail portion 12 in the operating position.

It should be noted that the outward end portions of tracks 70, 72 can have a rubber or elastomeric piece 120 slipped over such outward end portion since such an outward end portion may slightly protrude from the mattress side 32 and the side 34 of box spring 22. Rubber or elastomeric piece 120 can be generally U-shaped, as shown in FIG. 10.

As to bed rail 10, including the intermediate support member 48 disposed in or confronting the plane of the sleeping surface 30 at the upper edge or upper edge portion of the mattress side 32, including the height adjustability of intermediate support member 48, including the angle of the plane of the guard frame portion 12 relative to mattress side 32, including adjustable member 76, and including counter member 78, the Flannery et al. U.S. patent application Ser. No. 10/820,358 filed Apr. 7, 2004 and entitled Mattress Hugging Bed Rail is hereby incorporated by reference in its entirety.

As shown in FIGS. 2A, 2B, 3 and 4, each of the tracks 70, 72 can have a respective stabilizer or stabilizing foot 122, 124 extending outwardly and laterally relative to its respective track 70, 72. Each of the stabilizers 122, 124 can be engaged, such as via pins, to its respective track 70, 72, is about the same height as tracks 70, 72, and extends in the same plane as the tracks 70, 72. Stabilizers 122, 124 minimize any rocking of the bed rail 10 by providing a greater surface area for resistance to any such rocking motion and by providing a greater longitudinal length to the base frame portion 14. Stabilizers 122, 124 further provide greater surface area for a pinching action by the mattress 24 and box spring 22. Stabilizers 122, 124 can be formed of a metal, plastic, wood, or composite material. Stabilizers 122, 124 can be relatively hollow or relatively solid.

FIGS. 13A and 13B show that pin 102 of handle 100 can include threads 126 that can engage a threaded opening 114 in track portion 80, where such threaded opening 114 is a generally circular opening, and that further can engage a threaded opening 128 in coil spring housing 110. In such an embodiment, handle 100 is manually turned to turn pin 102 in and out of the open end of axle 56. FIG. 13A shows the locked

11

position of the second lock and FIG. 13B shows the unlocked position of the second lock where riders 54 and 64 are free to slide or roll by the head 106 of the pin 102.

FIG. 14A shows a guard frame portion 130 having the upper support member or cross tube 44, the lower support member or cross tube 46, and a pair of upper and lower intermediate support members or cross tubes 132, 134. Upper intermediate support member 132 is shown in the plane of the sleeping surface 30. If desired, upper intermediate support member 132 can be slightly below and confronting the plane of the sleeping surface 30. Lower intermediate support member 134 confronts the plane of the sleeping surface 30 and is positioned slightly below the plane of the sleeping surface 30. The axis of lower intermediate support member 134 may be disposed at a predetermined distance from the axis of lower support member 46 and such predetermined distance is preferably between about six and 10 inches, more preferably between about seven and nine inches, and most preferably about eight inches. Each of the upper and lower intermediate support members 132, 134 confronts the side 32 of the mattress 24.

FIG. 14B shows a guard frame portion 136 having the upper support member or cross tube 44, the lower support member or cross tube 46, and a pair of upper and lower intermediate support members or cross tubes 138, 140. Upper intermediate support member 138 confronts the plane of the sleeping surface 30 and is positioned slightly below the plane of the sleeping surface 30. Lower intermediate support member 140 is positioned generally several inches below upper intermediate support member 138. The axis of upper intermediate support member 138 may be disposed at a predetermined distance from the axis of lower support member 46 and such predetermined distance is preferably between about six and 10 inches, more preferably between about seven and nine inches, and most preferably about eight inches. Each of the upper and lower intermediate support members 138, 140 confronts the side 32 of the mattress 24.

FIG. 15A shows the guard frame portion 12 of FIG. 1A where the intermediate support member 48 is disposed in the plane of the sleeping surface 30. If desired, intermediate support member 48 can confront the plane of the sleeping surface 30 at a level slightly below the plane of the sleeping surface 30.

FIG. 15B shows a guard frame portion 142 having the upper support member or cross tube 44, the lower support member or cross tube 46, and an intermediate support member or cross tube 144. Intermediate support member 144 confronts the plane of the sleeping surface 30 and is positioned slightly below the plane of the sleeping surface 30. The axis of intermediate support member 144 may be disposed at a predetermined distance from the axis of lower support member 46 and such predetermined distance is preferably between about six and 10 inches, more preferably between about seven and nine inches, and most preferably about eight inches. Intermediate support member 144 confronts the side 32 of the mattress 24.

In FIGS. 14A and 14B, it should be noted that sheeting or wall 50 is engaged between the intermediate support members 132 and 134 (in FIG. 14A) and the intermediate support members 138 and 140 (in FIG. 14B), as well as between the other support members. Sheeting or wall 50 can also envelope such support members.

It should be noted that all support members 132, 134, 138, 140, 48, and 144 are adjustable in height by manipulating a connection with the side support members 40, 42. Specifically, it should be noted that intermediate support members 134, 138, 140, 48 and 144 are strategically adjustable to and

12

away from lower support member 46. Specifically, it should be noted that intermediate support members 132, 134, upper intermediate support member 138, upper support member 48, and upper support member 144, are strategically adjustable to and away from the plane of the sleeping surface 30 and to and away from a confronting relationship with the sleeping surface 30. As to such height adjustments, the Flannery et al. U.S. patent application Ser. No. 10/820,358 filed Apr. 7, 2004 and entitled Mattress Hugging Bed Rail is hereby incorporated by reference in its entirety.

Another embodiment of the present bed rail is shown in FIGS. 16A, 16B, 17A, 17B, 18A, 18B, 18C, 19A, 19B and 21B and is indicated by reference numeral 200. Bed rail 200 includes a base frame portion 202 and a guard frame portion 204. As with bed rail 10, base frame portion 202 is engaged between a box spring 22 and mattress 24, or underneath a mattress or sleep structure 24 without a box spring, such that the guard frame portion 204 confronts or hugs the first side 32 of the bed 16. It should be noted that FIG. 16A shows the box spring 22 and mattress 24 slightly cut away so as to expose a length of the base frame portion 202. In fact, very little of the base frame portion 202 projects beyond the first side 32 of the bed. Preferably such projection is less than about one inch, more preferably less than about one-half inch, and most preferably less than one-third of an inch.

Guard frame portion 204 can be generally disposed in a first plane at the side of the bed and in a second plane between the box spring 22 and mattress 24. Base frame portion is generally disposed in the second plane between the box spring 22 and mattress 24. The guard frame portion 204 extends from below the sleeping surface 30 to above the sleeping surface 30 when the bed rail 200 is in the operating position. The guard frame portion 204 is disposed generally between the two sides of the bed when the bed rail 200 is in the stored position. It should be noted that the guard frame portion 204 can also be in the second plane after having been slid almost completely out of the base frame portion 202, and at such a location or prior to such a location, can be pivoted upwardly toward the operating position.

FIG. 16A further shows that the guard frame portion 204 is engaged to the base frame portion 202 via a pair of connections or corner connections or two point or two location connections 206. Via such connections 206, the guard frame portion 204 can pivot via base frame portion 202, can further slide via base frame portion 202, and can be fixed firmly in the operating position via the base frame portion 202. Connection 206 is described in detail below with reference to FIGS. 17B, 18A, 18B, 18C, 19A and 19B.

FIG. 16A further shows that the guard frame portion 204 includes an inverted U-shaped support member 208. U-shaped member 208 runs from one of the connections 206, up the side 32 of the bed 16, beyond the sleeping surface 30 of the bed 16, across the sleeping surface at the side 32 of the bed 16, then down the side 32 of the bed 16, and to the other of the connections 206. U-shaped member 208 is preferably formed of two generally L-shaped member sections that are engaged with each other at a center connection or region 210, where the member sections engage each other with a male/female connection and where the connection may be a quick connect engagement such as with button spring connections. The U-shaped member 208 includes side member sections 209 and upper member sections 211. U-shaped member 208 is disposed in the first plane and at about a 90 degree angle relative to base frame portion 202, or more preferably between about 85 degrees and about 89 degrees relative to base frame portion 202.

Guard frame portion **202** further includes a generally linear lower support member **212** removably engaged between the corner connections **206**. A cradle **214** is rigidly affixed to each of the ends of U-shaped member **208** and ends of the lower support member **212** are engaged in the cradles **214** via quick connects such as button springs. Lower support member **212** includes a pair of member sections that are joined via a male/female connection, which can include a quick connect that includes button springs.

Guard frame portion **202** further includes an intermediate support member **216** disposed between the lower support member **212** and the upper member sections **211** of the U-shaped member **208**. Intermediate support member **216** is removably engaged to side member sections **209** via cradles **218**. End portions of the intermediate support member **216** have button springs that can engage openings in the cradle **218**. Intermediate support member **216** can include a pair of member sections that are joined via a male/female connection, which can include a quick connect that includes button springs.

Lower support member **212**, intermediate support member **216** and upper member sections **211** are generally parallel to each other and are generally of the same length. Lower support member **212** and intermediate support member **216** are removably engaged to the side member sections **209** of U-shaped support member **208**. Upper member sections **211** are disposed above the plane of the sleeping surface **30**. Intermediate support member **216** is disposed slightly below and confronts the plane of the sleeping surface **30**. Intermediate support member **216** runs generally parallel to the plane of the sleeping surface **30**. Lower support member **212**, intermediate support member **216** and upper member sections **211** run generally at a right angle relative to side member sections **209**. U-shaped support member **208**, lower support member **212**, and intermediate support member **216** are disposed generally in a common plane.

Guard frame portion **204** includes sheeting **220**. Sheeting **220** is engaged by the lower support member **212**, intermediate support member **216**, side member sections **209** and upper member sections **211**. Sheeting **220** includes three through openings **222**, **224**, and **226** for engaging lower support member **212**, intermediate support member **216** and upper member sections **211**, respectively. Sheeting **220** further includes a pair of through openings **228** for engaging the side member sections **209**. Via the through openings **222**, **224**, **226** and **228**, via lower support member **212** and intermediate support member **216** being removably engaged to the U-shaped support member **208**, and via the upper member sections **211** being disengagable relative to each other, the sheeting **220** is removable from the guard frame portion **204** for being washed or replaced. Sheeting **220** includes a rectangular mesh section **230** disposed between the intermediate support member **216** and the upper member sections **211**. Sheeting **220** is fixed relatively tightly or tautly on guard frame portion **204**.

FIG. **16B** shows the stored compact position of the bed rail **200**. In this position, each of the guard frame portion **204** and base frame portion **202** are generally completely disposed between the box spring **22** and the mattress **24**. In such position, the guard frame portion **204** lies in a common plane with the base frame portion **202**. In such position, each of the guard frame portion **204** and base frame portion **202** are generally disposed between the two sides of the bed with the exception of the counter members **238**, **240** and **342** that engage the sides of the bed.

As shown in FIGS. **16B** and **17A**, base frame portion **202** generally includes a pair of side rails or tracks **232**, **234**, a

cross support **236** and a pair of guard support receptors or counter members **238**, **240**. Each of the side rails **232**, **234** includes a proximal end portion **242** and a distal end portion **244**. The cross support **236**, formed of two removably engaged pieces, is removably engaged between the distal end portions **244** of the side rails **232**, **234**. Each of the guard support receptors **238**, **240** is integrally and rigidly formed with its respective side rail **232**, **234** at the proximal end portion **242**. Guard support receptors **238**, **240**, rigidly affixed to the base frame portion **202**, are counter members that oppose counter members **342** (shown in FIG. **21B**) such that the bed rail **200** or base frame portion **202** continually hugs the bed, regardless of whether the guard frame portion **204** is in the operating position or the stored position and such that the base frame portion **202** provides a firm base for the guard frame portion **204** in the operating position.

FIG. **17A** shows the guard frame portion **204** in the process of being swung, namely pivoted (after having been slid from the stored, compact and planar position of FIG. **16B**) to the operating and upright position of FIG. **16A**. After having been slid out of the base frame portion **202** and after having been swung fully upright, the guard frame portion **204** engages the guard support receptors **238**, **240**.

FIGS. **17B**, **18A**, **18B**, **18C**, **19A** and **19B** show in detail a two point connection or two location connection **245** between the base frame portion **202** and guard frame portion **204** that provides for sliding and swinging of the portions **202**, **204** relative to each other and that also provides for a stable operating position of the guard frame portion **204**. Each of the rails or tracks **232**, **234** is generally a tube square in section. Each of the rails or tracks **232** includes a slot **246** formed in the inner side **248** of the tubular rail **232**, **234**. The slot **246** extends longitudinally relative to rails **232**, **234** and extends from proximal end portion **242** to the distal end portion **244**. Slot **246** is closed off at the proximal end portion **242**. Slot **246** is closed off at the distal end portion **244** by the cross member **236**. Cross member **236** is removably engaged at the distal end portions **244** via a pivoting lock **250** having one end pivotally joined to its respective side rail **232** or **234** and having another end cooperating with a slot formed in cross member **236** so as to fix the cross member **236** relative to the distal end portion **244**, as shown in FIG. **17A**.

As shown in FIG. **19A**, each of the rails **232**, **234** includes a seat or point of connection or connection **252** that is co-extensive with slot **246**. Like slot **246**, seat **252** is formed in the inner side **248** of each of the rails **232**, **234**. Slot **246** may be referred to as a horizontally extending slot. Seat **252** may be referred to as a vertically extending slot. Seat **252** is offset from slot **246**. Seat **252** extends downwardly from slot **246**.

Each of the guard support receptors **238**, **240** is integrally formed with proximal end portion **242** of its respective rail **232** or **234**. Each of the guard support receptors **238**, **240** includes a plate section **254** coplanar with the inner side **248** of its respective rail **232** or **234**. Plate section **254** extends from the bottom edge of its respective tube **232** or **234** to and beyond the upper edge of its respective tube **232** or **234** and includes a height generally about twice that of the height of tubes **232**, **234**. Plate section **254** further extends beyond proximal end **242** so as to extend forwardly of proximal end portion **242** such that a portion of seat **252** is formed in its respective rail **232**, **234** and another portion of seat **252** is formed in plate section **254**, as shown in FIG. **19A**. The portion of plate section **254** extending forwardly of the proximal end portion **242** also projects beyond the side **32** of the mattress **24** and the side **32** of the box spring **22**. The terminal end of proximal end portion **242** is preferably coplanar with or tucked slightly inwardly of the side **32** of the mattress **24**

15

and the side 32 of the box spring 22. An upper end portion of plate section 254 includes a through hole 256 for reception of a pin connector 258.

Pin connector 258 and its cooperating structure such as slot 262, opening 256 and U-shaped receptor 260 can be referred to as a point of connection or a connection. Seat 252 and rider 290 and its pin is also a point of connection or a connection.

Each of the guard support receptors 238, 240 further includes the U-shaped receptor portion 260 integral with plate section 254 and extending from an upper end portion of the plate section 254. U-shaped receptor portion 260 extends inwardly from the upper end portion of the plate section 254 and includes an open ended slot 262 for receiving pin connector 258. U-shaped receptor portion 260 receives, cradles, supports and locks therein side member section 209 of the U-shaped support member 208.

Connection 245 further includes pin connector 258 engaged in openings diametrically opposite of each other in side member section 209. Pin connector 258 includes a handle or finger handle or proximal portion 264 and a distal end 266 that engages hole 256. The proximal portion 264 is greater in width than the width of slot 262. Pin connector 258 further includes a coil spring 268 mounted within side member section 209 and biasing pin connector 258 in a direction toward hole 256 such that pin connector 258 is biased toward a locked position.

Connection 245 further includes a rider or pin connector 270, shown in FIG. 19B. Rider 270 includes two disks interconnected by a pin, with the pin being engaged with a proximal end portion of side member section 209. The portion of the pin between the two disks rides in slot 246 and may ride on edge 272 of the slot 246. One of the disks, preferably a washer, of connector 270 rides outside of its respective rail 232 or 234. The other of the disks of connector 270 rides inside of its respective rail 232 or 234. The diameter of each of the disks is greater than the width of slot 246 such that connector 270 remains engaged with its respective rail 232 or 234. It should be noted that rider or pin connector 270 can be in the nature of a wheel, with the wheel being rotatably affixed via such pin to the proximal end portion of the side member section 209. Or the rider 270 can be rigidly fixed to the proximal end portion of the side member section 209, with the disk adjacent to the side member section 209 being, for example, welded to side member 209 or running free relative to side member 209 where such piece is a washer. As well as riding in slot 246, rider or connector 270 is seatable in seat 252. When the guard frame portion 204 is fixed in the upright and operating position, rider 270 is seated in seat 252.

With reference to the following figures in the order denoted below, operation of the bed rail is explained.

In FIG. 16B, the guard frame portion 204 has been fully slid into the base frame portion 202. In this position, the proximal or bottom end portions of the side member sections 209 confront the cross member 236. In this position, the rider 270 is engaged in the slot 246. In this position, the upper member sections 211 are disposed inwardly of the side 32 of the bed 16 such that the guard frame portion 204 is generally out-of-sight. In this position, the base frame portion 202 can be engaged to the second or far side of the box spring 22 and/or the second or far side of the mattress 24 via a strap 76 and counter member 78 as shown in FIG. 2A via the counter member and strap apparatus 330 of FIG. 21B. To slide the guard frame portion 204 out of the base frame portion 202, the guard frame portion 204 is grasped at or near the central region 210 such that the upper member sections 211 are grasped and the guard frame portion 204 is slid out from between the mattress 24 and box spring 22.

16

FIG. 19A shows the guard frame portion 204 almost fully slid to the end of the base frame portion 202. Rider 270 is about to engage the seat 252. When the rider 270 reaches the seat 252, the rider 270 drops down into the seat 252 and the user manipulating the guard frame portion 204 can feel such a drop. It should be noted that, in this position shown in FIG. 19A, the guard frame portion 204 is both slideable and pivotable relative to the base frame portion 202.

FIG. 18A shows the rider 270 in the seat 252 and out of the slot 246. At this point, the guard frame portion 204 is pivotable relative to the base frame portion 202 but not slideable relative to the base frame portion 202. Again, it should be noted that even before reaching the point of dropping into seat 252, the guard frame portion 204 is pivotable relative to the base frame portion 202, limited only by the compressibility of the mattress 24 and box spring 22 and the height of the U-shaped receptor portion 260.

FIG. 18B shows the guard frame portion 204 pivoting relative to the base frame portion 202. In this position, rider 270 is in the seat 252. In this position, the user can retract or start to retract connector pin 258. If not retracted, the distal end 266 of the connector pin 258 will hit the edge of plate section 254. In this position, the distal end 266 of pin connector 258 begins to approach hole 256 and the proximal end portion of the shaft of the pin connector 258 begins to approach slot 262.

In FIG. 18C, the guard frame portion 204 has been fully swung up to the upright, operating, and locked position where rider 270 is in the seat 252, where the distal end 266 of the connector pin or lock 258 is engaged in hole 256, and where the side member section 209 is engaged in the U-shaped receptor portion 260. In such position, each of the connections or locks 245 is locked. FIG. 17B and FIG. 19B show the same fully swung up, upright, operating and locked position between guard frame portion 204 and base frame portion 202.

To bring the guard frame portion 204 down from the upright, operating and locked position, the operation is reversed. Each of the pin connectors or locks 258 is pulled out and the guard frame portion 204 is swung down. Then the guard frame portion 204 is slightly lifted up to lift riders 270 out of their respective seats 252 and into their respective slots 246. Then the guard frame portion 204 is slid into base frame portion 202 with the riders 270 sliding in their respective slots 246 until the proximal or lower end portions of the side member sections 209 confront the cross member 236 whereupon the guard frame portion 204 attains its stored, flat, compact and coplanar position with base frame portion 202.

FIG. 20 shows another embodiment of the present invention where reference number 300 indicates two bed rails 200 placed back to back so as to guard and confront the two opposite sides of a bed. A plug 302 may be inserted in two confronting open ended distal end portions 244 of the rails 232, 234 to tie the bed rails 200 back to back. Plug 302 may include a pair of holes through which ends of the cross member 236 are inserted. A method of tying two bed rails 200 back to back may include the steps of unlocking the cross members 236 by operating locks 250, removing the cross members 236 from the rails 232, 234, inserting one plug between one rail 232 and its confronting rail 234, inserting the second plug between the other rail 232 and its confronting rail 234, inserting the cross members 236 back into aligned holes formed in the plugs 302 and rails 232, 234, and locking the locks 250. It should be noted that each of the plugs 302 may be elongate and have a number of linearly arranged holes such that the bed rails 200 can be set any one of a number of distances from each other. Such two bed rails 200 act as counter members for each other, even when one bed rail 200 is in the upright and

operating position and one bed rail **200** is tucked away in the compact and stored position because of the operation of the guard support receptors **238** and **240** as counter members. Specifically, the upright plate section **254** of the guard support receptors **238**, **240** confront the sides of the bed. Guard support receptors **238**, **240** as a whole of one bed rail **200** are counters to the guard support receptors **238** and **240** of the bed rail **200** on the other side of the bed.

FIG. **21A** shows a section view of an alternate connection **310**. Alternate connection or lock **310** replaces the pin connector **258** of FIG. **17B**. Alternate connection **310** includes the U-shaped receptor portion **260** where portion **260** is more rounded than the U-shaped receptor portion **260** of FIG. **17B** so as to form a portion of a circle. A semi-circular plate **312** is hinged to portion **260** via a hinge **314** at one end. At its other end **315**, semi-circular plate **312** includes an opening **316**. Opening **316** receives a depressable button **318** on U-shaped portion **260**. When end **315** hits the slanted surface **320** of button **318**, button **318** is pushed into portion **260**. Then button **318** snaps out and into opening **316**, thus locking the semi-circular plate **312** about side member tube **209** and thus locking the guard frame portion **204** to the base frame portion **202** in the first plane. Connection or lock **310** is unlocked by pushing on button **318** and then pivoting the semi-circular plate **312** outwardly, permitting the guard frame portion **204** to pivot and swing outwardly relative to the base frame portion **202**.

FIG. **21B** shows a counter member and strap apparatus **330**. Apparatus **330** includes a strap **332** having a proximal end **334** and a distal end **336**. Strap **332** is fed through a distal loop **340** engaged to the underside of each of the side rails **232** and **234** and is further fed through a proximal loop **338** affixed to the underside of each of the side rails **232** and **234**. Such loops **338** and **340** are rigid loops, such as formed from metal. Loops **338**, **340** having an opening running in the lateral direction of the bed and running in the axial direction of the side rails **232**, **234**. Strap **332** is further fed through a lock or buckle **341** that confronts the proximal loop **338** such that the effective length of a counter member **342** is adjustable. Lock or buckle **341** is engaged to the underside of each of the side rails **232**, **234**. Strap **332** is a flexible strap formed from a material such as nylon.

Apparatus **330** further includes the counter member **342** engaged to the distal end **336** of the strap **332**. Counter member **342** is a rigid angled piece having a first portion **344** generally in line with the strap **332** and a second portion **346** disposed at generally a right angle relative to first portion **344**. A plastic or elastomer or rubber cap **348** engages an upper section of second portion **346**.

In operation, strap **332** having counter member **342** is first fed through distal loop **340** and is then fed through lock **341** and proximal loop **338**. Then, bed rail **200** is engaged to the bed by inserting the rail **200** in its flat form under the bed, placing the counter members **342** on the second side of the bed with the second portions **346** turned upwardly, drawing or sliding out the guard frame portion **204**, pivoting the guard frame portion **204** up to its locked and operating position such that the guard frame portion **204** acts as a second counter member (along with first or primary counter members **238**, **240**) and opposes the counter members **342** when strap **332** is tightened and locked, and then by actually drawing out strap **332** so as to draw counter member **342** against the second side of the bed and so as to draw the guard frame portion **204** and guard support receptors or counter members **238**, **240** against the first side of the bed and then operating buckle **341** to lock the strap **332** in place such that the counter members **342** and counter members or guard support receptors **238** and **240**

(along with guard frame portion **204**) hug the bed therebetween. It should be noted that the above operation can also be performed with the guard frame portion **204** in the flat form because guard support receptors or counter members **238**, **240** (specifically plate section **254**) act as counter members on the first side of the bed, which counter members **238**, **240** oppose and work against their respective counter members **342** such that the bed is hugged therebetween when the guard frame portion **204** is in both the stored flat out of the way position and operating position.

It can be appreciated that the buckle or lock **341** and loose or proximal end **334** of the strap **332** are disposed so as to confront the first side of the bed. This is convenient for the caregiver to set up bed rail **200**, to loosen and tighten the bed rail **200** such as when sheets are being changed, and to take the bed rail **200** off the bed.

It should be noted that loops **340** and **338** confront the respective ends of the track or rails **232**, **234** so as to maximize support in the longitudinal direction for the bed rail **200**. It should further be noted that strap **332** extends colinearly with its respective track or rail **232**, **234** and with counter member **342**.

Instead of the counter member and strap apparatus **330**, it should be noted that other types of apparatus may be used. For example, rigid members or telescoping members or other members adjustable in length in the lateral direction of the bed may be substituted for the straps.

It should be noted that the bed rail embodiments **10**, **200** and **300** are not limited to mattress and box spring types of beds. Counter members **238**, **240** are disposed on the first side of the sleeping structure and counter members **342** engaged the other side of the sleeping structure and hug the sleeping structure therebetween.

The term engagement or connection includes the term lock. It should be noted that the term lock when used herein means a structure that firmly holds. The term lock does not require a key. The term lock can include a structure or engagement or connection that requires a manual manipulation to engage and/or disengage.

It should be noted that bed rail **10** includes a two point connection arrangement and the bed rail **200** includes a two point connection arrangement.

As to bed rail **200**, it should be noted that the upper point of connection may also be a seat or vertically extending slot for a pin and, in such a case, the guard frame portion can be lifted up slightly and then brought down into the upper and lower seats and/or slots at the same time to fix the guard frame portion in the operating position. In this latter case, the slots or seats minimize lateral movement of the guard frame portion and thus maintain the guard frame portion rigidly and sturdily in the first plane. For example, a two point connection may include the upper point of connection of bed rail **10** and the lower point of connection of bed rail **200**.

In the present case, a connection can be a restriction against movement in at least one direction, such as a restriction against movement in a lateral direction and/or a restriction against movement in a depth direction and/or a restriction against movement in a longitudinal direction and/or a restriction against movement in a swinging direction, and thus in this sense a seat or a slot is a connection or fixed connection.

The base frame **202** includes a cross support **236** engaged between distal end portions **244** of the first and second tracks **232**, **234**. The guard frame **204** includes a first edge **211**. The first edge **211** is a top edge when the guard frame **204** is in the operating position. The first edge **211** is an outside edge when the guard frame **204** is in the stored position. The distal end portions **244** of the first and second tracks **232**, **234** are distal

19

of the guard frame 204 when the guard frame 204 is in the operating position. The distal end portions 244 of the first and second tracks 232, 234 are distal of the first edge 211 when the guard frame 204 is in the stored position.

The guard frame 204, the base frame 202, the first track 232 5 and the tube of the first track 232, the second track 234 and the tube of the second track 234, the first rider 270, the second rider, and the cross support 236 form a one-piece unit that can be engaged to the bed 16 as said one-piece unit and that can be taken off the bed 16 as said one-piece unit. 10

As shown in FIGS. 18A, 18B, 18C, 19A and 19B, track 232 includes a tube having an interior and a longitudinal slot 246, with the rider 270 extending laterally through the longitudinal slot to ride in the interior of the tube of the track 232.

Thus since the invention disclosed herein may be embodied 15 in other specific forms without departing from the spirit or general characteristics thereof, some of which forms have been indicated, the embodiments described herein are to be considered in all respects illustrative and not restrictive. The scope of the invention is to be indicated by the appended claims, rather than by the foregoing description, and all 20 changes which come within the meaning and range of equivalents of the claims are intended to be embraced therein.

I claim:

1. A combination comprising:

- a) a bed, the bed having a head end, a foot end, a first side, a second side, a mattress, and a box spring, the mattress having a sleeping surface; and
- b) a bed rail, the bed rail adaptable for connection to the bed, the bed rail comprising:
 - i) a guard frame, the guard frame having an operating position at one of the sides of the bed in generally a

20

first plane, the guard frame having a stored position below the sleeping surface in generally a second plane, the stored position of the guard frame being generally between the first and second sides of the bed and below the sleeping surface, the stored position of the guard frame being generally between the head end and the foot end of the bed, the stored position of the guard frame being between the mattress and box spring; and

- ii) a base frame connected to the guard frame, the base frame having a base position below the sleeping surface in generally a second plane, the base position of the base frame being generally between the first and second sides of the bed and below the sleeping surface, the base position of the base frame being generally between the head end and the foot end of the bed, the base position of the base frame being between the mattress and box spring;
- iii) wherein the guard frame is pivotable and slideable relative to the base frame, and wherein the guard frame is slideable into the base frame.

2. The combination of claim 1, wherein the base frame further comprises a first counter member for engaging the first side of the bed.

25 3. The combination of claim 1, wherein the base frame further comprises a second counter member for engaging the second side of the bed.

4. The combination of claim 1, wherein the base frame further comprises a first counter member for engaging the first side of the bed and a second counter member for engaging the 30 second side of the bed.

* * * * *