

(10) **Patent No.:** US 9,132,921 B2  
(45) **Date of Patent:** Sep. 15, 2015

4,150,803 A \* 4/1979 Fernandez ..... 244/135 A

7,246,774	B2 *	7/2007	Von Thal et al. ....	244/135 A
7,469,863	B1 *	12/2008	Speer .....	244/135 A
7,472,868	B2 *	1/2009	Schuster et al. ....	244/135 A
7,769,543	B2	8/2010	Stecko et al.	

FOREIGN PATENT DOCUMENTS			
EP	2397405	A1	12/2011
WO	2009082400	A1	7/2009

\* cited by examiner

*Primary Examiner* — Benjamin P Lee

(74) *Attorney, Agent, or Firm* — Yee & Associates, P.C.

(57) **ABSTRACT**

A method and apparatus comprising a refueling controller. The refueling controller is configured to receive a number of operator commands for moving a refueling boom on a tanker aircraft in a desired direction. The number of operator commands defines at least one of an azimuth movement and an elevation movement of the refueling boom during flight of the tanker aircraft. The refueling controller is further configured to generate a number of intermediate commands for moving the refueling boom in the desired direction as defined by the number of operator commands. The number of intermediate commands defines at least one of a roll movement and a pitch movement such that the refueling boom moves in the desired direction.

## 12 Claims, 12 Drawing Sheets


## 12 Claims, 12 Drawing Sheets

## 12 Claims, 12 Drawing Sheets

## 12 Claims, 12 Drawing Sheets

## 12 Claims, 12 Drawing Sheets

## 12 Claims, 12 Drawing Sheets






FIG. 1





FIG. 2

FIG. 3






FIG. 4






FIG. 5








FIG. 8




FIG. 9






FIG. 10




FIG. 11




FIG. 12





FIG. 13

FIG. 14






FIG. 15




FIG. 16




FIG. 17



## 1

## REFUELING BOOM CONTROL SYSTEM

## BACKGROUND INFORMATION

## 1. Field

The present disclosure relates generally to aircraft and, in particular, to refueling aircraft. Still more particularly, the present disclosure relates to a method and apparatus for managing movement of a refueling boom for a refueling aircraft.

## 2. Background

Aerial refueling is the process of transferring fuel from one aircraft to another aircraft during flight. The aircraft from which the fuel originates is referred to as a tanker aircraft. The aircraft receiving the fuel is referred to as a receiver aircraft. This type of refueling process may be applied to various types of receiver aircraft, tanker aircraft, or both receiver aircraft and tanker aircraft. The various types of aircraft may include fixed wing aircraft, rotor wing aircraft, and other suitable types of aircraft.

One common approach for refueling aircrafts during flight involves the use of a refueling boom and a receptacle system. The refueling boom may be comprised of a tube that is fixed on a tanker aircraft or may be a telescoping refueling boom on the tanker aircraft. The refueling boom may be attached to the rear of the tanker aircraft. This refueling boom may move along three axes relative to the aircraft. In some cases, the refueling boom also may be flexible. An operator may extend a refueling boom and also may reposition the refueling boom for insertion into a receptacle on the receiver aircraft. When the end of the refueling boom is inserted into a receptacle of the receiver aircraft, the refueling boom may then be considered to be connected to the receiver aircraft. When a connection is made, fuel may be transferred from the tanker aircraft to the receiver aircraft through the refueling boom.

When the operator moves the refueling boom to make the connection with the aircraft, the operator performs this operation using a control device. This control device may take the form of a control stick. This control stick may be similar to a joystick. The operator moves the control stick in different directions to cause the refueling boom to move in different directions.

Moreover, different tanker aircraft have different types of systems for positioning the refueling boom. As a result, an operator that is trained and experienced with refueling operations in one type of tanker aircraft may not be able to control the refueling boom as easily in another type of tanker aircraft. The different controls and operations performed to move the refueling boom may be different between the different types of tanker aircraft.

In one example, a refueling boom may move about a rotational axis. More specifically, the refueling boom may move about a pitch and roll axis. The operator may move the control stick in a direction to correspond with the desired pitch and roll movement of the refueling boom. This type of input control may be more complicated than desired and may not be as intuitive to a less-experienced boom operator.

Consequently, an operator that works in more than one type of tanker aircraft may need training for the different types of tanker aircraft. As a result, in order to perform refueling operations in different types of tanker aircraft, an operator spends additional time in training and in practicing on different types of tanker aircraft.

This difference in the controls for performing refueling operations may result in more training and expense than desired. Further, if the different operators are not familiar with all the different types of tanker aircraft used, then the operators prepared for performing missions on a particular

## 2

type of aircraft may not be available as desired. Therefore, it would be desirable to have a method and apparatus that takes into account at least some of the issues discussed above, as well as other possible issues.

## SUMMARY

In one illustrative embodiment, an apparatus comprises a refueling controller. The refueling controller is configured to receive a number of operator commands for moving a refueling boom on a tanker aircraft in a desired direction. The number of operator commands defines at least one of an azimuth movement and an elevation movement of the refueling boom during flight of the tanker aircraft. The refueling controller is further configured to generate a number of intermediate commands for moving the refueling boom in the desired direction as defined by the number of operator commands. The number of intermediate commands defines at least one of a roll movement and a pitch movement such that the refueling boom moves in the desired direction.

In another illustrative embodiment, a method for moving a refueling boom on a tanker aircraft is present. A number of operator commands is received for moving the refueling boom on the tanker aircraft in a desired direction. The number of operator commands defines at least one of an azimuth movement and an elevation movement of the refueling boom during flight of the tanker aircraft. A number of intermediate commands is generated for moving the refueling boom in the desired direction as defined by the number of operator commands. The number of intermediate commands defines at least one of a roll movement and a pitch movement such that the refueling boom moves in the desired direction.

In yet another illustrative embodiment, a method for moving a refueling boom on a tanker aircraft is present. Operator commands generated by a control device are received. The operator commands are for a first type of movement of the refueling boom. Intermediate commands are generated for a second type of movement that causes a movement of the refueling boom using the first type of movement.

The features and functions can be achieved independently in various embodiments of the present disclosure or may be combined in yet other embodiments in which further details can be seen with reference to the following description and drawings.

## BRIEF DESCRIPTION OF THE DRAWINGS

The novel features believed characteristic of the illustrative embodiments are set forth in the appended claims. The illustrative embodiments, however, as well as a preferred mode of use, further objectives and features thereof, will best be understood by reference to the following detailed description of an illustrative embodiment of the present disclosure when read in conjunction with the accompanying drawings, wherein:

FIG. 1 is an illustration of a refueling environment in which an illustrative embodiment may be implemented;

FIG. 2 is a detailed illustration of a refueling boom in accordance with an illustrative embodiment;

FIG. 3 is a detailed illustration of a support system in accordance with an illustrative embodiment;

FIG. 4 is an illustration of a block diagram of a refueling environment in accordance with an illustrative embodiment;

FIG. 5 is an illustration of a refueling system in accordance with an illustrative embodiment;

FIG. 6 is an illustration of a graph of a refueling boom envelope in accordance with an illustrative embodiment;



## 3

FIG. 7 is another illustration of a graph of a refueling boom envelope in accordance with an illustrative embodiment;

FIG. 8 is an illustration of the movement of a refueling boom in response to the movement of a control stick in accordance with an illustrative embodiment;

FIG. 9 is another illustration of the movement of a refueling boom in response to the movement of a control stick in accordance with an illustrative embodiment;

FIG. 10 is another illustration of the movement of a refueling boom in response to the movement of a control stick using a command transformer in accordance with an illustrative embodiment;

FIG. 11 is another illustration of the movement of a refueling boom in response to the movement of a control stick using a command transformer in accordance with an illustrative embodiment;

FIG. 12 is an illustration of a flowchart of a process for moving refueling boom on a tanker aircraft in accordance with an illustrative embodiment;

FIG. 13 is an illustration of a flowchart of a process for moving a refueling boom on a tanker aircraft in accordance with an illustrative embodiment;

FIG. 14 is an illustration of an equation flow for obtaining a Jacobian inverse matrix for use in generating roll and pitch commands from azimuth and elevation commands in accordance with an illustrative embodiment;

FIG. 15 is an illustration of a block diagram of a data processing system in accordance with an illustrative embodiment;

FIG. 16 is an illustration of an aircraft manufacturing and service method in accordance with an illustrative embodiment; and

FIG. 17 is an illustration of an aircraft in which an illustrative embodiment may be implemented.

## DETAILED DESCRIPTION

The different illustrative embodiments recognize and take into account one or more considerations. For example, the illustrative embodiments recognize and take into account that the differences in the controls used to control a refueling boom may increase the difficulty in performing refueling operations with different types of tanker aircraft. Further, the illustrative embodiments recognize and take into account that one control that may be different between different types of tanker aircraft is the manner in which a refueling boom moves in response to a movement of a control stick.

The illustrative embodiments also recognize and take into account that if the operator moves the control stick in one direction, the refueling boom may not always move in the direction that corresponds to the movement of the control stick. For example, the operator may move the control stick to the left. The operator may expect that the refueling boom will move an azimuth direction in the refueling boom envelope. This type of movement, however, may not occur with all types of tanker aircraft. Depending on the type of tanker aircraft, the refueling boom may move with a roll movement and a pitch movement to the left rather than just moving to the left.

This roll movement and pitch movement may be a result of the kinematics of the refueling boom. In other words, the manner in which the refueling boom is moved may be a pitch movement and a roll movement rather than a similar movement to the movement of the control stick in an azimuth direction and/or an elevation direction.

Thus, the operator may need to input commands in the control stick to move the refueling boom along the pitch and roll axis. In this example, moving the refueling boom in the

## 4

azimuth direction in the refueling environment may take coordinated control stick input by the operator. As a result, the operator adjusts to moving the control stick in a manner that provides for the desired movement.

This adjustment in the way an operator moves the control stick, however, may not be as natural of a feel as compared to a refueling boom that moves in an azimuth direction and an elevation direction that corresponds to movement of the control stick in a left and right or forward and backward direction. Further, this type of roll movement and pitch movement requires additional training and experience as compared to a refueling boom that moves in an azimuth direction and elevation direction in response to a similar movement of the control stick.

Thus, the illustrative embodiments provide a method and apparatus for managing the movement of a refueling boom. One or more illustrative embodiments provide an ability to have refueling booms move in the same direction in different types of tanker aircraft with respect to the same movement of a control stick.

Operator commands generated by control devices are received. The operator commands are for a first type of movement of the refueling boom. Intermediate commands are generated for a second type of movement that causes movement of the refueling boom using the first type of movement.

In another illustrative example, a refueling controller may be configured to receive a number of operator commands for moving the refueling boom on the tanker aircraft in a desired direction. The number of operator commands define at least one of an azimuth movement and an elevation movement of the refueling boom during flight of the tanker aircraft. Further, the refueling controller may generate a number of intermediate commands for moving the refueling boom in the desired direction as defined by the number of operator commands. The number of intermediate commands define at least one of a roll movement and a pitch movement such that the refueling boom moves in a desired direction.

With reference now to the figures and, in particular, with reference to FIG. 1, an illustration of a refueling environment is depicted in accordance with an illustrative embodiment. In this illustrative example, refueling environment 100 includes aircraft 102 transferring fuel to aircraft 104. Aircraft 102 is tanker aircraft 106, while aircraft 104 is receiver aircraft 108.

In these illustrative examples, refueling boom 110 on tanker aircraft 106 is connected to receiver aircraft 108. As depicted, fuel is transferred from tanker aircraft 106 to receiver aircraft 108 through refueling boom 110.

An illustrative embodiment may be implemented in tanker aircraft 106 to manage the movement of refueling boom 110. In particular, one or more illustrative embodiments may be implemented in tanker aircraft 106 to manage the movement of refueling boom 110 in a manner that is more intuitive to an operator of refueling boom 110 in tanker aircraft 106. A more detailed illustration of refueling boom 110 in section 112 is depicted in FIG. 2.

With reference now to FIG. 2, a detailed illustration of a refueling boom is depicted in accordance with an illustrative embodiment. In this illustrative example, a more detailed view of section 112 with refueling boom 110 in FIG. 1 is shown.

As depicted, refueling boom 110 includes fixed tube 200, telescoping tube 202, nozzle 204, and control surfaces 205. Fixed tube 200 may also move in an elevation direction as indicated by arrow 212. This type of movement in the elevation direction may be referred to as an elevation movement of refueling boom 110. Arrow 212 may be used to describe movement along a z-axis.



## 5

Telescoping tube **202** may extend or retract along the direction of arrow **214**. Arrow **214** may be used to describe movement along the refueling boom axis.

Refueling boom **110** also may move in an azimuth direction as indicated by arrow **216**. Arrow **216** may be used to describe movement along a y-axis. This type of movement may be referred to as an azimuth movement of refueling boom **110**.

The movement of refueling boom **110** in the elevation direction as indicated by arrow **212** and along the azimuth direction as indicated by arrow **216** may be controlled using control surfaces **205**. In some illustrative examples, rudder **206**, rudder **208**, and elevator **209** are control surfaces **205** that control the movement of refueling boom **110**. Control surfaces **205** form force generator **210** for refueling boom **110**. In other illustrative examples, other control surfaces in addition to or in place of rudder **206**, rudder **208**, and elevator **209** in control surface **205** may be present to control the movement of refueling boom **110**.

The movement of refueling boom **110** also may be performed using roll movement and pitch movement. For example, refueling boom **110** may have a roll as indicated by arrow **220**. Additionally, refueling boom **110** also may have a pitch movement as indicated by arrow **222**. Control surfaces **205** may be used to control the pitch movement and roll movement of refueling boom **110**.

With the illustrative embodiments, the movement of refueling boom **110** along arrow **214**, arrow **216**, arrow **212**, and in other directions may be controlled by the operator in a more intuitive manner. Further, the control of refueling boom **110** may be such that the control device used by the operator moves refueling boom **110** in the same manner with different types of refueling aircraft even though different types of systems for moving refueling boom **110** may be present.

The type of movement that occurs may depend on support structure **230**. In other words, depending on support structure **230**, refueling boom **110** may move in an azimuth direction and an elevation direction, in a rolling direction and a pitching direction, or in some other manner in response to movement of a control device in tanker aircraft **106**.

Of course, although support structure **230** may provide for a type of movement such as a roll movement and a pitch movement, refueling boom **110** may be moved effectively with an azimuth movement and an elevation movement through a more complex movement of the control device. In other words, movement of the control device in first direction may typically provide for a roll movement while movement of the control device in a second direction may provide for a pitch movement.

To obtain an azimuth movement, the illustrative embodiments also recognize that a combination of directions of movement may be required to be input by the operator into the control device. In this manner, the desired type of movement of refueling boom **110** may be obtained, but with more complex and less natural movements in the control device. In other words, movement of the control device in one direction or another direction may not result in an azimuth movement or an elevation movement in these illustrative examples.

Thus, one or more illustrative embodiments may include mapping commands generated by a control device that are intended for an azimuth movement and an elevation movement into one or more commands that are for roll movement and pitch movement. Mapping commands from the control device to the refueling boom control system may allow an operator to obtain the desired type of movement of refueling boom **110**. A more detailed illustration of support structure **230** in section **232** is shown in FIG. **3** below.

## 6

In these illustrative examples, the configuration of force generator **210** may affect the manner in which refueling boom **110** may move. In other words, the configuration of force generator **210** may result in different types of movement for refueling boom **110**. For example, force generator **210** may cause azimuth movement and elevation movement in some cases. In other cases, force generator **210** may result in roll movement and pitch movement. In this illustrative example, rudder **206**, rudder **208**, and elevator **209** are configured such that movement of a control device in one direction results in a roll movement and movement of the control device in another direction results in a pitch movement. This type of movement is in contrast to an azimuth movement and an elevation movement for the same type of movement of the control device.

With reference now to FIG. **3**, a detailed illustration of a support system is depicted in accordance with an illustrative embodiment. FIG. **3** is a more detailed illustration of section **232** from FIG. **2**.

In this illustrative example, the support system that supports refueling boom **110** includes boom support fitting **300**, gimbal **302**, link **304**, and link **306**. Link **304** and link **306** may provide damping, resistance or both to movements and vibrations of gimbal **302**. As depicted, gimbal **302** has a pitching gimbal point **309** and refueling boom **110** has a pitching gimbal point **307**. Pitching gimbal point **307** and pitching gimbal point **309** are points about which gimbal **302** and refueling boom **110** move.

In this illustrative example, refueling boom **110** does not roll about boom axis **308**. Instead, refueling boom **110** rolls about gimbal axis **310**. Gimbal axis **310** extends through gimbal **302** in this illustrative example. Gimbal **302** may rotate about axis **312**, while refueling boom **110** may move about axis **314**. As refueling boom **110** pitches about axis **314**, gimbal **302** does not rotate about axis **312**. Similarly, as gimbal **302** rotates about axis **312**, refueling boom **110** does not move about axis **314**. In this manner, a “double pitch” system is present that allows for movement of either gimbal **302** or refueling boom **110** without the movement of the other structure.

As can be seen, this configuration of support structure **230** provides for roll movement in response to movement of a control device in a first direction and a pitch movement in response to movement of the control device in a second direction. The second direction may be substantially perpendicular to the first direction.

Turning now to FIG. **4**, an illustration of a block diagram of a refueling environment is depicted in accordance with an illustrative embodiment. The different components in refueling environment **100** in FIG. **1** and in FIG. **3** are examples of one physical implementation for refueling environment **400** shown in block form in this figure.

As depicted, aircraft **402** may provide fuel **404** to aircraft **406**. Aircraft **402** is tanker aircraft **408**, while aircraft **406** is receiver aircraft **410**. In this illustrative example, fuel **404** is transferred from tanker aircraft **408** to receiver aircraft **410** using refueling boom **412**.

Operator refueling station **414** provides a location for operator **416** to control refueling boom **412**. As depicted, operator refueling station **414** includes display **418** and control device **419**. In this illustrative example, control device **419** is a hardware device that is configured to control movement of refueling boom **412**. Control device **419** takes the form of control stick **420**. Other types of control devices may include, for example, without limitation, a mouse, a keyboard, a joystick, a touch screen, and other suitable types of control devices.



Display **418** is configured to display information about refueling boom **412** as well as other information about the refueling operation to transfer fuel **404** to receiver aircraft **410**. Display **418** also may display video images of refueling boom **412** at receiver aircraft **410** to operator **416**.

Operator **416** may manipulate control stick **420** to generate operator input **422**. In other words, as operator **416** manipulates control stick **420**, control stick **420** generates operator input **422**. In these illustrative examples, operator input **422** takes the form of operator commands **424**.

As depicted, operator commands **424** are received by refueling controller **426**. Refueling controller **426** may take the form of hardware, software, or a combination of the two. When software is used, the operations performed by refueling controller **426** may be implemented in program code configured to be run on a processor unit. When hardware is employed, the hardware may include circuits that operate to perform the operations in refueling controller **426**.

In these illustrative examples, the hardware may take the form of a circuit system, an integrated circuit, an application specific integrated circuit (ASIC), a programmable logic device, or some other suitable type of hardware configured to perform a number of operations. When software is used a programmable logic device may be configured to perform the number of operations. The device may be reconfigured at a later time or may be permanently configured to perform the number of operations. Examples of programmable logic devices include, for example, a programmable logic array, a programmable array logic, a field programmable logic array, a field programmable gate array, and other suitable programmable logic devices. Additionally, the processes may be implemented in organic components integrated with inorganic components and/or may be comprised entirely of organic components excluding a human being. For example, the processes may be implemented as circuits in organic semiconductors.

As depicted, refueling controller **426** may be implemented in computer system **428**. Computer system **428** is one or more computers. When more than one computer is present in computer system **428**, those computers may be in communication with each other via a communications medium such as a network.

In these illustrative examples, refueling controller **426** may include control laws **432**. Control laws **432** may be implemented as software, hardware, or a combination of the two. As depicted, control laws **432** are configured to control refueling boom **412**. The control of refueling boom **412** by control laws **432** may include processing operator commands **424** in operator input **422** received from operator refueling station **414**.

In these illustrative examples, refueling controller **426** may process operator commands **424** in operator input **422** using control laws **432** to generate commands **434**. In particular, commands **434** may take the form of movement commands **435**. Movement commands **435** are sent to refueling boom unit **436**. As depicted, operator refueling station **414**, refueling controller **426**, and refueling boom unit **436** form refueling system **437**.

As depicted, refueling boom unit **436** includes sensors **438**, movement system **440**, and refueling boom **412**. In these illustrative examples, sensors **438** are configured to generate data **442** about refueling boom **412**. Data **442** may include, for example, without limitation, the configuration of movement system **440**, the position of refueling boom **412**, images of refueling boom **412**, and other suitable information.

In these illustrative examples, sensors **438** may include at least one of an inertial measurement unit, a position sensor, an

accelerometer, a load sensor, a global positioning system device, and other suitable devices. In some illustrative examples, one or more of sensors **438** may be associated with refueling boom **412**.

In these illustrative examples, movement system **440** is configured to control movement of refueling boom **412**. As depicted, movement commands **435** are used by movement system **440** to move refueling boom **412**.

In this illustrative example, movement system **440** includes support system **444** and force generation system **446**. Support system **444** includes physical structures used to support refueling boom **412**. Support system **444** may include stationary structures **448** and moveable structures **450**. These structures support and allow for movement of refueling boom **412**.

The movement of refueling boom **412** may be caused by force generation system **446**. In this illustrative example, force generation system **446** may include at least one of actuator system **452**, control surfaces **454**, and other suitable components.

Actuator system **452** is one or more actuators configured to cause movement of refueling boom **412**. This movement may be caused directly or indirectly. For example, actuator system **452** may cause movement of refueling boom **412** indirectly by causing movement of moveable structure **450** in support system **444**.

Control surfaces **454** include one or more control surfaces that may be associated with refueling boom **412**. The position of these control surfaces may cause movement of refueling boom **412**. Control surfaces **454** may include, for example, at least one of a flap, an elevator, a ruddervator, a rudder, and other types of control surfaces.

Depending on the design of movement system **440**, the type of movement provided by movement system **440** may vary. In these illustrative examples, movement system **440** may provide for number of types of movement **470**. For example, number of types of movement **470** provided by movement system **440** may include first type of movement **472** and second type of movement **474**.

First type of movement **472** may include azimuth movement **476** and elevation movement **478**. Second type of movement **474** may include rolling movement **480** and pitching movement **482**.

In these illustrative examples, the type of movement generated by movement system **440** depends on the configuration of at least one of support system **444** and force generation system **446** in movement system **440**. In these illustrative examples, the type of movement provided is the movement that occurs when control device **419** is moved in one direction.

For example, movement system **440** may provide movement in directions with azimuth movement and elevation movement. In other examples, other configurations of movement system **440** may provide movement in directions with roll movement and pitch movement. Of course, still other types of movement may be provided depending on the configuration of movement system **440**.

Depending on the type of movement provided by movement system **440**, movement of refueling boom **412** may not be as intuitive for operator **416** as desired. For example, operator **416** may move control stick **420** in one direction that corresponds to azimuth movement from the perspective of operator **416**.

However, operator commands **424** may result in movement system **440** moving in a direction with a roll movement. More specifically, refueling boom **412** may first have a roll movement rather than an azimuth movement. The roll movement of



the refueling boom does not correspond to the movement of control stick **420** in the azimuth direction.

Movement commands **435** are generated in a manner that makes movement of control device **419** and the movement of refueling boom **412** more intuitive or easier for operator **416**. In these illustrative examples, command transformer **456** is present in refueling controller **426**. Command transformer **456** may be implemented using hardware, software, or a combination of the two. Command transformer **456** is configured to transform operator commands **424** generated by control stick **420** into intermediate commands **458**.

Intermediate commands **458** result in commands **434** that cause refueling boom **412** to move in a direction that substantially corresponds to the direction of movement of control device **419**. In particular, the movement of refueling boom **412** may move in a manner that corresponds to movement of control stick **420** when moved by operator **416** in these illustrative examples.

The illustration of refueling environment **400** and the different components in refueling environment **400** in FIG. **4** is not meant to imply physical or architectural limitations to the manner in which an illustrative embodiment may be implemented. Other components in addition to or in place of the ones illustrated may be used. Some components may be unnecessary. Also, the blocks are presented to illustrate some functional components. One or more of these blocks may be combined, divided, or combined and divided into different blocks when implemented in an illustrative embodiment.

In another illustrative example, control stick **420** may be moved in other directions other than left, right, forward, and backward. In other words, control stick **420** may be moved in directions other than a first direction and a second direction that is substantially perpendicular to the first direction. For example, control stick **420** also may be moved in a diagonal direction. This diagonal direction may be 45 degrees from the first direction, the second direction, or both. This type of movement results in a combination of azimuth and elevation commands being generated.

In yet another illustrative example, refueling system **437** may include additional components in addition to operator refueling station **414**, refueling controller **426**, and refueling boom unit **436**. In some illustrative examples, refueling boom **412** may also include fuel tanks that store fuel **404**.

Turning now to FIG. **5**, an illustration of a refueling system is depicted in accordance with an illustrative embodiment. Refueling system **500** is an example of one implementation for refueling system **437** in FIG. **4**.

As depicted, refueling system **500** includes control stick **502**, non-linear command transformer **504**, boom control law **506**, refueling boom **110**, and force generation system **510**. Control stick **502** is an example of a physical implementation for control stick **420** shown in block form in FIG. **4**. Refueling boom **110** and force generation system **510** are examples of physical implementations for refueling boom **412** and force generation system **446** shown in block form in FIG. **4**. Non-linear command transformer **504** is an example of command transformer **456** in FIG. **4**.

In this illustrative example, movement of control stick **502** in first direction **512** is an example of left and right movement of control stick **502**. This type of movement causes the generation of operator azimuth command ( $\Psi$ ) **514**. Movement of control stick **502** in second direction **516** is an example of forward and backward movement of control stick **502**. This type of movement causes the generation of operator elevation command ( $\Theta$ ) **518**.

The movement of control stick **502** in first direction **512** and second direction **516** are examples of movement that

corresponds more intuitively to movement of refueling boom **110**. In particular, this movement is azimuth movement and elevation movement of refueling boom **110**.

In this illustrative example, boom control law **506** interprets operator elevation command ( $\Theta$ ) **518** and operator azimuth command **514** ( $\Psi$ ) as pitch commands and roll commands resulting in pitch movement and roll movement instead. This type of movement of refueling boom **110** in response to movement of control stick **502** is not as intuitive as desired.

For example, when moving control stick **502** in the azimuth direction, the operator may expect refueling boom **110** to move directly in the azimuth direction corresponding to the movement of control stick **502**. In other words, if the operator moves control stick **502** directly to the right, the operator may expect refueling boom **110** to move to that location. However, because of the kinematics of refueling boom **110**, pitch commands and roll commands may be taken into account. As a result, the movement of refueling boom **110** using currently available systems is more complex than desired.

As an example, an operator may need to move the control stick in multiple directions to move refueling boom **110** to a desired location while taking into account the pitch and roll kinematics of the boom. Thus, with use of the illustrative embodiments, control stick commands may be automatically transformed to account for the kinematics of refueling boom **110**. In other words, the movement of control stick **502** becomes more intuitive with the use of boom control law **506**.

As depicted, boom control law **506** interprets these commands and transforms these commands to account for the kinematics of the support structure. In other words, the manner in which the refueling boom is moved may be a pitch movement and a roll movement rather than a similar movement to the movement of the control stick in an azimuth direction and/or an elevation direction.

In these illustrative examples, the desired movement for refueling boom **110** is an azimuth movement in response to movement of control stick **502** in first direction **512** and an elevation movement in response to movement of control stick **502** in second direction **516**. This type of movement of refueling boom **110** in response to the movement of control stick **502** is a more intuitive and desirable type of movement.

Non-linear command transformer **504** is an example of an implementation of command transformer **456** in FIG. **4**. Non-linear command transformer **504** makes the non-linear transformation of elevation and azimuth commands into pitch and roll commands. In this manner, non-linear command transformer **504** takes into account the kinematics of support system **444**.

In these illustrative examples, non-linear command transformer **504** is configured to generate pitch commands and roll commands to provide the desired azimuth movement and elevation movement. In other words, non-linear command transformer **504** is configured to map elevation commands and azimuth commands into pitch commands and roll commands.

For example, when operator azimuth command ( $\Psi$ ) **514** is received by non-linear command transformer **504**, non-linear command transformer **504** is configured to generate roll command ( $\phi$ ) **520** and pitch command ( $\theta$ ) **522** in a manner that provides for azimuth movement without elevation movement. When operator elevation command ( $\Theta$ ) **518** is received by non-linear command transformer **504**, non-linear command transformer **504** generates roll command ( $\phi$ ) **520** and pitch command ( $\theta$ ) **522** in a manner that provides for elevation movement without azimuth movement as set out in operator elevation command ( $\Theta$ ) **518**.



## 11

Boom control law **506** is an example of a control law in control laws **432** in FIG. 4. Boom control law **506** is configured to receive pitch and roll commands such as pitch command ( $\theta$ ) **522** and roll command ( $\phi$ ) **520**. In this illustrative example, boom control law **506** generates combinations of one or more of right rudder command **524**, left rudder command **526**, and elevator command **528**. These commands are used to change the configuration of force generation system **510**. In particular, the commands change the configuration of control surfaces **205** in force generation system **510**, which include rudder **206**, rudder **208**, and elevator **209**.

The change in the configuration of control surfaces **205** in force generation system **510** results in a movement of refueling boom **110** in the azimuth direction in response to operator azimuth command **514** ( $\Psi$ ) generated by movement of control stick **502** in first direction **512** instead of a roll movement. Additionally, the change in the configuration of control surfaces **205** in force generation system **510** results in elevation movement of refueling boom **110** in response to operator elevation command ( $\Theta$ ) **518** generated in response to movement of control stick **502** in second direction **516** instead of a pitch movement.

Thus, non-linear command transformer **504** provides a mapping of operator elevation commands and operator azimuth commands in a manner that generates pitch commands and roll commands that cause refueling boom **110** to move in an elevation direction or an azimuth direction. This type of movement of refueling boom **110** in response to the movements described for control stick **502** are considered corresponding movements. In other words, the movement of control stick **502** in first direction **512** results in a movement of refueling boom **110** that corresponds to the movement of control stick **502**. The movement of refueling boom **110** is an azimuth movement. Thus, the movement of refueling boom **110** in response to movement of control stick **502** is more intuitive.

Further, a similar movement of control stick **502** in second direction **516** results in a corresponding movement of refueling boom **110**. In other words, the movement of control stick **502** in first direction **512** and second direction **516** are linear movements. The movements of refueling boom **110** are corresponding movements that are also linear movements in these illustrative examples.

Turning now to FIG. 6, an illustration of a graph of a refueling boom envelope is depicted in accordance with an illustrative embodiment. In this illustrative example, graph **600** is a graph of boom envelope **602**. X-axis **604** represents azimuth, and Y-axis **606** represents elevation. Line **608** represents the mechanical limits of boom envelope **602**. Line **610** represents limits based on control laws.

In this illustrative example, operator azimuth command ( $\Psi$ ) **514** in FIG. 5 results in a roll movement as indicated by line **612**. Operator elevation command ( $\Theta$ ) **518** in FIG. 5 results in a pitching movement as indicated by line **614**. As can be seen, line **612** corresponding to the roll movement indicates movement in the azimuth direction and elevation direction. This movement is generated in response to operator azimuth command ( $\Psi$ ) **514** when non-linear command transformer **504** in FIG. 5 is not used.

In other words, boom control law **506** in FIG. 5 interprets operator azimuth command ( $\Psi$ ) **514** generated by movement in first direction **512** in FIG. 5 as a roll command rather than an azimuth command. Movement in second direction **516** generates operator elevation command ( $\Theta$ ) **518** in FIG. 5 which is interpreted as a pitch command rather than elevation command.

## 12

In particular, movement of control stick **502** in a line in first direction **512** does not result in the same type of movement of refueling boom **110** in FIG. 5 as shown by line **612**. Thus, the movement of control stick **502** does not result in corresponding movement of refueling boom **110** when that command is interpreted directly by boom control law **506** without the use of non-linear command transformer **504** in FIG. 5.

This type of command system using boom control law **506** without non-linear command transformer **504** is less intuitive because movement of refueling boom **110** does not substantially correspond to movement of control stick **502** in FIG. 5. As a result, more adjustments may need to be made by operator **416** in the manner in which control stick **502** is moved to cause refueling boom move to the desired location.

Turning now to FIG. 7, an illustration of a graph of a refueling boom envelope is depicted in accordance with an illustrative embodiment. In this illustrative example, graph **700** is a graph of boom envelope **702**. X-axis **704** represents azimuth and Y-axis **706** represents elevation. Line **708** represents the mechanical limits of boom envelope **702**. Line **710** represents limits based on control laws.

In this illustrative example, operator azimuth command ( $\Psi$ ) **514** in FIG. 5 results in movement as indicated by line **712**. As can be seen, this movement is only in the azimuth direction and not the elevation direction as compared to movement indicated by line **612** in FIG. 6. This movement substantially corresponds to the movement of control stick **502** in FIG. 5. In other words, movement of control stick **502** in first direction **512** results in movement of refueling boom **110** in FIG. 5 as indicated by line **712** instead of line **612** in FIG. 6.

In a similar fashion, operator elevation command ( $\Theta$ ) **518** in FIG. 5 results in movement of refueling boom **110** as indicated by line **714**. The movement in line **714** is only in the elevation direction and does not include movement in the azimuth direction. This movement occurs instead of the movement indicated by line **614** in FIG. 6 when non-linear command transformer **504** is not used.

Thus, movement of control stick **502** in a line results in a similar movement of refueling boom **110**. When control stick **502** is moved in first direction **512**, refueling boom **110** only moves in the azimuth direction and not in the elevation direction.

The illustration of refueling system **500** in FIG. 5 and the graphs of refueling boom envelopes in FIG. 6 and FIG. 7 for refueling system **500** are only some examples of an implementation for refueling system **437** in FIG. 4. These illustrations and graphs are not meant to imply limitations to other implementations of refueling system **437** in FIG. 4. For example, although refueling system **500** employs non-linear command transformer **504** in FIG. 5, other implementations may use a linear command transformer. Thus, the transformation provided in different command transformers in different refueling systems may be selected from at least one of a linear transformation and a non-linear transformation.

Turning now to FIG. 8, an illustration of the movement of a refueling boom in response to the movement of a control stick is depicted in accordance with an illustrative embodiment. The movement of refueling boom **110** in FIG. 1 occurs with the use of a command transformer.

As depicted, control stick **502** is moved in the direction of arrow **800**. Arrow **800** is in first direction **512**. In particular, arrow **800** represents a movement to the left relative to operator **802**. When operating refueling boom **110**, operator **802** faces the rear of the aircraft in these illustrative examples. Thus, movement to the left relative to operator **802** results in



## 13

movement of refueling boom 110 in a direction toward the right wing of the tanker aircraft, such as tanker aircraft 106 in FIG. 1.

As can be seen, this movement of control stick 502 in the direction of arrow 800 causes movement of refueling boom 110 as indicated by line 804. As can be seen, line 804 shows a roll movement of refueling boom 110.

This movement is not the desired movement of refueling boom 110 when operator 802 moves control stick 502 in the direction of arrow 800. Line 804 indicates movement in both elevation and azimuth, which is undesirable based on the movement of control stick 502 in the direction of arrow 800.

Turning now to FIG. 9, another illustration of the movement of a refueling boom in response to the movement of a control stick is depicted in accordance with an illustrative embodiment. The movement of refueling boom 110 occurs with the use of a command transformer.

After being moved in the direction of arrow 800 in FIG. 8, control stick 502 is now moved in the direction of arrow 900. Arrow 900 is in second direction 516 which is substantially perpendicular to first direction 512. In this example, arrow 900 is a backward movement relative to operator 802. Because operator 802 faces the rear of the aircraft when operating refueling boom 110, movement of control stick 502 in the direction of arrow 900 results in movement of refueling boom 110 toward the fuselage of the tanker aircraft.

This movement of control stick 502, however, results in the movement of refueling boom 110 as indicated by line 902. This movement is a pitch movement which includes movement in both an azimuth and elevation direction. This type of movement is undesirable with respect to the movement of control stick 502 in the direction of arrow 900 in this particular example.

Turning now to FIG. 10, another illustration of the movement of a refueling boom in response to the movement of a control stick using a command transformer is depicted in accordance with an illustrative embodiment. In this example, control stick 502 is again moved in the direction of arrow 800.

However, when a command transformer is used in the refueling controller, refueling boom moves in the direction as indicated by line 1000. Line 1000 indicates the refueling boom moves in a substantially azimuth direction and not in an elevation direction. This type of movement corresponds to the movement of control stick 502 in the direction of arrow 800.

Turning now to FIG. 11, another illustration of the movement of a refueling boom in response to the movement of a control stick using a command transformer is depicted in accordance with an illustrative embodiment. In this example, control stick 502 is moved in the direction of arrow 900. This backward movement of control stick 502 in the direction of arrow 900 results in refueling boom 110 moving along line 1100.

In this illustrative example, line 1100 is substantially in an elevation direction and not in an azimuth direction. This movement corresponds to the movement of control stick 502 in the direction of arrow 900.

The illustration of the movement of refueling boom 110 in FIGS. 8-11 are only examples of some types of movement that may occur. For example, a movement of control stick 502 in a diagonal direction to first direction 512 and second direction 516 may result in an elevation and pitch movement in the same corresponding manner of refueling boom 110. Other movements such as moving control stick 502 to the left or backward may result in azimuth movement or elevation movement as desired, rather than movement that may include rolling and pitching without the use of a command transformer.

## 14

The different components shown in FIGS. 1-3, 5, and 8-11 may be combined with components in FIG. 2 and FIG. 4, used with components in FIG. 2 and FIG. 4, or a combination of the two. Additionally, some of the components in FIG. 1 and FIG. 2 may be illustrative examples of how components shown in block form in FIG. 2 and FIG. 4 can be implemented as physical structures.

Turning now to FIG. 12, an illustration of a flowchart of a process for moving a refueling boom on a tanker aircraft is depicted in accordance with an illustrative embodiment. The process illustrated in FIG. 12 may be implemented in tanker aircraft 408 in FIG. 4. In particular, this process may be implemented using refueling system 437 in FIG. 4.

The process begins by receiving operator commands generated by a control device for a first type of movement (operation 1200). The operator commands are for the first type of movement of the refueling boom. This first type of movement may be, for example, movement in an azimuth direction and an elevation direction.

The process generates intermediate commands for a second type of movement that causes a movement of a refueling boom using the first type of movement (operation 1202) with the process terminating thereafter. This second type of movement may be, for example, movement in a roll direction and a pitch direction. These intermediate commands are commands such as roll and pitch commands that result in the desired azimuth and elevation movement as indicated by the operator commands that are in the form of azimuth commands and elevation commands.

Turning now to FIG. 13, an illustration of a flowchart of a process for moving a refueling boom on a tanker aircraft is depicted in accordance with an illustrative embodiment. The process illustrated in FIG. 13 may be implemented in refueling system 437 in FIG. 4.

The process begins by receiving a number of operator commands for moving a refueling boom on a tanker aircraft in a desired direction (operation 1300). These operator commands define at least one of an azimuth movement and an elevation movement of the refueling boom during flight of the tanker aircraft.

The process generates a number of intermediate commands for moving the refueling boom in the desired direction as defined by the number of operator commands (operation 1302). The process then sends the number of intermediate commands to control laws (operation 1304). In response, movement commands are sent to a movement system to move the refueling boom (operation 1306) with the process terminating thereafter.

The flowcharts and block diagrams in the different depicted embodiments illustrate the architecture, functionality, and operation of some possible implementations of apparatus and methods in an illustrative embodiment. In this regard, each block in the flowcharts or block diagrams may represent a module, segment, function, and/or a portion of an operation or step. For example, one or more of the blocks may be implemented as program code, in hardware, or a combination of the program code and hardware. When implemented in hardware, the hardware may, for example, take the form of integrated circuits that are manufactured or configured to perform one or more operations in the flowcharts or block diagrams.

In some alternative implementations of an illustrative embodiment, the function or functions noted in the blocks may occur out of the order noted in the figures. For example, in some cases, two blocks shown in succession may be executed substantially concurrently, or the blocks may sometimes be performed in the reverse order, depending upon the



## 15

functionality involved. Also, other blocks may be added in addition to the illustrated blocks in a flowchart or block diagram.

Turning now to FIG. 14, an illustration of an equation flow for obtaining a Jacobian inverse matrix for use in generating roll and pitch commands from azimuth and elevation commands is depicted in accordance with an illustrative embodiment. Equation flow 1400 is a diagram of equations used to derive a Jacobian inverse matrix for use in command transformer 456 in FIG. 4.

For example, command transformer 456 may provide a refueling boom to aircraft transformation. In other words, command transformer 456 may provide for a mapping from the rotating type of movement of the aircraft to more linear movement provided using boom coordinates. For example, roll movement and pitch movement may be mapped to azimuth movement and elevation movement.

In one illustrative example, this transformation may be provided by using transformation equation 1402. In transformation equation 1402,  $C_{ba}$  is the rotation from the aircraft transformed to boom coordinates,  $\theta_b$  is the pitch angle of the refueling boom,  $\phi$  is the roll axis, and  $\theta_i$  is the pitch angle of the rolling gimbal point. In these illustrative examples, the rolling gimbal point is the point about which the gimbal provides movement. Pitching gimbal point 307 and pitching gimbal point 309 in FIG. 3 are examples of pitching gimbal points.

The boom tip location may be identified using equation 1404 and equation 1406. These two equations identify a coordinate system for the boom. In these two equations,  $X_b$ ,  $Y_b$ , and  $Z_b$  are coordinates of the tip of the refueling boom.  $X_t$ ,  $Y_t$ ,  $Z_t$  are the transposed coordinates using the transposed function as indicated in equation 1406.

Equation 1404 and equation 1406 assume the origin is at a boom pivot, such as rolling gimbal point 307 in FIG. 3. A positive value of  $X$  in these examples is in a direction from the rolling gimbal point toward the nose of the tanker aircraft. A negative value of  $X$  is in a direction from the rolling gimbal point toward the end of the boom.

A positive value for  $Y$  is in a direction from the rolling gimbal point outward from the right wing of the aircraft. A negative value for  $Y$  is in a direction from the rolling gimbal point outward from the left wing of the aircraft. A positive value of  $Z$  is in a direction from the rolling gimbal point downward from the aircraft and a negative value of  $Z$  is in direction from rolling gimbal point upward from the aircraft.

The azimuth angle for the refueling boom may be defined using equation 1408. Thus, the azimuth angle may be represented as equation 1410.

The elevation angle is defined using equation 1412. In this example, the elevation angle may also be represented using equation 1414. Equation 1410 and equation 1414 may be used in equation 1420. Equation 1420 is a Jacobian matrix in these illustrative examples.

A Jacobian matrix is illustrated in equation 1420. When the azimuth and elevation are expanded to take the partial derivatives of azimuth angle in equation 1410 and elevation angle in equation 1414, Jacobian matrix 1422 results. An inverse of Jacobian matrix 1422 results in inverse Jacobian matrix 1424. Inverse Jacobian matrix 1424 is one illustrative example of an equation that may be used in command transformer 456 to provide a mapping of commands for azimuth movement and elevation movement into commands for roll movement and pitch movement that results in the desired azimuth movement and elevation movement.

Turning now to FIG. 15, an illustration of a block diagram of a data processing system is depicted in accordance with an

## 16

illustrative embodiment. Data processing system 1500 may be used to implement one or more computers in computer system 428 in tanker aircraft 408 in FIG. 4.

In this illustrative example, data processing system 1500 includes communications framework 1502, which provides communications between processor unit 1504, memory 1506, persistent storage 1508, communications unit 1510, input/output unit 1512, and display 1514. In this example, communication framework may take the form of a bus system.

Processor unit 1504 serves to execute instructions for software that may be loaded into memory 1506. Processor unit 1504 may be a number of processors, a multi-processor core, or some other type of processor, depending on the particular implementation.

Memory 1506 and persistent storage 1508 are examples of storage devices 1516. A storage device is any piece of hardware that is capable of storing information, such as, for example, without limitation, data, program code in functional form, and/or other suitable information either on a temporary basis and/or a permanent basis. Storage devices 1516 may also be referred to as computer readable storage devices in these illustrative examples. Memory 1506, in these examples, may be, for example, a random access memory or any other suitable volatile or non-volatile storage device. Persistent storage 1508 may take various forms, depending on the particular implementation.

For example, persistent storage 1508 may contain one or more components or devices. For example, persistent storage 1508 may be a hard drive, a flash memory, a rewritable optical disk, a rewritable magnetic tape, or some combination of the above. The media used by persistent storage 1508 also may be removable. For example, a removable hard drive may be used for persistent storage 1508.

Communications unit 1510, in these illustrative examples, provides for communications with other data processing systems or devices. In these illustrative examples, communications unit 1510 is a network interface card.

Input/output unit 1512 allows for input and output of data with other devices that may be connected to data processing system 1500. For example, input/output unit 1512 may provide a connection for user input through a keyboard, a mouse, and/or some other suitable input device. Further, input/output unit 1512 may send output to a printer. Display 1514 provides a mechanism to display information to a user.

Instructions for the operating system, applications, and/or programs may be located in storage devices 1516, which are in communication with processor unit 1504 through communications framework 1502. The processes of the different embodiments may be performed by processor unit 1504 using computer-implemented instructions, which may be located in a memory, such as memory 1506.

These instructions are referred to as program code, computer usable program code, or computer readable program code that may be read and executed by a processor in processor unit 1504. The program code in the different embodiments may be embodied on different physical or computer readable storage media, such as memory 1506 or persistent storage 1508.

Program code 1518 is located in a functional form on computer readable media 1520 that is selectively removable and may be loaded onto or transferred to data processing system 1500 for execution by processor unit 1504. Program code 1518 and computer readable media 1520 form computer program product 1522 in these illustrative examples. In one



17

example, computer readable media **1520** may be computer readable storage media **1524** or computer readable signal media **1526**.

In these illustrative examples, computer readable storage media **1524** is a physical or tangible storage device used to store program code **1518** rather than a medium that propagates or transmits program code **1518**.

Alternatively, program code **1518** may be transferred to data processing system **1500** using computer readable signal media **1526**. Computer readable signal media **1526** may be, for example, a propagated data signal containing program code **1518**. For example, computer readable signal media **1526** may be an electromagnetic signal, an optical signal, and/or any other suitable type of signal. These signals may be transmitted over communications links, such as wireless communications links, optical fiber cable, coaxial cable, a wire, and/or any other suitable type of communications link.

The different components illustrated for data processing system **1500** are not meant to provide architectural limitations to the manner in which different embodiments may be implemented. The different illustrative embodiments may be implemented in a data processing system including components in addition to and/or in place of those illustrated for data processing system **1500**. Other components shown in FIG. **15** can be varied from the illustrative examples shown. The different embodiments may be implemented using any hardware device or system capable of running program code **1518**.

Illustrative embodiments of the disclosure may be described in the context of aircraft manufacturing and service method **1600** as shown in FIG. **16** and aircraft **1700** as shown in FIG. **17**. Turning first to FIG. **16**, an illustration of an aircraft manufacturing and service method is depicted in accordance with an illustrative embodiment. During pre-production, aircraft manufacturing and service method **1600** may include specification and design **1602** of aircraft **1700** in FIG. **17** and material procurement **1604**.

During production, component and subassembly manufacturing **1606** and system integration **1608** of aircraft **1700** in FIG. **17** takes place. Thereafter, aircraft **1700** in FIG. **17** may go through certification and delivery **1610** in order to be placed in service **1612**. While in service **1612** by a customer, aircraft **1700** in FIG. **17** is scheduled for routine maintenance and service **1614**, which may include modification, reconfiguration, refurbishment, and other maintenance or service.

Each of the processes of aircraft manufacturing and service method **1600** may be performed or carried out by a system integrator, a third party, and/or an operator. In these examples, the operator may be a customer. For the purposes of this description, a system integrator may include, without limitation, any number of aircraft manufacturers and major-system subcontractors; a third party may include, without limitation, any number of vendors, subcontractors, and suppliers; and an operator may be an airline, a leasing company, a military entity, a service organization, and so on.

With reference now to FIG. **17**, an illustration of an aircraft is depicted in which an illustrative embodiment may be implemented. Aircraft **1700** may be one example of aircraft **102** and aircraft **104** shown in FIG. **1**.

In this example, aircraft **1700** is produced by aircraft manufacturing and service method **1600** in FIG. **16** and may include airframe **1702** with plurality of systems **1704** and interior **1706**. Examples of systems **1704** include one or more of propulsion system **1708**, electrical system **1710**, hydraulic system **1712**, and environmental system **1714**. Any number of other systems may be included.

Apparatuses and methods embodied herein may be employed during at least one of the stages of aircraft manu-

18

facturing and service method **1600** in FIG. **16**. For example, one or more illustrative embodiments may be implemented to develop aircraft **1700** during specification and design **1602**. In another illustrative example, command transformer **456** in FIG. **4** may be included in aircraft **1700** during system integration **1608**. For example, hardware, software, or both hardware and software for command transformer **456** may be implemented in aircraft **1700** during the assembly of aircraft **1700** in system integration **1608**. Further, command transformer **456** in FIG. **4** also may be included in aircraft **1700** during maintenance and service **1614** as a modification, an upgrade, or a refurbishment of aircraft **1700**.

Thus, the illustrative embodiments provide a method and apparatus for moving a refueling boom. In particular, one or more illustrative embodiments may provide a capability to generate commands to move a refueling boom in directions that correspond to direction of movement of a control stick. For example, if a control stick is moved in a first direction for an azimuth direction, the command transformer generates appropriate commands such that the control laws in the refueling controller generate commands to the refueling boom unit that moves the refueling boom in an azimuth direction rather than some other type of movement.

The description of the different illustrative embodiments has been presented for purposes of illustration and description, and is not intended to be exhaustive or limited to the embodiments in the form disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art. Further, different illustrative embodiments may provide different features as compared to other illustrative embodiments. The embodiment or embodiments selected are chosen and described in order to best explain the principles of the embodiments, the practical application, and to enable others of ordinary skill in the art to understand the disclosure for various embodiments with various modifications as are suited to the particular use contemplated.

What is claimed is:

1. A method for moving a refueling boom on a tanker aircraft, the method comprising:

receiving a number of operator commands for moving the refueling boom on the tanker aircraft in a desired direction, wherein the number of operator commands defines at least one of an azimuth movement and an elevation movement of the refueling boom during flight of the tanker aircraft; and

generating a number of intermediate commands for moving the refueling boom in the desired direction as defined by the number of operator commands, wherein the number of intermediate commands defines at least one of a roll movement and a pitch movement such that the refueling boom moves in the desired direction;

wherein the operator commands include an operator azimuth command and an operator elevation command; and wherein the roll movement and the pitch movement result in substantially linear azimuth movement of the refueling boom from the operator azimuth command and substantially linear elevation movement of the refueling boom from the operator elevation command.

2. The method of claim 1, wherein receiving the number of operator commands for moving the refueling boom on the tanker aircraft in the desired direction, wherein the number of operator commands defines at least one of the azimuth movement and the elevation movement of the refueling boom during flight of the tanker aircraft comprises:

receiving the number of operator commands for moving the refueling boom on the tanker aircraft in the desired direction, wherein the number of operator commands



19

defines at least one of the azimuth movement and the elevation movement of the refueling boom during flight of the tanker aircraft, wherein the number of operator commands is generated by movement of a control device.

3. The method of claim 1, wherein receiving the number of operator commands for moving the refueling boom on the tanker aircraft in the desired direction, wherein the number of operator commands defines at least one of the azimuth movement and the elevation movement of the refueling boom during flight of the tanker aircraft comprises:

receiving the number of operator commands for moving the refueling boom on the tanker aircraft in the desired direction, wherein the number of operator commands defines at least one of the azimuth movement and the elevation movement of the refueling boom during flight of the tanker aircraft, wherein the number of operator commands is generated by movement of a control stick.

4. The method of claim 1 further comprising:

identifying a movement of a control device in a direction; and

generating the number of operator commands based on the movement of the control device in the direction, wherein the number of operator commands defines at least one of the azimuth movement and the elevation movement of the refueling boom during flight of the tanker aircraft for moving the refueling boom in the desired direction.

5. The method of claim 4, wherein generating the number of intermediate commands for moving the refueling boom in the desired direction as defined by the number of operator commands, wherein the number of intermediate commands defines at least one of the roll movement and the pitch movement such that the refueling boom moves in the desired direction comprises:

generating the number of operator commands for the azimuth movement in response to the movement of the control device in a first direction; and

generating the number of operator commands for the elevation movement in response to the movement of the control device in a second direction, wherein the number of operator commands defines at least one of the azimuth movement and the elevation movement of the refueling boom during flight of the tanker aircraft for moving the refueling boom in the desired direction.

6. The method of claim 1, wherein the receiving step and the generating step are performed in a command transformer in a refueling controller in the tanker aircraft.

20

7. The method of claim 1, wherein the intermediate commands are generated using an inverse Jacobian Matrix.

8. A method for moving a refueling boom on a tanker aircraft, the method comprising:

receiving operator commands generated by a control device, wherein the operator commands are for a first type of movement of the refueling boom, wherein the operator commands include an operator azimuth command and an operator elevation command; and

generating intermediate commands for a second type of movement that causes a movement of the refueling boom using the first type of movement, wherein the intermediate commands define at least one of a roll movement and a pitch movement and wherein the second type of movement results in substantially linear azimuth movement of the refueling boom from the operator azimuth command and substantially linear elevation movement of the refueling boom from the operator elevation command.

9. The method of claim 8, wherein receiving the operator commands generated by the control device, wherein the operator commands are for the first type of movement of the refueling boom comprises:

receiving the operator commands generated by the control device, wherein the operator commands are for the first type of movement of the refueling boom in which the first type of movement is an azimuth movement and an elevation movement.

10. The method of claim 8, wherein generating the intermediate commands for the second type of movement that causes the movement of the refueling boom using the first type of movement comprises:

generating the intermediate commands for the second type of movement that causes the movement of the refueling boom using the first type of movement in which the second type of movement is a roll movement and a pitch movement and the first type of movement is an azimuth movement and elevation movement.

11. The method of claim 8, wherein the control device is a control stick and further comprising:

moving the control stick in a first direction to generate a pitch command for azimuth movement; and

moving the control stick in a second direction to generate a roll command for elevation movement.

12. The method of claim 8, wherein the receiving step and the generating step are performed in a command transformer in a refueling controller in the tanker aircraft.

\* \* \* \* \*