

US009156632B2

(12) **United States Patent**
Maeda et al.

(10) **Patent No.:** **US 9,156,632 B2**
(45) **Date of Patent:** ***Oct. 13, 2015**

(54) **CONVEYING APPARATUS**

(71) Applicant: **SINFONIA TECHNOLOGY CO., LTD.**, Tokyo (JP)

(72) Inventors: **Minoru Maeda**, Tokyo (JP); **Yosuke Muraguchi**, Tokyo (JP); **Mamoru Kosaki**, Tokyo (JP); **Takashi Fujiwara**, Tokyo (JP)

(73) Assignee: **SINFONIA TECHNOLOGY CO., LTD.**, Tokyo (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **13/970,375**

(22) Filed: **Aug. 19, 2013**

(65) **Prior Publication Data**

US 2014/0054136 A1 Feb. 27, 2014

(30) **Foreign Application Priority Data**

Aug. 21, 2012 (JP) 2012-182091

(51) **Int. Cl.**

H01L 21/67 (2006.01)
B65G 54/02 (2006.01)
H02K 41/02 (2006.01)
H02K 41/03 (2006.01)
H01L 21/677 (2006.01)
H02K 5/128 (2006.01)

(52) **U.S. Cl.**

CPC **B65G 54/02** (2013.01); **H01L 21/67709** (2013.01); **H02K 5/128** (2013.01); **H02K 41/02** (2013.01); **H02K 41/031** (2013.01)

(58) **Field of Classification Search**

CPC H01L 21/67709; H02K 41/031; H02K 5/128; H02K 41/02; B65G 25/04; B65G 54/02

USPC 198/619
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,641,054 A * 6/1997 Mori et al. 198/619
5,838,079 A * 11/1998 Morohashi et al. 310/12.24
6,326,708 B1 * 12/2001 Tsuboi et al. 310/12.06
6,348,746 B1 * 2/2002 Fujisawa et al. 310/12.24
6,873,404 B2 * 3/2005 Korenaga 355/72
7,211,908 B2 * 5/2007 Tamaki 310/12.25

(Continued)

FOREIGN PATENT DOCUMENTS

JP 2010-41889 A 2/2010

Primary Examiner — Gene Crawford


Assistant Examiner — Thomas Randazzo

(74) *Attorney, Agent, or Firm* — Knobbe Martens Olson & Bear LLP

(57) **ABSTRACT**

To provide a conveying apparatus that includes: a fixed section; a movable section movable with respect to the fixed section; and a pair of linear motors each located so as to be partially included in the fixed section and the movable section. Each linear motor includes a primary magnetic pole section and a secondary magnetic pole section, and these pole sections are arranged to face each other so as to enable the movable section to move with respect to the fixed section. The movable section includes a movable body capable of conveying a conveyed object, and one of the magnetic pole sections of each linear motor. Each linear motor is located at each of opposite ends of the movable body in a width direction that is orthogonal to a moving direction, and the fixed section includes the other of the magnetic pole sections.

8 Claims, 4 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

7,226,270	B2 *	6/2007	Hwang et al.	414/749.1	8,368,254	B2 *	2/2013	Hanamura et al.	310/12.02
7,633,188	B2 *	12/2009	Kitade et al.	310/12.23	8,522,958	B2 *	9/2013	Tobe et al.	198/619
7,859,142	B2 *	12/2010	Armeit et al.	310/12.24	2006/0012251	A1 *	1/2006	Miyata et al.	310/12
7,888,827	B2 *	2/2011	Kaneshige et al.	310/12.21	2009/0191030	A1 *	7/2009	Bluck et al.	414/217
8,330,307	B2 *	12/2012	Nagasaka	310/12.29	2010/0036523	A1 *	2/2010	Sato et al.	700/228
					2012/0247925	A1 *	10/2012	Cooke	198/617
					2013/0228415	A1 *	9/2013	Iwasaki et al.	198/339.1

* cited by examiner

FIG. 1




FIG. 2




FIG. 3





FIG. 4



1**CONVEYING APPARATUS****CROSS-REFERENCE TO RELATED APPLICATIONS**

This application claims the benefit of Japanese Patent Application No. 2012-182091, the contents of which are incorporated herein by reference.

FIELD

The present invention relates to a conveying apparatus driven by a linear motor.

BACKGROUND**Citation List****Patent Literature**

Patent Literature: Japanese Patent Application Laid-Open No. 2010-41889

A conveying apparatus driven by a linear motor is widely known. An example of such a conveying apparatus is described in Patent Literature 1. A movable section of the conveying apparatus, on which a conveyed object is mountable, is movable (specifically reciprocable) in the longitudinal direction of the conveying apparatus. A primary magnetic pole section, which projects upward and extends in the longitudinal direction of the movable section, is provided on the bottom surface of a housing of the conveying apparatus. Further, the movable section is provided with secondary magnetic pole sections which project downward, extend in the longitudinal direction of the movable section and located so as to hold therebetween the primary magnetic pole section from the opposite sides in the width direction of the movable section.

In the conveying apparatus described in Patent Literature 1, the single primary magnetic pole section is located at the center in the width direction of the housing, and the secondary magnetic pole sections are located so as to hold therebetween the primary magnetic pole section from the opposite sides in the width direction of the movable section. Therefore, it is necessary that a space, through which the secondary magnetic pole sections can pass, is secured on the opposite outer sides of the primary magnetic pole section in the width direction over the movable range of the movable section. For this reason, the utilization of the central space inside the housing is restricted.

As described above, the utilization of the central space inside the housing is restricted, and hence when various units, such as sensors, and a unit for lifting a conveyed object on the table, are to be arranged, these units may be subjected to restriction in space in which they arrangeable.

SUMMARY

Accordingly, an object of the present invention is to provide a conveying apparatus in which the space used for arranging various units is less restricted.

According to the present invention, there is provided a conveying apparatus, which includes:

- a fixed section;
- a movable section movable with respect to the fixed section; and
- a pair of linear motors each located so as to be partially included in the fixed section and the movable section, wherein

2

each of the linear motors includes a primary magnetic pole section and a secondary magnetic pole section, and the primary magnetic pole section and the secondary magnetic pole section are arranged to face each other so as to enable the movable section to move with respect to the fixed section,

the movable section includes a movable body capable of conveying a conveyed object, and one of the primary magnetic pole section and the secondary magnetic pole section of each of the pair of linear motors, each of the pair of linear motors being located at each of opposite ends of the movable body in a width direction that is orthogonal to a moving direction, and

the fixed section includes the other of the primary magnetic pole section and the secondary magnetic pole section.

Note that the term “opposite ends” includes not only end edge positions but also positions in the vicinity of end edge.

The secondary magnetic pole section of each of the pair of linear motors may include a permanent magnet at a position facing the primary magnetic pole section.

Further, the conveying apparatus may be configured so that the fixed section includes a supporting section which supports the movable section from below,

the supporting section includes a guide section which regulates the moving direction of the movable section and extends in a longitudinal direction,

the movable section includes a guided section which is movable while being engaged with the guide section, and

a load reduction mechanism, which presses the movable section upward with magnetic repulsion force or magnetic attraction force to thereby reduce weight load applied to the guide section and the guided section, is provided at a position directly above or directly below the guide section and the guided section.

Note that the term “directly above” or “directly below” described above includes not only a vertically above or below position but also a position in the vicinity of the vertically above or below position.

Further, the conveying apparatus may be configured so that the guide section and the guided section are located at opposite ends in the width direction of the fixed section and the movable section, and

the movable section includes mounting sections located outside or inside of the guide section and the guided section in the width direction, the mounting sections being for attaching one of the primary magnetic pole section and the secondary magnetic pole section.

BRIEF DESCRIPTION OF DRAWINGS

The foregoing and other features of the present invention will become apparent from the following description and drawings of an illustrative embodiment of the invention in which:

FIG. 1 is a perspective view showing a conveying apparatus of a present embodiment;

FIG. 2 is a longitudinal sectional view showing the conveying apparatus of the present embodiment;

FIG. 3 is a longitudinal sectional view showing another embodiment; and

FIG. 4 is a longitudinal sectional view showing still another embodiment.

DESCRIPTION OF EMBODIMENTS

An embodiment according to the present invention will be described below with reference to the drawings. As for the directions, the following description is given under the

assumption that the direction coincident with the long-side direction of a housing **1** is the longitudinal direction, and that the direction orthogonal to the longitudinal direction is the width direction. Note that the vertical and horizontal directions are based on the state of the present embodiment. However, for example, an embodiment, in which the upper and lower sides are reversed with respect to the state of the present embodiment (that is, an embodiment in which a conveyed object is hung and conveyed), can also be implemented. Therefore, the present invention is not limited to the form shown in the directions of the present embodiment. Further, as for the inner and outer directions, the description is given under the assumption that the direction directed toward the center in the width direction of the housing **1** is the inner direction, and that, on the contrary, the direction away from the center in the width direction of the housing **1** is the outer direction.

As shown in FIG. **1** and FIG. **2**, a conveying apparatus of the present embodiment includes a housing **1**, a conveying table **2**, a linear motor **3**, a linear guide **4**, and a load reduction mechanism **5**. Each of the components is arranged to be line-symmetrical with respect to the center in the width direction of the housing **1**.

The housing **1** functions as a fixed section and has a rectangular parallelepiped box-like external shape. Note that the fixed section is composed of the housing **1**, a part of the linear motor **3**, a part of the linear guide **4**, and a part of the load reduction mechanism **5**. The housing **1** includes a bottom wall section **11** located on the lower side thereof, side wall sections **12** located on the four sides thereof, and a top wall section (not shown for the purpose of description) located on the upper side thereof. Primary magnetic pole sections **31**, each of which constitutes the linear motor **3**, are arranged on the upper surface of the bottom wall section **11**. Further, the side wall section **12** is provided with a step section which has an upward facing surface extending in the longitudinal direction. The step section is composed of two portions, upper and lower, of a lower step section **13** and an upper step section **14**. The lower step section **13** functions as a supporting section which supports the conveying table **2** from below the conveying table **2**. A guide rail **41**, which constitutes the linear guide **4**, is arranged on the upper surface of the lower step section **13**. Further, an attraction plate **51**, which constitutes the load reduction mechanism **5**, is arranged on the upper surface of the upper step section **14**.

A processing chamber, which has a surrounded space and extends in the longitudinal direction, is formed by the wall sections. In the present embodiment, the bottom wall section **11** and the side wall section **12** are integrally formed of an aluminum alloy, and the wall sections are air-tightly combined with each other. Therefore, the processing chamber can be maintained in a vacuum state or a pressure-reduced state.

The conveying table **2** functions as a movable body in the movable section provided to be movable with respect to the fixed section. The conveying table **2** is located at an upper portion of the housing **1** (specifically above the bottom wall section **11**). Note that the movable section is composed of the conveying table **2**, a part of the linear motor **3**, a part of the linear guide **4**, and a part of the load reduction mechanism **5**, and is movable in the longitudinal direction. The conveying table **2** is movable (specifically reciprocable) in the longitudinal direction in the housing **1** by being driven by the linear motor **3**. The conveying table **2** includes a mounting section **21** located on the central side in the width direction, and supported sections **22** respectively located on opposite sides of the conveying table **2** in the width direction. A conveyed object, such as an electronic component (for example, a sili-

con wafer), is mounted on the upper surface of the mounting section **21** so as to be conveyed. Incidentally, the longitudinal dimension of the conveying table **2** is set according to the dimension of the conveyed object. A unit, such as, for example, a robot arm, which can perform operations, such as operations of moving, lifting, rotating the conveyed object on the conveying table **2**, may be arranged at the mounting section **21**. Further, the supported section **22** is formed to be lower by one step than the mounting section **21**. The linear guide **4** is located under the supported section **22**, and the load reduction mechanism **5** is located above the supported section **22**.

The conveying table **2** includes, at each of opposite ends thereof in the width direction, a secondary support bracket **23** as a mounting section for supporting a secondary magnetic pole section **32** which constitutes the linear motor **3**. The secondary support bracket **23** is formed in a plate shape so as to extend downward from the lower surface of the mounting section **21**. Further, the conveying table **2** includes, at each position on the outside of the secondary support bracket **23** in the width direction, a guide block **42** which constitutes the linear guide **4**. Further, a permanent magnet **52**, which constitutes the load reduction mechanism **5**, is attached to the upper surface of each of the opposite ends of the conveying table **2** in the width direction. Further, a part of a sensor for detecting the longitudinal position of the conveying table **2** is provided on the upper surface of the conveying table **2**. In the present embodiment, this part is a magnet section **612** of a magnetostrictive sensor **61**. Note that, as shown in FIG. **1**, the magnetostrictive sensor **61** can detect the longitudinal position of the magnet section **612** (that is, the longitudinal position of the conveying table **2**) in such a manner that torsional distortion, which is imparted by the magnet section **612** to a magnetostrictive line section **611** that is provided at the housing **1** so as to extend in the longitudinal direction, is detected by a detecting section **613** located at one end of the magnetostrictive line section **611**. Further, a power supply mechanism (not shown) for supplying electric power to a unit such as a robot arm, is provided, as required, on the conveying table **2**.

Next, the linear motor **3** will be described. The linear motor **3** is configured between the fixed section and the movable section (so as to straddle between the fixed section and the movable section). The linear motor **3** of the present embodiment is a synchronous linear motor in which a permanent magnet is used on the secondary side. The linear motor **3** is composed of the primary magnetic pole section **31** which is formed in a row so as to linearly extend in the longitudinal direction, and the secondary magnetic pole section **32** which is located in parallel with the primary magnetic pole section **31** and formed in a row so as to linearly extend in the longitudinal direction. That is, the linear motor **3** includes the primary magnetic pole section **31** and the secondary magnetic pole section **32**. Further, the primary magnetic pole section **31** and the secondary magnetic pole section **32** are arranged to face each other so as to enable the movable section to move with respect to the fixed section. That is, the primary magnetic pole section **31** and the secondary magnetic pole section **32** are arranged to face each other so that the propulsive force generated by the linear motor **3** acts to move the conveying table **2** in the longitudinal direction.

The housing **1** is provided with the primary magnetic pole section **31**, and the conveying table **2** is provided with the secondary magnetic pole section **32**. Further, a pair of the linear motors **3** and **3** are located so as to respectively coincide with opposite ends in the width direction (left and right ends in FIG. **2**) of the conveying table **2**. That is, the conveying

apparatus of the present embodiment includes two linear motors **3** per one conveying table **2**: one at one end in the width direction, and one at the other end.

Although not shown, the primary magnetic pole section **31** includes a core and a coil wound around the core. Note that the primary magnetic pole section **31** can also be configured to include only a coil without a core. The combination of coil and core is arranged in a row so as to correspond to the order of three phases U, V, W of AC, and magnetic flux mainly directed toward the inner side in the width direction is generated when the coil is energized. The core and the coil are covered with a cover **311** formed of a nonmagnetic body, such as a stainless alloy. When the conveying apparatus is used in a vacuum environment or in a reduced-pressure environment, the cover **311** functions as a partition wall between the vacuum (reduced-pressure) region and an atmospheric region. As shown in FIG. **1**, the primary magnetic pole sections **31** are intermittently arranged in the longitudinal direction. Further, as shown in FIG. **1** and FIG. **2**, the primary magnetic pole sections **31** are arranged so as to face each other in the width direction.

The secondary magnetic pole section **32** is composed of a plurality of permanent magnets **321** each fixed to the secondary support bracket **23** via a spacer **23a**. The plurality of permanent magnets **321** are arranged so that the N pole and the S pole of the magnetic poles exposed in the inner direction are adjacent each other in the longitudinal direction. The secondary magnetic pole section **32** is located inwardly from the primary magnetic pole section **31** to face the primary magnetic pole section **31** so as to maintain a predetermined interval (gap) between the magnetic pole sections. That is, the secondary magnetic pole section **32** is provided with the permanent magnets **321** at positions respectively facing the primary magnetic pole sections **31**.

Here, some conventional conveying apparatuses are configured such that one secondary magnetic pole section is held between primary magnetic pole sections from the opposite sides in the width direction of the secondary magnetic pole section. In the secondary magnetic pole section in this conveying apparatus, it is necessary that the magnetic flux generated from the secondary magnetic pole section is directed toward opposite sides in the width direction (for example, in the left and right direction). For this reason, when the secondary magnetic pole section is formed by using permanent magnets, it is necessary that the same magnetic poles are bonded to each other. However, this bonding work needs to be performed under the action of magnetic repulsion force, and hence the working efficiency is not high.

On the contrary, the secondary magnetic pole section **32** of the present embodiment can be manufactured only by arranging side by side the permanent magnets **321** along the longitudinal direction. For this reason, it is not necessary as described above, to perform the work of bonding the same magnetic poles of permanent magnets to each other under the action of magnetic repulsion force. Therefore, the working efficiency at the time of manufacturing the secondary magnetic pole section **32** is high.

The single linear motor **3** is composed of the primary magnetic pole section **31** and the secondary magnetic pole section **32**. A pair of the linear motors **3** are located so as to be separated from each other in the width direction. Thereby, as shown in FIG. **2**, a space S can be secured at the center of the housing **1** and under the conveying table **2**. In the present embodiment, as shown in FIG. **1**, a sensor (laser sensor **62**) for detecting the longitudinal position of the conveying table **2** is provided in the space S secured in this way. In order to reflect laser light irradiated from a laser irradiation section **621** of the

laser sensor **62** and to make the reflected light return to the laser sensor **62**, a reflection mirror section (not shown) is provided under the mounting section **21** of the conveying table **2**. The reflection mirror section includes a reflection surface which faces the laser irradiation section **621**. Note that the laser sensor **62** is a sensor different from the magnetostrictive sensor **61**. In the present embodiment, the longitudinal position of the conveying table **2** is mainly detected by the laser sensor **62**, and the magnetostrictive sensor **61** is used as a backup sensor. The space S can be secured under the conveying table **2** in this way, and hence the flexibility at the time of arranging various components of the conveying apparatus can be increased.

Further, in the single linear motor **3**, the primary magnetic pole section **31** and the secondary magnetic pole section **32** face each other at one position at which the surfaces of the magnetic pole sections **31** and **32** face each other. Therefore, it is easy to perform the work of setting, to an appropriate value, the interval (gap) between the primary magnetic pole section **31** and the secondary magnetic pole section **32**, as compared with the conventional configuration in which the secondary magnetic pole section is located on the opposite sides in the width direction of the primary magnetic pole section.

Further, the driving force for moving the conveying table **2** is generated at opposite end portions in the width direction of the conveying table **2**, and hence the generation source of the force of bending the conveying table **2** is distributed without being concentrated. Thereby, it is possible to reduce the bending of the conveying table **2**.

As shown in FIG. **2**, the linear guide **4** is configured such that the guide block **42** fixed to the conveying table **2** as a guided section straddles the guide rail **41** as a guiding section provided on the side of the housing **1** so as to extend in the longitudinal direction of the housing **1**. With this configuration, the moving direction of the conveying table **2** is regulated.

Ball bearings (not shown) are located between the guide rail **41** and the guide block **42**, so that the guide block **42** can be moved along the guide rail **41** with small resistance. The linear guide **4** is located on the outer side in the width direction of the linear motor **3**.

The linear motor **3** and the linear guide **4** can be arranged closer to each other as compared with the conventional configuration in which the linear motor **3** is provided at the center of the housing **1**. Thereby, the displacement of the conveying table **2**, which is generated by the propulsive force of the linear motor **3**, can be reduced. Therefore, the load applied to the linear guide **4** (especially, to the ball bearings) can be reduced. Particularly, in the conveying apparatus used in a vacuum environment or in a reduced pressure environment, oilless bearings having durability lower than that of bearings using lubricating oil are used in order to prevent contamination due to scattering of lubricating oil. Therefore, the life of the linear guide **4** can be extended by the load reduction.

The load reduction mechanism **5** includes the attraction plate **51** which is located on the side of the housing **1** and has a magnetic body, and the permanent magnet **52** which is located on the side of the conveying table **2**. The attraction plate **51** is located above the permanent magnet **52**. The load reduction mechanism **5** is located directly above the linear guide **4** (note that "directly above" in this specification conceptually includes not only a vertically above position but also a position in the vicinity of the vertically above position). In this configuration, the conveying table **2** is urged upward (directly upward) by the magnetic attraction force generated by the permanent magnet **52** to attract the attraction plate **51**.

The weight load applied to the linear guide **4** is reduced by the amount corresponding to the urging force applied to the conveying table **2**. For this reason, the load applied to the ball bearings of the linear guide **4** can be reduced and hence the life of the linear guide **4** can be extended. Further, in the load reduction mechanism **5**, a permanent magnet is used, and thereby the configuration of the load reduction mechanism **5** can be simplified.

In the above, the present invention has been described by way of an embodiment. However, the present invention is not limited to the above-described embodiment, and various variations are possible within the scope and spirit of the present invention.

For example, in the conveying apparatus of the present embodiment, the processing chamber in the housing **1** is used in a vacuum environment or in a reduced pressure environment. However, the present invention is not limited to this, and the processing chamber in the housing **1** may be used in an atmospheric environment. Further, the processing chamber may also be used in an inert gas environment.

Further, in the present embodiment, the primary magnetic pole section **31** is located on the outer side in the width direction, and the secondary magnetic pole section **32** is located on the inner side in the width direction. However, as shown in FIG. **3**, the primary magnetic pole section **31** may be located on the inner side, and the secondary magnetic pole section **32** may be located on the outer side. Further, in the present embodiment, the primary magnetic pole section **31** and the secondary magnetic pole section **32** are arranged side by side in the horizontal direction (left-right direction). However, as shown in FIG. **4**, the primary magnetic pole section **31** and the secondary magnetic pole section **32** may be arranged side by side in the vertical direction.

Further, in the present embodiment, the housing **1** is provided with the primary magnetic pole section **31**, and the conveying table **2** is provided with the secondary magnetic pole section **32**. On the contrary, however, the housing **1** may be provided with the secondary magnetic pole section **32**, and the conveying table **2** may be provided with the primary magnetic pole section **31**.

Further, the primary magnetic pole sections **31** of the present embodiment are intermittently arranged in the longitudinal direction but may also be continuously arranged in the longitudinal direction. Further, the primary magnetic pole sections **31** of the present embodiment are arranged to be symmetrical with respect to the center line in the width direction but may also be arranged to be shifted to one side in the width direction. However, when the conveying apparatus is used in a vacuum environment or in a reduced pressure environment, the symmetrical arrangement is desirable in order to prevent each of the components from being unevenly deformed under reduced pressure.

Further, the secondary magnetic pole section **32** may also be provided with a core and a coil wound around the core.

Further, the load reduction mechanism **5** may be located directly below the linear guide **4** (note that the term "directly below" in this specification conceptually includes not only a vertically below position but also a position in the vicinity of the vertically below position). Further, for example, the same magnetic poles of permanent magnets may be made to face each other so that the conveying table **2** is urged upward by the magnetic repulsion force. Further, an electromagnet may also be used instead of the permanent magnet.

Further, the longitudinal direction in the present embodiment is a linear direction (direction along a straight line). However, the present invention is not limited to this, and the

longitudinal direction may be a direction along a curved line when the housing **1** is formed to have a curved shape or an annular shape.

The above description is summarized as follows. The conveying apparatus according to the present embodiment is featured by including a fixed section (housing) **1**, a movable section movable with respect to the housing **1**, and a pair of linear motors **3** each located so as to be partially included in the housing **1** and the movable section, wherein each of the linear motors **3** includes a primary magnetic pole section **31** and a secondary magnetic pole section **32**, and the primary magnetic pole section **31** and the secondary magnetic pole section **32** are arranged to face each other so as to enable the movable section to move with respect to the housing **1**, the movable section includes a movable body (conveying table) **2** capable of conveying a conveyed object, and one of the primary magnetic pole section **31** and the secondary magnetic pole section **32** each located at opposite ends in the width direction that is orthogonal to the moving direction of the conveying table **2**, and the housing **1** includes the other of the primary magnetic pole section **31** and the secondary magnetic pole section **32**.

In this configuration, the movable section is provided, at opposite ends thereof in the width direction, with one of the primary magnetic pole section **31** and the secondary magnetic pole section **32** of each of the pair of linear motors **3**. For this reason, the space **S** can be secured between one of the pair of linear motors **3** and the other of the pair of linear motors **3**.

Further, the secondary magnetic pole section **32** can be provided with the permanent magnet **321** at a position facing the primary magnetic pole section **31**. With this configuration, the secondary magnetic pole section **32** can be manufactured only by arranging side by side the permanent magnets **321** along the longitudinal direction. For this reason, when the secondary magnetic pole section **32** is manufactured, it is not necessary to perform the work of bonding the same magnetic poles of the permanent magnets to each other under the action of magnetic repulsion force, and hence the working efficiency is high.

Further, the housing **1** can include a supporting section which supports the movable section from below. The supporting section can include the guide section (guide rail) **41** which regulates the moving direction of the movable section and extends in the longitudinal direction. The movable section can include the guided section (guide block) **42** which can be moved while being engaged with the guide rail **41**. The load reduction mechanism **5**, which presses the movable section upward with magnetic repulsion force or magnetic attraction force to thereby reduce weight load applied to the guide rail **41** and the guide block **42**, can be provided at a position directly above or directly below the guide rail **41** and the guide block **42**.

In this configuration, the load reduction mechanism **5**, which reduces weight load applied to the guide rail **41** and the guide block **42** by maintaining the vertical distance between the housing **1** and the movable section, is provided at a position directly above or directly below the guide rail **41** and the guide block **42**. For this reason, the life of the guide rail **41** and the guide block **42** can be extended by reducing the weight load.

Further, the guide rail **41** and the guide block **42** can be located at each of the opposite ends in the width direction of the housing **1** and the movable section. The movable section can include mounting sections located outside or inside of the guide rail **41** and the guide block **42** in the width direction, the

mounting sections being for attaching one of the primary magnetic pole section **31** and the secondary magnetic pole section **32**.

In this configuration, the guide rail **41** and the guide block **42** can be made close to the mounting section, and thereby the displacement of the movable section due to the propulsive force of the linear motor **3** can be reduced. For this reason, the life of the guide rail **41** and the guide block **42** can be extended by reducing the load.

According to the present invention, it is possible to secure the space **S** between each pair of the linear motors **3**. Thereby, it is possible to provide a conveying apparatus in which the restriction of space for arranging various apparatuses is reduced.

What is claimed is:

1. A conveying apparatus comprising:

a fixed section;

a movable section movable with respect to the fixed section; and

a pair of linear motors each located so as to be partially included in the fixed section and the movable section, wherein

the pair of the linear motors is located so as to be separated from each other in a width direction that is orthogonal to a moving direction,

each of the linear motors includes a primary magnetic pole section and a secondary magnetic pole section, the primary magnetic pole section comprises a coil, and the primary magnetic pole section and the secondary magnetic pole section are arranged to face each other so as to enable the movable section to move with respect to the fixed section,

the movable section includes a movable body capable of conveying a conveyed object, and the secondary magnetic pole section of each of the pair of linear motors, each of the pair of linear motors being located at each of opposite ends of the movable body in the width direction,

the fixed section includes the primary magnetic pole section and a supporting section which supports the movable section from below,

the supporting section includes a guide section which regulates the moving direction of the movable section and extends in a longitudinal direction,

the movable section includes a guided section which is movable while being engaged with the guide section,

one of the pair of the linear motors is located on one end side of the movable section in the width direction and the other is located on the other end side of the movable section in the width direction,

each of the linear motors is arranged exclusively at a position close to an inner surface of a housing in the width direction, the housing being a part of the fixed section, and

the supporting section is arranged adjacent to each of the linear motors and close to the inner surface of the housing in the width direction, and the guide section and the guided section are arranged in a vertical direction.

2. The conveying apparatus according to claim **1**, wherein the secondary magnetic pole section of each of the pair of linear motors includes a permanent magnet at a position facing the primary magnetic pole section.

3. The conveying apparatus according to claim **1**, wherein a load reduction mechanism, which presses the movable section upward with magnetic repulsion force or magnetic attraction force to thereby reduce weight load applied to the guide section and the guided section, is provided at a position directly above or directly below the guide section and the guided section.

4. The conveying apparatus according to claim **3**, wherein the guide section and the guided section are located at opposite ends in the width direction of the fixed section and the movable section, and

the movable section includes mounting sections located outside or inside of the guide section and the guided section in the width direction, the mounting sections being for attaching one of the primary magnetic pole section and the secondary magnetic pole section.

5. The conveying apparatus according to claim **2**, wherein the fixed section includes a supporting section which supports the movable section from below,

the supporting section includes a guide section which regulates the moving direction of the movable section and extends in a longitudinal direction,

the movable section includes a guided section which is movable while being engaged with the guide section, and

a load reduction mechanism, which presses the movable section upward with magnetic repulsion force or magnetic attraction force to thereby reduce weight load applied to the guide section and the guided section, is provided at a position directly above or directly below the guide section and the guided section.

6. The conveying apparatus according to claim **5**, wherein the guide section and the guided section are located at opposite ends in the width direction of the fixed section and the movable section, and

the movable section includes mounting sections located outside or inside of the guide section and the guided section in the width direction, the mounting sections being for attaching one of the primary magnetic pole section and the secondary magnetic pole section.

7. The conveying apparatus according to claim **1**, wherein the primary magnetic pole section and the secondary magnetic pole section are arranged side by side in a horizontal direction.

8. The conveying apparatus according to claim **1** used in a vacuum environment or in a reduced-pressure environment.

* * * * *