

US009162176B2

(12) **United States Patent**
Paton-Ash et al.

(10) **Patent No.:** **US 9,162,176 B2**
(45) **Date of Patent:** **Oct. 20, 2015**

(54) **APPARATUS AND METHOD FOR AFFECTING AIR**

(2013.01); **B01D 53/0415** (2013.01); **B01D 53/1475** (2013.01); **B01D 53/62** (2013.01); **B01D 2251/304** (2013.01); **B01D 2257/504** (2013.01); **B01D 2259/4558** (2013.01); **Y02C 10/04** (2013.01)

(71) Applicants: **Gregory Paton-Ash**, Marietta, GA (US); **Michael Bishoff**, Friendsville, MD (US); **Donald Beitzel**, Grantsville, MD (US); **John J. Reinmann, Jr.**, Alpharetta, GA (US)

(58) **Field of Classification Search**

CPC **B01D 53/02**; **B01D 53/14**; **B01D 53/1475**
USPC **55/385.2**, **467**, **516**, **518**; **96/108**, **151**; **95/90**, **139**

(72) Inventors: **Gregory Paton-Ash**, Marietta, GA (US); **Michael Bishoff**, Friendsville, MD (US); **Donald Beitzel**, Grantsville, MD (US); **John J. Reinmann, Jr.**, Alpharetta, GA (US)

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

(73) Assignee: **Strata Products Worldwide, LLC**, Sandy Springs, GA (US)

2,284,964 A	6/1942	Mautz et al.
2,325,049 A	7/1943	Frye et al.
3,261,659 A	7/1966	Schwichtenberg et al.
3,393,479 A	7/1968	Slotnick
4,096,702 A	6/1978	Burton
4,325,364 A	4/1982	Evans
4,451,435 A	5/1984	Holter
4,632,678 A	12/1986	Cosyns et al.

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(Continued)

(21) Appl. No.: **13/959,497**

FOREIGN PATENT DOCUMENTS

(22) Filed: **Aug. 5, 2013**

(65) **Prior Publication Data**

DE	3538135 A1	4/1987
EP	0050243 B1	4/1982

US 2013/0323144 A1 Dec. 5, 2013

(Continued)

Related U.S. Application Data

(62) Division of application No. 12/075,002, filed on Mar. 7, 2008, now Pat. No. 8,506,681.

Primary Examiner — Robert A Hopkins

(74) *Attorney, Agent, or Firm* — Ansel M. Schwartz

(60) Provisional application No. 60/905,948, filed on Mar. 9, 2007.

(57) **ABSTRACT**

An apparatus for affecting air includes a housing. The apparatus includes a treatment layer disposed in the housing for treating air. The apparatus includes a fan. The apparatus includes a gas powered motor mechanically engaged with the fan to operate the fan which forces the air through the treatment layer. The apparatus includes a compressed gas tank in fluid connection with the gas powered motor to provide gas to the motor to power the motor. A method for affecting air.


(51) **Int. Cl.**

B01D 53/14	(2006.01)
B01D 53/04	(2006.01)
B01D 53/62	(2006.01)
A62B 11/00	(2006.01)

(52) **U.S. Cl.**

CPC **B01D 53/0446** (2013.01); **A62B 11/00**

12 Claims, 11 Drawing Sheets



(56)

References Cited

FOREIGN PATENT DOCUMENTS

U.S. PATENT DOCUMENTS

4,708,053	A	11/1987	Forsythe et al.
4,838,910	A *	6/1989	Stollenwerk et al. 55/385.2
5,082,471	A	1/1992	Athayde et al.
5,411,046	A	5/1995	Wan
5,487,380	A	1/1996	Grabenkort
5,537,784	A	7/1996	Baldwin
5,595,949	A	1/1997	Goldstein et al.
5,706,846	A	1/1998	Sutton
5,862,819	A	1/1999	Cradeur
6,699,309	B1	3/2004	Worthington, II et al.
6,712,071	B1	3/2004	Parker
7,533,942	B2	5/2009	Kennedy et al.
2002/0061270	A1	5/2002	Osborne
2006/0278216	A1	12/2006	Gagas et al.
2007/0199244	A1	8/2007	Kennedy et al.
2007/0202796	A1	8/2007	Kennedy et al.
2008/0106137	A1	5/2008	Paton-Ash et al.

EP	0182581	A3	5/1986
EP	0230875	A1	8/1987
GB	515442	A	12/1939
GB	2043737	A	10/1980
GB	2420507	A	5/2006
JP	57187017	A	11/1982
KR	2004-058590		7/2004
RU	2158148	C1	2/1999
SU	955990		2/1981
WO	WO 00/16878	A2	3/2000
WO	WO 2005/052319		6/2005
WO	WO 2005/086613	A2	9/2005
WO	WO 2007/030783	A3	3/2007
WO	WO 2007/112482		10/2007
WO	WO 2007/117266	A3	10/2007

* cited by examiner




FIG. 3




FIG. 2






FIG. 1



42 FIG. 5



FIG. 4 24



56 SCRUBBER FIG. 7




FIG. 6

FAN
20




FIG. 8




FIG. 9






FIG.10









FIG. 15






FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26

1

**APPARATUS AND METHOD FOR
AFFECTING AIR****CROSS-REFERENCE TO RELATED
APPLICATIONS**

This is a divisional of U.S. patent application Ser. No. 12/075,002 filed on Mar. 7, 2008, now U.S. Pat. No. 8,506,681, which claims priority from U.S. provisional application Ser. No. 60/905,948 filed Mar. 9, 2007, all of which are incorporated by reference herein.

FIELD OF THE INVENTION

The present invention is related to the scrubbing of carbon dioxide from air without any electricity to maintain a safe and breathable environment in an enclosure for users. More specifically, the present invention is related the scrubbing of carbon dioxide from air without any electricity to maintain a safe and breathable environment in an enclosure for users using only compressed air and oxygen to power a motor to run a fan that draws air through a chamber where it is scrubbed of carbon dioxide and where the compressed air and oxygen are then further used to support the environment.

BACKGROUND OF THE INVENTION

As is well known, trees and plants through the process of photosynthesis naturally convert CO₂ into oxygen. When nature cannot do its job, chemistry takes over. In maimed, enclosed atmospheres such as rescue chambers, dive devices or submarines, two chemical technologies have historically been employed to scrub the CO₂ from the environment: lithium hydroxide and soda lime. Below are the pros and cons of both materials.

	Soda Lime w/ Scrubber	Lithium Hydroxide Curtains
CO ₂ Absorption:	150 liters CO ₂ per kg	402 liters CO ₂ per kg
Packaging:	20 kg (44 lb) sealed kegs	8 curtains per box; 5.72 lbs of LiOH per box.
96 Hr Requirements:	1 keg per man	2.75 boxes per man Per MSHA: (.244 lbs/man - hr) * 96 hr/ 5.72 lbs/box = 4.1 boxes
Approx Cost/unit:	\$135/keg	\$487/box
Cost/man for 96 hrs:	\$135/man	\$1339/man \$1997/man per MSHA
Shelf Life:	5 years	5 yers; must be discarded
Heat Generated:	32 Btu's per man per hour	130 Btu's per man per hour; curtains actually hot to the touch
Deployment:	Simple; new keg added when color changes	Complicated; curtains must be hung at a set schedule and spacing
Effectiveness:	good air circulation from Air driven fan	only works in small, confined areas; not effective in large areas
Power Requirements:	None; air/oxygen driven fan	None; passive system relies on localized natural convective currents

BRIEF SUMMARY OF THE INVENTION

The present invention pertains to an apparatus for cleaning air. The apparatus comprises a housing having a chamber. The scrubber comprises a carbon dioxide scrubber layer disposed in the chamber which cleans carbon dioxide from air passing through the scrubber layer. The apparatus comprises a forcing element which draws the air into the scrubber and forces the air through the scrubber layer which is powered without any electricity.

The present invention pertains to a system for supporting a breathable environment for users. The system comprises an

2

enclosure. The system comprises an air scrubber disposed in the enclosure which cleans carbon dioxide from air in the enclosure that is powered without any electricity.

The present invention pertains to a method for cleaning carbon dioxide from air. The method comprises the steps of flowing compressed air through a fluid driven motor to operate the motor without any electricity. There is the step of rotating a fan with the operating motor. There is the step of drawing air into a chamber of a housing with the fan blowing the air through a carbon dioxide scrubber layer of soda lime in the chamber, which scrubs the air of carbon dioxide, and out through an opening in the chamber above the layer.

The present invention is a cartridge for a scrubber. The cartridge comprises a cartridge housing having a cartridge chamber and a porous top and opposing porous bottom. The cartridge comprises soda lime disposed in and filling the cartridge chamber.

The present invention pertains to a method for scrubbing air. The method comprises the steps of activating a fan inside a refuge cartridge chamber. There is the step of drawing air in the refuge cartridge chamber through soda lime in a cartridge with the fan.

**BRIEF DESCRIPTION OF THE SEVERAL
VIEWS OF THE DRAWING**

In the accompanying drawings, the preferred embodiment of the invention and preferred methods of practicing the invention are illustrated in which:

FIG. 1 is a front view of the apparatus of the present invention.

FIG. 2 is a side sectional view of the apparatus.

FIG. 3 is a rear sectional view of the present invention.

FIG. 4 shows a top view of the table.

FIG. 5 shows a side view of the platform.

FIG. 6 shows a fan.

FIG. 7 shows a perspective view of the apparatus.

FIG. 8 shows the apparatus in a skid.

FIG. 9 shows a valve attached to the housing.

FIG. 10 shows a perspective view of an enclosure.

FIG. 11 is a side view of a cartridge of the present invention.

FIG. 12 is an overhead sectional view of the cartridge.

FIG. 13 is a side sectional view of the cartridge.

FIG. 14 is a perspective view of the cartridge.

FIG. 15 is a sectional view of a corner of the cartridge.

FIG. 16 is an overhead view of a table of the present invention.

FIG. 17 is a front view of the table.

FIG. 18 is a side sectional view of the table.

FIGS. 19-26 show the progression of steps of the production of the cartridge.

DETAILED DESCRIPTION OF THE INVENTION

Referring now to the drawings wherein like reference numerals refer to similar or identical parts throughout the several views, and more specifically to FIGS. 1-3 and 7-9 thereof, there is shown an apparatus 10 for cleaning air. The apparatus 10, otherwise called an air scrubber 56, comprises a housing 12 having a chamber 14. The scrubber 56 comprises a carbon dioxide scrubber layer 16 disposed in the chamber 14 which cleans carbon dioxide from air passing through the scrubber layer 16. The scrubber 56 comprises a forcing element 18 which draws the air into the scrubber 56 and forces the air through the scrubber layer 16 which is powered without any electricity.

Preferably, the forcing element 18 includes a fan 20, as shown in FIG. 6. The forcing element 18 preferably includes a fluid powered motor 22 mechanically engaged with the fan 20 to operate the fan 20 which draws the air into the chamber 14 and forces the air through the layer. Preferably, the scrubber layer 16 includes soda lime 74 and a platform 24 disposed in the chamber 14 upon which the soda lime 74 is disposed, as shown in FIGS. 4 and 5. The forcing element 18 preferably includes a valve 26 in fluid connection with the motor 22 through which fluid is provided to the motor 22 to operate the motor 22.

Preferably, the valve 26 includes a compressed air port 28 which receives a flow of compressed air. The valve 26 preferably includes a compressed oxygen port 30 which receives a flow of compressed oxygen, the valve 26 combining the compressed air flow and the compressed oxygen flow and directing it to the motor 22. Preferably, the valve 26 is adjustable to control the flow of compressed oxygen. The valve 26 preferably uses only fluid to operate.

Preferably, the fan 20 is attached to a side wall 32 of the housing 12 at a hole 34 in the side wall 32. The motor 22 preferably has an outlet port 36 through which the compressed air and compressed oxygen flows into the chamber 14 after flowing through the motor 22 to operate the motor 22. Preferably, the housing 12 has a top 38 with an opening 40 through which the air that has passed through the layer flows out of the housing 12. The opening 40 of the housing 12 preferably has a screen 42.

The present invention pertains to a system 50 for supporting a breathable environment for users. The system 50 comprises an enclosure 52, as shown in FIGS. 8-10. The system 50 comprises an air scrubber 56 disposed in the enclosure 52 which cleans carbon dioxide from air in the enclosure 52 that is powered without any electricity.

The present invention pertains to a method for cleaning carbon dioxide from air. The method comprises the steps of flowing compressed air through a fluid driven motor 22 to operate the motor 22 without any electricity. There is the step of rotating a fan 20 with the operating motor 22. There is the step of drawing air into a chamber 14 of a housing 12 with the fan 20 blowing the air through a carbon dioxide scrubber layer 16 of soda lime 74 in the chamber 14, which scrubs the air of carbon dioxide, and out through an opening 40 in the chamber 14 above the layer.

Preferably, the flowing step includes the step of flowing compressed air and compressed oxygen. There is preferably the step of flowing the compressed air and compressed oxygen into the chamber 14 after it flows through the motor 22 to operate the motor 22. Preferably, the flowing step includes the

step of connecting a compressed air tank to a compressed air line connected to a valve 26 connected to the motor 22.

The flowing step preferably includes the step of connecting a compressed oxygen tank to a compressed oxygen line connected to the valve 26 connected to a gas line to the motor 22. Preferably, the flowing step includes the step of combining the compressed air from the compressed air line and the compressed oxygen from the compressed oxygen line together with the valve 26 and providing the compressed air and the compressed oxygen together to the motor 22. There is preferably the step of placing the housing 12 into an enclosure 52.

The enclosure 52 can be inside a mine where a hazardous environment has presented itself, or in a hazardous environment generally where a safe refuge is needed for a prolonged period of time, until the hazardous environment abates or rescue can occur of the users in the enclosure 52. See U.S. patent application Ser. No. 11/903,079 titled "Refuge Chamber and Method," incorporated by reference herein, for a description of an enclosure and skid 54 which holds compressed air and compressed oxygen tanks and the air scrubber 56.

The compressed air and compressed oxygen turns the fan 20 motor 22 and then the compressed air and oxygen releases into the scrubber 56 chamber 14 through a return line from the motor 22. In terms of structural design, there is a valve 26 connecting lines from a compressed air tank and an oxygen tank which joins the two lines and together feeds the flow from both in one line to the fan 20 motor 22. The compressed air at a flow rate of 0.16 cfm is supplemented with the flow of oxygen to increase the speed of the fan 20. Oxygen is metered into the chamber 14 at 30 liters per person per hour, so the more people you have, the higher the flow rate and the faster the fan 20 turns, giving more air flow and better circulation in the chamber 14. This is one of the novel designs in the scrubber 56.

The fan 20 runs causing air outside the scrubber 56 to be drawn into the scrubber 56 where the continued action of the scrubber 56 blowing air and forces the air blown into the scrubber 56 to flow up through the soda lime 74 layer which scrubs the carbon dioxide and releases clean air. The soda lime 74 is a carbon dioxide absorbent. The compressed air and oxygen is released into the scrubber 56 chamber 14 and is blown through the lime 74 layer with the air from outside the scrubber 56 by the action of the fan 20.

The Air-Driven Carbon Dioxide Scrubber 56 operates in the following manner.

The air powered soda lime 74 carbon dioxide Scrubber 56 operates using compressed air as opposed to batteries. The compressed air powers a motor 22 which drives a fan 20. The fan 20 then facilitates the flow of air through the scrubbing system 50.

The system 50 has an oxygen manifold that connects to a bank of oxygen cylinders. The system 50 has a flow meter so that oxygen can be metered into the room/chamber 14 to replenish oxygen consumed by occupants. The flow rate is set based on the number of occupants.

Detailed Specifications of a Preferred Embodiment

48/96 Hr Air-Driven Motor Carbon Dioxide Scrubbing System 50

a. Brief Description:

The carbon dioxide Scrubber 56 is a self-contained system 50 designed to provide oxygen at controlled rates and remove carbon dioxide from the air in enclosed areas. It utilizes T or HC4500-size oxygen cylinders to provide oxygen and four or eight (4/8) 6000 psi compressed air cylinders to power a motor 22 that drives a fan 20. The

fan **20** facilitates the movement of air through the scrubber **56** to achieve successful scrubbing.

b. Specifications:

Housing:

Made from fully welded, powder coated steel or fiber glass outer and chemical tray.

Oxygen	Air
Occupants = 20	Inflate (Cu-Ft) = 928
Hours = 96	Purge (Cu-Ft)/per = 220
Oxy rate p/person CFM = 0.0177	# of Purges (x) = 4
Oxy req'd @ full cap. (CFM) = 0.3532	Total Purge (Cu-Ft) = 880
Oxy Vol. req'd @ full cap. (Cu-Ft) = 2034.4	

Use HC-4500 Bottle Oxygen and supplemental C/A combo to run fan
(Fan flow rate @ .16-.51 CFM, depending on occupancy.)

96 hrs

Oxygen HC-4500 @ 4500 psi							Compressed Air @ 6000 psi					
	Usage CFM	Bot. Cap.	Req.	% +	Total	Bottles	Usage CFM	Bot. Cap.	Req.	% +	Total	Bottles
Bottles Oxygen	0.353	500	4.07	1.25	5.09	5.00	—	—	—	—	—	—
Fan	SHARE	—	—	—	—	0	0.16	509	1.81	1.1	1.99	2.00
Inflate	0	—	—	—	—	0	N/A	509	1.82	1	1.82	2.00
Purge	0	—	—	—	—	0	N/A	509	1.73	1	1.73	2.00
Totals						5						6
												11

Unit Air Supply:

48/96 hour Air-Driven Motor carbon dioxide scrubber unit. The number of oxygen cylinders required depends on the number of occupants in the enclosure chamber.

Operation:

Compressed air powers a small motor **22** which drives a fan **20** in the system **50**. The fan **20** rotates to draw air from the enclosure chamber into the scrubber **56** and up through the tray of soda lime **74** chemicals. This scrubs the carbon dioxide out of the air.

Back-Up System:

Soda Lime **74** should be spread out on the floor.

Size:

16" Wide×22" Deep×18" High

Operation:

It requires activation by turning the valve **26** to start the flow of compressed air and placing the chemicals in the tray.

Maintenance:

It is recommended that monthly checks of the system **50** be performed to ensure proper function. The oxygen/compressed air cylinders must also be checked for correct volume of contents.

Added Benefit:

Additional flow of 15 cubic feet per hour will exhaust and reduce humidity and heat in the enclosure chamber

The fan **20** assembly is comprised of the following parts:

Fan: McMASTER-CARR 17545K65

Air Motor: LYNX™ Pro-5 Low Speed Handpiece

4-Hole Handpiece Tubing: DCI #401C

c. Materials:

i. Soda Lime Chemicals

d. Soda Lime Chemicals:

i. Requirements: (44 lb kegs)

15-Man 48 hrs	15-Man 96 hours
10	20

25

Novel Design Aspects

No external power source—All active scrubbers normally use electric or battery power.

De facto intrinsically safe—no electric connection or sparks

30

Use of Oxygen and Compressed air saves on use of Compressed air bottles and therefore reduces space in the skid **54**

Active scrubbing (as opposed to a passive curtain with lithium Hydroxide or Soda Lime) has significant advantages

35

Air Flow

Circulation and no dead spots in the room/area being scrubbed

Draws air through the soda lime **74** bed in the scrubber

40

Allows reduced size

Carbon Dioxide (CO₂) Scrubbing

Carbon dioxide (CO₂) makes up 4-6% of the air that humans exhale. The amount of CO₂ varies from man-to-man based on the level of effort and/or stress.

45

The West Virginia Task Force specifications do not specify a rate of CO₂ production per man to use; however, the MSHA PIB P07-03 includes a rate of 1.08 cubic feet per hour per person (30.6 liters/hour-man) in their example calculations. 30 liters/hour per man have been used in all calculations here.

50

The West Virginia Task Force specifications limit CO₂ concentrations to no greater than 5000 parts per million or 0.5%. The MSHA PIB defines unacceptable air to contain over 3% CO₂ or 30,000 ppm. A 0.5% limit has been used in all calculations.

55

In another embodiment, there is an optional soda lime filled cartridge **58** scrubber in addition to the soda lime **74** tray filled with bulk soda lime **74**. The present invention is a cartridge **58** for a scrubber **56**, as shown in FIGS. **11-15**. The cartridge **58** comprises a cartridge housing **60** having a cartridge chamber **62** and a porous cartridge top **64** and opposing porous bottom **66**. The cartridge **58** comprises soda lime **74** disposed in and filling the cartridge chamber **62**.

60

Preferably, the cartridge top **64** and bottom **66** each include a rigid mesh layer **70**. The cartridge top **64** and bottom **66** sides **68** each preferably have a porous containment layer **72** adjacent the mesh layer **70** which contains the soda lime **74**.

65

Preferably, the cartridge housing **60** includes sides **68** in contact with the cartridge top **64** and bottom **66**. At least either one of the sides **68**, the cartridge top **64** or the bottom **66** is preferably removable. Preferably, the cartridge top **64** and bottom **66** have a lip **76**. The soda lime **74** is preferably packed in the cartridge chamber **62** so channels for air to pass preferentially through the soda lime **74**.

The present invention pertains to a method for scrubbing air. The method comprises the steps of activating a fan **20** inside a refuge cartridge chamber **62**. There is the step of drawing air in the refuge cartridge chamber **62** through soda lime **74** in a cartridge **58** with the fan **20**.

The total cartridge **58** cross-sectional area, exposed to the flow of the air to be scrubbed, is the same as the cross-sectional area of the tray design. Multiple cartridges **58** can be used to come up with the total cross-sectional area. For example, a 36 man scrubber utilizes twelve cartridges with a nominal dimension of 12" wide×16" long by 6" high. The height of the cartridges matches the depth of the soda lime **74** in the tray design and is determined by the minimum desired residence time of the air as it passes through the bed. The total cross-sectional area of the tray/cartridges **58** is determined by the available pressure drop provided by the fan **20** drawing air through the bed. The fan **20** motor **22** is driven by an air/oxygen source at a certain available flow rate determined by the required flow rate of oxygen for the number of people in the chamber **14**. The fan **20** blade was selected based on the available RPM's of the motor **22**, the desired flow rate of air through the scrubber **56** bed and the pressure drop across the scrubber **56** tray/cartridge bed. The desired flow rate of the air to be scrubbed is a function of the required level of CO₂ removal, the number of people and the assumed scrubbing efficiency per pass through the scrubber **56**. Assume a 100% scrubbing efficiency per pass and a desired CO₂ level of 5000 ppm or 0.5% CO₂ in air.

The cartridge **58** is a box with a porous cartridge top **64** and bottom **66** and solid sides **68**. The sides **68** can be made of sheet metal or plastic. The cartridge top **64** and bottom **66** is an open, expanded metal mesh that allows the most air to flow with the least amount of pressure drop while also being strong enough to support the full weight of the contents of the cartridge **58**. Affixed to the inside surfaces of the cartridge top **64** and bottom **66** expanded metal is a fabric material that keeps the small particles from passing through the expanded metal. This fabric also allows the air to pass easily but keep the fine dust from entering the chamber **14** environment. The cartridges **58** also have removable sides **68** or tops to allow the soda lime **74** to be poured onto the rescue chamber **14** floor. This would be necessary in an emergency if the primary and secondary scrubber motors **22** both failed. While not as effective, the bulk soda lime **74** would continue to absorb CO₂ from the environment.

The solid sides **68** of the cartridge **58** are made of a non-permeable material. In one embodiment, the sides **68** are made of a 20 gauge, carbon steel sheet metal formed into a u-shape that creates three sides **68**. The fourth side is removable to allow for filling the cartridge **58** with the soda lime **74**. This side can be attached with screws or rivets or some mechanical means strong enough to hold the weight of the fill material. In another embodiment, an injection molded plastic is formed in a single piece. To avoid any chemical reactions, galvanized steel or unpainted steel is not used. Stainless steel, painted steel or plastic is preferred.

The expanded metal mesh (containment layer **72**) attached to the cartridge top **64** and bottom **66** is an 18 gauge (0.048" thick) flattened expanded steel 2×½" No. 18F with a minimum clear opening of 70%. Again, the material selected can

be painted steel, stainless steel or plastic. Stainless steel mesh can be molded into the plastic box to form the cartridge top **64** and bottom **66**.

The scrim material is attached per the instructions herein. The scrim is a non-woven nylon fabric 1 oz per square yard weight with a very low pressure drop. At 0.5 inches of water, the scrim allows 734 cfm of air to pass. The scrim material is supplied by CEREX called PNB-II.

The particle size distribution and particle shape are critical. A 4 to 8 mesh is used to give non-spherical shaped particles. A material supplied by WR Grace called Sodasorb HMED 4-8 is used. The material fills the entire cartridge **58** so that channels do not form that allow the air to pass preferentially. It is also critical to avoid channeling along the smooth interface between the walls of the box and the fill material. A lip **76** (approx ½ inch wide) on the cartridge top **64** and bottom **66** perimeter of the steel and plastic boxes is used to reduce any short circuiting of the air along the vertical walls of the box. Ribs or sponge-like gasket material could also be used.

The packed density of the material is 40 lbs per 0.68 cubic feet or 58 lbs/cubic foot. To achieve this density, the material (or the box itself) has to be vibrated during the filling process. If the material is packed too densely, the air flow will be restricted and the pressure drop will increase. If the material is too loosely packed, it will eventually settle during shipping and handling thereby allowing the undesirable channels to form which allow air to pass.

The current scrubber **56** sizes are as follows.

Number of People	Scrubber Size (Area open to flow ft ²)
6	3.96
16	7.92
20	10.6
24	10.6
26	11.88
30	13.2
36	15.84

As shown in FIGS. **16-18**, the cartridges **58** are placed on a table **78** having ridges **80** that define holding zones for the cartridges **58** so the cartridges **58** stay securely seated in place. When in place on the table **78**, the cartridges **58** basically abut each other to form an essentially complete soda lime **74** layer where the path of least resistance for air flow is through the soda lime **74** in the cartridges **58**. The fan **20** is attached to the table **78**, under the table **78**, so the fan **20** draws air downward through the soda lime **74** in the cartridges **58**. The table **78** has a closed alley **82** with an air zone under the table **78** to which the fan **20** is in fluidic communication. The fan **20** can only draw air from the alley **82**, so a flow path is created through the cartridges **58** into the alley **82** and out through the fan **20** into the refuge chamber **14** with the air now scrubbed. Tubing **84** extends through the alley **82** to supply pressurized air or oxygen to the fan **20** to power the fan **20**.

Procedure for Making Cartridge

Refer to FIGS. **19-26**.

Procedure for Inserting Scrim, Otherwise Known as the Containment Layer **72**

1. Measure and cut two pieces of scrim to cover expanded metal mesh layer **70**.
2. Use a spray adhesive on the inside of the box at the corners about one inch in width, making sure not to get any adhesive onto the expanded metal, and let dry for one minute.

9

3. While the adhesive is drying, use a piece of cardboard to lie on top of the scrim and fold the scrim over top of the cardboard.
 4. Lay the cartridge flat with the expanded metal facing down.
 5. Insert the scrim and unfold to fit approximately one inch all the way around the cartridge onto the adhesive, making sure a bond is made when the scrim contacts the adhesive.
 6. Flip the cartridge over and repeat.
- Procedure for Packing Soda Lime
7. When you have both pieces of scrim bonded inside the cartridge, fill the cartridge approximately half full of soda lime **74**.
 8. Compact soda lime. Test cartridges were settled using a "dead blow" hammer firmly moving from the bottom of the cartridge to the top on each side.
 9. Further compact by tapping loaded cartridge on a hard, rigid surface, such as a concrete pad/floor.
 10. Re-fill the cartridge to the top with soda lime and repeat steps eight through nine two or three times to ensure packing.
 11. Level the soda lime at the top of the cartridge, and fold scrim over the soda lime tucking the scrim under the lip **76** for the bolt holes.
 12. Place lid on top of cartridge making sure to insert the lip **76** of the lid over the expanded metal and thread the lid bolts into the holes.

Procedure for Emptying of Cartridge

13. Remove the cartridge lid and unfold one end of the scrim to make an opening **40**.
 14. Pour used soda lime, while holding the folded side of the scrim, into a designated container.
- In terms of FIGS. **19-26**:
 FIG. **19** shows the empty metal cartridge.
 In FIG. **20**, remove lid and apply spray adhesive to a 1" perimeter around expanded metal edges.
 In FIG. **21**, install scrim, press onto adhesive.
 In FIG. **22**, repeat for other side.
 In FIG. **23**, cartridge ready for loading.
 In FIG. **24**, fill with soda lime media and close scrim tabs.
 In FIG. **25**, install lid with fasteners.
 In FIG. **26**, seal lid corners with tape.

Although the invention has been described in detail in the foregoing embodiments for the purpose of illustration, it is to be understood that such detail is solely for that purpose and that variations can be made therein by those skilled in the art without departing from the spirit and scope of the invention except as it may be described by the following claims.

The invention claimed is:

1. An apparatus for affecting air comprising:
 a housing having a chamber;
 a treatment layer disposed in the housing for treating air;
 a fan, the housing includes an open gap extending along and under the treatment layer into which gas from the fan is blown;

10

- a gas powered motor mechanically engaged with the fan to operate the fan which blows the air into the chamber and through the treatment layer; and
 a compressed gas tank in fluid connection with the gas powered motor to provide gas to the motor to power the motor.
2. An apparatus as described in claim **1** including a valve in fluid connection with the motor through which fluid is provided to the motor, the valve includes a compressed gas port which receives a flow of compressed gas from the compressed gas tank.
 3. The apparatus as described in claim **2** wherein the treatment layer is a carbon dioxide scrubber layer of particles of soda lime.
 4. The apparatus as described in claim **2** wherein the compressed gas tank is a compressed air tank.
 5. The apparatus of claim **4** including a table in the housing on which the scrubber layer is disposed.
 6. The apparatus of claim **5** wherein the soda lime particles have a density of 58 lbs./cubic foot.
 7. A method for affecting air comprising the steps of:
 flowing compressed gas from a compressed gas tank through a compressed gas line to a fluid driven motor to operate the motor without any electricity;
 rotating the fan with the operating motor; and
 blowing the air with the fan through a treatment layer in a housing to treat the air, the treatment layer is a carbon dioxide scrubber layer of particles of soda lime.
 8. The method as described in claim **7** wherein the compressed gas line is connected to a valve connected to the motor.
 9. An apparatus for affecting air comprising:
 a housing having a chamber;
 a treatment layer disposed in the housing for treating air, the treatment layer is a carbon dioxide scrubber layer of particles of soda lime;
 a fan;
 a gas powered motor mechanically engaged with the fan to operate the fan which blows the air into the chamber and through the treatment layer;
 a compressed gas tank in fluid connection with the gas powered motor to provide gas to the motor to power the motor; and
 a valve in fluid connection with the motor through which fluid is provided to the motor, the valve includes a compressed gas port which receives a flow of compressed gas from the compressed gas tank.
 10. The apparatus of claim **9** wherein the housing includes an open gap extending along and under the scrubber layer into which gas from the fan is blown.
 11. The apparatus of claim **10** including a table in the housing on which the scrubber layer is disposed.
 12. The apparatus of claim **11** wherein the soda lime particles have a density of 58 lbs./cubic foot.

* * * * *