

US009162726B2

(12) **United States Patent**
Takenaka et al.

(10) **Patent No.:** **US 9,162,726 B2**
(45) **Date of Patent:** **Oct. 20, 2015**

(54) **MOBILE VEHICLE**

USPC 180/219, 223
See application file for complete search history.

(71) Applicant: **HONDA MOTOR CO., LTD.**, Tokyo (JP)

(56) **References Cited**

(72) Inventors: **Toru Takenaka**, Wako (JP); **Kazushi Akimoto**, Wako (JP); **Hiroshi Gomi**, Wako (JP); **Yusuke Yamamoto**, Wako (JP); **Takashi Kudo**, Wako (JP); **Makoto Araki**, Wako (JP); **Yoshiki Takahashi**, Wako (JP)

U.S. PATENT DOCUMENTS

4,600,207 A * 7/1986 Zosi 280/279
4,624,470 A * 11/1986 Love 280/279
2013/0066522 A1 * 3/2013 Haas et al. 701/41

(73) Assignee: **HONDA MOTOR CO., LTD.**, Tokyo (JP)

FOREIGN PATENT DOCUMENTS

JP 07-215258 8/1995
JP 4181113 9/2008
JP 2008-260316 10/2008
JP 2008260316 A * 10/2008
JP 2011-073624 4/2011
JP 2012-076490 4/2012
JP 2012-076502 4/2012
JP 2012-076511 4/2012
WO 03/090979 11/2003

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/199,363**

* cited by examiner

(22) Filed: **Mar. 6, 2014**

Primary Examiner — Joseph Rocca

Assistant Examiner — Felicia L Brittman

(65) **Prior Publication Data**

US 2014/0265224 A1 Sep. 18, 2014

(74) *Attorney, Agent, or Firm* — Rankin, Hill & Clark LLP

(30) **Foreign Application Priority Data**

Mar. 12, 2013 (JP) 2013-049718

(57) **ABSTRACT**

A mobile vehicle 1A includes a front-wheel support mechanism 4 having a trail adjustment mechanism 9, a steering actuator 8 which generates a steering force for steering a front wheel 3f, a trail adjustment actuator 15 which generates a driving force for changing a trail of the front wheel 3f, and a control device 50. The control device 50 has a function of controlling the steering actuator 8 so as to stabilize the posture of a vehicle body 2, and a function of controlling the trail adjustment actuator 15 in accordance with an observed value of the vehicle speed.

(51) **Int. Cl.**
B62K 23/00 (2006.01)
B62K 21/10 (2006.01)

15 Claims, 27 Drawing Sheets

(52) **U.S. Cl.**
CPC **B62K 21/10** (2013.01)

(58) **Field of Classification Search**
CPC B62K 21/00; B62K 23/00




FIG.1




FIG.2




FIG.3




FIG.4




FIG.5




FIG. 7




FIG.8




FIG.9




FIG.10




FIG.11




FIG.12




FIG. 13




FIG.14




FIG.15




FIG.16




FIG.17
BALANCE-ASSIST-OFF/TRAVEL-ASSIST-OFF MODE PROCESSING




FIG. 18

BALANCE-ASSIST-OFF/TRAVEL-ASSIST-ON MODE PROCESSING




FIG. 19

BALANCE-ASSIST-ON/TRAVEL-ASSIST-OFF MODE PROCESSING




FIG.20

BALANCE-ASSIST-ON/TRAVEL-ASSIST-ON MODE PROCESSING




FIG.21




FIG.22




FIG.23




FIG.24




FIG.25




FIG.26

ESTIMATED INVERTED PENDULUM
MASS POINT LATERAL VELOCITY
CALCULATING SECTION 32




FIG.27

POSTURE CONTROL ARITHMETIC SECTION 38




FIG.28

CONTROL GAIN
DETERMINING
SECTION 35




FIG.29A




FIG.29B





FIG.29C



MOBILE VEHICLE

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a mobile vehicle (mobile object) such as a two-wheeled vehicle having a front wheel and a rear wheel.

2. Description of the Related Art

In a mobile vehicle, for example a motorcycle, having a front wheel and a rear wheel arranged spaced apart from each other in the longitudinal direction of the vehicle body, the front wheel usually serves as a steered wheel.

Further, a motorcycle in which the rear wheel is made steerable, in addition to the front wheel, is also known as seen, for example, in Japanese Patent Application Laid-Open No. 2008-260316 (hereinafter, referred to as "Patent Literature 1"). In the motorcycle of this Patent Literature 1, the rear wheel is steered as appropriate, in accordance with the traveling conditions, to improve the turning performance, for example, of the vehicle.

In a motorcycle of this type, the steering axis of the front wheel (rotational axis of steering of the front wheel) is generally arranged such that the point of intersection of the steering axis and the ground surface with which the wheels come into contact lies in front of the ground contact point of the front wheel (i.e. such that the trail becomes positive).

SUMMARY OF THE INVENTION

For a two-wheeled vehicle such as a motorcycle, it is desired to enhance the stability of the posture of the vehicle body particularly when the vehicle is stopped.

On the other hand, during a high-speed traveling of the two-wheeled vehicle, it is desirable that a rider can readily control the posture of the vehicle body by banking the vehicle body in the roll direction, for example, at the time of turning of the two-wheeled vehicle.

In view of the foregoing, it is an object of the present invention to provide a mobile vehicle which can enhance the stability of the posture of the vehicle body at a standstill and which also allows a rider to readily control the posture of the vehicle body during a high-speed traveling.

To achieve the above object, a mobile vehicle according to the present invention is a mobile vehicle having a vehicle body and a front wheel and a rear wheel arranged spaced apart from each other in a longitudinal direction of the vehicle body, the front wheel being a steered wheel which can be steered about a steering axis, wherein

the mobile vehicle includes:

a front-wheel support mechanism configured to support the front wheel so as to be steerable about the steering axis and having a trail adjustment mechanism which makes a trail of the front wheel adjustable;

a steering actuator which generates a steering force for steering the steered wheel;

a trail adjustment actuator which generates a driving force for changing the trail of the front wheel; and

a control device which controls the steering actuator and the trail adjustment actuator, wherein

the control device is configured to include

a steering control section which controls the steering actuator so as to stabilize a posture of the vehicle body in accordance with at least an observed value of an inclination angle in a roll direction of the vehicle body, and a trail control section which controls the trail adjustment actuator in accordance with an observed value of a

vehicle speed of the mobile vehicle such that at least the trail in a case where the observed value of the vehicle speed is zero becomes smaller than the trail in a case where the observed value of the vehicle speed is greater than a first prescribed speed (a first aspect of the invention).

It should be noted that, in the first aspect of the invention, "to stabilize (the) posture of the vehicle body" means to generate a moment (in the roll direction) that acts on the mobile vehicle so as to make the posture in the roll direction of the vehicle body converge to, or approach, a desired posture.

Further, in the first aspect of the invention, the trail of the front wheel means a distance between the ground contact point of the front wheel and the point of intersection of the ground surface and the steering axis of the front wheel in a basic posture state of the mobile vehicle. The "basic posture state" is, specifically, the state in which the front wheel and the rear wheel are both stationary in an upright posture in contact with a flat ground surface and in which the axle centerlines (centers of rotational axes) of the front wheel and the rear wheel extend in parallel with each other in the direction orthogonal to the longitudinal direction of the vehicle body.

In this case, the polarity of the trail is defined to be positive when the point of intersection of the steering axis of the front wheel and the ground surface lies in front of the ground contact point of the front wheel, and it is defined to be negative when the point of intersection of the steering axis of the front wheel and the ground surface lies behind the ground contact point of the front wheel.

The present inventors have found, through various experiments and studies, that steering the front wheel of the mobile vehicle makes it possible to cause a moment in the roll direction to act on the vehicle body, and that, in this case, the magnitude or direction of the moment generated in accordance with the steering of the front wheel has dependency on the trail of the front wheel.

As will be described later in detail, according to the experiments and studies conducted by the present inventors, in order to cause an appropriate moment for stabilizing the posture of the vehicle body to act on the vehicle body by the steering of the front wheel, it is preferable that the trail takes a value (including zero or a negative value) that is smaller than a certain positive value. Further, the moment that can be generated per unit amount of change of the steering angle of the front wheel becomes larger as the trail becomes smaller (in the case of a negative trail, as the absolute value becomes larger).

In a situation where stabilization of the posture of the vehicle body is highly demanded, as in the case where the mobile vehicle is at a standstill, it is desirable that a sufficient moment can be generated sensitively by the steering of the front wheel for stabilizing the posture. Therefore, in such a situation, a trail of a relatively small value is preferable. A negative trail is further preferable.

On the other hand, in a situation where the mobile vehicle is traveling at a vehicle speed of a certain level or higher, setting a trail to a prescribed positive value can improve the operation stability, as known as general characteristics of two-wheeled vehicles.

When the trail is set in the above-described manner, if the mobile vehicle leans in the situation where it is traveling at a vehicle speed of a certain level or higher, a self-steering function works to restore the posture of the vehicle body, without the need to cause the aforesaid steering actuator to

generate a steering force for steering the front wheel. This effect leads to improved operation stability.

Conversely, in this case, if the control is performed to cause the steering actuator to generate a large steering force, the rider may have a sense of discomfort when maneuvering the vehicle body of the mobile vehicle by shifting the body weight or manipulating the operation apparatus. Therefore, in the situation where the mobile vehicle is traveling at a vehicle speed of a certain level or higher, it is desirable that the trail is set to a prescribed positive value and that the operation of stabilizing the posture of the vehicle body by the steering actuator is restricted.

In view of the foregoing, the mobile vehicle of the first aspect of the invention is configured such that the front wheel can be steered by the steering force of the steering actuator. Further, the mobile vehicle is configured such that the trail of the front wheel can be adjusted by the trail adjustment actuator.

Further, the control device is configured to include: the steering control section which controls the steering actuator so as to stabilize the posture of the vehicle body in accordance with at least the observed value of the inclination angle in the roll direction of the vehicle body; and the trail control section which controls the trail adjustment actuator, in accordance with the observed value of the vehicle speed of the mobile vehicle, such that at least the trail in the case where the observed value of the vehicle speed is zero becomes smaller than the trail in the case where the observed value of the vehicle speed is greater than a first prescribed speed.

According to the first aspect of the invention, in the case where the observed value of the vehicle speed of the mobile vehicle is zero, i.e. when the mobile vehicle is at a standstill, the actual trail of the front wheel becomes relatively small (for example, it takes a negative value). Therefore, a moment in the roll direction appropriate for stabilizing the posture of the vehicle body can be generated by controlling the steering actuator by the steering control section.

In the case where the observed value of the vehicle speed is greater than the first prescribed speed, i.e. when the mobile vehicle is traveling at a vehicle speed in a relatively high-speed range, the actual trail of the front wheel becomes relatively large (for example, it takes a positive value). This enables the self-steering function to work appropriately, resulting in improved operation stability. Consequently, the rider can readily and freely operate the vehicle body by him/herself.

Therefore, according to the first aspect of the invention, it is possible to enhance the stability of the posture of the vehicle body at a standstill, and also allow the rider to readily control the posture of the vehicle body during a high-speed traveling.

In the first aspect of the invention, it is preferable that the trail control section is configured to control the trail adjustment actuator such that the trail takes a prescribed positive value in the case where the observed value of the vehicle speed is greater than the first prescribed speed (a second aspect of the invention).

According to the second aspect of the invention, the actual trail becomes positive in the case where the mobile vehicle is traveling at a vehicle speed in a relatively high-speed range. This can further improve the operation stability of the mobile vehicle.

Further, in the first or second aspect of the invention, the trail control section is configured, for example, to control the trail adjustment actuator to make the trail match a prescribed upper trail limit in the case where the observed value of the vehicle speed is greater than the first prescribed speed, and

control the trail adjustment actuator to make the trail match a prescribed lower trail limit which is smaller than the upper trail limit in the case where the observed value of the vehicle speed is zero.

In this case, it is preferable that the trail control section is configured to control the trail adjustment actuator to make the trail match the lower trail limit while the observed value of the vehicle speed increases from zero to the first prescribed speed, control the trail adjustment actuator to make the trail match the upper trail limit when the observed value of the vehicle speed has exceeded the first prescribed speed and until the observed value of the vehicle speed drops below a second prescribed speed which is smaller than the first prescribed speed, and control the trail adjustment actuator to make the trail match the lower trail limit when the observed value of the vehicle speed has dropped below the second prescribed speed (a third aspect of the invention).

According to the third aspect of the invention, in the case where the observed value of the vehicle speed is in a high-speed range (at least greater than the first prescribed speed), the trail of the front wheel is controlled to match the upper trail limit. Further, in the case where the observed value of the vehicle speed is in a low-speed range (at least smaller than the second prescribed speed (including zero)), the trail of the front wheel is controlled to match the lower trail limit.

As the observed value of the vehicle speed increases (during acceleration), the trail is switched from the lower trail limit to the upper trail limit at the time when the observed value has exceeded the first prescribed speed. On the other hand, as the observed value of the vehicle speed decreases (during deceleration), the trail is switched from the upper trail limit to the lower trail limit at the time when the observed value has dropped below the second prescribed speed (<first prescribed speed).

Accordingly, during the acceleration and deceleration of the mobile vehicle, the trail is switched so as to have hysteresis characteristics with respect to the change in vehicle speed. This can prevent the trail from being switched frequently between the upper trail limit and the lower trail limit in the situation where the mobile vehicle is traveling at a vehicle speed near the first or second prescribed speed.

Further, in the first or second aspect of the invention, the trail control section may be configured to successively determine a desired trail as a desired value of the trail such that the desired trail changes continuously between a prescribed upper trail limit and a prescribed lower trail limit which is smaller than the upper trail limit in accordance with the observed value of the vehicle speed, and such that the desired trail becomes larger as the observed value of the vehicle speed becomes larger, and the trail control section may be configured to control the trail adjustment actuator to make an actual trail track the desired trail (a fourth aspect of the invention).

According to the fourth aspect of the invention, it is possible to control the actual trail to a trail suitable for each vehicle speed of the mobile vehicle. The trail may take a value intermediate between the upper trail limit and the lower trail limit.

In the third aspect of the invention, it is preferable that the mobile vehicle further includes a lock mechanism operable, at least in a state where the trail matches the upper trail limit, to lock a mobile section which is included in the trail adjustment mechanism and which moves in conjunction with a change of the trail (a fifth aspect of the invention). The same applies to the above-described fourth aspect of the invention (a sixth aspect of the invention).

According to the fifth or sixth aspect of the invention, in the state where the trail matches the upper trail limit, i.e. while the

mobile vehicle is traveling at a vehicle speed in a high-speed range, the mobile section is locked by the lock mechanism. Accordingly, the trail can be mechanically maintained at the upper trail limit, without the need of the control by the trail adjustment actuator.

This can increase the robustness of the function of maintaining the trail during the high-speed traveling of the mobile vehicle. This can also reduce the energy consumption by the trail adjustment actuator.

In the first through sixth aspects of the invention, it is preferable that the steering control section is configured to control the steering actuator so as to stabilize controlled state quantities for stabilizing the posture of the vehicle body, wherein the controlled state quantities include a motional state quantity of an inclination state quantity which is a prescribed kind of state quantity having a value responsive to the inclination angle in the roll direction of the vehicle body and a motional state quantity of a steering angle of the front wheel (a seventh aspect of the invention).

It should be noted that, in the seventh aspect of the invention, “to stabilize (the) controlled state quantities” means to generate a moment (in the roll direction) that acts on the mobile vehicle so as to make the actual values of the controlled state quantities converge to, or approach, prescribed desired values (for example, values in the aforesaid basic posture state).

Further, for the “motional state quantity of (the) inclination state quantity” in the seventh aspect of the invention, for example, one or both of the value of the “inclination state quantity” as it is and a temporal change rate thereof may be adopted. Similarly, for the “motional state quantity of (the) steering angle”, for example, one or both of the value of the “steering angle” as it is and a temporal change rate thereof may be adopted.

Further, for the “inclination state quantity”, the inclination angle in the roll direction of the vehicle body may be adopted. Alternatively, the state quantity related to the position in the horizontal direction of an inverted pendulum mass point which will be described below (for example, the position in the horizontal direction of the inverted pendulum mass point, or the amount of relative movement in the horizontal direction of the inverted pendulum mass point with respect to a given reference position, or the inclination angle in the roll direction of the line segment connecting the inverted pendulum mass point and a given reference point) may be adopted.

Here, generally, dynamics of the mobile vehicle may be equivalently transformed to a dynamics model which is expressed by dynamics of a mass point system which is made up of an inverted pendulum mass point and a ground surface mass point, wherein the inverted pendulum mass point moves in a horizontal direction above a ground surface, with which the mobile vehicle comes into contact, in accordance with the inclination angle in the roll direction of the vehicle body and the steering angle of the steered wheel, and wherein the ground surface mass point moves horizontally on the ground surface, with which the mobile vehicle comes into contact, in accordance with the steering angle of the steered wheel, independently of the inclination angle in the roll direction of the vehicle body. The above-described “inverted pendulum mass point” related to the “inclination state quantity” in the seventh aspect of the invention means the inverted pendulum mass point in the dynamics model obtained by the equivalent transformation.

Therefore, the motional state quantity of the inverted pendulum mass point in the case where the dynamics of the mobile vehicle is equivalently transformed to the dynamics model which is expressed by the dynamics of the mass point

system made up of the inverted pendulum mass point, which moves in the horizontal direction above the ground surface, with which the mobile vehicle comes into contact, in accordance with the inclination angle in the roll direction of the vehicle body and the steering angle of the steered wheel, and the ground surface mass point, which moves horizontally on the ground surface, with which the mobile vehicle comes into contact, in accordance with the steering angle of the steered wheel, independently of the inclination angle in the roll direction of the vehicle body, may be adopted as the “motional state quantity of (the) inclination state quantity” in the seventh aspect of the invention.

According to the seventh aspect of the invention, it is possible to perform the control such that the motional state quantity of the inclination state quantity and the motional state quantity of the steering angle of the front wheel both converge to, or approach, the desired values. This can effectively stabilize the posture of the vehicle body of the mobile vehicle, including the steered state of the front wheel.

In the seventh aspect of the invention, it is preferable that in the case where a steering angular acceleration of the front wheel steered by the steering actuator or a torque about the steering axis applied to the front wheel from the steering actuator is defined as a reference quantity, the steering control section is configured to control the steering actuator such that a sensitivity Ra of the change in value of the reference quantity to the change in observed value of the motional state quantity of the inclination state quantity included in the controlled state quantities changes in accordance with the trail, with a characteristic that the sensitivity Ra becomes higher as the trail becomes larger (an eighth aspect of the invention).

According to the various experiments and studies conducted by the present inventors, the moment in the roll direction which can be generated per unit change amount of the steering angle of the front wheel becomes larger as the trail of the front wheel becomes smaller, as stated above. Conversely, when the trail of the front wheel is large, compared to when it is small, it becomes harder to generate the moment in the roll direction for stabilizing the posture of the vehicle body with respect to a unit change amount of the steering angle of the front wheel.

In view of the foregoing, in the eighth aspect of the invention, the steering control section controls the steering actuator such that the sensitivity Ra of the change in value of the reference quantity changes, in accordance with the trail, with the characteristic that the sensitivity Ra becomes higher as the trail becomes larger. With this configuration, in the state where the trail is controlled to be small, the moment in the roll direction which is generated in response to the steering of the front wheel by the steering actuator can be prevented from becoming too large. In the state where the trail is controlled to be relatively large, the moment in the roll direction generated in response to the steering of the front wheel by the steering actuator can be prevented from becoming too small.

It should be noted that in the eighth aspect of the invention, in the case where the motional state quantity of the inclination state quantity includes both of the value of the inclination state quantity and a temporal change rate thereof, the above-described sensitivity Ra means the sensitivity for each of the value of the inclination state quantity and the temporal change rate thereof.

In the seventh aspect of the invention, it is preferable that in the case where a steering angular acceleration of the front wheel steered by the steering actuator or a torque about the steering axis applied to the front wheel from the steering actuator is defined as a reference quantity, the steering control section is configured to control the steering actuator such that

a sensitivity Rb of the change in value of the reference quantity to the change in observed value of the motional state quantity of the steering angle of the front wheel, included in the controlled state quantities, changes in accordance with the observed value of the vehicle speed, with a characteristic that the sensitivity Rb becomes lower as the vehicle speed becomes higher (a ninth aspect of the invention).

According to the ninth aspect of the invention, in the state where the mobile vehicle is traveling at a vehicle speed in a high-speed range, even if the actual steering angle of the front wheel deviates from a required or desired value, the steering of the front wheel by the steering actuator is restricted. This allows the rider to more easily operate the mobile vehicle according to the rider's preferences in the state where the mobile vehicle is traveling at a vehicle speed in a high-speed range.

It should be noted that the eighth aspect and the ninth aspect of the invention may be combined.

In the eighth aspect of the invention, it is preferable that the steering control section is configured to control the steering actuator such that the sensitivity Ra of the change in value of the reference quantity to the change in observed value of the motional state quantity of the inclination state quantity changes in accordance with the observed value of the vehicle speed, with a characteristic that the sensitivity Ra becomes lower as the vehicle speed becomes higher (a tenth aspect of the invention). The same applies to the above-described ninth aspect of the invention (an eleventh aspect of the invention).

With this configuration, when the observed value of the vehicle speed of the mobile vehicle is in a high-speed range, even if the inclination state quantity deviates from a required or desired value, the steering of the front wheel by the steering actuator is restricted as compared to when the observed value of the vehicle speed is in a low-speed range.

Therefore, in the case where a rider is riding the mobile vehicle at a vehicle speed in a high-speed range, the rider can readily bank the vehicle body of the mobile vehicle for turning.

On the other hand, while the mobile vehicle is stopped or traveling at a vehicle speed in a low-speed range, in the case where the inclination state quantity deviates from the desired value, the steering of the front wheel by the steering actuator is performed aggressively to eliminate the deviation, as compared to when the vehicle speed of the mobile vehicle is in a high-speed range. Consequently, the posture of the vehicle body can be stabilized autonomously, without the need of skillful operation by the rider.

Further, in the eighth aspect of the invention, it is preferable that the steering control section is configured to control the steering actuator such that the sensitivity Ra of the change in value of the reference quantity to the change in observed value of the motional state quantity of the inclination state quantity changes in accordance with an observed value of the steering angle of the front wheel, with a characteristic that the sensitivity Ra becomes lower as a magnitude of the steering angle of the front wheel becomes larger (a twelfth aspect of the invention). The same applies to the above-described ninth aspect of the invention (a thirteenth aspect of the invention).

Specifically, in the case where the magnitude of the actual steering angle of the front wheel is large, compared to the case where it is small, the radius of curvature of the ground contact part of the front wheel as seen in a cross section including the ground contact point of the front wheel and having a normal direction corresponding to the longitudinal direction of the vehicle body generally becomes larger.

Therefore, in the case where the magnitude of the actual steering angle of the front wheel is large, compared to the case

where it is small, the change in movement amount of the ground contact point of the front wheel according to the change in the steering angle becomes larger. Because of this, the moment in the roll direction which is generated according to a unit amount of change of the actual steering angle of the front wheel changes in accordance with the actual steering angle of the front wheel. Therefore, if it is configured such that the aforesaid sensitivity Ra is independent of the actual steering angle of the front wheel, oscillation is likely to occur in the control of the posture of the vehicle body when the steering angle is relatively large.

In view of the foregoing, in the twelfth or thirteenth aspect of the invention, it has been configured such that the sensitivity Ra changes in accordance with the observed value of the steering angle of the front wheel, as described above. This configuration can prevent the above-described oscillation even in the case where the magnitude of the actual steering angle of the front wheel is large. Consequently, it is possible to secure high robustness in the posture control of the vehicle body of the mobile vehicle over a wide steering range of the front wheel.

It should be noted that the configuration of the twelfth aspect of the invention may be combined with the tenth or eleventh aspect of the invention.

In the eighth aspect of the invention, it is preferable that the steering control section is configured to control the steering actuator such that the sensitivity Ra of the change in value of the reference quantity to the change in observed value of the motional state quantity of the inclination state quantity and sensitivity Rb of the change in value of the reference quantity to the change in observed value of the motional state quantity of the steering angle of the front wheel both become zero in the case where the observed value of the vehicle speed is greater than a third prescribed speed (a fourteenth aspect of the invention). The same applies to the above-described ninth aspect of the invention (a fifteenth aspect of the invention).

According to the fourteenth or fifteenth aspect of the invention, when the mobile vehicle is traveling at a vehicle speed of higher than the third prescribed speed, even if the inclination state quantity or the steering angle of the front wheel deviates from a required or desired value, the steering of the front wheel by the steering actuator is not carried out. This allows the rider to bank the vehicle body and/or steer the front wheel freely according to the rider's preferences.

It should be noted that the configuration of the fourteenth aspect of the invention may be combined with any of the above-described ninth to thirteenth aspects of the invention.

Further, in the first through fifteenth aspects of the invention, it is preferable that the control device has a posture-control disabled mode which is an operating mode in which the control of the steering actuator by the steering control section is disabled, and in the posture-control disabled mode, the trail control section is configured to control an actual trail to become a prescribed trail determined in advance, and that the mobile vehicle further includes a clutch mechanism which interrupts power transmission between the steering actuator and the front wheel in the posture-control disabled mode (a sixteenth aspect of the invention).

According to the sixteenth aspect of the invention, in the posture-control disabled mode, the power transmission between the steering actuator and the front wheel is interrupted by the clutch mechanism. This can reduce friction about the steering axis that would disturb the working of the self-steering function. Further, the actual trail is maintained constantly at a prescribed trail, so that the behavioral characteristics of the mobile vehicle in response to the rider's shifting of the body weight or manipulation of the operation

apparatus become invariant. This facilitates the operation of the mobile vehicle by the rider.

It should be noted that the prescribed trail described above is preferably a positive trail, which is for example the aforesaid upper trail limit. When it is assumed that the prescribed trail is the upper trail limit, the fifth aspect and the sixteenth aspect of the invention may be combined so that, in the state where the actual trail matches the upper trail limit in the posture-control disabled mode, the trail can be maintained at the upper trail limit without the need of the driving force of the trail adjustment actuator.

Supplementally, in the seventh through sixteenth aspects of the invention, the steering control section may adopt, by way of example, the following configuration. The steering control section includes, for example, an actuator operational target determining section which successively receives observed values of the actual values of the aforesaid controlled state quantities and determines an operational target of the aforesaid steering actuator (for example, the desired value of the aforesaid reference quantity), in accordance with deviations of the received observed values from desired values of the corresponding controlled state quantities for stabilizing the controlled state quantities, so as to make the deviations approach zero, by a feedback control law. The steering control section is configured to control the steering actuator in accordance with the determined operational target.

Further, in the present specification, the "observed value" of a given state quantity related to the mobile vehicle (such as the vehicle speed, inclination state quantity, or steering angle of the front wheel) means a detected value or an estimate of the actual value of the state quantity. In this case, the "detected value" means an actual value of the state quantity which is detected by an appropriate sensor. The "estimate" means a value which is estimated from a detected value of at least one state quantity having correlation with the state quantity, on the basis of the correlation, or it means a pseudo estimate which can be considered to coincide, or almost coincide, with the actual value of the state quantity.

For the "pseudo estimate", for example in the case where it is expected that the actual value of the state quantity can adequately track a desired value of the state quantity, the desired value may be adopted as the pseudo estimate of the actual value of the state quantity.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a diagram schematically showing a two-wheeled vehicle for illustrating the fundamental technical matters related to an embodiment of the present invention;

FIG. 2 is a diagram showing a mass point system (equivalent two-mass-point system) for expressing the dynamics of the two-wheeled vehicle in FIG. 1;

FIG. 3 is a diagram showing a model related to the behavior of the two-wheeled vehicle in FIG. 1;

FIG. 4 is a diagram for illustrating the behavior of the model in FIG. 3;

FIG. 5 is a graph for illustrating the behavior of the model in FIG. 3;

FIG. 6 is a diagram showing a model for illustrating a dynamic behavior of the two-wheeled vehicle in FIG. 1; and

FIGS. 7 and 8 are graphs showing the behavioral characteristics of the two-wheeled vehicle in FIG. 1.

FIG. 9 is a side view of a mobile vehicle (two-wheeled vehicle) according to an embodiment of the present invention;

FIG. 10 is a cross-sectional view taken along the line A-A in FIG. 9;

FIG. 11 is a cross-sectional view taken along the line B-B in FIG. 10;

FIG. 12 is a block diagram showing the configuration related to the control of the mobile vehicle in FIG. 9;

FIG. 13 is a block diagram showing the major functions of the control device shown in FIG. 12; and

FIG. 14 is a flowchart showing the processing in the control device shown in FIG. 12.

FIG. 15 is a diagram illustrating the transitions between the operating modes in relation to the flowchart in FIG. 14;

FIG. 16 is a flowchart showing the processing in the initialization mode in the flowchart in FIG. 14;

FIG. 17 is a flowchart showing the processing in the balance-assist-off/travel-assist-off mode in the flowchart in FIG. 14;

FIG. 18 is a flowchart showing the processing in the balance-assist-off/travel-assist-on mode in the flowchart in FIG. 14;

FIG. 19 is a flowchart showing the processing in the balance-assist-on/travel-assist-off mode in the flowchart in FIG. 14;

FIG. 20 is a flowchart showing the processing in the balance-assist-on/travel-assist-on mode in the flowchart in FIG. 14; and

FIG. 21 is a flowchart showing the processing in the abnormal mode in the flowchart in FIG. 14.

FIG. 22 is a block diagram showing the processing performed by the estimated vehicle speed calculating section shown in FIG. 13;

FIG. 23 shows graphs for illustrating, by way of example, the processing performed by the desired trail determining section shown in FIG. 13 and the processing for controlling the actual trail according to the desired trail;

FIG. 24 is a graph for illustrating another example of the processing performed by the desired trail determining section shown in FIG. 13 and the processing for controlling the actual trail according to the desired trail;

FIG. 25 is a block diagram showing the processing performed by the estimated inverted pendulum mass point lateral movement amount calculating section shown in FIG. 13;

FIG. 26 is a block diagram showing the processing performed by the estimated inverted pendulum mass point lateral velocity calculating section shown in FIG. 13;

FIG. 27 is a block diagram showing the processing performed by the posture control arithmetic section shown in FIG. 13;

FIG. 28 is a block diagram showing the processing performed by the control gain determining section shown in FIG. 13; and

FIGS. 29A, 29B, and 29C are graphs for illustrating the processing performed by the control gain determining section shown in FIG. 13.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

An embodiment of the present invention will be described below with reference to FIGS. 1 to 29.

First of all, the fundamental technical matters related to the present embodiment will be described with reference to FIGS. 1 to 8.

FIG. 1 is a schematic side view of a two-wheeled vehicle 1 (specifically, the two-wheeled vehicle 1 in the basic posture state as will be described later) which is a mobile vehicle having a vehicle body 2 and a front wheel 3_f and a rear wheel 3_r arranged spaced apart from each other in the longitudinal direction of the vehicle body 2. In FIG. 1, besides the side

11

view of the two-wheeled vehicle **1**, the rear wheel **3r** as seen from the back of the two-wheeled vehicle **1** is illustrated on the left side of the two-wheeled vehicle **1**, and the front wheel **3f** as seen from the front of the two-wheeled vehicle **1** is illustrated on the right side of the two-wheeled vehicle **1**.

The front wheel **3f** is axially supported in a rotatable manner by a front-wheel support mechanism **4** provided at the front portion of the vehicle body **2**. The front-wheel support mechanism **4** is made up, for example, of a front fork. The front wheel **3f** is a steered wheel which can be steered (turned) about a steering axis *Csf* which is tilted backward.

It should be noted that the steering axis *Csf* being tilted backward means that the steering axis *Csf* extends obliquely with respect to the longitudinal direction and up-and-down direction of the vehicle body **2** such that the steering axis *Csf* has its upper portion located rearward relative to its lower portion in the front-rear (longitudinal) direction of the vehicle body **2**.

The rear wheel **3r** is axially supported in a rotatable manner by a rear-wheel support mechanism **5** provided at the rear portion of the vehicle body **2**. The rear-wheel support mechanism **5** is made up, for example, of a swing arm. This rear wheel **3r** is a non-steered wheel.

According to various experiments and studies conducted by the present inventors, generally, the dynamic behaviors related to the change in posture in the roll direction (direction about the longitudinal axis of the vehicle body **2**) of the two-wheeled vehicle **1** having the above-described structure can be approximately expressed by the dynamics of a mass point system which is made up of an inverted pendulum mass point, which moves in a horizontal direction above a ground surface **110**, with which the two-wheeled vehicle **1** comes into contact, in accordance with an inclination angle in the roll direction of the vehicle body **2** and the steering angle of the steered wheel, and a ground surface mass point, which moves horizontally on the ground surface **110** in accordance with the steering angle of the steered wheel (front wheel **3f**), independently of the inclination angle in the roll direction of the vehicle body **2**.

The dynamics will now be described.

It is here assumed, by way of example, that a two-wheeled vehicle **1** which is in the state of standing still in a straight-ahead posture on a flat ground surface **110**, as shown in FIG. **1**, is regarded as one rigid body having the entire mass and inertia moment concentrated on the vehicle body **2**. It should be noted that the state in which the two-wheeled vehicle **1** is standing still in the straight-ahead posture means the state in which the front wheel **3f** and the rear wheel **3r** are both stationary in the upright posture in contact with the ground surface **110** and in which the axle centerlines (centers of rotational axes) *Cf* and *Cr* of the front wheel **3f** and the rear wheel **3r** extend in parallel with each other in the direction orthogonal to the longitudinal direction of the vehicle body **2**. Hereinafter, the state in which the two-wheeled vehicle **1** is standing still in the straight-ahead posture as described above will be referred to as the “basic posture state” of the two-wheeled vehicle **1**.

In the state where the two-wheeled vehicle **1** in the basic posture state is regarded as one rigid body, the overall mass of the two-wheeled vehicle **1** (hereinafter, also simply referred to as “total mass”) is denoted as *m*, the height of the overall center of gravity *G* of the two-wheeled vehicle **1** (hereinafter, also simply referred to as “center-of-gravity height”) is denoted as *h*, and the overall inertia moment of the two-wheeled vehicle **1** (hereinafter, also simply referred to as “overall inertia”) about the longitudinal axis *Crol* (hereinafter, referred to as “central roll axis *Crol*”) which extends in the

12

longitudinal direction of the vehicle body **2** while passing through the overall center of gravity *G* is denoted as *I*.

m: total mass

h: center-of-gravity height

I: overall inertia

The system obtained when the two-wheeled vehicle **1** is regarded as one rigid body as described above can be equivalently transformed to a system, as shown in FIG. **2**, which is made up of two mass points of a first mass point **123** having a height *h'* (>the above-described center-of-gravity height *h*) from the ground surface **110**, and a second mass point **124** located on the ground surface **110**. Hereinafter, this system will be referred to as “equivalent two-mass-point system”.

Here, as shown below, the mass of the first mass point **123** in the equivalent two-mass-point system is denoted as *m1*, the mass of the second mass point **124** as *m2*, and the difference (= *h'* - *h*) between the height *h'* of the first mass point **123** and the aforesaid center-of-gravity height *h* as *c* (where *c* > 0). In other words, the height *h'* of the first mass point **123** from the ground surface **110** is (*h* + *c*).

m1: mass of the first mass point **123**

m2: mass of the second mass point **124**

c: difference between the height *h'* of the first mass point **123** and the center-of-gravity height *h* (where *c* > 0)

In order for the equivalent two-mass-point system shown in FIG. **2** to be a system that is equivalent to the two-wheeled vehicle **1** regarded as one rigid body, the following condition needs to be satisfied: the overall mass of the equivalent two-mass-point system matches the aforesaid total mass *m*. This condition is expressed by the following expression (1).

$$m1 + m2 = m \quad (1)$$

Further, the following condition also needs to be satisfied: the height of the overall center of gravity of the mass points **123** and **124** in the equivalent two-mass-point system in FIG. **2** matches the aforesaid center-of-gravity height *h*. This condition is expressed by the following expression (2).

$$m1 * c = m2 * h \quad (2)$$

Further, the following condition also needs to be satisfied: the inertia moment about the overall center of gravity in the equivalent two-mass-point system in FIG. **2** (specifically, the inertia moment about the longitudinal axis passing through the overall center of gravity in the equivalent two-mass-point system) matches the aforesaid overall inertia *I*. This condition is expressed by the following expression (3).

$$m1 * c * c + m2 * h * h = I \quad (3)$$

From the above expressions (1) to (3), the following expressions (4), (5), and (6) are obtained.

$$c = I / (m * h) \quad (4)$$

$$m1 = (h / (h + I / (m * h))) * m \quad (5)$$

$$m2 = ((I / (m * h)) / (h + I / (m * h))) * m \quad (6)$$

Therefore, the equivalent two-mass-point system in FIG. **2** is, in other words, a system which has a first mass point **123** whose height *h'* from the ground surface **110** is higher than the center-of-gravity height *h* of the two-wheeled vehicle **1** in the basic posture state and a second mass point **124** on the ground surface **110** (second mass point **124** whose height from the ground surface **110** is “0”), and in which the difference *c* (= *h'* - *h*) between the height *h'* of the first mass point **123** and the center-of-gravity height *h* and the masses *m1* and *m2* are set by the above expressions (4), (5), and (6) in accordance with the total mass *m*, overall inertia *I*, and center-of-gravity height *h* of the two-wheeled vehicle **1**.

FIG. 3 shows an approximate dynamics model which approximately expresses the dynamics of the two-wheeled vehicle 1 in the aforesaid basic posture state and similar posture states (close to the basic posture state). This approximate dynamics model has been established by regarding the two-wheeled vehicle 1 as the above-described equivalent two-mass-point system.

It is here assumed a three-axis orthogonal coordinate system (XYZ coordinate system) in which a projected point obtained by projecting the overall center of gravity G of the two-wheeled vehicle 1 in the basic posture state onto the ground surface 110 in the perpendicular direction (up-and-down direction) is defined as the origin, the longitudinal direction of the vehicle body 2 of the two-wheeled vehicle 1 as the X-axis direction, the lateral direction (vehicle width direction) as the Y-axis direction, and the vertical direction as the Z-axis direction. In this case, the positive directions of the X, Y, and Z axes correspond to the forward, leftward, and upward directions, respectively.

Further, in terms of rotation or angle, the direction about the X axis is called the roll direction, the direction about the Y axis is called the pitch direction, and the direction about the Z axis is called the yaw direction. The positive directions of the roll, pitch, and yaw directions are each determined as the direction of rotation of a right-hand screw when the screw is turned so as to move in the positive direction of the corresponding one of the X, Y, and Z axes.

Further, the caster angle of the front wheel 3f (the inclination angle (with respect to the up-and-down direction) of the steering axis Csf of the front wheel 3f in the basic posture state) is denoted as θ_{cf} . In this case, the caster angle θ_{cf} in the case where the steering axis Csf of the front wheel 3f is tilted backward as shown in FIG. 1 is defined to be positive.

It is now assumed that, in the basic posture state of the two-wheeled vehicle 1, the steering angle of the front wheel 3f (hereinafter, also simply referred to as “front-wheel steering angle”) is changed instantaneously from “0” to δf ($\neq 0$). It is defined that the front-wheel steering angle is “0” in the basic posture state (non-steered state of the front wheel 3f). It is also defined that the positive rotational direction of the front-wheel steering angle (rotational angle) about the steering axis Csf corresponds to the direction of rotation that makes the front end of the front wheel 3f turn left with respect to the vehicle body 2 (so that the two-wheeled vehicle 1 turns to the left when traveling forward).

As shown in FIG. 4, the inclination angle in the roll direction (hereinafter, also referred to as “roll angle”) of the vehicle body 2 immediately after the instantaneous change of the front-wheel steering angle from “0” to δf ($\neq 0$) is denoted as ϕ_b , and the movement amount in the Y-axis direction of the second mass point 124 is denoted as q . It should be noted that the inclination angle in the roll direction of the line segment connecting the first mass point 123 and the second mass point 124 agrees with the roll angle ϕ_b of the vehicle body 2.

According to the dynamic relationship, the moment generated about the X axis by the resultant force of a reaction force that the two-wheeled vehicle 1 receives from the ground surface 110 and an inertial force resulting from the motions of the mass points 123 and 124 is “0”.

Here, the reaction force that the two-wheeled vehicle 1 receives from the ground surface 110 is composed of a reaction force in the vertical direction (vertical load) and a friction force in the horizontal direction. The friction force, however, does not generate a moment in the roll direction about the origin.

Further, when the front-wheel steering angle is changed, the ground contact point (point of application of the reaction

force in the vertical direction) moves by a finite distance. Immediately after the instantaneous change of the front-wheel steering angle, however, the lapse time is infinitesimal. Therefore, a value obtained by time integration of the moment in the roll direction generated by the reaction force in the vertical direction is infinitesimal. That is, immediately after the instantaneous change of the front-wheel steering angle, the total angular momentum (in the roll direction) about the origin due to the motions of the mass points 123 and 124 is infinitesimal.

Incidentally, the height of the second mass point 124 is “0”, and the motion of the second mass point 124 is limited to the transverse direction. Therefore, the angular momentum about the origin due to the motion of the second mass point 124 is “0”.

On the basis of the above, the angular momentum about the origin due to the motion of the first mass point 123 becomes infinitesimal. That is, the first mass point 123 is instantaneously held still. As a result, the rotation in the roll direction (change in roll angle) of the vehicle body 2 is performed about the mass point 123. In other words, it can be considered that the position of the first mass point 123 is fixed at the instant when the steering angle of the front wheel 3f is changed from the basic posture state.

In this case, the movement amount q in the Y-axis direction (hereinafter, simply referred to as “lateral movement amount q ”) of the second mass point 124 is expressed by the following expression (7).

$$q = (c+h) \cdot \phi_b \quad (7)$$

In the expression (7), it is considered that the magnitude of ϕ_b is sufficiently small and that the following holds: $\sin(\phi_b) \approx \phi_b$.

The roll angle of the front wheel 3f is denoted as ϕ_f , and the roll angle of the rear wheel 3r is denoted as ϕ_r .

Since the caster angle θ_{cf} is not “0”, the steering of the front wheel 3f causes a rotational motion component in the roll direction to be generated on the front wheel 3f. Therefore, the roll angle ϕ_f of the front wheel 3f is obtained approximately from the following expression (8). In the expression (8), the magnitude of δf is considered to be sufficiently small.

$$\phi_f = -\sin(\theta_{cf}) \cdot \delta f + \phi_b \quad (8)$$

Further, the roll angle ϕ_r of the rear wheel 3r is obtained by the following expression (9).

$$\phi_r = \phi_b \quad (9)$$

Further, as shown in FIG. 1, a distance in the longitudinal direction (in the X-axis direction) between the overall center of gravity G of the two-wheeled vehicle 1 and the ground contact point of the front wheel 3f in the basic posture state is denoted as L_f , and a distance in the longitudinal direction (in the X-axis direction) between the overall center of gravity G of the two-wheeled vehicle 1 and the ground contact point of the rear wheel 3r in the basic posture state is denoted as L_r . That is, L_f represents the longitudinal distance between the center of the axle of the front wheel 3f and the overall center of gravity G of the two-wheeled vehicle 1 in the basic posture state, and L_r represents the longitudinal distance between the center of the axle of the rear wheel 3r and the overall center of gravity G of the two-wheeled vehicle 1 in the basic posture state.

Further, in the basic posture state, the point of intersection of the steering axis Csf and a straight line connecting the center of the axle and the ground contact point of the front wheel 3f is denoted as E_f , and the height of the intersection point E_f (height from the ground surface 110) is denoted as a .

15

It should be noted that the height a of the intersection point E_f indicates the position in the Z -axis direction (Z coordinate) of the intersection point E_f . When the intersection point E_f lies above the ground surface **110**, $a > 0$; when the intersection point E_f lies below the ground surface **110**, $a < 0$. Furthermore, in the case where the caster angle θ_{cf} is positive, the height a being positive means a positive trail (t shown in FIG. 1), whereas the height a being negative means a negative trail t .

The relationship between the height a of the intersection point E_f and the trail t is expressed by the following expression (10).

$$t = a \cdot \tan(\theta_{cf}) \quad (10)$$

Further, as shown in FIG. 1, on a straight line connecting the center of the axle of the rear wheel **3r** and its ground contact point in the basic posture state, a point whose height from the ground surface **110** coincides with the aforesaid height a is denoted as E_r . The points E_f and E_r are fixed to the vehicle body **2**. The line segment connecting these points E_f and E_r intersects the line segment connecting the mass points **123** and **124** (i.e. the line segment which is orthogonal to the X axis and which passes through the overall center of gravity G). This point of intersection is denoted as E , as shown in FIG. 1.

The movement amount in the Y -axis direction (lateral movement amount) of the point E_f at the time when the front wheel **3f** is instantaneously steered from the basic posture state is denoted as e_f , and the movement amount in the Y -axis direction (lateral movement amount) of the point E_r at that time is denoted as e_r . These e_f and e_r are expressed by the following expressions (11) and (12), respectively.

$$e_f = -a \cdot \phi_f \quad (11)$$

$$e_r = -a \cdot \phi_r \quad (12)$$

In the expressions (11) and (12), it is considered that the magnitudes of ϕ_f and ϕ_r are sufficiently small and that the following hold: $\sin(\phi_f) \approx \phi_f$, $\sin(\phi_r) \approx \phi_r$.

The movement amount in the Y -axis direction (lateral movement amount) of the point E is denoted as e . As the point E is an internally dividing point between the points E_f and E_r , the lateral movement amount e of the point E is expressed by the following expression (13).

$$e = (L_r / (L_f + L_r)) \cdot e_f + (L_f / (L_f + L_r)) \cdot e_r \quad (13)$$

On the other hand, as shown in FIG. 4, the inclination of the line segment connecting the point E and the second mass point **124** is equal to the roll angle ϕ_b of the vehicle body **2**. The height of the point E is a . Therefore, the following expression (14) holds. In the expression (14), it is considered that the magnitude of ϕ_b is sufficiently small and that the following holds: $\sin(\phi_b) \approx \phi_b$.

$$q = e + a \cdot \phi_b \quad (14)$$

From the above expressions (9) and (11) to (14), the following expression (15) is obtained.

$$q = L_r / (L_f + L_r) \cdot a \cdot \sin(\theta_{cf}) \cdot \delta f \quad (15)$$

From the expressions (4), (7), and (15), the following expression (16) is obtained.

$$\phi_b = a \cdot (L_r / ((L_f + L_r) \cdot (h + I / (m \cdot h)))) \cdot \sin(\theta_{cf}) \cdot \delta f \quad (16)$$

As shown in FIG. 1 or 3, the radius of curvature of the transverse cross-sectional shape of the front wheel **3f** at the position of the ground contact point of the front wheel **3f** in the basic posture state is denoted as R_f . Similarly, the radius of curvature of the transverse cross-sectional shape of the rear

16

wheel **3r** at the position of the ground contact point of the rear wheel **3r** in the basic posture state is denoted as R_r .

It should be noted that the above-described transverse cross-sectional shape of the front wheel **3f** means the shape of the ground contact part as seen in a transverse cross section including the axle centerline C_f and the ground contact point of the front wheel **3f** (this corresponds to the transverse cross-sectional shape of the ground contact part of the tire of the front wheel **3f**). The radius of curvature at the point of contact with the ground surface **110** in this transverse cross-sectional shape is the above-described R_f . The same applies to the rear wheel **3r**.

The point of application, on the ground surface **110**, of the resultant force of the reaction force in the vertical direction which acts on the front wheel **3f** from the ground surface **110** and the reaction force in the vertical direction which acts on the rear wheel **3r** from the ground surface **110**, i.e. the center of contact pressure, is denoted as COP, and the movement amount in the Y -axis direction (lateral movement amount) of the COP is denoted as p .

As shown in FIG. 5, the movement amount in the Y -axis direction of the ground contact point of the front wheel **3f** is $(-R_f \cdot \phi_f)$, and the movement amount in the Y -axis direction of the ground contact point of the rear wheel **3r** is $(-R_r \cdot \phi_r)$. The example shown in FIG. 5 is the case where $\phi_r > 0$ and $\phi_f < 0$.

The COP is, as shown in FIG. 5, the point of intersection between the Y axis and the line segment connecting the ground contact point of the front wheel **3f** and the ground contact point of the rear wheel **3r**. Therefore, the lateral movement amount p of the COP is expressed by the following expression (17).

$$p = -(L_r / (L_f + L_r)) \cdot R_f \cdot \phi_f - (L_f / (L_f + L_r)) \cdot R_r \cdot \phi_r \quad (17)$$

From the expressions (8), (9), and (17), the following expression (18) is obtained.

$$p = (L_r / (L_f + L_r)) \cdot R_f \cdot \sin(\theta_{cf}) \cdot \delta f - ((L_f / (L_f + L_r)) \cdot R_r + (L_r / (L_f + L_r)) \cdot R_f) \cdot \phi_b \quad (18)$$

Supplementally, it can be interpreted that the part $(L_r / (L_f + L_r)) \cdot R_f$ in the first term on the right side of the expression (18) corresponds to a virtual tire radius (tire radius as seen on the plane orthogonal to the X axis) at the position immediately beneath the overall center of gravity G corresponding to the roll angle resulting from the steering of the front wheel **3f**.

Further, it can be interpreted that the part $((L_f / (L_f + L_r)) \cdot R_r + (L_r / (L_f + L_r)) \cdot R_f)$ in the second term on the right side of the expression (18) corresponds to a virtual tire radius (tire radius as seen on the plane orthogonal to the X axis) at the position immediately beneath the overall center of gravity G corresponding to the roll angle of the vehicle body **2**.

Consideration will now be given to balancing in moment about the origin (of the XYZ coordinate system) immediately after the steering angle of the front wheel **3f** of the two-wheeled vehicle **1** in the basic posture state is changed stepwise from "0" to δf ($\neq 0$) at a given initial time t_0 .

The dynamic behavior at this time can be expressed by a model shown in FIG. 6.

This model includes, as virtual components, a body link **132** which is supported on a dolly **131** movable in the Y axis direction, and a mobile section **133** which is movably supported by the body link **132**. The body link **132** and the mobile section **133** correspond to the vehicle body **2**.

The Y axis is set above a floor **134** which supports the dolly **131**. The floor **134** does not correspond to the actual ground surface **110** with which the two-wheeled vehicle **1** comes into contact. That is, the floor **134** is simply a virtual plane that supports the dolly **131** to enable the dolly **131** to move in a

horizontal direction. The actual ground surface **110** exists at the level of the Y axis (the level where the Z coordinate (position coordinate in the Z-axis direction) becomes “0”).

In the model shown in FIG. 6, all the components are set to have the inertia moment of “0”. Of the components of this model, the components except the body link **132** and the mobile section **133** are set to have the mass of “0”.

The body link **132** has a rail portion **132a** which extends in the transverse direction and an erecting portion **132b** which extends upward from the rail portion **132a**. The model has a first mass point **123** having a mass m_1 at the upper portion of the erecting portion **132b**. Before the initial time t_0 , the Y coordinate of the position of the first mass point **123** is “0”, and its Z coordinate is $(h+c)$ ($=h+I/(m*h)$).

The body link **132** is connected via a link **136** to a member **135** which is fixedly secured to the floor **134**. This constrains the movement in the Y-axis direction of the body link **132**; it cannot move in the Y-axis direction. Before the initial time t_0 , the rail portion **132a** of the body link **132** extends in the Y-axis direction.

The mobile section **133** is supported by the rail portion **132a** of the body link **132** so as to be movable along the rail portion **132a**. The position in the Y-axis direction (Y coordinate) of this mobile section **133** is controlled by an actuator **137** which is interposed between the mobile section **133** and the erecting portion **132b** of the body link **132**.

Further, the mobile section **133** has a second mass point **124** having a mass m_2 . Before the initial time t_0 , the Z coordinate of the position of the mass point **124** is “0”.

The dolly **131** supporting the body link **132** is freely movable in a horizontal direction on the floor **134**. This dolly **131** has a wheel **131a** at its upper end, and is in contact (point contact) with the body link **132** via the wheel **131a**, thereby supporting the body link **132** from underneath. The point of contact between the wheel **131a** of the dolly **131** and the body link **132** corresponds to the aforesaid COP. With the COP as the fulcrum, the body link **132** can be inclined in the direction about the X axis (roll direction).

The Z coordinate of the position of the COP is always “0”. Further, the Y coordinate of the position of the COP is controlled by an actuator **138** which is interposed between the lower portion of the rail portion **132a** of the body link **132** and the dolly **131**. Supplementally, the inclination in the direction about the X axis (roll direction) of the line segment connecting the first mass point **123** and the second mass point **124** corresponds to the inclination in the direction about the X axis (roll direction) of the vehicle body **2**.

Before the initial time t_0 , the Y coordinate of the position of the COP and the Y coordinate of the position of the second mass point **124** are both “0”.

It is here assumed that, with a stepwise change (from “0” to δf) of the front-wheel steering angle at the initial time t_0 , the Y coordinate of the position of the COP has instantaneously become p by the actuator **138** and the Y coordinate of the position of the second mass point **124** has instantaneously become q by the actuator **137**.

Before the initial time t_0 , the Y coordinate of the position of the first mass point **123** is “0”. Further, instantaneously, the first mass point **123** can be regarded as a fixed point, as stated above. Therefore, immediately after the initial time t_0 , the moment in the roll direction which is generated about the origin due to the gravitational force acting on the first mass point **123** is “0”.

Further, the moment M_2 (hereinafter, also referred to as “gravitational moment M_2 ”) in the roll direction which is generated about the origin due to the gravitational force acting on the second mass point **124** is obtained by the following

expression (19). It should be noted that g represents the gravitational acceleration constant (>0).

$$M_2 = -m_2 * g * q \quad (19)$$

Further, the moment M_p (hereinafter, also referred to as “road surface reaction force moment M_p ”) in the roll direction which is generated about the origin due to the road surface reaction force in the vertical direction (vertical load) acting on the COP from the ground surface **110** is obtained by the following expression (20).

$$M_p = m * g * p \quad (20)$$

According to the dynamic relationship, the sum of the above-described moments M_2 and M_p coincides with the sign-reversed (or, opposite-polarity) total inertial force moment M_a in the roll direction generated about the origin due to the motions of the first mass point **123** and the second mass point **124**. That is, the following expression (21) holds.

$$M_a + M_2 + M_p = 0 \quad (21)$$

Consideration will now be given to the inertial force moment M_a .

The motions of the first mass point **123** and the second mass point **124** are made up of the motion which is generated by the actuator **137** and the motion which is generated as the body link **132** inclines (rotates) in the roll direction about the COP.

The direction of the acceleration of the second mass point **124** generated by the actuator **137** corresponds to the direction of the straight line connecting the second mass point **124** and the origin. Thus, the inertial force moment in the roll direction generated about the origin due to the motion of the second mass point **124** by the actuator **137** is “0”.

Here, the rotational angular velocity of the body link **132** which inclines in the roll direction about the COP is denoted as ω , and its differential value (i.e. rotational angular acceleration) is denoted as $\dot{\omega}$. The inertial force moment in the roll direction generated about the origin due to the motions of the mass points **123** and **124** resulting from this rotational motion is obtained as a sum, multiplied by -1 , of the square of the distance between the first mass point **123** and the origin multiplied by the mass m_1 and $\dot{\omega}$, and the square of the distance between the second mass point **124** and the origin multiplied by the mass m_2 and $\dot{\omega}$.

The distance between the origin and the second mass point **124**, however, is “0” before the initial time t_0 . Even after the initial time t_0 , it is considered that the distance between the origin and the second mass point **124** ($=$ absolute value of q) is sufficiently small compared to the distance between the origin and the first mass point **123** ($=h+c$). Further, the mass m_2 is generally smaller than the mass m_1 .

Therefore, the magnitude of the inertial force moment due to the motion of the second mass point **124** is sufficiently small compared to the magnitude of the inertial force moment due to the motion of the first mass point **123**, so that the inertial force moment due to the motion of the second mass point **124** can be ignored. Accordingly, M_a becomes comparable to the inertial force moment generated due to the motion of the first mass point **123** accompanying the inclination of the vehicle body **2**.

As a result, the total inertial force moment M_a in the roll direction generated about the origin is obtained by the following expression (22).

$$M_a = -m_1 * (h+I/(m*h)) * (h+I/(m*h)) * \dot{\omega} \quad (22)$$

19

From the expressions (21) and (22), the following expression (23) is obtained.

$$m1*(h+I/(m*h))*(h+I/(m*h))*\omega\dot{=}Mp+M2 \quad (23)$$

The expression (23) can be interpreted that it expresses the behavior of inclination of an inverted pendulum, having a mass $m1$ and a mass point height $(h+I/(m*h))$ and having the origin at the fulcrum, at the time when the moment $(Mp+M2)$ is applied to the fulcrum of the inverted pendulum. Thus, hereinafter, the first mass point **123** may also be referred to as “inverted pendulum mass point **123**”.

Even if the body link **132** inclines in the roll direction about the COP, the position of the origin of the body link **132** hardly moves in the transverse direction. Therefore, the inclination of the inverted pendulum mass point **123** coincides with the inclination in the roll direction of the body link **132**.

Further, the position of the fulcrum of the inverted pendulum mass point **123** corresponds to the origin of the aforesaid three-axis orthogonal coordinate system (the projected point obtained by projecting the overall center of gravity G in the basic posture state of the two-wheeled vehicle **1** onto the ground surface **110** in the perpendicular direction (up-and-down direction)).

Furthermore, since the first mass point (inverted pendulum mass point) **123** and the second mass point **124** (hereinafter, also referred to as “ground surface mass point **124**”) are on the plane of symmetry of the vehicle body **2** (plane of symmetry when the vehicle body **2** is considered to be bilaterally symmetrical), the inclination in the roll direction of the line segment connecting the first mass point **123** and the second mass point **124** corresponds to the inclination in the roll direction of the vehicle body **2** of the two-wheeled vehicle **1**.

Further, as can be seen from the expression (15), the movement amount q in the Y-axis direction of the second mass point **124** is determined uniquely from the steering angle δf . It should be noted that in an actual two-wheeled vehicle such as the two-wheeled vehicle **1A** in an embodiment which will be described later, the movement amount q is determined from the steering angle δf by a nonlinear function.

On the basis of the foregoing, stabilizing the motional state of the inverted pendulum mass point **123** while stabilizing the steering angle δf becomes equivalent to stabilizing the inclination in the roll direction of the vehicle body **2** of the two-wheeled vehicle **1** while stabilizing the steering angle δf .

It can be appreciated from the above expression (23) that the rotational angular acceleration $\omega\dot{}$ in the roll direction of the body link **132** (in other words, the rotational angular acceleration in the roll direction of the line segment connecting the origin and the inverted pendulum mass point **123**, or in yet other words, the rotational angular acceleration in the roll direction of the inverted pendulum mass point **123** as seen from the origin) at the instant immediately after the initial time $t0$ is determined depending on: the aforesaid road surface reaction force moment Mp , which is generated about the origin due to the reaction force in the vertical direction acting on the two-wheeled vehicle **1** from the ground surface **110** via the COP, and the aforesaid gravitational moment $M2$, which is generated about the origin due to the gravitational force acting on the second mass point (ground surface mass point) **124**.

Accordingly, it is possible to use $(Mp+M2)$ as a manipulation moment for controlling the motional state of the inverted pendulum mass point **123**. Consequently, it is possible to use $(Mp+M2)$ as a manipulation moment for controlling the posture (inclination angle in the roll direction) of the vehicle body **2** of the two-wheeled vehicle **1** to a desired or required posture. Therefore, hereinafter, $(Mp+M2)$ is denoted

20

as $Msum$, as in the following expression (24), and is called the “posture controlling manipulation moment”.

$$Msum=Mp+M2 \quad (24)$$

This posture controlling manipulation moment $Msum$ is expressed by the following expression (25) from the aforesaid expressions (6), (15), (16), (18), (19), (20), and (24).

$$Msum=-((Rg+I/(m*h))/(h+I/(m*h)))*a-Rf*(Lr/(Lf+Lr))*m*g*\sin(\theta cf)*\delta f \quad (25)$$

$$\text{where } Rg=(Lr/(Lf+Lr))*Rf+(Lf/(Lf+Lr))*Rr \quad (25a)$$

As can be seen from the aforesaid expression (18), Rg corresponds to the ratio of the amount of change in lateral movement amount p of the COP to the amount of change in roll angle of the vehicle body **2** (i.e. sensitivity of the change in lateral movement amount p of the COP to a small change in roll angle) in the case where the roll angle of the vehicle body **2** is changed by a small amount from the basic posture state.

On the other hand, the gravitational moment $M2$ is expressed by the following expression (26) from the aforesaid expressions (6), (15), and (19).

$$M2=-((I/(m*h))/(h+I/(m*h)))*Lr/(Lf+Lr)*a*m*g*\sin(\theta cf)*\delta f \quad (26)$$

Further, the road surface reaction force moment Mp is expressed by the following expression (27) from the aforesaid expressions (16), (18), (20), and (25a).

$$Mp=-((Rg/(h+I/(m*h)))*a-Rf)*Lr/(Lf+Lr)*m*g*\sin(\theta cf)*\delta f \quad (27)$$

Here, a_sum , k_sum , a_p , k_p , and k_m are defined as follows.

$$a_sum=((h+I/(m*h))/(Rg+I/(m*h)))*Rf \quad (28)$$

$$k_sum=-((Rg+I/(m*h))/(h+I/(m*h)))*Lr/(Lf+Lr)*m*g*\sin(\theta cf) \quad (29)$$

$$k_m=-((I/(m*h))/(h+I/(m*h)))*Lr/(Lf+Lr)*m*g*\sin(\theta cf) \quad (30)$$

$$a_p=((h+I/(m*h))/Rg)*Rf \quad (31)$$

$$k_p=-((Rg/(h+I/(m*h)))*Lr/(Lf+Lr))*m*g*\sin(\theta cf) \quad (32)$$

From the expressions (25), (28), and (29), the following expression (33) is obtained.

$$Msum=k_sum*(a-a_sum)*\delta f \quad (33)$$

Further, from the expressions (26) and (30), the following expression (34) is obtained.

$$M2=k_m*a*\delta f \quad (34)$$

Further, from the expressions (27), (31), and (32), the following expression (35) is obtained.

$$Mp=k_p*(a-a_p)*\delta f \quad (35)$$

As can be seen from the expressions (33), (34), and (35), $Msum$, $M2$, and Mp are proportional to the steering angle δf .

It should be noted that, from the expressions (28) and (31), the following magnitude relationship holds between a_sum and a_p .

$$0 < a_sum < a_p \quad (36)$$

FIG. 7 is a graph showing the relationships between the height a and $Msum/\delta f$, $M2/\delta f$, and $Mp/\delta f$ (indicated by the expressions (33), (34), and (35)).

Consideration will now be given to the relation between the setting value of the height a and the stability of the two-wheeled vehicle **1** at a standstill, with reference to FIG. 7.

First, the case is assumed where the height a coincides with a_{sum} determined by the expression (28) (the case where $a=a_{sum}$). In this case, the posture controlling manipulation moment M_{sum} obtained by the aforesaid expression (33) is always "0", irrespective of a change in front-wheel steering angle. Therefore, it is not possible to control, using M_{sum} , the motional state of the inverted pendulum mass point **123** (or the posture (inclination angle in the roll direction) of the vehicle body **2** of the two-wheeled vehicle **1**).

Next, the case is assumed where the height a is greater than a_{sum} and smaller than a_p , as shown by the following expression (37).

$$a_{sum} < a < a_p \quad (37)$$

In this case, as shown in FIG. 7, $M_{sum}/\delta f$ takes a negative value. Therefore, when the steering angle δf is positive, M_{sum} becomes negative; when the steering angle δf is negative, M_{sum} becomes positive.

Accordingly, it is theoretically possible to control the posture (inclination angle in the roll direction) of the vehicle body **2** of the two-wheeled vehicle **1** by manipulating the front-wheel steering angle. According to the experiments and studies conducted by the present inventors, however, it has been found that the following disadvantages arise in this case.

In the case where $a_{sum} < a < a_p$, as shown in FIG. 7, $M_2/\delta f$ and $M_p/\delta f$ differ in polarity from each other, and the absolute value of $M_2/\delta f$ is larger than the absolute value of $M_p/\delta f$.

Therefore, the posture controlling manipulation moment M_{sum} obtained by manipulating the front-wheel steering angle depends primarily on M_2 . Further, M_p functions to disturb the control of the posture of the vehicle body **2** of the two-wheeled vehicle **1** by M_{sum} generated in the same direction as M_2 (making the absolute value of M_{sum} decreased further than the absolute value of M_2).

This means that, in order to generate the posture controlling manipulation moment M_{sum} of the magnitude sufficient for controlling the posture of the vehicle body **2** of the two-wheeled vehicle **1**, the front-wheel steering angle will have to be manipulated more largely compared to the case where the assumption is made that M_p would not disturb the control of the posture of the vehicle body **2** (i.e. the case where $M_p=0$, or M_p and M_2 are in the same polarity).

That is, in the case where $a_{sum} < a < a_p$, when the posture (inclination angle in the roll direction) of the vehicle body **2** of the two-wheeled vehicle **1** deviates from a desired or required posture, in order to generate a restoring force for making the posture of the vehicle body **2** restored to the required posture (that can stabilize the inverted pendulum mass point **123**), it is necessary to considerably increase the absolute value of the feedback gain for changing the front-wheel steering angle in response to the change in inclination angle in the roll direction of the vehicle body **2** of the two-wheeled vehicle **1**.

Incidentally, in the case where the front-wheel steering angle is changed from the basic posture state of the two-wheeled vehicle **1** and, thus, the second mass point **124** is accelerated in the lateral direction of the two-wheeled vehicle **1**, the inertial force generated by the second mass point **124** by the acceleration is balanced with the friction force which acts on the two-wheeled vehicle **1** from the ground surface **110**.

The tires fitted to the front wheel **3f** and the rear wheel **3r** generally undergo shear deformation in the transverse direction due to the friction force received from the ground surface **110**. This generally causes a delay in response of the behavior of the second mass point **124** to the change in front-wheel steering angle and, hence, a delay in response of the change of the gravitational moment M_2 to the change in front-wheel steering angle.

Therefore, if the absolute value of the feedback gain for changing the front-wheel steering angle in response to the change in inclination angle of the vehicle body **2** of the two-wheeled vehicle **1** is set large, an oscillation phenomenon is likely to occur in the control system due to the delay in response of the change of the gravitational moment M_2 and the delay in response of the inclination angle in the roll direction of the vehicle body **2** of the two-wheeled vehicle **1** to the change in front-wheel steering angle. This leads to degradation in robustness of the control of the posture of the vehicle body **2** by the manipulation of the front-wheel steering angle.

As such, when the posture controlling manipulation moment M_{sum} becomes highly dependent on M_2 , an oscillation phenomenon becomes more likely to occur in the control system due to the effect of the delay in response of the change of M_2 attributable to the shear deformation of the tires fitted to the front wheel **3f** and the rear wheel **3r**. That is, in the case where $a_{sum} < a < a_p$, the oscillation phenomenon is likely to occur in the control system due to the effect of the delay in response of the change of M_2 caused by the shear deformation of the tires.

Further, in the case where $a_{sum} < a < a_p$, at the time when the absolute value of the steering angle δf is large, it is difficult to stabilize the control of the posture of the two-wheeled vehicle **1**, for the following reasons.

When the absolute value of the steering angle δf is large, the radius of curvature of the ground contact part of the steered wheel (front wheel **3f**) as seen in a cross section including the ground contact point of the steered wheel (front wheel **3f**) and having a normal corresponding to the X-axis direction (longitudinal direction of the vehicle body **2**) becomes greater than the radius of curvature in the case where the steering angle δf is "0". Accordingly, the substantial R_f becomes larger as the absolute value of the steering angle δf becomes larger. Further, M_p has dependency on R_f , as indicated by the aforesaid expression (27).

FIG. 8 illustrates differences in graphs of $M_p/\delta f$ due to the differences in magnitude of R_f . A straight line α_1 illustrates a graph of $M_p/\delta f$ in the case where R_f takes a standard value (radius of curvature of the transverse cross-sectional shape of the front wheel **3f** at the position of the ground contact point of the front wheel **3f** in the basic posture state). A straight line α_2 illustrates a graph of $M_p/\delta f$ in the case where R_f is larger than the standard value. Further, a_{p1} and a_{p2} denote the values of a_p (values of a when $M_p/\delta f$ is "0") corresponding respectively to the straight lines α_1 and α_2 .

As shown in FIG. 8, a_{p2} , i.e. the value of a_p when R_f is large, is larger than a_{p1} , i.e. the value of a_p when R_f is small. Further, the inclination of the straight line α_2 when R_f is large is greater than the inclination of the straight line α_1 when R_f is small.

Therefore, in the case where a takes a value satisfying $a_{sum} < a < a_p$, when R_f becomes larger, $M_p/\delta f$ increases in the positive direction (that is, it changes toward a direction of opposite polarity to that of $M_2/\delta f$). This causes $M_{sum}/\delta f$ to approach "0". Accordingly, the restoring force for making the posture of the vehicle body **2** of the two-wheeled vehicle **1** restored to a desired or required posture is decreased. Alternatively, the polarity of $M_{sum}/\delta f$ is reversed from negative to positive. This makes it difficult to stabilize the control of the posture of the vehicle body **2**.

As such, in the case where $a_{sum} < a < a_p$, when the absolute value of the steering angle δf is large, it is difficult to stabilize the control of the motional state of the inverted pendulum mass point **123** (and, hence, the control of the posture of the vehicle body **2** of the two-wheeled vehicle **1**)

because the substantial R_f deviates from the R_f (standard value) in the basic posture state.

Next, the case is assumed where the height a is not smaller than a_p , as shown by the following expression (38).

$$a \geq a_p \quad (38)$$

In this case, as shown in FIG. 7, $M_{sum}/\delta f$ takes a negative value. Therefore, when the steering angle δf is positive, M_{sum} becomes negative; when the steering angle δf is negative, M_{sum} becomes positive, as in the case where $a_{sum} < a < a_p$.

Accordingly, it is theoretically possible to control the motional state of the inverted pendulum mass point **123** by manipulating the front-wheel steering angle. Consequently, it is possible to control the posture (inclination angle in the roll direction) of the vehicle body **2** of the two-wheeled vehicle **1** by the manipulation of the front-wheel steering angle.

Further, in this case, $M_2/\delta f$ and $M_p/\delta f$ will not become opposite in polarity. That is, in the case where $a = a_p$, $M_p/\delta f = 0$ and $M_2/\delta f < 0$. In the case where $a > a_p$, $M_2/\delta f$ and $M_p/\delta f$ are in the same polarity. Therefore, it is possible to generate the posture controlling manipulation moment M_{sum} by M_2 alone, or by cooperation of M_2 and M_p .

Accordingly, the absolute value of the feedback gain for the posture control of the vehicle body **2** can be set to a value smaller than in the case where $a_{sum} < a < a_p$.

However, since the absolute value of $M_2/\delta f$ is larger than the absolute value of $M_p/\delta f$, as shown in FIG. 7, M_{sum} is highly dependent on M_2 . Further, since the height a is large, the lateral acceleration (acceleration in the Y-axis direction) of the second mass point **124** tends to become large.

Therefore, the effect of the shear deformation of the tires fitted to the front wheel **3f** and the rear wheel **3r** becomes large, as in the case where $a_{sum} < a < a_p$. The response of the change of the gravitational moment M_2 to the change of the front-wheel steering angle is likely to delay, and accordingly, an oscillation phenomenon is likely to occur in the control system.

Next, the value of a which makes the following expression (39) hold is denoted as a_s .

$$M_{sum} = -M_2 \quad (39)$$

The state where the above expression (39) holds corresponds to the state where M_2 functions to disturb the control of the posture of the vehicle body **2** of the two-wheeled vehicle **1** by M_{sum} (i.e. the direction of M_2 becomes opposite to the direction of M_{sum}) and where the absolute values of M_2 and M_{sum} are equal to each other.

From the expressions (25) and (27), the above a_s is expressed by the following expression (40).

$$a_s = ((h + I/(m \cdot h)) / (Rg + 2 \cdot I/(m \cdot h))) \cdot R_f \quad (40)$$

From the fact that all the parameters on the right side of the expression (40) are positive and from the aforesaid expressions (28) and (40), the relationship in the following expression (41) is obtained.

$$0 < a_s < a_{sum} \quad (41)$$

Next, the case is assumed where the height a is larger than a_s and smaller than a_{sum} , as shown by the following expression (42).

$$a_s < a < a_{sum} \quad (42)$$

In this case, $M_{sum}/\delta f$ ($=M_p/\delta f + M_2/\delta f$) takes a positive value. In other words, $M_p/\delta f > -M_2/\delta f$.

Therefore, when the steering angle δf is positive, the posture controlling manipulation moment M_{sum} becomes positive; when the steering angle δf is negative, the posture con-

trolling manipulation moment M_{sum} becomes negative. Accordingly, it is theoretically possible to control the motional state of the inverted pendulum mass point **123** by manipulating the front-wheel steering angle. Consequently, it is possible to control the posture (inclination angle in the direction about the X axis) of the vehicle body **2** of the two-wheeled vehicle **1** by the manipulation of the front-wheel steering angle.

In the case where $a_s < a < a_{sum}$, the absolute value of M_2 becomes smaller than in the case where $a > a_{sum}$. Consequently, the oscillation in the control of the posture of the vehicle body **2** resulting from the shear deformation of the tires of the front wheel **3f** and the rear wheel **3r** is restricted. However, compared to the case where $0 < a \leq a_s$ which will be described later, oscillation is still likely to occur in the control of the posture of the vehicle body **2** due to the shear deformation of the tires of the front wheel **3f** and the rear wheel **3r**, for the following reasons.

In the case where a takes a value satisfying the expression (42), $M_{sum}/\delta f$ and $M_2/\delta f$ are opposite in polarity, as shown in FIG. 7. That is, M_2 functions to disturb the control of the posture of the vehicle body **2** by M_{sum} . In addition, as explained above, M_2 is accompanied by lateral acceleration due to the movement of the second mass point **124**, causing shear deformation of the tires of the front wheel **3f** and the rear wheel **3r**. Consequently, an oscillation phenomenon is likely to occur in the control system because of the delay in response resulting from the shear deformation.

Further, when a takes a value satisfying the expression (42), the absolute value of $M_{sum}/\delta f$ is smaller than the absolute value of $M_2/\delta f$. That is, the absolute value of the posture controlling manipulation moment M_{sum} becomes smaller than the absolute value of M_2 which disturbs the posture control of the vehicle body **2** and causes an oscillation phenomenon in the control system. Therefore, when the absolute value of the feedback gain is set to a relatively small value so as to avoid the oscillation phenomenon in the control system, the magnitude of the posture controlling manipulation moment M_{sum} is likely to become insufficient.

Next, the case is assumed where the height a is larger than "0" and not larger than a_s , as shown by the following expression (43).

$$0 < a \leq a_s \quad (43)$$

In this case, $M_{sum}/\delta f$ becomes positive, as shown in FIG. 7. Therefore, M_{sum} becomes positive when the steering angle δf is positive, while M_{sum} becomes negative when the steering angle δf is negative.

Further, in this case, $M_{sum}/\delta f$ and $M_2/\delta f$ are opposite in polarity, as in the case where $a_s < a < a_{sum}$. That is, M_2 functions to disturb the control of the posture of the vehicle body **2** by M_{sum} .

However, when a takes a value satisfying the expression (43), the absolute value of $M_{sum}/\delta f$ becomes equal to or larger than the absolute value of $M_2/\delta f$. In other words, $M_{sum}/\delta f \geq -M_2/\delta f$. That is, the absolute value of M_2 which disturbs the posture control of the vehicle body **2** and causes the oscillation phenomenon in the control system is kept at or below the absolute value of the posture controlling manipulation moment M_{sum} .

Accordingly, even if the absolute value of the feedback gain is set to a relatively large value in order to cause a sufficiently large posture controlling manipulation moment M_{sum} to be generated for making the posture (inclination angle in the roll direction) of the vehicle body **2** restored to a required posture, oscillation is not likely to occur in the control system. That is, it is possible to enhance the stability of the

control of the motional state of the inverted pendulum mass point 123 by the manipulation of the front-wheel steering angle (and, hence, the stability of the posture control of the vehicle body 2 of the two-wheeled vehicle 1).

Next, the case is assumed where the height a is "0" (in the case where $a=0$).

In this case, as shown in FIG. 7, $M_{sum}/\delta f$ becomes positive. Thus, M_{sum} becomes positive when the steering angle δf is positive, while M_{sum} becomes negative when the steering angle δf is negative.

Further, in this case, M_2 is always "0". Therefore, the posture controlling manipulation moment M_{sum} caused by the manipulation of the front-wheel steering angle is generated by M_p alone. In this case, even if the front-wheel steering angle is manipulated from the basic posture state, the movement amount in the Y-axis direction of the second mass point 124 is "0". Accordingly, no friction force is generated to act on the two-wheeled vehicle 1 from the ground surface 110.

Therefore, the tires of the front wheel 3f and the rear wheel 3r do not undergo shear deformation, and thus, an oscillation phenomenon in the control system due to the shear deformation of the tires is unlikely to occur. Accordingly, it is possible to further increase the absolute value of the aforesaid feedback gain, than in the case where the value of a satisfies the aforesaid expression (43). As a result, the restoring force for making the motional state of the inverted pendulum mass point 123 restored to the required state can be increased. Further, the stability of the control of the motional state can be enhanced. Consequently, the restoring force for making the posture of the vehicle body 2 restored to the required posture can be increased. Furthermore, the stability of the control of the posture can be enhanced.

Further, the magnitude of M_{sum} which can be generated per unit change amount of the front-wheel steering angle becomes larger than in the case where the value of a satisfies the aforesaid expression (43). Accordingly, it is also possible to decrease the magnitude of the change amount of the front-wheel steering angle that is necessary for making the posture of the vehicle body 2 restored to the required posture.

Next, the case is assumed where the height a is negative (in the case where $a<0$).

In this case, as shown in FIG. 7, $M_{sum}/\delta f$ becomes positive. Thus, the posture controlling manipulation moment M_{sum} becomes positive when the steering angle δf is positive, while the posture controlling manipulation moment M_{sum} becomes negative when the steering angle δf is negative.

Further, in this case, $M_2/\delta f$ and $M_p/\delta f$ are in the same polarity. This enables M_2 and M_p to cooperate to generate the posture controlling manipulation moment M_{sum} . As a result, the magnitude of M_{sum} that can be generated per unit change amount of the front-wheel steering angle becomes larger than in the case where $a=0$. Accordingly, it is possible to still further decrease the magnitude of the change amount of the front-wheel steering angle necessary for making the posture of the vehicle body 2 restored to the required posture.

It can be said from the foregoing that, in the case of attempting to control the posture (inclination angle in the roll direction) of the vehicle body 2 of the two-wheeled vehicle 1 to a required posture by steering of the front wheel 3f of the two-wheeled vehicle 1 (in the case of attempting to control the motional state of the inverted pendulum mass point 123 in the dynamics model of the two-wheeled vehicle 1), setting the arrangement position of the backwardly tilted steering axis C_{sf} of the front wheel 3f (steered wheel) such that the height a of the intersection point E_f of the steering axis C_{sf} and the straight line connecting the center of the axle of the front

wheel 3f (steered wheel) and the ground contact point of the front wheel 3f becomes smaller than a_{sum} defined by the expression (28) is a preferable condition for stably controlling the motional state of the inverted pendulum mass point 123 (and, hence, the posture of the vehicle body 2).

In the case where the arrangement position of the steering axis C_{sf} is set as described above, $M_{sum}/\delta f$ becomes positive, as shown in FIG. 7. Therefore, the polarity of the posture controlling manipulation moment M_{sum} generated by the steering of the front wheel 3f agrees with the polarity of the steering angle δf . Accordingly, in the case where the vehicle body 2 leans to the left from the basic posture state as seen from the back of the two-wheeled vehicle 1, the posture controlling manipulation moment M_{sum} in the direction of making the inclination in the roll direction of the vehicle body 2 restored to the basic posture state can be generated by steering the front wheel 3f counterclockwise as seen from the above (so that the front end of the front wheel 3f turns toward the left).

On the contrary to the above, in the case where the vehicle body 2 leans to the right from the basic posture state, the posture controlling manipulation moment M_{sum} in the direction of making the inclination in the roll direction of the vehicle body 2 restored to the basic posture state can be generated by steering the front wheel 3f clockwise as seen from the above (so that the front end of the front wheel 3f turns toward the right).

The direction of steering of the front wheel 3f so as to generate the posture controlling manipulation moment M_{sum} as described above agrees with the direction of steering of the front wheel 3f by the self-steering function in the case where the vehicle body 2 leans in the roll direction while the two-wheeled vehicle 1 is traveling at a relatively high vehicle speed.

Therefore, from the standstill state to the high-speed traveling state of the two-wheeled vehicle 1, the polarity of the steering direction of the front wheel 3f with respect to the inclination in the roll direction of the vehicle body 2 remains the same, so that the rider can readily operate the two-wheeled vehicle 1.

Further, in order to suppress the oscillation phenomenon in the control system due to the tire shear deformation, it is preferable to set the arrangement position of the steering axis C_{sf} such that the height a becomes not larger than a_s defined by the expression (40).

Moreover, for still further decreasing the magnitude of the change amount of the front-wheel steering angle necessary for making the posture of the vehicle body 2 restored to the required posture, it is preferable to set the arrangement position of the steering axis C_{sf} such that the height a becomes "0" or takes a negative value.

As such, in order to make the posture of the vehicle body 2 stably restored to a required posture, it is preferable that the height a takes a value smaller than a_{sum} , including zero or a negative value. Further, the sensitivity of the change of the posture controlling manipulation moment M_{sum} to the change in front-wheel steering angle can be made higher as the height a becomes smaller.

Here, the relationship between the height a and the trail t is expressed by the aforesaid expression (10). Thus, the height a being smaller than a_{sum} means that the trail t is smaller than $a_{sum} \cdot \tan(\theta_{cf})$, the height a being not larger than a_s means that the trail t is not larger than $a_s \cdot \tan(\theta_{cf})$, and the height a being not larger than "0" means that the trail t is not larger than "0".

Therefore, in order to make the posture of the vehicle body 2 stably restored to the required posture, the arrangement

position of the steering axis C_{sf} may be set such that the trail t of the two-wheeled vehicle **1** takes a value smaller than $a_{\text{sum}} \cdot \tan(\theta_{cf})$ (suitably, a value not larger than $a_s \cdot \tan(\theta_{cf})$, or a negative value).

As described above, in the case of controlling the posture in the roll direction of the vehicle body **2** of the two-wheeled vehicle **1** by steering the front wheel **3f**, the dynamic behavior of the two-wheeled vehicle **1** can be approximately expressed by the dynamic behavior of the aforesaid equivalent two-mass-point system. In this case, controlling the front-wheel steering angle so as to stabilize the motional state of the first mass point (inverted pendulum mass point) **123** of the equivalent two-mass-point system can stabilize the posture of the vehicle body **2** of the two-wheeled vehicle **1**.

In the case of controlling the posture in the roll direction of the vehicle body **2** of the two-wheeled vehicle **1** by steering the front wheel **3f** while the two-wheeled vehicle **1** is stopped or traveling at a vehicle speed in a low-speed range, it is preferable that the height a is smaller than a_{sum} , or, in other words, that the trail t takes a value smaller than $a_{\text{sum}} \cdot \tan(\theta_{cf})$ (for example, a negative value).

In order to improve the operation stability of the two-wheeled vehicle **1** while the vehicle is traveling at a vehicle speed in a high-speed range, however, it is preferable that the trail t takes a positive value, or, that the point of intersection of the ground surface **110** and the steering axis C_{sf} of the front wheel **3f** in the basis posture state lies in front of the ground contact point of the front wheel **3f**.

Incidentally, it can be considered that it is practically impossible in the two-wheeled vehicle **1** that the center-of-gravity height h becomes equal to or smaller than R_g defined by the aforesaid expression (25a).

Even assuming that the center-of-gravity height h is R_g or smaller, in this case, the two-wheeled vehicle **1** becomes dynamically stable in the basic posture state, without the need of posture control by steering of the front wheel **3f**. Therefore, in discussing the stability of the posture control of the vehicle body **2** by way of steering, it is only necessary to consider the case where the center-of-gravity height h is larger than R_g .

In this case, the value of $((h+I/(m \cdot h))/(R_g+I/(m \cdot h)))$ in the two-wheeled vehicle **1** becomes larger than 1, so that the right side of the expression (28) becomes larger than R_f . That is, as long as h is larger than R_g , the value of a_{sum} determined by the expression (28) becomes always larger than R_f with respect to arbitrary h , I , and m .

On the other hand, when the height a is smaller than a_{sum} , $M_p/\delta f$ becomes positive, $M_p/\delta f > (-M_2/\delta f)$, and $M_{\text{sum}}/\delta f$ becomes positive, as explained above.

From the above, when a is set to R_f or lower, as long as h is larger than R_g , $M_p/\delta f$ becomes positive, $M_p/\delta f > (-M_2/\delta f)$, and $M_{\text{sum}}/\delta f$ becomes positive with respect to arbitrary h , I , and m .

That is, when a is set to R_f or lower, even in the case where the values of h , I , and m have not been calculated at the planning phase, or the values of h , I , and m have not been measured, or even in the case where the values of h , I , and m may vary because a given object may be mounted on or attached to the two-wheeled vehicle **1**, $M_p/\delta f$ becomes always positive, $M_p/\delta f$ becomes always greater than $(-M_2/\delta f)$, and $M_{\text{sum}}/\delta f$ becomes always positive, as long as h is larger than R_g . Accordingly, it is possible to cause the posture controlling manipulation moment M_{sum} for making the posture (inclination angle in the roll direction) of the vehicle body **2** restored to a required posture to be generated in an appropriate direction, independently of the values of h , I , and m .

Accordingly, for controlling the posture in the roll direction of the vehicle body **2** by steering of the front wheel **3f**, the height a may be set to R_f or smaller, instead of being set to a value smaller than a_{sum} . In other words, the trail t may be set to $R_f \cdot \tan(\theta_{cf})$ or smaller.

Further preferably, the height a may be set to 0 or smaller, instead of R_f or smaller. In other words, the trail t may be set to 0 or smaller.

Supplementally, in the dynamics model of the two-wheeled vehicle **1** described above, the mass and the inertia moment (inertia) were concentrated on the vehicle body **2**. In the model, the gravitational force which acts on a steering mobile section made up of the front wheel **3f** and the front-wheel support mechanism **4**, and the inertial force of the steering mobile section which is generated when the steering mobile section makes a motion relative to the vehicle body **2** in accordance with the steering of the front wheel **3f** were both ignored.

Alternatively, the two-wheeled vehicle **1** may be modeled by further taking into account the gravitational force which acts on the steering mobile section made up of the front wheel **3f** and the front-wheel support mechanism **4** as well as the inertial force of the steering mobile section which is generated when the steering mobile section makes a motion relative to the vehicle body **2**.

In this case as well, the two-wheeled vehicle **1** can be equivalently transformed to a model having the structure similar to that shown in FIG. 2 (model made up of a first mass point which is an inverted pendulum mass point and a second mass point which is a ground surface mass point).

That is, even in the case where at least one of a mass point and an inertia moment is set for the steering mobile section made up of the front wheel **3f** and the front-wheel support mechanism **4** in addition to the mass point and the inertia moment set for the vehicle body **2**, it is possible to equivalently transform the dynamic behavior of the two-wheeled vehicle **1** to the behavior of a system which is made up of a mass point (inverted pendulum mass point) that moves in accordance with the inclination angle in the roll direction of the vehicle body **2** and the steering angle of the front wheel **3f**, and a mass point (ground surface mass point) that moves on the ground surface **110** in accordance with the steering angle of the front wheel **3f**, independently of the inclination angle in the roll direction of the vehicle body **2**.

The above has described the fundamental technical matters related to the present embodiment.

An embodiment of the present invention will be described in detail below on the premise of the above-described matters. In the description of the present embodiment, for convenience sake, the components having the same functions as those of the two-wheeled vehicle **1** shown in FIG. 1 will be denoted by the same reference signs as those used in FIG. 1.

Referring to FIG. 9, a mobile vehicle **1A** according to the present embodiment is a two-wheeled vehicle which has a vehicle body **2**, and a front wheel **3f** and a rear wheel **3r** arranged spaced apart from each other in the longitudinal direction of the vehicle body **2**. The mobile vehicle **1A** will be hereinafter referred to as "two-wheeled vehicle **1A**".

On the upper surface of the vehicle body **2**, a seat **6** is provided for a rider to sit astride.

At the front portion of the vehicle body **2**, a front-wheel support mechanism **4** for axially supporting the front wheel **3f**, an operation apparatus **7** for a rider who has sat on the seat **6** to hold, and an actuator **8** (hereinafter, also referred to as "steering actuator **8**") which generates a steering force for steering the front wheel **3f** are mounted.

The front-wheel support mechanism **4** includes a trail adjustment mechanism **9**, which is a mechanism for making the trail t of the front wheel $3f$ adjustable, and a front fork **10** which includes a suspension mechanism such as a damper. At a lower end of the front fork **10**, the front wheel $3f$ is axially supported, via bearings or the like, such that it can rotate about the axle centerline C_f (rotational axis of the front wheel $3f$) that extends in the direction orthogonal to the diameter direction of the front wheel $3f$.

The trail adjustment mechanism **9** is configured as shown in FIGS. **10** and **11**.

Specifically, the trail adjustment mechanism **9** includes a frame-shaped steering rotation section **12**, which is rotatably supported by a head pipe **11** provided at the front end of the vehicle body **2**, a frame-shaped swing section **14**, which is swingably attached to the steering rotation section **12** via a hinge mechanism **13**, an actuator **15** (hereinafter, also referred to as "trail adjustment actuator **15**"), which generates a driving force for causing the swing section **14** to swing, and a crank mechanism **16**, which causes the swing section **14** to swing with respect to the steering rotation section **12** by the driving force of the actuator **15**.

The head pipe **11** has its shaft center corresponding to the steering axis C_{sf} of the front wheel $3f$. The head pipe **11** is fixedly secured to the front end of the vehicle body **2** such that the steering axis C_{sf} is tilted backward. The steering rotation section **12** is arranged such that the head pipe **11** is placed between an upper end portion and a lower end portion of the steering rotation section **12**. The steering rotation section **12** is fitted to the head pipe **11** so as to be able to rotate about the steering axis C_{sf} relative to the head pipe **11**.

It should be noted that, as the steering axis C_{sf} is tilted backward, the front wheel $3f$ has a positive caster angle θ cf.

The swing section **14** is arranged in front of the steering rotation section **12**. The swing section **14** has its upper end portion connected to the upper end portion of the steering rotation section **12** via the hinge mechanism **13**. The front fork **10** extends downward from the lower end portion of the swing section **14**.

With this configuration, the swing section **14** is rotatable about the steering axis C_{sf} in an integrated manner with the steering rotation section **12**, together with the front fork **10** and the front wheel $3f$. The swing section **14** is also swingable, relative to the steering rotation section **12**, in the direction about the center of the rotational axis of the hinge mechanism **13**. In this case, the center of the rotational axis of the hinge mechanism **13** (central axis of swing of the swing section **14**) extends in the lateral direction (vehicle width direction) of the vehicle body **2**. Accordingly, the swing section **14** swings in the pitching direction with respect to the steering rotation section **12** in the basic posture state of the two-wheeled vehicle **1A**.

It should be noted that the basic posture state of the two-wheeled vehicle **1A** is, as with the basic posture state of the two-wheeled vehicle **1** in FIG. **1**, the state where the front wheel $3f$ and the rear wheel $3r$ are both stationary in the upright posture in contact with the ground surface **110** and the axle centerlines (centers of the rotational axes) C_f and C_r of the front wheel $3f$ and the rear wheel $3r$ extend in parallel with each other in the direction orthogonal to the longitudinal direction of the vehicle body **2**.

The trail adjustment actuator **15** is made up of an electric motor mounted to the swing section **14**. The trail adjustment actuator **15** outputs a rotative driving force via a speed reducer **17**. More specifically, in the example of the present embodiment, the trail adjustment actuator **15** and the speed reducer **17** are arranged inside the swing section **14**, at an upper

portion and a lower portion, respectively, therein. The housings of the trail adjustment actuator **15** and the speed reducer **17** are each fixedly secured to the swing section **14**. It should be noted that the speed reducer **17** may have an arbitrary structure; it may be, for example, Harmonic Drive (registered trademark), or a structure comprising a plurality of gears.

The trail adjustment actuator **15** has its output shaft connected to the input shaft of the speed reducer **17** via a power transmission mechanism **18** which is formed by a pulley-belt mechanism or the like. With this configuration, the rotative driving force generated by the trail adjustment actuator **15** is input from the output shaft of the actuator **15** via the power transmission mechanism **18** to the speed reducer **17**, and it is further output from the speed reducer **17**.

Further, in the present embodiment, the trail adjustment actuator **15** has an electric lock mechanism **15a** built therein. The lock mechanism **15a** holds the output shaft of the actuator **15** in a non-rotatable state. The lock mechanism **15a** is formed by a friction brake mechanism or the like.

It should be noted that the power transmission mechanism **18** may be configured to have the function as a speed reducer, in which case the speed reducer **17** can be omitted. Alternatively, the output shaft of the trail adjustment actuator **15** and the input shaft of the speed reducer **17** may be coupled in a coaxial manner, so that the rotative driving force of the trail adjustment actuator **15** is input directly to the speed reducer **17**.

Further, the trail adjustment actuator **15** may be made up of a hydraulic actuator.

The crank mechanism **16** includes a pair of crank arms **19a** and **19b**, arranged to rotate in an integrated manner with the output shaft of the speed reducer **17**, and a connecting rod **20** which connects the crank arms **19a** and **19b** to the steering rotation section **12**.

The crank arms **19a** and **19b** are arranged inside the swing section **14** such that they face each other, with spacing therebetween, in the axis direction of the output shaft of the speed reducer **17**.

One crank arm **19a** has a portion near its one end fixedly secured to the output shaft of the speed reducer **17**, so that it can rotate in an integrated manner with the output shaft.

The other crank arm **19b** has, at a portion near its one end, a spindle **21** which is secured concentrically with the output shaft of the speed reducer **17**. Via this spindle **21**, the crank arm **19b** is axially supported in a rotatable manner by a bearing **22** fixedly secured to the swing section **14**.

These crank arms **19a** and **19b** have their other ends connected to each other via an eccentric shaft **23** which is eccentric from the shaft center of the output shaft of the speed reducer **17** (=axes of rotation of the crank arms **19a** and **19b**). The connecting rod **20** has its one end arranged between the crank arms **19a** and **19b** and axially supported in a rotatable manner by the eccentric shaft **23**. The other end of the connecting rod **20** is axially supported, inside the steering rotation section **12**, in a rotatable manner by a spindle **24** which is fixedly secured to the steering rotation section **12**. The axis direction of the spindle **24** is parallel to the shaft center of the eccentric shaft **23**.

The trail adjustment mechanism **9** is configured as described above. Therefore, as the steering rotation section **12** and swing section **14** of the trail adjustment mechanism **9** are caused to rotate about the steering axis C_{sf} , the front wheel $3f$ is steered about the steering axis C_{sf} .

Furthermore, as the crank arms **19a** and **19b** are caused to rotate about the shaft center of the output shaft of the speed reducer **17** by the rotative driving force of the trail adjustment actuator **15**, the swing section **14** swings about the center of

the rotational axis of the hinge mechanism **13**, relative to the steering rotation section **12**, within a prescribed angle range. As the swing section **14** swings, the front wheel **3f** also swings about the center of the rotational axis of the hinge mechanism **13**. This makes the front wheel **3f** displaced in the longitudinal direction with respect to the vehicle body **2**. Consequently, the ground contact point of the front wheel **3f** is displaced in the longitudinal direction, within a prescribed range, with respect to the point of intersection of the steering axis C_{sf} and the ground surface **110**. This results in a change of the trail t within a prescribed range.

In this case, with the swinging of the swing section **14**, the front wheel **3f** can be displaced in the longitudinal direction between, for example, the state indicated by the solid line in FIG. **9** and the state indicated by the two-dot chain line. In FIG. **9**, the state of displacement of the front wheel **3f** indicated by the solid line corresponds to the state where the trail t takes a negative value t_n . The state of displacement of the front wheel **3f** indicated by the two-dot chain line corresponds to the state where the trail t takes a positive value t_p . Accordingly, the trail t can be changed within the range between the lower limit t_n (<0) and the upper limit t_p (>0).

Hereinafter, the above-described lower limit t_n will be referred to as “lower trail limit t_n ”, and the above-described upper limit t_p will be referred to as “upper trail limit t_p ”. Further, the state of displacement of the front wheel **3f** when the trail t is t_n (state of displacement of the front wheel **3f** shown by the solid line in FIG. **9**) will be referred to as “lower trail limit state”, and the state of displacement of the front wheel **3f** when the trail t is t_p (state shown by the two-dot chain line in FIG. **9**) will be referred to as “upper trail limit state”.

Supplementally, the lower trail limit state is, in other words, the state where the height a of the intersection point E_f of the steering axis C_{sf} and the straight line connecting the ground contact point and the axle center point of the front wheel **3f** takes a negative value (the state where the intersection point E_f lies below the ground surface **110**) in the basis posture state of the two-wheeled vehicle **1A**. Further, the upper trail limit state is, in other words, the state where the above-described height a takes a positive value (the state where the intersection point E_f lies above the ground surface **110**) in the basic posture state of the two-wheeled vehicle **1A**.

Further, in the present embodiment, the aforesaid lock mechanism **15a** mechanically holds the output shaft of the trail adjustment actuator **15** non-rotatable, so that the swing section **14** is held in a non-swingable state with respect to the steering rotation section **12**. This enables the trail t to be mechanically fixedly secured (locked), without the need to control the driving force of the trail adjustment actuator **15**.

In the present embodiment, the trail adjustment actuator **15** is provided with the lock mechanism **15a**. Alternatively, instead of the lock mechanism **15a**, a lock mechanism which holds the output shaft of the speed reducer **17** or the crank arms **19a** and **19b** non-rotatable, for example, may be provided on the output side of the speed reducer **17**.

The aforesaid steering actuator **8** generates, as a steering force for performing the steering of the front wheel **3f**, a rotative driving force to cause the front wheel **3f** to rotate about the steering axis C_{sf} . In the present embodiment, this steering actuator **8** is made up of an electric motor. The steering actuator **8** has its housing fixedly secured to the vehicle body **2**. Further, the output shaft of the steering actuator **8** is connected to the lower end portion of the steering rotation section **12** via a power transmission mechanism **25** which is formed by a pulley-belt mechanism or the like. With this configuration, the rotative driving force about the steering

axis C_{sf} is applied from the steering actuator **8** via the power transmission mechanism **25** to the steering rotation section **12**. It should be noted that the power transmission mechanism **25** also has a speed reducing function.

As the rotative driving force is applied from the steering actuator **8** to the steering rotation section **12**, the front-wheel support mechanism **4** including the trail adjustment mechanism **9** and the front fork **10** is rotatively driven about the steering axis C_{sf} together with the front wheel **3f**. As a result, the front wheel **3f** is steered by the rotative driving force of the steering actuator **8**.

Further, in the present embodiment, a steering clutch **8a**, which is a clutch mechanism for interrupting the power transmission between the steering actuator **8** and the steering rotation section **12** as appropriate, is built in the power transmission mechanism **25**. This steering clutch **8a** is made up, for example, of an electromagnetic clutch.

It should be noted that the steering actuator **8** is not limited to the electric motor; it may be made up, for example, of a hydraulic actuator.

The operation apparatus **7** is mounted to the trail adjustment mechanism **9**. In the present embodiment, the operation apparatus **7** is fixedly secured to the upper end portion of the steering rotation section **12** of the trail adjustment mechanism **9** via a support strut **26**, such that the operation apparatus **7** rotates about the steering axis C_{sf} in an integrated manner with the steering rotation section **12**. Although not shown in detail in the figure, this operation apparatus **7** is equipped with an accelerator grip, brake lever, turn signal switch, and so on, as with the handlebar of a conventional motorcycle.

An actuator **27** for rotatively driving the front wheel **3f** about its axle centerline C_f is attached to the axle of the front wheel **3f**. The actuator **27** has a function as a power engine which generates a thrust force for the two-wheeled vehicle **1A**. In the present embodiment, this actuator **27** (hereinafter, also referred to as “travel-assist actuator **27**”) is made up of an electric motor (with a speed reducer).

It should be noted that the travel-assist actuator **27** may be made up of a hydraulic actuator, for example, instead of the electric motor. Alternatively, the travel-assist actuator **27** may be made up of an internal combustion engine. Furthermore, the travel-assist actuator **27** may be attached to the vehicle body **2** at a position apart from the axle of the front wheel **3f**, and the travel-assist actuator **27** and the axle of the front wheel **3f** may be connected by an appropriate power transmission device.

Further, instead of, or in addition to, the travel-assist actuator **27**, an actuator for rotatively driving the rear wheel **3r** may be provided.

At the rear portion of the vehicle body **2**, a rear-wheel support mechanism **5** for axially supporting the rear wheel **3r** in a rotatable manner is mounted. The rear-wheel support mechanism **5** includes a swing arm **28**, and a suspension mechanism **29** including a coil spring, damper, and so on. These mechanical structures are similar to those in the rear-wheel support mechanism in a conventional motorcycle, for example.

At one end of the swing arm **28** (at its end on the rear side of the vehicle body **2**), the rear wheel **3r** is axially supported, via bearings or the like, such that it can rotate about the axle centerline C_r (center of the rotational axis of the rear wheel **3r**) that extends in the direction orthogonal to the diameter direction of the rear wheel **3r** (in the direction perpendicular to the paper plane of FIG. **9**). It should be noted that the rear wheel **3r** is a non-steered wheel.

Besides the above-described mechanical configuration, the two-wheeled vehicle **1A** includes, as shown in FIG. **12**, a

control device **50** which carries out control processing for controlling the operations of the aforesaid steering actuator **8**, steering clutch **8a**, trail adjustment actuator **15**, lock mechanism **15a**, and travel-assist actuator **27**.

The two-wheeled vehicle **1A** further includes, as sensors for detecting various kinds of state quantities necessary for the control processing in the control device **50**, a vehicle-body inclination detector **51** for detecting an inclination angle ϕ_b in the roll direction of the vehicle body **2**, a front-wheel steering angle detector **52** for detecting a steering angle δf (angle of rotation about the steering axis C_{sf}) of the front wheel **3f**, a trail detector **53** for detecting a trail, a front-wheel rotational speed detector **54** for detecting a rotational speed (angular velocity) of the front wheel **3f**, a rear-wheel rotational speed detector **55** for detecting a rotational speed (angular velocity) of the rear wheel **3r**, and an accelerator manipulation detector **56** which outputs a detection signal corresponding to the accelerator manipulated variable which is the manipulated variable (rotational amount) of the accelerator grip of the operation apparatus **7**.

It should be noted that the steering angle δf of the front wheel **3f** more specifically means the rotational angle of the front wheel **3f** from the steering angle (neutral steering angle) in its non-steered state (the state in which the direction of the axle centerline C_f of the front wheel **3f** corresponds to the direction orthogonal to the longitudinal direction of the vehicle body **2** (or, direction parallel to the Y axis)). Therefore, the steering angle δf of the front wheel **3f** in the non-steered state is "0". The positive rotational direction of the steering angle δf of the front wheel **3f** corresponds to the direction of rotation that makes the front end of the front wheel **3f** turn left with respect to the vehicle body **2** (in other words, the direction in which the front wheel **3f** turns counterclockwise about the steering axis C_{sf} as the two-wheeled vehicle **1A** is seen from above), as in the case of the two-wheeled vehicle **1** shown in FIG. **1**.

Further, the two-wheeled vehicle **1A** includes an operation switch **57** (hereinafter, referred to as "balance-on switch **57**") which instructs the control device **50** to control the posture in the roll direction of the vehicle body **2**, an operation switch **58** (hereinafter, referred to as "balance-off switch **58**") which instructs the control device **50** to release the posture control, and an operation switch **59** (hereinafter, referred to as "travel-assist switch **59**") which instructs the control device **50** to start assisted traveling of the two-wheeled vehicle **1A** (traveling by the driving force of the travel-assist actuator **27**).

The control device **50**, which is an electronic circuit unit made up of a CPU, RAM, ROM, interface circuit and so on, is mounted on the vehicle body **2**. This control device **50** is configured to receive outputs (detection signals) from the above-described detectors **51** to **56** and outputs from the switches **57** to **59** (signals indicating the operational states of the switches **57** to **59**).

The control device **50** may include a plurality of CPUs or processors. Further, the control device **50** may be made up of a plurality of mutually communicable electronic circuit units.

The vehicle-body inclination detector **51**, which is made up of an acceleration sensor and a gyro sensor (angular velocity sensor), for example, is mounted on the vehicle body **2**. In this case, the control device **50** carries out arithmetic processing on the basis of the outputs of the acceleration sensor and the gyro sensor, to measure the inclination angle in the roll direction (more specifically, the inclination angle in the roll direction with respect to the vertical direction (direction of gravitational force)) of the vehicle body **2**. For this measurement, the technique proposed by the present applicant in Japanese Patent No. 4181113, for example, may be adopted.

The front-wheel steering angle detector **52** is made up, for example, of a rotary encoder or other detector attached to the steering actuator **8** (electric motor) (the detector outputting a detection signal responsive to the rotational angle or rotational angular velocity of the output shaft of the steering actuator **8**). Alternatively, the front-wheel steering angle detector **52** may be made up of a rotary encoder attached to the aforesaid power transmission mechanism **25** or steering rotation section **12** on the aforesaid steering axis C_{sf} (the detector outputting a detection signal responsive to the rotational angle or rotational angular velocity of the steering rotation section **12**).

The trail detector **53** is made up, for example, of a rotary encoder or other detector attached to the aforesaid trail adjustment actuator **15** (electric motor) (the detector outputting a detection signal responsive to the rotational angle or rotational angular velocity of the output shaft of the trail adjustment actuator **15**).

Here, in the present embodiment, the trail t is defined in accordance with the amount of swing of the swing section **14** (angle of rotation about the center of rotational axis of the hinge mechanism **13**) relative to the steering rotation section **12** of the trail adjustment mechanism **9**. The amount of swing of the swing section **14** is defined in accordance with the angles of rotation of the crank arms **19a** and **19b**. Further, the angles of rotation of the crank arms **19a** and **19b** are defined in accordance with the angle of rotation of the output shaft of the trail adjustment actuator **15**. Accordingly, the trail t can be detected from an output of the rotary encoder or other detector attached to the trail adjustment actuator **15**.

It should be noted that the trail detector **53** may be made up, for example, of a rotary encoder or other detector attached to the aforesaid speed reducer **17** (the detector outputting a detection signal responsive to the rotational angle or rotational angular velocity of the output shaft of the speed reducer **17**).

The front-wheel rotational speed detector **54** is made up, for example, of a rotary encoder or other detector attached to the axle of the front wheel **3f** (the detector outputting a detection signal responsive to the rotational angle or rotational angular velocity of the front wheel **3f**).

The rear-wheel rotational speed detector **55** is made up, for example, of a rotary encoder or other detector attached to the axle of the rear wheel **3r** (the detector outputting a detection signal responsive to the rotational angle or rotational angular velocity of the rear wheel **3r**).

The accelerator manipulation detector **56** is made up, for example, of a rotary encoder, potentiometer, or other detector built in the operation apparatus **7** (the detector outputting a detection signal responsive to the rotational angle or rotational angular velocity of the accelerator grip).

The balance-on switch **57**, balance-off switch **58**, and travel-assist switch **59** are each formed of a push-button switch, for example. These switches **57** to **59** are attached to the operation apparatus **7** or the like so that the rider can manipulate them.

The functions of the above-described control device **50** will be described further with reference to FIG. **13**. The XYZ coordinate system used in the following description is, as in the case of the two-wheeled vehicle **1** in FIG. **1**, a coordinate system in which, in the basic posture state of the two-wheeled vehicle **1A**, the vertical direction (up-and-down direction) is defined as the Z-axis direction, the longitudinal direction of the vehicle body **2** as the X-axis direction, the lateral direction of the vehicle body **2** as the Y-axis direction, and a point on the

ground surface **110** immediately beneath the overall center of gravity **G** of the two-wheeled vehicle **1A** as the origin (see FIG. **9**).

Further, in the following description, the suffix “_act” is added to the reference characters of a state quantity as a sign indicating an actual value or its observed value (detected value or estimate). For a desired value, the suffix “_cmd” is added.

The control device **50** includes, as major functions implemented when the CPU executes installed programs (functions implemented by software) or as major functions implemented by hardware, as shown in FIG. **13**: an estimated inverted pendulum mass point lateral movement amount calculating section **31** which calculates an estimate of an actual value $Pb_diff_y_act$ (hereinafter, referred to as “estimated inverted pendulum mass point lateral movement amount $Pb_diff_y_act$ ”) of an inverted pendulum mass point lateral movement amount Pb_diff_y representing a movement amount in the Y-axis direction (lateral direction of the vehicle body **2**) of an inverted pendulum mass point **123** (=first mass point **123**) of the two-wheeled vehicle **1A**; an estimated inverted pendulum mass point lateral velocity calculating section **32** which calculates an estimate of an actual value Vby_act (hereinafter, referred to as “estimated inverted pendulum mass point lateral velocity Vby_act ”) of an inverted pendulum mass point lateral velocity Vby representing a translational velocity in the Y-axis direction (lateral direction of the vehicle body **2**) of the inverted pendulum mass point **123**; an estimated vehicle speed calculating section **33** which calculates an estimate of an actual value Vox_act (hereinafter, referred to as “estimated vehicle speed Vox_act ”) of the vehicle speed Vox of the two-wheeled vehicle **1A**; a desired posture state determining section **34** which determines a desired value $Pb_diff_y_cmd$ (hereinafter, referred to as “desired inverted pendulum mass point lateral movement amount $Pb_diff_y_cmd$ ”) of the inverted pendulum mass point lateral movement amount Pb_diff_y and a desired value Vby_cmd (hereinafter, referred to as “desired inverted pendulum mass point lateral velocity Vby_cmd ”) of the inverted pendulum mass point lateral velocity Vby ; a control gain determining section **35** which determines values of a plurality of gains $K1$, $K2$, $K3$, and $K4$ for posture control of the vehicle body **2**; a desired vehicle speed determining section **36** which determines a desired value Vox_cmd (hereinafter, referred to as “desired vehicle speed Vox_cmd ”) of the vehicle speed of the two-wheeled vehicle **1A**; and a desired trail determining section **37** which determines a desired value t_cmd (hereinafter, referred to as “desired trail t_cmd ”) of the trail t .

The control device **50** further includes a posture control arithmetic section **38** which carries out arithmetic processing for the posture control of the vehicle body **2** to thereby determine a desired value δf_cmd (hereinafter, referred to as “desired front-wheel steering angle δf_cmd ”) of the steering angle δf of the front wheel **3f**, a desired value δf_dot_cmd (hereinafter, referred to as “desired front-wheel steering angular velocity δf_dot_cmd ”) of the steering angular velocity δf_dot which is a temporal change rate of the steering angle δf , and a desired value δf_dot2_cmd (hereinafter, referred to as “desired front-wheel steering angular acceleration δf_dot2_cmd ”) of the steering angular acceleration δf_dot2 which is a temporal change rate of the steering angular velocity δf_dot .

In controlling the posture in the roll direction of the vehicle body **2**, the control device **50** controls the steering actuator **8** in accordance with the desired front-wheel steering angle δf_cmd , the desired front-wheel steering angular velocity

δf_dot_cmd , and the desired front-wheel steering angular acceleration δf_dot2_cmd determined by the posture control arithmetic section **38**.

In controlling the posture in the roll direction of the vehicle body **2**, the control device **50** also controls the trail adjustment actuator **15** in accordance with the desired trail t_cmd determined by the desired trail determining section **37**.

During the traveling of the two-wheeled vehicle **1A**, the control device **50** controls the travel-assist actuator **27** in accordance with the desired vehicle speed Vox_cmd determined by the desired vehicle speed determining section **36**.

A description of how the two-wheeled vehicle **1A** of the present embodiment works will be given below, with a focus on the control processing performed by the control device **50**.

When a power switch, for example a key switch, (not shown) of the two-wheeled vehicle **1A** is turned on, the control device **50** and others are started. The control device **50** executes an installed program to perform the processing shown in the flowchart in FIG. **14**.

In the state where the power switch is off, the trail adjustment actuator **15**, the steering actuator **8**, and the travel-assist actuator **27** are in the off state (where they do not generate driving or steering force). Further, the lock mechanism **15a** is in the state where it holds the output shaft of the trail adjustment actuator **15** non-rotatable. Further, the steering clutch **8a** is in the off state (where it interrupts the power transmission between the steering actuator **8** and the steering rotation section **12**).

First, in STEP **1**, the control device **50** selects an initialization mode as the operating mode of the two-wheeled vehicle **1A**.

In the present embodiment, the operating modes of the two-wheeled vehicle **1A** include: an initialization mode in which initialization processing immediately after the startup is carried out; a balance-assist-off/travel-assist-off mode which is an operating mode in which neither the control of posture in the roll direction of the vehicle body **2** (hereinafter, also simply referred to as “posture control”) nor the control of assisted traveling (or, travel-assist control) is carried out; a balance-assist-on/travel-assist-off mode which is an operating mode in which only the posture control out of the posture control and the travel-assist control is carried out; a balance-assist-off/travel-assist-on mode which is an operating mode in which only the travel-assist control out of the posture control and the travel-assist control is carried out; a balance-assist-on/travel-assist-on mode which is an operating mode in which both of the posture control and the travel-assist control are carried out; and an abnormal mode in which processing to be performed in the event of occurrence of a prescribed anomaly is carried out.

The control device **50** selectively carries out the processing in one of the operating modes. In STEP **1** described above, the control device **50** selects the initialization mode as the operating mode immediately after the startup.

Next, in STEP **2**, the control device **50** acquires outputs (detection signals) from the detectors **51** to **56** and outputs (operational states) of the switches **57** to **59**.

Next, in STEP **3**, the control device **50** determines the operating mode currently selected. In STEP **4**, the control device **50** carries out the processing corresponding to the operating mode currently selected. Then, in STEP **5**, the control device **50** waits for a timer interrupt for each prescribed control processing cycle.

Thereafter, at each prescribed control processing cycle, the processes in STEPS **2** to **5** are carried out successively.

Here, a general description of the transitions between the operating modes will be given with reference to FIG. **15**. As

shown in FIG. 15, immediately after the turning-on of the power switch, the operating mode is set to the initialization mode. In the initialization mode, the on/off state of the balance-on switch 57 is monitored. When the balance-on switch 57 is maintained in the off state (not turned on), the operating mode shifts to the balance-assist-off/travel-assist-off mode. On the other hand, when the balance-on switch 57 is turned on, the operating mode shifts to the balance-assist-on/travel-assist-off mode.

In the balance-assist-off/travel-assist-off mode, the on/off states of the travel-assist switch 59 and the balance-on switch 57 are monitored. When the travel-assist switch 59 is turned on, the operating mode shifts to the balance-assist-off/travel-assist-on mode. When the balance-on switch 57 is turned on, the operating mode shifts to the balance-assist-on/travel-assist-off mode.

In the balance-assist-on/travel-assist-off mode, the on/off states of the travel-assist switch 59 and the balance-off switch 58 are monitored. When the travel-assist switch 59 is turned on, the operating mode shifts to the balance-assist-on/travel-assist-on mode. When the balance-off switch 58 is turned on, the operating mode shifts to the balance-assist-off/travel-assist-off mode.

In the balance-assist-off/travel-assist-on mode, the on/off state of the balance-on switch 57 is monitored. When the balance-on switch 57 is turned on, the operating mode shifts to the balance-assist-on/travel-assist-on mode.

In the balance-assist-on/travel-assist-on mode, the on/off state of the balance-off switch 58 is monitored. When the balance-off switch 58 is turned on, the operating mode shifts to the balance-assist-off/travel-assist-on mode.

In any of the initialization mode, balance-assist-off/travel-assist-off mode, balance-assist-on/travel-assist-off mode, balance-assist-off/travel-assist-on mode, and balance-assist-on/travel-assist-on mode, if there occurs a prescribed anomaly such as an anomaly in output from any of the detectors 51 to 56, an anomaly in operation of any of the actuators 8, 15, and 27, or an anomaly in operation of the electrical equipment system, the operating mode shifts preferentially to the abnormal mode.

Further, in any of the initialization mode, balance-assist-off/travel-assist-off mode, balance-assist-on/travel-assist-off mode, balance-assist-off/travel-assist-on mode, and balance-assist-on/travel-assist-on mode, when the power switch of the two-wheeled vehicle 1A is turned off, the processing in the operating mode is terminated.

It should be noted that the sequence of transitions between the operating modes may be set differently from the above.

The processing in each of the above-described operating modes will now be described.

The processing in the initialization mode is carried out as shown by a flowchart in FIG. 16.

First, in STEP 101, the control device 50 causes the lock mechanism 15a to keep the output shaft of the trail adjustment actuator 15 non-rotatable, to thereby lock the trail t in the current state.

Then, in STEP 102, the control device 50 sets the trail adjustment actuator 15 to the off state (the state of generating no driving force). Specifically, the control device 50 maintains the state where no power is supplied to the trail adjustment actuator 15 (electric motor).

Next, in STEP 103, the control device 50 initializes each of the values of the posture control gains $K1$, $K2$, $K3$, and $K4$ (described later) for use in posture control of the vehicle body 2, to zero.

Further, in STEP 104, the control device 50 sets a desired front-wheel steering angle δf_cmd and a desired front-wheel

steering angular velocity δf_dot_cmd to match a detected value of the actual steering angle δf_act (hereinafter, referred to as “detected front-wheel steering angle δf_act ”) of the front wheel 3f, and a detected value of the actual steering angular velocity δf_dot_act (hereinafter, referred to as “detected front-wheel steering angular velocity δf_dot_act ”) of the front wheel 3f, respectively, which are each indicated by an output from the front-wheel steering angle detector 52.

Then, in STEP 105, the control device 50 sets the aforesaid steering clutch 8a to the off state (where the power transmission between the steering actuator 8 and the steering rotation section 12 is interrupted). Further, the control device 50 sets the steering actuator 8 to the off state (the state of generating no steering force). Specifically, the control device 50 maintains the state where no power is supplied to the steering actuator 8 (electric motor).

Next, in STEP 106, the control device 50 sets the value of the desired vehicle speed Vox_cmd of the two-wheeled vehicle 1A to zero, and also sets the travel-assist actuator 27 to the off state (the state of generating no driving force). Specifically, the control device 50 maintains the state where no power is supplied to the travel-assist actuator 27 (electric motor).

Next, in STEP 107, the control device 50 determines whether any of the aforesaid prescribed anomalies has been detected. If no anomaly has been detected, in STEP 108, the control device 50 determines the operational state of the balance-on switch 57.

If it is determined in STEP 108 that the balance-on switch 57 remains in the off state, in STEP 109, the control device 50 sets the operating mode in the next time’s control processing cycle to the balance-assist-off/travel-assist-off mode, and terminates the processing in the initialization mode in the current (current time’s) control processing cycle.

If it is determined in STEP 108 that the balance-on switch 57 has been turned on, in STEP 111, the control device 50 sets the operating mode in the next time’s control processing cycle to the balance-assist-on/travel-assist-off mode, and terminates the processing in the initialization mode in the current time’s control processing cycle.

Further, if it is determined in the aforesaid STEP 107 that an anomaly has been detected, in STEP 110, the control device 50 sets the operating mode in the next time’s control processing cycle to the abnormal mode, and terminates the processing in the initialization mode in the current time’s control processing cycle.

The above has described the processing in the initialization mode. With this processing, when there has occurred an anomaly, when the balance-on switch 57 is in the off state, or when the balance-on switch 57 has been turned on, the operating mode in the next time’s control processing cycle shifts to the abnormal mode, the balance-assist-off/travel-assist-off mode, or the balance-assist-on/travel-assist-off mode, respectively.

It should be noted that in the initialization mode, the actuators 8, 15, and 27 are all maintained in the off state.

The processing in the balance-assist-off/travel-assist-off mode is carried out as shown by a flowchart in FIG. 17.

First, in STEP 201, the control device 50 determines whether the detected value of the actual trail t_act (hereinafter, referred to as “detected trail t_act ”) indicated by an output from the trail detector 53 coincides, or almost coincides, with the aforesaid upper trail limit t_p .

This determination is made according to whether the magnitude (absolute value) of the difference between the detected trail t_act and the upper trail limit t_p is a predetermined, prescribed value or less. It should be noted that in the state

where the trail t_{act} is being controlled to a required or desired trail t_{cmd} by the trail adjustment actuator **15**, the desired trail t_{cmd} , instead of the detected trail t_{act} , may be used to perform the determination process in STEP **201**.

If the determination result in STEP **201** is "YES" (when the detected trail t_{act} coincides, or almost coincides, with the upper trail limit tp), in STEP **202**, the control device **50** locks the trail t . Further, in STEP **203**, the control device **50** sets the trail adjustment actuator **15** to the off state. The processes in STEPS **202** and **203** are identical to the processes in STEPS **101** and **102**, respectively, in the aforesaid initialization mode.

If the determination result in STEP **201** is "NO", in STEP **204**, the control device **50** causes the lock mechanism **15a** to unlock the trail (or, sets the lock mechanism **15a** to the off state). Further, in STEP **205**, the control device **50** controls the trail adjustment actuator **15** to change the trail t_{act} gradually to the upper trail limit tp .

For example, the control device **50** controls the trail adjustment actuator **15** such that it makes the trail t_{act} approach the upper trail limit tp at a prescribed rate.

Following the STEP **203** or **205**, in STEPS **206** to **210**, the control device **50** carries out the processes identical to those in STEPS **103** to **107** in the aforesaid initialization mode.

Then, if it is determined in STEP **210** that no anomaly has been detected, in STEP **211**, the control device **50** determines the operational state of the travel-assist switch **59**.

If it is determined in STEP **211** that the travel-assist switch **59** remains in the off state, next, in STEP **212**, the control device **50** determines the operational state of the balance-on switch **57**.

If it is determined in STEP **212** that the balance-on switch **57** remains in the off state, in STEP **213**, the control device **50** sets the operating mode in the next time's control processing cycle to the balance-assist-off/travel-assist-off mode (which is the same mode as in the current time's control processing cycle), and terminates the processing in the balance-assist-off/travel-assist-off mode in the current time's control processing cycle.

If it is determined in STEP **212** that the balance-on switch **57** has been turned on, in STEP **216**, the control device **50** sets the operating mode in the next time's control processing cycle to the balance-assist-on/travel-assist-off mode, and terminates the processing in the balance-assist-off/travel-assist-off mode in the current time's control processing cycle.

Further, if it is determined in the aforesaid STEP **211** that the travel-assist switch **59** has been turned on, in STEP **215**, the control device **50** sets the operating mode in the next time's control processing cycle to the balance-assist-off/travel-assist-on mode, and terminates the processing in the balance-assist-off/travel-assist-off mode in the current time's control processing cycle.

Further, if it is determined in the aforesaid STEP **210** that an anomaly has been detected, in STEP **214**, the control device **50** sets the operating mode in the next time's control processing cycle to the abnormal mode, and terminates the processing in the balance-assist-off/travel-assist-off mode in the current time's control processing cycle.

The above has described the processing in the balance-assist-off/travel-assist-off mode. With this processing, except for the case where an anomaly has been detected, or the travel-assist switch **59** has been turned on, or the balance-on switch **57** has been turned on, the operating mode in the next time's control processing cycle is maintained in the balance-assist-off/travel-assist-off mode. When an anomaly has been detected, the travel-assist switch **59** has been turned on, or the balance-on switch **57** has been turned on, the operating mode

in the next time's control processing cycle shifts to the abnormal mode, the balance-assist-off/travel-assist-on mode, or the balance-assist-on/travel-assist-off mode, respectively.

Further, in the balance-assist-off/travel-assist-off mode, the steering actuator **8** and the travel-assist actuator **27** are in the off state. This allows a rider of the two-wheeled vehicle **1A** to freely steer the front wheel **3f** by maneuvering the operation apparatus **7**. The rider can also move the two-wheeled vehicle **1A** by holding the operation apparatus **7** and causing the front wheel **3f** and the rear wheel **3r** to roll.

At this time, the steering clutch **8a** is in the off state. This can reduce the friction at the time when the rider steers the front wheel **3f** by operating the operation apparatus **7**.

Further, in the balance-assist-off/travel-assist-off mode, the trail t is maintained at the upper trail limit tp (>0), or it is displaced toward the upper trail limit tp and then maintained at the upper trail limit tp . In this case, the trail t is fixedly held at the upper trail limit tp by activation of the lock mechanism **15a**. Therefore, in this state, the driving force of the trail adjustment actuator **15** is unnecessary. It is thus possible to set the trail adjustment actuator **15** to the off state to thereby save the electricity otherwise consumed by the trail adjustment actuator **15**.

The processing in the balance-assist-off/travel-assist-on mode is carried out as shown by a flowchart in FIG. **18**.

First, in STEPS **301** to **308**, the control device **50** carries out the processes identical to those in STEPS **201** to **208** in the aforesaid balance-assist-off/travel-assist-off mode.

Next, in STEP **309**, the control device **50** determines a desired vehicle speed Vox_{cmd} of the two-wheeled vehicle **1A**, and controls the travel-assist actuator **27** in accordance with the desired vehicle speed Vox_{cmd} . The processing in this STEP **309** will be described in detail later.

Next, in STEP **310**, the control device **50** carries out the determination process which is identical to that in STEP **107** in the aforesaid initialization mode. That is, the control device **50** determines whether a prescribed anomaly has been detected. If no anomaly has been detected, in STEP **311**, the control device **50** determines the operational state of the balance-on switch **57**.

If it is determined in STEP **311** that the balance-on switch **57** remains in the off state, in STEP **312**, the control device **50** sets the operating mode in the next time's control processing cycle to the balance-assist-off/travel-assist-on mode (which is the same mode as in the current time's control processing cycle), and terminates the processing in the balance-assist-off/travel-assist-on mode in the current time's control processing cycle.

If it is determined in STEP **311** that the balance-on switch **57** has been turned on, in STEP **314**, the control device **50** sets the operating mode in the next time's control processing cycle to the balance-assist-on/travel-assist-on mode, and terminates the processing in the balance-assist-off/travel-assist-on mode in the current time's control processing cycle.

Further, if it is determined in the aforesaid STEP **310** that an anomaly has been detected, in STEP **313**, the control device **50** sets the operating mode in the next time's control processing cycle to the abnormal mode, and terminates the processing in the balance-assist-off/travel-assist-on mode in the current time's control processing cycle.

The processing in the above-described STEP **309** will now be described in detail. In STEP **309**, the control device **50** determines the desired vehicle speed Vox_{cmd} by the processing in the aforesaid desired vehicle speed determining section **36**. Specifically, the desired vehicle speed determining section **36** determines the desired vehicle speed Vox_{cmd} from the detected value of the actual value of the accelerator

manipulated variable indicated by an output from the accelerator manipulation detector **56**, in accordance with a preset mapping or arithmetic expression. In this case, the desired vehicle speed V_{ox_cmd} is determined, within the range not exceeding a predetermined maximum value, such that the desired vehicle speed becomes higher as the accelerator manipulated variable becomes larger.

When the brake is being applied to the two-wheeled vehicle **1A**, the desired vehicle speed V_{ox_cmd} may be determined in accordance with the detected value of the brake manipulated variable, or in accordance with both of the detected value of the brake manipulated variable and the detected value of the accelerator manipulated variable, by a predetermined mapping or arithmetic expression.

The control device **50** further calculates an estimated vehicle speed V_{ox_act} (an estimate of the actual vehicle speed V_{ox_act}) by the processing in the aforesaid estimated vehicle speed calculating section **33**.

In this case, as shown in FIG. **13**, the estimated vehicle speed calculating section **33** receives a detected value of the actual value δf_{act} (hereinafter, referred to as “detected front-wheel steering angle δf_{act} ”) of the steering angle δf of the front wheel **3f**, and an estimate of the actual value Vf_{act} (hereinafter, referred to as “estimated front-wheel rotational transfer velocity Vf_{act} ”) of the rotational transfer velocity Vf of the front wheel **3f**.

It should be noted that the detected front-wheel steering angle δf_{act} is a detected value (observed value) indicated by an output from the front-wheel steering angle detector **52**. Further, the estimated front-wheel rotational transfer velocity Vf_{act} is a velocity which is calculated by multiplying a detected value (observed value) of the rotational angular velocity of the front wheel **3f**, indicated by an output from the aforesaid front-wheel rotational speed detector **54**, by a predetermined effective rolling radius of the front wheel **3f**.

The estimated vehicle speed calculating section **33** carries out the processing shown in the block diagram in FIG. **22** to calculate the estimated vehicle speed V_{ox_act} .

In FIG. **22**, a processing section **33-1** represents a processing section which multiplies a detected front-wheel steering angle δf_{act} at the current time by a cosine value of the caster angle θ_{cf} of the front wheel **3f** to calculate an estimate of the actual value $\delta'f_{act}$ (hereinafter, referred to as “estimated front-wheel effective steering angle $\delta'f_{act}$ ”) of a front-wheel effective steering angle $\delta'f$ which corresponds to the rotational angle in the yaw direction of the front wheel **3f**, a processing section **33-2** represents a processing section which obtains a cosine value $\cos(\delta'f_{act})$ of the estimated front-wheel effective steering angle $\delta'f_{act}$, and a processing section **33-3** represents a processing section which multiplies an estimated front-wheel rotational transfer velocity Vf_{act} at the current time by the above-described cosine value $\cos(\delta'f_{act})$ to thereby calculate an estimated vehicle speed V_{ox_act} .

Accordingly, the estimated vehicle speed calculating section **33** is configured to calculate V_{ox_act} by the following expression (51).

$$\begin{aligned} V_{ox_act} &= Vf_{act} * \cos(\delta'f_{act}) \\ &= Vf_{act} * \cos(\delta f_{act} * \cos(\theta_{cf})) \end{aligned} \quad (51)$$

The estimated vehicle speed V_{ox_act} calculated in this manner corresponds to a component in the X-axis direction of the estimated front-wheel rotational transfer velocity Vf_{act} .

Supplementally, the front-wheel effective steering angle $\delta'f$ is an angle of the line of intersection of the ground surface **110** and the rotational plane of the front wheel **3f** being steered (plane passing through the center of the axle of the front wheel **3f** and orthogonal to the axle centerline Cf of the front wheel **3f**) with respect to the longitudinal direction (X-axis direction) of the vehicle body **2**.

In the case where the roll angle ϕ_b of the vehicle body **2** is relatively small, the estimated front-wheel effective steering angle $\delta'f_{act}$ can be calculated approximately through the computation in the above-described processing section **33-1**.

It should be noted that in order to further improve the accuracy of $\delta'f_{act}$, $\delta'f_{act}$ may be obtained by a mapping from δf_{act} . Alternatively, to still further improve the accuracy of $\delta'f_{act}$, $\delta'f_{act}$ may be obtained by a mapping (two-dimensional mapping) or the like from δf_{act} and a detected value of the actual value ϕ_{b_act} (hereinafter, referred to as “detected roll angle ϕ_{b_act} ”) of the roll angle ϕ_b of the vehicle body **2**, which is indicated by an output from the aforesaid vehicle-body inclination detector **51**.

The estimated vehicle speed calculating section **33** calculates the estimated vehicle speed V_{ox_act} by the processing described above. It should be noted that a value of the actual rotational transfer velocity of the rear wheel **3r** estimated on the basis of an output from the rear-wheel rotational speed detector **55** (specifically, a value obtained by multiplying the rotational angular velocity of the rear wheel **3r**, indicated by the output from the rear-wheel rotational speed detector **55**, by a predetermined effective rolling radius of the rear wheel **3r**) may be obtained as the estimated vehicle speed V_{ox_act} .

The control device **50** controls the travel-assist actuator **27** so as to cause the estimated vehicle speed V_{ox_act} calculated in the above-described manner to track the desired vehicle speed V_{ox_cmd} . For example, the control device **50** multiplies the deviation of V_{ox_act} from V_{ox_cmd} by a gain of a prescribed value, to determine an electric current command value of the travel-assist actuator **27** (electric motor) (or, a desired value of the electric current passed through the actuator). The control device **50** then controls the electric current passed through the travel-assist actuator **27** (electric motor) in accordance with the electric current command value.

According to the above-described processing in STEP **309**, the travel-assist actuator **27** is controlled such that the actual vehicle speed V_{ox_act} of the two-wheeled vehicle **1A** tracks the desired vehicle speed V_{ox_cmd} .

The above has described the processing in the balance-assist-off/travel-assist-on mode. With this processing, except for the case where an anomaly has been detected, or the balance-on switch **57** has been turned on, the operating mode in the next time’s control processing cycle is maintained in the balance-assist-off/travel-assist-on mode. When an anomaly has been detected, or the balance-on switch **57** has been turned on, the operating mode in the next time’s control processing cycle shifts to the abnormal mode, or the balance-assist-on/travel-assist-on mode, respectively.

In the balance-assist-off/travel-assist-on mode, as the rider manipulates the accelerator, the front wheel **3f** is rotatively driven by the driving force of the travel-assist actuator **27**, thereby allowing the two-wheeled vehicle **1A** to travel by that driving force.

Further, in the balance-assist-off/travel-assist-on mode, the trail t is maintained at the upper trail limit t_p (>0), or it is displaced toward the upper trail limit t_p and then maintained at the upper trail limit t_p . In this case, the trail t is fixedly held at the upper trail limit t_p by activation of the lock mechanism **15a**. Therefore, in this state, the driving force of the trail adjustment actuator **15** is unnecessary. It is thus possible to set

the trail adjustment actuator **15** to the off state to thereby save the electricity otherwise consumed by the trail adjustment actuator **15**.

Further, in this case, as the upper trail limit t_p takes a positive value, the operation stability during the traveling of the two-wheeled vehicle **1A** is secured smoothly.

Further, in the balance-assist-off/travel-assist-on mode, the steering actuator **8** is in the off state. This allows the rider of the two-wheeled vehicle **1A** to freely steer the front wheel **3f** by maneuvering the operation apparatus **7**.

At this time, the steering clutch **8a** is in the off state. This can reduce the friction at the time when the rider steers the front wheel **3f** by operating the operation apparatus **7**.

The processing in the balance-assist-on/travel-assist-off mode is carried out as shown by a flowchart in FIG. **19**.

First, in STEP **401**, the control device **50** determines a desired trail t_{cmd} by the processing in the aforesaid desired trail determining section **37**.

As shown in FIG. **13**, the desired trail determining section **37** successively receives the estimated vehicle speed Vox_{act} calculated in the above-described manner by the estimated vehicle speed calculating section **33**. The desired trail determining section **37** determines the desired trail t_{cmd} in accordance with the estimated vehicle speed Vox_{act} at the current time.

In this case, in the present embodiment, the desired trail t_{cmd} is determined to either one of the aforesaid upper trail limit t_p and lower trail limit t_n . More specifically, the desired trail t_{cmd} is determined, in accordance with the estimated vehicle speed Vox_{act} , with the characteristics as shown in FIG. **23**.

That is, when the estimated vehicle speed Vox_{act} is zero, the desired trail t_{cmd} is determined to be the lower trail limit t_n (<0). In the state where $t_{cmd}=t_n$, t_{cmd} is maintained at the lower trail limit t_n (<0) until the estimated vehicle speed Vox_{act} increases to exceed a predetermined, first prescribed value Vox_1 (i.e., as long as Vox_{act} remains in a low-speed range of not higher than Vox_1 (including zero)).

When Vox_{act} exceeds the first prescribed value Vox_1 , t_{cmd} is switched from the lower trail limit t_n to the upper trail limit t_p (>0). Thereafter, in the state where $t_{cmd}=t_p$, t_{cmd} is maintained at the upper trail limit t_p (>0) until the estimated vehicle speed Vox_{act} decreases to a level below a predetermined, second prescribed value Vox_2 (i.e. as long as Vox_{act} is maintained in a high-speed range of not lower than Vox_2). In this case, the second prescribed value Vox_2 is set smaller than the first prescribed value Vox_1 .

When Vox_{act} drops below the second prescribed value Vox_2 , t_{cmd} is returned from the upper trail limit t_p to the lower trail limit t_n .

As described above, basically, the desired trail t_{cmd} is set to the lower trail limit t_n (<0) when the actual vehicle speed Vox_{act} is in a low-speed range (including the standstill state), and it is set to the upper trail limit t_p (>0) when the actual vehicle speed Vox_{act} is in a high-speed range. In this case, t_{cmd} is determined in accordance with Vox_{act} such that it has hysteresis characteristics with respect to the change in Vox_{act} . Therefore, t_{cmd} is determined such that it will not be switched frequently in the situation where Vox_{act} is near the first prescribed value Vox_1 or the second prescribed value Vox_2 .

Supplementally, in the example shown in FIG. **23**, the desired trail t_{cmd} was determined such that it would change to either t_n or t_p discontinuously. Alternatively, the desired trail t_{cmd} may be determined such that it changes continuously with respect to the vehicle speed Vox_{act} .

For example, the desired trail t_{cmd} may be determined, in accordance with the vehicle speed Vox_{act} , with the characteristics as shown in FIG. **24**. In this example, in the low vehicle speed range of not higher than a prescribed vehicle speed Vox_3 , t_{cmd} is maintained constantly at the lower trail limit t_n . Further, in the high vehicle speed range of not lower than a prescribed vehicle speed Vox_4 , t_{cmd} is maintained constantly at the upper trail limit t_p . In the vehicle speed range between Vox_3 and Vox_4 , t_{cmd} is increased monotonically with increasing Vox_{act} .

Next, in STEP **402**, the control device **50** determines whether the desired trail t_{cmd} at the current time is the upper trail limit t_p and whether the detected trail t_{act} at the current time coincides, or almost coincides, with the upper trail limit t_p .

In this case, the determination as to whether the detected trail t_{act} coincides, or almost coincides, with the upper trail limit t_p is made in the same manner as in the aforesaid STEP **201**.

If the determination result in STEP **402** is "YES" (when $t_{cmd}=t_p$ and t_{act} coincides, or almost coincides, with t_p), in STEP **403**, the control device **50** locks the trail t . Further, in STEP **404**, the control device **50** sets the trail adjustment actuator **15** to the off state. The processes in STEPS **403** and **404** are identical to the processes in STEPS **101** and **102**, respectively, in the aforesaid initialization mode.

If the determination result in STEP **402** is "NO", in STEP **405**, the control device **50** causes the lock mechanism **15a** to unlock the trail (or, sets the lock mechanism **15a** to the off state). Further, in STEP **406**, the control device **50** controls the trail adjustment actuator **15** to make the trail t_{act} converge to or match the desired trail t_{cmd} .

Specifically, in the case where t_{cmd} is switched from t_n to t_p , for example, the trail adjustment actuator **15** is controlled such that t_{act} changes from t_n to t_p within a predetermined time T_{acc} , as shown by the dotted line in the lower graph in FIG. **23**. In this case, the trail adjustment actuator **15** is controlled, for example, to maintain the change rate of the trail t_{act} at a constant value.

In the case where t_{cmd} is switched from t_p to t_n , the trail adjustment actuator **15** is controlled such that t_{act} changes from t_p to t_n within a predetermined time T_{dec} , as shown by the dotted line in the lower graph in FIG. **23**. In this case, the trail adjustment actuator **15** is controlled, for example, to maintain the change rate of the trail t_{act} at a constant value.

It should be noted that the predetermined times T_{acc} and T_{dec} described above may be the same or different from each other.

Further, when t_{cmd} is switched, the trail t_{act} does not necessarily have to be changed at a constant rate. For example, in the case where t_{cmd} is switched from t_p to t_n , the trail adjustment actuator **15** may be configured to simply generate a prescribed driving force in the direction of decreasing the trail t_{act} . The same applies to the case where t_{cmd} is switched from t_n to t_p .

Following the STEP **404** or **406**, in STEP **407**, the control device **50** determines desired values for the posture control gains K_1 , K_2 , K_3 , and K_4 (described later) which are used when performing the posture control of the vehicle body **2**. The control device **50** then determines actually used values of the posture control gains K_1 , K_2 , K_3 , and K_4 such that they gradually approach the desired values. The processing in this STEP **407** will be described in detail later.

Next, in STEP **408**, the control device **50** determines a desired front-wheel steering angular acceleration δf_{dot2_cmd} , a desired front-wheel steering angular velocity δf_{dot_cmd} , and a desired front-wheel steering angle

δf_{cmd} , in accordance with a prescribed control law for the posture control. The processing in this STEP 408 will be described in detail later.

Next, in STEP 409, the control device 50 sets the aforesaid steering clutch 8a to the on state (the state enabling power transmission between the steering actuator 8 and the steering rotation section 12), and also controls the steering actuator 8 in accordance with the desired front-wheel steering angular acceleration $\delta f_{\text{dot2_cmd}}$, the desired front-wheel steering angular velocity $\delta f_{\text{dot_cmd}}$, and the desired front-wheel steering angle δf_{cmd} .

Specifically, the control device 50 for example determines an electric current command value $I_{\delta f_{\text{cmd}}}$, which is a desired value of the electric current passed through the steering actuator 8 (electric motor), from $\delta f_{\text{dot2_cmd}}$, $\delta f_{\text{dot_cmd}}$, δf_{cmd} , detected front-wheel steering angle δf_{act} , and detected front-wheel steering angular velocity $\delta f_{\text{dot_act}}$, by the following expression (52).

$$I_{\delta f_{\text{cmd}}} = K\delta f_p * (\delta f_{\text{cmd}} - \delta f_{\text{act}}) + K\delta f_v * (\delta f_{\text{dot_cmd}} - \delta f_{\text{dot_act}}) + K\delta f_a * \delta f_{\text{dot2_cmd}} \quad (52)$$

It should be noted that δf_{act} and $\delta f_{\text{dot_act}}$ are detected values which are each indicated by an output from the front-wheel steering angle detector 52, and $K\delta f_p$, $K\delta f_v$, and $K\delta f_a$ are gains of prescribed values.

Therefore, the electric current command value $I_{\delta f_{\text{cmd}}}$ is determined by summing up a feedback manipulated variable component responsive to the deviation of δf_{act} from δf_{cmd} , a feedback manipulated variable component responsive to the deviation of $\delta f_{\text{dot_act}}$ from $\delta f_{\text{dot_cmd}}$, and a feedforward manipulated variable component responsive to $\delta f_{\text{dot2_cmd}}$.

Then, the control device 50 controls the actual electric current passed through the steering actuator 8 (electric motor) to match the electric current command value $I_{\delta f_{\text{cmd}}}$, by an electric current control section (not shown) which is made up of a motor driver or the like.

In this manner, the control is performed such that the actual steering angle of the front wheel 3f tracks the desired front-wheel steering angle δf_{cmd} . In this case, the electric current command value $I_{\delta f_{\text{cmd}}}$ includes the third term on the right side of the above expression (52), i.e. the feedforward manipulated variable component, which ensures improved tracking in the above-described control.

It should be noted that the technique of controlling the steering actuator 8 to cause the actual steering angle of the front wheel 3f to track the desired front-wheel steering angle δf_{cmd} is not limited to the above-described technique; other techniques may be used as well. For example, various kinds of known servo control techniques related to electric motors (feedback control techniques for causing the actual angle of rotation of the rotor of the electric motor to track a desired value) may be adopted.

Next, in STEP 410, the control device 50 sets the desired vehicle speed $V_{\text{ox_cmd}}$ to zero, and also sets the travel-assist actuator 27 to the off state. This process is identical to that in the aforesaid STEP 106.

Next, in STEP 411, the control device 50 carries out the determination process which is identical to that in STEP 107 in the aforesaid initialization mode. That is, the control device 50 determines whether a prescribed anomaly has been

detected. If no anomaly has been detected, in STEP 412, the control device 50 determines the operational state of the travel-assist switch 59.

If it is determined in STEP 412 that the travel-assist switch 59 remains in the off state, next, in STEP 413, the control device 50 determines the operational state of the balance-off switch 58.

If it is determined in STEP 413 that the balance-off switch 58 remains in the off state, in STEP 414, the control device 50 sets the operating mode in the next time's control processing cycle to the balance-assist-on/travel-assist-off mode (which is the same mode as in the current time's control processing cycle), and terminates the processing in the balance-assist-on/travel-assist-off mode in the current time's control processing cycle.

If it is determined in STEP 413 that the balance-off switch 58 has been turned on, in STEP 417, the control device 50 sets the operating mode in the next time's control processing cycle to the balance-assist-off/travel-assist-off mode, and terminates the processing in the balance-assist-on/travel-assist-off mode in the current time's control processing cycle.

Further, if it is determined in the aforesaid STEP 412 that the travel-assist switch 59 has been turned on, in STEP 416, the control device 50 sets the operating mode in the next time's control processing cycle to the balance-assist-on/travel-assist-on mode, and terminates the processing in the balance-assist-on/travel-assist-off mode in the current time's control processing cycle.

Further, if it is determined in the aforesaid STEP 411 that an anomaly has been detected, in STEP 415, the control device 50 sets the operating mode in the next time's control processing cycle to the abnormal mode, and terminates the processing in the balance-assist-on/travel-assist-off mode in the current time's control processing cycle.

The processing in the above-described STEPS 407 and 408 will be described in detail below. For the sake of better understanding, the processing in STEP 408 will be described first.

In STEP 408, the control device 50 determines a desired front-wheel steering angular acceleration $\delta f_{\text{dot2_cmd}}$, a desired front-wheel steering angular velocity $\delta f_{\text{dot_cmd}}$, and a desired front-wheel steering angle δf_{cmd} , by carrying out the processing in the estimated inverted pendulum mass point lateral movement amount calculating section 31, the estimated inverted pendulum mass point lateral velocity calculating section 32, the desired posture state determining section 34, and the posture control arithmetic section 38 shown in FIG. 13.

The control device 50 first carries out the processing in the estimated inverted pendulum mass point lateral movement amount calculating section 31. It should be noted that the algorithm of the processing in the estimated inverted pendulum mass point lateral movement amount calculating section 31 in the present embodiment has been established assuming, by way of example, that the dynamic behavior of the two-wheeled vehicle 1A is expressed by the dynamic behavior that is obtained when the two-wheeled vehicle 1A is equivalently transformed to the system, shown in FIG. 2, which is made up of the first mass point 123 (inverted pendulum mass point) and the second mass point 124.

As shown in FIG. 13, the estimated inverted pendulum mass point lateral movement amount calculating section 31 receives a detected roll angle ϕb_{act} and a detected front-wheel steering angle δf_{act} .

The detected roll angle ϕb_{act} is a detected value (observed value) indicated by an output from the vehicle-body inclination detector 51.

Here, in the case where it is assumed that a mass point and an inertia moment are set only for the vehicle body **2** of the two-wheeled vehicle **1A** and that the dynamic behavior of the two-wheeled vehicle **1A** is expressed by the behavior of the mass point system made up of the first mass point **123** (inverted pendulum mass point) and the second mass point **124**, the inclination in the roll direction of the line segment connecting the first mass point **123** and the second mass point **124** corresponds to the inclination in the roll direction of the vehicle body **2** of the two-wheeled vehicle **1A**, as explained above.

Accordingly, in the case where the inclination angle ϕ_b in the roll direction of the vehicle body **2** of the two-wheeled vehicle **1A** is sufficiently small, the difference between the movement amount in the Y-axis direction of the first mass point **123** and the movement amount in the Y-axis direction of the second mass point **124** coincides with a value obtained by multiplying the inclination angle ϕ_b in the roll direction of the vehicle body **2** by the height h' of the first mass point **123**.

Further, in the two-wheeled vehicle **1A** of the present embodiment, the front wheel **3f** alone is a steered wheel. Therefore, the movement amount q in the Y-axis direction of the second mass point **124** is determined uniquely from the steering angle δf of the front wheel **3f**, as explained above.

Accordingly, the movement amount in the Y-axis direction of the first mass point **123**, which is the inverted pendulum mass point, is obtained as a sum of a component attributable to the inclination in the roll direction of the vehicle body **2** of the two-wheeled vehicle **1A** and a component attributable to the steering angle δf of the front wheel **3f**.

The estimated inverted pendulum mass point lateral movement amount calculating section **31** uses this relationship to calculate an estimated inverted pendulum mass point lateral movement amount $Pb_diff_y_act$ on the basis of the detected roll angle ϕ_{b_act} and the detected front-wheel steering angle δf_act .

More specifically, the estimated inverted pendulum mass point lateral movement amount calculating section **31** calculates the estimated inverted pendulum mass point lateral movement amount $Pb_diff_y_act$ by the processing shown in the block diagram in FIG. **25**.

This processing is configured to sum up a first estimated lateral movement amount component $Pb_diff_y_act_1$, which is an estimate of the actual movement amount in the Y-axis direction of the inverted pendulum mass point **123** caused by the inclination in the roll direction of the vehicle body **2**, and a second estimated lateral movement amount component $Pb_diff_y_act_2$, which is an estimate of the actual movement amount in the Y-axis direction of the inverted pendulum mass point **123** caused by the steering of the front wheel **3f**, to thereby calculate the estimated inverted pendulum mass point lateral movement amount $Pb_diff_y_act$.

In FIG. **25**, a processing section **31-1** represents a processing section which obtains the first estimated lateral movement amount component $Pb_diff_y_act_1$, a processing section **31-2** represents a processing section which obtains the second estimated lateral movement amount component $Pb_diff_y_act_2$, and a processing section **31-3** represents a processing section which sums up the first estimated lateral movement amount component $Pb_diff_y_act_1$ and the second estimated lateral movement amount component $Pb_diff_y_act_2$.

The processing section **31-1** determines the first estimated lateral movement amount component $Pb_diff_y_act_1$ in accordance with the detected roll angle ϕ_{b_act} at the current time. More specifically, the processing section **31-1** multi-

plies the detected roll angle ϕ_{b_act} (angle value in [rad]) by the height h' ($=c+h$), multiplied by -1 , of the inverted pendulum mass point **123**, to calculate the first estimated lateral movement amount component $Pb_diff_y_act_1$ ($=\phi_{b_act}*(-h')$).

Accordingly, the first estimated lateral movement amount component $Pb_diff_y_act_1$ is calculated, in accordance with the detected roll angle ϕ_{b_act} , as a value of a linear function with respect to the roll angle ϕ_b of the vehicle body **2** (a value of a constant multiple of ϕ_b). Further, $Pb_diff_y_act_1$ becomes zero in the state where $\phi_{b_act}=0$ (where the vehicle body **2** is not leaned to the right or left), and therefore, it is the movement amount in the Y-axis direction with reference to the position of the inverted pendulum mass point **123** in that state.

It should be noted that $\sin(\phi_{b_act})$ is approximated by ϕ_{b_act} in the calculating processing in the processing section **31-1**. Further, the value of h' (or c , h) has been preset in the two-wheeled vehicle **1A** and is stored in a memory in the control device **50**. For example, the value has been set to satisfy the relationship in the aforesaid expression (4) (the relationship that $c=(h'-h)=I/(m*h)$), from the height h of the overall center of gravity G in the basic posture state of the two-wheeled vehicle **1A**, the overall inertia I of the two-wheeled vehicle **1A** (inertia moment about the axis passing through the overall center of gravity G and parallel to the X-axis direction), and the total mass m of the two-wheeled vehicle **1A**.

The value of h' , however, may be set to a value roughly approximating the value satisfying the relationship in the above expression (4) such that optimal control characteristics can be obtained on the basis of various experiments, simulation, etc.

The processing section **31-2** in FIG. **25** determines the second estimated lateral movement amount component $Pb_diff_y_act_2$ in accordance with the detected front-wheel steering angle δf_act at the current time. More specifically, the processing section **31-2** obtains the second estimated lateral movement amount component $Pb_diff_y_act_2$ ($=Plfy(\delta f_act)$) from the detected front-wheel steering angle δf_act at the current time, by a preset conversion function $Plfy(\delta f)$. That is, the processing section **31-2** obtains a value $Plfy(\delta f_act)$ of the conversion function $Plfy(\delta f)$ corresponding to δf_act , and determines the obtained value as the second estimated lateral movement amount component $Pb_diff_y_act_2$.

The above conversion function $Plfy(\delta f)$ is defined, for example, by a mapping or an arithmetic expression. The conversion function $Plfy(\delta f)$ has been preset, as illustrated by the graph shown in the processing section **31-2** in FIG. **25**, such that it monotonically changes (in the present embodiment, monotonically decreases) with increasing steering angle δf of the front wheel **3f**. Further, the conversion function $Plfy(\delta f)$ is a nonlinear function which has been preset such that the magnitude of the rate of change of $Plfy(\delta f)$ with respect to the steering angle δf (the amount of change of $Plfy(\delta f)$ per unit increase of δf) becomes relatively small in the region where the magnitude (absolute value) of the steering angle δf of the front wheel **3f** is relatively large, compared to that in the region where the magnitude of the steering angle δf is small (region where δf is near zero).

Accordingly, the second estimated lateral movement amount component $Pb_diff_y_act_2$ is determined, in accordance with the detected front-wheel steering angle δf_act , as a value of a nonlinear function with respect to the steering angle δf of the front wheel **3f**.

The estimated inverted pendulum mass point lateral movement amount calculating section 31 determines the estimated inverted pendulum mass point lateral movement amount $Pb_diff_y_act$ by summing up, in the processing section 31-3, the first estimated lateral movement amount component $Pb_diff_y_act_1$ and the second estimated lateral movement amount component $Pb_diff_y_act_2$ calculated in the above-described manner.

Accordingly, the estimated inverted pendulum mass point lateral movement amount $Pb_diff_y_act$ is determined by the following expression (53).

$$\begin{aligned} Pb_diff_y_act &= Pb_diff_y_act_1 + Pb_diff_y_act_2 \\ &= \phi b_act * (-h') + Plfy(\delta f_act) \end{aligned} \quad (53)$$

In the above expression (53), the first term on the right side is a linear term with respect to the detected roll angle ϕb_act , and the second term on the right side is a nonlinear term with respect to the detected front-wheel steering angle δf_act .

It should be noted that the second term on the right side of the expression (53) can be ignored when the magnitude of the value $Plfy(\delta f_act)$ of the aforesaid conversion function $Plfy(\delta f)$ corresponding to the actual steering angle δf_act of the front wheel 3f is sufficiently small (when the magnitude of δf_act is small). In this case, the detected roll angle ϕb_act of the vehicle body 2 may be used instead of the estimated inverted pendulum mass point lateral movement amount $Pb_diff_y_act$.

With this configuration, the processing in the estimated inverted pendulum mass point lateral movement amount calculating section 31 becomes unnecessary, and the computational load of the control device 50 can be reduced.

Next, the control device 50 carries out the processing in the estimated inverted pendulum mass point lateral velocity calculating section 32. As shown in FIG. 13, the estimated inverted pendulum mass point lateral velocity calculating section 32 receives the estimated inverted pendulum mass point lateral movement amount $Pb_diff_y_act$ calculated in the estimated inverted pendulum mass point lateral movement amount calculating section 31, a detected front-wheel steering angle δf_act , and an estimated front-wheel rotational transfer velocity Vf_act .

It should be noted that the estimated front-wheel rotational transfer velocity Vf_act is a velocity which is calculated by multiplying a detected value (observed value) of the rotational angular velocity of the front wheel 3f, indicated by an output from the aforesaid front-wheel rotational speed detector 54, by a predetermined effective rolling radius of the front wheel 3f.

The estimated inverted pendulum mass point lateral velocity calculating section 32 carries out the processing shown in the block diagram in FIG. 26 to calculate an estimated inverted pendulum mass point lateral velocity Vby_act .

This processing is configured to sum up a first estimated lateral velocity component Vby_act_1 , which is an estimate of the actual transfer velocity (relative to the origin) in the Y-axis direction of the inverted pendulum mass point 123 as seen from the origin of the XYZ coordinate system set in the above-described manner for the two-wheeled vehicle 1A, and a second estimated lateral velocity component Vby_act_2 , which is an estimate of the actual transfer velocity in the Y-axis direction of the inverted pendulum mass point 123 (=transfer velocity of the origin of the XYZ coordinate system) caused by the translational movement of the two-

wheeled vehicle 1A accompanying the rolling of the front wheel 3f while the front wheel 3f is being steered (when the actual steering angle of the front wheel 3f is not "0"), to thereby calculate the estimated inverted pendulum mass point lateral velocity Vby_act .

In FIG. 26, a processing section 32-1 represents a processing section which obtains the first estimated lateral velocity component Vby_act_1 , a processing section 32-2 represents a processing section which obtains the second estimated lateral velocity component Vby_act_2 , and a processing section 32-3 represents a processing section which sums up the first estimated lateral velocity component Vby_act_1 and the second estimated lateral velocity component Vby_act_2 .

The processing section 32-1 calculates, as the first estimated lateral velocity component Vby_act_1 , a temporal change rate $Pb_diff_y_dot_act$ (amount of change per unit time) at the current time of the estimated inverted pendulum mass point lateral movement amount $Pb_diff_y_act$ successively calculated by the estimated inverted pendulum mass point lateral movement amount calculating section 31. That is, the processing section 32-1 calculates a differential value $Pb_diff_y_dot_act$ of $Pb_diff_y_act$ as Vby_act_1 .

Further, the processing section 32-2 multiplies, in a processing section 32-2-1, a detected front-wheel steering angle δf_act at the current time by a cosine value $\cos(\theta cf)$ of the caster angle θcf of the front wheel 3f, to thereby calculate the estimated front-wheel effective steering angle $\delta'f_act$, which was described above in conjunction with the processing in the estimated vehicle speed calculating section 33.

The processing section 32-2 further calculates a sine value $\sin(\delta'f_act)$ of the calculated, estimated front-wheel effective steering angle $\delta'f_act$ and multiplies the estimated front-wheel rotational transfer velocity Vf_act at the current time by the sine value, in a processing section 32-2-2 and a processing section 32-2-3, to thereby calculate a transfer velocity in the Y-axis direction (in other words, a component in the Y-axis direction of Vf_act) of the ground contact part of the front wheel 3f.

Further, the processing section 32-2 multiplies, in a processing section 32-2-4, the value as a result of calculation in the processing section 32-2-3 by Lr/L (where $L=Lf+Lr$), to obtain a second estimated lateral velocity component Vby_act_2 ($=Vf_act*\sin(\delta'f_act)*(Lr/L)$).

It should be noted that Lr in this processing refers to a distance in the X-axis direction between the ground contact point of the rear wheel 3r and the overall center of gravity G in the basic posture state of the two-wheeled vehicle 1A, and Lf refers to a distance in the X-axis direction between the ground contact point of the front wheel 3f and the overall center of gravity G in the basic posture state of the two-wheeled vehicle 1A.

The values of Lr and Lf have been preset for the two-wheeled vehicle 1A and are stored in a memory in the control device 50.

The value of the caster angle θcf used in the processing in the processing section 32-2 has also been preset for the two-wheeled vehicle 1A, as with the values of Lf and Lr , and is stored in the memory in the control device 50.

The estimated inverted pendulum mass point lateral velocity calculating section 32 sums up, in the processing section 32-3, the first estimated lateral velocity component Vby_act_1 and the second estimated lateral velocity component Vby_act_2 calculated in the above-described manner, to calculate an estimated inverted pendulum mass point lateral velocity Vby_act .

51

Accordingly, the estimated inverted pendulum mass point lateral velocity V_{by_act} is calculated by the following expression (54).

$$\begin{aligned} V_{by_act} &= V_{by_act_1} + V_{by_act_2} \\ &= P_{b_diff_y_dot_act} + V_{f_act} * \sin(\delta'_{f_act}) * (Lr/L) \\ &= P_{b_diff_y_dot_act} + V_{f_act} * \\ &\quad \sin(\delta_{f_act} * \cos(\theta_{cf})) * (Lr/L) \end{aligned} \quad (54)$$

It should be noted that in the case where the magnitude of the value of the aforesaid conversion function $Plfy(\delta f)$ corresponding to the actual steering angle δf_{act} of the front wheel $3f$ is sufficiently small (when the magnitude of δf_{act} is small), a differential value of the value of $P_{b_diff_y_act}$ obtained by ignoring the second term on the right side of the expression (53) may be adopted as $P_{b_diff_y_dot_act}$ for use in the expression (54). That is, in the expression (54), a value, multiplied by $-h'$, of the differential value of the detected roll angle ϕ_{b_act} of the vehicle body 2 may be used instead of $P_{b_diff_y_dot_act}$. With this configuration, the computational load of the control device 50 can be reduced.

Next, the control device 50 carries out the processing in the desired posture state determining section 34 . The desired posture state determining section 34 determines a desired inverted pendulum mass point lateral movement amount $P_{b_diff_y_cmd}$, which is a desired value of the inverted pendulum mass point lateral movement amount $P_{b_diff_y}$, and a desired inverted pendulum mass point lateral velocity V_{by_cmd} , which is a desired value of the inverted pendulum mass point lateral velocity V_{by} . In the present embodiment, the desired posture state determining section 34 sets both of $P_{b_diff_y_cmd}$ and V_{by_cmd} to zero, by way of example.

Next, the control device 50 carries out the processing in the posture control arithmetic section 38 . As shown in FIG. 13, the posture control arithmetic section 38 receives the desired inverted pendulum mass point lateral movement amount $P_{b_diff_y_cmd}$ and the desired inverted pendulum mass point lateral velocity V_{by_cmd} determined in the desired posture state determining section 34 , the estimated inverted pendulum mass point lateral movement amount $P_{b_diff_y_act}$ calculated in the estimated inverted pendulum mass point lateral movement amount calculating section 31 , the estimated inverted pendulum mass point lateral velocity V_{by_act} calculated in the estimated inverted pendulum mass point lateral velocity calculating section 32 , and posture control gains $K1$, $K2$, $K3$, and $K4$ (hereinafter, also simply referred to as "gains $K1$, $K2$, $K3$, and $K4$ ") determined in the control gain determining section 35 in the manner as will be described later.

The posture control arithmetic section 38 uses the above-described input values to carry out the processing shown in the block diagram in FIG. 27, to thereby determine a desired front-wheel steering angle δf_{cmd} , a desired front-wheel steering angular velocity δf_{dot_cmd} , and a desired front-wheel steering angular acceleration δf_{dot2_cmd} .

In FIG. 27, a processing section $38-1$ represents a processing section which obtains a deviation of $P_{b_diff_y_act}$ from $P_{b_diff_y_cmd}$, a processing section $38-2$ represents a processing section which multiplies the output of the processing section $38-1$ by the gain $K1$, a processing section $38-3$ represents a processing section which obtains a deviation of V_{by_act} from V_{by_cmd} , a processing section $38-4$ represents a processing section which multiplies the output of the process-

52

ing section $38-3$ by the gain $K2$, a processing section $38-5$ represents a processing section which multiplies a last time's desired front-wheel steering angle δf_{cmd_p} , which is a value of the desired front-wheel steering angle δf_{cmd} determined in the last time's control processing cycle, by the gain $K3$, a processing section $38-6$ represents a processing section which multiplies a last time's desired front-wheel steering angular velocity $\delta f_{dot_cmd_p}$, which is a value of the desired front-wheel steering angular velocity δf_{dot_cmd} determined in the last time's control processing cycle, by the gain $K4$, and a processing section $38-7$ represents a processing section which sums up the outputs from the processing sections $38-2$ and $38-4$ and the values, each multiplied by -1 , of the outputs from the processing sections $38-5$ and $38-6$, to thereby calculate a desired front-wheel steering angular acceleration δf_{dot2_cmd} .

Further, a processing section $38-8$ represents a processing section which integrates the output of the processing section $38-7$ to obtain a desired front-wheel steering angular velocity δf_{dot_cmd} , a processing section $38-9$ represents a delay element which outputs the output from the processing section $38-8$ in the last time's control processing cycle (i.e. last time's desired front-wheel steering angular velocity $\delta f_{dot_cmd_p}$) to the processing section $38-6$, a processing section $38-10$ represents a processing section which integrates the output of the processing section $38-8$ to obtain a desired front-wheel steering angle δf_{cmd} , and a processing section $38-11$ represents a delay element which outputs the output from the processing section $38-10$ in the last time's control processing cycle (i.e. last time's desired front-wheel steering angle δf_{cmd_p}) to the processing section $38-5$.

Accordingly, the posture control arithmetic section 38 calculates the desired front-wheel steering angular acceleration δf_{dot2_cmd} by the following expression (55).

$$\begin{aligned} \delta f_{dot2_cmd} &= (K1 * (P_{b_diff_y_cmd} - P_{b_diff_y_act}) + \\ &\quad K2 * (V_{by_cmd} - V_{by_act}) - \\ &\quad K3 * \delta f_{cmd_p} - K4 * \delta f_{dot_cmd_p}) \end{aligned} \quad (55)$$

In the above expression (55), $K1 * (P_{b_diff_y_cmd} - P_{b_diff_y_act})$ is a feedback manipulated variable having the function of making the deviation $(P_{b_diff_y_cmd} - P_{b_diff_y_act})$ approach "0", $K2 * (V_{by_cmd} - V_{by_act})$ is a feedback manipulated variable having the function of making the deviation $(V_{by_cmd} - V_{by_act})$ approach "0", $-K3 * \delta f_{cmd_p}$ is a feedback manipulated variable having the function of making δf_{cmd} approach "0", and $-K4 * \delta f_{dot_cmd_p}$ is a feedback manipulated variable having the function of making δf_{dot_cmd} approach "0".

The posture control arithmetic section 38 integrates δf_{dot2_cmd} , determined by the above expression (55), to determine a desired front-wheel steering angular velocity δf_{dot_cmd} . Further, the posture control arithmetic section 38 integrates this δf_{dot_cmd} to determine a desired front-wheel steering angle δf_{cmd} .

It should be noted that δf_{cmd_p} and $\delta f_{dot_cmd_p}$ used in the computation of the expression (55) have the meanings as pseudo estimates (alternative observed values) of the actual steering angle and steering angular velocity, respectively, of the front wheel $3f$ at the current time. Therefore, instead of δf_{cmd_p} , a detected front-wheel steering angle δf_{act} at the current time may be used. Further, instead of $\delta f_{dot_cmd_p}$, a detected front-wheel steering angular velocity δf_{dot_act} at the current time may be used.

The above has described the details of the processing in STEP 408.

In accordance with the processing in STEP 408 described above, the desired front-wheel steering angular acceleration δf_dot2_cmd is determined such that any divergence of the actual inverted pendulum mass point lateral movement amount (estimated inverted pendulum mass point lateral movement amount $Pb_diff_y_act$) of the two-wheeled vehicle 1A from the desired inverted pendulum mass point lateral movement amount $Pb_diff_y_cmd$, or any divergence of the actual inverted pendulum mass point lateral velocity (estimated inverted pendulum mass point lateral velocity Vby_act) of the two-wheeled vehicle 1A from the desired inverted pendulum mass point lateral velocity Vby_cmd , is eliminated through manipulation of the steering angle δf of the front wheel 3f (and, hence, that the actual inverted pendulum mass point lateral movement amount or lateral velocity of the two-wheeled vehicle 1A is restored to the desired inverted pendulum mass point lateral movement amount $Pb_diff_y_cmd$ or desired inverted pendulum mass point lateral velocity Vby_cmd).

Further, in the present embodiment, the desired inverted pendulum mass point lateral movement amount $Pb_diff_y_cmd$ is "0". Therefore, in the state where the actual inverted pendulum mass point lateral movement amount of the two-wheeled vehicle 1A is held at a value which coincides, or almost coincides, with the desired inverted pendulum mass point lateral movement amount $Pb_diff_y_cmd$, the desired front-wheel steering angular acceleration δf_dot2_cmd is determined so as to keep the actual steering angle of the front wheel 3f at "0" or almost "0".

Consequently, the front wheel 3f is steered to stabilize the posture in the roll direction of the vehicle body 2 and to make the steering angle δf_act of the front wheel 3f ultimately converge to the neutral steering angle (zero).

The processing in STEP 407 will now be described. In STEP 407, the control device 50 determines the posture control gains K1, K2, K3, and K4 for use in the computation of the aforesaid expression (55), by the processing in the control gain determining section 35 shown in FIG. 13.

As shown in FIG. 13, the control gain determining section 35 receives an estimated vehicle speed Vox_act at the current time, calculated by the processing in the estimated vehicle speed calculating section 33, and a detected trail t_act at the current time. The control gain determining section 35 also receives, via a delay element 39, a last time's desired front-wheel steering angle δf_cmd_p , determined by the posture control arithmetic section 38.

It should be noted that the last time's desired front-wheel steering angle δf_cmd_p has the meaning as a pseudo estimate (alternative observed value) of the actual steering angle of the front wheel 3f at the current time. Therefore, it may be configured such that, instead of δf_cmd_p , a detected front-wheel steering angle δf_act at the current time, indicated by an output from the front-wheel steering angle detector 52, is input to the control gain determining section 35.

The control gain determining section 35 first determines, from the estimated vehicle speed Vox_act , the last time's desired front-wheel steering angle δf_cmd_p , and the detected trail t_act input thereto, desired values $K1_cmd$, $K2_cmd$, $K3_cmd$, and $K4_cmd$ of the respective gains K1, K2, K3, and K4, by processing in processing sections 35-1, 35-2, 35-3, and 35-4 shown in the block diagram in FIG. 28.

Each processing section 35-*i* (*i*=1, 2, 3, 4) determines the desired value Ki_cmd of the gain Ki by, for example, a conversion function Ki (Vox , δf , t) which is defined by a preset three-dimensional mapping.

In this case, in the present embodiment, the desired value Ki_cmd of each gain Ki is determined, in accordance with Vox_act , δf_cmd_p , and t_act , such that it changes with the trends as shown in FIGS. 29A to 29C with respect to the vehicle speed Vox , the front-wheel steering angle δf , and the trail t .

Specifically, in the case where the front-wheel steering angle δf and the trail t are kept constant, each Ki_cmd is determined with the trend as shown in FIG. 29A such that the magnitude of Ki_cmd becomes smaller (approaches zero) as the vehicle speed Vox becomes higher. Particularly, Ki_cmd is determined such that its magnitude becomes zero or almost zero when the vehicle speed Vox is in a high-speed range (higher than a prescribed vehicle speed $Vox5$ in FIG. 29A).

In the case where the vehicle speed Vox and the trail t are kept constant, each Ki_cmd is determined with the trend as shown in FIG. 29B such that the magnitude of Ki_cmd becomes smaller (approaches zero) as the magnitude (absolute value) of the front-wheel steering angle δf becomes larger.

Further, in the case where the vehicle speed Vox and the front-wheel steering angle δf are kept constant, each Ki_cmd is determined with the trend as shown in FIG. 29C such that the magnitude of Ki_cmd becomes larger as the trail t becomes larger (as it is closer to the upper trail limit tp (>0)).

After determining the desired value Ki_cmd of each gain Ki in the above-described manner, the control gain determining section 35 determines a value of each gain Ki which is actually used for the computation of the aforesaid expression (55).

Specifically, the control gain determining section 35 determines the value of each gain Ki (*i*=1, 2, 3, 4) at each control processing cycle such that it gradually approaches (gradually converges to) the desired value Ki_cmd . For example, a deviation of the last time's value of the gain Ki (that was determined in the last time's control processing cycle) from the desired value Ki_cmd determined in the current time's control processing cycle is obtained, and the amount of change determined in accordance with the deviation (for example, a value obtained by multiplying the deviation by a prescribed proportionality constant) is added to the last time's value of the gain Ki , to thereby determine the current time's value (value in the current time's control processing cycle) of the gain Ki .

The above has described the details of the processing in STEP 407. In this case, each gain Ki (*i*=1, 2, 3, 4) is determined basically with the trend as shown in FIG. 29A with respect to the vehicle speed Vox (estimated vehicle speed Vox_act). Therefore, when the two-wheeled vehicle 1A is stopped or traveling at a low speed, the front wheel 3f is steered by the aforesaid steering actuator 8 in accordance with the desired front-wheel steering angular acceleration δf_dot2_cmd , the desired front-wheel steering angular velocity δf_dot_cmd , and the desired front-wheel steering angle δf_cmd determined in the above-described manner by the posture control arithmetic section 38, so that the posture control function for stabilizing the posture in the roll direction of the two-wheeled vehicle 1A works effectively. That is, when the estimated inverted pendulum mass point lateral movement amount $Pb_diff_y_act$ or the estimated inverted pendulum mass point lateral velocity Vby_act deviates from a required or desired value, the front wheel 3f is steered to quickly eliminate the deviation (and, hence, to quickly stabilize the posture in the roll direction of the vehicle body 2).

On the other hand, when the vehicle speed Vox of the two-wheeled vehicle 1A has increased to a certain level, even if the estimated inverted pendulum mass point lateral move-

ment amount $Pb_diff_y_act$ or the estimated inverted pendulum mass point lateral velocity Vby_act deviates from the required or desired value, the posture control function for eliminating the deviation is weakened, or set to a substantially off state (disabled state). Accordingly, in the case where a rider is riding the two-wheeled vehicle 1A at a vehicle speed in a high-speed range, the rider can readily bank the vehicle body 2 for turning. That is, it is possible to make the behavioral characteristics of the two-wheeled vehicle 1A approach the characteristics comparable to those of a conventional two-wheeled vehicle.

Further, each gain K_i ($i=1, 2, 3, 4$) is determined basically with the trend as shown in FIG. 29B with respect to the front-wheel steering angle δf (last time's desired front-wheel steering angle δf_cmd_p).

Here, in the case where the magnitude of the actual steering angle δf_act of the front wheel 3f is large, compared to the case where it is small, the radius of curvature of the ground contact part of the front wheel 3f as seen in a cross section including the ground contact point of the front wheel 3f and having a normal in the X-axis direction (longitudinal direction of the vehicle body 2) becomes larger.

Therefore, in the case where the magnitude of the actual steering angle δf_act of the front wheel 3f is large, compared to the case where it is small, the change in movement amount of the ground contact point of the front wheel 3f responsive to the change in the steering becomes larger. Because of this, if the magnitudes of the gains K_1 and K_2 in particular are set independently of the actual steering angle δf_act , oscillation is likely to occur in the control of the posture in the roll direction of the vehicle body 2 of the two-wheeled vehicle 1A.

When it is configured such that the magnitudes of the gains K_1 and K_2 are changed in accordance with the magnitude of δf_cmd_p , as described above, the above-described oscillation can be prevented even in the case where the magnitude (absolute value) of the actual steering angle δf_act of the front wheel 3f is large.

Further, each gain K_i ($i=1, 2, 3, 4$) is determined basically with the trend as shown in FIG. 29C with respect to the trail t (detected trail t_act).

Here, as understood from the description about the two-wheeled vehicle 1 shown in FIG. 1, the sensitivity of the change in the aforesaid posture controlling manipulation moment $Msum$ to the change in the steering angle δf is higher when the actual trail t_act is closer to the lower trail limit t_n (<0) than to the upper trail limit t_p (>0) (i.e. when the aforesaid height a is smaller).

Because of this, if the magnitudes of particularly the gains K_1 and K_2 are set independently of the actual trail t_act , oscillation is likely to occur in the control of the posture in the roll direction of the vehicle body 2 when the actual trail t_act is equal to or close to the lower trail limit t_n . Further, when the actual trail t_act is equal to or close to the upper trail limit t_p , the function of controlling the posture in the roll direction of the vehicle body 2 may not work sufficiently.

In contrast, when it is configured such that the magnitudes of the gains K_1 and K_2 are changed in accordance with t_act as described above, a proper posture control function can be implemented stably, irrespective of the actual trail t_act , without causing the oscillation in the control of the posture in the roll direction of the vehicle body 2.

The above has described the processing in the balance-assist-on/travel-assist-off mode. With this processing, except for the case where an anomaly has been detected, or the travel-assist switch 59 has been turned on, or the balance-off switch 58 has been turned on, the operating mode in the next

time's control processing cycle is maintained in the balance-assist-on/travel-assist-off mode. When an anomaly has been detected, the travel-assist switch 59 has been turned on, or the balance-off switch 58 has been turned on, the operating mode in the next time's control processing cycle shifts to the abnormal mode, the balance-assist-on/travel-assist-on mode, or the balance-assist-off/travel-assist-off mode, respectively.

Further, in the balance-assist-on/travel-assist-off mode, the travel-assist actuator 27 is in the off state. Therefore, the rider of the two-wheeled vehicle 1A can move the two-wheeled vehicle 1A by holding the operation apparatus 7 and causing the front wheel 3f and the rear wheel 3r to roll.

At the same time, in the balance-assist-on/travel-assist-off mode, particularly when the two-wheeled vehicle 1A is stopped or running in a low vehicle speed range, the front wheel 3f is steered by the steering force of the steering actuator 8, as appropriate, such that the posture in the roll direction of the vehicle body 2 is stabilized autonomously.

Further, in the balance-assist-on/travel-assist-off mode, the trail t is controlled to match the lower trail limit to (<0) when the two-wheeled vehicle 1A is stopped or running in a low vehicle speed range. This ensures that the posture control function according to the steering of the front wheel 3f (the function of generating a moment in the roll direction for making the posture of the vehicle body 2 restored to a desired posture (posture in the basic posture state) by the steering of the front wheel 3f) works effectively, so that the stability of the posture in the roll direction of the vehicle body 2 can be enhanced.

Supplementally, in the processing in the control gain determining section 35, each gain K_i ($i=1, 2, 3, 4$) was determined in accordance with Vox_act , δf_cmd_p , and t_act , by using a three-dimensional mapping. Alternatively, each gain K_i may be determined by a technique not using the three-dimensional mapping.

Further, the last time's desired front-wheel steering angle δf_cmd_p has the meaning as a pseudo estimate (alternative observed value) of the actual steering angle of the front wheel 3f at the current time.

Accordingly, for determining each gain K_i , the aforesaid detected front-wheel steering angle δf_act may be used instead of δf_cmd_p .

Further, in the case where the response of the travel-assist actuator 27 is sufficiently quick, the desired vehicle speed Vox_cmd determined in the desired vehicle speed determining section 36 in the last time's control processing cycle (hereinafter, this will be denoted as "last time's desired vehicle speed Vox_cmd_p ") has the meaning as a pseudo estimate (alternative observed value) of the actual vehicle speed of the two-wheeled vehicle 1A at the current time.

Accordingly, for determining each gain K_i , the above-described last time's desired vehicle speed Vox_cmd_p may be used instead of Vox_act .

The processing in the balance-assist-on/travel-assist-on mode is carried out as shown by a flowchart in FIG. 20.

First, in STEPS 501 to 509, the control device 50 carries out the processes identical to those in STEPS 401 to 409 in the aforesaid balance-assist-on/travel-assist-off mode.

Next, in STEP 510, the control device 50 determines a desired vehicle speed Vox_cmd of the two-wheeled vehicle 1A, and controls the travel-assist actuator 27 in accordance with the desired vehicle speed Vox_cmd . The process in this STEP 510 is identical to that in STEP 309 in the aforesaid balance-assist-off/travel-assist-on mode.

Next, in STEP 511, the control device 50 carries out the determination process which is identical to that in STEP 107 in the aforesaid initialization mode. That is, the control device

57

50 determines whether a prescribed anomaly has been detected. If no anomaly has been detected, in **STEP 512**, the control device **50** determines the operational state of the balance-off switch **58**.

If it is determined in **STEP 512** that the balance-off switch **58** remains in the off state, in **STEP 513**, the control device **50** sets the operating mode in the next time's control processing cycle to the balance-assist-on/travel-assist-on mode (which is the same mode as in the current time's control processing cycle), and terminates the processing in the balance-assist-on/travel-assist-on mode in the current time's control processing cycle.

If it is determined in **STEP 512** that the balance-off switch **58** has been turned on, in **STEP 515**, the control device **50** sets the operating mode in the next time's control processing cycle to the balance-assist-off/travel-assist-on mode, and terminates the processing in the balance-assist-on/travel-assist-on mode in the current time's control processing cycle.

Further, if it is determined in the aforesaid **STEP 511** that an anomaly has been detected, in **STEP 514**, the control device **50** sets the operating mode in the next time's control processing cycle to the abnormal mode, and terminates the processing in the balance-assist-on/travel-assist-on mode in the current time's control processing cycle.

The above has described the processing in the balance-assist-on/travel-assist-on mode. With this processing, except for the case where an anomaly has been detected, or the balance-off switch **58** has been turned on, the operating mode in the next time's control processing cycle is maintained in the balance-assist-on/travel-assist-on mode. When an anomaly has been detected, or the balance-off switch **58** has been turned on, the operating mode in the next time's control processing cycle shifts to the abnormal mode, or the balance-assist-off/travel-assist-on mode, respectively.

In the balance-assist-on/travel-assist-on mode, as the rider manipulates the accelerator, the front wheel **3f** is rotatively driven by the driving force of the travel-assist actuator **27**, thereby allowing the two-wheeled vehicle **1A** to travel by that driving force.

At the same time, in the balance-assist-on/travel-assist-on mode, primarily when the two-wheeled vehicle **1A** is stopped or traveling in a low vehicle speed range, the front wheel **3f** is steered by the steering force of the steering actuator **8**, as appropriate, such that the posture in the roll direction of the vehicle body **2** is stabilized autonomously, as in the balance-assist-on/travel-assist-off mode.

Further, at this time, the control is performed such that the trail t matches the lower trail limit t_0 (<0). This enables the posture control function according to the steering of the front wheel **3f** to work effectively, to thereby enhance the stability of the posture in the roll direction of the vehicle body **2**.

On the other hand, when the two-wheeled vehicle **1A** is traveling in a high vehicle speed range, the control is performed such that the trail t matches the upper trail limit t_p . In this case, the upper trail limit t_p takes a positive value. This enables a proper self-steering function to work in the two-wheeled vehicle **1A**, leading to improved operation stability.

In addition, when the two-wheeled vehicle **1A** is traveling in a high vehicle speed range, the posture control function according to the steering of the front wheel **3f** is sufficiently weakened, or set to a substantially disabled state. This allows the rider to readily bank the vehicle body **2** by shifting the body weight. Further, the rider can freely steer the front wheel **3f** by operating the operation apparatus **7**.

That is, during the traveling of the two-wheeled vehicle **1A** in a high vehicle speed range, the rider can drive the two-

58

wheeled vehicle **1A** with the driving characteristics similar to those of a conventional two-wheeled vehicle.

Further, during the traveling of the two-wheeled vehicle **1A** in a high vehicle speed range, in the state where the trail t_{act} matches the upper trail limit t_p , the lock mechanism **15a** is activated to fixedly hold the trail t_{act} at the upper trail limit t_p . Therefore, in this state, the trail adjustment actuator **15** can be turned off to save the electricity otherwise consumed by the trail adjustment actuator **15**. Further, the stiffness of the steering system of the front wheel **3f** during the traveling of the two-wheeled vehicle **1A** in a high vehicle speed range can be improved.

The processing in the abnormal mode is carried out as shown by a flowchart in **FIG. 21**.

In **STEPS 601 to 606**, the control device **50** carries out the processes identical to those in **STEPS 101 to 106** in the aforesaid initialization mode, and terminates the processing in the abnormal mode.

In this manner, the trail t is locked, and the actuators **8**, **15**, and **27** are set to the off state.

It should be noted that, in this case, a certain annunciator (alarm) provided at the operation apparatus **7** or the like gives the rider a warning (for example, visual or audio warning) that there has occurred an anomaly in the two-wheeled vehicle **1A**.

The above has described the details of the control processing in the control device **50** according to the present embodiment.

Here, the correspondence between the present embodiment and the present invention will be described. In the present embodiment, the control device **50** has the functions as the steering control section and the trail control section in the present invention.

In this case, the function as the steering control section is implemented by the processes in **STEPS 407 to 409** in the aforesaid balance-assist-on/travel-assist-off mode, or by the processes in **STEPS 507 to 509** in the aforesaid balance-assist-on/travel-assist-on mode.

The function as the trail control section is implemented by the processes in **STEPS 401 to 404** in the balance-assist-on/travel-assist-off mode, or by the processes in **STEPS 501 to 504** in the balance-assist-on/travel-assist-on mode.

In the function as the trail control section of the control device **50**, the trail adjustment actuator **15** is controlled to change the trail t_{act} , in accordance with the vehicle speed V_{ox_act} , between the upper trail limit t_p (>0) and the lower trail limit t_0 (<0).

In this case, in a low vehicle speed range including the case where the vehicle speed V_{ox_act} is zero (in the vehicle speed range of lower than V_{ox2} in the example shown in **FIG. 23** or in the vehicle speed range of lower than V_{ox3} in the example shown in **FIG. 24**), the trail is controlled to a smaller value ($=t_n$) than that in a high vehicle speed range (in the vehicle speed range of higher than V_{ox1} in the example shown in **FIG. 23** or in the vehicle speed range of higher than V_{ox3} in the example shown in **FIG. 24**).

It should be noted that, in the example shown in **FIG. 23**, V_{ox1} and V_{ox2} correspond to the first prescribed speed and the second prescribed speed, respectively, in the present invention. In the example shown in **FIG. 24**, V_{ox3} corresponds to the first prescribed speed in the present invention.

Further, in the state where the trail t_{act} coincides, or almost coincides, with the upper trail limit t_p , the swing section **14**, corresponding to the mobile section in the present invention, is mechanically locked to be non-swingable, by the lock mechanism **15a**. With this configuration, the trail t_{act} is

mechanically held at t_p , without the need of the driving force of the trail adjustment actuator **15**.

Further, in the function as the steering control section of the control device **50**, in order to stabilize the posture of the vehicle body **2**, the steering actuator **8** (electric motor) is controlled to make the inverted pendulum mass point lateral movement amount and inverted pendulum mass point lateral velocity, each representing the motional state quantity of the inverted pendulum mass point **123**, approach (or converge to) zero as their desired values ($Pb_diff_y_cmd$, Vby_cmd), and also make the steering angle and steering angular velocity, each representing the motional state quantity of the steering angle of the steered wheel (front wheel **3f**), approach (or converge to) zero as their desired values.

Specifically, in the processing in the posture control arithmetic section **38**, the desired front-wheel steering angular acceleration δf_dot2_cmd as an operational target of the steering actuator **8** is determined, by a feedback control law, so as to cause a deviation of each of the estimated inverted pendulum mass point lateral movement amount $Pb_diff_y_act$, the estimated inverted pendulum mass point lateral velocity Vby_act , the last time's desired front-wheel steering angle δf_cmd_p , representing a pseudo estimate of the steering angle δf , and the last time's desired front-wheel steering angular velocity $\delta f_dot_cmd_p$, representing a pseudo estimate of the steering angular velocity δf_dot , from the corresponding desired value to converge to zero.

Further, the steering force of the steering actuator **8** is controlled by the control device **50** such that the actual steering angle of the front wheel **3f** tracks a desired front-wheel steering angle δf_cmd which has been determined by performing integration twice on the above-described δf_dot2_cmd .

In this manner, the steering actuator **8** is controlled so as to stabilize the motional state quantity of the inverted pendulum mass point **123** and the motional state quantity of the steering angle of the front wheel **3f** (steered wheel) and, hence, to stabilize the posture (in the roll direction) of the vehicle body **2**.

It should be noted that the inverted pendulum mass point lateral movement amount Pb_diff_y has the meaning as the inclination state quantity in the present invention.

Supplementally, in the present embodiment, the lower trail limit t_n , which is the desired trail t_cmd when the vehicle speed Vox_act is zero, takes a negative value. Accordingly, t_n is the trail which satisfies the condition that $a < a_sum$ (in other words, the condition that $t_n < a_sum * \tan(\theta_{cf})$) and the condition that $a \leq a_s$ (in other words, the condition that $t_n \leq a_s * \tan(\theta_{cf})$). Further, t_n is the trail which also satisfies the condition that $a \leq Rf$ (in other words, the condition that $t_n \leq Rf * \tan(\theta_{cf})$).

Further, in the present embodiment, the steering angular acceleration δf_dot2_cmd of the front wheel **3f** corresponds to the reference quantity in the present invention.

The aforesaid gains $K1$ and $K2$ each correspond to the sensitivity Ra of the change in value of the reference quantity (δf_dot2_cmd) to the change in observed value ($Pb_diff_y_act$, Vby_act) of the motional state quantity of the inclination state quantity. Further, the aforesaid gains $K3$ and $K4$ each correspond to the sensitivity Rb of the change in value of the reference quantity (δf_dot2_cmd) to the change in observed value (δf_act , δf_dot_act) of the motional state quantity of the steering angle of the front wheel **3f**.

In this case, the gains $K1$, $K2$, $K3$, and $K4$ are each determined with the above-described characteristic (shown in FIG. **29A**) with respect to the observed value of the actual vehicle speed Vox_act of the two-wheeled vehicle **1A**. Therefore, the steering force of the steering actuator **8** is controlled such that

the magnitude of each of the above-described sensitivities Ra and Rb becomes smaller as the magnitude of the observed value of the vehicle speed Vox_act becomes larger.

Particularly, in the vehicle speed range of higher than the prescribed vehicle speed $Vox5$, the gains $K1$, $K2$, $K3$, and $K4$ each become zero (or almost zero), and accordingly, the above-described sensitivities Ra and Rb both become zero. Consequently, the steering actuator **8** enters the state where it generates substantially no steering force. It should be noted that the prescribed vehicle speed $Vox5$ corresponds to the third prescribed speed in the present invention.

Further, the gains $K1$ and $K2$ are each determined with the above-described characteristic (shown in FIG. **29B**) with respect to the observed value (δf_cmd_p) of the steering angle δf_act of the front wheel **3f**. Therefore, the steering force of the steering actuator **8** is controlled such that the magnitudes of the gains $K1$ and $K2$ each corresponding to the above-described sensitivity Ra become smaller as the magnitude of the observed value of the steering angle δf_act of the front wheel **3f** from its non-steered state becomes larger.

Further, the gains $K1$ and $K2$ are each determined with the above-described characteristic (shown in FIG. **29C**) with respect to the observed value of the trail t_act . Therefore, the steering force of the steering actuator **8** is controlled such that the magnitudes of the gains $K1$ and $K2$ each corresponding to the above-described sensitivity Ra become larger as the magnitude of the observed value of the trail t_act becomes larger.

Further, in the present embodiment, the aforesaid balance-assist-off/travel-assist-off mode and balance-assist-off/travel-assist-on mode correspond to the posture-control disabled mode in the present invention. In these balance-assist-off/travel-assist-off mode and balance-assist-off/travel-assist-on mode, the trail t_act is controlled to the upper trail limit t_p (>0) as a constant trail. Further, the steering clutch **8a**, corresponding to the clutch mechanism in the present invention, is set to the off state, and the power transmission between the steering actuator **8** and the front wheel **3f** is interrupted.

According to the present embodiment described above, in a low vehicle speed range including the case where the vehicle speed Vox_act is zero, the trail t_act is controlled to the lower trail limit to which takes a negative value (the trail that satisfies the condition that $a < a_sum$ or $a \leq a_s$ or $a \leq Rf$). Accordingly, when the posture of the vehicle body **2** of the two-wheeled vehicle **1A** deviates from a desired posture (posture in the basic posture state in the present embodiment), steering of the front wheel **3f** by the steering actuator **8** can make the posture quickly restored to the desired posture.

Further, in a high vehicle speed range, the trail t_act is controlled to the upper trail limit t_p which takes a positive value. This can assure the operation stability of the two-wheeled vehicle **1A**.

Further, in a high vehicle speed range, the posture control function is weakened, or set to a substantially disabled state. Therefore, in the case where a rider is riding the mobile vehicle at a vehicle speed in a high-speed range, the rider can readily bank the vehicle body of the mobile vehicle for turning.

[Modifications]

Several modifications related to the aforesaid embodiment will be described below.

In the aforesaid embodiment, the trail adjustment mechanism may have a structure different from the one illustrated in FIGS. **10** and **11**. The trail adjustment mechanism for making the trail of the front wheel **3f** adjustable may have any structure as long as the mechanism can adjust the trail of the front wheel **3f** by an actuator. For example, the trail adjustment mechanism may be configured to use a ball screw mechanism

61

or the like to move the front wheel **3f** linearly in the longitudinal direction with respect to the aforesaid steering rotation section **12**.

In the aforesaid embodiment, the rear wheel **3r** is a non-steered wheel. Alternatively, the rear wheel **3r** may be configured to be passively steered by, for example, the reaction force from the ground surface **110**.

Further, in the aforesaid embodiment, as the motional state quantity of the inverted pendulum mass point **123**, which is a constituent element of the controlled state quantities, the inverted pendulum mass point lateral movement amount Pb_diff_y and the inverted pendulum mass point lateral velocity Vby were used. Alternatively, the steering actuator **8** may be controlled, using only one of the above as the controlled state quantity related to the inverted pendulum mass point **123**, to cause the one state quantity to approach its desired value.

Furthermore, as the motional state quantity of the steering angle of the steered wheel, which is another constituent element of the controlled state quantities, a value of the steering angle δf and its angular velocity δf_dot were used. Alternatively, the steering actuator **8** may be controlled, using only one of the above as the controlled state quantity related to the steering angle of the steered wheel, to cause the one state quantity to approach its desired value.

It should be noted that the desired value of the motional state quantity of the inverted pendulum mass point **123** (inverted pendulum mass point lateral movement amount Pb_diff_y , inverted pendulum mass point lateral velocity Vby) may be set to a value other than zero, as long as the value can stabilize the inverted pendulum mass point **123** and, hence, can stabilize the posture of the vehicle body **2** (preventing the posture in the roll direction of the vehicle body **2** from becoming unstable).

Further, the desired value of the motional state quantity of the steering angle (steering angle δf , steering angular velocity δf_dot) of the steered wheel may be set to zero. It should be noted that the desired value of the motional state quantity of the steering angle of the steered wheel may be set to a value other than zero, as long as the value can stabilize the inverted pendulum mass point **123** and, hence, can stabilize the posture of the vehicle body **2** (preventing the posture in the roll direction of the vehicle body **2** from becoming unstable).

The desired value of the motional state quantity of the inverted pendulum mass point **123** (inverted pendulum mass point lateral movement amount Pb_diff_y , inverted pendulum mass point lateral velocity Vby), or the desired value of the motional state quantity of the steering angle (steering angle δf , steering angular velocity δf_dot) of the steered wheel, may be a value which is determined in accordance with, for example, the force applied to the operation apparatus **7** by the rider, or the manipulated variable of the operation apparatus **7**.

In the aforesaid embodiment, instead of controlling the inverted pendulum mass point lateral movement amount Pb_diff_y and the inverted pendulum mass point lateral velocity Vby , desired values may be set for the roll angle ϕb and its angular velocity of the vehicle body **2**, for example, and the steering actuator **8** may be controlled so as to cause the actual roll angle (detected roll angle ϕb_act) and its angular velocity of the vehicle body **2** to approach the desired values, to thereby stabilize the posture of the vehicle body **2**.

For example, in the aforesaid expression (55), instead of the deviations ($Pb_diff_y_cmd - Pb_diff_y_act$) and ($Vby_cmd - Vby_act$), a deviation of the detected roll angle ϕb_act from the desired value of the roll angle of the vehicle body **2** and a deviation of the detected value or estimate of the angular

62

velocity (temporal change rate of the detected roll angle ϕb_act or the like) from the desired value of the angular velocity of the roll angle, respectively, may be used to determine the desired front-wheel steering angular acceleration δf_dot2_cmd as an operational target of the steering actuator **8**.

Further, in this case, in determining the desired value of the roll angle ϕb , the centrifugal force during turning of the two-wheeled vehicle **1A** may be taken into account. That is, the desired value of the roll angle ϕb may be determined such that a moment generated about the origin of the XYZ coordinate system in the direction about the X axis (roll direction) due to the gravitational force acting on the overall center of gravity G of the two-wheeled vehicle **1A** and a moment generated about the origin of the XYZ coordinate system in the direction about the X axis (roll direction) due to the centrifugal force acting on the overall center of gravity G are balanced (so that the sum of the moments becomes "0").

In this case, the desired value of the roll angle ϕb (hereinafter, referred to as "desired roll angle ϕb_cmd ") can be determined, for example, in the following manner. Hereinafter, the roll angle ϕb in the state where the moments generated about the origin of the XYZ coordinate system due to the gravitational force and the centrifugal force acting on the overall center of gravity G are balanced with each other will be called a "balanced roll angle ϕb_lean ".

This balanced roll angle ϕb_lean is obtained approximately by the following expression (61).

$$\phi b_lean = -Vox_act * \omega z_act / g \quad (61)$$

Here, ωz_act represents a turning angular velocity about the vertical axis (yaw rate) of the vehicle body **2**. For this value, for example, a detected value of the yaw rate, which is indicated by an output from the aforesaid vehicle-body inclination detector **51** including the angular velocity sensor, may be used.

Alternatively, it may be obtained from, for example, an actual value of the aforesaid front-wheel effective steering angle $\delta'f$ (estimated front-wheel effective steering angle $\delta'f_act$), an actual value of the rear-wheel effective steering angle $\delta'r$ (estimated rear-wheel effective steering angle $\delta'r_act$), and an actual value of the vehicle speed Vox (estimated vehicle speed Vox_act) of the two-wheeled vehicle **1A**, by the following expression (62).

$$\omega z_act = Vox_act * ((1/L) * \tan(\delta'f_act) - (1/L) * \tan(\delta'r_act)) \quad (62)$$

It should be noted that the rear-wheel effective steering angle $\delta'r$ corresponds to the rotational angle in the yaw direction of the rear wheel **3r**. Therefore, the estimated rear-wheel effective steering angle $\delta'r_act$, which is an estimate of the actual value $\delta'r_act$ of the rear-wheel effective steering angle $\delta'r$, may be calculated by multiplying the detected value of the actual steering angle of the rear wheel **3r** by a cosine value of the caster angle of the rear wheel **3r**, for example, as in the case of calculating the estimated front-wheel effective steering angle $\delta'f_act$.

In the case where the rear wheel **3r** is a non-steered wheel, as in the case of the two-wheeled vehicle **1A** described in the aforesaid embodiment, the computation of the expression (62) can be performed by setting: $\delta'r_act = 0$.

The balanced roll angle ϕb_lean calculated in the above-described manner may be determined as a desired value of the desired roll angle ϕb_cmd . Alternatively, a value obtained by multiplying ϕb_lean by a positive constant of 1 or less may be determined as the desired roll angle ϕb_cmd .

63

It should be noted that the desired roll angle ϕ_b_cmd may be "0" when the two-wheeled vehicle 1A is stopped before it starts moving, or when the vehicle speed V_{ox_act} is sufficiently low.

Further, the desired value of the angular velocity of the roll angle ϕ_b may be set to zero. It should be noted that the desired value of the angular velocity of the roll angle ϕ_b may be set to a value other than zero, as long as the value can stabilize the posture of the vehicle body 2.

For example, the desired value of the angular velocity of the roll angle ϕ_b may be determined in accordance with the force applied to the operation apparatus 7 by the rider, or the like.

In the aforesaid embodiment, in the processing in the posture control arithmetic section 38, the desired front-wheel steering angular acceleration δf_dot2_cmd was determined as an operational target of the steering actuator 8.

Alternatively, a desired value of the torque about the steering axis C_{sf} of the front wheel 3f may be determined instead of the desired front-wheel steering angular acceleration δf_dot2_cmd . Then, the steering force (torque) of the steering actuator 8 may be controlled to cause the actual torque about the steering axis C_{sf} to match the desired value.

Further, in the aforesaid embodiment, the lower trail limit t_n as a desired trail t_cmd at the time when the two-wheeled vehicle 1A is stopped or traveling in a low vehicle speed range was set to be negative. Consequently, the height a of the aforesaid intersection point E_f corresponding to the lower trail limit t_n was made to take a negative value. Alternatively, the desired trail t_cmd at the time when the two-wheeled vehicle 1A is stopped or traveling in a low vehicle speed range may be determined to satisfy: $a < a_sum$, or $a \leq a_s$, or $a \leq R_f$, or $a \leq 0$.

Further, in the aforesaid embodiment, the description was made by giving, as an example, the case where the mass and the inertia moment were set only for the vehicle body 2. The mass or the inertia moment, however, may also be set for the front wheel 3f. In such a case as well, the two-wheeled vehicle 1A may be equivalently transformed to a system made up of an inverted pendulum mass point and a ground surface mass point, so that the posture of the vehicle body 2 can be controlled as in the aforesaid embodiment.

Further, similarly to a case where a variable related to the position of a mass point may be converted to a variable related to the angle of the line segment connecting the mass point and the origin, any one of the variables and constants used in the embodiment may be replaced with another variable or constant that has a one-to-one relationship therewith. Any variables or constants for which such replacement is possible can be regarded as equivalent to each other.

Furthermore, those equivalently transformed from the techniques, means, and algorithms shown in the above-described embodiment to produce the same result can be regarded as being identical thereto.

What is claimed is:

1. A mobile vehicle having a vehicle body and a front wheel and a rear wheel arranged spaced apart from each other in a longitudinal direction of the vehicle body, the front wheel being a steered wheel which can be steered about a steering axis,

the mobile vehicle comprising:

a front-wheel support mechanism configured to support the front wheel so as to be steerable about the steering axis and having a trail adjustment mechanism which makes a trail of the front wheel adjustable;

a steering actuator which generates a steering force for steering the steered wheel;

64

a trail adjustment actuator which generates a driving force for changing the trail of the front wheel; and
a control device which controls the steering actuator and the trail adjustment actuator, wherein
the control device is configured to include

a steering control section which controls the steering actuator so as to stabilize a posture of the vehicle body in accordance with at least an observed value of an inclination angle in a roll direction of the vehicle body, and

a trail control section which controls the trail adjustment actuator in accordance with an observed value of a vehicle speed of the mobile vehicle such that at least the trail in a case where the observed value of the vehicle speed is zero becomes smaller than the trail in a case where the observed value of the vehicle speed is greater than a first prescribed speed,

wherein the steering control section is configured to control the steering actuator so as to stabilize controlled state quantities for stabilizing the posture of the vehicle body, wherein the controlled state quantities include a motional state quantity of an inclination state quantity which is a prescribed kind of state quantity having a value responsive to the inclination angle in the roll direction of the vehicle body and a motional state quantity of a steering angle of the front wheel.

2. The mobile vehicle according to claim 1, wherein the trail control section is configured to control the trail adjustment actuator such that the trail takes a prescribed positive value in the case where the observed value of the vehicle speed is greater than the first prescribed speed.

3. The mobile vehicle according to claim 1, wherein the trail control section is configured to control the trail adjustment actuator to make the trail match a prescribed upper trail limit in a case where the observed value of the vehicle speed is greater than the first prescribed speed, and control the trail adjustment actuator to make the trail match a prescribed lower trail limit which is smaller than the prescribed upper trail limit in a case where the observed value of the vehicle speed is zero, and wherein the trail control section is configured to control the trail adjustment actuator to make the trail match the prescribed lower trail limit while the observed value of the vehicle speed increases from zero to the first prescribed speed, control the trail adjustment actuator to make the trail match the prescribed upper trail limit when the observed value of the vehicle speed has exceeded the first prescribed speed and until the observed value of the vehicle speed drops below a second prescribed speed which is smaller than the first prescribed speed, and control the trail adjustment actuator to make the trail match the prescribed lower trail limit when the observed value of the vehicle speed has dropped below the second prescribed speed.

4. The mobile vehicle according to claim 3, further comprising a lock mechanism operable, at least in a state where the trail matches the prescribed upper trail limit, to lock a mobile section which is included in the trail adjustment mechanism and which moves in conjunction with a change of the trail.

5. The mobile vehicle according to claim 1, wherein the trail control section is configured to successively determine a desired trail as a desired value of the trail such that the desired trail changes continuously between a prescribed upper trail limit and a prescribed lower trail limit which is smaller than the prescribed upper trail limit in accordance with the observed value of the vehicle speed, and such that the desired trail becomes larger as the observed value of the vehicle speed becomes larger, and wherein the trail control section is con-

65

figured to control the trail adjustment actuator to make an actual trail track the desired trail.

6. The mobile vehicle according to claim 5, further comprising a lock mechanism operable, at least in a state where the trail matches the prescribed upper trail limit, to lock a mobile section which is included in the trail adjustment mechanism and which moves in conjunction with a change of the trail.

7. The mobile vehicle according to claim 1, wherein in a case where a steering angular acceleration of the front wheel steered by the steering actuator or a torque about the steering axis applied to the front wheel from the steering actuator is defined as a reference quantity, the steering control section is configured to control the steering actuator such that a sensitivity Ra of the change in value of the reference quantity to the change in observed value of the motional state quantity of the inclination state quantity included in the controlled state quantities changes in accordance with the trail, with a characteristic that the sensitivity Ra becomes higher as the trail becomes larger.

8. The mobile vehicle according to claim 7, wherein the steering control section is configured to control the steering actuator such that the sensitivity Ra of the change in value of the reference quantity to the change in observed value of the motional state quantity of the inclination state quantity changes in accordance with the observed value of the vehicle speed, with a characteristic that the sensitivity Ra becomes lower as the vehicle speed becomes higher.

9. The mobile vehicle according to claim 7, wherein the steering control section is configured to control the steering actuator such that the sensitivity Ra of the change in value of the reference quantity to the change in observed value of the motional state quantity of the inclination state quantity changes in accordance with an observed value of the steering angle of the front wheel, with a characteristic that the sensitivity Ra becomes lower as a magnitude of the steering angle of the front wheel becomes larger.

10. The mobile vehicle according to claim 7, wherein the steering control section is configured to control the steering actuator such that the sensitivity Ra of the change in value of the reference quantity to the change in observed value of the motional state quantity of the inclination state quantity and sensitivity Rb of the change in value of the reference quantity to the change in observed value of the motional state quantity of the steering angle of the front wheel both become zero in the case where the observed value of the vehicle speed is greater than a third prescribed speed.

11. The mobile vehicle according to claim 1, wherein in a case where a steering angular acceleration of the front wheel steered by the steering actuator or a torque about the steering

66

axis applied to the front wheel from the steering actuator is defined as a reference quantity, the steering control section is configured to control the steering actuator such that a sensitivity Rb of the change in value of the reference quantity to the change in observed value of the motional state quantity of the steering angle of the front wheel included in the controlled state quantities changes in accordance with the observed value of the vehicle speed, with a characteristic that the sensitivity Rb becomes lower as the vehicle speed becomes higher.

12. The mobile vehicle according to claim 11, wherein the steering control section is configured to control the steering actuator such that sensitivity Ra of the change in value of the reference quantity to the change in observed value of the motional state quantity of the inclination state quantity changes in accordance with the observed value of the vehicle speed, with a characteristic that the sensitivity Ra becomes lower as the vehicle speed becomes higher.

13. The mobile vehicle according to claim 11, wherein the steering control section is configured to control the steering actuator such that sensitivity Ra of the change in value of the reference quantity to the change in observed value of the motional state quantity of the inclination state quantity changes in accordance with an observed value of the steering angle of the front wheel, with a characteristic that the sensitivity Ra becomes lower as a magnitude of the steering angle of the front wheel becomes larger.

14. The mobile vehicle according to claim 11, wherein the steering control section is configured to control the steering actuator such that sensitivity Ra of the change in value of the reference quantity to the change in observed value of the motional state quantity of the inclination state quantity and the sensitivity Rb of the change in value of the reference quantity to the change in observed value of the motional state quantity of the steering angle of the front wheel both become zero in the case where the observed value of the vehicle speed is greater than a third prescribed speed.

15. The mobile vehicle according to claim 1, wherein the control device has a posture-control disabled mode which is an operating mode in which the control of the steering actuator by the steering control section is disabled, and in the posture-control disabled mode, the trail control section is configured to control an actual trail to become a prescribed trail determined in advance, and the mobile vehicle further comprises a clutch mechanism which interrupts power transmission between the steering actuator and the front wheel in the posture-control disabled mode.

* * * * *