

US009173042B2

(12) **United States Patent**  
**Jinton et al.**

(10) **Patent No.:** **US 9,173,042 B2**  
(45) **Date of Patent:** **Oct. 27, 2015**

(54) **BONE ANCHOR FIXTURE FOR A MEDICAL PROSTHESIS**

(75) Inventors: **Lars Jinton**, Molndal (SE); **Erik Holgersson**, Gothenburg (SE); **Peter Elmberg**, Kallered (SE)

(73) Assignee: **Cochlear Limited**, Macquarie University, NSW (AU)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 1322 days.

(21) Appl. No.: **12/177,083**

(22) Filed: **Jul. 21, 2008**

(65) **Prior Publication Data**  
US 2009/0023109 A1 Jan. 22, 2009

**Related U.S. Application Data**

(60) Provisional application No. 60/951,163, filed on Jul. 20, 2007, provisional application No. 60/951,169, filed on Jul. 20, 2007.

(51) **Int. Cl.**  
*A61B 17/00* (2006.01)  
*H04R 25/00* (2006.01)  
*A61C 8/00* (2006.01)

(52) **U.S. Cl.**  
CPC ..... *H04R 25/606* (2013.01); *A61C 8/0025* (2013.01); *A61C 8/0066* (2013.01); *A61C 8/0069* (2013.01)

(58) **Field of Classification Search**  
USPC ..... 606/300, 301, 305, 308, 315, 316; 411/72, 173-174, 411, 424  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,016,610	A *	10/1935	Moeller	411/424
4,025,964	A	5/1977	Owens	
4,498,461	A	2/1985	Håkansson	
D294,295	S	2/1988	Brånemark	
4,738,623	A	4/1988	Driskell	
4,904,233	A	2/1990	Håkansson et al.	
4,917,555	A *	4/1990	Taubert	411/411

(Continued)

FOREIGN PATENT DOCUMENTS

EP	0996391	5/2000
SE	531177	1/2009

(Continued)

OTHER PUBLICATIONS

<http://www.merriam-webster.com/dictionary/tapered>, Retrieved Apr. 10, 2012.\*

(Continued)


*Primary Examiner* — Christian Sevilla

(74) *Attorney, Agent, or Firm* — Hauptman Ham, LLP

(57) **ABSTRACT**

A screw-shaped anchoring fixture for anchoring a prosthesis in the skull bone. The anchoring fixture comprises a main body configured to be implanted into the bone and a flange configured to function as a stop to prevent the main body from completely penetrating through the bone. The main body comprises a distal tapered apical portion, a first portion, and a second portion. The inner diameter of the second portion is greater than the inner diameter of the first portion. The method for inserting the anchoring fixture includes providing the anchoring fixture, drilling a hole, and inserting the anchoring fixture into the hole until the flange contacts the skull bone, wherein the hole has a diameter that is greater than the inner diameter of the first portion and less than the outer diameter of the second portion.

**31 Claims, 2 Drawing Sheets**



(56)

References Cited

U.S. PATENT DOCUMENTS

4,936,317 A 6/1990 MacGregor  
 4,998,461 A 3/1991 Ishiwata et al.  
 5,135,395 A 8/1992 Marlin  
 5,269,685 A \* 12/1993 Jorneus et al. .... 433/174  
 5,588,883 A 12/1996 Hattori  
 5,653,710 A \* 8/1997 Harle ..... 606/308  
 5,735,790 A \* 4/1998 Håkansson et al. .... 600/25  
 5,833,463 A 11/1998 Hurson  
 5,961,329 A \* 10/1999 Stucki-McCormick ..... 433/173  
 6,030,162 A \* 2/2000 Huebner ..... 411/413  
 6,086,303 A \* 7/2000 Fluckiger ..... 411/399  
 6,474,991 B1 11/2002 Hansson  
 6,643,378 B2 11/2003 Schumaier  
 6,669,701 B2 12/2003 Steiner et al.  
 6,840,919 B1 1/2005 Håkansson  
 6,953,463 B2 \* 10/2005 West, Jr. .... 606/326  
 7,065,223 B2 6/2006 Westerkull  
 7,074,222 B2 \* 7/2006 Westerkull ..... 606/312  
 7,806,693 B2 10/2010 Hurson  
 D634,186 S \* 3/2011 Kemper ..... D8/387  
 8,170,252 B2 5/2012 Parker et al.  
 2003/0176866 A1 \* 9/2003 Westerkull ..... 606/73  
 2004/0032962 A1 2/2004 Westerkull  
 2004/0152047 A1 8/2004 Odrich et al.  
 2004/0210103 A1 10/2004 Westerkull  
 2004/0228705 A1 \* 11/2004 Baer et al. .... 411/424  
 2005/0106534 A1 5/2005 Gahlert  
 2005/0153261 A1 7/2005 Chang  
 2005/0248158 A1 11/2005 Westerkull  
 2005/0249366 A1 11/2005 Westerkull  
 2005/0287497 A1 \* 12/2005 Carter ..... 433/173  
 2006/0050913 A1 3/2006 Westerkull  
 2006/0056649 A1 3/2006 Schumaier  
 2006/0093175 A1 \* 5/2006 Westerkull ..... 381/326  
 2006/0126874 A1 6/2006 Westerkull  
 2006/0172257 A1 \* 8/2006 Niznick ..... 433/173  
 2006/0195099 A1 8/2006 Bottlang  
 2006/0211910 A1 9/2006 Westerkull  
 2007/0009853 A1 1/2007 Pitulia  
 2007/0053536 A1 3/2007 Westerkull  
 2007/0059666 A1 3/2007 Zickman et al.  
 2007/0147973 A1 \* 6/2007 Laan ..... 411/411  
 2009/0082817 A1 3/2009 Jinton et al.  
 2010/0249784 A1 9/2010 Andersson

FOREIGN PATENT DOCUMENTS

WO 9205745 4/1992  
 WO 9205745 A1 \* 4/1992 ..... A61C 8/00  
 WO 96/19950 7/1996  
 WO 9855049 \* 12/1998 ..... A61F 2/20  
 WO 9923971 5/1999  
 WO 0193634 12/2001  
 WO 0193645 12/2001  
 WO 02/09622 2/2002  
 WO 0209622 2/2002  
 WO 2004/012622 2/2004  
 WO 2004/045432 6/2004  
 WO 2004093401 10/2004  
 WO 2004105650 12/2004  
 WO 2005000391 1/2005  
 WO 2006052527 5/2006  
 WO WO 2009015102 1/2009  
 WO WO 2009015103 1/2009

OTHER PUBLICATIONS

<http://www.merriam-webster.com/dictionary/apical>, Retrieved Apr. 10, 2012.\*  
<http://www.merriam-webster.com/dictionary/portion>, Retrieved Apr. 10, 2012.\*  
 Written Opinion for PCT/US2008/070679, dated Oct. 15, 2008.  
 International Preliminary Report on Patentability for PCT/US2008/70681, dated Aug. 21, 2009.  
 International Search Report for PCT/US2008/070681, dated Dec. 15, 2008.  
 Written Opinion for PCT/US2008/070681, dated Dec. 15, 2008.  
 International Search Report for PCT/US2008/070679, dated Oct. 27, 2008.  
 Extended European Search Report for European Application No. 08782157.5 mailed Feb. 1, 2013 (8 Pages).  
 Extended European Search Report for European Application No. 08782159.1 mailed Jan. 3, 2013 (15 Pages).  
 Sjostrom et al., "Monitoring of implant stability in grafted bone using resonance frequency analysis—A clinical study from implant placement to 6 months of loading", International Journal of Oral and Maxillofacial Surgery, Copenhagen, DK, vol. 34, No. 1, Jan. 1, 2005, pp. 45-51.

\* cited by examiner

FIG. 1







FIG. 2



# BONE ANCHOR FIXTURE FOR A MEDICAL PROSTHESIS

## CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims the benefit of U.S. Provisional Application No. 60/951,163, entitled "Bone Anchor Fixture for a Medical Prosthesis," filed Jul. 20, 2007 and U.S. Provisional Application No. 60/951,169, entitled "Coupling Apparatus for a Bone Anchored Hearing device," filed Jul. 20, 2007. These applications are hereby incorporated by reference herein.

## BACKGROUND

### 1. Field of the Invention

The present invention relates generally to hearing devices and, more particularly, to anchoring elements for bone anchored hearing devices.

### 2. Related Art

For persons who cannot benefit from traditional, air conduction hearing aids there are other types of hearing aids on the market commonly referred to as bone anchored hearing aids. Bone anchored hearing aids mechanically transmit sound information to a person's inner ear via the skull bone by means of a vibrator. Such hearing aid devices are typically connected to a percutaneous implant in the form of a titanium screw implanted in the skull bone behind the external ear so that sound is transmitted via the skull bone to the cochlea (inner ear). This enables the hearing aid to be effective regardless of whether there is disease or damage in the middle ear. Moreover, penetration of the skin makes the vibratory transmission very efficient.

Bone anchored hearing aids were initially developed to rehabilitate certain types of hearing-impaired patients. They may also be utilized for other indications such as stuttering and for certain non-medical applications. A bone anchored hearing aid may be connected to an implant by means of a bayonet coupling, a snap-in coupling, a magnetic coupling or the like. One example of this type of hearing aid device is the BAHA® bone anchored hearing aid, described in U.S. Pat. No. 4,498,461 and commercially available from Cochlear Bone Anchored Solutions AB (previously Entific Medical Systems AB) in Göteborg, Sweden.

The implant connecting the hearing aid to the skull generally comprises two components: a bone attachment piece that is attached or implanted directly into the skull bone and a skin penetrating piece coupled to the bone attachment piece. The reason for this two-piece design is that installation of the implant is occasionally performed in two steps. In the first step, the bone attachment piece is installed and the surrounding issue is allowed to heal for a period of time that may last up to a few months. In the second step, the skin penetrating piece is coupled to the bone attachment piece. In the event that the skin penetrating piece becomes damaged, it may be replaced without removing the anchoring fixture from the skull. Moreover, the hearing aid may be changed or upgraded if necessary, without removing the bone attachment piece from the skull.

Although conventional fixtures normally provide a certain degree of osseointegration, a more effective integration between the implant screw and the skull bone is desired, for example, for patients having impaired bone quality. Moreover, loading of the implant at an earlier stage would also be desired.

## SUMMARY

In one embodiment, an anchoring fixture for anchoring a prosthesis to a skull bone is disclosed. The anchoring fixture comprises a main body configured to be implanted into the skull bone. The main body further comprises a distal tapered apical portion and a first portion adjacent to the distal tapered apical portion. The main body also comprises a second portion adjacent to the first portion. The first portion has a first inner diameter and the second portion has a second inner diameter that is greater than the first inner diameter. This configuration provides compression in the radial direction on the skull bone to improve the initial stability of the anchoring fixture.

In another embodiment, an anchoring fixture for anchoring a prosthesis to a skull bone is disclosed. The anchoring fixture comprises a main body configured to be implanted into the skull bone and a flange. The main body further comprises a distal tapered apical portion and a first threaded portion having a first diameter adjacent to the distal apical portion and an adjacent second threaded portion having a second diameter. The second diameter is greater than the first diameter. The flange is adjacent to the second threaded portion, the flange comprising a planar bottom surface adapted to rest on top of the skull bone when the main body is implanted into the skull bone.

In yet another embodiment, an anchoring fixture for anchoring a prosthesis to a skull bone is disclosed. The anchoring fixture comprises an implantation means for securing the anchoring fixture onto the skull bone without completely penetrating through the skull bone. The implantation means comprises a compression means for exerting a compression onto the skull bone in a radial direction to stabilize the fixture in the skull bone.

In a further embodiment, a method for installing the anchoring fixture into a skull bone is disclosed. The method comprises providing an anchoring fixture, drilling a hole into the skull bone and inserting the anchoring fixture in the hole until the flange contacts the skull bone, wherein the hole has a diameter that is greater than the inner diameter of the first portion and less than the outer diameter of the second portion. In one aspect of the embodiment, the inserting step comprises screwing the anchoring fixture into the skull bone.

## BRIEF DESCRIPTION OF THE DRAWINGS

Embodiments of the present invention are described herein with reference to the accompanying drawings, in which:

FIG. 1 is a perspective view of an anchoring element in accordance with one embodiment of the anchoring fixture; and

FIG. 2 is a cross-sectional side view of the anchoring element illustrated in FIG. 1.

Like numerals refer to like parts throughout the several views of the drawings.

## DETAILED DESCRIPTION OF THE INVENTION

Aspects of the various embodiments disclosed herein are generally directed to providing screw-shaped anchoring fixtures configured to be anchored in the comparatively thin skull bone and having a certain compressive ability in the radial direction to improve the initial stability of the fixture.

In one embodiment, the anchoring fixture has a main body configured to be inserted in the skull bone and a flange configured to prevent the fixture from completely penetrating through the skull bone. The main body comprises a first and



second substantially cylindrical portion. The first portion comprises a screw thread having a first inner diameter and the second portion is adjacent to the flange and has a second inner diameter that is greater than the first inner diameter. Preferably, the second portion has at least one groove extending around the periphery of the cylindrical portion. The groove may have a bottom diameter exceeding the first inner diameter of the screw thread. Preferably, the groove forms a second screw thread having an inner diameter exceeding the inner diameter of the first, main screw thread. The surface of at least the first portion of the main body may be modified to increase the surface roughness.

In another embodiment, a method for inserting the anchoring fixture is disclosed. In accordance with one aspect of this embodiment, a drill may be used to drill a hole in the skull bone before installing the anchoring fixture. The drill creates a hole in the skull bone having a diameter which is larger than the inner diameter of the screw thread of the first cylindrical portion, but less than the outer diameter of the second cylindrical portion. When the fixture is inserted into the drilled hole, the wider second portion of the fixture, i.e. the portion next to the flange, provides a certain compression to the bone, specifically the cortical bone, in the radial direction of the hole.

Embodiments of the bone anchored coupling apparatus will be described below with reference to the accompanying drawings. FIG. 1 illustrates an example of a screw-shaped anchoring fixture **100** in accordance with one embodiment. Fixture **100** is preferably made of any biocompatible material that has a known ability to integrate with the surrounding bone tissue, a phenomenon commonly referred to as osseointegration. In one embodiment, fixture **100** is made of titanium. Fixture **100** has a main body **102** configured to be implanted into the skull bone, a flange **103** configured to serve as a stop to prevent fixture from penetrating through the skull bone, and a tool engaging socket **104** in the form of an internal grip section **105** for easy lifting and handling of fixture **100**. The geometrical configuration of the internal grip section may be configured in a manner that allows for engagement with an insertion tool. In accordance with one aspect, the geometric configuration may be in the form of a hex, multi-lobed surfaces, slots or grooves. As shown in FIG. 1 a number of lobe-shaped surfaces **106** is provided in the internal grip section and extends a distance or height (H) **120** in the longitudinal direction of the main body of the fixture parallel to longitudinal axis **107** of the fixture. The lobe-shaped surfaces **106** may be configured to cooperate with an insertion tool having slightly tapered engaging surfaces to engage and lift the fixture.

The main body **102** has a length sufficient to securely anchor fixture **100** into, without penetrating entirely through, the skull bone. The length of main body **102** may therefore depend on the thickness of the skull bone at the implantation site. In one embodiment, main body **102** has a length (L) **122** no greater than approximately 5 mm. Main body **102** further comprises a distal tapered apical portion **102A** and a straight, generally cylindrical body comprising two portions, a first portion **102B** and a second portion **102C**. First portion **102B** comprises external threads that form the main screw thread **108** adjacent to the distal tapered apical portion. The second portion **102C** is adjacent to the flange. As illustrated in FIG. 2, main screw thread **108** has an inner diameter **124** and an outer diameter **126**. In one embodiment, the outer diameter **126** is approximately 3.5-5.0 mm.

As further shown in FIGS. 1 and 2, the distal tapered apical part **102A** of main body **102** is configured with self-tapping cutting edges **109**. Additional information regarding the self-

tapping action is described in greater detail in WO 02/09622, which is hereby incorporated by reference herein. Clearance or relief surfaces **110** may also be provided, wherein the self-tapping cutting edges **109** and the clearance or relief surfaces **110** are provided in an alternating configuration around the main body periphery. This alternating configuration is advantageous because it creates more volume for the cut-off bone chips and therefore reduces the squeezing effect between the fixture **100** and the bone during installation.

As more clearly illustrated in FIG. 2, flange **103** has a planar bottom surface **111** for resting against the outer bone surface, indicated by **112**, when the fixture **100** has been screwed into the skull bone. Again, flange **103** prevents the fixture **100** from completely penetrating through the skull bone. Preferably, flange **103** has a diameter which exceeds the peak diameter of the threads by approximately 10-20%. The outer peripheral surface of the flange has a cylindrical part **113** and a tapered top portion **114**. The upper end of the flange is designed with an open cavity with a tapered inner side wall **115**, a grip section **105**, and an inner bottom bore **116** with an internal screw thread for directly or indirectly connecting a hearing aid device or any orbital or ear prosthesis. In order to achieve a stable connection, the inner opening and bore extends to the bottom half of the main body of the fixture **100**. The tapered inner side wall **115** forms a seat for a skin-penetrating abutment or the like to create a good connecting fit between the two parts fixture and abutment. The cone angle  $\alpha$  may be in the range of about 30-40 degrees. However, the connection with abutment and other parts in the system are not part of this invention and will not be described in any detail here.

In one embodiment, no protruding hex is provided in the embodiment depicted in FIGS. 1 and 2. Rather, the flange forms a smooth, open upper end. The smooth upper end of flange **103** and the absence of any sharp corners provides for improved soft tissue adaptation. Flange **103** also comprises a cylindrical part **113** and a flared top portion **114** which provide sufficient height in the longitudinal direction for internal connection with an abutment sleeve (not shown).

FIG. 2 shows the second portion **102C** adjacent to flange **103** having an inner diameter **128** which exceeds the inner diameter **124** of the main threads **108** of the first portion **102B**. As noted, this configuration provides a radial compression to the surrounding bone. Preferably the second portion **102C** is provided with circumferential grooves **117**, having an inner diameter **128** and an outer diameter **130**. A drill may then be used having a diameter that is greater than the inner diameter **124** of screw thread **108** of first portion **102B**, but less than the outer diameter **130** of second portion **102C** of the cylindrical main body of the fixture, that is,  $124 < \text{Drill Diameter} < 130$ . When fixture **100** is inserted into the drilled hole, the second portion **102C** compresses the bone to some extent to impart initial stability. The wide diameter portion is located next to the flange so that the compressive action is more concentrated to the hard cortical part of the skull bone tissue.

As mentioned and illustrated in FIGS. 1 and 2, second portion **102C** is preferably provided with circumferential grooves **117**. In one embodiment, the inner diameter **128** also exceeds the inner diameter **124** of screw thread **108** of first portion **102B**. Preferably the height **132** of the groove ( $130 - 128 = 132$ ) is approximately  $\frac{1}{3}$  or less than the height of screw thread **108** of first portion **102B**. In addition to the noted compressive action, such grooves may provide an increased retention between the fixture and the surrounding bone tissue, and spread the forces directed to the abutment more evenly in the bone.



## 5

This retention may also be improved by increasing the surface roughness of the bone contacting surfaces of fixture **100**. For instance the surface may be modified by means of an abrasive blasting process according to WO 92/05745. In one embodiment the process is used to provide an average surface roughness Sa of about 0.2-2.0  $\mu\text{m}$ , preferably 0.8-1.2  $\mu\text{m}$ , and Sdr(2d/3d)=8-60%, preferably approximately 20-60%.

Circumferentially oriented grooves **117** may extend completely or partly around the periphery of the main body. In the embodiment shown in FIGS. **1** and **2** there are three separate grooves as an example. As an alternative, the grooves may be formed as a screw thread, which may have the same pitch as main screw thread **108**, but having an inner diameter **128** that is greater than the inner diameter **124** of main screw thread **108**, so that the height of the grooves **117** would be only approximately  $\frac{1}{3}$  or less of the height **134** of main screw thread **108** (126-124=134). In one embodiment, the extension of the second wide diameter portion **102C** in the longitudinal direction of the fixture is about 15-25% of the total height of the fixture.

A method for inserting the fixture may comprise providing the anchoring fixture, drilling a hole, and inserting the anchoring fixture into the hole until the flange contacts the skull bone, wherein the hole has a diameter that is greater than the inner diameter of the first portion and less than the outer diameter of the second portion. No countersinking or removal of cortical bone is used which leaves more good bone left. When fixture **100** is inserted into such a drilled hole, the wider second portion of the fixture, that is, portion **102C** next to the flange, provides a certain compression of the cortical bone on the radial direction of the prepared bone hole.

Further features and advantages of the present invention may be found in U.S. Provisional Application No. 60/951,169, entitled "Coupling Apparatus For a Bone Anchored Hearing Device," and filed Jul. 20, 2007, and U.S. Provisional Application No. 60/951,163, entitled "Bone Anchor Fixture for a Medical Prosthesis," and filed Jul. 20, 2007, which are hereby incorporated by reference herein.

The invention is not limited to the embodiment illustrated in the drawings but may be varied within the scope of the accompanying claims. Specifically, it is understood that other types of abrasive methods, coatings etc, may be used for increasing the roughness of bone-contacting surfaces. Such methods are known per se and not described here in any detail.

What is claimed is:

**1.** An anchoring fixture for anchoring a hearing prosthesis to a cranial section of a skull bone comprising:

a main body configured to be implanted into the bone, the main body comprising a distal tapered apical portion and a non-tapered first portion adjacent to the distal tapered apical portion and a non-tapered second portion adjacent to the first portion; and

a flange, adjacent to the second portion, having a bottom surface configured to abut the skull bone when the main body is implanted therein thereby resisting deeper insertion;

wherein the first portion has a first inner diameter and the second portion has a second inner diameter; and wherein the second inner diameter is greater than the first inner diameter.

**2.** The anchoring fixture of claim **1**, wherein the fixture comprises a material capable of integrating into the surrounding bone tissue.

**3.** The anchoring fixture of claim **1**, further comprising: a tool engaging socket for lifting and handling the fixture by a cooperating insertion tool.

## 6

**4.** The anchoring fixture of claim **3**, wherein the tool engaging socket comprises an internal grip section.

**5.** The anchoring fixture of claim **4**, wherein the internal grip section has a multi-lobed surface and grooves.

**6.** The anchoring fixture of claim **1**, wherein the main body has a length that is less than approximately 5 mm.

**7.** The anchoring fixture of claim **1**, wherein the distal tapered apical portion comprises alternating self-tapping cutting edges and clearance or relief surfaces along a periphery of the distal tapered apical portion.

**8.** The anchoring fixture of claim **1**, wherein the first and second portion of the main body is generally cylindrical.

**9.** The anchoring fixture of claim **8**, wherein the first portion further comprises main screw threads, wherein said main screw threads have an inner diameter, an outer diameter, and a height.

**10.** The anchoring fixture of claim **9**, wherein the second portion further comprises circumferential grooves, the circumferential grooves having an inner diameter, an outer diameter, and a height.

**11.** The anchoring fixture of claim **10**, wherein the inner diameter of the circumferential grooves is less than the outer diameter of the main screw threads.

**12.** The anchoring fixture of claim **10**, wherein the height of the main screw threads is greater than the height of the circumferential grooves.

**13.** The anchoring fixture of claim **10**, wherein the height of the circumferential grooves is approximately or less than approximately 33% of the height of the main screw threads.

**14.** The anchoring fixture of claim **4**, further comprising: an inner bottom bore adjacent to the internal grip section, the inner bottom bore comprising internal screw threads.

**15.** The anchoring fixture of claim **1**, wherein the hearing prosthesis is a bone conduction device.

**16.** The anchoring fixture of claim **1**, wherein the main body has a surface roughness sufficient to retain of the fixture in the bone.

**17.** The anchoring fixture of claim **15**, wherein the surface roughness has a value of about 0.2  $\mu\text{m}$  to about 2.0  $\mu\text{m}$ .

**18.** The anchoring fixture of claim **17**, wherein the surface roughness has a value of about 0.8  $\mu\text{m}$  to about 1.2  $\mu\text{m}$ .

**19.** An anchoring fixture for anchoring a hearing prosthesis to a cranial section of a skull bone comprising:

a main body configured to be implanted into the skull bone, the main body comprising a distal tapered apical portion, a non-tapered first threaded portion having a first diameter adjacent to the distal apical portion, and an adjacent non-tapered second threaded portion having a second diameter; and

a flange adjacent to the second threaded portion, the flange comprising a planar bottom surface adapted to rest on top of the skull bone when the main body is implanted into the skull bone;

wherein the second diameter is greater than the first diameter.

**20.** The anchoring fixture of claim **1**, wherein: the skull bone includes a mastoid bone; and the main body is configured to be inserted into the mastoid bone at an orientation normal to a surface thereof.

**21.** The anchoring fixture of claim **19**, wherein: the skull bone includes a mastoid bone; and the main body is configured to be inserted into the mastoid bone at an orientation normal to a surface thereof.

**22.** The anchoring fixture of claim **19**, wherein: the main body has a length that is less than approximately 5 mm.

7

23. The anchoring fixture of claim 19, wherein:  
the hearing prosthesis is a bone conduction device.

24. The anchoring fixture of claim 1, further comprising:  
a third portion adjacent to the second portion, the third  
portion including the flange, the third portion also  
including an open cavity establishing a seat for a skin-  
penetrating abutment.

25. The anchoring fixture of claim 1, wherein:  
the first portion includes first grooves;  
the second portion includes second grooves;  
wherein a height of the second grooves is less than the  
height of the first grooves.

26. The anchoring fixture of claim 1, wherein:  
the first portion includes first grooves; and  
the second portion includes second grooves;  
wherein a height of the second grooves is approximately  $\frac{1}{3}$   
less than the height of the first grooves.

27. The anchoring fixture of claim 1, wherein:  
the first portion includes first grooves; and  
the second portion includes second grooves;

8

wherein an outer maximum diameter of the second grooves  
is less than an outer maximum diameter of the first  
grooves.

28. The anchoring fixture of claim 1, further comprising:  
a third portion adjacent to the second portion, the third  
portion including the flange, the third portion also  
including a tapered inner side wall extending from a  
proximal end of the anchoring fixture to a location hav-  
ing a depth within the anchoring fixture relative to a  
longitudinal axis at least proximate a beginning of the  
second portion relative to the longitudinal axis.

29. The anchoring fixture of claim 1, wherein:  
the distal tapered apical portion includes threads.

30. The anchoring fixture of claim 29, wherein:  
the first portion and the second portion also includes  
threads.

31. The anchoring fixture of claim 29, wherein:  
the distal tapered apical portion comprises alternating self-  
tapping cutting edges or relief surfaces along a periphery  
of the distal tapered apical portion.

\* \* \* \* \*