



US009175479B2

(12) **United States Patent**  
**Stanley**

(10) **Patent No.:** **US 9,175,479 B2**  
(45) **Date of Patent:** **Nov. 3, 2015**

(54) **SYSTEM FOR MOUNTING OBJECTS TO POLYMERIC MEMBRANES**

(58) **Field of Classification Search**  
None  
See application file for complete search history.

(75) Inventor: **Joel A. Stanley**, Colleyville, TX (US)

(56) **References Cited**

(73) Assignee: **BWDT, LLC**, Colleyville, TX (US)

U.S. PATENT DOCUMENTS

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 473 days.

|           |     |         |              |          |
|-----------|-----|---------|--------------|----------|
| 2,769,333 | A   | 11/1956 | Rientjes     |          |
| 3,505,636 | A   | 4/1970  | McDowell     |          |
| 3,680,851 | A   | 8/1972  | Takada       |          |
| 4,389,826 | A   | 6/1983  | Kelly        |          |
| 4,568,243 | A   | 2/1986  | Schubert     |          |
| 4,581,863 | A * | 4/1986  | Thaler ..... | 52/126.2 |
| 4,657,802 | A   | 4/1987  | Morman       |          |
| 4,747,241 | A   | 5/1988  | Whitman      |          |

(21) Appl. No.: **13/396,377**

(22) Filed: **Feb. 14, 2012**

(65) **Prior Publication Data**

US 2012/0138208 A1 Jun. 7, 2012

(Continued)

**Related U.S. Application Data**

FOREIGN PATENT DOCUMENTS

(63) Continuation of application No. 13/099,008, filed on May 2, 2011, now Pat. No. 8,623,158, which is a continuation-in-part of application No. PCT/US2010/048734, filed on Sep. 14, 2010, and a continuation-in-part of application No. 12/559,117, filed on Sep. 14, 2009, now Pat. No. 7,935,202.

|    |            |    |         |
|----|------------|----|---------|
| WO | 03093604   | A1 | 11/2003 |
| WO | 2009095273 |    | 8/2009  |

(Continued)

OTHER PUBLICATIONS

Advertisement for Applied Energy Technologies (Date Unknown).  
Online Advertisement for EcoFasten Solar (as of Jul. 31, 2009).  
Online Advertisement for Architecture Yamade from www.a-yamade.co.jp: (Date Unknown).  
Notice of Allowance dated Feb. 7, 2010 from corresponding U.S. Appl. No. 12/559,117.

(Continued)

(51) **Int. Cl.**

|                   |           |
|-------------------|-----------|
| <b>F24J 2/52</b>  | (2006.01) |
| <b>E04D 13/14</b> | (2006.01) |
| <b>E04D 5/14</b>  | (2006.01) |
| <b>F24F 3/044</b> | (2006.01) |
| <b>F24F 13/32</b> | (2006.01) |
| <b>H01Q 1/12</b>  | (2006.01) |
| <b>F24J 2/46</b>  | (2006.01) |

Primary Examiner — Barbara J Musser

(74) Attorney, Agent, or Firm — James E. Walton


(52) **U.S. Cl.**

CPC ..... **E04D 13/1407** (2013.01); **E04D 5/143** (2013.01); **E04D 5/145** (2013.01); **F24F 3/0442** (2013.01); **F24F 13/32** (2013.01); **F24J 2/5245** (2013.01); **H01Q 1/1214** (2013.01); **F24J 2002/4669** (2013.01); **F24J 2002/4676** (2013.01); **Y02B 10/20** (2013.01); **Y02E 10/47** (2013.01); **Y10T 156/15** (2015.01)

(57) **ABSTRACT**

A system and method to attach an object to a structure. The system includes a first membrane, a second membrane and a mounting plate. The method includes covering a portion of the structure with the first membrane and then placing the mounting plate thereupon. The second membrane placed over the mounting plate and subsequently bonded to both the mounting plate and the first membrane. The object is secured to the mounting plate via a fastener attached thereto and extending through the second membrane.

**14 Claims, 33 Drawing Sheets**



(56)

**References Cited**

U.S. PATENT DOCUMENTS

|              |      |         |                    |          |
|--------------|------|---------|--------------------|----------|
| 4,754,958    | A    | 7/1988  | Markowski          |          |
| 4,778,702    | A *  | 10/1988 | Hutter, III        | 428/40.9 |
| 5,316,834    | A    | 5/1994  | Matsuda et al.     |          |
| 5,349,791    | A    | 9/1994  | Zaleski            |          |
| 5,407,310    | A    | 4/1995  | Kassouni           |          |
| 5,572,843    | A    | 11/1996 | Jordan             |          |
| 5,762,720    | A    | 6/1998  | Hanoka et al.      |          |
| 5,853,895    | A    | 12/1998 | Lewno              |          |
| 5,921,973    | A    | 7/1999  | Newkirk            |          |
| 5,986,203    | A    | 11/1999 | Hanoka et al.      |          |
| 6,046,399    | A    | 4/2000  | Kapner             |          |
| 6,110,311    | A    | 8/2000  | Mayle et al.       |          |
| 6,124,016    | A    | 9/2000  | Weil               |          |
| 6,167,717    | B1   | 1/2001  | Dudley et al.      |          |
| 6,177,161    | B1   | 1/2001  | Riom et al.        |          |
| 6,230,461    | B1   | 5/2001  | Piront             |          |
| 6,238,502    | B1   | 5/2001  | Hubbard            |          |
| 6,453,964    | B1   | 9/2002  | Pfotenhauer et al. |          |
| 6,554,947    | B2   | 4/2003  | Pfotenhauer et al. |          |
| 6,640,511    | B1   | 11/2003 | Link               |          |
| 6,773,780    | B2   | 8/2004  | Hutter, III        |          |
| 6,883,336    | B2   | 4/2005  | Dudley et al.      |          |
| 6,902,694    | B2   | 6/2005  | Novak              |          |
| 7,365,266    | B2   | 4/2008  | Heckeroth          |          |
| 7,588,652    | B2   | 9/2009  | Repp               |          |
| 7,900,413    | B2   | 3/2011  | Stanley            |          |
| 7,935,202    | B2   | 5/2011  | Stanley            |          |
| 8,557,070    | B2   | 10/2013 | Stanley            |          |
| 2001/0030380 | A1   | 10/2001 | Fujihira           |          |
| 2004/0173255 | A1   | 9/2004  | Heckeroth          |          |
| 2005/0183346 | A1   | 8/2005  | Dudley et al.      |          |
| 2007/0069434 | A1   | 3/2007  | Kato               |          |
| 2007/0175170 | A1   | 8/2007  | Shah               |          |
| 2009/0107073 | A1   | 4/2009  | Kalkanoglu         |          |
| 2009/0151869 | A1   | 6/2009  | Peterson           |          |
| 2010/0109318 | A1 * | 5/2010  | Mulligan           | 285/42   |
| 2010/0269882 | A1   | 10/2010 | Stanley            |          |
| 2010/0275975 | A1   | 11/2010 | Monschke           |          |
| 2011/0041429 | A1   | 2/2011  | Rummens            |          |
| 2013/0032191 | A1   | 2/2013  | Rummens            |          |

FOREIGN PATENT DOCUMENTS

|    |            |    |         |
|----|------------|----|---------|
| WO | 2009142480 | A1 | 11/2009 |
| WO | 2011032134 | A2 | 3/2011  |

OTHER PUBLICATIONS

Request for Continued Examination dated Jan. 21, 2011 from corresponding U.S. Appl. No. 12/559,117.

Advisory Action dated Jan. 20, 2011 from corresponding U.S. Appl. No. 12/559,117.

Amendment After Final dated Jan. 13, 2010 from corresponding U.S. Appl. No. 12/559,117.

Final Office Action dated Dec. 21, 2010 from corresponding U.S. Appl. No. 12/559,117.

Interview Summary dated Dec. 15, 2010 from corresponding U.S. Appl. No. 12/559,117.

Amendment dated Dec. 13, 2010 from corresponding U.S. Appl. No. 12/559,117.

Office Action dated Dec. 9, 2010 from corresponding U.S. Appl. No. 12/559,117.

Advertisement for Eco-Fasten (as of Jan. 1, 2008).

International Preliminary Report on Patentability International Application No. PCT/US10/48734, issued by the International Preliminary Examining Authority on Dec. 5, 2011.

The International Search Report and the Written Opinion of the International Searching Authority from counterpart International Application No. PCT/US2010/048734, filed Sep. 14, 2010, issued by the International Searching Authority on Nov. 3, 2010.

Advertisement for Eco-Fasten, "Bulls Eye Target Patch" (as of Mar. 2011).

Office Action dated Nov. 5, 2014 from counterpart CN App. No. 201080051439.7.

Examiner's Amendment dated Feb. 7, 2011 from U.S. Appl. No. 12/559,117.

Article 34 Amendments dated Dec. 1, 2010 from counterpart PCT App. No. PCT/US2010/048734.

Advertisement for Alpine Snowguards dated Aug. 20, 2009 from U.S. Appl. No. 12/559,117.

Office Action dated Oct. 1, 2012 from U.S. Appl. No. 13/099,008.

Amendment dated Dec. 31, 2012 from U.S. Appl. No. 13/099,008.

Office Action dated May 10, 2013 from U.S. Appl. No. 13/099,008.

Amendment dated Aug. 12, 2013 from U.S. Appl. No. 13/099,008.

Notice of Allowance dated Aug. 28, 2013 from U.S. Appl. No. 13/099,008.

International Search Report and Written Opinion of the International Searching Authority dated May 25, 2012 from counterpart PCT App. No. PCT/US2012/025165.

Article 34 Amendments dated Dec. 14, 2012 from counterpart PCT App. No. PCT/US2012/025165.

International Preliminary Report on Patentability dated Apr. 9, 2013 from counterpart PCT App. No. PCT/US2012/025165.

Office Action dated Dec. 20, 2012 from U.S. Appl. No. 13/624,003.

Amendment dated Oct. 20, 2013 from U.S. Appl. No. 13/624,003.

Notice of Allowance dated Apr. 16, 2013 from U.S. Appl. No. 13/624,003.

Advisory Action—Restriction/Election Requirement dated Jul. 1, 2014 from U.S. Appl. No. 13/653,935.

Response to Advisory Action—Restriction/Election Requirement dated Aug. 29, 2014 from U.S. Appl. No. 13/653,935.

Advertisement for PermaCity Solar Strap, date unknown, from U.S. Appl. No. 14/107,415.

Partial Supplementary European Search Report dated Nov. 11, 2014 from counterpart EP App. No. 12746690.2.

Advertisement for Eco-Fasten, "Bulls Eye Target Patch" dated Mar. 22, 2011.

Advisory Action, Election/Restriction dated Jun. 12, 2012 from U.S. Appl. No. 13/027,865.

Response to Election/Restriction dated Jul. 11, 2012 from U.S. Appl. No. 13/027,865.

Non-Final Office Action dated Dec. 20, 2012 from U.S. Appl. No. 13/027,865.

Amendment dated Mar. 20, 2013 from U.S. Appl. No. 13/027,865.

Notice of Allowance dated Apr. 8, 2013 from U.S. Appl. No. 13/027,865.

Examination Report dated Mar. 13, 2013 from counterpart AU App. No. 2010291913.

Preliminary Amendment dated Mar. 21, 2011 from U.S. Appl. No. 13/029,627.

Advisory Action—Required Election/Restriction dated Apr. 12, 2013 from U.S. Appl. No. 13/029,627.

Response to Election/Restriction dated May 3, 2013 from U.S. Appl. No. 13/029,627.

Office Action dated Jul. 13, 2013 from U.S. Appl. No. 13/029,627.

Amendment dated Oct. 18, 2013 from U.S. Appl. No. 13/029,627.

Office Action dated Jan. 27, 2014 from U.S. Appl. No. 13/029,627.

Amendment dated Apr. 28, 2014 from U.S. Appl. No. 13/029,627.

Office Action dated Sep. 29, 2014 from counterpart KR App. No. 10-2012-7009303.

Office Action dated Sep. 26, 2012 from U.S. Appl. No. 13/029,728.

Amendment dated Dec. 21, 2012 from U.S. Appl. No. 13/029,728.

Final Office Action dated Apr. 24, 2013 from U.S. Appl. No. 13/029,728.

Amendment After Final dated Jun. 24, 2013 from U.S. Appl. No. 13/029,728.

Notice of Allowance dated Jul. 9, 2013.




Office Action dated Jan. 4, 2013 from U.S. Appl. No. 13/043,052.


Amendment dated Apr. 4, 2013 from U.S. Appl. No. 13/043,052.

Notice of Allowance Jun. 13, 2013 from U.S. Appl. No. 13/043,052.

Office Action dated Apr. 30, 2015 from counterpart KR App. No. 10-2012-7009303.

\* cited by examiner










FIG 3






FIG 6F



FIG 6E




FIG 6D




FIG 6B




FIG 6A



FIG 6C

FIG 6








FIG 7






FIG 8D



FIG 8C




FIG 8A






FIG 8B

FIG 8






FIG 11





FIG 12






FIG 14




Fig. 15




Fig. 16




Fig. 17




Fig. 18




Fig. 19




Fig. 20A




Fig. 20B




Fig. 20C






Fig. 21




Fig. 22




Fig. 23




Fig. 24




Fig. 26

Fig. 25




Fig. 27




Fig. 29

Fig. 28




Fig. 31

Fig. 30




Fig. 32




Fig. 33




Fig. 34






Fig. 35




Fig. 36




Fig. 37




Fig. 38




Fig. 39




Fig. 40




FIG. 41




FIG. 42




Fig. 43




Fig. 44




Fig. 45




Fig. 46




Fig. 47




Fig. 48






FIG. 49




Fig. 50




Fig. 51




Fig. 52




Fig. 53

## SYSTEM FOR MOUNTING OBJECTS TO POLYMERIC MEMBRANES

### CROSS REFERENCE TO RELATED APPLICATIONS

This application is a continuation-in-part of U.S. application Ser. No. 13/099,008, filed 2 May 2011, titled "System for Mounting Objects to Polymeric Membranes," which claims the benefit of U.S. application Ser. No. 12/559,117, filed 14 Sep. 2009, titled "System for Mounting Objects to Polymeric Membranes," and International Application No. PCT/US10/48734, filed 14 Sep. 2010, titled "System for Mounting Objects to Polymeric Membranes," which claims the benefit of U.S. application Ser. No. 12/559,117, filed 14 Sep. 2009, titled "System for Mounting Objects to Polymeric Membranes;" both of which are both hereby incorporated by reference for all purposes as if fully set forth herein.

### BACKGROUND

#### 1. Field of the Present Description

The present description relates to methods and system for mounting objects to polymeric membranes.

#### 2. Description of Related Art

Various applications exist in which a polymeric membrane may be placed over a surface. For example, it may be desirable to provide a polymeric membrane as a roofing material. That is, a polymeric membrane may be applied to an outer surface of a building structure, such as a roof, to protect the structure from the environment.

### DESCRIPTION OF THE DRAWINGS

The novel features believed characteristic of the invention are set forth in the appended claims. However, the invention itself, as well as a preferred mode of use, and further objectives and advantages thereof, will best be understood by reference to the following detailed description when read in conjunction with the accompanying drawings, wherein:

FIGS. 1A-1C show an example systems for attaching a mounting plate to a polymeric membrane;

FIG. 1D shows a cross-sectional view of an example mounting plate;

FIG. 2A is a cross-sectional view of an example mounting system including a mounting plate secured to polymeric membrane with an adhesive;

FIG. 2B shows an exploded view in cross section of an example mounting system with a tape including adhesive on opposing sides thereof;

FIG. 2C shows a cross-sectional view of a further example mounting system.

FIG. 3 shows an example mounting assembly that may be coupled to a polymeric membrane;

FIG. 4 shows another example mounting assembly that may be coupled to a polymeric membrane;

FIG. 5 is a bottom view of the mounting assembly shown in FIG. 4;

FIGS. 6A-F, 7A-E, and 8A-D show various views of example mounting plates;

FIG. 9 shows a cross-sectional view of a further example mounting system;

FIG. 10 shows a cross-sectional view of an example mounting plate illustrated in FIG. 9;

FIG. 11 shows another example mounting system;

FIG. 12 is a side view of an example mounting plate shown in FIG. 11;

FIG. 13 is a further example mounting system that includes, among other features, an insulating member;

FIG. 14 is an example system for bonding a ridge member to a polymeric membrane;

FIG. 15 is an oblique view of a mounting system according to the preferred embodiment of the present invention;

FIG. 16 is an oblique view of a mounting system of FIG. 15 shown attached to a support structure;

FIG. 17 is a front view of the mounting system of FIG. 15;

FIG. 18 is an exploded front view of the mounting system of FIG. 15;

FIG. 19 is a bottom view of a membrane of the mounting system of FIG. 15;

FIG. 20A-20C are front views of the mounting system of FIG. 15 shown as a force is exerted on an object attached to the mounting system;

FIG. 21 is a top view of a mounting plate according to the preferred embodiment of the present invention;

FIG. 22 is a side cross-sectional view of the mounting plate of FIG. 21 taken at XXII-XXII;

FIG. 23 is a side view of the mounting plate of FIG. 22 shown attached to the mounting system of FIG. 17;

FIG. 24 is a front view of an alternative embodiment of the mounting plate of FIG. 21

FIG. 25 is an oblique view of a riser according to the preferred embodiment of the present invention;

FIG. 26 is a cross-sectional front view of the riser of FIG. 25 taken at XXVI-XXVI;

FIG. 27 is a front view of the riser of FIG. 25 shown attached to the mounting assembly of FIG. 4;

FIG. 28 is an oblique view of a riser according to an alternative embodiment of the present invention;

FIG. 29 is a cross-sectional front view of the riser of FIG. 28 taken at XXIX-XXIX;

FIG. 30 is an oblique view of a riser according to an alternative embodiment of the present invention;

FIG. 31 is a cross-sectional side view of the riser of FIG. 30 taken at XXXI-XXXI;

FIG. 32 is an oblique view of a riser according to an alternative embodiment of the present invention;

FIG. 33 is an oblique view of an alternative embodiment of a mounting plate;

FIG. 34 is a cross-sectional view of a portion of the mounting plate of FIG. 33 taken at XXXIV-XXXIV;

FIG. 35 is an oblique view of a fastener;

FIG. 36 is an oblique view of an alternative embodiment of the fastener of FIG. 35;

FIGS. 37 and 38 are cross-sectional views of an alternative embodiment of the fastener of FIG. 35;

FIG. 39 is an oblique view of an alternative embodiment of the mounting plate of FIG. 33;

FIG. 40 is a cross-sectional view of mounting plate of FIG. 39 taken at XL-XL;

FIG. 41 is a flow chart depicting the preferred method of assembling the mounting system according to the preferred embodiment of the present application;

FIG. 42 is a flow chart depicting the preferred method of assembling the mounting plate of FIG. 33;

FIG. 43 is a front view of an alternative embodiment of the mounting system of FIG. 18;

FIG. 44 is the assembled embodiment of the mounting system of FIG. 43;

FIG. 45 is an oblique exploded view of an alternative embodiment of the mounting system;

FIG. 46 shows an assembled oblique view of mounting system of FIG. 45;

3

FIG. 47 shows a cross-sectional front view of the mounting system of FIG. 45 during operation;

FIG. 48 shows a front view of the mounting system of FIG. 45 during operation and without a bracket;

FIG. 49 is a flow chart depicting the preferred method of assembling a mounting system;

FIG. 50 is an exploded front view of a mounting system;

FIG. 51 is an assembled front view of the mounting system of FIG. 50;

FIG. 52 is an oblique view of a mounting plate of the mounting system of FIG. 50; and

FIG. 53 is an oblique view of the mounting system of FIG. 51.

While the mounting system of the present application is susceptible to various modifications and alternative forms, specific embodiments thereof have been shown by way of example in the drawings and are herein described in detail. It should be understood, however, that the description herein of specific embodiments is not intended to limit the invention to the particular embodiment disclosed, but on the contrary, the intention is to cover all modifications, equivalents, and alternatives falling within the spirit and scope of the process of the present application as defined by the appended claims.

#### DETAILED DESCRIPTION

The present disclosure describes methods and systems for mounting or otherwise attaching an object to polymeric membranes. For example, in some instances, the present disclosure describes methods and systems for attaching objects to polymeric membranes utilized for covering all or a portion of a building structure roof. In some instances, the polymeric membranes may include thermoplastic polymeric membranes (“thermoplastic membranes”), while, in other instances, the polymeric membranes may include thermoset polymeric membranes (“thermoset membranes”). Example objects that may be attached include a solar system having photovoltaic cells, an air handling component (e.g., air conditioning or heating components), telecommunications equipment (e.g., antennas, satellite dishes, etc.), or any other desired object. It should be understood that the materials described herein provide sufficient elasticity for the features described below.

Utilizing the described systems and methods for securing one or more photovoltaic cells to the roof of a structure may provide tax benefits. For example, tax benefits may exist for having photovoltaic cells attached to the structure of a roof that are otherwise unavailable for photovoltaic cells that are merely placed on a roof unattached to the roof structure. Thus, in some implementations, the system and methods described herein provide for attaching an object to the roof structure, and, in the case of photovoltaic cells, may enable a user to enjoy the available tax benefits associated therewith.

In other implementations, the described methods and systems may be utilized for attaching objects to a polymeric membrane forming part of a structure. Further, while some implementations may be described with respect to thermoplastic membranes, thermoset membranes may also be applicable and vice versa. In general, the described methods and systems may be applicable to applications including roofing, waterproofing, earth lining, pond lining, tent construction, tension fabric applications, air forming technologies, flexible plastic forming (such as with flexible plastic films), rigid plastic forms, as well as any other suitable application.

FIG. 1A shows a perspective view of an example implementation of a system for mounting an object to a polymeric membrane. FIG. 1A shows a polymeric membrane (inter-

4

changeably referred to as “membrane”) 10 and a mounting plate 20. In some instances, the polymeric membrane 10 is a thermoplastic membrane. Example thermoplastic membranes may include polyvinyl chloride (PVC), thermoplastic olefins (TPO), ketone ethylene esters (KEE), nitrile butadiene polymers (NBP), as well as other suitable thermoplastics. In other instances, thermoset membranes may also be used. For example, examples thermoset membranes may include membranes formed from ethylene propylene diene monomer (EPDM) as well as any other suitable thermoset membranes, including thermoplastic membranes that may morph into thermoset membranes over time, such as chlorosulfonated polyethylene (CSPE).

The polymeric membrane 10 may be secured to a structure 40, such as a roof structure. The polymeric membrane 10 may be secured to the structure 40 in any known or suitable manner. Further, in some instances, the mounting plate 20 may be formed entirely or in part from a metal, such as steel, galvanized steel, aluminum, titanium, or other desired or suitable metal. Additionally, the mounting plate 20 may or may not be weatherized. In other instances, the mounting plate 20 may be formed from other materials, such as glass, plastic, ceramics, composite materials, or any other material. It should be appreciated that some applications may not require polymeric membrane 10; as such, mounting plate 20 may be bonded or attached directly to structure 40 without the use of polymeric membrane 10.

As shown, the mounting plate 20 has a protrusion 30 extending therefrom that may be used for securing a structure. The protrusion 30 may allow attachment and detachment of the structure, such as structure 35, without damage or alteration to the polymeric membrane 10. For example, in some instances, the protrusion 30 may provide for a threaded connection with structure 35, although any other suitable connection mechanism may be used. In other implementations, the mounting plate 20 may be integral to a structure. In still other implementations, the mounting plate 20 may omit the protrusion 30. Alternately, the mounting plate 20 may include a mechanism for attaching or detaching a corresponding structure thereto. For example, the mounting plate 20 may include an interlocking mechanism for accepting one or more structures. Example structures may include one or more photovoltaic cells, air handling equipment (e.g., air conditioning equipment or heating equipment), one or more antennas, mounting structures therefor, a barrier, or any other desired structure.

In still other implementations, an example mounting plate 20 may include a threaded portion for mating engaging with a corresponding threaded portion provided on a structure to be attached or otherwise coupled to the mounting plate 20. For example, FIG. 1B shows a mounting plate 20 that includes a welded nut 22 for accepting a protrusion having mating threads. Alternately, as shown in FIG. 1C, the mounting plate 20 may have a threaded portion 24 formed therein for accepting the protrusion.

FIG. 1D shows a cross-sectional view of another example mounting plate 20 in which the protrusion 30 is a separate piece insertable into an opening 32 formed in the mounting plate 20. Further, a head 34 of the protrusion 30 may be retained in a pocket 36 formed in the mounting plate 20. In other instances, the head 34 may not be retained in a pocket formed in the mounting plate 20. In some implementations, the protrusion 30 may be a carriage bolt insertable into the opening 32, and the interface between the opening 32 and the protrusion 30 prevents the protrusion 30 from rotating relative to the mounting plate 20. Further, a mounting plate 20 having

5

an opening **32** of a single size may be operable to accept protrusions **30** having varying shaft lengths, widths, and/or diameters.

The mounting plate **20** may be attached to the polymeric membrane **10** in numerous ways. FIGS. 2A-2C show several cross sectional views of the mounting plate **20** attached to the polymeric membrane **10**. For example, FIG. 2A shows the mounting plate **20** attached to the membrane **10** with a binding agent, such as an adhesive **50**, disposed therebetween. Alternately, the binding agent for securing the mounting plate **20** may be a carrier tape **60** having adhesive **70**, **80** provided on opposing sides thereof, as shown in FIG. 2B. In some implementations, the carrier tape **60** may have a removable protective film or backing **65**. In some instances the adhesive **70** and adhesive **80** may be the same adhesive, while, in other instances, the adhesives **70**, **80** may be different. For example, adhesives **70**, **80** may be selected based on the material being adhered. For example, for a mounting plate **20** formed from steel, the adhesive **70** may be selected to adhere steel, while, for a membrane **10** formed from PVC, the adhesive **80** may be selected to adhere to PVC. In some instances the carrier tape **60** may be a foam-based tape. Carrier tape **60** may be used to secure the mounting plate **20** to the membrane **10**. One or more tape strips or sheets may be used to secure the mounting plate **20**. Further, the carrier tape **60** may be custom shaped and/or formed to fit to geometry of the mounting plate **20**. For example, the carrier tape **60** may be custom fit to correspond to one or more geometric features of the mounting plate **20**, such as protrusions or other topographical shapes.

Multiple options for adhesives **50**, **70**, and **80** are available and selecting an appropriate adhesive is often dependent upon the desired engineered failure during testing. In some instances, it may be desirable for the adhesion provided by the selected adhesive to give way at a chosen weight threshold preventing damage to other components within the assembly. In other instances, it may be desirable for the adhesive bond to be so strong that components would not separate without damage to one surface or another. In addition, the selected adhesive may be applied to a carrier tape, the carrier tape and selected adhesive also being capable of being engineered with a chosen weight threshold and thickness. Adhesives **50**, **60**, and **70** include cross linking as well as non-cross linked butyl adhesives. A non-exclusive list of adhesives **50**, **70**, and **80**, as well as carrier tapes **60**, that may be used are: 3M VHB 4941 F, 3M VHB 4941, 3M VHB 4932, 3M VHB 4952, 3M VHB 5925, 3M VHB 5952, 3M VHB 5962, 3M weather strip tapes, 3M Polyurethane 560, 3M Hybrid Sealant 760, 3M DP 190, 3MDP 125, and 3M 1099 Scotch Weld Adhesive, all of which are produced by 3M of 3M Center, St. Paul, Minn. 55144. Additionally, Ashland Aroset 1930 produced by Ashland Inc of Covington, Ky. 41012 is another example of a suitable adhesive. Further, SikaLastomer-68 produced by Sika Corporation of Madison Heights, Mich. 48071, is example of a suitable carrier tape. The following companies make similar or competing adhesive to those named above: Carlisle Syntec of Carlisle, Pa., Carlisle Hardcast Incorporated of Wylie, Tex., and Firestone Building Products of Indianapolis, Ind. It should be appreciated that the adhesives and carrier tapes identified above may be identified as adhesives alone, or as carrier tape alone, or any combination of carrier tape and adhesive.

FIG. 2C shows another example implementation in which the binding agent may be a coating of thermoplastic material **90** applied to one or more surfaces of the mounting plate **20** placed into contact with the polymeric membrane **10**. For example, the polymeric membrane **10** may be a thermoplastic membrane. The mounting plate **20** may be located at a desired

6

location on the polymeric membrane **10**, and the coating **90** may be heated to form a bond between the mounting plate **20** and the polymeric membrane **10**. In some instances, the coating **90** may be heated by heating the mounting plate **20**, such as with a thermoinduction welder or hot iron. In other instances, energy may be applied more directly to the coating **90**, such as with sonic welding. For example, the mounting plate **20** may be affixed using the coating **90** such as by dielectrical or sonic or vibration welding, solvent bonding, heat bonding (such as using induction heating, infra red heating, hot air heating, or hot iron heating), any combination of the above, or in any other suitable manner.

It should be appreciated that thermoplastic coating **90**, as well as the thermoplastic coatings described in the other embodiments herein, may be represented in a variety of forms. Such forms include, but are not limited to: solids, liquids, or any mixtures of material phases suitable for the implementations disclosed herein.

A further example mounting system is shown in FIG. 3. FIG. 3 shows a mounting plate **20** secured to a polymeric membrane **10** (e.g., a thermoplastic membrane) with a binding agent **100**. According to various implementations, the binding agent **100** may be, for example, a coating of thermoplastic material applied to a contact surface of the mounting plate **20**. With the thermoplastic coating, the mounting plate **20** may be located at a desired location on the polymeric membrane **10** and heated to bind the mounting plate **20** to the polymeric membrane **10**. Alternatively, any adhesive or carrier tape, such as the adhesives and carrier tapes described above, may be used to secure the mounting plate **20** to the membrane **10**. The combination of the mounting plate **20** and the polymeric membrane **10** may be considered a mounting assembly **110**.

Referring still to FIG. 3, the mounting assembly **110** may be attached to a polymeric membrane **120**. In the present example, the polymeric membrane **120** may be a thermoplastic membrane. However, in other instances, the polymeric membrane **120** may be a thermoset membrane. The mounting assembly **110** may be attached to the polymeric membrane **120** in numerous ways. For example, the polymeric membrane **10** of the mounting assembly **110** may be coupled to the polymeric membrane **120** using one or more of the methods described above in regards to the bonding of mounting plate **20** to polymeric membrane **10**. In other instances, a bonding agent **130**, such as a carrier tape and/or adhesive (such as the carrier tape and adhesive, described respectively above) may be used. It should be appreciated that bonding agent **130** may be another bonding medium, including various bonding materials or various bonding members. Similar to above, the carrier tape may be applied in pieces, such as one or more strips or sheets. Further, as also described above, the carrier tape may be formed to correspond to geometry of the mounting assembly **110**.

FIGS. 4 and 5 illustrate an alternate implementation for securing the mounting assembly **110** to the polymeric membrane **120**. As shown, a central portion **140** of the mounting assembly **110** may be secured to the polymeric membrane **120** with an adhesive material **145**, such as one or more pieces of carrier tape or adhesive, such as the carrier tape and adhesive described above. Another attachment method or material may be used around a perimeter portion **150**. For example, a coating of thermoplastic material **155** at one or more locations along the perimeter portion **150** may be used to secure the perimeter portion **150** to the polymeric membrane **120**. The coating of thermoplastic material **155** may be bonded using one or more of the methods described above. Alternately, one or more of an adhesive or carrier tape may be used

on the perimeter portion **150**. For example, the bonding material used on the perimeter portion **150** may act to further secure the mounting assembly **110** or as a waterproofing material.

It is noted that, in some instances, a coating of thermoplastic material may be used to bond one thermoplastic membrane to another same or similar thermoplastic membrane. In other instances, the thermoplastic material may be omitted. For example, some thermoplastic membranes may be joined using one or more of the welding techniques above without the aid of a bonding material. On the other hand, a coating of thermoplastic membrane may not be capable of bonding a thermoplastic membrane or thermoset membrane to another thermoset membrane. In such instances, an adhesive, such as an adhesive or carrier tape may be used to bond such dissimilar materials to each other.

In some instances, the polymeric membrane **120** may be the same or a similar thermoplastic as a thermoplastic forming the thermoplastic membrane **10**, such as one or more of the thermoplastics described above. However, the thermoplastics forming the respective thermoplastic membrane **10** and the thermoplastic membrane **120** may be different while still bondable with or without the use of a thermoplastic material. In some instances, the thermoplastic membrane **120** may form an outer surface of a roof structure. However, the description is not so limited, and the present description may be applicable to a thermoplastic membrane in any desired application.

The mounting plate **20** may be of any desired shape. For example, the mounting plate may be circular, rectangular, square, elongated, or be of any other size or shape. Example mounting plates are illustrated in FIGS. 6-8. FIGS. 6A-6E show various views of a circular mounting plate **20** having a plurality of concentric ridges **21** formed therein as well as a central cavity **22** that may be used to capture a head of a protrusion, as discussed in a similar manner above. As also described above, the central cavity **22** may accept a protrusion of different sizes. The protrusion may extend through opening **23**.

Referring to FIGS. 7A-E, the example mounting plate **20** also includes cavities **22** to accept the heads of protrusions. The protrusions may extend through openings **23** formed in a wall of the cavities **22**. FIGS. 8A-D are various views of another example mounting plate **20**. The mounting plate **20** may include various ridges **24** formed therein along with a cavity **22** and opening **23**. Again, the cavity **22** may be used to capture an end portion of a protrusion extending through the opening **23**. The mounting plate **20** may also include openings **25** formed around a periphery thereof.

Further, for the example mounting plate **20** shown in FIG. 6A-8D along with others within the scope of the disclosure, the cavities **22**, openings **23**, and/or the combination thereof may be operable to prevent rotation of the protrusion relative to the mounting plate **20** while also accepting protrusions of different sizes. Additionally, the respective sizes of the ridges **24**, openings **23**, cavities **22**, as well as other aspects of the mounting plates **20** may be altered to any desired size.

Another example mounting system is shown in FIG. 9 in which a mounting plate **20** is disposed between a first polymeric membrane **500** and a second polymeric membrane **510**. Fasteners **520** extend through the mounting plate **20**, the second polymeric membrane **510**, and into a substructure **530**. The first polymeric membrane **510** overlays a first surface **540** of the mounting plate **20** and includes an opening **550** through which the protrusion **30** extends. A bonding material **560** may be used to adhere the first polymeric membrane **500** to the mounting plate **20**.

In some instances, the bonding material **560** may be a coating of a thermoplastic material applied to a portion of the first surface **540** between the protrusion **30** and openings **570** formed in the mounting plate **20** through with the fasteners **520** extend. Still further, in some instances, the bonding material **560** may be applied and the first polymeric membrane **500** coupled therewith to the mounting plate **20** during one or more manufacturing processes. That is, bonding the first polymeric membrane **500** to the mounting plate **20** with the bonding material **560** may be performed remote from a job site, such as at a manufacturing facility. In other instances, the first polymeric membrane **500** may be bonded to the mounting plate **20** with the bonding material **560** at a jobsite. The bonding material **560** may be a coating of thermoplastic material and used to bond the two components in one or more of the methods described above. In addition to adhering the first polymeric membrane **500** to the mounting plate **20**, the bonding material **560** may also form a seal preventing or substantially preventing fluids from penetrating through the opening **550** formed through the openings **570** and into the substructure **530**.

A bonding material **580** may also be applied to the first surface **540** of the mounting plate **20**. In some instances, the bonding material **580** may also be used to secure the first polymeric membrane **500** to the mounting plate **20**, such as after the fasteners **520** have been used to secure the mounting plate **20** to the substructure **530**. Utilizing the bonding material **580** after fasteners **520** have been applied avoids the need to puncture the first polymeric membrane **500** for the fastener **570**. Thus, in some instances, the bonding material **560** may be used to secure only a portion of the first polymeric membrane **500** to the mounting plate **20** while still allowing passage of the fasteners **520** through the openings **570** without the need to puncture the first polymeric membrane **500**. The bonding material **580** may be utilized thereafter to secure the first polymeric membrane **500** to the mounting plate **20** thereby also providing a seal. The first polymeric membrane **500** may also be secured to the second polymeric membrane **510** with a bonding material **590**. Also, a coating or bonding material may be omitted where the polymeric membranes are capable of being joined without such materials. For example, the membranes may be thermoplastic membranes capable of being joined using one or more of the bonding techniques described above. In such instances, the bonding material **590** may be omitted.

A bonding material **600** may also be used to secure the mounting plate **20** to the second polymeric membrane **510**. The bonding materials **560**, **580**, **590**, and **600** cooperate to form a seal around the mounting plate **20** to aid in preventing or substantially reducing penetration of fluids and/or debris into the substructure **530**. One or more of the bonding materials **560**, **580**, **590**, and **600** may be a coating of a thermoplastic material and used to form a bond using one or more of the techniques described above. In some instances, the bonding materials **560**, **580**, and **590** may be the same material, such as a coating of thermoplastic material **610**, and may be applied to the mounting plate **20**, as shown in the example of FIG. 10. Alternately, one or more of the bonding materials **560**, **580**, **590**, and **600** may be a carrier tape or adhesive as also described above. In still other implementations, one or more of the bonding materials **560**, **580**, **590**, and/or **600** may be omitted. For example, in some implementations, the polymeric membranes **500**, **510** may be secured directly to each other using one or more of the joining techniques described above without the use of a bonding material. Still further, the mounting plate **20** may also be formed from a material that is joinable to one or more of the polymeric membrane **500**

and/or polymeric membrane **510** without the use of a bonding agent using one or more of the techniques described above. In such instances, one or more of the bonding materials **560**, **580**, and/or **600** may be omitted.

The mounting plate **20** is shown with a protrusion **30** includes, although the protrusion **30** may be omitted. Alternatively, the mounting plate **20** may be fixedly attached to another object. Still further, the mounting plate **20** may have a mechanism for selectively attaching and detaching another object.

FIGS. **11** and **12** show another example system **700** in which one or more mounting plates **710** are secured to a structure **720**. For example, the structure **720** may be a roof structure, although structure **720** is not so limited but may encompass other structures, such as one or more of the structures identified above or other suitable structure. In some instances, the mounting plates **710** may be coupled to the structure **720** with fasteners, although the mounting plates **710** may be attached in other ways. A polymeric membrane **725** is applied over the mounting plates **710**, such as by unrolling a roll of the polymeric membrane **725**. An example mounting plate **710** is shown in FIG. **12**. The mounting plate **710** may include a protrusion **730**. Further, in some implementations, the protrusion **730** may include a piercing portion **740** adapted to puncture the polymeric membrane **725**. Also, a portion of the protrusion **730** may include a fastening portion **735** that may be used to attach a structure to the mounting plate. For example, in some instances, the fastening portion **735** may be a threaded portion. However other fastening mechanisms may also be used.

One or more of the mounting plates **710** may be secured to the structure **720**, such as in an array or any other configuration. The mounting plates **710** may be secured with fasteners and/or with one or more of the techniques described herein (e.g., using a coating of thermoplastic material, carrier tape, adhesive, etc.). With the mounting plates **710** secured to the structure **720**, the polymeric membrane **725** may be overlaid. The mounting plate **725** may be made to extend through the polymeric membrane **725** such as by puncturing the polymeric membrane **725** with the piercing portion **740**. In other implementations, the polymeric membrane **725** may have preformed openings to allow the protrusions **730** to extend therethrough. The polymeric membrane **725** may be secured to the mounting plate **710** using one or more of the techniques described above. For example, the mounting plate **710** may be coupled to the polymeric membrane **725** with a bonding material **727**. The bonding material **727** may be one or more of the materials discussed above and the coupling may be formed using one or more of the methods described above.

FIG. **13** shows another example system **900** including a mounting plate **910** coupled to a substructure **920**. Among other uses, the system **900** may be applicable to roofing applications. The mounting plate **910** is shown as being attached with fasteners **930**. However, other techniques may be used to secure the mounting plate **910** to the substructure **920**. The mounting plate **910** may include a protrusion **940** and a piercing portion **950**. Further, in some implementations, the protrusion **940** may include a fastening portion **955**. Additionally, while the protrusion **940** is shown as an integral portion of the mounting plate **910**, the protrusion **940** may be attached to the mounting plate **910** using a fastening mechanism. For example, in some implementations, the protrusion **940** may be attached to the mounting plate **910** via a threaded connection. An insulating member **960** may be disposed above the substructure **920**. An attachment member **970** may be secured to the protrusion **940**, such as by engaging the fastening portion **950**. In some implementations, the fasten-

ing portion **950** and attachment member **970** may have a threaded engagement, although other attachment interfaces may be used. A polymeric membrane **965** overlays the insulating member **960** and may be bonded to the attachment member **970** with a bonding material **980**. In some implementations, the bonding material **980** may be a coating of thermoplastic material applied to attachment member **970**. In other implementations, a carrier tape and/or an adhesive may be used to couple polymeric membrane **965** to the attachment member **970**.

In addition, the described methods and systems can also reduce damage to a polymeric membrane. For example, when objects are unattached but are in contact, debris may become lodged between the object and the polymeric membrane, and, because of the relative movement between the two, the debris may act as an abrasive on the polymeric membrane. Over time, holes, rips, or other damage may occur to the polymeric membrane exposing the underlying structure to the environment, such as moisture, wind, etc. This exposure can cause damage to the structure. However, the present disclosure describes methods and systems that avoid these drawbacks.

Additionally, some of the methods and systems described herein also provide for securing one or more objects to a polymeric membrane without piercing the polymeric membrane. Consequently, objects remain attached to the polymeric membrane without providing a pathway for moisture or other objects, e.g., insects, debris, etc., to pass through the membrane. Again, this can have particular value in waterproofing covering applications where an unperforated covering is greatly desired.

Another example system **1000** is illustrated in FIG. **14**. The system **1000** includes a polymeric membrane **1010**, a ridge member **1020**, and a bonding member **1030**. In some implementations, the polymeric membrane **1010** may form a portion of a roof structure, such as an exterior membrane. The ridge member **1020** may be coupled to the polymeric membrane **1010** by the bonding member **1030**. In some instances, the bonding member **1030** may be a double sided carrier tape similar to the carrier tape described above. In some implementations, the adhesive on the sides of the carrier tape may be selected to provide a bond according to the material forming the polymeric membrane **1010** and/or the ridge member **1020**. In other implementations, the bonding member **1030** may be an adhesive selected to adhere polymeric membrane **1010** to the ridge member **1020**. In some instances, the adhesive may be an adhesive similar to the adhesive described above.

The bonding member **1030** may occupy a channel **1040** formed in a base **1050** of the ridge member **1020**. Lips **1055** may also be formed in the ridge member **1020** to aid in preventing intrusion of fluids and other materials into the channel **1040**. A benefit of the bonding member **1030** is that while coupling the ridge member **1020** to the polymeric membrane **1010**, the bonding member **1030** may have a bonding strength less than the yield strength of the polymeric membrane **1010** and/or the ridge member **1020**. Consequently, the bonding member **1030** will yield, separating the ridge member **1020** from the polymeric membrane **1010** when a shearing load on the ridge member **1020** exceeds the strength of the bonding member **1030**. Consequently, the bonding member **1030** will yield without damaging either the ridge member **1020** or the polymeric membrane **1010**. For example, in an application in which the polymeric membrane **1010** and ridge member **1020** form an exterior portion of a roof structure, a shearing force on the ridge member **1020**, for example, caused by a sheet of ice formed on the roof structure, would not tear the polymeric membrane **1010** as the ice



## 11

sheet moves down a slope of the roof. Rather, the shearing force would merely sever the ridge member **1020** from the polymeric membrane **1010**. In other implementations, the bonding member **1030** may have a yield strength equal to or greater than one or more of the ridge member **1020** and/or the polymeric membrane **1010**.

Referring now to FIGS. **15** and **16** in the drawings, FIG. **15** shows an oblique view of a mounting system **1501** according to the preferred embodiment of the present invention, while FIG. **16** shows an oblique view of mounting system **1501** attached to a support structure **1601**. It should be appreciated that mounting system **1501** is substantially similar in form and function to the mounting systems described above. Like the mounting systems disclosed herein, mounting system **1501** utilizes one or more membranes to securely attach an object to the support structure, which includes, but should not be limited to a polymeric membrane and/or a rooftop. Mounting system **1501** comprises one or more membranes that elastically extend as a force is exerted on the object attached thereto. Further description and illustration of the elastic membrane is provided with reference to FIGS. **17-20C**.

Mounting system **1501** comprises one or more of a first membrane **1503**, a second membrane **1505**, and an object **1507**. First membrane **1503** is preferable composed of a polymeric material and is adapted to securely bond with at least a portion of second membrane **1505**. It should be understood that first membrane **1503** is an optional membrane. For example, second membrane **1505** could attach directly to the support structure. However, as in most applications, the first membrane is adapted to attach directly to the support structure and the second membrane is adapted to bond to a top surface of the first membrane.

In the preferred embodiment, second membrane **1505** thermally fuses to first membrane **1503**; however, it should be appreciated that alternative embodiments could incorporate different methods for bonding second membrane **1505** to first membrane **1503**, as disclosed herein and as conventional known in the art. Object **1507** is preferable a mounting plate substantially similar in form and function to the mounting plates disclosed herein; however, it should be understood that object **1507** should not be limited to a mounting plate, but could include other devices in lieu of a mounting plate. For example, in some embodiments, object **1507** could be an attachment device, i.e., a quick-release device, for securing a structure to mounting system **1501**. Mounting system **1501** is further provided with an optional protrusion **1509** adapted to attach to object **1507**. Protrusion **1509** is substantially similar in form and function to the protrusions disclosed herein, wherein the protrusion is utilized for securing a riser (not shown) to mounting system **1501**.

It should be understood that mounting system **1501** could include the additional features of the mounting systems disclosed above. For example, mounting system **1501** could include a third polymeric material, a riser, a bonding medium, and/or other features described herein. Furthermore, the first and second membranes of mounting system **1501** could be composed of the same elastic materials described herein in addition to other suitable materials for providing elasticity to second membrane **1505** and/or any other desired membrane.

Referring now to FIGS. **17** and **18** in the drawings, front views of mounting system **1501** are shown. FIG. **17** shows an assembled mounting system **1501**, while FIG. **18** shows and exploded view of mounting system **1501**. Object **1507** includes a bottom surface **1801** which bonds to an upper surface **1803** of second membrane **1505**. Second membrane includes a lower surface **1805** which bonds to a top surface

## 12

**1807** of first membrane **1503**. First membrane **1503** includes a bottom surface **1809** which attaches to a top surface **1811** of support structure **1601**.

Referring to FIG. **19** in the drawings, a bottom view of second membrane **1505** is shown. Lower surface **1805** preferably comprises two surface areas, a first surface area **1901** being adapted to extend peripherally around a perimeter of lower surface **1805**, and a second remaining surface area **1903**, which is preferably enclosed within surface area **1901**. In the preferred embodiment, area **1901** is bonded to top surface **1807** of first membrane **1503**, while area **1903** remains separable from top surface **1807** of first membrane **1503**. This feature allows second membrane **1505** to elastically extend in a direction away from first membrane **1503** as a force is exerted on object **1507**.

Referring to FIGS. **20A-20C** in the drawings, front views of mounting system **1501** are shown. FIGS. **20A-20C** depicts second membrane **1505** elastically extending away from support structure **1601**. Specifically, as a force *F* is exerted on object **1507**, second membrane **1505** elastically extends in the direction of the force, and then returns to its original position after the force dissipates. FIG. **20A** shows mounting system **1501** prior to force exerted against object **1507**. FIG. **20B** shows second membrane **1505** elastically extending in direction *D1* as a force *F* is exerted on object **1507**. FIG. **20C** shows second membrane **1505** moving in the direction *D2*, thus returning back to its original position after force *F1* is applied.

Referring now to FIGS. **21** and **22** in the drawings, respective top and side cross-sectional views of a mounting plate **2101** are shown according to the preferred embodiment of the present invention. It should be appreciated that mounting plate **2101** is substantially similar in function to the mounting plates shown and described herein. Specifically, mounting plate **2101** is adapted to secure an object such as a fastener, riser, attachment device, and/or other suitable device to the mounting system.

During assembly, a worker attaches an object, i.e., a solar panel attachment, to the mounting plate, and in some embodiments, it is not feasible to couple the object at a desired position and orientation because the raised surfaces of the mounting plate causes the object to tilt. The mounting plate of the present invention overcomes such problems by extending the contact surface area between the mounted object and the mounting plate, which in turn creates a relatively planar surface area for mounting objects thereto. To do this, mounting plate **2101** is provided with one or more elongated members adapted to extend from a primary housing. The housing and members form a relatively planar surface area for supporting the object resting thereon. Of course, it should be understood that mounting plate **2101** is not intended to be limited to the figures and description below, but could include the features of the mounting plates described herein and other modifications without departing from the spirit thereof.

Mounting plate **2101** comprises a housing **2103** raised from a base **2105**, the housing being adapted to receive and support an object, i.e., a riser (not shown) thereon. Housing **2103** preferably forms a cavity **2201** for receiving a bolt, nut, and/or other any other type of fastener. However, it should be appreciated that alternative embodiments could include a solid housing, in lieu of a hollow cavity, and a shaft disposed therein for fastening to the object. Housing **2103** creates a contact surface area **2107**, which receives and supports the object attached to mounting plate **2101**.

Mounting plate **2101** is provided with one or more elongated members **2109** with a top surface area **2111** having a height relative flush with contact surface area **2107**. Members **2109** are adapted to extend the contact surface area between

13

the object and mounting plate **2101**, which in turn creates a relatively planar surface area for mounting objects thereto. In the preferred embodiment, housing **2103** and members **2109** form a continuous contact surface area. However, it should be appreciated that alternative embodiments could include members spaced apart from housing **2103**. For example, alternative embodiments could include one or more isolated members spaced apart from the housing and adapted to receive and maintain a flush surface area with the housing for mounting an object thereon.

In the preferred embodiment, mounting plate **2101** comprises five elongated members **2109**, each member having a longitudinal centerline A, and each longitudinal centerline A being oriented at the same angle B relative to each other on a surface planar to base **2105**. It should be appreciated that alternative embodiments could include more less elongated members for supporting the object. For example, alternative embodiments could include three members in lieu and/or different angles relative to each other.

Mounting plate **2101** is further provided with one or more optional holes **2113** for receiving a fastener (not shown) and a hole **2115** extending through the thickness of housing **2103**. Hole **2115** is utilized to either receive an attachment device, i.e., a fastener, of the object being attached thereon or adapted to allow a fastener to extend therethrough for fastening to the object. In some embodiments, hole **2115** could be threaded for threadingly engaging with a threaded fastener. Mounting plate **2101** also includes an optional rim **2117** extending peripherally along an edge of base **2105**. It should be appreciated that although shown in the circular form, mounting plate **2101** could easily be manufactured in different geometric shapes, depending on the desired application.

Referring to FIG. **23** in the drawings, a cross-sectional side view of mounting plate **2101** taken at XXII-XXII is shown attached to mounting system **1501**. In the preferred embodiment, an adhesive, as described herein, is applied to a bottom surface **2203** of mounting plate **2101** and thereafter bonded, preferably thermally fused, to membrane **1505** of mounting system **1501**. In the exemplary embodiment, a fastener **2301** is shown securely positioned within cavity **2201**.

Referring now to FIG. **24** in the drawings, a front view of an alternative embodiment of mounting plate **2101** is shown. Mounting plate **2401** is adapted with a perforated surface area **2403**. The perforated areas allow the membrane of the mounting system to extend therethrough as heat is applied to the membrane. Thereafter, the membrane securely bonds to above, within, and below the perforated areas after the membrane is cooled.

It should be appreciated that mounting plate **2401** is substantially similar in function to the mounting plates shown and described herein. Specifically, mounting plate **2401** is adapted to secure an object such as a fastener, riser, attachment device, and/or other suitable device to the mounting system. The features of the mounting plates described herein could easily be adapted to include the features of mounting plate **2401**, and likewise mounting plate **2401** could be adapted to include the features of the mounting plates described herein. Of course, it should be understood that mounting plate **2401** is not intended to be limited to the embodiment shown in FIG. **24**, but includes the features of the mounting plates described herein and other modifications without departing from the spirit thereof.

Referring now to FIGS. **25** and **26** in the drawings, FIG. **25** shows an oblique view of a riser **2501** according to the preferred embodiment of the present invention, while FIG. **26** shows a front cross-sectional view of riser **2501** taken at XXVI-XXVI of FIG. **25**. In the preferred embodiment, riser

14

**2501** is adapted to couple to and elevate an object, i.e., an attachment device for a solar panel, at a desired height, preferably 4 inches, above a structure. It should be understood that, riser **2501**, and the alternative embodiments disclosed herein, are adapted to couple to one or more of the mounting systems described herein and/or other modifications without departing from the spirit thereof. In addition, it should be appreciated that riser **2501** and other alternative embodiments thereof could easily be adapted to fasten to other types of devices in lieu of a mounting assembly.

Riser **2501** is preferably composed of a rigid, metallic material such as aluminum, which allows little to no flexure, thus restricting transverse, longitudinal, and rotational movement of riser **2501**. The metallic material allows an object, such as a solar panel, to rigidly attach to the structure via riser **2501**. However, it should be appreciated that alternative embodiments of riser **2501** could be composed of different materials, both flexible and rigid, depending on the preferred application. For example, riser **2501** could be composed, partially or in whole, of a composite, wood, and/or an elastomeric material, which creates flexibility, conductive resistance, and/or other desired attributes.

Riser **2501** provides significant advantageous over conventional devices for securing an object to a roof structure. Specifically, riser **2501** is preferably manufactured through an extruding process, wherein multiple risers are formed simultaneously as a continuously extruded member. During the manufacturing process, the extruded member is transversely cut to form individual risers. Then, two opposing holes are machined on opposing surfaces of the riser for attaching the riser to both the mounting plate and the object coupled thereto. The relatively simple design and advanced extruding process greatly reduces the manufacturing costs.

Riser **2501** comprises an attachment portion **2503** for securing an object to riser **2501** and a base portion **2505** for coupling riser **2501** to one or more mounting systems described herein. In the exemplary embodiment, riser **2501** is adapted to attach to mounting assembly **110**, which in turn attaches to a roof structure. Of course, it should be understood that although described as being utilized with a roof structure, riser **2501** could easily be utilized with other structures in lieu of the preferred roof structure, i.e., a vertical wall, membrane for covering ponds, and/or other suitable structures.

Riser **2501** comprises a first sidewall **2507** and a second sidewall **2509** extending relatively parallel to each other. The sidewalls are adapted to elevate attachment portion **2503** at a predetermined height relative to the structure (not shown). Riser **2501** further comprises a first attachment device **2511**, which is preferable a hole extending through the thickness of base **2505** and a second attachment device **2513**, which is preferable a hole extending through the thickness of attachment portion **2503**. Attachment device **2511** is adapted to couple riser **2501** to the mounting plate, while attachment device **2513** is adapted to couple an object to riser **2501**.

Base **2505** preferably includes two elongated leg members, a first leg **2515** and a second leg **2517**, both legs being adapted to elevate base **2505** at a height H1 above the top surface of the mounting plate. In the preferred embodiment, leg **2515** and leg **2517** elevate base **2505** above one or more raised surfaces of the mounting plate. For example, the mounting plate, as shown and described above, could include a raised surface directly underneath base **2505**, thereby requiring base **2505** to be raised at a height H1 to create a tight, secure fit between riser **2501** and the mounting system. It should be appreciated that leg **2515** and leg **2517** are optional features and are not required in alternative embodiments wherein the mounting plate is devoid of raised surfaces below base **2505**. In these

15

alternative embodiments, base **2505** could easily be adapted to sit directly on the top surface of the mounting plate.

Attachment portion **2503** includes one or more surfaces for abutting against the object coupled thereto (see FIG. **27**). Attachment portion **2503** preferably comprises six surfaces, a front surface **2519**, an opposing rear surface **2521**, a side surface **2523**, an opposing side surface **2525**, a first top surface **2527**, a second top surface **2529**, and an elevated top surface **2531**. In the preferred embodiment, riser **2501** has a length **L**, a top surface width **W1** extending the width of surface **2529**, a top surface width **W2** extending the width of surface **2531**, a top surface width **W3** extending the width of surface **2527**, and a height **H2** extending the height between top surface **2531** and surface **2529**. In the preferred embodiment, **W2** is greater than **W1** or **W3** and **H2** has a length of approximate  $\frac{3}{8}$  of an inch. Of course, it should be understood that the foregoing lengths, widths, and heights are not intended to limit riser **2501** to these dimensions. It should be appreciated that alternative embodiments could include different dimensions depending on the desired application.

In the preferred embodiment, an object **2701**, like that shown in FIG. **27**, rests on top surface **2531** and/or top surfaces **2527** and **2529**. Side surfaces **2527** and **2529** and/or front surface **2519** and rear surface **2521** provide means for restricting movement of the object. For example, the object could include a surface extending alongside surface **2523**, which creates contact and restricts rotational movement of the object as rotational torque is applied thereto.

Referring now to FIG. **27** in the drawings, a front cross-sectional view of riser **2501** is shown attached to mounting assembly **110** and shown attached to an object **2701**. It should be noted that the term mounting assembly and mounting system are interchangeable used herein, and intended to refer to a system adapted to secure an object to a structure. It should also be noted that the front view of mounting assembly **110** is depicted in FIG. **4** above. When assembled, protrusion **30** extends through attachment device **2511**, which in turn, is received by an attachment device **2703** for securing base **2505** to assembly **110**. In the preferred embodiment, attachment device **2703** is a nut **2705** threadingly engaged with protrusion **30**; however, it should be appreciated that alternative embodiments could include different attachment devices, i.e., a quick release device, snap, clip, and/or other suitable devices in lieu of the preferred embodiment.

Attachment device **2511** is preferable a non-threaded hole, which allows the protrusion to slide therein, while attachment device **2513** is preferably a threaded hole, which provides attachment means for a threaded bolt and/or other suitable device. It should be appreciated that alternative embodiments could include either threaded or non-threaded holes in lieu of the preferred embodiment.

During assembly, riser **2501** is positioned on plate **20** such that hole **2511** receives protrusion **30**. Thereafter, riser **2501** is attached to plate **20** with attachment device **2703** such that the legs of riser **2501** securely contact the top surface of plate **20**. Finally, object **2701** is placed on attachment portion **2503** and secured with attachment device **2707**, i.e., a bolt **2709**.

Referring now to FIGS. **28** and **29** in the drawings, FIG. **28** shows an oblique view of a riser **2801** according to an alternative embodiment of the present invention, while FIG. **29** shows a front cross-sectional view of riser **2801** taken at XXIX-XXIX of FIG. **28**. It should be noted that riser **2801** is substantially similar in function to riser **2501**, wherein both riser **2801** and riser **2501** are adapted to elevate an object at a predetermined height above a structure and both risers are adapted to securely attach to a mounting assembly. The fea-

16

tures of riser **2801** could easily be incorporated in riser **2501**, and likewise, the features of riser **2501** could be incorporated in riser **2801**.

Riser **2801** comprises an attachment portion **2803** for securing an object to riser **2801** and a base portion **2805** for attaching riser **2801** to a mounting assembly. Base portion **2805** is preferably a separate member rigidly attached to attachment portion **2803** through bonding means, i.e., welding, to form a unitary body with attachment portion **2803**. However, it should be appreciated that attachment portion **2803** and base **2805** could easily be manufactured as a single member in alternative embodiments. For example, riser **2801** could be manufactured through a lathing or milling process.

Riser **2801** comprises a first attachment device **2807**, which is preferably a hole, and a second attachment device, which is preferable a hole, both holes being adapted to extend partially through the thickness of attachment portion and base portion, respectively. Attachment device **2811** is adapted to couple riser **2801** to mounting assembly **110**, while attachment device **2807** is adapted to secure an object to riser **2801**. It should be appreciated that alternative embodiments could include a continuous conduit interconnecting the two opposing attachment devices in lieu of the preferred embodiment. In the preferred embodiment, attachment device **2811** threadingly engages with protrusion **30** of mounting assembly **110**, and attachment device **2807** threadingly engages with a threaded bolt and/or other suitable attachment device.

In the exemplary embodiment, riser **2801** attaches to mounting assembly **110**. Of course, it should be understood that riser **2801** could easily be attached to other types of mounting assemblies, either attached to a roof structure or other types of structures.

During assembly, riser **2801** is positioned on plate **20** such that attachment device **2811** receives protrusion **30**. Thereafter, a worker rotates riser **2801**, which in turn, causes attachment device **2811** to threadingly engage with protrusion **30**. Finally, an object is placed on surface **2809** and secured with an attachment device (not shown), i.e., a fastener adapted to engage with attachment device **2807**.

Riser **2801** is further provided with a cavity **2815** for receiving a raised surface of the mounting plate. It should be appreciated that cavity **2815** is an optional feature and is not required in alternative embodiments where the mounting plate is devoid of raised surfaces directly beneath surface **2813**. In these alternative embodiments, base **2805** could easily be adapted to sit directly on the top surface of the mounting plate.

Referring now to FIGS. **30** and **31** in the drawings, FIG. **30** shows an oblique view of a riser **3001** according to an alternative embodiment of the present application, while FIG. **31** shows a front cross-sectional view of riser **3001** taken at XXXI-XXXI of FIG. **30**. FIG. **31** also shows riser **3001** coupled to mounting assembly **110**, as depicted in FIG. **4** above. It should be appreciated that riser **3001** is substantially similar in function to riser **2801** and riser **2501**, wherein riser **2801**, riser **2501** and riser **3001** are adapted to raise an object at a predetermined height above a structure and adapted to securely attach to a mounting assembly. The features of riser **3001** could easily be incorporated in both risers **2501** and **2801**, and likewise, the features of risers **2501** and **2801** could be incorporated in riser **3001**.

Like risers **2501** and **2801**, riser **3001** comprises an attachment portion **3003** for securing an object to riser **3001** and a base **3005** for attaching riser **3001** to a mounting assembly. In the preferred embodiment, riser **3001** is formed as a single member, preferably manufactured through the extruding process described above. Riser **3001** is provided with a first

attachment device **3007**, which is preferable a hole extending through the thickness of attachment portion **3003** and a second attachment device **3009**, which is preferably a hole extending through the thickness of base **3005**. Attachment device **3007** provides means for attaching riser **3001** to the roof structure, while attachment device **3009** provides means for securing an object to riser **3001**.

Riser **3001** is further provided with a structure **3011**, which can either be separable from or rigidly attached to base **3005** through a bonding process, i.e., welding, to form a unitary body with base portion **3005**. Structure **3011** elevates base **3005** above a raised surface area (not shown) of the mounting plate. Structure **3011** is provided with a cavity **3013** extending through the thickness of structure **3011** for receiving the raised surface and for allowing protrusion **30** to extend there-through.

During assembly, riser **3001** is positioned on plate **20** such that hole **3013** and hole **3007** receive protrusion **30**. Thereafter, an attachment device **3015**, i.e., a bolt **2117**, attaches to protrusion **30** for securing riser **3001** to mounting assembly **110**. Finally, an object is coupled to either a surface **2019** and/or a surface **2021** of attachment portion **3003** and secured with an attachment device (not shown) adapted to couple to hole **3009**.

Referring now to FIG. **32** in the drawings, an oblique view of an alternative embodiment of riser **2501** is shown. Riser **3201** is substantially similar in function to the risers described herein. Specifically, riser **3201** is adapted to elevate an object at a predetermined height above a structure via one or more of the mounting systems described herein. The features of riser **3201** could easily be incorporated in the risers described herein, and likewise the features of risers disclosed herein could be incorporated in riser **3201**.

Riser **3201** comprises one or more of an attachment portion **3203** having a top surface **3205** and an opposing base portion **3207** having a bottom surface **3209**. Attachment portion **3203** is adapted to support and attach to an object thereon, while base portion **3207** is adapted to secure riser **3201** to one or more of the mounting systems described herein.

Riser **3201** further comprises a sidewall **3211** rigidly attached to attachment portion **3203** and base portion **3209**. Sidewall **3211** elevates attachment portion **3203** at a predetermined height, preferably around 4 inches above a structure the mounting system is attached thereto. In the preferred embodiment, sidewall **3211** is manufactured in a curved profile, which is formed through a stamping manufacturing process. It should be appreciated that other profiles, i.e., rectangular profiles, could be utilized in lieu of the preferred embodiment. The curved profile provides sufficient rigidity for supporting the object coupled to attachment portion **3203**. In the preferred embodiment, riser **3201** is manufactured with a stamping process; however, it should be appreciated that alternative manufacturing process, i.e., milling, could be utilized in lieu of the preferred process.

Sidewall **3211** curves from a first end **3213** to a second end **3215**. In the preferred embodiment, sidewall **3211** does not attach to the entire edged surfaces of attachment portion **3203** and base portion **3207**. Attachment portion **3203** includes a top tab portion **3217**, while base portion **3207** includes a bottom tab portion **3219**. However, it should be appreciated that alternative embodiments could include a sidewall that attach to the entire edged surfaces of the top and bottom members.

Riser **3201** further comprises a first attachment device **3221**, which is preferable a hole extending through the thickness of attachment portion **3203** and a second attachment device **3233** extending through the thickness of base portion

**3207**. In the preferred embodiment, attachment portion **3221** is adapted to couple to the object being mounted thereto, and attachment portion **3223** is adapted to couple riser **3201** to one or more of the mounting systems described herein. It should be appreciated that attachment device **3221** and/or attachment device **3223** could either be threaded or unthreaded, depending on the preferred application.

Referring now to FIGS. **33** and **34** in the drawings, oblique and cross-sectional views of a mounting plate **3301** according to a preferred embodiment of the present application are shown. Mounting plate **3301** is substantially similar in function to the foregoing mounting plates. In particular, mounting plate **3301** is utilized to secure an object, i.e., a riser, to one or more of mounting systems discussed herein. It will be appreciated that the features of mounting plate **3301** and the foregoing mounting plates are interchangeable, for example, mounting plate **3301** could include the features of the mounting plate **2101** and/or mounting plate **2401**. Like the foregoing mounting plates, mounting plate **3301** preferably thermally bonds to upper surface **1803** of second membrane **1505**. In the preferred embodiment, mounting plate **3301** is utilized with mounting system **1501**; however, it will be appreciated that mounting plate **3301** could easily be utilized with alternative embodiments of mounting system **1501**.

Mounting plate **3301** comprises a raised portion **3303** being raised at a height relative to a base **3305**. Base **3305** includes a bottom surface area **3403**, which thermally bonded to second membrane **1501** according to one or more of the bonding methods discussed herein. In the preferred embodiment, mounting plate **3301** is composed of a metallic material sufficiently rigid to support an object to the mounting system in a relatively fixed position, yet sufficiently elastic to receive different embodiments of a fastener, as will be discussed in detail below (see FIGS. **37** and **38**).

Mounting plate **3301** is preferably formed through a stamping process, which provides easy and rapid manufacturing of raised portion **3303**. The stamping process is an effective means for forming raised portion **3303**; however, it should be appreciated that alternative embodiments of mounting plate **3301** could be composed of other materials, including but not limited to, plastics, ceramics, composites, elastomeric material, and/or other suitable materials and could be manufactured through alternative machining processes such as milling, extrusion, molding, and/or other suitable manufacturing processes.

Raised portion **3303** is utilized to secure a fastener **3403** to mounting system **1501**. In the preferred embodiment, raised portion **3303** is adapted to sandwich fastener **3403** between a lower surface area **3405** and upper surface area **1803** of second membrane **1505**. Raised portion **3303** forms a cavity **3407** for receiving fastener **3403**. Cavity **3407** is formed with a lower surface **3405** and a contoured joining material **3307**. Joining material **3307** extends from base **3305** to a top surface **3309** and includes an inner surface **3409** selectively contoured to abut against the top and side surfaces of fastener **3403**. Thus, the snug fit between the surfaces of fastener **3403** and inner surfaces of cavity **3405** prevent rotational, transverse, and longitudinal movement of fastener **3403**, which in turn enables an object attached thereto to remain in a relatively fixed position while mounted to mounting system **1501**.

It should be appreciated that alternative embodiments of raised portion **3303** could include cavities which are not formed with contoured inner surfaces adapted to create a snug fit with the fastener. In these alternative embodiments, the fastener disposed therein is capable of some movement, depending on the preferred application. For example, the

raised portion could be configured to enable rotational movement, while restricting transverse and longitudinal movement. An example of this type of embodiment is found in FIG. 38, as will be discussed below.

Raised portion **3303** is further provided with a port **3311** extending through the thickness formed between top surface area **3309** and lower surface area **3405**. Port **3311** provides passage for a fastening device, i.e., a threaded shaft (not shown), to extend therethrough and fasten to an attachment device **3411** of fastener **3403**. In the preferred embodiment, port **3311** is a hole, either partially or fully extending through thickness **T** of fastener **3403**, and is preferably threaded for engaging a threaded member of an object being supported thereto. However, it will be appreciated that alternative embodiments of fastener **3403** could include different fastening means, i.e., slots, clips, clamps, quick-release devices, in lieu of the preferred embodiment. Also, alternative embodiments could include a protrusion extending through port **3311** and adapted to couple to the object (see FIG. 36).

Mounting plate **3301** is optionally manufactured with a rim **3313** extending around the peripheral edge of base **3307** and oriented at an angle with respect to and in a direction away from base **3307**. Rim **3313** provides means for preventing water, debris, and/or other foreign objects from entering and/or blocking port **3311**. Also, rim **3313** could provide attachment means for coupling an attachment device, i.e., a clip or clamp, to mounting plate **3301**.

FIG. 35 shows an oblique view of fastener **3403**. Fastener **3403** comprises a base **3501** and one or more anti-rotational members **3503** extending therefrom. Members **3503** are utilized to prevent transverse, longitudinal, and rotational movement of fastener **3403** while fastener **3403** is disposed within cavity **3407**. Specifically, members **3503** and base **3501** include a side surface **3505** that abuts against inner surface **3409** of joining material **3307**, thereby creating a snug fit therebetween and preventing movement. In the preferred embodiment, fastener **3403** comprises four members **3503**; however, alternative embodiments could include more or less members depending on the preferred application. Fastener **3403** is further provided with a top surface **3507**, which comes in contact with surface **3405**, and a bottom surface **3509**, which comes in contact with upper surface **1803** of second membrane **1501**. During operation, movement of fastener **3403** is restricted when the side, top, and bottom surfaces of the fastener abut against the inner surfaces of cavity **3407** and surface **1803** of membrane **1501** as forces are exerted against fastener **3403**.

FIG. 36 shows an oblique view of an alternative embodiment of fastener **3403**. Fastener **3601** is substantially similar in form and function to fastener **3403**. For example, fastener **3601** is provided with one or more anti-rotational members **3603** extending from a base **3605** and adapted to prevent rotational, longitudinal, and transverse movement of fastener **3601** when sandwiched between surface **3405** and surface **1803**.

Fastener **3601** is further provided with a protrusion **3607** extending from base **3605**. Fastener **3601** is preferably manufactured as an integral member with protrusion **3607**, thus being rigidly formed with base **3605**. Protrusion **3607** is utilized to provide coupling means for attaching an object to fastener **3601**. Protrusion **3607** is further optionally provided with an attachment portion **3609** utilized to couple with the object. In the preferred embodiment, attachment portion **3609** preferably includes threads for engaging with a threaded member of the object. Of course it should be appreciated that

alternative embodiments of attachment portion **3609** could include different surface treatments and/or device in lieu of the preferred embodiment.

Referring now to FIGS. 37 and 38 in the drawings, a cross-sectional view of an alternative embodiment of fastener **3601** is shown. Fastener **3701** is substantially similar in form and function to fastener **3601**. For example, fastener **3701** comprises a base portion **3703** and a protrusion **3705** extending therefrom. It will be appreciated that the features of fastener **3701** and the foregoing fasteners are interchangeable, for example, fastener **3701** could include the features of fastener **3601**.

Fastener **3701** is further provided with a notch **3707** utilized to couple fastener **3701** to port **3311**. In the preferred embodiment, notch **3707** is adapted to tightly fit with port **3311**, which in turn prevents rotational, longitudinal, and transverse movement of fastener **3701**, thereby eliminating the need to sandwich fastener **3701** within cavity **3407** of raised portion **3303**. It should be appreciated that alternative embodiments of notch **3707** could be utilized to allow some movement, i.e., rotational movement, depending on the preferred application. Notch **3707** peripherally extends around protrusion **3705** and comprises a bottom surface **3709**, a top surface **3711**, and an inner side surface **3713**. A contoured surface **3715** is positioned above notch **3707** and is utilized to elastically deform the material around port **3311** such that the material widens while in contact with surface **3715**, then retracts to its original geometric shape in notch **3707**.

Referring now to FIG. 39 in the drawings, an alternative embodiment of mounting plate **3301** is shown. Mounting plate **3901** is substantially similar in function to mounting plate **3301**. In particular, mounting plate **3901** is adapted to secure an object, i.e., a riser to mounting system **1501**. It will be appreciated that mounting plate **3901** could include the features of the other mounting plates discussed herein, and likewise, the features of mounting plate **3901** could be incorporated in the foregoing mounting plates.

Mounting plate **3901** is provided with a protrusion **3903** extending from a base portion **3903**. Protrusion **3903** is utilized to couple an object to mounting plate **3901**. FIG. 40 shows a cross-sectional view of mounting plate **3901** taken at XL-XL of FIG. 39. As is shown, protrusion **3903** and base **3905** are preferably formed as an integral body, and preferably manufactured through a stamping process. Protrusion is provided with an attachment portion **3907**, which in the preferred embodiment, is a ridge recessed on the surface of protrusion **3903**. Although shown as an elongated rectangular member, protrusion **3903** can easily be manufactured with different shapes and sizes. For example, an alternative embodiment could include a cylindrical protrusion in lieu of a rectangular profile. Also, alternative embodiments could include different attachment devices in lieu of a ridge. For example, attachment portion **3907** could include threads for engaging a threaded structure.

FIG. 41 shows a flow chart **4101** illustrating the preferred method of the manufacturing the mounting systems disclosed herein. Box **4103** shows the first step, which includes providing an elastic membrane having an upper and lower surface. The next step includes placing and bonding a mounting plate to the upper surface with heat and pressure, as depicted in boxes **4105** and **4107**. Thereafter, the mounting plate is secured in place with a magnet positioned on the opposing lower surface, as depicted in box **4109**. Finally, the magnet is removed after sufficient time is allowed to cool the mounting plate, as depicted in boxes **4111** and **4113**.

FIG. 42 shows a flow chart **4201** illustrating the preferred method of the manufacturing and assembling the mounting

systems with plate 3301. Box 4203 includes the first step, which includes providing a membrane, mounting plate, and a fastener. The next step includes securing the fastener to the mounting plate, which includes the steps of first forming a cavity having the contouring of the fastener, as depicted in boxes 4205 and 4207. The next step includes placing and bonding a mounting plate to the upper surface with heat and pressure, as depicted in boxes 4209 and 4211. Thereafter, the mounting plate is secured in place with a magnet positioned on the opposing lower surface, as depicted in box 4213. Finally, the magnet is removed after sufficient time is allowed to cool the mounting plate, as depicted in boxes 4215 and 4217.

Referring to FIGS. 43 and 44 in the drawings, unassembled and assembled front views of an alternative embodiment of mounting system 1501 is shown. Mounting system 4301 is substantially similar in form and function to mounting system 1501. The features of the mounting systems described herein could easily be adapted to include the features of mounting system 4301, and likewise mounting system 4301 could be adapted to include the features of the foregoing mounting system described herein.

Mounting system 4301 is further provided with one or more fastening device 4303 utilized to secure membrane 1503 to structure 1601. FIG. 44 shows fastening devices 4303 securing membrane 1503 to structure 1601 as force F is exerted against mounting system 4301, which in turn causes elastic stretching of membrane 1505.

Referring now to FIGS. 45 and 46 in the drawings, an alternative embodiment of mounting system 1501 is shown. FIG. 45 shows an exploded oblique view of mounting system 4501, while FIG. 46 shows an assembled oblique view of mounting system 4501. Mounting system 4501 is substantially similar in form and function to the mounting systems described above, namely, mounting system 4501 comprises one or more membranes adapted to secure an object to a structure, i.e., a polymeric membrane, rooftop, and/or other rigid or non-rigid type of structure. It should be appreciated that the features of mounting system 4501 could be incorporated in any of the foregoing mounting plates, and likewise, mounting system 4501 could be adapted to include the mounting plate features disclosed herein.

Mounting system 4501 comprises a second membrane 4503, substantially similar in function to membrane 1505, and a first membrane 4505. First membrane is preferably a flashing membrane, which securely bonds to a structure 4507, i.e., a rooftop at end 4509 and at end 4511 according to one or more of the bonding methods discussed above. It should be noted that the entire bottom surface of first membrane 4505 is not bonded to structure 4507 in the preferred embodiment. For this reason, mounting system 4501 is further provided with a bracket 4513 adapted to securely fasten a portion of first membrane 4505 to structure 4507. One or more fastener means 4515 are utilized to secure bracket 4513, which in turn secures a portion of first membrane 4509, to structure 4507. Bracket 4513 forms a hollow area 4517, which enables a portion of first membrane to extend therethrough when a force is exerted against mounting plate 4591 bonded to second membrane 4503.

In the preferred embodiment, a single bracket 4513 is utilized to secure first membrane 4505 to structure 4507; however, it will be appreciated that alternative embodiments could include two or more brackets in lieu of the preferred embodiment. For example, an alternative embodiment could include a second bracket having a smaller diameter than bracket 4513 and adapted to fit within hollow area 4517. The two brackets provide additional means for securing the first

membrane to the structure. In the preferred embodiment, bracket 4513 is composed of a metallic material; however, alternative embodiments could include different materials, i.e., wood, composite, plastic, and/or other suitable materials, both rigid and flexible, in lieu of the preferred embodiment. Bracket 4513 is also preferably circular in shape; however, it will be appreciated that alternative embodiments could include different geometric shapes, sizes, and embodiments wherein the bracket does not form a unitary body.

Referring now to FIGS. 47 and 48 in the drawings, respective cross-sectional and front views of mounting system 4501 are shown as a force F is exerted against mounting plate 4517. Mounting system 4501 is further provided with a bonding material 4701 utilized to bond a portion of second membrane 4503 to first membrane 4505 within hollow area 4517.

FIG. 48 shows the effects of force F exerted against mounting system 4501 when bracket 4513 is not utilized. As is shown, a large gap 4801 is formed between first membrane 4505 and structure 4507. In this exemplary depiction, first membrane 4505 remains securely bonded to structure 4507 at ends 4509 and 4511, while the remaining area is separated.

Referring now to FIG. 49 in the drawings, a flow chart depicting the preferred method of assembling a mounting system is shown. In particular, box 4903 depicts the first step, which includes placing a lower surface of a first membrane on a structure and bonding it thereto via one or more of the bonding methods discussed herein. Thereafter, a mounting plate is placed on an upper surface of the first membrane and securely attached thereto via a fastener, i.e., a screw or bolt, wherein the fastener is adapted to extend through the thickness of the mounting plate, first membrane and into the structure, as depicted in boxes 4905 and 4907. The fastener is countersunk into the mounting plate and a second membrane is placed thereon, as depicted in boxes 4909 and 4913. The second membrane has a hole for receiving a protrusion extending from the mounting plate. A bonding agent is applied to the top surface of the mounting plate and disposed between the lower surface of the second membrane and the top surface of the mounting plate, as depicted in boxes 4911 and 4915. In the preferred embodiment, the bonding agent and the second membrane are thermally fused together, and sufficient bonding agent is applied such that second membrane forms a fluidly sealed barrier between the top surface of the mounting plate and the lower surface of the second membrane. Thus, forming a fluidly sealed bond between the second membrane and the mounting plate. In the preferred embodiment, the bonding agent is one or more of the different types of bonding agents and/or adhesive described herein and preferably thermally fused at a temperature ranging between 300-700 degrees Fahrenheit. Finally a portion of the lower surface of the second membrane is bonded to the upper surface of the first membrane.

Referring next to FIGS. 50 and 51 in the drawings, front views of an alternative embodiment of the mounting systems discussed herein are shown. In FIG. 50, a simplified unassembled front view of mounting system 5001 is shown, while FIG. 51 shows mounting system 5001 assembled and a force F1 being applied thereto. It will be appreciated that mounting system 5001 is substantially similar in form and function to one or more of the mounting systems discussed above, and is contemplated including the features discussed above, and vice-versa.

Mounting system 5001 securely fastens an object to the support structure. It is contemplated having mounting system 5001 being adapted to secure a riser to a roof structure, and more specifically, an array of photoelectric cells to a roof structure and/or a snow guard to a roof structure. However, it

should be understood that mounting system **5001** should not be narrowly limited to these two applications and it is contemplated utilizing mounting system **5001** for other applications, all falling within the spirit of the present application.

In this embodiment, mounting system **5001** fastens to the support structure with one or more fasteners, which in turn provides effective means for securing an object to the structure via the mounting plate. Mounting system **5001** further comprises a second membrane, which preferably thermally fuses to both the first membrane and the mounting plate. When assembled, the mounting plate is sandwiched between the first and second membranes. To prevent water, dirt and other foreign objects from reaching the support structure, an adhesive is applied between the mounting plate and the second membrane and bonded thereafter, preferably by a thermal process. Further description and illustration of the features are discussed in detail below and shown in the corresponding figures.

Mounting system **5001** comprises one or more of a first elastomeric membrane **5003**, a second elastomeric membrane **5005**, and a mounting plate **5007**. When assembled, mounting plate **5007** is sandwiched between first membrane **5003** and second membrane **5005**. First membrane **5003** has a bottom surface **5009**, which bonds to a top surface **5011** of a structure **5013**. Mounting plate **5007** has a bottom surface **5015** that preferably bonds to a top surface **5017** of first membrane **5003** and a top surface **5019** that bonds to a bottom surface **5021** of second membrane **5005**.

It will be appreciated that the method of assembly, including the bonding process and materials disclosed above, are optionally incorporated in the method for manufacturing and assembly of mounting system **5001**.

In the preferred embodiment, mounting plate **5007** securely attaches to structure **5013** via one or more fasteners **5023**. Fastener **5023** attaches to and extends through mounting plate **5007** via one or more countersunk holes **5201** (see FIG. **52**). In the preferred embodiment, countersunk hole **5201** receives a head **5029** of fastener **5023**, which in turn provides means for the top surface of head **5029** to sit flush with top surface **5019** of mounting plate **5007**. This feature provides a flat contact surface area between top surface **5019** of mounting plate **5007** and bottom surface **5021** of second membrane **5005**. In the exemplary embodiment, fastener **5023** has sufficient length to extend through the thickness of first membrane **5003** and partially through structure **5013**. In the exemplary embodiment, fasteners **5023** are threaded bolts; however, it will be appreciated that other types of fasteners, i.e., screws, nails, and other suitable fasteners could be utilized in lieu of the preferred embodiment.

Mounting plate **5007** further comprises a protrusion **5025** extending from top surface **5019** and configured to secure an object (not shown) to mounting plate **5007**. In the preferred embodiment, protrusion **5025** includes an attachment portion **5027** that is threaded for threadingly engaging to a threaded member of the object. However, attachment portion **5027** could easily be adapted with other surface treatments, i.e., a groove, and/or other devices configured to attach the object thereto.

In the preferred embodiment, second membrane **5005** includes a hole **5301** (see FIG. **53**) for receiving protrusion **5025**. During assembly, protrusion **5025** passes through hole **5301**, which in turn attaches to the object being secured thereto. It should be understood that penetrating second membrane **5005** creates potential passage for water, dirt, and other undesired foreign debris that could damage structure **5013**. To restrict these foreign debris from entering, mounting plate

**5007** is further provided with an adhesive, preferably a thermal adhesive, which thermally fuses top surface **5019** thereto.

Referring now to FIG. **52**, an oblique view of mounting plate **5007** is shown. In the contemplated embodiment, protrusion **5025** is manufactured as an integral piece with mounting plate **5007**. However, alternative embodiments could include protrusion **5025** and mounting plate **5007** being manufactured as separate pieces and thereafter assembled via one or more manufacturing processes known in the art. For example, protrusion **5025** could include a threaded portion for threading within a threaded channel formed through the centerline of mounting plate **5007** or alternatively, protrusion **5025** could be welded to mounting plate **5007**.

Protrusion **5025** is preferably oriented at about 90 degrees relative to top surface **5019**, resulting in no raised portions around protrusion **5025**, which in turn creates a flat surface peripherally extending around protrusion **5025**. In the exemplary embodiment, protrusion **5025** is a threaded rod; however, alternative embodiments could include different attachment means in lieu of the exemplary embodiment.

Mounting system **5001** is further provide with an adhesive **5203** applied to top surface **5019** of mounting plate **5007**. Adhesive **5203** bonds mounting plate **5007** to second membrane **5005**, which in turn prevents water and other foreign debris from passing through hole **5301**. In the preferred embodiment, adhesive **5203** can be one or more of a thermal liquid plastic, thermal adhesive, liquid PVC, and/or plastisol. Of course, it should be appreciated that alternative embodiments could utilize different suitable adhesives in lieu of the preferred embodiment. In the preferred embodiment, heat and pressure is applied to both second membrane **5005** and adhesive **5203** during assembly such that second membrane **5005** thermally fuses with adhesive **5203**.

Referring now to FIG. **53** in the drawings, an oblique assembled view of mounting system **5001** is shown. The preferred method of assembling mounting system **5001** includes the process of first adhering the adhesive to the mounting plate. Next, the first membrane is bonded to the structure. Thereafter, the mounting plate is positioned on the first membrane and secured thereupon with one or more fasteners. The fasteners extend through both the mounting plate and first membrane to secure to mounting plate to the structure. A second membrane is placed over the mounting plate and a hole extending therethrough receives the protrusion of the mounting plate. Heat and pressure is applied to the second membrane and the adhesive, which in turn causes the second membrane to thermally fuse to the adhesive. Heat and pressure is also applied to other portions of the second membrane for thermally fusing the second membrane to the first membrane.

FIG. **53** shows the two areas fused through the preferred method of assembly. As discussed, heat and pressure is applied to the adhesive, which in turn causes a first area **5303** of the second membrane **5005** to thermally fuse to adhesive **5203**. Heat and pressure can also be optionally applied to thermally fuse area **5305** to first membrane **5003**. Thermally fused area **5303** prevents fluid and debris seepage through hole **5301**, while area **5305** provides additional means to securely attach second membrane **5005** to first membrane **5003**.

When assembled, the mounting system provides effective means to secure an object to the structure, i.e., via the mounting plate and fasteners, and effective means for preventing water and/or other foreign debris from damaging the structure, i.e., via the adhesive. It should also be appreciated that adhesive effectively seals passage between top surface **5019** of mounting plate **5007** and bottom surface **5021** of second

25

membrane **5005** that other devices, i.e., nuts, caps, are not required to block passage of water and/or debris through hole **5301**.

The particular embodiments disclosed above are illustrative only, as the invention may be modified and practiced in different but equivalent manners apparent to those skilled in the art having the benefit of the teachings herein. It is therefore evident that the particular embodiments disclosed above may be altered or modified, and all such variations are considered within the scope and spirit of the invention. Accordingly, the protection sought herein is as set forth in the description. It is apparent that an invention with significant advantages has been described and illustrated. Although the present invention is shown in a limited number of forms, it is not limited to just these forms, but is amenable to various changes and modifications without departing from the spirit thereof.

What is claimed is:

**1.** A mounting system for attaching an object to a structure, the system comprising: a first membrane secured to the structure;

a second membrane, having:

a hole extending from a bottom surface to a top surface; and

a first section of the bottom surface for bonding with a top surface of the first membrane;

a mounting plate sandwiched between the top surface of the first membrane and a second section of the bottom surface of the second membrane, the mounting plate having:

a base portion; and

a raised portion, the raised portion being raised at a height relative to the base portion;

a protrusion that extends from a top surface of the raised portion of the mounting plate and configured to pass through the hole of the second membrane; and

an adhesive applied to a portion of the top surface of the mounting plate;

a fastener configured to extend through the mounting plate and the first membrane, and configured to secure to the mounting plate to the structure;

wherein the adhesive securely bonds the mounting plate to the second membrane and prevents foreign debris from passing between the top surface of the mounting plate and the bottom surface of the second membrane; and wherein the object securely couples to the protrusion of the mounting plate.

**2.** The mounting system of claim **1**, the mounting plate further comprising:

a hole extending from a bottom surface to the top surface of the mounting plate;

wherein the hole receives the fastener.

26

**3.** The mounting system of claim **2**, wherein the hole extending from a bottom surface to the top surface of the mounting plate is a countersunk hole for receiving the fastener such that a head of the fastener sits flush with the top surface of the mounting plate.

**4.** The mounting system of claim **1**, wherein the first membrane and the second membrane are both composed of an elastomeric material.

**5.** The mounting system of claim **1**, the protrusion having: an attachment portion configured to couple with the object.

**6.** The mounting system of claim **5**, wherein the attachment portion is a threaded section of the protrusion for threadingly engaging with the object.

**7.** The mounting system of claim **1**, wherein the structure is a roof and the object is a riser for a solar system.

**8.** The mounting system of claim **1**, wherein the adhesive is composed of a liquid thermal plastic for thermally fusing the mounting plate with the second membrane.

**9.** The mounting system of claim **1**, wherein the adhesive is composed of a polyvinyl chloride liquid material for thermally fusing the mounting plate to the second membrane.

**10.** The mounting system of claim **1**, wherein the adhesive is composed of a plastisol material for thermally fusing the mounting plate with the second membrane.

**11.** The mounting system of claim **1**, wherein the protrusion is oriented at 90 degrees relative to the top surface of the mounting plate.

**12.** The mounting system of claim **1**, wherein the bottom surface of the mounting plate is bonded to the first membrane.

**13.** A method to mount an object to a structure, comprising: covering a portion of the structure with a first membrane; bonding a second membrane to the first membrane; sandwiching a mounting plate between a top surface of the first membrane and a bottom surface of the second membrane;

bonding the mounting plate to the bottom surface of the second membrane, the mounting plate having:

a base portion; and

a raised portion, the raised portion being raised at a height relative to the base portion;

extending a protrusion rigidly attached to the raised portion of the mounting plate through a hole extending from the bottom surface to the top surface of the second membrane;

mounting the object to the protrusion;

fastening the mounting plate to the structure with a fastener that extend through the mounting plate and first membrane.

**14.** The method of claim **13**, wherein the step of bonding the mounting plate to the second membrane is achieved through thermal fusion.

\* \* \* \* \*