

US009194118B2

(12) **United States Patent**
Spyrou

(10) **Patent No.:** **US 9,194,118 B2**
(45) **Date of Patent:** ***Nov. 24, 2015**

(54) **BRICK BRACKET FOR INSTALLATION OF A LEDGER ON THE BRICK FACING OR VENEER OF A STRUCTURE AND ASSOCIATED METHODS FOR THE INSTALLATION OF THE BRICK BRACKET ON THE BRICK FACING**

(58) **Field of Classification Search**
CPC E04B 1/38; E04B 2/30; E04B 1/40; E04B 2/56; E04B 1/003; E04B 2001/405; E04B 2002/565; E04F 13/142
USPC 52/489.1, 705, 712, 713, 714, 745.21, 52/169.5, 378, 379; 248/216.1, 216.4, 248/218.3
See application file for complete search history.

(71) Applicant: **Alexis Spyrou**, Port Jefferson, NY (US)

(72) Inventor: **Alexis Spyrou**, Port Jefferson, NY (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.
This patent is subject to a terminal disclaimer.

(21) Appl. No.: **14/087,824**

(22) Filed: **Nov. 22, 2013**

(65) **Prior Publication Data**
US 2015/0135630 A1 May 21, 2015

Related U.S. Application Data

(63) Continuation of application No. 12/792,358, filed on Jun. 2, 2010, now Pat. No. 8,621,802.

(60) Provisional application No. 61/183,740, filed on Jun. 3, 2009.

(51) **Int. Cl.**
E04B 1/38 (2006.01)
E04B 2/30 (2006.01)
E04B 1/41 (2006.01)
E04B 1/00 (2006.01)
E04B 2/56 (2006.01)
E04F 13/14 (2006.01)

(52) **U.S. Cl.**
CPC . *E04B 1/40* (2013.01); *E04B 1/003* (2013.01); *E04B 2/56* (2013.01); *E04F 13/142* (2013.01); *E04B 2001/405* (2013.01); *E04B 2002/565* (2013.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,920,520	A *	8/1933	Nord	248/48.2
3,471,988	A *	10/1969	Allen	52/714
3,494,090	A *	2/1970	Allen	52/713
3,729,882	A *	5/1973	Allen	52/300
3,782,058	A *	1/1974	Allen	52/300
D246,573	S *	12/1977	White	D8/384
4,711,593	A *	12/1987	Wilhelmi	403/187
4,765,111	A *	8/1988	Osawa	52/509
4,837,991	A *	6/1989	Shaw	52/98
5,170,977	A *	12/1992	McMillan	248/300
5,501,050	A *	3/1996	Ruel	52/513
5,890,334	A *	4/1999	Hughes, Jr.	52/299
6,463,710	B1 *	10/2002	Barnhart	52/698

(Continued)


Primary Examiner — Rodney Mintz

(74) *Attorney, Agent, or Firm* — Sorell, Lenna & Schmidt, LLP

(57) **ABSTRACT**

A brick bracket which is installed in a recess provided by removal of brick of a brick veneer in order to be attached to studs of a framework of the building without contacting the bricks. The brick bracket has a front wall which extends outwardly and covers the brick facing and carries carriage bolts to which a ledger can be affixed such that the ledger is able to support an attached structure so that the brick bracket will not apply any force to the bricks of the brick facing.

19 Claims, 3 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

7,856,776	B2 *	12/2010	Van Der Lee	52/235	2006/0016138	A1 *	1/2006	Blount	52/263
8,443,569	B2 *	5/2013	Sias	52/715	2006/0101760	A1 *	5/2006	Cahoon	52/459
8,621,802	B2 *	1/2014	Spyrou	52/378	2010/0024331	A1 *	2/2010	Stiffler et al.	52/236.8
8,826,620	B2 *	9/2014	Krause	52/506.08	2010/0307094	A1 *	12/2010	Spyrou	52/489.1
8,833,025	B2 *	9/2014	Krause	52/506.08	2012/0167505	A1 *	7/2012	Krause	52/302.1
9,045,892	B2 *	6/2015	Smith et al.	1/1	2013/0074429	A1 *	3/2013	Lehtinen et al.	52/182
2002/0062616	A1 *	5/2002	Ocampo	52/656.9	2013/0152498	A1 *	6/2013	Krause	52/235
						2014/0215956	A1 *	8/2014	Smith et al.	52/705
						2015/0059259	A1 *	3/2015	Hatzinikolas	52/98

* cited by examiner




FIG. 1




FIG. 2




FIG. 3

1

**BRICK BRACKET FOR INSTALLATION OF A
LEDGER ON THE BRICK FACING OR
VENEER OF A STRUCTURE AND
ASSOCIATED METHODS FOR THE
INSTALLATION OF THE BRICK BRACKET
ON THE BRICK FACING**

CROSS RELATED APPLICATION

This application is a continuation of U.S. patent applica-
tion Ser. No. 12/792,358, filed on Jun. 2, 2010, which claims
the benefit of U.S. Provisional Application Ser. No. 61/183,
740 filed Jun. 3, 2009 and claims the priority thereof. Each of
the above-identified applications being incorporated herein
by reference in their respective entirety.

FIELD OF THE INVENTION

The invention relates to a bracket referred to as a brick
bracket for the installation of a ledger at the surface of a brick
facing or veneer of a structure such as a building.

The invention also relates to a method for the installation of
such a brick bracket.

BACKGROUND

A problem exists as regards how to connect a load bearing
member to a building having a brick facing or veneer. Most
Building Codes specify that brick veneer can only support its
own weight and cannot support additional loads, such as
those from an outside structure such as a deck or roof system.

This presents a problem when it is desired to build a deck
on a house with a brick veneer as it is necessary to support a
ledger at the side of the house, that serves to support the joists
of the deck and resists the weight of the deck. Since the ledger
cannot be attached to the brick of the veneer other measures
need to be taken.

Normally, the bricks must be removed in the area of the
ledger and supported from above which is a difficult and
expensive process.

In such case, the ledger is attached to the existing frame-
work of the house with very long bolts of sufficient strength
that can resist the bending forces induced in them as the bolts
project outwardly from the framework four to five inches.
Furthermore this can still lead to application of load on the
bricks of the brick veneer because the bolts deflect under the
load.

In the case of a deck it can be built free standing with
additional girders and posts on footings. This is costly and
also lacks attachment of the deck to the building.

All of these solutions create additional engineering mate-
rial and labor costs and are difficult to implement.

SUMMARY OF THE INVENTION

An object of the invention is to provide means by which the
deck can be connected to the framework of the building in a
simple manner without the need for incident costs and labor
as described above.

A further object of the invention is to provide such means
by which the ledger can be attached to the framework without
risk of applying forces to the brick veneer.

In accordance with the invention a bracket is provided
which enables the ledger to be connected to the framework of
the building without applying a load from the ledger to the
bricks of the brick veneer.

2

In further accordance with the invention a plurality of brick
brackets are installed on studs of the framework of the build-
ing, usually spaced at 16 inches. The brick brackets can be
installed on each stud or on spaced studs depending on the
size and weight of the deck. At each brick bracket location,
three bricks are removed, namely two bricks in each row and
one brick in the row thereabove. This is easily done and
involves minimum labor and without any additional shoring.
The brick bracket is formed with a rear wall serving as a back
plate and the bracket is inserted into the recess formed by the
removal of the bricks until the back wall fits flush against the
respective stud for the sheathing thereon, (if any) and is fixed
thereto by a plurality of lag bolts. A spanning plate extends
forwardly from the back plate wall over the top surface of the
next lower row of bricks by a spacing thereof so that no
contact is made by the spanning plate and the bricks of the
next lower row. A front wall or support plate depends from the
spanning plate outside the surface of the brick veneer. The
front wall supports a ledger, usually of wood. The ledger
extends along the length of the brackets and is secured thereto
by carriage bolts. The three bricks can be reinstalled or alter-
natively the space can be left open and subsequently covered
by the deck joists and sealed by flags.

A feature of the invention is that the brick is rigid and made
of metal in order to resist deflection.

In further accordance with the invention the bracket serves
as a means to apply the load from the deck to the framework
of the building without application of any force to the under-
lying bricks.

The method of the invention is very simple and requires no
complexity in the installation of the brackets to the framing
and it also assures that no bending forces will be applied to the
underlying bricks of the brick veneer due to the weight of the
deck and the use to which it is put.

Although the invention is described with respect to instal-
lation of a deck, the invention is also applicable to the attach-
ment of numerous other structure or equipment.

BRIEF DESCRIPTION OF THE FIGURES OF
THE DRAWING

FIG. 1 is a front view of a portion of a building having a
brick veneer to which is installed a brick bracket according to
the invention.

FIG. 2 is a sectional view taken along line 2-2 in FIG. 1.

FIG. 3 is a perspective view from the front and right side of
FIG. 2.

DETAILED DESCRIPTION OF THE
EMBODIMENTS OF THE INVENTION

FIG. 1 shows a portion of a wall 1 of a building 2 such as a
house. The wall 1 has a brick facing or veneer 3 composed of
rows of bricks 4 placed one above the other.

The invention is based on a construction by which a struc-
ture such as a deck (not shown) can be attached to a building.
Although the invention will be described in relation to the
attachment of a deck to the building it is only by way of
example and other structures can be attached within the con-
templation of the invention.

Since numerous Building Codes prohibit the application of
load to the brick facing or veneers of the building 1 to the
invention provides a unique way in which the deck can be
attached to the building without imposing any load upon the
brick facing. In this regard, the invention provides a plurality
of brackets 5 spaced longitudinally along the line of bricks
attached to the building and adapted to support the ledger 6

3

which extends along the length of the building over a distance corresponding to the width of the deck. The ledger **6** is intended to support the ends of joists of the deck whose opposite ends are supported at a distance from the building corresponding to the length of the deck. The manner of support of these opposite ends is not shown and is well known in the art. It should be noted that the deck can be placed at ground level or at an elevation, for example, where a door can be opened to lead to the deck. Since the brackets **5** are associated with the bricks of the brick facing they will be referred to at various times as brick brackets.

In order to attach the brackets **5** to the building **2**, three bricks are removed two in one line of bricks and one in the next higher row centrally located above the two bricks in order to provide a void or recess **7** in the brick facing **3**. The removal of the bricks **4** is easily carried out and requires no special skill or implements. The brick bracket **5** is then inserted within the recess **7**.

The brick bracket **5** comprises a back plate or wall **10** forming an attachment wall from which a spanning plate or wall **11** extends forwardly substantially perpendicular to the back plate. At the remote end of the spanning plate **11**, a front plate **12** or wall depends substantially perpendicular to the spanning plate **11** the lower end of the front plate, a ledge **13** extends substantially perpendicular thereto.

The brick bracket **5** is inserted into the recess **7** so that the back wall **10** of the brick bracket abuts against sheathing (not shown) of a stud **14** of the framing **15** of the building. Since it is intended that the brick brackets **5** are to be secured to the studs **14**, the brackets are spaced along the wall of the building at intervals corresponding to the spacing of the studs **14**. Normally this is 16" and the brackets **6** can be secured at 16" spacing for relatively large and heavy decks, whereas for smaller and lighter decks the spacing can be at 32" or any other multiple of 16". The back wall **10** of each bracket extends over a height so that its top edge is spaced below the lower surface of the next higher row of bricks while its lower edge extends below the next lower row of bricks in order to fit into the space between the next lower row of bricks and the stud **14**. The back wall is secured to the stud **14** by lag bolts **16** to be fixed thereto. The back wall is fixed to the stud **14** at such a height so that the spanning wall **11** extends a distance *d* above the top surface **17** of the fixed lower brick. The distance is generally equal to the thickness of the mortar placed between superimposed bricks. A layer of closed cell foam **19** can be introduced to fill this space and provide no transmission of force between the brick bracket and the top surface **17**. By spacing the spanning plate **11** above the top surface **17** of the next lower row of bricks, transmission of any force from the spanning plate **11** and thereby of the brick brackets to the bricks is avoided.

The front plate **12** extends downwardly from the spanning plate **11** over the next lower row of bricks and beyond and the ledge **13** extends forwardly from the front wall. The pair of carriage bolts **18** have been fixedly installed in the front plate and extend outwardly therefrom as shown in FIG. **2**. The ledger **6** is installed on the carriage bolts and affixed thereto by nuts (not shown). The ledge can serve as a support means for the ledger in the course of its installation on the carriage bolts.

The bricks that have been removed from the brick facing can now be reinstalled in the recess **7** and mortar can be filled in the space between the adjoining bricks except for the lower surface which adjoins the upper surface **17** of the next lower row of bricks. Alternatively, the space can be left open with-

4

out reinsertion of the removed bricks as the ledger will cover this space. In such case, sealing can be carried out between the ledger and the brick facing.

The ledger is of a size to accommodate the joists of the deck and in general will vary between 2×6 and 2×10. The ends of the joist rest on the top of the ledger and are secured thereto by conventional means, such as nails, bolts, and cleats.

The brick bracket is made substantially rigid to avoid bending and deflection and its thickness is a function of the size of the deck. In general the brick bracket will have a thickness between $\frac{3}{16}$ " and $\frac{3}{8}$ ". The brick brackets are made of metal and in particular aluminum as these are light weight and strong.

The brick bracket **5** is preferably made as an extrusion. Specifically, in a preferred embodiment, the back wall **10** and the spanning wall **11** are made as one extrusion of T shape, and the front wall **12** and ledge **13** are made as a second extrusion of L-shape. The facing ends of walls **11** and **12** are formed with an interlocking joint, such as a tongue and groove, and are engaged and welded together to form the bracket.

The back plate **10** is formed with ridges (not shown) of triangular cross-section that extend thereacross to form a "washbasin-like" effect to provide strength and facilitate installation on the studs.

In order to install the lag bolts **16** and small recesses (not shown) are provided in the respective plates to facilitate such installation.

The back plate **10** is formed with projections **21** and its front face of trapezoidal cross section that extend thereacross provide strength and facilitate installation on the studs. To this effect the projections are interrupted to form recesses **22** into which the lag bolts **16** are inserted. At the lower end of plate **10** a triangular brace **23** is formed to join the back plate **10** with the spanning plate **11**.

Although the invention has been described in relation to specific embodiments thereof it will become apparent to those skilled in the art that numerous modifications and variations thereof can be made without departing from the scope and spirit of the invention as defined in the attached claims.

What is claimed is:

1. A brick bracket comprising:

a first wall having a front face defining at least one cavity configured for disposal of a fastener, wherein the front face has at least one projection adjacent the at least one cavity;

a second wall disposed between a first brick and a second brick and having a first end connected to the first wall and a second end, the second wall including a first surface and a second surface oriented to face the second brick, the second surface spaced apart from the second brick to prevent a force applied to the brick bracket from being transmitted to the second brick; and

a third wall connected to the second wall and including a first surface extending transversely to engage a support member and a second surface extending along at least a portion of the second brick, the second surface of the third wall is oriented to face the second brick and spaced apart from the second brick.

2. The brick bracket as recited in claim **1**, wherein the first end of the second wall is attached to the first wall via interlocking components.

3. The brick bracket as recited in claim **1**, wherein the at least one projection has a trapezoidal cross-section.

4. The brick bracket as recited in claim **1**, wherein the front face of the first wall defines a plurality of projections, the projections being interrupted to form the at least one cavity.

5

5. The brick bracket as recited in claim 1, wherein the first surface of the second wall is oriented to face the first brick.

6. The brick bracket as recited in claim 1, wherein a plurality of brick brackets are arranged in a spaced relation along a row of bricks.

7. The brick bracket as recited in claim 1, wherein a space between the second wall and the second brick is filled with a closed cell foam.

8. The brick bracket as recited in claim 1, wherein a triangular brace is configured to join the first wall with the second wall to provide support to the brick bracket.

9. The brick bracket as recited in claim 1, wherein the brick bracket is formed as an extrusion.

10. The brick bracket as recited in claim 1, wherein the brick bracket is rigid.

11. The brick bracket as recited in claim 1, wherein the at least one cavity includes a recess.

12. The brick bracket as recited in claim 11, wherein the recess is configured for disposal of a lag bolt.

13. The brick bracket as recited in claim 1, wherein the first wall is configured for attachment to a stud within a framework.

14. The brick bracket as recited in claim 13, wherein the first wall is fixed to the stud at a height such that the second wall is spaced apart a distance from a fixed lower brick.

15. A brick bracket comprising:
 a back wall configured for attachment to a stud having a front face defining a plurality of projections that define at least one cavity therebetween configured for disposal of a lag bolt;
 a spanning wall extending perpendicular to the back wall and being disposed between a first brick and a second brick, the spanning wall having a first end attached to the back wall via interlocking components and a second end, the spanning wall including a first surface oriented to face the first brick and a second surface oriented to face the second brick, the second surface being spaced from the second brick to prevent a force applied to the brick bracket from being transmitted to the second brick;
 and

6

a front wall connected to the spanning wall and including a first surface extending transversely to engage a ledger and a second surface extending along at least a portion of the second brick, the second surface of the front wall is oriented to face the second brick and spaced apart from the second brick.

16. A brick bracket system comprising:
 at least one brick bracket including:

a first wall having a front face defining at least one cavity;

a second wall disposed between a first brick and a second brick and having a first end connected to the first wall and a second end, the second wall including a first surface and a second surface oriented to face the second brick, the second surface spaced apart from the second brick to prevent a force applied to the brick bracket from being transmitted to the second brick, and

a third wall connected to the second wall and including a first surface extending transversely to engage a ledger and a second surface extending along at least a portion of the second brick, the second surface of the third wall is oriented to face the second brick and spaced apart from the second brick;

at least one lag bolt configured for disposal with the at least one cavity and connection to a stud; and

a fastener configured to connect the ledger with the first surface of the third wall.

17. The brick bracket system as recited in claim 16, wherein the brick bracket is formed as an extrusion.

18. The brick bracket system as recited in claim 16, wherein the first wall is fixed to the stud at a height such that the second wall is spaced apart a distance from a fixed lower brick.

19. The brick bracket system as recited in claim 18, wherein the space between the second wall and the fixed lower brick is filled with a closed cell foam.

* * * * *