



US009204999B2

(12) **United States Patent**  
**Barta et al.**

(10) **Patent No.:** **US 9,204,999 B2**  
(45) **Date of Patent:** **Dec. 8, 2015**

(54) **SEE-THROUGH REDUCED-PRESSURE DRESSINGS AND SYSTEM**

(75) Inventors: **Eric Woodson Barta**, San Antonio, TX (US); **Justin Alexander Long**, San Antonio, TX (US); **Richard Marvin Kazala, Jr.**, San Antonio, TX (US); **Matthew Francis Cavanaugh, II**, San Antonio, TX (US); **Michael Girouard**, San Antonio, TX (US); **Kenneth Mitchel Knowles**, Bandera, TX (US)

(73) Assignee: **KCI Licensing, Inc.**, San Antonio, TX (US)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 359 days.

(21) Appl. No.: **13/455,383**

(22) Filed: **Apr. 25, 2012**

(65) **Prior Publication Data**

US 2012/0203189 A1 Aug. 9, 2012

**Related U.S. Application Data**

(62) Division of application No. 12/475,380, filed on May 29, 2009, now Pat. No. 8,188,331.

(60) Provisional application No. 61/057,807, filed on May 30, 2008, provisional application No. 61/057,798,

(Continued)

(51) **Int. Cl.**

**A61F 13/00** (2006.01)  
**A61F 13/02** (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC ..... **A61F 13/00038** (2013.01); **A61F 13/00029** (2013.01); **A61F 13/00034** (2013.01);

(Continued)

(58) **Field of Classification Search**

CPC ..... A61F 13/02  
USPC ..... 602/41-48, 52-56, 58-60; 604/317, 604/358, 367, 369, 378, 381, 382, 383; 424/447, 448, 443, 449

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

1,355,846 A 10/1920 Rannells  
2,547,758 A 4/1951 Keeling

(Continued)

**FOREIGN PATENT DOCUMENTS**

AU 550575 A1 8/1982  
AU 745271 4/1999

(Continued)

**OTHER PUBLICATIONS**

International Search Report and Written Opinion for International Patent Application No. PCT/US2009/045751 mailed Oct. 26, 2009.

(Continued)


*Primary Examiner* — Victoria J Hicks

*Assistant Examiner* — Tarla Patel

(57) **ABSTRACT**

A see-through dressing assembly is presented for use with a reduced-pressure system for treating a wound on a patient using reduced pressure that allows visual observation of the wound during treatment. The dressing assembly includes a bolster for providing a directed force when under reduced pressure, a sealing member for covering the bolster and providing a seal over the bolster and a patient's epidermis, and wherein the bolster and sealing member are formed from see-through materials sufficient to allow perception of color from a point external to the system. Other systems, dressings, and methods are presented.

**12 Claims, 9 Drawing Sheets**



**Related U.S. Application Data**

filed on May 30, 2008, provisional application No. 61/057,808, filed on May 30, 2008, provisional application No. 61/057,802, filed on May 30, 2008, provisional application No. 61/057,803, filed on May 30, 2008, provisional application No. 61/057,800, filed on May 30, 2008, provisional application No. 61/057,797, filed on May 30, 2008, provisional application No. 61/057,805, filed on May 30, 2008, provisional application No. 61/057,810, filed on May 30, 2008, provisional application No. 61/121,362, filed on Dec. 10, 2008, provisional application No. 61/144,067, filed on Jan. 12, 2009.

(51) **Int. Cl.**

*A61L 15/60* (2006.01)  
*A61M 1/00* (2006.01)  
*A61H 1/00* (2006.01)  
*A61F 15/00* (2006.01)

(52) **U.S. Cl.**

CPC ..... *A61F13/00068* (2013.01); *A61F 13/022* (2013.01); *A61F 13/0209* (2013.01); *A61F 13/0216* (2013.01); *A61F 13/0223* (2013.01); *A61F 13/0243* (2013.01); *A61F 13/0289* (2013.01); *A61F 15/008* (2013.01); *A61H 1/008* (2013.01); *A61L 15/60* (2013.01); *A61M 1/0023* (2013.01); *A61M 1/0088* (2013.01); *A61F 13/00* (2013.01); *A61F 2013/0028* (2013.01); *A61F 2013/0054* (2013.01); *A61F 2013/00131* (2013.01); *A61F 2013/00174* (2013.01); *A61F 2013/00536* (2013.01); *A61F 2013/00748* (2013.01); *Y10T 29/49* (2015.01); *Y10T 29/49826* (2015.01)

(56)

**References Cited**

U.S. PATENT DOCUMENTS

2,632,443 A 3/1953 Leshner  
 2,682,873 A 7/1954 Evans et al.  
 2,910,763 A 11/1959 Lauterbach  
 2,969,057 A 1/1961 Simmons  
 3,066,672 A 12/1962 Crosby, Jr. et al.  
 3,367,332 A 2/1968 Groves  
 3,520,300 A 7/1970 Flower, Jr.  
 3,568,675 A 3/1971 Harvey  
 3,648,692 A 3/1972 Wheeler  
 3,682,180 A 8/1972 McFarlane  
 3,826,254 A 7/1974 Mellor  
 4,080,970 A 3/1978 Miller  
 4,096,853 A 6/1978 Weigand  
 4,139,004 A 2/1979 Gonzalez, Jr.  
 4,165,748 A 8/1979 Johnson  
 4,184,510 A 1/1980 Murry et al.  
 4,233,969 A 11/1980 Lock et al.  
 4,245,630 A 1/1981 Lloyd et al.  
 4,256,109 A 3/1981 Nichols  
 4,261,363 A 4/1981 Russo  
 4,275,721 A 6/1981 Olson  
 4,284,079 A 8/1981 Adair  
 4,297,995 A 11/1981 Golub  
 4,333,468 A 6/1982 Geist  
 4,373,519 A 2/1983 Errede et al.  
 4,382,441 A 5/1983 Svedman  
 4,392,853 A 7/1983 Muto  
 4,392,858 A 7/1983 George et al.  
 4,419,097 A 12/1983 Rowland  
 4,465,485 A 8/1984 Kashmer et al.  
 4,475,909 A 10/1984 Eisenberg  
 4,480,638 A 11/1984 Schmid  
 4,525,166 A 6/1985 Leclerc

4,525,374 A 6/1985 Vaillancourt  
 4,540,412 A 9/1985 Van Overloop  
 4,543,100 A 9/1985 Brodsky  
 4,548,202 A 10/1985 Duncan  
 4,551,139 A 11/1985 Plaas et al.  
 4,569,348 A 2/1986 Hasslinger  
 4,605,399 A 8/1986 Weston et al.  
 4,608,041 A 8/1986 Nielson  
 4,640,688 A 2/1987 Hauser  
 4,655,754 A 4/1987 Richmond et al.  
 4,664,662 A 5/1987 Webster  
 4,710,165 A 12/1987 McNeil et al.  
 4,733,659 A 3/1988 Edenbaum et al.  
 4,743,232 A 5/1988 Kruger  
 4,758,220 A 7/1988 Sundblom et al.  
 4,787,888 A 11/1988 Fox  
 4,826,494 A 5/1989 Richmond et al.  
 4,838,883 A 6/1989 Matsuura  
 4,840,187 A 6/1989 Brazier  
 4,863,449 A 9/1989 Therriault et al.  
 4,872,450 A 10/1989 Austad  
 4,878,901 A 11/1989 Sachse  
 4,897,081 A 1/1990 Poirier et al.  
 4,906,233 A 3/1990 Moriuchi et al.  
 4,906,240 A 3/1990 Reed et al.  
 4,919,654 A 4/1990 Kalt et al.  
 4,941,882 A 7/1990 Ward et al.  
 4,953,565 A 9/1990 Tachibana et al.  
 4,969,880 A 11/1990 Zamierowski  
 4,985,019 A 1/1991 Michelson  
 5,018,515 A \* 5/1991 Gilman ..... 602/52  
 5,037,397 A 8/1991 Kalt et al.  
 5,086,170 A 2/1992 Luheshi et al.  
 5,092,858 A 3/1992 Benson et al.  
 5,100,396 A 3/1992 Zamierowski  
 5,134,994 A 8/1992 Say  
 5,149,331 A \* 9/1992 Ferdman et al. .... 604/290  
 5,167,613 A 12/1992 Karami et al.  
 5,176,663 A 1/1993 Svedman et al.  
 5,215,522 A 6/1993 Page et al.  
 5,232,453 A 8/1993 Plass et al.  
 5,261,893 A 11/1993 Zamierowski  
 5,278,100 A 1/1994 Doan et al.  
 5,279,550 A 1/1994 Habib et al.  
 5,298,015 A 3/1994 Komatsuzaki et al.  
 5,342,376 A 8/1994 Ruff  
 5,344,415 A 9/1994 DeBusk et al.  
 5,358,494 A 10/1994 Svedman  
 5,437,622 A 8/1995 Carion  
 5,437,651 A 8/1995 Todd et al.  
 5,527,293 A 6/1996 Zamierowski  
 5,549,584 A 8/1996 Gross  
 5,556,375 A 9/1996 Ewall  
 5,607,388 A 3/1997 Ewall  
 5,636,643 A \* 6/1997 Argenta et al. .... 128/897  
 5,645,081 A 7/1997 Argenta et al.  
 6,071,267 A 6/2000 Zamierowski  
 6,135,116 A 10/2000 Vogel et al.  
 6,241,747 B1 6/2001 Ruff  
 6,287,316 B1 9/2001 Agarwal et al.  
 6,345,623 B1 2/2002 Heaton et al.  
 6,488,643 B1 12/2002 Tumey et al.  
 6,493,568 B1 12/2002 Bell et al.  
 6,553,998 B2 4/2003 Heaton et al.  
 6,814,079 B2 11/2004 Heaton et al.  
 7,534,927 B2 5/2009 Lockwood et al.  
 2001/0043943 A1 \* 11/2001 Coffey ..... 424/447  
 2002/0077661 A1 6/2002 Saadat  
 2002/0115951 A1 8/2002 Norstrem et al.  
 2002/0120185 A1 8/2002 Johnson  
 2002/0143286 A1 10/2002 Tumey  
 2003/0212359 A1 11/2003 Butler

(56)

## References Cited

## U.S. PATENT DOCUMENTS

2006/0079852 A1 4/2006 Bubb et al.  
 2007/0185463 A1\* 8/2007 Mulligan ..... 604/305  
 2008/0009812 A1 1/2008 Riesinger

## FOREIGN PATENT DOCUMENTS

AU	755496	2/2002
CA	2005436	6/1990
DE	26 40 413 A1	3/1978
DE	43 06 478 A1	9/1994
DE	295 04 378 U1	10/1995
EP	0100148 A1	2/1984
EP	0117632 A2	9/1984
EP	0161865 A2	11/1985
EP	0358302 A2	3/1990
EP	0424165 A1	4/1991
EP	1018967 B1	8/2004
GB	692578	6/1953
GB	2 195 255 A	4/1988
GB	2 197 789 A	6/1988
GB	2 220 357 A	1/1990
GB	2 235 877 A	3/1991
GB	2 333 965 A	8/1999
GB	2 329 127 B	8/2000
JP	4129536	4/1992
JP	2000-189427 A	7/2000
JP	2000-189427	11/2000
JP	2003-116907	4/2003
JP	2003116907	4/2003
SG	71559	4/2002
WO	WO 80/02182	10/1980
WO	WO 87/04626	8/1987
WO	WO 90/10424	9/1990
WO	WO 93/09727	5/1993
WO	94/20041	9/1994
WO	WO 94/20041	9/1994
WO	WO 96/05873	2/1996
WO	WO 97/18007	5/1997
WO	WO 99/13793	3/1999
WO	01/02478 A1	1/2001
WO	WO 01/02478 A1	1/2001
WO	01/89431	11/2001
WO	02/20067 A2	3/2002
WO	WO 02/20067 A2	3/2002
WO	WO 03/057071 A2	7/2003
WO	WO 03/057307 A1	7/2003
WO	2004060413 A1	7/2004
WO	WO 2004/060413 A1	7/2004
WO	2007030599 A2	3/2007
WO	2007041642 A2	4/2007

## OTHER PUBLICATIONS

Communication pursuant to Rule 114(2) EPC for corresponding EP Application 09770664.2, mailed Aug. 22, 2013.

A Prospective, Blinded, Randomized, Controlled Clinical Trial of Topical Negative Pressure Use in Skin Grafting, Elias Moisisidis, Tim Heath, Catherine Boorer, Kevin Ho, Anand K. Deva, Sydney, Australia, From the Department of Plastic and Maxillofacial Surgery, Liverpool Hospital. Received for publication Mar. 25, 2003; revised Oct. 1, 2003.

The Vacuum Assisted Closure Device, A Method of Securing Skin Grafts and Improving Grafts Survival; Lynette A. Scherer, MD; Stephen Shiver, MD; Michael Chang, MD; J. Wayne Meredith, MD; John T. Owings, MD; From the Departments of Surgery, University of California-Davis Medical Center, Sacramento (Drs. Scherer and Owings), and Wake Forest University Baptist Medical Center, Winston-Salem, NC (Drs. Shiver, Chang, and Meredith); Arch Surg/vol. 137, Aug. 2002; www.archsurg.com.

N.A. Bagautdinov, "Variant of External Vacuum Aspiration in the Treatment of Purulent Diseases of the Soft Tissues," *Current Problems in Modern Clinical Surgery: Interdepartmental Collection*, edited by V. Ye Volkov et al. (Chuvashia State University, Cheboksary, U.S.S.R. 1986); pp. 94-96. (certified translation).

Louis C. Argenta, MD and Michael J. Morykwas, PhD; "Vacuum-Assisted Closure: A New Method for Wound Control and Treatment: Clinical Experience"; *Annals of Plastic Surgery*, vol. 38, No. 6, Jun. 1997; pp. 563-576.

Susan Mendez-Eastmen, RN; "When Wounds Won't Heal" RN Jan. 1998, vol. 61(1); Medical Economics Company, Inc., Montvale, NJ, USA; pp. 20-24.

James H. Blackburn, II, MD, et al; "Negative-Pressure Dressings as a Bolster for Skin Grafts"; *Annals of Plastic Surgery*, vol. 40, No. 5, May 1998, pp. 453-457.

John Masters; "Reliable, Inexpensive and Simple Suction Dressings"; Letter to the Editor, *British Journal of Plastic Surgery*, 1998, vol. 51 (3), p. 267; Elsevier Science/The British Association of Plastic Surgeons, UK.

S.E. Greer, et al "The Use of Subatmospheric Pressure Dressing Therapy to Close Lymphocutaneous Fistulas of the Groin" *British Journal of Plastic Surgery* (2000), 53, pp. 484-487.

George V. Letsou, MD., et al; "Stimulation of Adenylate Cyclase Activity in Cultured Endothelial Cells Subjected to Cyclic Stretch"; *Journal of Cardiovascular Surgery*, 31, 1990, pp. 634-639.

Orringer, Jay, et al; "Management of Wounds in Patients with Complex Enterocutaneous Fistulas"; *Surgery, Gynecology & Obstetrics*, Jul. 1987, vol. 165, pp. 79-80.

International Search Report for PCT International Application PCT/GB95/01983; Nov. 23, 1995.

PCT International Search Report PCT International Application PCT/GB98/02713; Jan. 8, 1999.

PCT Written Opinion; PCT International Application PCT/GB98/02713; Jun. 8, 1999.

PCT International Examination and Search Report, PCT International Application PCT/GB96/02802; Jan. 15, 1998 & Apr. 29, 1997.

PCT Written Opinion, PCT International Application PCT/GB96/02802; Sep. 3, 1997.

Dattilo, Philip P., Jr., et al; "Medical Textiles: Application of an Absorbable Barbed Bidirectional Surgical Suture"; *Journal of Textile and Apparel, Technology and Management*, vol. 2, Issue 2, Spring 2002, pp. 1-5.

Kostyuchenok, B.M., et al; "Vacuum Treatment in the Surgical Management of Purulent Wounds"; *Vestnik Khirurgi*, Sep. 1986, pp. 18-21 and 6 page English translation thereof.

Davydov, Yu. A., et al; "Vacuum Therapy in the Treatment of Purulent Lactation Mastitis"; *Vestnik Khirurgi*, May 14, 1986, pp. 66-70, and 9 page English translation thereof.

Yusupov, Yu. N., et al; "Active Wound Drainage"; *Vestnik Khirurgi*, vol. 138, Issue 4, 1987, and 7 page English translation thereof.

Davydov, Yu. A., et al; "Bacteriological and Cytological Assessment of Vacuum Therapy for Purulent Wounds"; *Vestnik Khirurgi*, Oct. 1988, pp. 48-52, and 8 page English translation thereof.

Davydov, Yu. A., et al; "Concepts for the Clinical-Biological Management of the Wound Process in the Treatment of Purulent Wounds by Means of Vacuum Therapy"; *Vestnik Khirurgi*, Jul. 7, 1980, pp. 132-136, and 8 page English translation thereof.

Chariker, Mark E., M.D., et al; "Effective Management of incisional and cutaneous fistulae with closed suction wound drainage"; *Contemporary Surgery*, vol. 34, Jun. 1989, pp. 59-63.

Egnell Minor, *Instruction Book*, First Edition, 300 7502, Feb. 1975, pp. 24.

Egnell Minor: Addition to the Users Manual Concerning Overflow Protection—Concerns all Egnell Pumps, Feb. 3, 1983, pp. 2.

Svedman, P.: "Irrigation Treatment of Leg Ulcers", *The Lancet*, Sep. 3, 1983, pp. 532-534.

Chinn, Steven D. et al.: "Closed Wound Suction Drainage", *The Journal of Foot Surgery*, vol. 24, No. 1, 1985, pp. 76-81.

Arnljots, Björn et al.: "Irrigation Treatment in Split-Thickness Skin Grafting of Intractable Leg Ulcers", *Scand J. Plast Reconstr. Sur.*, No. 19, 1985, pp. 211-213.

Svedman, P.: "A Dressing Allowing Continuous Treatment of a Biosurface", *IRCS Medical Science: Biomedical Technology, Clinical Medicine, Surgery and Transplantation*, vol. 7, 1979, p. 221.

Svedman, P. et al.: "A Dressing System Providing Fluid Supply and Suction Drainage Used for Continuous or Intermittent Irrigation", *Annals of Plastic Surgery*, vol. 17, No. 2, Aug. 1986, pp. 125-133.

(56)

**References Cited**

## OTHER PUBLICATIONS

K.F. Jeter, T.E. Tintle, and M. Chariker, "Managing Draining Wounds and Fistulae: New and Established Methods," *Chronic Wound Care*, edited by D. Krasner (Health Management Publications, Inc., King of Prussia, PA 1990), pp. 240-246.

G. Živadinović, V. Đukić, Ž. Maksimović, Đ. Radak, and P. Peška, "Vacuum Therapy in the Treatment of Peripheral Blood Vessels," *Timok Medical Journal* 11 (1986), pp. 161-164 (certified translation).  
F.E. Johnson, "An Improved Technique for Skin Graft Placement Using a Suction Drain," *Surgery, Gynecology, and Obstetrics* 159 (1984), pp. 584-585.

A.A. Safronov, Dissertation Abstract, *Vacuum Therapy of Trophic Ulcers of the Lower Leg with Simultaneous Autoplasty of the Skin* (Central Scientific Research Institute of Traumatology and Orthopedics, Moscow, U.S.S.R. 1967) (certified translation).

M. Schein, R. Saadia, J.R. Jamieson and G.A.G. Decker, "The 'Sandwich Technique' in the Management of the Open Abdomen," *British Journal of Surgery* 73 (1986), pp. 369-370.

D.E. Tribble, An Improved Sump Drain-Irrigation Device of Simple Construction, *Archives of Surgery* 105 (1972) pp. 511-513.

M.J. Morykwas, L.C. Argenta, E.I. Shelton-Brown, and W. McGuirt, "Vacuum-Assisted Closure: A New Method for Wound Control and

Treatment: Animal Studies and Basic Foundation," *Annals of Plastic Surgery* 38 (1997), pp. 553-562 (Morykwas I).

C.E. Tennants, "The Use of Hyperemia in the Postoperative Treatment of Lesions of the Extremities and Thorax," *Journal of the American Medical Association* 64 (1915), pp. 1548-1549.

Selections from W. Meyer and V. Schmieden, *Bier's Hyperemic Treatment in Surgery, Medicine, and the Specialties: A Manual of Its Practical Application*, (W.B. Saunders Co., Philadelphia, PA 1909), pp. 17-25, 44-64, 90-96, 167-170, and 210-211.

V.A. Solovev et al., Guidelines, The Method of Treatment of Immature External Fistulas in the Upper Gastrointestinal Tract, editor-in-chief Prov. V.I. Parahonyak (S.M. Kirov Gorky State Medical Institute, Gorky, U.S.S.R. 1987) ("Solovev Guidelines").

V.A. Kuznetsov & N.A. Bagautdinov, "Vacuum and Vacuum-Sorption Treatment of Open Septic Wounds," in II All-Union Conference on Wounds and Wound Infections: Presentation Abstracts, edited by B.M. Kostyuchenok et al. (Moscow, U.S.S.R. Oct. 28-29, 1986) pp. 91-92 ("Bagautdinov II").

V.A. Solovev, Dissertation Abstract, Treatment and Prevention of Suture Failures after Gastric Resection (S.M. Kirov Gorky State Medical Institute, Gorky, U.S.S.R. 1988) ("Solovev Abstract").

V.A.C.® Therapy Clinical Guidelines: A Reference Source for Clinicians (Jul. 2007).

\* cited by examiner





FIG. 1






FIG. 3A




FIG. 3B




FIG. 3C




FIG. 4A









FIG. 4B






FIG. 6




FIG. 7




FIG. 8

## SEE-THROUGH REDUCED-PRESSURE DRESSINGS AND SYSTEM

### RELATED APPLICATIONS

The present application is a divisional of U.S. patent application Ser. No. 12/475,380, filed May 29, 2009 now U.S. Pat. No. 8,188,331 entitled "See-Through, Reduced-Pressure Dressings and Systems", which claims the benefit, under 35 USC §119(e), of the filing of U.S. Provisional Patent Application Ser. No. 61/057,807, entitled "Reduced-Pressure Surgical Wound Treatment System," filed May 30, 2008; U.S. Provisional Patent Application Ser. No. 61/057,798, entitled "Dressing Assembly For Subcutaneous Wound Treatment Using Reduce Pressure," filed May 30, 2008; U.S. Provisional Patent Application Ser. No. 61/057,808, entitled "See-Through, Reduced-Pressure Dressing," filed May 30, 2008; U.S. Provisional Patent Application Ser. No. 61/057,802, entitled "Reduced-Pressure Dressing Assembly For use in Applying a Closing Force," filed May 30, 2008; U.S. Provisional Patent Application Ser. No. 61/057,803, entitled "Reduced-Pressure, Linear-Wound Treatment System," filed May 30, 2008; U.S. Provisional Patent Application Ser. No. 61/057,800, entitled "Reduced-Pressure, Compression System and Apparatus for use on a Curved Body Part," filed May 30, 2008; U.S. Provisional Patent Application Ser. No. 61/057,797, entitled "Reduced-Pressure, Compression System and Apparatus for use on Breast Tissue," filed May 30, 2008; U.S. Provisional Patent Application Ser. No. 61/057,805, entitled "Super-Absorbent, Reduced-Pressure Wound Dressing and System," filed May 30, 2008; U.S. Provisional Patent Application Ser. No. 61/057,810, entitled "Reduced-Pressure, Compression System and Apparatus for Use on a Joint," filed May 30, 2008; U.S. Provisional Patent Application Ser. No. 61/121,362, entitled "Reduced-Pressure Wound Treatment System Employing an Anisotropic Drape," filed Dec. 10, 2008; and U.S. Provisional Patent Application Ser. No. 61/144,067, entitled "Reduced-Pressure, Compression System and Apparatus for use on a Joint," filed Jan. 12, 2009. All of these provisional applications are incorporated herein by reference for all purposes.

### BACKGROUND

The present invention relates generally to medical treatment systems, and more particularly, to reduced-pressure wound treatment systems suitable for use with linear wounds, such as surgical wounds.

Physicians perform millions of surgical procedures each year around the world. Many of the procedures are performed as open surgery and an increasing number are performed using minimally invasive surgery, such as arthroscopic, laparoscopic, and endoscopic procedures. As one example, the American Society for Aesthetic Plastic Surgery reports that there were more than 450,000 liposuction procedures in the United States in 2007.

Surgical procedures involve acute wounds, e.g., an incision or linear wound, in the skin and related tissue. In addition to surgical wounds, linear wounds are also caused by trauma. In many instances, the linear wound is closed using a mechanical apparatus, such as staples, suture, or adhesives, and then the wound is merely covered with a dry, sterile bandage. Often the bandage must be removed to view the wound to monitor the wound's progress and to check for infection or

other issues. Unless otherwise indicated, as used herein, "or" does not require mutual exclusivity.

### BRIEF SUMMARY

5

Shortcomings with certain aspects of wound care are addressed by the illustrative embodiments herein. The present invention may be used on a linear wound, an area wound, or other wound. "Linear wound" refers generally to a laceration or incision whether in a line or not. According to an illustrative embodiment, a see-through dressing assembly for use with a reduced-pressure system for treating a linear wound on a patient includes a closing dressing bolster for providing a closing force when under reduced pressure and a sealing member for covering the closing dressing bolster and providing a seal over the closing dressing bolster. The closing dressing bolster and sealing member are formed from see-through materials sufficient to allow perception of color from a point external to the see-through dressing assembly. The closing dressing bolster may include a top wall and a bottom wall. The top wall and bottom wall are coupled in a spaced relationship. The bottom wall includes a center portion, a first lateral portion, and a second lateral portion. A first closing member is formed on the first lateral portion, and a second closing member is formed on the second lateral portion. When placed under reduced pressure, the first closing member and the second closing member move towards each other.

According to another illustrative embodiment, a system for treating a wound on a patient with reduced pressure allows visual observation of the wound during treatment is presented. The system includes a see-through dressing bolster for placing on the patient's epidermis over the wound; a see-through sealing subsystem for providing a fluid seal over the closing bolster; and a reduced-pressure subsystem for delivering reduced pressure to the sealing subsystem. The sealing subsystem and reduced-pressure subsystem are operable to deliver reduced pressure to the see-through dressing bolster whereupon the system develops a directed force realized at the wound and delivers reduced pressure to the wound. The see-through members are operable to allow light to pass such that the color, shades of color, or a wound edge of the wound may be perceived from a place external to the system.

According to another illustrative embodiment, a method of manufacturing a see-through dressing assembly includes the steps of forming a bolster for providing a directed force to a wound treatment area when under reduced pressure and providing a see-through sealing member to cover the bolster and which allows a fluid seal over the bolster and a patient's epidermis. The step of forming a bolster includes forming a bolster from a see-through material.

According to another illustrative embodiment, a dressing assembly for use with a reduced-pressure treatment system on a patient includes a bolster for placing over a wound on the patient and for providing a directed force when under reduced pressure; a sealing member for covering the bolster and providing a fluid seal over the bolster and a portion of the patient's epidermis; and a visual inspection device for visually detecting the color of the wound on the patient. Still other illustrative embodiments are presented further below.

Other features and advantages of the illustrative embodiments will become apparent with reference to the drawings and detailed description that follow.

### BRIEF DESCRIPTION OF THE DRAWINGS

65

A more complete understanding of the method and apparatus of the present invention may be obtained by reference to

the following Detailed Description when taken in conjunction with the accompanying Drawings wherein:

FIG. 1 is a schematic, perspective view, with a portion in cross section, of an illustrative embodiment of a system for treating a linear wound on a patient;

FIG. 2 is a schematic, perspective view of an illustrative embodiment of a closing dressing bolster for use in treating a linear wound on a patient;

FIG. 3A is a schematic cross-section of an illustrative embodiment of a system for treating a linear wound on a patient;

FIG. 3B is a schematic cross-section of a detail from FIG. 3A;

FIG. 3C is a schematic cross-section of a detail from FIG. 3A;

FIG. 4A is a schematic, perspective view of an illustrative embodiment of a closing dressing bolster for use in treating a linear wound on a patient;

FIG. 4B is a partially exploded, perspective view of the closing dressing bolster of FIG. 4A showing one illustrative embodiment of a tubing connector;

FIG. 4C is a cross-section of the closing dressing bolster of FIG. 4A;

FIG. 4D is a detail of the closing dressing bolster of FIG. 4C;

FIG. 5 is a schematic, perspective view of an illustrative embodiment of a closing dressing bolster for use in treating a linear wound on a patient;

FIG. 6 is a schematic cross-section of a portion of an illustrative embodiment of a system for treating a linear wound on a patient;

FIG. 7 is a schematic cross-section of an illustrative embodiment of a portion of a system for treating a linear wound on a patient; and

FIG. 8 is a schematic, perspective view, with a portion in cross section, of an illustrative embodiment of a system for treating damaged subcutaneous tissue that allows the wound to be seen from a point external to the system.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

In the following detailed description of the preferred embodiments, reference is made to the accompanying drawings that form a part hereof, and in which is shown by way of illustration specific preferred embodiments in which the invention may be practiced. These embodiments are described in sufficient detail to enable those skilled in the art to practice the invention, and it is understood that other embodiments may be utilized and that logical structural, mechanical, electrical, and chemical changes may be made without departing from the spirit or scope of the invention. To avoid detail not necessary to enable those skilled in the art to practice the invention, the description may omit certain information known to those skilled in the art. The following detailed description is, therefore, not to be taken in a limiting sense, and the scope of the present invention is defined only by the appended claims.

Referring to FIGS. 1-3, an illustrative embodiment of a reduced-pressure system 10 for treating a linear wound 12, such as a laceration or, more typically, an incision 14 is presented. The reduced-pressure system 10 may hold or support peri-incisional tissue, enhance tensile strength of the incision 14; compress subcutaneous tissue 20; remove interstitial fluid, which may help reduce or eliminate edema; and isolate the linear wound 12 from infectious sources. The

reduced-pressure system 10 may be particularly well suited for use with at-risk patients, e.g., obese patients, diabetic patients, smokers, etc.

While the linear wound 12 may extend to different depths, in this example the incision 14 extends through epidermis 16, dermis 18, and into the subcutaneous tissue 20. A damaged subcutaneous tissue 22 includes, in this illustration, a subcutaneous void 24 or dead space. While not shown in this embodiment, the linear wound 12 may have any number of closing devices employed on the linear wound, e.g., mechanical closing devices (suture, staples, clamps, etc.), adhesives, bonding, etc. The wound may be or include a graft.

The reduced-pressure system 10 may include a dressing assembly 40, which may be placed over the linear wound 12 and used with reduced pressure to supply a directed force, which may include a compressive force 42 or a closing force 44 (or an inward force with respect to an outer edge of the dressing assembly). The dressing assembly 40 may include a closing dressing bolster 46 that under reduced pressure develops the directed force, e.g., the compressive forces 42 or the closing forces 44. The closing dressing bolster 46 may be formed with a bolster body 50. The closing dressing bolster 46 is preferably made from a material that allows flexing and yet is rigid enough to deliver a closing force.

The bolster body 50 may include a first closing member 52 and a second closing member 54. Additional closing members, such as members 56, 58, 60, and 62 may be included. A sealing subsystem 70 and a reduced-pressure subsystem 90 cooperate with the closing dressing bolster 46 to develop the directed force, e.g., the closing force 44 or the compressive force 42.

The closing dressing bolster 46 may be made from a material that helps to distribute reduced pressure to the linear wound 12, provides the compressive force 42, and, through the closing members, e.g., closing member 56, provides a closing force 44—preferably a force that is substantially within the plane of the epidermis 16. In addition, the material for the closing dressing bolster 46 is preferably translucent or see through to an extent that light may pass through allowing one to view the linear wound 12 through the bolster material from a point external to the reduced-pressure system 10. The material from which the closing dressing bolster 46 may be formed is further described below.

As previously noted, the reduced-pressure system 10 may allow wound color, shades of color, wound edge, or other features to be perceived visually from a point external the reduced-pressure system 10. As such, the color, shades of color, nature of the wound edge, or other features may be determined by a healthcare provider without requiring removal of the dressing assembly 40 and thereby may avoid the increased risk of complications and pain of a dressing change. As such, the expense of another a dressing assembly 40 or part of thereof may also be avoided. The reduced-pressure system 10 may also provide the compressive force 42 to the linear wound 12 and that force may help the linear wound 12, subcutaneous tissue 22, or subcutaneous void 24 to heal and may stabilize the linear wound 12 against shear. The reduced-pressure system 10 may also help remove exudates from the linear wound 12 and may help close the void 24.

The sealing subsystem 70 may include the sealing member 72. The sealing member 72 has a first side 74 and a second, inward-facing side 76. A portion of the sealing member 72 may extend beyond the closing dressing bolster 46, e.g., beyond edge 48, to form a flap, or a drape extension 77, which has a first side 78 and a second, inward-facing side 79. The sealing member 72 may be any material that provides a fluid seal that allows reduced pressure to be held. The sealing

member may, for example, be an impermeable or semi-permeable, elastomeric material. "Elastomeric" means having the properties of an elastomer. It generally refers to a polymeric material that has rubber-like properties. More specifically, most elastomers have elongation rates greater than 100% and a significant amount of resilience. The resilience of a material refers to the material's ability to recover from an elastic deformation. Examples of elastomers may include, but are not limited to, natural rubbers, polyisoprene, styrene butadiene rubber, chloroprene rubber, polybutadiene, nitrile rubber, butyl rubber, ethylene propylene rubber, ethylene propylene diene monomer, chlorosulfonated polyethylene, polysulfide rubber, polyurethane, EVA film, co-polyester, and silicones. Specific examples of sealing member materials include a silicone drape, 3M Tegaderm® drape, acrylic drape (such as one available from Avery Dennison), or an incise drape.

A sealing apparatus **80**, or attachment device, may be used to help provide a fluid seal between the drape extension **77** and the patient's epidermis **16**. In the present embodiment, the sealing apparatus **80** may be an adhesive **82** that is applied to the second, inward-facing side **79** of the flap extension **77** to provide such a seal against the epidermis **16**. The sealing apparatus **80** may be used to hold the sealing member **72** against the patient's epidermis **16** or another layer, such as a gasket or additional sealing member. The sealing apparatus **80** may take numerous forms. For example, the sealing apparatus **80** may be a medically acceptable, pressure-sensitive adhesive that extends about a periphery of the sealing member **72**.

The reduced-pressure subsystem **90** includes a reduced-pressure source **92**, or therapy unit. The reduced-pressure source **92** provides reduced pressure. The reduced-pressure source **92** may be any device for supplying reduced pressure, such as a vacuum pump, wall suction, or other source. While the amount and nature of reduced pressure applied to a tissue will typically vary according to the application, reduced pressure will typically be between  $-5$  mm Hg and  $-500$  mm Hg and more typically between  $-100$  mm Hg and  $-300$  mm Hg. In one embodiment, the reduced pressure is held around  $-200$  mm Hg. The reduced-pressure source **92**, for convenience and mobility purposes, may be a battery-operated unit that is capable of providing a continuous and intermittent reduced pressure. The reduced-pressure source **92**, or therapy unit, may include a canister **94**, or reservoir, and may be provided with windows **96** to allow the patient or healthcare provider to view the fill status of the canister **94**. The reduced-pressure subsystem **90** further includes a reduced-pressure delivery conduit **98**, or medical tubing, which if fluidly coupled to a reduced-pressure interface **100**, such as a port **102**. The reduced-pressure delivery conduit **98** and the reduced-pressure interface **100** allow reduced pressure to be delivered into the sealing subsystem **70**.

As used herein, "reduced pressure" generally refers to a pressure less than the ambient pressure at a linear wound **12**, tissue site, or treatment site that is being subjected to treatment. In most cases, this reduced pressure will be less than the atmospheric pressure at which the patient is located. Alternatively, reduced pressure may be less than a hydrostatic pressure at the tissue site. Unless otherwise indicated, values of pressure stated herein are gauge pressures. Reduced pressure delivered may be constant or varied (patterned or random) and may be delivered continuously or intermittently. Although the terms "vacuum" and "negative pressure" may be used to describe the pressure applied to the tissue site, the actual pressure applied to the tissue site may be more than the pressure normally associated with a complete vacuum. Con-

sistent with the use herein, an increase in reduced pressure or vacuum pressure typically refers to a relative reduction in absolute pressure.

The closing dressing bolster **46** may be made from a polymer and is preferably a soft polymer. In one illustrative embodiment, the closing dressing bolster **46** is a material having a durometer of 50 Shore A, but other materials and characteristics are possible. The closing dressing bolster **46** and the bolster body **50** may be made of a see-through material, as is a sealing member **72**, in order to allow the color, shades of color, wound edges, or other features of the linear wound **12** to be viewed from a point external to the reduced-pressure system **10** (see FIG. 6). A color change, or change in the shade of a color, of the linear wound **12** can signify the onset of infection or other issues, and such visual cues provide useful information to the healthcare provider. The bolster body **50** may be made from a flexible closing bolster material, e.g., a soft polymer, a medical grade silicone, or other suitable material. The closing dressing bolster **46** may be extruded, pour molded, injection molded, blow molded, or formed by other manufacturing techniques. "Flexible" means able to move enough to generate the inward closing force.

Referring now primarily to FIG. 2, the closing dressing bolster **46** is shown with a plurality of apertures **64** formed on a second, inward-facing side or surface **49** of a second wall **55**, or bottom wall, of the bolster body **50**. The apertures **64** are formed under a center portion **66**, and in particular, near center line **68** of the bolster body **50**. A detail showing one aperture **64** is shown in FIG. 3C. A first wall **53**, or top wall, and the second wall **55** are coupled in a spaced relationship to form a hollow region or central compartment **57**. Referring again primarily to FIG. 2, the apertures **64** facilitate the transmission of reduced pressure by the bolster body **50** to the linear wound **12**. Additional apertures in various patterns may be provided in the bolster body **50** to facilitate communication of reduced pressure to the patient's epidermis **16**, and, in particular, to the linear wound **12**. One or more apertures, such as aperture **65**, may be formed on a first side **47** of the first wall **53** of the bolster body **50**. Closing members **52**, **54**, **56**, **58**, **60**, and **62** are shown on the second, inward-facing side **49**. Closing members **52**, **56**, and **58** are on a first lateral side of the center portion **66** and closing members **54**, **60**, and **62** are on a second lateral side of the center portion **66**.

As shown clearly in FIGS. 3A and 3B, an oblique surface **69** has an angle formed with respect to an imaginary plane extending vertically (vertical for the orientation shown in FIG. 2). The oblique surface **69**, which is opposite a surface **63**, is shown making an angle **61** with respect to a reference vertical plane **59** formed at the apex of the oblique surface **69**.

In operation, when treatment is desired, the closing dressing bolster **46** is placed over the linear wound **12** with the center portion **66** over the linear wound **12** proximate a center wound area **45**. If the closing dressing bolster **46** is not pre-manufactured with the sealing member **72** applied on the first side **47**, then the sealing member **72** is applied over the first side **47** of the closing dressing bolster **46** and beyond the closing dressing bolster **46** to form the flap extension or drape extension **77**. The drape extension **77** is either taped down or an adhesive **82** is applied to provide a fluid seal between the sealing member **72** and the patient's epidermis **16**. "Fluid seal," or "seal," means a seal adequate to hold reduced pressure at the desired site given the particular reduced-pressure subsystem involved.

The reduced-pressure subsystem **90** is fluidly coupled to the sealing subsystem **70** through the reduced-pressure interface **100**. The reduced-pressure source **92** is activated and develops and delivers reduced pressure through the reduced-



pressure delivery conduit **98** to the reduced-pressure interface **100**. When activated, the reduced-pressure source **92** delivers reduced pressure to the sealing subsystem **70** and reduced pressure causes the closing dressing bolster **46** to develop the compressive force **42**. The geometry of the closing dressing bolster **46** may cause a bending moment to develop about the center portion **66** and thereby cause the closing members **52**, **54**, **56**, **58**, **60**, and **62** to develop a resultant force downward and inward (for the orientation shown). This action produces the directed force, e.g., the compressive force **42** or the closing force **44**. These forces may be experienced at or near the linear wound **12**.

Referring primarily to FIG. 2, the development of the closing force or compressive force is described in more detail. Each of the oblique surfaces **69** between adjacent closing members, **58** and **56**, **56** and **52**, **52** and **54**, **54** and **60**, and **60** and **62**, form part of a triangle-shaped ridge, each having an apex: first apex **67**, second apex **71**, central apex **75**, third apex **83**, and fourth apex **85**. As the reduced pressure enters the aperture **65**, the central compartment **57** is evacuated until some or all of the apexes **67**, **71**, **75**, **83**, and **85** encounter the first wall **53**. Reduced pressure is also delivered from the central compartment **57** through apertures **64** and may provide a force urging the apexes higher, or trying to make the angle associated with each apex smaller. As a result of one or more of these actions, the closing members **52**, **54**, **56**, **58**, **60**, and **62** are urged toward the center line **68** and, through friction against the patient's epidermis from the closing members **52**, **54**, **56**, **58**, **60**, and **62**, the closing force is developed on the patient's epidermis. The compressive force may be developed as the first wall **53** and second wall **55** are pulled by reduced pressure toward the patient or in the direction going from the first wall **53** to the second wall **55**.

Referring now primarily to FIGS. 4A, 4B, 4C, and 4D, another illustrative embodiment of a closing dressing bolster **146** is presented. The closing dressing bolster **146** has a bolster body **150** formed with a first closing member **152** and a second closing member **154**. A third closing member **156** and a fourth closing member **158** are also shown. The closing members **152** and **156** are formed on a first side or first portion **153** which is one side of a center plane **168**, or center portion, and may extend the longitudinal length of the closing dressing bolster **146**. The closing members **154** and **158** are formed on a second portion or side **155**, which is on the other side of the center plane **168**.

A central trough area **157** may help the bolster body **150** to flex in that region as a bending moment is developed under reduced pressure. The bending moment helps to press the closing members **152**, **154**, **156**, and **158** into the patient's epidermis and may provide the directed force, e.g., the compressive force and closing force directed towards the central wound area (e.g., area **45** in FIG. 1). The shape of the bolster body **150** in this illustrative embodiment has been chosen for strength and ease in extruding from a material, e.g., silicone, and so that the bolster body **150** collapses or moves in a desired way to develop the directed force, e.g., the compressive or closing forces. The closing dressing bolster **146** may be made of a see-through or at least partially transparent material so that the closing dressing bolster **146** may help the color, shades of color, wound edge, or other features of the linear wound underneath the closing dressing bolster **146** be viewed from a point exterior to a system utilizing the closing dressing bolster **146**.

As shown in FIGS. 4A and 4B, a tubing connector **199** may be used to provide reduced pressure to the closing dressing bolster. The tubing connector **199** is sized and configured to mate with central trough area **157** on the closing dressing

bolster **146**. The tubing connector **199** is fluidly coupled to a reduced-pressure delivery conduit **198** whereby reduced pressure is delivered to the closing dressing bolster **146**. Apertures **151** allow reduced pressure to communicate inside the closing dressing bolster **146**. As shown clearly in FIG. 4C, an aperture **164** may be formed in a portion of the closing dressing bolster **146** to help communicate reduced pressure to the linear wound below.

Referring now primarily to FIGS. 4C-4D, the development of the closing force or a compressive force will be described in more detail. In this illustrative embodiment, the bolster body **150** has been extruded with a central compartment **123** and a plurality of compartments. Six of the plurality of compartments **111**, **113**, **115**, **117**, **119**, and **121** are formed on the first portion **153**. The central compartment **123** is formed substantially adjacent to the central trough **157**. Six of the plurality of compartments **125**, **127**, **129**, **131**, **133**, and **135** are formed on the second portion **155**. In this embodiment, only the central compartment **123** receives reduced pressure and does so through apertures **151**.

The plurality of compartments, e.g., compartments **111**, **113**, **115**, **117**, **119**, **121**, **125**, **127**, **129**, **131**, **133**, and **135** are formed using a first wall **139** (or top wall), a second wall **141** (or bottom wall), and a plurality of web members **143**. The plurality of compartments provides strength to keep the first wall **139** from collapsing against the second wall **141**, except that a lower portion **145** of the central trough **157** is designed to collapse under reduced pressure against a shelf portion **161** of the central compartment **123**. It should be noted that first closing member **152** and second closing member **154** are spaced apart and sized and configured to provide a treatment trough **163**. The treatment trough **163** may have a dome-cutout **165** and oblique walls **167**. The first closing member **152** is formed on a first lateral portion with respect to the center plane **168**, and the second closing member **154** is formed on a second lateral portion with respect to the center plane **168**.

As reduced pressure is delivered to apertures **151**, the reduced pressure enters the central compartment **123** and is delivered through aperture **164** into the treatment trough **163**. The reduced pressure causes the lower portion **145** of the central trough **157** to collapse and touch the shelf portion **161** of the central compartment **123**. In addition, reduced pressure in the treatment trough **163** pulls the oblique walls **169** towards each other. One or more of these actions causes the bolster body **150** to flex, or bend, about the center plane **168** and thereby urges the closing members towards the center plane **168**. The plurality of compartments preferably do not collapse and continue to provide strength. Moreover, as the reduced pressure pulls the closing dressing bolster **146** inward, i.e., in the direction going from the first wall **139** to the second wall **141**, and a compressive force is developed.

Referring now primarily to FIG. 5, another embodiment of a closing dressing bolster **246** is presented. The closing dressing bolster **246** includes a bolster body **250** formed with a first closing member **252** on a first side **253**, or first lateral side, and a second closing member **254** on a second side **255**, or second lateral side. The first and second closing members **252** and **254** have oblique walls that angle up (for orientation shown) toward the wicking material holder **236**. With respect to a center portion **268**, an overlay piece **265**, or overlay, may cover and hold the closing members **252** and **254**. A gap between closing members **252** and **254** forms a wicking-material holder **236** that holds a wicking material **238**. The shape of the wicking material **238** and the substance of the

wicking material **238** may be operable to help keep an underlying linear wound (e.g., linear wound **12** in FIG. 1) dry and clean.

The materials that may be used for the wicking material **238** include hydrophobic materials, hydrophilic materials, and all the materials listed elsewhere that may be used for a shaped dressing bolster **532** described below (see FIG. 8). The overlay piece **265** and closing members **252** and **254** may be made of a see-through material that allows the closing dressing bolster **246** to be used with a system that allows a healthcare provider to view the color, shades of color, wound edges, or other features of the linear wound beneath the closing dressing bolster **246** from a point external to the closing dressing bolster **246** (see FIG. 6 for an example) and external to the system.

In operation, the closing dressing bolster **246** may develop a bending moment under reduced pressure causing the lower portion of the first closing member **252** and the lower portion of the second closing member **254** to press downward (for the orientation shown) and inward on the patient's epidermis causing both a compressive force or a closing force towards the linear wound. Reduced pressure delivered to the wicking-material holder **236** may move the first closing member **252** and the second closing member **254** closer together and thereby provide the closing force. The closing dressing bolster **246** is sized and configured so that the wicking material **238** may be in contact with the linear wound and thereby helps to remove any fluids that might have emanated from the linear wound. Any such fluids would be delivered to a reduced-pressure interface and then be delivered by a reduced-pressure conduit to a canister under the influence of a reduced-pressure source.

The illustrative closing dressing bolsters **46**, **146**, and **246** presented above may provide for the visual determination of the color, shades of color, wound edge, or other features of the wound from a location external to the closing dressing bolster. This feature is also possible with other types of dressings as will now be discussed. Referring now to FIG. 6, a portion of a reduced-pressure treatment system **310** is shown. The reduced-pressure treatment system **310** includes a see-through dressing assembly **340**, which has a bolster body **350**. The bolster body **350** may be made of any number of materials, such as a bolster mesh or bolster foam, provided that the spacing of pores on the foam (non-opaque foam) or between structural elements of the material allow for sufficient light to pass through the material such that the color, shades of color, wound edge, or other features of a linear wound **312** can be seen from a point external to the reduced-pressure treatment system **310**, e.g., can be seen in a line of sight location shown by reference numeral **384**. For example, the bolster body **350** may be formed from silicone or porous foam, e.g., a Granu-Foam® material available from Kinetic Concepts, Inc. of San Antonio, Tex. The pore size and density may be varied to help provide the see-through characteristic.

In an alternative illustrative embodiment, a window **386**, such as a window made of see-through silicone, may be placed over a portion of the bolster material such that when reduced pressure is provided to the bolster body **350** and the window **386** is compressed down further on the bolster material, the linear wound **312** becomes visible through the window **386** from a point exterior to the bolster body **350** and the system **310**. For example, a patient or healthcare provider may see the linear wound **312** on a line of sight **388**.

In another alternative, illustrative embodiment, clear beads may be used as or included within bolster body **350**. The beads may be arranged within the bolster body so that under negative pressure, the beads come together over the wound

allowing the patient or healthcare provider to see through to the wound from a point exterior or external to the bolster body **350** and the system **310**. The bolster body **350** may be a mesh material that the beads can displace as they come together under reduced pressure.

In another embodiment, a window can be made such that when reduced pressure is removed from the bolster body **350**, a biased portion moves aside allowing one to view the linear wound **312**. For example, two portions of the bolster body **350** may overlap as reduced pressure compresses the two portions, but when reduced pressure is removed, the portions separate and allow a clear view of the linear wound. As such, it will be appreciated that numerous visual inspection devices may be used to allow the color and other characteristics of the wound to be visually detected. The visual inspection device may be a see-through bolster and a see-through sealing member, a window **386**, a bolster material that allows adequate light to pass, a plurality of clear beads, or a moveable portion of a bolster that allows visual inspection when not under reduced pressure.

The bolster body **350** is shown covered by a sealing member **372** that extends beyond the bolster body **350**, e.g., beyond edge **348**, to form a drape extension **377**. The drape extension **377** may be sealed to form a fluid seal between the sealing member **372** and a patient's epidermis **314** using a sealing apparatus **380**, such as a drape tape **383** or other sealing device.

Referring now primarily to FIG. 7, a portion of an illustrative system **410** for treating a linear wound **412** is presented. The system **410** includes a dressing assembly **440**. The dressing assembly **440** includes a dressing bolster **446**, which has a dressing body **450**. The dressing body **450** may be formed with two portions: the first side, or first lateral portion **453**, and a second side, or second lateral portion **455**. The first portion **453** and second portion **455** may be integrally connected or may be two separate pieces. The first portion **453** is formed with closing members **452** and **456**. The second portion **455** is formed with closing members **454** and **460**. Under reduced pressure, the closing members **452**, **454**, **456**, and **460** develop both a compressive force and a closing force towards the linear wound **412**. The dressing body **450** is shown covered by a sealing member **472** that is sealed with a sealing apparatus **480** to provide a seal against a patient's epidermis **416**.

A first wall **437** on the first portion **453** and a second wall **439** on the second portion **455** together may form a wicking-material holder **436** for holding a wicking material **438**. The wicking material **438** may be held against the linear wound **412** to help to remove any fluids, e.g., exudates, when the dressing assembly **440** is placed under reduced pressure.

Referring now primarily to FIG. 8, an illustrative see-through wound treatment system **510** is presented that allows a healthcare provider to view a treatment site, e.g., linear wound **512**, area wound, a portion of intact epidermis **514**, etc., and may provide a compressive force. The see-through wound treatment system **510** may provide for the treatment of subcutaneous damaged tissue and may allow the treatment site to be viewed from a place external to the see-through wound treatment system **510**.

The see-through wound treatment system **510** is shown in a peri-incisional region around the linear wound **512**, which is through the epidermis **514**, dermis **516**, and reaching into a hypodermis, or subcutaneous tissue **518**. The subcutaneous tissue **518** may include numerous tissue types, such as fatty tissue or muscle. A damaged subcutaneous tissue site **520** is shown extending out from the linear wound **512** and includes, in this instance, a subcutaneous defect, dead space, or void

**522.** The damaged subcutaneous tissue site **520** may be caused by surgical procedures, such as liposuction. The damaged subcutaneous tissue site **520** may include voids, such as the void **522**, open spaces, and various defects that can be troublesome for a number of reasons, such as fluid accumulation that may result in edema.

The linear wound **512** may be closed using any closing device or technique, such as staples, sutures, or adhesive, but is shown in this illustrative embodiment with a staple **513**. The see-through wound treatment system **510** may be used for treating an area and, in particular, may be used for treating a subcutaneous tissue site **520** and the tissue around subcutaneous tissue site **520**, but the see-through wound treatment system **510** may also be used to treat the more limited area of a linear wound **512**.

The see-through wound treatment system **510** includes a dressing assembly **530**, which includes the shaped dressing bolster **532**, a sealing subsystem **560**, and a reduced-pressure subsystem **580**. In operation, the see-through wound treatment system **510** may develop the directed force, which may include a net compressive force, represented by reference numerals **524**, that is realized in the subcutaneous tissue site **520**. As described further below, the shaped dressing bolster **532** may be shaped and configured to allow the compressive force **524** to be distributed fairly evenly over the patient's epidermis **514**. Otherwise, if there are areas of substantially increased force as compared to other areas on the epidermis **514**, skin irritation may result.

The directed force may also include the closing force, or inward force, i.e., a force towards an interior portion of the dressing assembly **530**. The closing force is represented by reference numerals **526**. The closing force **526** remains substantially within the plane of the epidermis **514**. In other words, the closing force **526** operates mainly within the epidermis **514**. In addition, the see-through wound treatment system **510** is operable to deliver reduced pressure to the linear wound **512** and, depending on the phase of healing and the nature of the linear wound **512**, through the linear wound **512** such that reduced pressure is realized at the level of any subcutaneous voids **522** to help approximate—bring together—the tissues in that region as well as to help remove any air or any other fluids.

The dressing assembly **530** includes the shaped dressing bolster **532** that has a first side **534** and a second, inward-facing side **536**. The shaped dressing bolster **532** may be sized and shaped to substantially match the estimated area of the damaged subcutaneous tissue site **520** although a larger or smaller size may be used in different applications. The shaped dressing bolster **532** has an edge **538**. The shaped dressing bolster **532** may be made of a number of different medical bolster materials, i.e., materials suitable for use in medical applications and that may be made sterile. In one illustrative embodiment, the shaped dressing bolster **532** is made from a medical bolster material that is a manifold material. In one illustrative embodiment, the shaped dressing bolster **532** is made from bolster material that is a porous and permeable foam-like material and, more particularly, a reticulated, open-cell polyurethane or polyether foam that allows good permeability of wound fluids while under reduced pressure. One such foam material that has been used is the VAC® Granu-Foam® material available from Kinetic Concepts, Inc. (KCI) of San Antonio, Tex. Any material or combination of materials may be used for the bolster material provided that the bolster material is operable to distribute, or manifold, reduced pressure.

The term “manifold” as used herein generally refers to a substance or structure that is provided to assist in applying

reduced pressure to, delivering fluids to, or removing fluids from a tissue site. The bolster material may also be a combination or layering of materials; for example, a first bolster layer of hydrophilic foam may be disposed adjacent to a second bolster layer of hydrophobic foam to form the bolster material. The term “fluid” as used herein generally refers to gas or liquid, but may also include any other flowable material, including but not limited to gels, colloids, and foams.

The reticulated pores of the Granufoam® material, which are typically in the range of about 400 to 600 microns, are helpful in carrying out the manifold function, but other materials may be used. The density of the medical bolster material, e.g., Granufoam® material, is typically in the range of about 1.3 lb/ft<sup>3</sup>-1.6 lb/ft<sup>3</sup> (20.8 kg/m<sup>3</sup>-25.6 kg/m<sup>3</sup>). A material with a higher density (smaller pore size) than Granufoam® material may be desirable in some situations. For example, the Granufoam® material or similar material with a density greater than 1.6 lb/ft<sup>3</sup> (25.6 kg/m<sup>3</sup>) may be used. As another example, the Granufoam® material or similar material with a density greater than 2.0 lb/ft<sup>3</sup> (32 kg/m<sup>3</sup>) or 5.0 lb/ft<sup>3</sup> (80.1 kg/m<sup>3</sup>) or even more may be used. The more dense the material is, the higher compressive force that may be generated for a given reduced pressure. If a foam with a density less than the tissue at the tissue site is used as the medical bolster material, a lifting force may be developed.

The bolster material may be a reticulated foam that is later felted to thickness of about 1/3 the foam's original thickness. Among the many possible materials, the following may be used: GranuFoam® material or a Foamex® technical foam (www.foamex.com). In some instances it may be desirable to add ionic silver to the bolster material in a microbonding process or to add other substances to the bolster material, such as antimicrobial agents. The bolster material may be isotropic or anisotropic depending on the exact orientation of the directed force that is desired during reduced pressure. The bolster material may be made anisotropic by adding filaments, felting a portion, adding adhesive selectively, etc. The bolster material could be a bio-absorbable material.

The sealing subsystem **560** includes a sealing member **562**, or drape, which is analogous to the sealing member **72**. The sealing member **562** may be coupled to the shaped dressing bolster **532**. For example, the sealing member **562** and shaped dressing bolster **532** may be coupled using adhesives, such as an acrylic adhesive, silicone adhesive, hydrogel, hydrocolloid, etc. As another example, the sealing member **562** and the shaped dressing bolster **532** may be bonded by heat bonding, ultrasonic bonding, and radio frequency bonding, etc. The coupling may occur in patterns or completely. Structure may be added to the bond to make the sealing member **562** behave anisotropically in a desired direction, i.e., to make an anisotropic drape material. An anisotropic drape material helps the dressing assembly **530** to primarily move in a given direction, i.e., only about a certain axis or axes.

In the illustrative embodiment of FIG. 8, the sealing member **562** may be sized to extend beyond the shaped dressing bolster **532**, e.g., beyond the edge **538** on an extremity **533**, to form a drape extension **564**, or extension. The drape extension **564** has a first surface **566** and a second, inward-facing surface **568**. The sealing member **562** may be sealed against the epidermis **514** of the patient using a sealing apparatus **569**, which helps to provide a seal and allows reduced pressure to be maintained by the reduced-pressure subsystem **580** at the treatment site. The sealing apparatus **569** may take numerous forms, such as an adhesive **570**; a sealing tape, or drape tape or strip; double-side drape tape; paste; hydrocolloid; hydrogel; or other sealing device. If a tape is used, the tape may be formed of the same material as the sealing member **562** with

a pre-applied, pressure-sensitive adhesive. The pressure sensitive adhesive **570** may be applied on the second, inward-facing surface **568** of the drape extension **564**. The pressure-sensitive adhesive **570** provides a seal between the sealing member **562** and the epidermis **514** of the patient. Before the sealing member **562** is secured to the patient, the pressure-sensitive adhesive **570** may have removable strips or backing covering the pressure-sensitive adhesive **570**.

The reduced-pressure subsystem **580** includes a reduced-pressure source **582**, or therapy unit, which can take many different forms. The reduced-pressure source **582** provides reduced pressure as a part of the see-through wound treatment system **510**. The reduced-pressure source **582** may be any device for supplying reduced pressure, such as a vacuum pump, wall suction, or other source. While the amount and nature of reduced pressure applied to a tissue will typically vary according to the application, reduced pressure will typically be between  $-5$  mm Hg and  $-500$  mm Hg and more typically between  $-100$  mm Hg and  $-300$  mm Hg. In order to maximize patient mobility and ease, the reduced-pressure source **582** may be a battery-powered, single-use reduced-pressure generator, which facilitates application in the operating room and provides mobility and convenience for the patient during the rehabilitation phase.

In the illustrative embodiment of FIG. **8**, the reduced-pressure source **582** is shown having a battery compartment **584** and a canister region **586** with windows **588** providing a visual indication of the level of fluid within the canister region **586**. An interposed membrane filter, such as hydrophobic or oleophobic filter, may be interspersed between a reduced-pressure delivery conduit, or tubing, **590** and the reduced-pressure source **582**.

Reduced pressure developed by reduced-pressure source **582** is delivered through the reduced-pressure delivery conduit **590** to a reduced-pressure interface **592**, which may be an elbow port **594**. In one illustrative embodiment, the elbow port **594** is a TRAC® technology port available from KCI of San Antonio, Tex. The reduced-pressure interface **592** allows reduced pressure to be delivered to the sealing subsystem **560** and realized within an interior portion of the sealing subsystem **560**. In this illustrative embodiment, the elbow port **594** extends through the sealing member **562** and into the shaped dressing bolster **532**.

In operation, the see-through wound treatment system **510** is applied to the linear wound **512**. The see-through wound treatment system **510** may be applied to the linear wound **512** in the operating room after a surgical procedure on the patient. The second, inward-facing side **536** of the shaped dressing bolster **532** is placed against the patient's epidermis **514** with the shaped dressing bolster **532** over the damaged subcutaneous tissue site **520** and with a portion of the shaped dressing bolster **532** over the linear wound **512**. The dressing assembly **530** may be sized for the typical application involved in the procedure performed by a healthcare provider. The dressing assembly **530** may be sized, shaped, and configured to work with different anatomical applications, such as the abdomen, chest, arms, thighs, etc.

If the sealing member **562** has not already been coupled, the sealing member **562** is placed over the first side **534** of the shaped dressing bolster **532** with a portion extending beyond the shaped dressing bolster **532** to form the drape extensions **564**. The drape extensions **564** may then be taped down or an adhesive **570** used to form a seal between the sealing member **562** and the patient's epidermis **514**. The seal need only be adequate to allow the see-through wound treatment system **510** to hold reduced pressure on the desired treatment area. The reduced-pressure interface **592** and the reduced-pressure

source **582** are fluidly coupled using the reduced-pressure delivery conduit **590**. The reduced-pressure source **582** may then be activated and reduced pressure delivered to the shaped dressing bolster **532**.

As the pressure is reduced in the shaped dressing bolster **532**, the shaped dressing bolster **532** compresses and contracts laterally and forms a semi-rigid substrate, and a number of beneficial forces and actions may take place. Reduced pressure is transmitted further still through the shaped dressing bolster **532** so that reduced pressure delivered to the linear wound **512**. At least at the early stages of the healing process, reduced pressure may also be realized through the linear wound **512** and into the subcutaneous tissue site **520**. As such, reduced pressure may help close defects, such as subcutaneous void **522**, and generally provides stability to the area. Reduced pressure delivered to the shaped dressing bolster **532** also develops the compressive force **524** that again may provide stability and therapy. The compressive force **524** is more than just at the top of the epidermis **514**. The compressive force **524** extends down deeper and may be experienced at the level of the subcutaneous tissue site **520**. The compressive force may help close defects and provide stability.

It may be desirable to apply the see-through wound treatment system **510** in the operating room and allow the see-through wound treatment system **510** to remain on the patient until adequate healing has taken place. In this regard, it may be desirable to form the sealing member **562**, shaped dressing bolster **532**, and any other layers from see-through materials that allow the healthcare provider to gain visual cues about the healing of the linear wound **512** and damaged subcutaneous tissue site **520** without having to remove the dressing assembly **530**.

According to one illustrative embodiment, a see-through dressing assembly for use with a reduced-pressure system for treating a linear wound on a patient includes a closing dressing bolster for providing a closing force when under reduced pressure and a sealing member for covering the closing dressing bolster and providing a seal over the closing dressing bolster. The closing dressing bolster and sealing member are formed from see-through materials sufficient to allow perception of color from a point external to the see-through dressing assembly. The closing dressing bolster may include a top wall and a bottom wall. The top wall and bottom wall are coupled in a spaced relationship. The bottom wall includes a center portion, a first lateral portion, and a second lateral portion. A first closing member is formed on the first lateral portion, and a second closing member is formed on the second lateral portion. When placed under reduced pressure, the first closing member and the second closing member move towards each other.

According to one illustrative embodiment, a system for treating a wound on a patient with reduced pressure and that allows visual observation of the wound during treatment includes a dressing bolster for placing on a portion of the patient's epidermis over the wound. The dressing bolster is formed from a see-through material. The system further includes a sealing subsystem for providing a seal over the closing bolster and the patient's epidermis and a reduced-pressure subsystem for delivering a reduced pressure to the sealing subsystem. The sealing subsystem and reduced-pressure subsystem are operable to deliver reduced pressure to the dressing bolster. The dressing bolster, sealing subsystem, and reduced-pressure subsystem are operable to develop a directed force and to deliver reduced pressure to the wound. The sealing subsystem includes a see-through sealing member. The dressing bolster and sealing subsystem are operable to allow light to pass such that shades of color of the wound

15

may be perceived from a place external to the system. The dressing bolster has a first surface, a second, inward-facing surface and includes an oblique extremity formed a portion of the dressing bolster. The dressing bolster is formed from a medical bolster material that has a density greater than 20 kg/m<sup>3</sup>. The dressing bolster has the characteristic of evenly distributing a directed force when under a reduced pressure.

Although the present invention and its advantages have been disclosed in the context of certain illustrative, non-limiting embodiments, it should be understood that various changes, substitutions, permutations, and alterations can be made without departing from the scope of the invention as defined by the appended claims. It will be appreciated that any feature that is described in a connection to any one embodiment may also be applicable to any other embodiment.

We claim:

1. A method for treating a linear wound on a patient, the method comprising the steps of:

deploying a see-through dressing assembly over the linear wound and on top of the patient's epidermis;

deploying a see-through sealing member over the see-through dressing assembly and a portion of the patient's epidermis to form a fluid seal; and

providing reduced pressure to the see-through dressing assembly whereupon a closing force that is substantially within the plane of the patient's epidermis is developed; wherein the see-through dressing assembly includes a closing dressing bolster that comprises a first closing member and a second closing member;

reduced pressure from the reduced pressure source causes a bending moment about a center portion of the closing dressing bolster; and

the bending moment causes the first closing member and second closing member to develop the closing force.

2. The method of claim 1 wherein the see-through dressing assembly comprises the closing dressing bolster formed from see-through silicone.

3. The method of claim 1, wherein the see-through dressing assembly also develops a compressive force.

4. A method for treating a linear wound, the method comprising:

placing a closing dressing bolster having a first closing member and a second closing member over the linear wound;

placing a sealing member over the closing dressing bolster; providing a fluid seal between the sealing member and an epidermis proximate to the linear wound;

fluidly coupling the sealing member to a reduced pressure source; and

activating the reduced pressure source to cause a bending moment about a center portion of the closing dressing bolster that causes the first closing member and the

16

second closing member to develop a closing force substantially within a plane of the epidermis on the linear wound;

wherein the closing dressing bolster and the sealing member are comprised of a material that allows for sufficient light to pass through such that at least one characteristic of the linear wound may be observed from a point external to the closing dressing bolster.

5. The method of claim 4, wherein the material is silicone.

6. The method of claim 4, wherein the closing dressing bolster comprises a window such that the window is drawn closer to the wound under reduced pressure and the characteristic becomes observable through the window.

7. The method of claim 4, wherein the closing dressing bolster comprises a transparent silicone window such that the window is drawn closer to the wound under reduced pressure and the characteristic becomes observable through the window.

8. The method of claim 4, wherein the closing dressing bolster comprises a movable portion that moves aside to allow the characteristic to be observed if reduced pressure is removed from the closing dressing bolster.

9. The method of claim 4, wherein the closing dressing bolster comprises a first portion and a second portion that overlap under reduced pressure and separate if reduced pressure is removed.

10. A method for treating a linear wound, the method comprising:

placing a closing bolster having a first closing member and a second closing member on a portion of an epidermis over the linear wound;

applying a sealing subsystem over the closing bolster and the epidermis to provide a seal against the epidermis;

delivering a reduced pressure from a reduced-pressure subsystem to the closing bolster;

wherein the closing bolster, sealing subsystem, and reduced-pressure subsystem are operable to cause a bending moment about a center portion of the closing bolster to develop a closing force substantially within a plane of the epidermis and to deliver reduced pressure to the linear wound;

wherein the closing bolster and the sealing subsystem comprise a material that allows light to pass such that characteristics of the linear wound may be perceived from a place external to the system.

11. The method of claim 10, wherein the material is a soft polymer.

12. The method of claim 10, wherein the material is silicone.

\* \* \* \* \*