

US009213094B2

(12) **United States Patent**
Golparian et al.

(10) **Patent No.:** **US 9,213,094 B2**
(45) **Date of Patent:** **Dec. 15, 2015**

(54) **IN-FIELD CONFIGURATION OF LAND SURVEY SENSORS**

(75) Inventors: **Daniel Golparian**, Tokyo (JP); **John Lepper**, Rykkinn (NO)

(73) Assignee: **WesternGeco L.L.C.**, Houston, TX (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 714 days.

(21) Appl. No.: **12/482,584**

(22) Filed: **Jun. 11, 2009**

(65) **Prior Publication Data**

US 2010/0318298 A1 Dec. 16, 2010

(51) **Int. Cl.**

G01C 15/00 (2006.01)
G01S 5/00 (2006.01)
G01V 1/00 (2006.01)
G01S 13/82 (2006.01)

(52) **U.S. Cl.**

CPC **G01S 13/825** (2013.01); **G01C 15/00** (2013.01); **G01S 5/0027** (2013.01); **G01V 1/003** (2013.01)

(58) **Field of Classification Search**

CPC G01C 15/00; G01V 1/003; G01S 13/825; G01S 5/0027
USPC 702/14; 367/14, 16
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,897,821 A 1/1990 Thierry et al.
5,276,655 A 1/1994 Rialan et al.
5,920,828 A * 7/1999 Norris et al. 702/14

6,823,262 B2	11/2004	Bahorich et al.	
7,117,094 B2	10/2006	Fenton	
7,292,943 B2 *	11/2007	Elder et al.	702/14
7,725,264 B2 *	5/2010	Pavel et al.	702/14
7,894,301 B2 *	2/2011	Eperjesi et al.	367/77
2003/0075380 A1	4/2003	Orban et al.	
2003/0159877 A1	8/2003	Martin et al.	
2005/0033519 A1	2/2005	Fenton	
2005/0047275 A1	3/2005	Chamberlain et al.	
2005/0114033 A1	5/2005	Ray et al.	
2005/0236479 A1 *	10/2005	Schmidtberg et al.	235/384
2007/0052540 A1 *	3/2007	Hall et al.	340/572.1
2007/0188342 A1 *	8/2007	Valeriano et al.	340/825.49
2007/0286020 A1 *	12/2007	Bull et al.	367/56
2008/0021658 A1 *	1/2008	Pavel et al.	702/14
2008/0082701 A1 *	4/2008	Pavel et al.	710/10
2008/0159074 A1 *	7/2008	Guis	367/40
2008/0219094 A1	9/2008	Barakat	
2009/0122645 A1	5/2009	Guigne et al.	
2009/0218891 A1 *	9/2009	McCullough, Jr.	307/154
2010/0286919 A1 *	11/2010	Lee et al.	702/16
2010/0332688 A1	12/2010	Pavel et al.	

FOREIGN PATENT DOCUMENTS

EP 2105764 A2 9/2009
WO 0116622 A1 3/2001

OTHER PUBLICATIONS

Motorola RFID Product Brochure, 2007.
PCT Search Report, dated Dec. 30, 2010, Application No. PCT/US2010/038029.


* cited by examiner

Primary Examiner — Alexander Satanovsky

(57) **ABSTRACT**

Described herein are implementations of various technologies for a method for in-field configuration of land survey sensors. One or more planned positions of the sensors may be received. One or more actual positions of the sensors may be determined. The actual positions may be sent to the sensors while the sensors are powered off.

19 Claims, 6 Drawing Sheets






FIG. 1

100




FIG. 2

300




FIG. 3




FIG. 4

500




FIG. 5




FIG. 6

1

IN-FIELD CONFIGURATION OF LAND
SURVEY SENSORS

BACKGROUND

1. Field of the Invention

Implementations of various technologies described herein generally relate to methods and systems for configuring land survey sensors.

2. Description of the Related Art

The following descriptions and examples are not admitted to be prior art by virtue of their inclusion within this section.

Typically, land surveys may be performed for the purpose of geotechnical projects, such as hydrocarbon exploration. Land survey sensors may be deployed in the area to be surveyed based on a plan devised by a geophysicist. The initial plan may simply describe a pattern within which the sensors are to be placed. The pattern usually describes the relationships of sensors to each other in the deployment. These relationships may describe vertical and horizontal distances between individual sensors and/or rows of sensors.

Once the pattern is devised, a survey team may identify coordinates within the survey area where the sensors can be deployed according to the pattern. The survey team may use an actual map of the area to identify potential obstacles in deploying the sensors according to the pattern. Based on the positioning of roads, rivers, private property and the like, the survey team may modify the pattern in order to plan the physical deployment of the sensors.

Once coordinates have been determined for the sensors' deployment, a survey crew may place markers at the coordinates for each sensor. The markers may include flags, pegs, or even colored bags of sand. The crew may then later deploy each sensor at the positions of the markers.

In some circumstances, conditions on the ground may prevent the placement of a sensor at the planned coordinates. For example, some of the markers may have been removed before the sensors are deployed. Further, soil conditions at the planned coordinates may impede sensor deployment. For example, rocky soil at the planned coordinates may make digging impractical. Accordingly, the survey crew may place the sensor at a different location near the planned coordinates.

The data collected by the sensors is later processed at a data center to produce images of the subsurface of the survey area. As such, placing the sensors in locations other than the planned coordinates may introduce errors into the processing and the images produced therefrom.

SUMMARY

Described herein are implementations of various technologies for a method for in-field configuration of land survey sensors. In one implementation, one or more planned positions of the sensors may be received. One or more actual positions of the sensors be determined. The actual positions may be sent to the sensors while the sensors are powered off.

In another implementation, a plurality of sensors may be disposed in a survey area. A handheld device may be used for configuring the sensors. The handheld device may receive one or more planned positions of the sensors. The handheld device may determine one or more actual positions of the sensors. Further, the handheld device may send the actual positions to the sensors while the sensors are powered off.

In another implementation, seismic data may be received from one or more sensors in a survey area. The actual positions of the sensors may be received. The seismic data may be processed based on the actual positions.

2

The claimed subject matter is not limited to implementations that solve any or all of the noted disadvantages. Further, the summary section is provided to introduce a selection of concepts in a simplified form that are further described below in the detailed description section. The summary section is not intended to identify key features or essential features of the claimed subject matter, nor is it intended to be used to limit the scope of the claimed subject matter.

BRIEF DESCRIPTION OF THE DRAWINGS

Implementations of various technologies will hereafter be described with reference to the accompanying drawings. It should be understood, however, that the accompanying drawings illustrate only the various implementations described herein and are not meant to limit the scope of various technologies described herein.

FIG. 1 illustrates a land-based survey data acquisition system in accordance with one or more implementations described herein.

FIG. 2 illustrates a land-based survey data acquisition system in accordance with one or more implementations described herein.

FIG. 3 illustrates a flow chart of a method for configuring land survey sensors in accordance with one or more implementations described herein.

FIG. 4 illustrates a land-based survey data acquisition system in accordance with one or more implementations described herein.

FIG. 5 illustrates a flow chart of a method for processing seismic data in accordance with one or more implementations described herein.

FIG. 6 illustrates a computer network into which implementations of various technologies described herein may be implemented.

DETAILED DESCRIPTION

The discussion below is directed to certain specific implementations. It is to be understood that the discussion below is only for the purpose of enabling a person with ordinary skill in the art to make and use any subject matter defined now or later by the patent "claims" found in any issued patent herein.

The following paragraph provides a brief summary of various techniques described herein. In general, a set of coordinates for positioning land survey sensors may be downloaded to a handheld device. A survey crew may place the sensors according to the downloaded coordinates. In some circumstances, the sensors may be placed in positions different than, but near to, the planned positions. After placing the sensor, the survey crew may determine the actual coordinates of the placed sensor by using a global navigation satellite system device. The coordinates may be written to a radio frequency identification (RFID) tag in the sensor. After the survey is conducted, the coordinates may be merged with the acquired survey data for processing. One or more implementations of various techniques for in-field configuration of land survey sensors will now be described in more detail with reference to FIGS. 1-6 in the following paragraphs.

FIG. 1 illustrates a land-based survey data acquisition system **100** in accordance with one or more implementations described herein. The system **100** may include rows **108** of land survey sensors **105**, concentrators **106**, a network **101**, and a recording truck **102**. The system **100** may be used to acquire data for an electromagnetic or a seismic survey. As such, the sensors **105** may be electromagnetic or seismic. For

the purpose of clarity, the following discussion describes implementations of various techniques for the seismic survey.

The survey data acquisition system **100** may aim to capture information about acoustic and elastic energy that propagates through the subsurface of the survey area. The energy may be generated by one or more seismic sources (not shown). In one implementation, the seismic sources may be vibratory sources (vibrators). The vibrators may produce a pressure signal that propagates through the earth into the various subsurface layers of the survey area. In this manner, elastic waves may be formed through interaction with the geologic structure in the subsurface layers.

Elastic waves may be characterized by a change in local stress in the subsurface layers and a particle displacement, which is essentially in the same plane as the wavefront. Acoustic and elastic waves may also be known as pressure and shear waves. Acoustic and elastic waves may also be collectively referred to as the seismic wavefield.

The structure in the subsurface may be characterized by physical parameters such as density, compressibility and porosity. A change in the value of these parameters is referred to as an acoustic or elastic contrast and may be indicative of a change in subsurface layers, which may contain hydrocarbons. When an acoustic or elastic wave encounters an acoustic or elastic contrast, some part of the waves will be reflected back to the surface and another part of the wave will be transmitted into deeper parts of the subsurface. The elastic waves that reach the land surface may be measured by the sensors **105**. The sensors may measure seismic data, such as displacement, velocity, and acceleration. Examples of sensors **105** may include geophones, accelerometers, and the like.

The measurement of elastic waves at the land surface may be used to create a detailed image of the subsurface including a quantitative evaluation of the physical properties such as density, compressibility, porosity, etc. This is achieved by appropriate processing of the seismic data at a data center (not shown).

The recording truck **102** may receive the seismic data from the concentrators **106**. Each of the concentrators **106** may route the seismic data from multiple sensors **105** within a row **108** to the recording truck **102** over the network **101**. In one implementation, the network **101** may be a wireless network.

Typically, the appropriate processing of the seismic data is based on the coordinates of the actual positions where the sensors **105** are placed. As will be explained later in this document, in one implementation, the coordinates are contained within the sensors **105**. The coordinates may also be transferred to the recording truck **102** as described above.

FIG. **2** illustrates a close up view of a portion of the land-based survey data acquisition system **100** in accordance with one or more implementations described herein. As stated previously, the survey crew may place the sensors **105** according to a set of positions planned by the survey team. The planned positions may be downloaded to a handheld device **203**. Once placed in position by the survey crew, the coordinates of the actual positions where the sensors **105** are placed may be stored within the sensors **105**.

In one implementation, a tool **215** containing a global navigation satellite system (GNSS) device **212** and a read-write device **210** may be positioned on top of the placed sensor **105**. The tool **215** may then be used in conjunction with the handheld device **203** to determine the coordinates of the actual positions, and send the actual positions to the sensor **105** for storage.

GNSS may refer to a space-based navigation system, such as the global positioning system (GPS). Implementations of

the various techniques described herein may include GNSS's such as Glonass, Galileo, Compass, or combinations thereof.

The read-write device **210** may be used to send the actual position of the sensor **105** upon which the tool **215** is placed to the sensor **105**. Further, the read-write device **210** may be used to receive a serial number of the sensor **105**. The serial number may be used for later processing in determining whether seismic data from all the sensors **105** is being processed. In one implementation, the read-write device **210** may be a radio frequency identification (RFID) reader and writer.

RFID is an automatic identification method, relying on storing and remotely retrieving data using devices called RFID tags or transponders. RFID is a two-part system including interrogators and tags. The interrogators are also referred to herein as readers. The readers may be devices that communicate with tags to receive information from the tag.

Tags may be passive, semi-passive, or active. In the case of a passive or semi-passive tag, the reader may also provide power to the tag. Passive tags require no internal power source. However, semi-passive and active tags may require a power source, usually a small battery. The active RFID tags may include a RFID transceiver, which broadcasts signals to the reader, and a non-volatile memory. Further, the active RFID tags may have their own internal power source that may be used to power integrated circuits and to broadcast signals to the reader.

Semi-passive tags are similar to active tags as they have their own power source, but the battery is used just to power the microchip and not broadcast a signal. The radio frequency (RF) energy may be reflected back to the reader like a passive tag. A reader may emit radio waves in ranges from about one inch to over 30 meters, depending upon its power output and the RF used. When a passive tag passes through an electromagnetic zone of the reader, the passive tag may detect the reader's signal. The reader may decode the tag's data and typically, the data may be passed to a host computer for processing.

The GNSS device **212**, read-write device **210** and the handheld device **203** are described in greater detail with reference to FIGS. **3-4**.

FIG. **3** illustrates a flow chart of a method **300** for configuring land survey sensors **105** in accordance with one or more implementations described herein. The method **300** will be described with reference to FIG. **2** and FIG. **4**. FIG. **4** illustrates a land-based survey data acquisition system **400** in accordance with one or more implementations described herein. Further, it should be understood that while the operational flow chart for method **300** indicates a particular order of execution of the operations, in other implementations, the operations might be executed in a different order. The method **300** may be performed by the handheld device **203**, the GNSS device **212** and the RFID read-write device **210**.

At step **310**, the handheld device **203** may receive the one or more planned positions of the sensors **105**. As stated previously, the survey team may plan the deployment of the sensors **105** by determining coordinates for each planned position of the sensors **105**. These coordinates may be downloaded into the memory **455** of the handheld device **203**.

At step **320**, the sensors **105** may be placed according to the planned positions. As stated previously, in some circumstances, an obstruction may exist at the planned position. If an obstruction exists at the planned position, the sensor **105** may be placed at a position different from the planned position. For example, the sensor **105** may be placed in a nearby position that is clear of obstructions.

At step **330**, the actual position of the sensors **105** may be determined. In one implementation, the GPS module **415**

5

may be used to determine the actual positions of the sensors **105**. In such a case, the survey crew may place the tool **215** on top of the placed sensor **105**. The GPS module **415** may then communicate with satellites **410** of the GNSS to determine the coordinates of the actual positions based on the position of the tool **215**.

At step **340**, the actual positions may be sent to the sensors **105**. In one implementation, the GNSS device **212** may send the coordinates of the actual positions to the handheld device **203** via the wireless modules **420** of each device. The actual positions may be stored in the memory **455** of the handheld device. In turn, the handheld device **203** may send the actual positions to the RFID read-write device **210** via the wireless modules **420** of each device.

The RFID read-write device **210** may include an RFID read-write module **425**. The RFID read-write module **425** may include an RFID write module that is configured to send the actual positions to the sensors **105**.

The sensors **105** may include an active RFID tag **460**. The active RFID tag **460** may include an RFID transceiver **430** and non-volatile memory **435**. The RFID read-write module **425** may send the actual positions to the RFID transceiver **430**. The RFID transceiver **430** may store the actual positions in the non-volatile memory **435**. Advantageously, because the RFID tag **460** may have its own power source (not shown), the RFID transceiver **430** may receive and store the actual positions while the sensors **105** are powered off.

In one implementation, the handheld device **203** may also include the GPS module **415**, an RFID read module, an RFID write module, the RFID read-write module **425**, or combinations thereof. In such an implementation, the RFID transceiver **430** may be configured to receive the actual positions from the handheld device **203**.

In another implementation, additional information may be sent to the sensors **105** for storage in the non-volatile memory **435**. For example, the time of the placement of the sensors **105**, the weather conditions, a description of the surface geology, and a description of the coupling of the sensors **105** to the surface may also be sent to the sensors **105**. In such an implementation, a user may enter the information into the handheld device **203** via the user interface **450**. Consequently, the information may be sent to the RFID read-write device **210**, and the sensors **105** as described above.

At step **350**, the handheld device **203** may receive serial numbers of the sensors **105**. The serial numbers may uniquely identify individual sensors. In one implementation, the serial number for each of the sensors **105** may be contained within the non-volatile memory **435**. In such an implementation, the RFID-read-write module **425** may be configured to receive the serial numbers from the sensors **105**. In particular, the RFID read-write module **425** may receive the serial numbers from the RFID transceivers **430**.

In turn, the RFID read-write device **210** may send the serial numbers to the handheld device **203** via the wireless modules **420** of each device. The handheld device **230** may store the serial numbers in the memory **455**. In one implementation, the handheld device **203** may build a table that associates the serial numbers with the actual positions for their corresponding sensors **105**.

The table data may then be sent to the data center for later processing. In some implementations, the table data may be sent to a recording truck or camp.

At step **360**, the actual positions may be forwarded to the data center. At step **370**, the serial numbers may be forwarded to the data center. The forwarded data may be used in the processing of the seismic data as described with reference to FIG. **5**.

6

FIG. **5** illustrates a flow chart of a method **500** for processing seismic data in accordance with one or more implementations described herein. The method **500** may be performed at the data center after the seismic survey has been conducted. Further, it should be understood that while the operational flow chart for method **500** indicates a particular order of execution of the operations, in other implementations, the operations might be executed in a different order.

At step **510**, the serial numbers may be received from the handheld device **203**. At step **520**, the serial numbers may be received from the sensors **105**. In other words, all the sensors **105** that send seismic data may also send their serial numbers **105**. In the event that one of the sensors **105** fails, the serial number of the failed sensor **105** may not be received.

At step **530**, the serial numbers from the handheld device **203** and the sensors **105** may be compared. If there are serial numbers received from the handheld device **203** that are not received from the sensors **105**, data from the sensors with the missing serial numbers may not have been received.

At step **540**, if data is not received from all the sensors **105**, the method **500** may terminate. If at step **540**, data is received from all the sensors **105**, the method **500** continues to step **550**.

At step **550**, the actual positions of the sensors **105** may be received. At step **560**, the seismic data from the sensors **105** may be received.

At step **570**, the seismic data may be processed based on the actual positions received from the sensors **105**. The appropriate processing of the seismic data may depend on having the coordinates for the actual positions where the sensors **105** are located during the survey. For example, having incorrect data about the actual positions may result in errors being introduced into the generated images of the subsurface.

FIG. **6** illustrates a computing system **600**, into which implementations of various technologies described herein may be implemented. The computing system **600** may include one or more system computers **630**, which may be implemented as any conventional personal computer or server. However, those skilled in the art will appreciate that implementations of various technologies described herein may be practiced in other computer system configurations, including hypertext transfer protocol (HTTP) servers, handheld devices, multiprocessor systems, microprocessor-based or programmable consumer electronics, network PCs, mini-computers, mainframe computers, and the like.

The system computer **630** may be in communication with disk storage devices **629**, **631**, **632**, and **633**, which may be external hard disk storage devices. It is contemplated that disk storage devices **629**, **631**, **632**, and **633** are conventional hard disk drives, and as such, will be implemented by way of a local area network or by remote access. Of course, while disk storage devices **629**, **631**, **632**, and **633** are illustrated as separate devices, a single disk storage device may be used to store any and all of the program instructions, sensor data, device data, and results as desired.

In one implementation, seismic data collected from the land-based survey data acquisition system **100** may be stored in disk storage device **631**. Additionally, data received from the handheld device **203** may be stored in disk storage device **632**. The system computer **630** may retrieve the appropriate data from the disk storage devices **631**, **632** to process seismic and device data according to program instructions that correspond to implementations of various technologies described herein. The program instructions may be written in a computer programming language, such as C++, Java and the like. The program instructions may be stored in a computer-readable medium, such as program disk storage device **633**. Such

computer-readable media may include computer storage media and communication media.

Computer storage media may include volatile and non-volatile, and removable and non-removable media implemented in any method or technology for storage of information, such as computer-readable instructions, data structures, program modules or other data. Computer storage media may further include RAM, ROM, erasable programmable read-only memory (EPROM), electrically erasable programmable read-only memory (EEPROM), flash memory or other solid state memory technology, CD-ROM, digital versatile disks (DVD), or other optical storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, or any other medium which can be used to store the desired information and which can be accessed by the system computer **630**.

Communication media may embody computer readable instructions, data structures, program modules or other data in a modulated data signal, such as a carrier wave or other transport mechanism and may include any information delivery media. The term "modulated data signal" may mean a signal that has one or more of its characteristics set or changed in such a manner as to encode information in the signal. By way of example, and not limitation, communication media may include wired media such as a wired network or direct-wired connection, and wireless media such as acoustic, RF, infrared and other wireless media. Combinations of any of the above may also be included within the scope of computer readable media.

In one implementation, the system computer **630** may present output primarily onto graphics display **627**, or alternatively via printer **628**. The system computer **630** may store the results of the methods described above on disk storage **629**, for later use and further analysis. The keyboard **626** and the pointing device (e.g., a mouse, trackball, or the like) **625** may be provided with the system computer **630** to enable interactive operation.

The system computer **630** may be located at a data center remote from the area of interest. The system computer **630** may be in communication with the sensors **105**, and the handheld device **203** (either directly or via a recording unit, not shown), to receive seismic and device data. After conventional formatting and other initial processing, this data may be stored by the system computer **630** as digital data in the disk storage **631**, **632** for subsequent retrieval and processing in the manner described above.

While FIG. 6 illustrates the disk storage **631**, **632** as directly connected to the system computer **630**, it is also contemplated that the disk storage devices **631**, **632** may be accessible through a local area network or by remote access. Furthermore, while disk storage devices **629**, **631**, and **632** are illustrated as separate devices for storing input data and analysis results, the disk storage devices **629**, **631**, and **632** may be implemented within a single disk drive (either together with or separately from program disk storage device **633**), or in any other conventional manner as will be fully understood by one of skill in the art having reference to this specification.

While the foregoing is directed to implementations of various technologies described herein, other and further implementations may be devised without departing from the basic scope thereof, which may be determined by the claims that follow. Although the subject matter has been described in language specific to structural features and/or methodological acts, it is to be understood that the subject matter defined in the appended claims is not necessarily limited to the specific features or acts described above. Rather, the specific

features and acts described above are disclosed as example forms of implementing the claims.

What is claimed is:

1. A method for configuring land survey sensors, comprising:
 - receiving one or more planned positions of the sensors;
 - determining one or more actual positions of the sensors;
 - sending the actual positions to radio-frequency identification (RFID) transceivers of the sensors receiving one or more serial numbers of the sensors from the RFID transceivers of the sensors forwarding the one or more serial numbers to a data center using the handheld device; and
 - forwarding the actual positions to the data center.
2. The method of claim 1, wherein the actual positions of the sensors are determined using a global navigation satellite system.
3. The method of claim 1, further comprising placing the sensors according to the planned positions.
4. The method of claim 3, wherein placing the one or more sensors according to the planned positions comprises placing the one or more sensors in one or more positions different from the planned positions if an obstruction exists at the planned positions.
5. The method of claim 3, wherein the planned positions are different from the actual positions.
6. The method of claim 1, further comprising sending a time of the placement of the sensors, a weather condition at the time, a geology description of a surface at the actual positions, a description of a coupling of the sensors to the surface at the actual positions, or combinations thereof, to the sensors.
7. The method of claim 1, wherein the sensors comprise electromagnetic survey sensors.
8. The method of claim 1, wherein the sensors comprise seismic survey sensors.
9. A land acquisition system, comprising:
 - a plurality of sensors disposed in a survey area;
 - a handheld device for configuring the sensors comprising:
 - a processor; and
 - a memory having program instructions configured to cause the processor to:
 - receive one or more planned positions of the sensors;
 - determine one or more actual positions of the sensors;
 - send the actual positions to radio-frequency identification (RFID) transceivers of the sensors while the sensors are powered off;
 - receive one or more serial numbers of the sensors from the RFID transceivers of the sensors;
 - forward the one or more serial numbers to a data center; and
 - send the actual positions to the data center.
10. The land acquisition system of claim 9, wherein the handheld device further comprises a global navigation satellite system (GNSS) module configured to determine the actual positions of the sensors.
11. The land acquisition system of claim 9, wherein the handheld device further comprises a RFID write module configured to send the actual positions to the sensors.
12. The land acquisition system of claim 9, wherein the handheld device further comprises a RFID read module configured to receive the one or more serial numbers of the sensors.
13. The land acquisition system of claim 9, wherein each sensor comprises an active RFID tag that is configured to receive the actual positions from the handheld device and to write the actual positions to a memory of the RFID tag.

9

14. The land acquisition system of claim 9, wherein the sensors comprise electromagnetic survey sensors.

15. The land acquisition system of claim 9, wherein the sensors comprise seismic survey sensors.

16. A method for processing seismic data, comprising:
receiving, at a data center, a first set of serial numbers of sensors from a handheld device, wherein the first set of serial numbers was received from radio-frequency identification (RFID) transceivers of the sensors while the sensors were powered off;

receiving, at the data center, a second set of serial numbers of the sensors from the sensors;

comparing the first set of serial numbers with the second set of serial numbers;

determining, using a microprocessor, whether seismic data has been received from the sensors in a seismic survey area based on the comparison;

receiving actual positions of the sensors; and

10

processing the seismic data based on the actual positions if it is determined that the seismic data has been received from the sensors based on the comparison.

17. The method of claim 16, wherein determining whether the seismic data has been received from the sensors comprises:

determining that the seismic data from all of the sensors have not been received, if the first set of serial numbers does not match the second set of serial numbers.

18. The method of claim 16, wherein determining whether the seismic data has been received from the sensors comprises:

determining that the seismic data from all of the sensors have been received, if the first set of serial numbers matches the second set of serial numbers.

19. The method of claim 16, wherein the first set of serial numbers was received by the handheld device from the RFID transceivers of the sensors.

* * * * *