

US009227641B2

(12) **United States Patent**
Schwellnus et al.

(10) **Patent No.:** **US 9,227,641 B2**
(45) **Date of Patent:** **Jan. 5, 2016**

(54) **VEHICLE POSITION DETERMINING SYSTEM AND METHOD OF USING THE SAME**

4,851,851 A 7/1989 Hane
5,227,803 A 7/1993 O'Connor et al.
5,332,180 A 7/1994 Peterson et al.
5,351,052 A 9/1994 D'Hont et al.
5,532,697 A 7/1996 Hidaka et al.
5,602,919 A 2/1997 Hurta
5,686,928 A 11/1997 Pritchett et al.
5,719,567 A 2/1998 Norris

(71) Applicant: **Thales Canada Inc**, Toronto, Ontario (CA)

(72) Inventors: **Carl Schwellnus**, York (CA); **Colin Bantin**, Oakville (CA)

(Continued)

(73) Assignee: **Thales Canada Inc**, Toronto, Ontario (CA)

FOREIGN PATENT DOCUMENTS

CA 952221 7/1974
DE 102007043460 B4 3/2009

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 354 days.

(Continued)

(21) Appl. No.: **13/886,674**

(22) Filed: **May 3, 2013**

(65) **Prior Publication Data**

US 2014/0326835 A1 Nov. 6, 2014

International Search Report for corresponding International PCT Application No. PCT/IB2014/060455 dated Jul. 15, 2014.

Primary Examiner — Jason C Smith

(74) *Attorney, Agent, or Firm* — Hauptman Ham, LLP

(51) **Int. Cl.**
B61L 25/00 (2006.01)
B61L 25/02 (2006.01)
B61L 3/12 (2006.01)

(57) **ABSTRACT**

(52) **U.S. Cl.**
CPC **B61L 25/023** (2013.01); **B61L 3/121** (2013.01); **B61L 25/02** (2013.01); **B61L 25/025** (2013.01)

A position determining system for a vehicle on a guideway which includes an on-board controller configured to determine a position of the vehicle on the guideway. The position determining system further includes a transmitter/detector array configured to emit an interrogation signal and to receive reflection signals based on the emitted interrogation signal. The transmitter/detector array includes a first antenna and a second antenna, the second antenna spaced from the first antenna in a direction of travel of the vehicle. The position determining system further includes a transponder identification database configured to store transponder information. The on-board controller is configured to determine the position of the vehicle along the guideway based on a modulated reflection signal received by the transmitter/detector array and a first non-modulated reflection signal received by the transmitter/detector array.


(58) **Field of Classification Search**
CPC B61L 29/24; B61L 29/18; B61L 29/00; B61L 29/32; B61L 29/246; B61L 25/025; B61L 25/02; B61L 25/021; B61L 2205/04; B61L 1/188; B61L 27/088
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,768,740 A 9/1988 Corrie
4,804,961 A 2/1989 Hane

20 Claims, 6 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

6,072,421 A 6/2000 Fukae et al.
 6,179,252 B1 * 1/2001 Roop B61L 29/18
 246/122 R
 6,219,596 B1 4/2001 Fukae et al.
 7,145,475 B2 12/2006 Kavner
 7,196,636 B2 * 3/2007 Graham B61L 29/28
 246/122 R
 7,315,770 B2 * 1/2008 Wade B61L 29/00
 246/1 R
 7,347,379 B2 3/2008 Ward et al.
 7,388,483 B2 * 6/2008 Welles B61L 5/02
 200/61.45 M
 7,626,488 B2 12/2009 Armstrong
 7,769,544 B2 * 8/2010 Blesener B61L 29/28
 246/124
 7,772,996 B2 * 8/2010 Burns G08G 1/164
 340/988
 8,297,558 B2 * 10/2012 O'Dell B61L 29/226
 246/126
 8,630,757 B2 * 1/2014 Daum B61L 3/006
 701/19

8,838,301 B2 * 9/2014 Makkinejad B61L 25/025
 246/3
 2002/0017979 A1 2/2002 Krause et al.
 2010/0271188 A1 10/2010 Nysen
 2011/0084176 A1 * 4/2011 Reichelt B61L 23/041
 246/473.1
 2011/0095139 A1 * 4/2011 O'Dell B61L 29/28
 246/293
 2012/0323474 A1 12/2012 Breed et al.
 2013/0062474 A1 * 3/2013 Baldwin B61L 29/282
 246/122 R
 2013/0270395 A1 * 10/2013 Steffen, II B61L 29/266
 246/125
 2014/0012438 A1 * 1/2014 Shoppa B61L 1/188
 701/19
 2014/0263857 A1 * 9/2014 Huntimer B61L 25/025
 246/122 R
 2014/0326835 A1 * 11/2014 Schwellnus B61L 25/02
 246/122

FOREIGN PATENT DOCUMENTS

EP 0487708 B1 6/1992
 JP H0686215 11/1994
 JP 9002269 1/1997

* cited by examiner




FIGURE 1





Figure 2






Figure 4




FIGURE 5




FIGURE 6

1

VEHICLE POSITION DETERMINING SYSTEM AND METHOD OF USING THE SAME

BACKGROUND

Determining a position of each vehicle in a guideway network helps to maintain precise control and coordinated movement of vehicles in the guideway network. In some instances, vehicle positioning information is generated using on-guideway devices positioned on a guideway, such as axle counters or track circuits, which generate a position signal in response to the presence of the vehicle on the guideway at the location of the on-guideway device.

In some instances, vehicle positioning information is generated by an isolated transponder which receives a signal from the vehicle and transmits a modulated signal back to the vehicle. The modulated signal provides a unique identification of the transponder used to determine the position of the vehicle.

BRIEF DESCRIPTION OF THE DRAWINGS

One or more embodiments are illustrated by way of example, and not by limitation, in the figures of the accompanying drawings, wherein elements having the same reference numeral designations represent like elements throughout. It is emphasized that, in accordance with standard practice in the industry various features may not be drawn to scale and are used for illustration purposes only. In fact, the dimensions of the various features in the drawings may be arbitrarily increased or decreased for clarity of discussion. The figures of the drawings are incorporated herein and include the following wherein:

FIG. 1 is a block diagram of a vehicle position determining system in accordance with one or more embodiments;

FIG. 2 is a block diagram of a transmitter/detector array on-board a vehicle in accordance with one or more embodiments;

FIG. 3 is a block diagram of a transmitter/detector array on-board a vehicle in accordance with one or more embodiments;

FIG. 4 is a schematic diagram of a vehicle position determining arrangement disposed along a guideway in accordance with one or more embodiments;

FIG. 5 is a block diagram of a general purpose computing device for implementing the vehicle position determining system shown in FIG. 1 in accordance with one or more embodiments; and

FIG. 6 is a flow chart of a method of determining a vehicle position in accordance with one or more embodiments.

DETAILED DESCRIPTION

The following disclosure provides many different embodiments, or examples, for implementing different features of the invention. Specific examples of components and arrangements are described below to simplify the present disclosure. These are examples and are not intended to be limiting.

As automated control of vehicles traveling along guideways increases, precision of position determination of the vehicles becomes more important. In some instances, positioning systems relying solely on a transponder having a unique identification code are capable of determining a position of the vehicle with an accuracy of approximately 2 meters (m). In some automatically controlled systems, a higher degree of precision helps to ensure accurate stopping

2

locations for the vehicle. For example, a system seeking to align exit doors of a vehicle with certain positions on a platform, such as entry gates, doorways or other demarcations, would be aided by a higher degree of position accuracy. In some embodiments, a position determining system detects a location of a reflective positioning element and a transponder and is capable of determining the position of the vehicle within an accuracy of approximately 3 centimeters (cm). The increased precision of the position determination facilitates alignment of exit doors of the vehicle with positions on the platform, for example. The increased precision also increases efficiency of control for multiple vehicles along the guideway by reducing a potential error in the position for each of the vehicles on the guideway.

In some embodiments, the position determining system also provides an advantage of determining a heading of the vehicle using a single transponder. In other position determining systems, the heading of the vehicle is determined by comparing the unique identification code of consecutive transponders. In some instances, a distance between consecutive transponders is significant which delays determination of the heading of the vehicle until the vehicle can traverse the distance between the consecutive transponders. If transponders are positioned too close together, a risk of the unique identification code of two consecutive transponders interfering with each other increases. In addition, the cost of installing and maintaining the transponders increases as a number of transponders on the guideway increases. In some embodiments, the position determining system determines the heading of the vehicle by detecting a single transponder and two reflective positioning elements positioned along the guideway. The use of a single transponder decreases installation and maintenance costs. The use of the two reflective positioning elements also helps reduce a delay time in determining the heading of the vehicle because the reflective positioning elements can be located close to the transponder without a risk of interference with the unique identification code of the transponder. The use of the two reflective positioning elements also helps to increase accuracy of the position determining system in comparison with a single reflective positioning element arrangement.

FIG. 1 is a block diagram of a position determining system **100** in accordance with one or more embodiments. Position determining system **100** includes a vital on-board controller (VOBC) **102** configured to determine a position of the vehicle along the guideway. Position determining system **100** further includes a transmitter/detector array **104** configured to transmit a signal to interrogate positioning elements along the guideway and receive signals from the interrogated positioning elements. Position determining system **100** further includes a transponder ID database **106** configured to store the unique identification codes of transponders and a corresponding position along the guideway. Position determining system **100** further includes an external control system **108** configured to communicate with VOBC **102**.

In some embodiments, VOBC **102** is implemented by running a background process on every vital machine having safety integrity level 4 (SIL 4) in the system which listens to communication traffic and collects key data as identified by a configuration profile of the VOW. SIL 4 is based on International Electrotechnical Commission's (IEC) standard IEC 61508. SIL level 4 means the probability of failure per hour ranges from 10^{-8} to 10^{-9} .

In some embodiments, VOBC **102** is configured to communicate with transmitter/detector array **104** through a wired or wireless connection. In some embodiments, transmitter/detector array **104** is incorporated into VOBC **102**. In some

embodiments, VOBC 102 is configured to communicate with transponder ID database 106 through a wired or wireless connection. In some embodiments, transponder identification (ID) database 106 is incorporated into VOBC 102. VOBC 102 is configured to communicate with external control system 108 via a wireless connection. In at least some embodiments, a wireless connection comprises a radio frequency signal, an inductive loop signal, an optical signal, a microwave signal, or another suitable signal. VOBC 102 is configured to transmit position information to external control system 108. In some embodiments, VOBC 102 is configured to transmit heading information to external control system 108. VOBC 102 is configured to receive information, such as movement authority instructions, updates for transponder ID database 106, switch positions along the guideway, position information for other vehicles along the guideway, or other suitable information, from external control system 108.

Transmitter/detector array 104 is configured to emit an interrogation signal for interrogating positioning elements positioned along the guideway. In some embodiments, the interrogation signal is a single wavelength unique to the vehicle. In some embodiments, the interrogation signal includes a tunable wavelength. Transmitter/detector array 104 is configured to receive signals from the positioning elements. The signals from the positioning elements include a reflected signal of the interrogation signal or a modulated reflection signal based on the interrogation signal, in some embodiments. In some embodiments, the signals from the positioning elements are analyzed by circuitry in transmitter/detector array 104 and the result of the analysis is transmitted to VOBC 102. In some embodiments, the signals from the positioning elements are received by transmitter/detector array 104 and are sent directly to VOBC 102 and are analyzed by circuitry in the VOBC. Additional details of some embodiments of transmitter/detector array 104 are provided below in reference to FIG. 2.

Transponder ID database 106 is a non-transitory computer readable medium configured to store the unique identification codes of transponders disposed along the guideway cross-referenced with a location of the transponder along the guideway. In some embodiments, VOBC 102 is configured to update transponder ID database 106 based on information received from external control system 108. In some embodiments, transponder ID database 106 includes the unique identification codes for less than all of the transponders along the guideway. In some embodiments, transponder ID database 106 includes the unique identification codes for all of the transponders along the guideway. In some embodiments where the signals from the positioning elements are analyzed in the transmitter/detector array 104, the transmitter/detector array is configured to communication with transponder ID database 106.

External control system 108 is configured to communicate with VOBC 102. In some embodiments, external control system 108 is a de-centralized control system configured to control movement of vehicles along less than an entirety of a guideway network. In some embodiments, external control system 108 is a centralized control system configured to control movement of vehicles along the entirety of the guideway network. In some embodiments, external control system 108 is configured to provide movement instructions to VOBC 102 which are implemented by a driver or by an automatic speed and braking control system (not shown). In some embodiments, the movement instructions are based on position information received from VOBC 102. In some embodiments, external control system 108 is configured to receive position information from VOBC 102 and transmit move-

ment instructions to other vehicles in the guideway network based on the position information from the VOBC.

FIG. 2 is a block diagram of a transmitter/detector array 200 in accordance with one or more embodiments. Transmitter/detector array 200 is configured to analyze signals received from positioning elements along the guideway. Transmitter/detector 200 includes at least two antennae 202 with one configured to emit interrogation signals and two or more configured to receive reflection signals. Antennae 202 are spaced from each other in a direction of travel along the guideway. Each antenna 202 is connected to a corresponding splitter 204 configured to split a signal received by the respective antenna. Each splitter 204 is connected to a summing circuit 206 configured to add the signals from the splitters 204 together. Each splitter 204 is also connected to a difference circuit 208 configured to determine a difference between the signals from the splitters 204. Summing circuit 206 and difference circuit 208 are both connected to a phase comparator 210 configured to compare the sum of the signals from the splitters 204 with a difference between the signals from the splitters. Transmitter/detector array 200 further includes a position detection unit 212 configured to determine if a highest magnitude sum from summing circuit 206 coincides with a determined phase difference of zero in order to identify a precise location of the positioning element. In some embodiments where the positioning element is a half-wavelength reflector, phase comparator 210 is configured to determine the half-wavelength reflector is located an equal distance from each antennae 202 if a phase of an output of summing circuit 206 matches a phase of an output of difference circuit 208.

Transmitter/detector 200 is also configured to receive a main radio frequency (RF) signal for interrogating the positioning elements at summing circuit 206. The main RF signal is received at summing circuit 206. In some embodiments, the main RF signal is received at a different location in transmitter/detector array 200. In some embodiments, the main RF signal is received from VOBC 102 (FIG. 1). In some embodiments, the main RF signal is received from a separate signal generator. In some embodiments, the main RF signal is generated by a signal generator within transmitter/detector array 200. In some embodiments, a wavelength of the main RF signal is unique to the vehicle. In some embodiments, the wavelength of the main RF signal is tunable. In some embodiments, the wavelength of the main RF signal is in a radio frequency wavelength range. In some embodiments, the wavelength of the main RF signal is in an infrared frequency wavelength range.

In operation, summing circuit 206 receives the main RF signal and transmits the main RF signal to splitters 204, which in turn supply the main RF signal to at least one antenna of antennae 202. Antennae 202 convert the main RF signal into the interrogation signal and emit the interrogation signal. In some embodiments, antennae 202 emit the interrogation signal continuously. In some embodiments, antennae 202 emit the interrogation signal in a pulsed manner. Antennae 202 also receive reflection signals from positioning elements along the guideway. In some embodiments, the reflection signals are modulated reflections of the interrogation signal. In some embodiments, the reflection signals include the unique identification code of a transponder. In some embodiments, the reflection signals are non-modulated reflections of the interrogation signals.

Antennae 202 convert the reflection signals to detection signals and transmit the detection signals to the respective splitters 204. Splitters 204 split the detection signals and transfer the split detection signals to both summing circuit

5

206 and difference circuit 204. Summing circuit 206 determines a sum of the split detection signals and transmits the sum to phase comparator 210 and position determining unit 212. Difference circuit 208 determines a difference between the split detection signals and transmits the difference to phase comparator 210.

Phase comparator 210 determines a phase difference between the sum and the difference. Phase comparator 210 outputs a determined phase difference. Phase comparator 210 determines a reflective positioning element, e.g., a half-wavelength reflector, is positioned an equal distance from each antennae 202 if the determined phase difference is zero. Determining the position of the vehicle based on the phase difference between the received signals of antennae 202 increases precision of the position determination. Position detection unit 212 receives the sum from summing circuit 206. Position detection unit 212 also receives the determined phase difference and determines whether the sum from summing circuit 206 is at the highest magnitude. The vehicle is directly over the reflective positioning element if the phase difference is equal to zero and the sum is at the highest magnitude. In some embodiments, transmitter/detector array 200 determines the position of the vehicle relative to the reflective positioning element within an error of less than 3 cm.

Antennae 202 also detect the modulated reflection signal from a transponder. In some embodiments, a separate antenna detects the modulated reflection signal from the transponder. In operation, transmitter/detector array 200 receives the modulated reflection signal and transmits the modulated reflection signal to VOBC 102 (FIG. 1). In some embodiments, transmitter/detector array 200 identifies the unique identification code of the transponder and transmits the unique identification code to VOBC 102. In some embodiments, transmitter/detector array 200 transmits the modulated reflection signal to VOBC 102, and the VOBC identifies the unique identification code of the transponder.

FIG. 3 is a block diagram of a transmitter/detector array 300 on-board a vehicle in accordance with one or more embodiments. Transmitter/detector array 300 is similar to transmitter/detector array 200, transmitter/detector array 300 does not include difference circuit 208. Similar elements in transmitter/detector array 300 are labeled with a same reference number as in transmitter/detector array 200 increased by 100. Phase comparator 310 is configured to determine a phase difference of the reflection signals received directly from splitters 304.

In operation, the interrogation signal is transmitted on one antenna 302a. In some embodiments, antenna 302a emits the interrogation signal continuously. In some embodiments, antenna 302a emits the interrogation signal in a pulsed manner. Both antennae 302a and 302b receive reflection signals from positioning elements along the guideway. Antennae 302 convert the reflection signals to detection signals and transmit the detection signals to the respective splitters 304. Splitters 204 split the detection signals and transfer the split detection signals to both summing circuit 304 and phase comparator 310. Summing circuit 306 determines a sum of the split detection signals and transmits the sum to position determining unit 312.

Phase comparator 310 determines a phase difference between signals received directly from splitters 304. Phase comparator 310 outputs a determined phase difference. Position detection unit 312 receives the sum from summing circuit 306. Position detection unit 312 also receives the determined phase difference and determines whether the sum from summing circuit 306 is at the highest magnitude. The vehicle is

6

directly over the reflective positioning element if the phase difference is equal to zero and the sum is at the highest magnitude. In some embodiments, transmitter/detector array 300 determines the position of the vehicle relative to the reflective positioning element within an error of less than 3 cm.

Antennae 302 also detect the modulated reflection signal from a transponder. In some embodiments, a separate antenna detects the modulated reflection signal from the transponder. In operation, transmitter/detector array 300 receives the modulated reflection signal and transmits the modulated reflection signal to VOBC 102 (FIG. 1). In some embodiments, transmitter/detector array 300 identifies the unique identification code of the transponder and transmits the unique identification code to VOBC 102. In some embodiments, transmitter/detector array 300 transmits the modulated reflection signal to VOBC 102, and the VOBC identifies the unique identification code of the transponder.

FIG. 4 is a schematic diagram of a vehicle position determining arrangement 400 disposed along a guideway 402 in accordance with one or more embodiments. Vehicle position determining arrangement 400 includes a transponder 404 having a unique identification code. Vehicle position determining arrangement 400 further includes a first reflective positioning element 406a and a second reflective positioning element 406b positioned along guideway 402 and spaced on opposite sides of transponder 404 along the guideway. First reflective positioning element 406a is spaced a first distance D1 from transponder 404. Second reflective positioning element 406b is spaced a second distance D2 from transponder 404. First distance D1 is different from second distance D2. Vehicle position determining arrangement 400 also includes an external control system 408 configured to communicate with transponder 404 and a vehicle 410. Only a portion of vehicle 410 is present in FIG. 4 for clarity and ease of explanation. A position determining system 412 is disposed on-board vehicle 410. Position determining system 412 is located on an axle of vehicle 410. In some embodiments, position determining system 412 is located on an undercarriage of vehicle 410, inside the vehicle, on a side panel of the vehicle or in another suitable position on the vehicle.

Guideway 402 is a dual rail guideway. In some embodiments, guideway 402 is a single rail guideway. In some embodiments, guideway 402 is free of rails.

Transponder 404 is configured to receive the interrogation signal from position determining system 412 and transmit the modulated reflection signal which includes the unique identification code for the transponder. Transponder 404 is located between rails of guideway 402. In some embodiments, transponder 404 is positioned on a wayside of guideway 402.

First reflective positioning element 406a and second reflective positioning element 406b are configured to reflect the interrogation signal without modulating or modifying the reflection signal. First reflective positioning element 406a and second reflective positioning element 406b are located between the rails of guideway 402. In some embodiments, first reflective positioning element 406a and second reflective positioning element 406b are located outside the rails of guideway 402, on a supporting device located on the wayside of the guideway, on a wall of a tunnel, or at other suitable locations. In some embodiments, first reflective positioning element 406a and second reflective positioning element 406b are half-wavelength reflectors. Half-wavelength reflectors have a dimension, in the direction of travel, approximately equal to half of the wavelength of the interrogation signal. In some embodiments, first reflective positioning element 406a

and second reflective positioning element **406b** comprise copper, aluminum, or another suitable reflective material.

First reflective positioning element **406a** and second reflective positioning element **406b** are spaced from transponder **404** in a single dimension. In some embodiments, reflective positioning element **406a** and second reflective positioning element **406b** are spaced from transponder **404** in two or three dimensions, so long as a distance in the direction of travel along guideway **402** between the transponder and the first and second reflective positioning elements is known. First distance D1 is greater than second distance D2. In some embodiments, second distance D2 is greater than first distance D1. In some embodiments, second reflective positioning element **406b** is omitted.

External control **408** is positioned on the wayside of guideway **402**. In some embodiments, external control **408** is a de-centralized control. In some embodiments, external control **408** is a centralized control. External control **408** is configured to communicate with position determining system **412** on-board vehicle **410** and transponder **404**. External control **408** is configured to determine whether transponder **404** is functioning properly. In some embodiments, position determining system **412** determines whether transponder **404** is functioning properly based on a direction of travel and a database of transponder locations. External control **408** is also configured to receive position information from position determining system **412** and to provide movement instructions to the position determining system or an automatic speed and braking system on-board vehicle **410**. In some embodiments, external control **408** is configured to transmit update information to position determining system **412** for updating a transponder ID database, e.g., transponder ID database **106** (FIG. 1).

Vehicle **410** is a rail mounted vehicle. In some embodiments, vehicle **410** is a train, a roller coaster, a monorail, a magnetic guided vehicle, or another suitable vehicle.

Positioning determining system **412** is configured to determine a position of vehicle **410** along guideway **402** based on transponder **404**, at least one of first reflective positioning element **406a** or second reflective positioning element **406b**, and a corresponding first distance D1 or second distance D2. In some embodiments, position determining system **412** is position determining system **100** (FIG. 1).

In operation, as vehicle **410** travels along guideway **402**, position determining system **412** emits the interrogation signal. In this example, vehicle **410** is traveling so as to pass, in order, first reflective positioning element **406a**, transponder **404** and second reflective positioning element **406b**. Position determining system **412** interrogates first reflective positioning element **406a** and receives the reflection signal. Position determining system **412** determines the precise position of vehicle **410** relative to the first reflective positioning element, as described above with respect to transmitter/detector array **200** (FIG. 2) or transmitter/detector array **300** (FIG. 3). As vehicle **410** continues along guideway **402**, position determining system **412** interrogates transponder **404** and receives the modulated reflection signal including the unique identification code of the transponder. Position determining system **412** identifies the absolute location of transponder **404** using the transponder ID database, e.g., transponder ID database **106**. Position determining system **412** uses the determined position relative to first reflective positioning element **406a**, the known location of transponder **404** having the detected unique identification code, and the known first distance D1 to calculate the position of vehicle **410**. In some embodiments, the accuracy of the position determination is less than a 3 cm error.

Using a single reflective positioning element, position determining system **412** is able to determine the position of vehicle **410** along guideway **402**. Using two reflective positioning elements, position determining system **412** is able to determine both the position of vehicle **410** and the heading of the vehicle. Continuing with the example above, as vehicle **410** passes second reflective positioning element **406b**, position determining system **412** determines when the vehicle is passing the second reflective positioning element. Using a known distance traveled by vehicle **410** after passing transponder **404**, position determining system **412** calculates a distance traveled between the transponder and second reflective positioning element **406b**. Position determining system **412** compares the calculated time with first distance D1 and second distance D2 to determine the heading of vehicle. That is, position determining system **412** determines in which order vehicle **410** passes the first reflective positioning element **406a** and second reflective positioning element **406b** based on the calculated distance traveled and the known first distance D1 and the known second distance D2.

FIG. 5 is a block diagram of a general purpose computing device for implementing a position determining system **500** in accordance with one or more embodiments. In some embodiments, position determining system **500** is similar to position determining system **412** (FIG. 4). Position determining system **500** includes a hardware processor **502** and a non-transitory, computer readable storage medium **504** encoded with, i.e., storing, the computer program code **506**, i.e., a set of executable instructions. Computer readable storage medium **504** is also encoded with instructions **507** for interfacing with elements of position determining system **500**. The processor **502** is electrically coupled to the computer readable storage medium **504** via a bus **508**. The processor **502** is also electrically coupled to an I/O interface **510** by bus **508**. A network interface **512** is also electrically connected to the processor **502** via bus **508**. Network interface **512** is connected to a network **514**, so that processor **502** and computer readable storage medium **504** are capable of connecting and communicating to external elements, e.g., external control **108** (FIG. 1) or external control **408** (FIG. 4), via network **514**. In some embodiments, network interface **512** is replaced with a different communication path such as optical communication, microwave communication, inductive loop communication, or other suitable communication paths. A transponder ID database **516** is also electrically connected to the processor **502** via bus **508**. Transponder ID database **516** stores positions and unique identification codes of transponders along the guideway. The processor **502** is configured to execute the computer program code **506** encoded in the computer readable storage medium **504** in order to cause position determining system **500** to be usable for performing a portion or all of the operations as described with respect to position determining system **100** (FIG. 1), transmitter/detector array **200** (FIG. 2), transmitter/detector array **300** (FIG. 3), position determining system **412** (FIG. 4) or a method **600** (FIG. 6).

In some embodiments, the processor **502** is a central processing unit (CPU), a multi-processor, a distributed processing system, an application specific integrated circuit (ASIC), and/or a suitable processing unit. In some embodiments, processor **502** is configured to generate position information signals for transmitting to external circuitry via network interface **512**. In some embodiments, processor **502** is configured to update transponder ID database **516** based on information received via network interface **512**.

In some embodiments, the computer readable storage medium **504** is an electronic, magnetic, optical, electromagnetic, infrared, and/or a semiconductor system (or apparatus

or device). For example, the computer readable storage medium **304** includes a semiconductor or solid-state memory, a magnetic tape, a removable computer diskette, a random access memory (RAM), a read-only memory (ROM), a rigid magnetic disk, and/or an optical disk. In some embodiments using optical disks, the computer readable storage medium **504** includes a compact disk-read only memory (CD-ROM), a compact disk-read/write (CD-R/W), and/or a digital video disc (DVD). In some embodiments, the computer readable storage medium **404** is part of an embedded microcontroller or a system on chip (SoC).

In some embodiments, the storage medium **504** stores the computer program code **506** configured to cause position determining system **500** to perform the operations as described with respect to position determining system **100** (FIG. 1), transmitter/detector array **200** (FIG. 2), transmitter/detector array **300** (FIG. 3), position determining system **412** (FIG. 4) or method **600** (FIG. 6). In some embodiments, the storage medium **504** also stores information needed for performing the operations as described with respect to position determining system **500**, such as a position parameter **518**, a first distance parameter **520**, a second distance parameter **522**, a vehicle speed parameter **524**, an emitted wavelength parameter **526**, a heading parameter **528** and/or a set of executable instructions to perform the operation as described with respect to position determining system **500**.

In some embodiments, the storage medium **504** stores instructions **507** for interfacing with external components. The instructions **507** enable processor **502** to generate operating instructions readable by the external components to effectively implement the operations as described with respect to position determining system **500**.

Position determining system **500** includes I/O interface **510**. I/O interface **510** is coupled to external circuitry. In some embodiments, I/O interface **510** is configured to receive instructions from a port in an embedded controller.

Position determining system **500** also includes network interface **512** coupled to the processor **502**. Network interface **512** allows position determining system **500** to communicate with network **514**, to which one or more other computer systems are connected. Network interface **512** includes wireless network interfaces such as BLUETOOTH, WIFI, WIMAX, GPRS, or WCDMA; or wired network interface such as ETHERNET, USB, IEEE-1394, or asynchronous or synchronous communications links, such as RS485, CAN or HDLC. In some embodiments, the operations as described with respect to position determining system **500** are implemented in two or more position determining systems, and information such as position, first distance, second distance, vehicle speed, emitted wavelength and heading are exchanged between different position determining system **500** via network **514**.

Position determining system **500** also includes transponder ID database **516** coupled to the processor **502**. Transponder ID database **516** stores unique identification codes of transponders cross referenced with the position of the transponder along the guideway. Transponder ID database **516** allows position determining system **500** to determine the position of the vehicle based on the stored transponder position.

Position determining system **500** is configured to receive information related to the position from a transmitter/detector array, e.g., transmitter/detector array **200** (FIG. 2), or transmitter/detector array **300**. The information is transferred to processor **502** via bus **508** to determine a position of the vehicle along the guideway. The position is then stored in computer readable medium **504** as position parameter **518**. In some embodiments, processor **502** determines a heading of

the vehicle along the guideway. The position is then stored in computer readable medium **504** as heading parameter **528**. Position determining system **500** is configured to receive information related to the vehicle speed through I/O interface **510** or network interface **512**. The information is then stored in computer readable medium **504** as vehicle speed parameter **524**. Position determining system **500** is configured to receive information related to the first distance through I/O interface **510** or network interface **512**. The information is then stored in computer readable medium **504** as first distance parameter **520**. Position determining system **500** is configured to receive information related to the second distance through I/O interface **510** or network interface **512**. The information is then stored in computer readable medium **504** as second distance parameter **522**. Position determining system **500** is configured to receive information related to the emitted wavelength through I/O interface **510** or network interface **512**. The information is then stored in computer readable medium **504** as emitted wavelength parameter **526**.

During operation, processor **502** executes a set of instructions to determine a position of the vehicle along the guideway based on a comparison of the parameters stored in computer readable medium **504** and the stored unique identification codes of transponder ID database **516**.

FIG. 6 is a flow chart of a method **600** of determining a vehicle position in accordance with one or more embodiments. In operation **602**, a position determining system, e.g., position determining system **100**, position determining system **412** or position determining system **500**, detects a position of a first reflective positioning element, e.g., first reflective positioning element **406b** (FIG. 4). The positioning determining system detects the first reflective positioning element using a transmitter/detector array, e.g., transmitter/detector array **200** (FIG. 2), or transmitter/detector array **300** (FIG. 3). The position determining system detects the position of the vehicle when the first reflective positioning element is located an equal distance from each antenna of the transmitter/detector array.

In operation **604**, the position determining system detects a unique identification code of a transponder, e.g., transponder **404** (FIG. 4). Position determining system detects the unique identification code of the transponder based on a modulated reflection signal.

In optional operation **606**, the position determining system detects a second reflective positioning element, e.g., second reflective positioning element **406b**. The positioning determining system detects the second reflective positioning element using a transmitter/detector array, e.g., transmitter/detector array **200**. The position determining system detects the position of the vehicle when the second reflective positioning element is located an equal distance from each antenna of the transmitter/detector array. Operation **606** is omitted if determining a heading of the vehicle is not necessary or desired.

In operation **608**, the positioning determining system determines the position of the vehicle along the guideway. The position determining system determines the position of the vehicle by determining a position where the vehicle passed the first reflective positioning element, identifying the transponder closest to the first reflective positioning element and calculating the vehicle position based on a known distance along the guideway between the first reflective element and the known location of the transponder.

In optional operation **610**, the position determining system determines a heading of the vehicle along the guideway. The position determining system determines the heading of the vehicle by calculating a distance between the transponder and the second reflective positioning element and comparing the

11

calculated distance with known distances between the first reflective positioning element and the transponder and between the second reflective positioning element and the transponder. Operation 610 is omitted if determining a heading of the vehicle is not necessary or desired.

In operation 612, the position determining system transmits the vehicle position information to an external control, e.g., external control 108 (FIG. 1) or external control 408 (FIG. 4). The position determining system transmits the vehicle position information using a network interface, e.g., network interface 512. In some embodiments, the position determining system transmits the vehicle position information via an inductive loop communication system, a radio communication system, an optical communication system or other suitable communication means.

One of ordinary skill in the art would recognize the order of the above operations is adjustable. For example, in some embodiments, the unique identification code of the transponder is detected prior to detecting the first reflective positioning element. One of ordinary skill in the art would recognize additional operations are able to be added, in some embodiments.

One aspect of this description relates to a position determining system for a vehicle on a guideway. The position determining system includes an on-board controller configured to determine a position of the vehicle on the guideway. The position determining system further includes a transmitter/detector array configured to emit an interrogation signal and to receive reflection signals based on the emitted interrogation signal, wherein the transmitter/detector array is configured to communicate with the on-board controller. The transmitter/detector array includes a first antenna and a second antenna, the second antenna spaced from the first antenna in a direction of travel of the vehicle. The position determining system further includes a transponder identification database configured to store transponder information; the transponder identification database is configured to communicate with at least one of the on-board controller or the transmitter/detector array. The on-board controller is configured to determine the position of the vehicle along the guideway based on a modulated reflection signal received by the transmitter/detector array and a first non-modulated reflection signal received by the transmitter/detector array.

Another aspect of this description relates to a position determining arrangement for determining a position of a vehicle on a guideway. The position determining arrangement includes a position determining system on-board the vehicle, the position determining system configured to emit an interrogation signal, receive a modulated reflection signal having a unique identification code, receive a first non-modulated reflection signal and determine the position of the vehicle based on the modulated reflection signal and the first non-modulated reflection signal. The position determining system further includes a transponder configured to receive the interrogation signal and emit the modulated reflection signal having the unique identification code. The position determining system further includes a first reflective positioning element configured to receive the interrogation signal and to reflect the interrogation signal to form the first non-modulated reflection signal, the first reflective positioning element located a first known distance along the guideway from the transponder.

Still another aspect of this description relates to a method of determining a position of a vehicle on a guideway. The method includes detecting a position of the vehicle relative to a first reflective positioning element along the guideway. The method further includes detecting a unique identification code of a transponder along the guideway, wherein the tran-

12

spponder is located a first known distance along the guideway from the first reflective positioning element. The method further includes determining the position of the vehicle, using a position determining system, based on a modulated reflection signal received from the transponder, a first non-modulated reflection signal received from the first reflective positioning element, and the first known distance.

It will be readily seen by one of ordinary skill in the art that the disclosed embodiments fulfill one or more of the advantages set forth above. After reading the foregoing specification, one of ordinary skill will be able to affect various changes, substitutions of equivalents and various other embodiments as broadly disclosed herein. It is therefore intended that the protection granted hereon be limited only by the definition contained in the appended claims and equivalents thereof.

What is claimed is:

1. A position determining system for a vehicle on a guideway, the position determining system comprising:
 - an on-board controller configured to determine a position of the vehicle on the guideway;
 - a transmitter/detector array configured to emit an interrogation signal and to receive reflection signals based on the emitted interrogation signal, wherein the transmitter/detector array is configured to communicate with the on-board controller, the transmitter/detector array comprising:
 - a first antenna, and
 - a second antenna, the second antenna spaced from the first antenna in a direction of travel of the vehicle; and
 - a transponder identification database configured to store transponder information, the transponder identification database is configured to communicate with at least one of the on-board controller or the transmitter/detector array,
 - wherein the on-board controller is configured to determine the position of the vehicle along the guideway based on a modulated reflection signal received by the transmitter/detector array and a first non-modulated reflection signal received by the transmitter/detector array.
2. The position determining system of claim 1, wherein the transmitter/detector array further comprises:
 - a summing circuit configured to generate a sum signal based on the reflection signals received by first antenna and the second antenna; and
 - a phase comparator configured to determine a phase difference between the reflection signals.
3. The position determining system of claim 2, wherein the transmitter/detector further comprises a position detection unit configured to determine a position of the vehicle based on the determined phase difference and an intensity of the sum signal.
4. The position determining system of claim 1, wherein the on-board controller is configured to transmit the determined position of the vehicle to an external control system.
5. The position determining system of claim 1, wherein the on-board controller is configured to receive update information from an external control system, and update the transponder identification database based on the received update information.
6. The position determining system of claim 1, wherein the on-board controller is configured to determine a heading of the vehicle on the guideway based on the modulated reflection signal the first non-modulated reflection signal and a second non-modulated reflection signal received by the transmitter/detector array.

13

7. The position determining system of claim 6, wherein the on-board controller is configured to transmit the determined heading of the vehicle to an external control system.

8. A position determining arrangement for determining a position of a vehicle on a guideway, the position determining arrangement comprising:

a position determining system on-board the vehicle, the position determining system configured to emit an interrogation signal, receive a modulated reflection signal having a unique identification code, receive a first non-modulated reflection signal and determine the position of the vehicle based on the modulated reflection signal and the first non-modulated reflection signal;

a transponder configured to receive the interrogation signal and emit the modulated reflection signal having the unique identification code; and

a first reflective positioning element configured to receive the interrogation signal and to reflect the interrogation signal to form the first non-modulated reflection signal, the first reflective positioning element located a first known distance along the guideway from the transponder.

9. The position determining arrangement of claim 8, wherein the position determining system comprises:

an on-board controller configured to determine the position of the;

a transmitter/detector array configured to emit the interrogation signal and to receive the modulated reflection signal and the first non-modulated reflection signal, wherein the transmitter/detector array is configured to communicate with the on-board controller, the transmitter/detector array comprising:

a first antenna, and

a second antenna, the second antenna spaced from the first antenna in a direction of travel of the vehicle; and

a transponder identification database configured to store the unique identification code and a location of the transponder on the guideway, the transponder identification database is configured to communicate with at least one of the on-board controller or the transmitter/detector array.

10. The position determining arrangement of claim 9, wherein the transmitter/detector further comprises a position detection unit configured to determine a position of the vehicle based on a phase difference of reflection signals from the first antenna and the second antenna and an intensity of a sum of the reflection signals.

11. The position determining arrangement of claim 8, wherein the first reflective positioning element is half-wavelength reflector.

12. The position determining arrangement of claim 8, further comprising a second reflective positioning element configured to receive the interrogation signal and to reflect the interrogation signal to form a second non-modulated reflection signal, the second reflective positioning element located a second known distance along the guideway from the transponder.

13. The position determining arrangement of claim 12, wherein the first known distance is different from the second known distance.

14

14. The position determining arrangement of claim 12, wherein the position determining system is configured to determine a heading of the vehicle based on based on the modulated reflection signal, the second non-modulated reflection signal, the first known distance and the second known distance.

15. The position determining arrangement of claim 8, further comprising an external control system configured to communicate with the position determining system and the transponder, wherein the position determining system is configured to transmit the determined position to the external control system.

16. A position determining system, the position determining system comprising:

an on-board controller configured to determine a position of a vehicle on a guideway;

a transmitter/detector array configured to emit an interrogation signal and to receive reflection signals based on the emitted interrogation signal, wherein the transmitter/detector array is configured to communicate with the on-board controller, the transmitter/detector array comprising:

a first antenna, and

a second antenna, the second antenna spaced from the first antenna in at least a direction of travel of the vehicle; and

a transponder identification database configured to communicate with at least one of the on-board controller or the transmitter/detector array,

wherein the on-board controller is configured to determine the position of the vehicle along the guideway based on a modulated reflection signal received by the transmitter/detector array and a non-modulated reflection signal received by the transmitter/detector array.

17. The position determining system of claim 16, wherein the transmitter/detector array further comprises:

a summing circuit configured to generate a sum signal based on the reflection signals received by the first antenna and the second antenna; and

a phase comparator configured to determine a phase difference between the reflection signals.

18. The position determining system of claim 17, wherein the transmitter/detector further comprises a position detection unit configured to determine a position of the vehicle based on the determined phase difference and an intensity of the sum signal.

19. The position determining system of claim 16, wherein the transponder identification database has at least one unique identification code stored therein and wherein at least one of the received reflection signals comprises a unique identification code.

20. The position determining system of claim 16, wherein the on-board controller is configured to receive update information from an external control system, and update the transponder identification database based on the received update information.

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 9,227,641 B2
APPLICATION NO. : 13/886674
DATED : January 5, 2016
INVENTOR(S) : Carl Schweltnus et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Claim 9 as currently written:

9. The position determining arrangement of claim 8, wherein the position determining system comprises:

an on-board controller configured to determine the position of the;

Claim 9 should read as:

9. The position determining arrangement of claim 8, wherein the position determining system comprises:

an on-board controller configured to determine the position of the vehicle;

Signed and Sealed this
Twenty-third Day of August, 2016



Michelle K. Lee
Director of the United States Patent and Trademark Office