



US009237416B2

(12) **United States Patent**
Root et al.

(10) **Patent No.:** **US 9,237,416 B2**
(45) **Date of Patent:** **Jan. 12, 2016**

(54) **INTERACTIVE ADVISORY SYSTEM FOR PRIORITIZING CONTENT**

H04W 4/06; H04W 36/06; H04W 72/005;
H04W 80/12; H04W 4/20; H04W 4/021;
H04W 4/023; H04W 4/18; H04W 4/028

(71) Applicant: **LOCATOR IP, L.P.**, State College, PA (US)

USPC 455/456.1, 12.1, 3.01, 414.1, 434, 566,
455/404.1, 410, 456.2; 370/352, 329, 495,
370/230, 328, 338, 341, 395.4

(72) Inventors: **Steven A. Root**, Edmond, OK (US);
Michael R. Root, Edmond, OK (US)

See application file for complete search history.

(73) Assignee: **Locator IP, L.P.**, State College, PA (US)

(56) **References Cited**

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 88 days.

U.S. PATENT DOCUMENTS

4,015,366 A 4/1977 Hall, III
4,438,439 A 3/1984 Shreve

(Continued)

(21) Appl. No.: **14/095,427**

FOREIGN PATENT DOCUMENTS

(22) Filed: **Dec. 3, 2013**

AU 2001277030 B2 3/2006
AU 2006204945 A1 7/2006

(65) **Prior Publication Data**

(Continued)

US 2014/0099931 A1 Apr. 10, 2014

OTHER PUBLICATIONS

Related U.S. Application Data

Author Unknown, "The Nexterna Clearview Dispatch Module," 2005, 2 pp., Nexterna Limited, Burlington, Ontario, Canada.

(63) Continuation of application No. 11/710,346, filed on Feb. 23, 2007, now Pat. No. 8,634,814.

(Continued)

(51) **Int. Cl.**

H04W 24/00 (2009.01)
H04W 4/02 (2009.01)

(Continued)

Primary Examiner — Inder Mehra

(74) *Attorney, Agent, or Firm* — Blank Rome LLP

(52) **U.S. Cl.**

CPC **H04W 4/02** (2013.01); **H04L 67/18** (2013.01); **H04L 67/306** (2013.01); **H04L 67/322** (2013.01); **H04M 3/42348** (2013.01); **H04M 3/4872** (2013.01); **G01W 2203/00** (2013.01); **H04L 67/12** (2013.01); **H04M 3/42153** (2013.01); **H04M 3/42187** (2013.01);

(Continued)


(57) **ABSTRACT**

A method for passing content to at least one communicator device. The user of a communicator device registers with at least one service provider for delivering a plurality of different types of content to be passed to the at least one communicator device. A user defined priority is assigned to the at least one type of content. The user defined priority is stored on a computer readable medium. The different types of content are passed to the at least one communicator device based on the user defined priority.

(58) **Field of Classification Search**

CPC H04W 4/02; H04W 4/12; H04W 4/04;

22 Claims, 7 Drawing Sheets



(51)	Int. Cl.		5,848,378 A	12/1998	Shelton et al.
	<i>H04M 3/487</i>	(2006.01)	5,864,860 A	1/1999	Holmes
	<i>H04L 29/08</i>	(2006.01)	5,864,875 A	1/1999	Van Huben et al.
	<i>H04M 3/42</i>	(2006.01)	5,867,109 A	2/1999	Wiedeman
			5,867,110 A	2/1999	Naito et al.
(52)	U.S. Cl.		5,867,821 A	2/1999	Ballantyne et al.
	CPC . <i>H04M2203/205</i> (2013.01); <i>H04M 2203/2083</i>		5,880,958 A	3/1999	Helms et al.
	(2013.01); <i>H04M 2203/353</i> (2013.01)		5,884,267 A	3/1999	Goldenthal et al.
			5,884,309 A	3/1999	Vanechanos, Jr.
			5,892,917 A	4/1999	Myerson
(56)	References Cited		5,893,905 A	4/1999	Main et al.
	U.S. PATENT DOCUMENTS		5,913,201 A	6/1999	Kocur
			5,948,041 A	9/1999	Abo et al.
			5,950,161 A	9/1999	Kozuma et al.
			5,963,130 A	10/1999	Schlager et al.
			5,974,447 A	10/1999	Cannon et al.
			5,991,735 A	11/1999	Gerace
			5,999,126 A	12/1999	Ito
			5,999,882 A	12/1999	Simpson et al.
			6,000,285 A	12/1999	Leslie et al.
			6,014,090 A	1/2000	Rosen et al.
			6,018,699 A	1/2000	Baron, Sr. et al.
			6,021,432 A	2/2000	Sizer, II et al.
			6,023,223 A	2/2000	Baxter, Jr.
			6,023,765 A	2/2000	Kuhn
			6,028,514 A	2/2000	Lemelson et al.
			6,031,455 A	2/2000	Grube et al.
			6,040,781 A	3/2000	Murray
			6,043,756 A	3/2000	Bateman et al.
			6,047,236 A	4/2000	Hancock et al.
			6,047,327 A	4/2000	Tso et al.
			6,049,776 A	4/2000	Donnelly et al.
			6,070,142 A	5/2000	McDonough et al.
			6,070,143 A	5/2000	Barney et al.
			6,078,260 A	6/2000	Desch
			6,084,510 A	7/2000	Lemelson et al.
			6,088,679 A	7/2000	Barkley
			6,091,959 A	7/2000	Souissi et al.
			6,094,509 A	7/2000	Zheng et al.
			6,098,048 A	8/2000	Dashefsky et al.
			6,100,806 A	8/2000	Gaukel
			6,108,699 A	8/2000	Moiin
			6,112,074 A	8/2000	Pinder
			6,133,912 A	10/2000	Montero
			6,134,530 A	10/2000	Bunting et al.
			6,138,073 A	10/2000	Uchigaki
			6,148,261 A	11/2000	Obradovich et al.
			6,161,092 A	12/2000	Latshaw et al.
			6,167,255 A	12/2000	Kennedy, III et al.
			6,177,873 B1	1/2001	Cragun
			6,185,427 B1	2/2001	Krasner et al.
			6,199,045 B1	3/2001	Giniger et al.
			6,202,023 B1	3/2001	Hancock et al.
			6,209,026 B1	3/2001	Ran et al.
			6,212,393 B1	4/2001	Suarez et al.
			6,219,667 B1	4/2001	Lu et al.
			6,233,122 B1	5/2001	Summers
			6,240,369 B1	5/2001	Foust
			6,252,539 B1	6/2001	Phillips et al.
			6,252,544 B1	6/2001	Hoffberg
			6,266,612 B1	7/2001	Dussell et al.
			6,266,683 B1	7/2001	Yehuda et al.
			6,269,309 B1	7/2001	Buckingham
			6,275,774 B1	8/2001	Baron, Sr. et al.
			6,295,502 B1	9/2001	Hancock et al.
			6,297,766 B1	10/2001	Koeller
			6,329,904 B1	12/2001	Lamb
			6,333,980 B1	12/2001	Hollatz et al.
			6,334,133 B1	12/2001	Thompson et al.
			6,339,744 B1	1/2002	Hancock et al.
			6,339,747 B1	1/2002	Daly et al.
			6,347,216 B1	2/2002	Marko et al.
			6,351,218 B1	2/2002	Smith
			6,356,834 B2	3/2002	Hancock et al.
			6,360,172 B1	3/2002	Burfeind et al.
			6,363,411 B1	3/2002	Dugan et al.
			6,381,535 B1	4/2002	Durocher et al.
			6,405,134 B1	6/2002	Smith et al.
			6,408,337 B1	6/2002	Dietz et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,411,687 B1	6/2002	Bohacek et al.	6,985,929 B1	1/2006	Wilson et al.
6,411,809 B1	6/2002	Haakana et al.	6,988,037 B2	1/2006	Root et al.
6,418,371 B1	7/2002	Arnold	6,989,765 B2	1/2006	Gueziec
6,430,562 B1	8/2002	Kardos et al.	6,990,458 B2	1/2006	Harrison et al.
6,446,004 B1	9/2002	Cao et al.	7,010,501 B1	3/2006	Roslak et al.
6,456,852 B2	9/2002	Bar et al.	7,016,689 B2	3/2006	Clark et al.
6,462,665 B1	10/2002	Tarlton et al.	7,024,205 B1	4/2006	Hose
6,469,664 B1	10/2002	Michaelson et al.	7,024,310 B2	4/2006	Root et al.
6,473,692 B2	10/2002	Hancock et al.	7,031,724 B2	4/2006	Ross et al.
6,484,033 B2	11/2002	Murray	7,047,114 B1	5/2006	Rogers
6,490,525 B2	12/2002	Baron, Sr. et al.	7,058,510 B2	6/2006	Kelly et al.
6,496,776 B1	12/2002	Blumberg et al.	7,072,666 B1	7/2006	Kullman et al.
6,498,987 B1	12/2002	Kelly et al.	7,079,631 B1	7/2006	Kaufman
6,501,392 B2	12/2002	Gremmert et al.	7,080,018 B1	7/2006	Fox et al.
6,505,123 B1	1/2003	Root et al.	7,084,775 B1	8/2006	Smith
6,522,875 B1	2/2003	Dowling et al.	7,089,116 B2	8/2006	Smith
6,522,888 B1	2/2003	Garceran et al.	7,096,276 B2	8/2006	Bodin et al.
6,526,268 B1	2/2003	Marrah et al.	7,103,596 B2	9/2006	Abe et al.
6,531,218 B2	3/2003	Hoyt et al.	7,123,926 B2	10/2006	Himmelstein
6,542,825 B2	4/2003	Jones et al.	7,139,664 B2	11/2006	Kelly et al.
6,553,317 B1	4/2003	Lincoln et al.	7,171,325 B2	1/2007	Hsu et al.
6,560,456 B1	5/2003	Lohtia et al.	7,171,372 B2	1/2007	Daniel et al.
6,564,143 B1	5/2003	Alewine et al.	7,181,345 B2	2/2007	Rosenfeld et al.
6,571,279 B1	5/2003	Herz et al.	7,184,540 B2	2/2007	Dezonno et al.
6,578,005 B1	6/2003	Lesaint et al.	7,184,896 B1	2/2007	Benson
6,587,813 B1	7/2003	Whitt et al.	7,191,064 B1	3/2007	Myers et al.
6,587,831 B1	7/2003	O'Brien	7,191,065 B2	3/2007	Root et al.
6,587,851 B1	7/2003	Ditcharo et al.	7,197,308 B2	3/2007	Singhal et al.
6,590,529 B2	7/2003	Schwoegler	7,212,811 B2	5/2007	Dowling et al.
6,597,983 B2	7/2003	Hancock	7,212,829 B1	5/2007	Lau et al.
6,603,405 B2	8/2003	Smith	7,218,938 B1	5/2007	Lau et al.
6,609,062 B2	8/2003	Hancock	7,219,066 B2	5/2007	Parks et al.
6,611,687 B1	8/2003	Clark et al.	7,231,657 B2	6/2007	Honarvar et al.
6,633,900 B1	10/2003	Khalessi et al.	7,233,781 B2	6/2007	Hunter et al.
6,646,559 B2	11/2003	Smith	7,248,159 B2	7/2007	Smith
6,647,257 B2	11/2003	Owensby	7,254,481 B2	8/2007	Yamada et al.
6,650,902 B1	11/2003	Richton	7,254,588 B2	8/2007	Sung et al.
6,654,689 B1	11/2003	Kelly et al.	7,269,505 B2	9/2007	Zhao et al.
6,675,151 B1	1/2004	Thompson et al.	7,283,971 B1	10/2007	Levine et al.
6,677,894 B2	1/2004	Sheynblat et al.	7,284,000 B2	10/2007	Kuehr-McLaren et al.
6,680,675 B1	1/2004	Suzuki	7,284,033 B2	10/2007	Jhanji
6,684,136 B2	1/2004	Sinex	7,289,908 B2	10/2007	Root et al.
6,697,859 B1	2/2004	Takahashi	7,299,492 B2	11/2007	Thrash et al.
6,707,905 B2	3/2004	Lenard	7,315,782 B2	1/2008	Root et al.
6,731,940 B1	5/2004	Nagendran	7,327,271 B2	2/2008	Greenstein et al.
6,742,002 B2	5/2004	Arrowood	7,330,693 B1	2/2008	Goss
6,745,021 B1	6/2004	Stevens	7,366,522 B2	4/2008	Thomas
6,751,553 B2	6/2004	Young et al.	7,400,976 B2	7/2008	Young et al.
6,753,784 B1	6/2004	Sznaider et al.	7,403,925 B2	7/2008	Schlesinger et al.
6,754,585 B2	6/2004	Root et al.	7,406,382 B2	7/2008	Brulle-Drews
6,792,615 B1	9/2004	Rowe et al.	7,411,493 B2	8/2008	Smith
6,798,358 B2	9/2004	Joyce et al.	7,426,203 B1 *	9/2008	McNamara et al. 370/338
6,812,855 B1	11/2004	Sudou et al.	7,486,943 B2	2/2009	Choti et al.
6,816,878 B1	11/2004	Zimmers et al.	7,502,748 B1	3/2009	Baldwin et al.
6,823,263 B1	11/2004	Kelly et al.	7,557,730 B2	7/2009	Gueziec
6,823,315 B1	11/2004	Bucci et al.	7,567,575 B2	7/2009	Chen et al.
6,826,481 B2	11/2004	Root et al.	7,568,217 B1	7/2009	Prasad et al.
6,829,233 B1	12/2004	Gilboy	7,599,795 B1	10/2009	Blumberg et al.
6,829,334 B1	12/2004	Zirngibl et al.	7,602,285 B2	10/2009	Sznaider et al.
6,836,730 B2	12/2004	Root et al.	7,606,663 B2	10/2009	Neef et al.
6,838,998 B1	1/2005	Brown et al.	7,647,022 B2	1/2010	Ng et al.
6,845,324 B2	1/2005	Smith	7,650,633 B2	1/2010	Whitson
6,850,895 B2	2/2005	Brodersen et al.	7,668,832 B2	2/2010	Yeh et al.
6,853,915 B2	2/2005	Hubschneider et al.	7,706,523 B2	4/2010	Agusta
6,892,390 B1	5/2005	Lieberman et al.	7,720,606 B2	5/2010	Burfeind et al.
6,909,361 B2	6/2005	McCarthy et al.	7,860,376 B2	12/2010	Kudo et al.
6,909,903 B2	6/2005	Wang	7,890,124 B2	2/2011	Smith et al.
6,912,545 B1	6/2005	Lundy et al.	7,917,555 B2	3/2011	Gottumukkala et al.
6,941,126 B1	9/2005	Jordan, Jr.	8,229,467 B2	7/2012	Root et al.
6,944,447 B2	9/2005	Portman et al.	8,359,019 B2	1/2013	Ramer et al.
6,962,531 B2	11/2005	Pace et al.	8,483,651 B1	7/2013	Zamora et al.
6,973,384 B2	12/2005	Zhao et al.	2001/0029160 A1	10/2001	Aznal
6,975,942 B2	12/2005	Young et al.	2001/0030624 A1	10/2001	Schwoegler
6,980,909 B2	12/2005	Root et al.	2001/0042001 A1	11/2001	Goto et al.
6,985,813 B2	1/2006	Root et al.	2001/0049584 A1	12/2001	Jones et al.
			2001/0049636 A1	12/2001	Hudda et al.
			2001/0051888 A1	12/2001	Mayhak et al.
			2001/0053999 A1	12/2001	Feinberg
			2002/0000930 A1	1/2002	Crowson et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2002/0009353	A1	1/2002	Kelsey et al.	2006/0009155	A1	1/2006	Paalasmaa et al.	
2002/0010615	A1	1/2002	Jacobs	2006/0010467	A1*	1/2006	Segel	725/34
2002/0025964	A1	2/2002	Streuff et al.	2006/0022846	A1	2/2006	Tummala	
2002/0029160	A1	3/2002	Thompson et al.	2006/0028400	A1	2/2006	Lapstun et al.	
2002/0029272	A1	3/2002	Weller	2006/0046740	A1	3/2006	Johnson	
2002/0040313	A1	4/2002	Hunter et al.	2006/0111089	A1	5/2006	Winter et al.	
2002/0048283	A1*	4/2002	Lin	2006/0123053	A1	6/2006	Scannell	
2002/0049310	A1	4/2002	Tateishi et al.	2006/0142024	A1	6/2006	Thalanany et al.	
2002/0052674	A1	5/2002	Chang et al.	2006/0161469	A1	7/2006	Root et al.	
2002/0062451	A1	5/2002	Scheidt et al.	2006/0164259	A1	7/2006	Winkler et al.	
2002/0077876	A1	6/2002	O'Meara et al.	2006/0178140	A1	8/2006	Smith et al.	
2002/0091568	A1	7/2002	Kraft et al.	2006/0194595	A1	8/2006	Myllynen et al.	
2002/0095333	A1	7/2002	Jokinen et al.	2006/0200480	A1	9/2006	Harris et al.	
2002/0147642	A1	10/2002	Avallone et al.	2006/0265228	A1	11/2006	Ando	
2002/0160745	A1	10/2002	Wang	2006/0271560	A1	11/2006	Mitchell	
2002/0165732	A1	11/2002	Ezzeddine et al.	2006/0293065	A1	12/2006	Chew et al.	
2002/0173981	A1	11/2002	Stewart	2006/0294147	A1	12/2006	Root et al.	
2002/0175211	A1	11/2002	Dominquez et al.	2007/0005363	A1	1/2007	Cucerzan et al.	
2002/0183117	A1	12/2002	Takahashi et al.	2007/0021906	A1	1/2007	Yeh et al.	
2002/0194366	A1	12/2002	Bodin et al.	2007/0030973	A1	2/2007	Mikan	
2003/0004780	A1	1/2003	Smith et al.	2007/0061844	A1*	3/2007	Hakusui et al.	725/62
2003/0004802	A1	1/2003	Callegari	2007/0094071	A1	4/2007	Seraji et al.	
2003/0014297	A1	1/2003	Kaufman et al.	2007/0112511	A1	5/2007	Burfeind et al.	
2003/0028410	A1	2/2003	House et al.	2007/0127423	A1	6/2007	Ho	
2003/0055705	A1	3/2003	Kilpatrick	2007/0162320	A1	7/2007	Joshi et al.	
2003/0059158	A1	3/2003	Lacey	2007/0162328	A1	7/2007	Reich	
2003/0060211	A1	3/2003	Chern et al.	2007/0168131	A1	7/2007	Root et al.	
2003/0068974	A1	4/2003	Kanamaluru et al.	2007/0168524	A1	7/2007	Chao et al.	
2003/0100315	A1	5/2003	Rankin	2007/0180119	A1*	8/2007	Khivesara et al.	709/226
2003/0113014	A1	6/2003	Katoh	2007/0192159	A1	8/2007	Root et al.	
2003/0125963	A1	7/2003	Haken	2007/0197231	A1*	8/2007	Lin	455/456.1
2003/0125963	A1	7/2003	Haken	2007/0260531	A1	11/2007	Bezancon	
2003/0132298	A1	7/2003	Swartz et al.	2007/0260708	A1	11/2007	Beaton et al.	
2003/0149607	A1	8/2003	Ogasawara et al.	2007/0260741	A1	11/2007	Bezancon	
2003/0169367	A1	9/2003	Ranta	2007/0270165	A1	11/2007	Poosala	
2003/0171870	A1	9/2003	Gueziec	2007/0270166	A1	11/2007	Hampel et al.	
2003/0191765	A1	10/2003	Bargh et al.	2007/0270166	A1	11/2007	Hampel et al.	
2003/0191795	A1	10/2003	Bernardin et al.	2007/0293240	A1	12/2007	Drennan	
2003/0198337	A1	10/2003	Lenard	2008/0020702	A1*	1/2008	Jendbro et al.	455/3.01
2004/0002348	A1	1/2004	Fraccaroli	2008/0021645	A1	1/2008	Lau et al.	
2004/0010372	A1	1/2004	Schwoegler	2008/0064351	A1	3/2008	Landschaft et al.	
2004/0010591	A1	1/2004	Sinn et al.	2008/0070550	A1	3/2008	Hose	
2004/0023666	A1	2/2004	Moon et al.	2008/0082264	A1	4/2008	Hill et al.	
2004/0059996	A1	3/2004	Fasciano	2008/0084857	A1	4/2008	Gorti et al.	
2004/0093265	A1	5/2004	Ramchandani et al.	2008/0134043	A1	6/2008	Georgis et al.	
2004/0107126	A1	6/2004	Kataoka et al.	2008/0134258	A1*	6/2008	Goose et al.	725/91
2004/0110515	A1	6/2004	Blumberg et al.	2008/0140318	A1	6/2008	Breed	
2004/0161097	A1	8/2004	Henry	2008/0157990	A1	7/2008	Belzer et al.	
2004/0167813	A1	8/2004	Robertson et al.	2008/0160956	A1	7/2008	Jackson et al.	
2004/0172343	A1	9/2004	Allibhoy et al.	2008/0160966	A1	7/2008	McKiou et al.	
2004/0199655	A1	10/2004	Davies et al.	2008/0161012	A1	7/2008	Haran et al.	
2004/0203630	A1	10/2004	Wang	2008/0162036	A1	7/2008	Breed	
2004/0203854	A1*	10/2004	Nowak	2008/0183710	A1	7/2008	Serjeantson et al.	
2004/0221308	A1	11/2004	Cuttner et al.	2008/0189028	A1*	8/2008	Nair et al.	701/200
2004/0267595	A1	12/2004	Woodings et al.	2008/0207183	A1	8/2008	Root et al.	
2005/0003828	A1	1/2005	Sugar et al.	2008/0271120	A1	10/2008	Parkes et al.	
2005/0021666	A1	1/2005	Dinnage et al.	2008/0275759	A1	11/2008	Parkes et al.	
2005/0021806	A1	1/2005	Richardson et al.	2008/0294478	A1	11/2008	Joshi et al.	
2005/0021980	A1	1/2005	Kanai	2008/0313037	A1	12/2008	Root et al.	
2005/0027449	A1	2/2005	Marsh	2008/0319652	A1	12/2008	Moshfeghi	
2005/0040847	A1	2/2005	Unger et al.	2008/0319653	A1	12/2008	Moshfeghi	
2005/0050008	A1	3/2005	Root et al.	2009/0061903	A1	3/2009	Khokhar	
2005/0055374	A1	3/2005	Sato	2009/0073885	A1	3/2009	Jalil et al.	
2005/0096040	A1	5/2005	Haberman et al.	2009/0083150	A1	3/2009	Mashinsky	
2005/0096962	A1	5/2005	Narasimhan et al.	2009/0131080	A1	5/2009	Nadler et al.	
2005/0136917	A1	6/2005	Taylor	2009/0156161	A1	6/2009	Strahs	
2005/0136983	A1	6/2005	Agapi et al.	2009/0176511	A1	7/2009	Morrison	
2005/0174235	A1	8/2005	Davis et al.	2009/0176512	A1	7/2009	Morrison	
2005/0181803	A1	8/2005	Weaver et al.	2009/0177374	A1	7/2009	Liu	
2005/0192724	A1	9/2005	Hendry	2009/0209233	A1	8/2009	Morrison	
2005/0227709	A1	10/2005	Chang et al.	2009/0210441	A1	8/2009	Mercer et al.	
2005/0228873	A1	10/2005	Tapuska et al.	2009/0233575	A1	9/2009	Morrison	
2005/0240378	A1	10/2005	Smith et al.	2009/0233633	A1	9/2009	Morrison	
2005/0243784	A1	11/2005	Fitzgerald et al.	2009/0239511	A1	9/2009	Chen et al.	
2005/0245243	A1	11/2005	Zuniga	2009/0240428	A1	9/2009	Shahrestani	
2005/0251370	A1	11/2005	Li et al.	2009/0265099	A1	10/2009	Gottlieb	
				2009/0275348	A1	11/2009	Weinreich et al.	
				2009/0287587	A1	11/2009	Bloebaum et al.	
				2009/0305645	A1	12/2009	Watanabe	
				2010/0009657	A1	1/2010	Dingler et al.	

(56)

References Cited

U.S. PATENT DOCUMENTS

2010/0013629 A1 1/2010 Sznaider et al.
 2010/0036717 A1 2/2010 Trest
 2010/0042483 A1 2/2010 Hipsher
 2010/0069052 A1 3/2010 Ahomaki et al.
 2010/0069093 A1 3/2010 Morrison
 2013/0029693 A1 1/2013 Bradley, Jr. et al.
 2013/0165070 A1 6/2013 Hoffberg

FOREIGN PATENT DOCUMENTS

AU 2007207616 A1 7/2007
 AU 2006202473 A1 1/2010
 CA 2418268 A1 1/2002
 CA 2514868 A1 8/2004
 CA 2594001 A1 7/2006
 CN 1449615 A 10/2003
 CN 1659602 A 8/2005
 JP 08221694 A 8/1996
 JP 2000030148 A 1/2000
 JP 2001126170 A 5/2001
 JP 2002162475 A 6/2002
 JP 2002216021 A 8/2002
 JP 2002251484 A 9/2002
 JP 2002255465 A 9/2002
 JP 2003099350 A 4/2003
 JP 2003186900 A 7/2003
 JP 2003196284 A 7/2003
 JP 2003208367 A 7/2003
 JP 2003272078 A 9/2003
 JP 2003281694 A 10/2003
 JP 2003281694 A 10/2003
 JP 2003337874 A 11/2003
 JP 2004505501 A 2/2004
 JP 2004127044 A 4/2004
 JP 2004511836 A 4/2004
 JP 2004514333 A 5/2004
 JP 2004157863 A 6/2004
 JP 2004282610 A 10/2004
 JP 2005073147 A 3/2005
 JP 2005184065 A 7/2005
 JP 2005293255 A 10/2005
 JP 2006011617 A 1/2006
 JP 2006127144 A 5/2006
 JP 2007-265449 A 10/2007
 JP 2009524150 A 6/2009
 KR 20010100635 A 11/2001
 KR 20030075238 A 9/2003
 KR 20050080370 A 8/2005
 KR 20110012122 A 2/2011
 WO 9741654 A1 11/1997
 WO 9802824 A1 1/1998
 WO 9923591 A1 5/1999
 WO 0004730 A1 1/2000
 WO 0004734 A1 1/2000
 WO 0209353 A2 1/2001
 WO 0195140 A2 12/2001
 WO 0225964 A2 3/2002
 WO WO-02/28137 A1 4/2002
 WO 0249310 A2 6/2002
 WO 03069576 A1 8/2003

OTHER PUBLICATIONS

Author Unknown, "Dispenser Services Inc. Selects Web-Based Field Resource Management Solution From Nexterna," PR Newswire, Aug. 14, 2002, 2 pp., ProQuest LLC, New York, NY, USA.

Author Unknown, "Nexterna Announces Newest Release of Nexterna Clearview," PR Newswire, Sep. 26, 2002, 2 pp., ProQuest LLC, New York, NY, USA.

Author Unknown, "Nexterna.com Web Pages Nexterna Inc. 2002-2003," retrieved from Archive. Org on May 20, 2009, 31 pp.

Author Unknown, "Nexterna Optitrac," Nexterna Inc. 2002-2003, retrieved from Archive.Org on May 20, 2009, pp. 32-38.

Lesaint, et al., "Dynamic Workforce Management," AI for Network: Management Systems, Apr. 14, 1997, pp. 1-5, IEE, London, UK.
 Author Unknown, "TMC Labs Reviews—Maxima Advantage," Call Center CRM Solutions, Jan. 2000, 4 pp., vol. 18, No. 7, ABI/Inform Global.

Author Unknown, "MDSI Mobile Data Solution—Innovative and Effective Mobile Workforce Management," MDSI-Advantex.com, Feb. 1999, 19 pp.

Author Unknown, "MobileAria and WeatherBank Announce Partnership to Avert Delays, Increase Driver Productivity," Business Wire, Jun. 26, 2001, pp. 1-2, ProQuest LLC, New York, NY, USA.

Author Unknown, "Real-Time Wireless Workforce Solutions—With Mobile Centrex You Can . . .," Mobile Centrex Inc., retrieved from Archive.org on Oct. 15, 2008, 5 pp.

Partyka, et al., "On the Road to Service," ORMS Today, Aug. 2000, pp. 1-8, Lionheart Publishing, Inc., Marietta, GA, USA.

Rhinehart, "City Uses GIS to Monitor Snow-Fighting Fleet," The American City & County, Apr. 1999, p. 31, vol. 144, No. 4, ABI/Inform Global.

Author Unknown, "Vantive and MDSI to Provide Enterprise Wide Wireless Field Service Solution," PR Newswire, Oct. 26, 1998, pp. 1-3, ProQuest LLC, New York, NY, USA.

Weigel, et al., "Applying GIS and or Techniques to Solve Sears Technician-Dispatching and Home-Delivery Problems," Interfaces, Jan.-Feb. 1999, pp. 112-130, vol. 29, No. 1, Institute for Operations Research and Management Sciences.

Author Unknown, "iMedeon Announces Support for Microsoft Windows CE Devices for its Wireless, Web-Based Mobile Workforce Management Applications," Business Wire, Feb. 5, 2001, 2 pp., ProQuest LLC, New York, NY, USA.

Howard County Bureau of Highways, "Web-Enabled Snowplow Tracking System," Howard County, 1999, pp. 1-11.

Author Unknown, "Motorola iRadio(TM) System Hits the Road at Consumer Electronics Show 2001," PR Newswire, Jan. 4, 2001, pp. 1-2, ProQuest LLC, New York, NY, USA.

Le Comte, "Using Your Computer—Software Review," Weatherwise, Aug. 1991, pp. 48-51, vol. 44, No. 4.

Freedman, "Pinpoint Weather," Technology Review, Jun. 2003, pp. 52-58, vol. 106, No. 5, ABI/Inform Global.

Author Unknown, "Yahoo! and Weather.com Forge Multi-National Agreement to Provide Enhanced Weather Reports," Business Wire, Jan. 7, 2002, pp. 1-3, ProQuest LLC, New York, NY, USA.

Ohta, et al., "Real-World Community Platform: Mobile Multi-User Communication System," Multimedia Laboratories, NTT DoCoMo, Inc., 2000, pp. 601-606.

Lee, et al., "Statistical Analysis with Arcview GIS," 2001, pp. 1-192, John Wiley & Sons, Inc., New York, NY, USA.

Ohbuchi, et al., "Shape-Similarity Search of Three-Dimensional Models Using Parameterized Statistics," Oct. 9-11, 2002, in The Proceedings of the 10th Pacific Conference on Computer Graphics and Applications, pp. 265-274, IEEE.

Oh et al., "A Model for Role Administration Using Organization Structure", SACMAT '02, Jun. 3-4, 2002, pp. 155-162.

Botha, R.A. et al., "Separation of duties for access control enforcement in workflow environments", IBM Systems Journal, vol. 40, No. 3, 2001, pp. 666-682.

What is Access Management?, 2AB Inc., Jan. 2004, 6 pages.

Harris, Shon, Mike Myer's Certification Passport CISSP, McGraw-Hill, 2002, ISBN 0-07-222578-5, Chapter 2, 54 pages.

Park, Joon S. et al., "Role-Based Access Control on the Web", ACM Transactions on Information and System Security, vol. 4, No. 1, Feb. 2001, pp. 37-71.

McCormick, Vickie L., "Using HR Information systems for HIPAA role-based access compliance", Journal of Health Care Compliance, vol. 5, No. 2, Mar./Apr. 2003, pp. 31-32.

Langford, Jeff, "Implementing Least Privilege at your Enterprise", SANS Institute, Jul. 5, 2003, 21 pages.

Cuppens, Frederick et al., "Modeling Contexts in the Or-BAC Model", ACSAC'03, 2003, pp. 1-10.

Principles of Least Privilege definition, Wikipedia.org, Reprinted Jul. 11, 2012, 5 pages.

Boselly, III, Edward, et al., "Road Weather Information Systems vol. 2: Implementation Guide," 1993, pp. 1-82.

(56)

References Cited

OTHER PUBLICATIONS

Myers, "Personal Digital Radio Service," IBM Technical Disclosure Bulletin, vol. 38, No. 8, p. 315, Aug. 1995.

Visual Staff Scheduler Pro Version 3.0 User Guide Atlas Business Solutions, Inc. 1997.

Maxima Advantage Call Center CRM Solutions, vol. 18, No. 7, Jan. 2000.

MobileCentrex.com Web Pages, Mobile Centrex, Mar. 2003, Retrieved from Archive.org Oct. 15, 2008.

Dispatch definition, Retrieved from Wikipedia.org Oct. 15, 2008.

Feldman, W. and Feldman, P., "Making Cell Phones Indispensable for Techs," Contractor; Jul. 2004; 51, 7; ABI/Inform Global, pp. 40 and 54.

Timmins, Annmarie, Mobile Workers Sync Up, It Support News; Dec. 1999, pp. 28 and 30.

Bisio, R., Gavazzi, F., Malaboccia, F. and Sisto, L., "Effective Resource Scheduling in Work Force Management Context for Tele-

communication Work Centers," Centro Studi E. Laboratori Telecomunicazioni, Via G. Reiss Romoli, 274, 10148 Torino, Italy; pp. 1-5. Kruse, John, "Snow and Ice Go Hi-Tech." Mobile Radio Technology Magazine, Oct. 1, 1999.

Jing, Jin et al., "WHAM: Supporting Mobile Workforce and Applications in Workflow Environments RIDE 2000," Research Issues in Data Engineering, Feb. 2000.

Collins, J. E. and Sisley, E. M., 3M Company, "Automated Assignment and Scheduling of Service Personnel," AI in Corporate Service & Support; Apr. 1994, IEEE Expert; pp. 33-39.

Sakagumi et al., "ActiveTrace: Mobile Marketing Platform for Location and Behavior-Dependent Information Distribution and Analysis," Collection of Papers/Multimedia, Distribution, Collaboration and Mobile (DICOMO) Symposium, Jun. 27, 2001, vol. 2001, No. 7, pp. 501-506.

Murray R. Barrick et al., "The Big Five Personality Dimensions and Job Performance: A Meta-Analysis"; Personnel Psychology; Spring 1991; vol. 44; No. 1, pp. 1-26.

* cited by examiner










FIG. 1












Fig. 6




Fig. 7

INTERACTIVE ADVISORY SYSTEM FOR PRIORITIZING CONTENT

CROSS-REFERENCE TO RELATED APPLICATIONS

The present application is a Continuation of U.S. patent application Ser. No. 11/710,346, filed Feb. 23, 2007, the disclosure of which is hereby incorporated by reference in its entirety.

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT

Not applicable.

BACKGROUND OF THE INVENTION

During recent years, the demand for detailed information, such as for example, weather information, has risen sharply. Personal computers and communication devices have increased the demand for more information because of their power to gather, manipulate, transmit and receive data. As a result, specialized information and value-added services are in great demand. End users no longer desire to gather, manipulate and evaluate raw data. For instance, nowhere is this condition more apparent than with weather services across North America.

Years ago, radio and television broadcasters recognized an increasing demand for weather information from their audience, and thus increased the number of on-air weather segments as a means for increasing market ranking. Today, the demand for specific content in weather information has exceeded the ability of broadcasters to meet this demand. Virtually every facet of business and personal activities are continually influenced by the weather, good or bad.

In the United States as in most countries, a governmental agency (the National Weather Service in the United States), has the primary responsibility of generating weather products for the general public. These products, such as advisories, statements, and forecasts are generated and made available to third parties, such as broadcasters, newspapers, internet web sites, paging companies and others who, in turn, distribute them to the public. However, this chain of data custody is one way.

Today's lifestyles are fast-paced and sophisticated. Requests for detailed weather information for specific applications outnumber the governments' ability to process them. However, adhering to their mandated responsibility, the National Weather Service generates the general products for public consumption twice daily. This condition forces the public to interpret general and outdated advisories to meet their needs. Often, this interpretation is made erroneously. Even worse, these products are usually regional or national in scope, and may not apply to a particular location where various local activities are underway.

By way of example, weather warnings are broadcast by radio stations across the United States. These warnings identify certain weather impacts within a specified area. In most cases, the warning area includes one or more counties, covering dozens to hundreds of square miles. Most often, these threats (such as severe thunderstorms, tornadoes, etc.), only impact a very small zone within the warning area. These threats also move rapidly. As impacts approach specific zones, they are in fact, moving away from other zones, inside the total warning area. Essentially, the existing reporting system is insufficient to specifically identify and adequately

warn of personal risk. Furthermore, if the threat is imminent, the existing system cannot and does not provide preventive measures for each user near or at the threat. Thus, by default, distant or unaffected users are placed "on alert" unnecessarily when the threat may be moving away from their location.

Another common example further clarifies the problem. A family, excited to attend the championship softball game this upcoming weekend, closely monitors the local weather forecast. All week-long the forecast has advised fair to partly cloudy weather for game day. Early on game day, the forecast changes to partly cloudy, with a thirty percent chance for late afternoon showers. The family decides to attend the game, believing that the chances for rain are below their perceived risk, level. Unknown to the family at midday, some clusters of showers are intensifying and will place dangerous lightning over the game field. While the morning weather report was not completely inaccurate, the participants and spectators are exposed to risk. If later asked, it is likely the family members did not hear or remember the weather forecast. They also failed to link their limited knowledge of the weather to their own needs and risk exposure. They did not monitor changing weather events. Most likely, they had no ability to monitor developing risk at the game. Clearly, these people were forced to interpret outdated, limited information as applied to their specific application.

Therefore, a need exists for a system to automatically and continuously provide consumer customized reports, advisories, alerts, forecasts and warnings relevant to a consumer-defined level of need or dynamic spatial location. It is to such a system that the present invention is directed.

SUMMARY OF THE INVENTION

The present invention provides an interactive advisory system and method of delivering individualized, user-defined information based upon prioritization of the information typically assigned by the user or recipient of such information. More specifically, the present invention relates to a method for passing content to at least one communicator device. The method includes the step of selecting at least one service for delivering a plurality of different types of content to be passed to the at least one communicator device.

The method further includes the step of assigning a user-defined priority to at least one of the types of content and also assigning a user-defined priority to one or more communicator service providers. The method also includes the step of storing the user-defined priority on a computer readable medium and passing the different types of content to the communicator device based on the user-defined priority.

Other advantages and features of the present invention will become apparent to those skilled in the art when the following detailed description is read in view of the attached drawings and appended claims.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

FIG. 1 is a block diagram of an interactive weather advisory system constructed in accordance with the present invention.

FIG. 2 is a coordinate system illustrating a spatial location identifier and a spatial range identifier utilized by versions of the present invention.

FIG. 3 is a block diagram of an interactive advisory system constructed in accordance with the present invention.

3

FIG. 4 is a block diagram of an interactive weather advisory system constructed in accordance with the present invention.

FIG. 5 is a block diagram of an interactive advisory system constructed in accordance with the present invention.

FIG. 6 is a block diagram of another version of an interactive advisory system constructed in accordance with the present invention.

FIG. 7 is a block diagram of yet another embodiment of an interactive advisory system constructed in accordance with the present invention.

DETAILED DESCRIPTION OF THE INVENTION

Referring now to the drawings and more particularly to FIG. 1 shown therein in block diagram form, is one embodiment of the invention in the form of an interactive weather advisory system constructed in accordance with the present invention. The weather advisory system **8** is provided with a broadcast network **10** for selectively transmitting individualized weather output signals to remote communicator devices **11**. The broadcast network **10** includes a weather analysis unit **12**, a user input database **14**, a communicator location database **16**, and a communication network **20**. The weather analysis unit **12** receives real-time weather data from a weather information database **21**. The weather information database **21** can be located at the broadcast network **10**, or remotely from the broadcast network **10**. The weather analysis unit **12**, the user input database **14**, the communicator location database **16**, the weather information database **21**, and the communication network **20**, interrelate and communicate via signal paths **22**, **24**, **26**, **28**, **30** and **32**.

The user input database **14** permits a plurality of users to input data corresponding to the weather reports, advisories or forecasts such that individualized weather reports, advisories or prediction of events can be transmitted to each individual user. The user input database **14** contains data representative of at least one user-defined parameter correlated to each one of a plurality of users. In one version of the present invention, each of the user-defined parameters includes various information related to weather output signals, such as a spatial range identifier, a user profile, one or more weather content identifiers for identifying particular weather patterns, one or more time identifiers for identifying particular times or time intervals that a user may desire a weather product, a spatial location fixed or dynamic code, and a spatial location identifier for identifying particular spatial locations of interest to the user if the spatial location fixed or dynamic code indicates that the spatial location is to be fixed. The user profile in each of the user-defined parameters includes at least a user identifier code for identifying a particular communicator device **11** associated with a particular user.

For instance, the user identifier code could be a mobile telephone number identifying one of the communicator devices **11**, which in this instance could be a mobile telephone or a pager, for example. The weather content identifier could be a computer code to identify one or a variety of weather conditions or events such as tornadoes, thunderstorms, hail storms, lightning storms, showers, snow storms, blizzards, high winds, winds aloft, rapidly rising or rapidly falling barometric pressure or other such weather patterns or conditions. The time identifier desirably could be a computer code for identifying the particular time, times, or time intervals the user desires the interactive weather advisory system **8** to communicate weather data to the user or to monitor the real-time weather data for a particular time and/or date. The spatial location identifier **26** could be a computer code identifying a

4

particular predetermined spatial location such as, by way of example but not limitation, a longitude and latitude anywhere in the world, a town, a county, a township, address, zip code, altitude and combinations thereof.

As discussed above, the spatial location identifier identifies a particular spatial location anywhere in the world and/or altitude above sea level. The spatial range identifier identifies a particular spatial range surrounding the spatial location identifier. Each of the users can select the spatial location identifier and the spatial range identifier so as to receive weather forecasts and/or weather advisories or any other weather information for the spatial location identified by the spatial location identifier, and within the spatial range identified by the spatial range identifier.

For example, referring to FIG. 2, shown therein is a coordinate system illustrating four spatial location identifiers and four spatial range identifiers selected by different users of the present invention. That is, one of the users selects the spatial location identifier (X1, Y1, Z1), and the spatial range identifier (R1). Another one of the users selects the spatial location identifier (X2, Y2, Z2), and the spatial range identifier (R2).

The user who selected the spatial location identifier (X1, Y1, Z1) and the spatial range identifier R1 will receive weather products and advisories concerning the spatial range identified by the spatial location identifier (X1, Y1, Z1) and the spatial range identifier R1, as predefined in his user input database. The user who selected the spatial location identifier (X2, Y2, Z2) and the spatial range identifier R2 will receive weather products and advisories concerning the spatial range identified by the spatial location identifier (X2, Y2, Z2) and the spatial range identifier R2, and as predefined in the user input database **14**. Likewise, the users who selected the spatial location identifiers (X3, Y3, Z3) and (X4, Y4, Z4) and the spatial range identifiers R3 and R4 will receive weather products and advisories concerning the spatial range identified by the spatial location identifiers (X3, Y3, Z3), (X4, Y4, Z4) and the spatial range identifier R3, R4, and as predefined in the user input database **14**.

The magnitudes of the spatial range identifiers R1, R2, R3 and R4 can be different or the same. In addition, the magnitudes of the spatial range identifiers R1, R2, R3 and R4 can vary widely and are desirably selected by the users.

Particular users can input the user-defined parameters into the user input database **14** via any suitable method. For example, the user input database **14** is desirably configured to acquire its data from a variety of optional sources preferably chosen by the user, such as verbally through a telephone customer service network, a mobile phone network equipped with wireless application protocol technology, email, a personal digital assistant, a laptop computer, or an interactive web site. Furthermore, users could mail the user-defined parameters to the broadcast network **10**, and an individual at the broadcast network **10** could input the user-defined parameters directly into the user input database **14** via a keyboard or other similar input device. In one embodiment, the user inputs the selected information into the user input database **14** via the user's communicator device **11**.

The weather information database **21** contains real-time weather data for at least the spatial locations contained in the communicator location database **16** and the spatial locations identified by the spatial location identifier in the user input database **14**. The weather analysis unit **12** generates predictions of all weather events based on the real-time weather data. The weather information database **21** desirably receives its real-time weather data from at least one of a plurality of possible resources such as, by way of example but not limitation, government weather information resources, privately

operated weather information resources, and other various meteorological resources. The real-time weather data could also be either input directly at the physical location of the weather information database **21** or input via a mobile phone network, a mobile phone network with wireless application protocol, the Internet, aircraft communication systems, email, a personal digital assistant, a laptop computer, regular computer, or other wireless devices.

Alternatively, the weather information database **21** may contain weather prediction data and/or weather forecast data for at least the spatial locations contained in the communicator location database **16** and the spatial locations identified by the spatial location identifier in the user input database **14**. In this embodiment, the weather analysis unit **12** generates predictions of all weather events based on the real-time weather data.

The communicator location database **16** is an optional feature of the present invention, and is enabled via the signal path **22** when the user requests real-time weather advisories or prediction of events at the dynamic spatial location of the user's communicator device **11**. The communicator location database **16** is continuously updated such that the communicator location database **16** contains real-time data indicative of the spatial locations of the communicator devices **11**. In one embodiment, the user identifier code in the user's profile is transmitted to the communicator location database **16** via the signal path **22**. The communicator location database **16** desirably receives data from the communicator devices **11** identified by the user identifier codes via at least one of a variety of possible resources such as a mobile phone network, a mobile phone network equipped with the wireless application protocol technology, global positioning satellite technology, the Internet, loran technology, radar technology, transponder technology or any other type of technology capable of tracking the spatial location of a communicator device **11** and communicating the location of such communicator device **11** to the communicator location database **16** of the broadcast network **10**. Preferably, the communicator location database **16** is continuously and automatically updated as to the location of each of the communicator devices **11**, such as by the wireless application protocol technology. Alternatively, the communicator location database **16** may be updated upon demand of a user as to the location of each of the communicator devices **11**, such as by the wireless application protocol technology.

The communication network **20** can be, by way of example but not limitation, a mobile phone network, a mobile phone network with wireless application protocol technology, the Internet, a facsimile network, a satellite network (one or two-way), a RF radio network, or any other means of transmitting information from a source to an end user.

The communicator devices **11** can be bidirectional or unidirectional communicator devices. The communicator devices **11** can be, by way of example but not limitation, a portable device, such as a mobile telephone, a smart phone, a pager, a laptop computer or a personal digital assistant, or any other electronic device capable of receiving weather information data. Furthermore, the communicator device **11** can be incorporated into an object that is utilized or accessible by the user, such as a helmet, an automobile, or an airplane, for example. While only three communicator devices **11** are represented in FIG. **1** for purposes of illustration, the interactive weather advisory system **8** contemplates the utilization of a large number of communicator devices **11**.

The weather analysis unit **12** receives the data in the user input database **14**, the communicator location database **16**, and the weather information database **21** from the signal

paths **24**, **26**, and **28**. The weather analysis unit **12** can be, by way of example but not limitation, a computer desirably programmed to automatically and continuously compare the data in the user input database **14**, communicator location database **16**, and weather information database **21** so as to generate an individualized weather output signal including weather information within the spatial range identified by the spatial range identifier for each user-defined parameter in the user input database **14**. The weather output signals are transmitted to the communication network **20** via the signal path **32**.

The weather analysis unit **12** gathers the real-time weather data from the weather information database **21**. The term "real-time weather data", as used herein, refers to weather data which is continually updated so as to indicate current or near current information. In some instances, the "real-time weather data" may be delayed by relatively small increments of five minutes, 15 minutes, or 30 minutes, for example. In other instances, the "real-time weather data" can be provided with substantially no delay. It is expected that the increments will become smaller as communication networks and weather related technology become faster. The weather analysis unit **12** generates predictions of all weather related events and compares past and current events contained in the weather information database **21** (such as future position, strength, trajectory, etc.), to construct a four-dimensional database. Three dimensions of the database define a physical location on or above the earth's surface (the spatial location identifier (X1, Y1, Z1). The fourth dimension is time—past, present or future (identified as T1, T2, T3, T4). By employing high speed computer processors in real-time, the weather analysis unit **12** compares all events (past, current and predicted), at specific positions (X1, Y1, Z1, T1) with identical user supplied data (the user input database—X1, Y1, Z1, R1, T1), and identifies any matches (weather output signals) to the user through the communication network **20** and communication devices **11**.

The communication network **20** receives the weather output signals and the user identification codes via the signal paths **32** and **30**. In response thereto, the communication network **20** transmits the individualized weather output signals to the communicator devices **11** associated with the user identification codes via the signal paths **34a**, **34b** and **34c**, such that each user receives the individualized weather information that was requested.

The signal paths **34a**, **34b** and **34c** refer to any suitable communication link which permits electronic communications. For example, the signal paths **34a**, **34b** and **34c** can be point-to-point shared and dedicated communications, infra red links, microwave links, telephone links, CAN links, satellite and radio links and fiber optic links.

Various combinations of weather information can be incorporated into the user input database **14** so as to provide the user with selected and specific weather information. For example, a user traveling in his automobile may wish to be informed by the interactive weather advisory system **8** concerning all hailstorms for an area within a 2.5 mile radius of his vehicle as he is traveling from his point of origin to his destination. The user, for example, through his smart phone (communicator device **11**) in his vehicle working in conjunction with a mobile phone network (communication network **20**) with wireless application protocol, inputs selected information into the user input database **14**; namely, the user's smart phone number (user identifier code), hail (weather content identifier), 2.5 mile radius (spatial range identifier **24**)

and spatial location dynamic (spatial location of the user's smart phone is then automatically and continuously monitored), and the like.

The interactive weather advisory system **8** then monitors weather information and predictions of events in the weather analysis unit **12**, and transmits the individualized weather output signal to the user's smart phone if a hailstorm is detected or is highly likely to form within a 2.5 mile radius of the vehicle along the vehicle's path of travel, for the duration of travel.

The individualized weather output signal can be an audio, video, textural and/or graphical data signal. For example, the individualized weather output signal can be a .WAV file or other suitable file containing an animated representation of a real or hypothetical individual speaking an individualized message to the user. In the example given above, the individualized message may be that the hailstorm is 2.5 miles ahead of the vehicle and thus, the user should consider stopping for a short period of time so as to avoid the hailstorm. Alternatively, the individualized message may be that the hailstorm is 2.5 miles ahead of the vehicle and thus, the user should consider stopping until further notified by another individualized weather output signal so as to avoid the hailstorm. In other words, the weather analysis unit **12** may transmit another individualized weather output signal to the user via the communication network **20** and the communicator devices **11** notifying the user that the weather condition identified by the weather content identifier has passed or is beyond the spatial location identified by the spatial range identifier.

As another example, a user may desire to be informed of all real-time weather data and predictions of events within a particular spatial range of a particular dynamic spatial location. For instance, the user may be interested in whether his aircraft is at risk of icing as he flies from Oklahoma City to Tulsa, Okla. To provide a suitable level of comfort and safety, the user may wish to be informed of icing conditions within 10 miles of the dynamic spatial location of his aircraft. The user, for example, through his smart phone or other suitable avionic device (communicator device **11**) in his aircraft working in conjunction with a mobile phone network (communication network **20**) with wireless application protocol, inputs selected information into the user input database **14**; namely, the user's smart phone number (user identifier code), icing (weather content identifier), 10 mile radius (spatial range identifier **24**), and the spatial location dynamic. The spatial location of the user's smart phone or other suitable avionic device is then automatically and continuously monitored as the aircraft traverses through time and space from (X1, Y1, Z1, T1) to (X4, Y4, Z4, T4). The interactive weather analysis unit **12** then monitors the real-time weather data in the weather information database **21** and the predicted events in the weather analysis unit **12** so as to transmit the individualized weather output signal to the user's smart phone or other avionic device identifying, if icing is detected or is highly likely to form relevant to a 10 mile radius of the aircraft.

As yet another example, perhaps the user is only interested in a particular weather pattern at a particular fixed spatial location and within a particular spatial range irrespective of the immediate location of the communicator device **11**. To accomplish this user's request, the broadcast network **10** does not utilize the communicator location database **16**. The user inputs selected information into the user input database **14**, namely the user's phone number (user identifier code), the code for the particular weather pattern in which the user is interested (weather content identifier), the spatial range around the spatial location in which the user is interested (spatial range identifier), and the spatial location in which the

user is interested (spatial location identifier). The weather analysis unit **12** then monitors the real-time weather data in the weather information database **21** and the predicted events in the weather analysis unit **12** so as to transmit the individualized weather information concerning the weather pattern in the spatial location and range requested by the user.

As a further example, perhaps the user is only interested in a particular weather condition at the spatial location and within a particular spatial range at a particular time. The user inputs selected information into the user input database **14**, namely, the user's phone number (user identifier code), the code for the particular weather pattern in which the user is interested (weather content identifier), the spatial range around the spatial location in which the user is interested (spatial range identifier and the spatial location in which the user is interested spatial location identifier) and the time and date (time identifier) that the user wishes to be informed of the weather conditions at the spatial location of interest. In response thereto, the weather analysis unit **12** monitors the real time weather data from the weather information database **21** for the spatial location and range identified by the spatial range identifier and spatial location identifier to determine the probability of the particular weather pattern occurring at the time identified by the time identifier. The weather analysis unit **12** sends, via the signal path **32**, the individualized weather output signal to the communication network **20**. The communication network **20** receives the user identifier code, via signal path **30**, from the user input database **14** and transmits the weather output signal received from the weather analysis unit **12** to the particular communicator device **11** identified by the user identifier code. Thus, the user receives the individualized weather information concerning the spatial location, spatial range and time requested by the user.

The signal paths **22**, **24**, **26**, **28**, **30** and **32** can be logical and/or physical links between various software and/or hardware utilized to implement the present invention. It should be understood that each of the signal paths **22**, **24**, **26**, **28**, **30** and **32** are shown and described separately herein for the sole purpose of clearly illustrating the information and logic being communicated between the individual components of the present invention. In operation, the signal paths may not be separate signal paths but may be a single signal path. In addition, the various information does not necessarily have to flow between the components of the present invention in the manner shown in FIG. **1**. For example, although FIG. **1** illustrates the user identifier code being transmitted directly from the user input database **14** to the communication network **20** via the signal path **30**, the user identifier code can be communicated to the weather analysis unit **12** via the signal path **24** and then communicated to the communication network **20** via the signal path **32**.

It should be understood that although the user has been described as manually inputting the user identifier code into the user input database **14**, the user identifier code could be automatically input into the user input database **14** by the communicator device **11**.

Once the user-defined parameters have been input into the user input database **14**, the user-defined parameters can be analyzed by the weather analysis unit **12** along with weather content identifiers for purposes of targeted marketing. A plurality of vendors **36** can be provided access to the weather analysis unit **12** of the broadcast network **10** via a plurality of signal paths **38a**, **38b**, and **38c**. The vendors **36** can independently input search information into the weather analysis unit **12** for compiling a data set of information which is useful to the vendors **36**.

For example, a particular vendor **36a**, who is in the business of selling snow blowers, may input a weather content identifier and time identifier into the weather analysis unit **12** so as to request a list of all spatial locations in the United States which are expected to receive at least 10 inches of snow in the next week. The weather analysis unit **12** would then compile the data set of all spatial locations in the United States which is expected to receive at least 10 inches of snow in the next week based on at least one weather content identifier, the time identifier, and the real-time weather data stored in the weather information database **21**. The data set is then output to the vendor **36a**. Based on the data set, the vendor **36a** may send advertisements or additional snow blowers to the areas identified in the data set.

As another example, the particular vendor **36a**, who is in the business of selling snow blowers, may input a weather content identifier and time identifier into the weather analysis unit **12** so as to request a list of all user profiles identifying users who resided in spatial locations in the United States which are expected to receive at least 10 inches of snow in the next week. The weather analysis unit **12** would then compile the data set of all spatial locations in United States which is expected to receive at least 10 inches of snow in the next week based on at least one weather content identifier, the time identifier, the user profiles, and the real-time weather data stored in the weather information database **21**. The data set is then output to the vendor **36a**. Based on the data set, the vendor **36a** may send advertisements to the users who are identified in the data set.

It is envisioned that users will subscribe to the services provided by the broadcast network **10**. In this regard, the broadcast network **10** may or may not charge a service fee to the users. In addition, some services may be provided by the broadcast network **10** for one charge and additional services may be provided at an enhanced charge.

To save processing power, the weather analysis unit **12** may periodically determine which communicator devices **11** are turned off or out of range. Once this has been determined, the weather analysis unit **12** would then not generate any individualized weather output signals for the communicator devices **11** which are turned off or out of range. Once a particular one of the communicator devices **11** is turned on or comes within range, the weather analysis unit **12** would then attempt to generate individualized weather output signals for such communicator devices **11**. In other words, to save processing power the weather analysis unit **12** may only generate individualized weather output signals for the communicator devices **11** which are active and within range.

The weather analysis unit **12** can be located at the broadcast network **10**. Alternatively, the weather analysis unit **12** can be separate from the remainder of the broadcast network **10** and provided as a service to the broadcast network **10**.

In one preferred embodiment, rather than or in addition to the user providing user-defined parameters to the user input database **14**, the user input database **14** is programmed to provide a plurality of pre-defined user profiles with each of the pre-defined user profiles directed to an activity designated by the user optionally including data and time of the activity. The activity can be a business, personal or recreational need. For example, the business need can be any work dependent upon or impacted by weather conditions to carry out a desired activity, such as, but not limited to a rancher, contractor, farmer, or painter. The personal need can be any activity positively or negatively impacted by weather conditions, such as but not limited to, duties performed by a homeowner, such as mowing the lawn, painting the house, trimming trees, or the like. The recreational need can be any recreational or other

outdoor activity dependent upon weather conditions, such as but not limited to golfing, cycling, boating, hiking, fishing, or snow skiing.

In this case, the user selects or provides an activity or category to the user input database **14**. The user input database **14** retrieves pre-defined information concerning such activity or category and stores or links such pre-defined information with the user's user profile. The broadcast network **10** and/or weather analysis unit **12** then functions as set forth above to provide weather alerts or other information concerning the information contained in the user's user profile.

For example, a user may plan on golfing on a particular weekend during the hours of 9:00 a.m. to 4:00 p.m. In this case, the user would select the pre-defined user profile for "golfing", and the time frame of such planned activity. The location of planned activity can also be entered into the user input database **14**, or the location of the communicator device **11** can be monitored by the communicator location database **16**. The information contained in the pre-defined user profile is input into the user input database **14** and output weather alerts and forecasts are then generated as discussed above.

The pre-defined user profiles are determined by member(s) of the broadcast network **10** and/or weather analysis unit **12**, who identify weather conditions which are typically suitable and/or adverse to each designated activity. Thus, for example, a pre-defined user profile for "golfing" will contain data such as wind conditions, lightning, rain, temperature and other conditions which will positively or negatively impact a golfing activity. The data in the pre-defined user profile can be determined either before or after selection of the activity by the user.

If desired by the user, the broadcast network **10** and/or weather analysis unit **12** can assume the responsibility for generating the appropriate size of the spatial range identifier (as in the case with the user profile, or pre-defined user profile). Alternatively, the spatial range identifier can be determined by the nature of the weather event. In the latter case, member(s) of the broadcast network **10** and/or weather analysis unit **12** would determine an "area of concern" around each weather event that would or could occur and the communication network **20** would then send notifications to any user or communicator device **11** that may come into contact with the area of concern.

For example, a tornado may be 1/2 mile wide and the broadcast network **10** and/or weather analysis unit **12** would, based upon its experience, knowledge and/or abilities, determine that the area of concern would be 1 1/2 miles wide and 8 miles long—moving northeasterly. Any user contained within the user input database **14** would be notified, as discussed above, if the user's location comes into contact with the "area of concern".

Other Uses of this System

Shown in FIGS. 3-4, are advisory systems **8a** and **8b** which can be used for delivering other types of information or for more accurately predicting weather related events. The advisory systems **8a** and **8b** are similar in construction and function to the weather advisory system **8**, except as described below. For purposes of clarity, similar components have been provided with the same numeric prefix, and different alphabetic suffix.

The advisory system **8a** is provided with a broadcast network **10a**. In one embodiment, the broadcast network **10a** is used for transmitting individualized real-time work assignments from, for example, an employer to an employee. The broadcast network **10a** is provided with an analysis unit **12a**, a communicator location database **16a**, and communicator devices **11a** and **11b**. The communicator device **11a** is

11

referred to herein as an “employer communicator device”, and the communicator device **11b** is referred to herein as an “employee communicator device.” The communicator location database **16a** is continuously updated to contain real-time data indicative of the spatial locations of the communicator devices **11a** and **11b**. In a similar manner as described above, the analysis unit **12a** makes comparisons between user profiles (as represented by a box **80a**), dynamic locations stored in the communicator location database **16a**, fixed locations as represented by a box **82a** and job assignments entered into the analysis unit **12a** from one of the employer communicator devices **11a**. The system **8a** may be further described as an employer system **40a** and an employee system **42a** to delineate the types of information being conveyed within the system **8a**.

For example, an employer uses the employer communicator device **11a** to input employee information and/or criteria into an employee’s user profile such as, for example, job location, job schedule, skill set requirements, personality traits, and other criteria as represented by a box **84a**. Further, the employer inputs work or job assignment criteria into the analysis unit **12a** such as, for example, job location, job schedule, skill set requirements, personality traits, and other criteria. The employer inputs the above criteria into one of the employer communicator devices **11a** which may be, for example, a computer, a personal digital assistant (PDA), a cellular phone, a combination cellular phone/PDA, or any other device which may then transmit the employee information and/or job assignment criteria to the analysis unit **12a**. The analysis unit **12a** may be, for example, a computer or a web server. The analysis unit **12a** matches the employee user profile criteria with the work assignment criteria to generate a data set of at least one individualized work assignment.

The individualized real-time work assignment is transmitted to one of the employee communicator devices **11b** based upon the matching of the work assignment criteria with the employee user-profile. The data set can be transmitted to the employer communicator device **11a** such that the employer can review the data set to assign the work assignment to a particular one of the employees, or alternatively, the analysis unit **12a** can automatically assign the work assignment to a particular one of the employees and thereby transmit the work assignment to the employee’s communicator device **11b** without any intervention by the employer. The employee’s communicator device **11b** may be, for example, a PDA, a cellular phone, a combination cellular phone/PDA, a pager, or any other device in which the analysis unit **12a** or the employer may communicate information to the employee.

The user profile for each of the employees includes information relating to the employee’s traits such as, for example, personality, sales style, dress, skill set, location, schedule, or any other quality or trait relating to the particular employee. Further, the user profile is preferably accessible by both the employer communicator device **11a** and the employee communicator device **11b**. However, it is preferred that the employer communicator device **11a** have access to the entire user profile, while the employee communicator device **11b** only have access to a subset of the user profile. Thus, the user profile accessible by the employer system **40a** may differ from the user profile accessible by the employee system **42a**.

For example, the user profile accessible by the employer system **40a** may include traits related to a particular employee that remain hidden or unknown to the employee. For instance, the employee may have access to information stored in his user profile such as location, schedule, skill set, and other criteria as represented by a box **86a** and may be provided access to his user-profile to update information as needed. In

12

addition to the above-mentioned employee-accessible information, the employer may have access to the employee user profile to input and access employee traits such as personality, sales style, dress, and skill set and may be provided access to update this information as needed.

In another embodiment, the system **8a** is used to deliver goods based upon real-time location of a carrier of the goods. More specifically, the system **8a** can be used to accommodate purchasers of products ordered online in order to quickly and efficiently deliver goods to the purchaser’s specified location.

The analysis unit **12a** is loaded with employee user profiles and locations. The analysis unit **12a** identifies delivery persons (employees) located near a purchaser’s location. Part of the employee’s user profile can include an inventory of the goods on the employee’s delivery truck. The employee need not know what inventory is located on his delivery truck, but only his delivery destination.

For example, a purchaser may order fresh produce online. The employer may input the purchaser’s order (work assignment) into the employer communicator device **11a** (which inputs the work assignment into the analysis unit **12a**) so that the analysis unit **12a** may determine which delivery person may efficiently deliver the specified goods to the purchaser. Also, by ordering online, the purchaser may send his order directly to the analysis unit **12a** such that the analysis unit **12a** automatically determines the appropriate delivery person to deliver goods to the purchaser and sends the assignment to the delivery person via the employee’s communicator device **11b**. Further, the employer updates the user profile to track and monitor the precise inventory located on the employee’s delivery truck, the inventory being delivered, and any inventory that may be stolen from the delivery truck.

In yet another embodiment, the system **8a** can be used for sending salesmen to the field for soliciting new clients. For example, a company may receive an inquiry from a sales lead. Information about the lead is entered into the analysis unit **12a** as a job assignment from the employer communicator device **11a**. The analysis unit **12a** then determines the appropriate salesman to send to the lead based on information stored in the salesman’s user-profile. The salesman’s user-profile may include information such as salesman location, personality traits, dress style or other attributes used to determine which salesman may be appropriate to send to the lead.

Shown in FIG. **4** is another advisory system **8b** constructed in accordance with the present invention. The advisory system **8b** includes a broadcast network **10b**. The broadcast network **10b** is similar in construction and function as the broadcast network **10** discussed above, except that the broadcast network **10b** includes individualized sensor networks **48a** having weather and environmental sensors **48b** which are specifically associated with geographic areas associated with predetermined users.

For example, the weather and environmental data collection sites are tremendously sparse in growing areas of the world. In the state of Iowa, only a minimal number of National Weather Service data collection points exist. The scarcity of weather data hinders farmers because a dense grid of weather data points is non-existent in order for farmers to make critical decisions about their crops. For example, how do you know what 160-acre tract of land to fertilize when soil temperature data, crop moisture data, and chance of precipitation data is unavailable?

The sensor network **48a** includes temporary or permanent data collection sensors **48b** which may be installed, for example, on a 10 acre to 40 acre grid on the land of a subscriber or user of the system **8b**. Each sensor **48b** may have a unique spatial range associated with it such as, for example, a

five mile or twenty mile radius. The spatial range associated with each sensor **48b** can be selected by the user and specified as a result of the sensor **48b** type and purpose as well as the density of the sensor network **48a**. For example, if the user is interested in soil moisture in order to schedule a fertilizer treatment, the spatial range associated with the chosen sensor **48b** may be set, for example, at 375 feet. In another example, the user may be interested in soil temperature for placing seeds in the ground and the desired spatial range associated with the chosen sensor **48b** may be, for example, 2,000 feet. The user of the system **8b** includes a user profile as discussed above, which is supplemented with information regarding the sensors **48b** associated with the user, e.g., installed on or near the user's land. The sensors **48b** transmit site-specific, individualized information to the weather analysis unit **12b** so that more detailed information can be used by the weather analysis unit **12b** in generating the site-specific weather information for the user.

The sensors **48b** can be any type of sensor which generates information usable for forecasting weather, transmitting current weather conditions, transmitting current environmental conditions, and/or forecasting environmental conditions. For example, the sensors **48b** can be used to sample or record such parameters as, but not limited to, air temperature, humidity, precipitation, solar radiation, wind speed and direction, soil temperature, soil moisture, and/or chemical constituents in the soil.

For example, a user may enter into his user profile types of information the user would like the sensor network **48a** to monitor such as, for example, temperature, moisture and/or soil conditions. The weather analysis unit **12b** receives the sensor data from the sensor network **48a** and transmits information to the user via the user's communicator device **50b** based on information entered into his user profile. The user may also choose a specific sensor for monitoring a specific area at any given time by modifying his user profile.

Further, the system **8b** may be used to transmit real-time road condition information to the weather analysis unit **12b** to enhance the weather information transmitted to the users of the system **8b**. Although the sensors **48b** can include their own power source such as a battery or solar power source, the sensors **48b** are preferably positioned on a device which has its own electrical power source. For example, a temporary or permanent sensor or sensors **48b** may be placed in various locations along a roadway such as on a vehicle, on or beside the roadway, on a billboard, gas pump, cell phone tower or sign alongside the roadway or railway, on a delivery vehicle(s) such as, for example, UPS and/or FedEx, or on the streetlights. If the sensor **48b** is placed on the roadway, it may be placed in the concrete or asphalt. If placed beside the roadway, the sensor **48b** may be placed in, for example, a ditch. The sensor(s) **48b** may detect, for example, moisture, temperature or any other weather or environmental condition associated with the roadway, sign alongside the roadway, on streetlights, or on delivery vehicles such as, for example, UPS and/or FedEx, or on railway cars. Alternatively, the sensor(s) **48b** may be used to detect traffic conditions or any other condition associated with a particular roadway or railway.

For example, each sensor **48b** may be placed 100 feet away from the nearest sensor in order to create the sensor network **48a** for determining conditions for a specified area along a roadway or railway. Further, the sensor(s) **48b** may be placed on various cellular phone towers so that users of a particular cellular phone system associated with the tower may access various conditions using the system **8b**.

Each of the weather sensors **48a** can also include a system such as a GPS system for determining the current location of

such weather sensor so that the current location of the weather sensor is transmitted to the weather analysis unit **12b**.

One skilled in the art will recognize many uses of the system **8b**. For example, when sensor data is collected by sensors **48a** positioned on moving vehicles along roadways or railways, the weather analysis unit **12b** can transmit such weather information to communicator devices **11b** located in close proximity to where the sensor data is being collected. Thus, assuming that a Federal Express truck is located five miles from a subscriber, the information collected from the sensor on the Federal Express truck can be transmitted to the subscriber.

Shown in FIG. 5 is an advisory system **8c** which can be used for delivering other types of information. The advisory system **8c** is similar in construction and function to the advisory system **8a**, except as described below. For purposes of clarity, similar components have been provided with the same numeric prefix, and different alphabetic suffix.

The advisory system **8c** is provided with a broadcast network **10c**. In one embodiment, the broadcast network **10c** is used for locating at least one known or unknown individual located remotely from the broadcast network **10c**. The broadcast network **10c** is provided with an analysis unit **12c**, a communicator location database **16c**, and at least one communicator device **11c** and preferably at least two communicator devices **11c** and **11d**. The communicator device **11c** is referred to herein as a "locator communicator device", and the communicator device **11d** is referred to herein as a "locatee communicator device". The term "locator" as used herein shall mean a person trying to locate a locatee. The term "locatee" as used herein shall mean a person to be located. The communicator location database **16c** is continuously updated to contain real-time data indicative of the spatial locations of the locator communicator device **11c** and the locatee communicator device **11d**.

In a similar manner as described above, the analysis unit **12c** makes comparisons between user profiles (including information indicative of unique personal traits) entered into the analysis unit **12c** from one of the remote communicator devices **11c** and **11d** (as represented by a box **80c**), dynamic locations stored in the communicator location database **16c**, and fixed locations as represented by a box **82c**. The system **8c** may be further described as a locator system **40c** and a locatee system **42c** to delineate the types of information being conveyed within the system **8c**.

For example, a locator utilizes the locator communicator device **11c** to input his or her locator information and/or criteria into his or her user profile such as, for example, personal characteristics (i.e., height, weight, age, eye color, hair color, gender, race, occupation and the like) personality traits (i.e., outgoing, social drinker, non-smoker, and the like), a photograph, an audio presentation by the locator, a video presentation of and/or by the locator, an audio/video presentation of and/or by the locator, and other user information and/or criteria as represented by a box **84c**. Additionally or alternatively, the locator inputs desired criteria of a locatee into the analysis unit **12c** such as, for example, personal characteristics, personality traits, proximity (including a spatial range identifier indicating a distance from the locator's fixed or dynamic location), or any other criteria. The locator inputs the above criteria into one of the locator communicator devices **11c** which may be, for example, a computer, a personal digital assistant (PDA), a cellular phone, a combination cellular phone/PDA, or any other device which may then transmit the locator criteria to the analysis unit **12c**. The analysis unit **12c** may be, for example, a computer or a web server. The analysis unit **12c** matches the locatee user profile

criteria with the locator user profile criteria and/or locator desired criteria to generate a data set of locatee user profiles that match the locator criteria.

The locator criteria are transmitted to one of the locatee communicator devices **11d** based upon the matching of the locator criteria with the locatee user-profile. The permission of the locatee may be obtained prior to forwarding any information about the locatee to the locator communicator device **11c**, if desired. Once the locatee's permission is received (if required), the data set can be transmitted to the locator communicator device **11c** such that the locator can review the data set to determine a locatee to contact by text message or any other means of communication, or alternatively, the analysis unit **12c** can automatically determine a locatee to contact and thereby transmit the text message or other means of communication to the locatee's communicator device **11d** without any intervention by the locator. The locatee's communicator device **11d** may be, for example, a PDA, a cellular phone, a combination cellular phone/PDA, a pager, or any other device in which the analysis unit **12c** or the locator may communicate information to the locatee.

The user profile for each of the locatees includes information relating to the locatee's personal characteristics such as, for example, height, weight, age, eye color, hair color, gender, race, occupation and the like and/or personality traits such as, for example, outgoing, social drinker, non-smoker, and the like, or any other quality or trait relating to the particular locatee. The locatee's user profile may additionally include a photograph of the locatee, an audio presentation by the locatee, a video presentation of and/or by the locatee, an audio/video presentation of and/or by the locatee, and other user information and/or criteria as represented by a box **86c**.

Once the locatee's user profile is downloaded to a locator's communicator device **11c**, the locator may add additional information relating to the locatee such as the locator's impression or opinion of the locatee or any other information the locator considers relevant to the locatee. This additional information remains hidden from the locatee, however, may be broadcast to additional users of the advisory system **8c**. For example, the user profile accessible by the locator system **40c** may include traits related to a particular locatee that remain hidden or unknown to the locatee as represented by the box **86c**. For instance, the locatee may have access to information stored in his user profile such as inputted personal characteristics and/or personality criteria as represented by the box **86c** and may be provided access to his user-profile to update information as needed. In addition to the above-mentioned locatee-accessible information, the locator may have access to the locatee user profile to access locatee traits such as personal characteristics and/or personality traits.

For example, a locator may include in his user profile that he is single, white, male, age 26, college student, non-smoker, and a light social drinker. The locator desires to locate white, single, females that share the same personal characteristics and/or personality traits. The locator may download the user profiles entered by other users ("locatees") of the advisory system **8c**. The locator may send the locatee a text message or other means of communication to make further contact with the locatee. In this embodiment, the present invention may be considered a flirt-service, dating service, or match-making service.

In another embodiment, the system **8c** is used to locate and provide entertainment among users with similar user profiles. Examples of such users include movie goers, gamers, or other persons interested in a particular segment of the entertainment industry. More specifically, the system **8c** can be used to locate individuals having similar interests in the entertain-

ment industry and provide desired entertainment for such individuals. The system **8c** can be used to locate individuals relative to a designated spatial range inputted into the analysis unit **12c** by the locator. Alternatively, the system **8c** can be used to locate individuals/locatees regardless of the locatee's location.

In the same manner as described above, the locator utilizes the locator communicator device **11c** to input his or her locator information and/or criteria into his or her user profile such as, for example, entertainment interests, desired and/or designated spatial range (based upon a fixed or dynamic location), and other user information and/or criteria as represented by the box **84c**. Additionally or alternatively, the locator inputs desired criteria of a locatee into the analysis unit **12c** such as for example, entertainment interests, desired and/or designated spatial range, and any other criteria desired by the user. The analysis unit **12c** matches the locator information with the locatee information in the same manner as described above to locate and match other users of the system **8c** having similar interests in the entertainment industry and/or a proximity within the area designated by the locator.

For example, a locator wishing to play a game such as, for example, tag, with other users of the system **8c** may input his locator user profile information into the analysis unit **12c** via his locator communicator device **11c** in the same manner as described above. Examples of such locator user profile information include, for example, personal characteristics and/or personality traits, and/or a desired spatial range for locating locatees. In addition, the locator may input desired criteria of the locatee into the analysis unit **12c** such as, for example, desired personal characteristics and/or personality traits, desired locatee location, and/or a desired spatial range for locating locatees.

A locator wishing to play a game of tag, for example, inputs information (via the locator communicator device **11c**) relating to the type of game, the locator's personality traits and/or personal characteristics, into the analysis unit **12c** and designates his desire to locate locatees within a spatial range of, e.g., 50 miles from his location. Using the world as a "game-board" for participating in the designated game of tag, the analysis unit **12c** matches the locatee user profile criteria with the locator user profile criteria and/or locator desired criteria to generate a data set of locatee user profiles that match the locator criteria.

Based upon this data set of locatees, the locator may choose locatees/participants to participate in the designated game and send a message such as, for example, a text message, via his locator communicator device **11c** such as "Tag, you're it" to the designated locatee via the locatee communicator device **11d**. Alternatively, the system **8c** can automatically determine a locatee to contact and thereby transmit the text message or other means of communication to the locatee's communicator device **11d** without any intervention by the locator.

In addition to locating and matching users having similar interests in the entertainment industry, the system **8c** is used by users/gamers to play or participate in a game such as, for example, a video game and the like, and/or interact with other users/gamers to play a desired or designated game. In the same manner as described above, the system **8c** allows the user to interact with another individual/user involved in the game based upon the location (static or dynamic) of each user involved in a particular game (including a spatial range identifier indicating a distance from a user's fixed or dynamic location).

Additionally, the locator may use the system **8c** to retrieve (via his locator communicator device **11c**) specific locations of entertainment (i.e., movie theaters, casinos and the like) or

specific events (i.e., a particular movie, a particular gaming event, and the like). The system **8c** may also be used to alert the user of entertainment events based upon his user profile.

In another embodiment, the system **8c** is used to track an individual (“locatee”) based upon real-time location of the individual with or without the aid of a spatial range identifier. More specifically, the system **8c** can be used to locate individuals traveling within a specified spatial range and notify a user when a particular individual has traveled outside of the specified spatial range. Additionally, the system **8c** can be used to locate individuals regardless of their location or location relative to a designated spatial range.

The analysis unit **12c** is loaded with a locatee user profile. Additionally, the analysis unit **12c** may be loaded with a desired spatial range or path in which the locatee intends or is instructed to travel, i.e., the locatee intended range of travel and/or the locatee destination. The analysis unit **12c** tracks the location of the locatee communicator device **11d** and may alert the locator communicator device **11c** when the locatee communicator device **11d** travels outside of the locatee’s intended range of travel and/or the locatee’s intended destination. Additionally, the analysis unit **12c** may alert the locator communicator device **11c** when the locatee communicator device **11d** travels to an area that is geo-referenced as a “good area” or “bad area.” The system **8c** may require the consent of the locatee to track the locatee via the locatee communicator device **11d**, if desired.

For example, a parent may desire to track the travel of his child via the system **8c**. The parent may input the child’s intended destination (with or without a desired spatial range) into the locator communicator device **11c** (which inputs the child’s intended destination into the analysis unit **12c**) so that the analysis unit **12c** may track the travel of the child via the locatee communicator device **11d** and may additionally alert the parent via his locator communicator device **11c** if the child should travel outside the desired spatial range, if designated. Also, the analysis unit **12c** may alert the parent via his locator communicator device **11c** if the child travels into a geo-referenced “good area” (i.e., a school and the like) or “bad area” (i.e., a drinking bar and the like).

Additionally, a user may keep track (via his locator communicator device **11c**) of a friend’s (“locatee’s”) location by tracking the friend’s locatee communicator device **11d** in the same manner as described above in locations such as, for example, a mall, a football stadium, and the like. In this embodiment, a desired spatial range may or may not be designated. Additionally, the system **8c** may require the consent of the locatee to track the locatee via the locatee communicator device **11d**, if desired.

An optional aspect of the systems **8**, **8a**, **8b**, and **8c** is the performance of “operations research.” The term “operations research” as used herein shall mean the geo-referencing of an object coupled with the time-tracking of the object. The term “geo-referencing” as used herein shall mean the determination of an object’s position, O1, in relation to an X1,Y1, coordinate (expected location or expected route) and/or an X1,Y1,Z1, coordinate (expected location or expected route). The term “time-tracking” as used herein shall mean an initial departure time (Td) of an individual and/or object coupled with a predicted and/or expected arrival time (Te) of the individual and/or object. Operations research is applicable to each and every embodiment of the present invention described herein.

Operations research may be employed in various fields such as, for example, mobile commercial services (i.e., fleet management, asset location, and field sales and service) entertainment services (i.e., gaming services, individual loca-

tion services, and flirting and other “social” services), security services (i.e., child-locator services, and mobile roadside assistance), information services (i.e., points-of-interest identification, GPS navigation support, weather information and data, and traffic information and data), or any other field desiring the employment and application of operations research.

For example, a child along with his locatee communicator device **11d** leaves his home (X1, Y1) at 8:00 a.m. (Td) expected to arrive at school (X2, Y2) at 8:30 a.m. (Te). The child’s parent, via his locator communicator device **11c**, may keep track of the child’s location (O1) by, for example, inputting (1) a unique identification code identifying the child’s locatee communicator device **11c**, (2) the child’s intended destination (i.e., school) (with or without a desired spatial range), (3) the child’s time of departure (Td) and (4) the child’s estimated time of arrival (Te) into the locator communicator device **11c**. The locator communicator device **11c** then inputs the unique identification code identifying the child’s locatee communicator device **11c**, (2) the child’s intended destination (i.e., school) (with or without a desired spatial range), (3) the child’s time of departure (Td) and (4) the child’s estimated time of arrival (Te) into the analysis unit **12c** so that the analysis unit **12c** may track the travel of the child via the locatee communicator device **11d** and may additionally alert the parent via his locator communicator device **11c** if the child should travel outside the desired spatial range, if designated, and/or may alert the parent should the child not arrive at school by the inputted estimated time of arrival (Te) and/or may alert the parent as to the child’s actual time of arrival (Ta) to his intended destination and/or a deviation of the child’s location from the expected location and/or expected route, if designated. Also, as discussed above, the analysis unit **12c** may alert the parent via his locator communicator device **11c** if the child travels into a geo-referenced “good area” (i.e., a school and the like) or “bad area” (i.e., a drinking bar and the like).

As another example, an employer uses the employer communicator device **11a** to input the employee’s intended destination (i.e., delivery destination) (with or without a desired spatial range) into the employer communicator device **11a** (which inputs the employee’s intended destination into the analysis unit **12a**), the employee’s time of departure (Td) and the employee’s estimated time of arrival (Te) so that the analysis unit **12a** may track the travel of the employee via the employee communicator device **11b** and may additionally alert the employer via his employer communicator device **11a** if the employee should travel outside the desired spatial range, if designated, and/or may alert the employer should the employee not arrive at the delivery destination by the inputted estimated time of arrival (Te) and/or may alert the employer as to the employee’s actual time of arrival (Ta) to his intended destination and/or a deviation of the employee’s location from the expected route, if designated. Also, as discussed above, the analysis unit **12a** may alert the employer via his employer communicator device **11a** if the employee travels into a geo-referenced “good area” or “bad area.”

Referring now to the drawings and more particularly to FIG. 6, shown there is another embodiment of an advisory system **8e** constructed in accordance with the present invention. The advisory system **8e** is provided with one or more communicator devices **11**, one or more service providers (three being shown by way of example and designated with the reference numerals **90**, **92** and **94**) and one or more prioritization units **95**. The prioritization unit **95** communicates with the communicator devices **11** via one or more communication networks **96**, and also communicates with the one or

more service providers **90**, **92** and **94** via one or more communication networks. The prioritization unit **95** is adapted to permit users of the communicator devices **11** to individually select and/or assign different types of content, service providers, communication networks and/or third party vendors (as discussed below) to have different priorities. Alternatively, the prioritization unit **95** can automatically and individually select at least one of the communication networks **96** for passing the content to each communicator device **11** or groups of communicator devices **11**.

The prioritization unit **95** is implemented as instructions (stored on one or more computer readable medium) running on a suitable logic device, such as a computer or group of computers. In a preferred implementation, the prioritization unit **95** is provided with a web server and communicates with the service providers **90**, **92** and **94** as well as the communicator devices **11** using a global public network, such as the Internet.

The user defined priorities can be provided to the prioritization unit **95** by the users using a variety of different manners, such as electronically using a communicator device, telephone, another computer, facsimile, e-mail or mail. The user's priority instructions are stored as "user defined priorities" on one or more computer readable medium(s) that can be read by the prioritization unit **95** when determining the priority for passing content to the communicator devices **11**.

The user defined priorities can also be based upon a predetermined condition, location and/or service provider. For example, the predetermined condition can be a geographic area in which the communicator device **11** is presently located (or not located). The location of the communicator device **11** can also be used to determine the priority of content to be provided to the communicator device **11**. For example, the location of the communicator device **11** can be utilized to provide a higher priority when the communicator device **11** enters the service area of one or more vendor or service provider.

The present location of the communicator device **11** can be automatically monitored using the communicator location database **16** as described above, or the communicator device **11** can provide its own location to the prioritization unit **95** and/or one of the service providers **90**, **92** or **94**. The location of the communicator device **11** can be determined using any of a variety of possible resources such as a mobile phone network, a mobile phone network equipped with the wireless application protocol technology, global positioning satellite technology, the Internet, loran technology, radar technology, transponder technology or any other type of technology capable of determining or tracking the spatial location of a communicator device **11**.

Each service provider **90**, **92** and **94** is typically implemented as instructions (stored on one or more computer readable medium) running on a suitable logic device, such as a computer or a group of computers adapted to provide one or more services, such as, for example, movie services, news services, financial data services, weather and other environmental data services, business delivery data services, work assignment data services, location-specific gaming data (entertainment data) services, and third-party location data services, as discussed above. Users associated with the communicator devices **11** sign up or register with the service providers **90**, **92** or **94** and also sign up or register with the prioritization unit **95** so that the services or content provided by the service providers **90**, **92** or **94** are delivered to the communicator devices **11** with the aid of the prioritization unit **95**. Once the user is signed up with the service providers **90**, **92** or **94**, the content is continuously or on-demand (on a

push or pull basis) provided to the user's communicator device **11**. In a preferred implementation, each service provider **90**, **92** or **94** is provided with a web server and communicates with the prioritization unit **95** or the communicator devices **11** using a global, public network such as the Internet. However, it should be understood that the prioritization unit **95** can communicate with the service providers **90**, **92** and **94** in other manners.

For example, one of the service providers **90**, **92** or **94** can be adapted to provide third-party location data to the communicator devices **11**. A priority for the third-party location data is selected, assigned, ranked, and/or given priority at the prioritization unit **95** for forwarding the third-party location data to the communicator device(s) **11** on a first priority basis. As another example, weather data may be ranked second priority and entertainment data may be ranked third priority based upon each user's desires. In this example, when resources become scarce, third-party location data will be given priority over weather data and entertainment data such that the user will receive the third-party location data paramount to weather data and entertainment data.

Content can either be originated directly by the service provider **90**, **92** or **94**, or originated by a third-party vendor who communicates such content to the service provider **90**, **92** or **94**. More than one third-party vendor may provide content to a single service provider. Also, a third-party vendor may provide a single content or multiple contents to the service provider. The third-party vendors are typically implemented as one or more computer systems, such as one or more database servers cooperating to obtain and/or generate content.

Designation of priority via the prioritization unit **95** may be offered on a variety of levels within the system **8e**. For example, the user of any of the system **8e** may assign priority via the prioritization unit **95** including, for example, the service provider level (as in content originated by one service provider **90**, **92** or **94** would be given priority over content originated by another one of the service provider **90**, **92** or **94**), the content level (based upon the assigned priority of different types of content), or a third-party vendor level, or any combination thereof.

A service provider **90**, **92** or **94** may originate or obtain at least one content to be passed to at least one communicator device **11**. For example, as shown in FIG. **6** the service providers **90**, **92**, and **94** originate multiple contents **102**, **104**, **106**, **108**, **110**, **112**, **114**, **116**, **118**, respectively, to be passed to the one or more communicator devices **11** via the prioritization unit **95** and the communication networks.

Referring now to FIG. **7**, shown therein and designated by a reference numeral **8f** is another advisory system constructed in accordance with the present invention. The advisory system **8f** includes one or more communicator devices **11** and one or more service providers **90a**, **92a**, and **94a** communicating with the communicator devices via one or more communication networks **96a**. The service providers **90a**, **92a** and **94a** are similar in construction and function as the service providers **90**, **92** and **94** shown in FIG. **6**, with the exception that each service providers **90a**, **92a** and **94a** includes one or more prioritization units **95a** for prioritizing the delivery of content **102a**, **104a**, **106a**, **108a**, **110a**, **112a**, **114a**, **116a**, and **118a** to the communicators devices **11** individually from each service provider. The prioritization units **95a** are similar in construction and function as the prioritization unit **95** described above, with the exception that the prioritization units **95a** are associated solely with one of the service providers **90a**, **92a** or **94a**.

Thus, in summary, the broadcast network in each of the systems (8, 8a, 8b, 8c, 8d) described above can be one of the service providers 90, 92 or 94 in the systems 8e and 8f by including one or more prioritization units 95 and 95a for prioritizing the desired content passed to the communicator device(s) 11 via the communication networks 96 or 96a. Examples of the desired content include, but are not limited to, weather and other environmental data, business delivery data, work assignment data, location-specific gaming data (entertainment data), third-party location data, and the like based upon assignment of a user-defined priority assigned by the user.

Desired content may be pre-determined such that only assignment of user-defined priority is required or, alternatively, the desired content and user-defined priority may be selected and assigned simultaneously. By assigning priority to the various desired content, potential memory storage limit capabilities associated with the user's communicator device 11 and/or service provider 90, 92 or 94 may be alleviated so that content that is assigned first priority will preferably be received by the user. Content having a lower priority may not be received by the particular communicator device 11 if resources such as storage and/or service provider bandwidths are scarce.

The desired content is passed to at least one communicator device 11 by selecting at least one service provider for delivering one or more different types of content to be passed to the at least one communicator device 11 via the communication network 96 or 96a. The content may be provided by at least one or more vendor(s) providing identical content or different content. In addition, priority may be assigned to the content based upon the vendor providing such content. At least one user-defined priority is assigned to at least one of the types of content and to one or more communicator service providers.

Content assignment may be based upon a predetermined condition, location, and/or service provider. The predetermined condition is selected from the group consisting of a geographic area in which the communicator device is presently located, and a geographic area in which the communicator device is not presently located. The selected geographic area may or may not be within the service territory of the at least one or more vendor(s). The user-defined priority and/or the predetermined condition, location, and/or service provider is stored on a computer readable medium such that the different types of content are passed to the communicator device based on the user-defined priority. In one embodiment, it may be determined whether the predetermined condition, location, and/or service provider is available prior to any content being passed to the communicator device 11 via the communication network 96 or 96a. In addition, the content may be received and the user-defined priority may be read prior to the step of passing the different types of content to the communicator device 11 via the communication network 96 or 96a.

The computer readable medium is readable by the communicator device 11 and may be located on the communicator device 11. Alternatively, the computer readable medium may be located remotely from the communicator device 11, such as at the prioritization unit 95 or 95a.

In one version of the invention, the communicator devices 11 may be adapted to send a confirmation to the prioritization unit 95 (via the communication network 96), or the service providers 90a, 92a, or 94a (via the communication network 96a) indicating receipt of the content by the communicator device 11. If a confirmation is not received by the prioritization unit 95 or 95a, or the service provider 90a, 92a, or 94a then the prioritization unit 95 or 95a, or the service provider

90a, 92a, or 94a continue to resend the content until such confirmation is received. Thus, at least one type of content may be re-sent to the communicator device 11 until receipt of the content by the communicator device 11 is confirmed. Whether or not content is re-sent can be selected by the user in the user-defined priorities.

In another version of the invention, the system 8e or 8f may assign priority to available content to be passed to a user's communicator device 11 based upon a user's historical selections of available content and/or the user's historical prioritization of the available content based upon the user's historical preferences. That is, the system 8e or 8f may be adapted to automatically assign priority to available content originated by the service provider or the third-party vendor via the prioritization unit 95 or 95a at the various levels discussed above including, for example, the service provider level (as in content originated by one service provider 90, 92 or 94 and/or 90a, 92a, or 94a would be given priority over content originated by another one of the service provider 90, 92 or 94 and/or 90a, 92a, or 94a), the content level (based upon the assigned priority of different types of content), or a third-party vendor level, or any combination thereof based upon a user's historical selection of the available content and/or a user's historical prioritization of the available content.

For example, a user has selected and is receiving a variety of types of content, such as, for example, location specific data, weather and other environmental data, business delivery data, work assignment data, location-specific gaming data (entertainment data), third-party location data. But changes in the location of his kid is a higher priority than his gaming updates and weather data, so he rates the kid-finder data as the highest priority and that way he always gets it first, and/or resources are conserved so that he can receive it regardless of bandwidth, communicator device memory or other communication network or communicator device limitation.

In the embodiments of the system described above, the communicator device 11 may be adapted to include a prioritization unit (not shown) alternatively or in addition to the prioritization units 95 or 95a such that the presentation of content to the user (e.g., reception, display or storage) can be prioritized independently of any prioritization scheme usable by the service providers 90, 92, 94, 90a, 92a or 94a or prioritization unit 95. The prioritization unit included in the communicator device can be implemented in a variety of manners, such as instructions running on a suitable logic device, such as a microprocessor, digital signal processor or microcontroller, for example, and can receive the user defined priorities using any suitable input device, such as a keyboard, tablet, touch screen or the like. Such instructions can be implemented in a variety of manners, such as software, firmware or hardware.

Also, in any of the embodiments of the system described above, content that is not assigned priority by a user or by the system may be rejected by the prioritization unit such that non-prioritized content is not received by the user.

The entire contents of U.S. Ser. No. 11/334,898 filed on Jan. 19, 2006, are expressly incorporated herein by reference in its entirety.

From the above description, it is clear that the present invention is well adapted to carry out the objects and to attain the advantages mentioned herein as well as those inherent in the invention. While presently preferred embodiments of the invention have been described for purposes of this disclosure, it will be readily understood that numerous changes may be made which will readily suggest themselves to those skilled in the art and which are accomplished within the spirit of the invention disclosed.

23

What is claimed is:

1. A system, comprising:
a service provider configured to output content, including a first content and a second content, to a communication network, the communication network configured to transmit the content to a communicator device; and
a prioritization unit configured to:
receive real-time data indicative of the spatial location of the communicator device, the real-time data indicative of the spatial location of the communicator device being a spatial location dynamic code determined using global positioning satellite technology or a mobile phone network; and
associate priority information with the content based on the spatial location of the communicator device, including associating first priority information with the first content based on the spatial location of the communicator device and associating second priority information with the second content based on the spatial location of the communicator device,
wherein the first content is transmitted to the communicator device based on the first priority information and the second content is not transmitted to the communicator device based on the second priority information.
2. The system of claim 1, wherein the prioritization unit is further configured to determine whether the spatial location of the communicator device is within a predetermined geographic area.
3. The system of claim 2, wherein the prioritization unit associates the first priority information with the first content based on a determination that the spatial location of the communicator device is within the predetermined geographic area.
4. The system of claim 2, wherein the prioritization unit associates the second priority information with the second content based on a determination that the spatial location of the communicator device is within the predetermined geographic area.
5. The system of claim 1, wherein:
the service provider is further configured to output the content to a second communicator device; and
the prioritization unit is further configured to:
receive real-time data indicative of the spatial location of the second communicator device;
associate priority information with the content based on the spatial location of the second communicator device, including associating third priority information with the second content based on the spatial location of the second communicator device, the third priority information being unrelated to the first priority information; and
determine whether the second content is transmitted to the second communicator device based on the third priority information.
6. The system of claim 1, wherein the prioritization unit receives the real-time data indicative of the spatial location of the communicator device from the communicator device.
7. The system of claim 1, wherein the prioritization unit receives the real-time data indicative of the spatial location of the communicator device from the service provider.
8. The system of claim 1, wherein the prioritization unit receives the real-time data indicative of the spatial location of the communicator device from a second service provider, the second service provider adapted to provide third-party location data.

24

9. The system of claim 1, wherein:
the service provider is further configured to output the content to a second communicator device;
the prioritization unit is further configured to receive real-time data indicative of the spatial location of the second communicator device; and
the data indicative of the spatial location of the communicator device and the data indicative of the spatial location of the second communicator device are stored in a communicator location database.
10. The system of claim 9, wherein the communicator location database is automatically updated.
11. The system of claim 9, wherein:
the prioritization unit is configured to repeatedly receive real-time data indicative of the spatial location of the communicator device; and
the communicator location database is updated to reflect an updated spatial location of the communicator device.
12. The system of claim 1, wherein the content originates directly from the service provider.
13. The system of claim 1, wherein the service provider receives the content from a third-party vendor.
14. The system of claim 13, wherein the prioritization unit associates the first priority information with the first content based on a determination that the spatial location of the communicator device is within a service territory of the third-party vendor.
15. The system of claim 13, wherein the prioritization unit associates the second priority information with the second content based on a determination that the spatial location of the communicator device is within a service territory of the third-party vendor.
16. A method of outputting content to a communicator device, the content including a first content and a second content, the method comprising:
receiving real-time data indicative of the spatial location of the communicator device, the real-time data indicative of the spatial location of the communicator device being a spatial location dynamic code determined using global positioning satellite technology or a mobile phone network;
associating first priority information with the first content based on the spatial location of the communicator device;
associating second priority information with the second content based on the spatial location of the communicator device;
outputting the first content to a communications network based on the first priority information, the communication network configured to transmit the content to the communicator device; and
preventing the second content from being transmitted via the communications network to the communicator device based on the second priority information.
17. The method of claim 16, further comprising:
determining whether the spatial location of the communicator device is within a predetermined geographic area.
18. The method of claim 17, wherein the associating the first priority information with the first content based on the spatial location of the communicator device comprises associating the first priority information with the first content based on a determination that the spatial location of the communicator device is within the predetermined geographic area.
19. The method of claim 17, wherein the associating the second priority information with the second content based on the spatial location of the communicator device comprises

25

associating the second priority information with the second content based on a determination that the spatial location of the communicator device is within the predetermined geographic area.

20. A system, comprising:

a service provider configured to output content to a communication network, the communication network configured to transmit the content to a first communicator device and a second communicator device; and

a prioritization unit configured to:

receive real-time data indicative of the spatial location of the first communicator device;

determine whether the spatial location of the first communicator device is within a predetermined geographic area;

associate first priority information with the content based on the determination of whether the spatial location of the first communicator device is within the predetermined geographic area;

determine whether the content is transmitted to the first communicator device based on the first priority information;

26

receive real-time data indicative of the spatial location of the second communicator device;

determine whether the spatial location of the second communicator device is within the predetermined geographic area;

associate second priority information with the content based on the determination of whether the spatial location of the second communicator device is within the predetermined geographic area; and

determine whether the content is transmitted to the second communicator device based on the second priority information.

21. The system of claim **20**, wherein the prioritization unit determines that the content is transmitted to the first communicator device based a determination that the spatial location of the first communicator device is within the predetermined geographic area.

22. The system of claim **20**, wherein the prioritization unit determines that the content is not transmitted to the first communicator device based a determination that the spatial location of the first communicator device is within the predetermined geographic area.

* * * * *