



US009243788B2

(12) **United States Patent**
Chen

(10) **Patent No.:** **US 9,243,788 B2**
(45) **Date of Patent:** **Jan. 26, 2016**

(54) **DECORATIVE LIGHTING WITH REINFORCED WIRING**

- (71) Applicant: **Willis Electric Co., Ltd.**, Taipei (TW)
- (72) Inventor: **Johnny Chen**, Taipei (TW)
- (73) Assignee: **Willis Electric Co., Ltd.**, Taipei (TW)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

- (21) Appl. No.: **14/627,427**
- (22) Filed: **Feb. 20, 2015**

(65) **Prior Publication Data**
US 2015/0167944 A1 Jun. 18, 2015

Related U.S. Application Data

(63) Continuation of application No. 14/485,911, filed on Sep. 15, 2014, now Pat. No. 9,140,438, which is a continuation-in-part of application No. 14/328,221, filed on Jul. 10, 2014.

(60) Provisional application No. 61/877,854, filed on Sep. 13, 2013.

- (51) **Int. Cl.**
F21V 23/00 (2015.01)
H01B 7/04 (2006.01)
F21S 4/00 (2006.01)
F21W 121/04 (2006.01)
F21Y 105/00 (2006.01)

(52) **U.S. Cl.**
CPC *F21V 23/001* (2013.01); *F21S 4/002* (2013.01); *H01B 7/04* (2013.01); *F21W 2121/04* (2013.01); *F21Y 2105/003* (2013.01)

(58) **Field of Classification Search**
CPC *F21S 4/002*; *H01B 7/04*
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,656,148 A	1/1928	Harris
1,677,972 A	7/1928	Marks
1,895,656 A	1/1933	Gadke
2,050,364 A	8/1936	Morton
2,072,337 A	3/1937	Kamm
2,484,813 A	10/1949	Waltz

(Continued)

FOREIGN PATENT DOCUMENTS

CN	1181693	5/1998
CN	1509670 A	7/2004

(Continued)

OTHER PUBLICATIONS

U.S. Appl. No. 14/328,221, filed Jul. 10, 2014, inventor Johnny Chen.

(Continued)


Primary Examiner — Elmito Breal

(74) *Attorney, Agent, or Firm* — Christensen Fonder P.A.

(57) **ABSTRACT**

A reinforced wire for decorative lighting, the wire defining a central longitudinal wire axis and including: a longitudinally-extending reinforcing strand, the reinforcing strand comprising one or more fibers comprising a polymer material and defining a reinforcing-strand axis; a plurality of conductor strands wound about the reinforcing strand, each of the plurality of conductor strands defining a conductor strand axis; and an outer insulating layer adjacent to, and covering, one or more of the conductor strands. The reinforcing strand in cross section normal to the wire axis defines an asymmetrical shape.

21 Claims, 28 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2,806,938 A	9/1957	Henry	5,915,827 A	6/1999	Wang
2,969,456 A	1/1961	Raymaley	5,921,806 A	7/1999	Shuey
3,115,435 A	12/1963	Abramson	5,934,793 A	8/1999	Rahman
3,118,617 A	1/1964	Hellrich	5,944,408 A	8/1999	Tong et al.
3,214,318 A	10/1965	Snow	5,962,088 A	10/1999	Tanaka et al.
3,214,579 A	10/1965	Pacini	6,004,006 A	12/1999	Wang
3,296,430 A	1/1967	Eckert	6,030,670 A	2/2000	Chang
3,504,169 A	3/1970	Freeburger	6,053,774 A	4/2000	Lin
3,571,586 A	3/1971	Duckworth	6,056,427 A	5/2000	Kao
3,616,107 A	10/1971	Kershner	6,079,848 A	6/2000	Ahroni
3,617,732 A	11/1971	Fisher	6,084,357 A	7/2000	Janning
3,704,366 A	11/1972	Korb et al.	6,111,201 A	8/2000	Drane et al.
3,783,437 A	1/1974	Graff et al.	6,113,430 A	9/2000	Wu
3,806,399 A	4/1974	Cocjin	6,116,563 A	9/2000	Tsai
3,970,834 A	7/1976	Smith	6,123,433 A	9/2000	Chen
3,985,924 A	10/1976	Pritza	6,126,298 A	10/2000	Wu
4,020,201 A	4/1977	Miller	6,147,367 A	11/2000	Yang et al.
4,072,857 A	2/1978	DeVicaris	6,155,697 A	12/2000	Ahroni
4,097,917 A	6/1978	McCaslin	6,162,515 A	12/2000	Hill
4,140,823 A	2/1979	Weskamp	6,203,169 B1	3/2001	Coushaine et al.
4,203,476 A	5/1980	Vitellaro	6,257,740 B1	7/2001	Gibboney, Jr.
4,262,480 A	4/1981	Wasserman et al.	6,257,793 B1	7/2001	Lin
4,493,523 A	1/1985	Leong et al.	6,273,584 B1	8/2001	Wang et al.
4,516,193 A	5/1985	Murphy	6,283,797 B1	9/2001	Wu
4,631,650 A	12/1986	Ahroni	6,302,562 B1	10/2001	Wu
4,753,600 A	6/1988	Williams	6,347,965 B1	2/2002	Pan
4,777,573 A	10/1988	Liao	6,354,719 B1	3/2002	Pan
4,779,177 A	10/1988	Ahroni	6,361,368 B1	3/2002	Tseng
4,805,075 A	2/1989	Damore	6,457,839 B1	10/2002	Grandoit
4,807,098 A	2/1989	Ahroni	6,458,435 B1	10/2002	Lai
4,855,880 A	8/1989	Mancusi Jr.	6,514,581 B1	2/2003	Gregory
4,859,205 A	8/1989	Fritz	6,533,437 B1	3/2003	Ahroni
4,899,266 A	2/1990	Ahroni	6,536,916 B1	3/2003	Rahman
5,033,976 A	7/1991	Sarian et al.	6,541,800 B2	4/2003	Barnett et al.
5,104,608 A	4/1992	Pickering	6,544,070 B1	4/2003	Radliff
5,109,324 A	4/1992	Ahroni	6,559,385 B1	5/2003	Johnson et al.
5,121,310 A	6/1992	Ahroni	6,575,595 B1	6/2003	Wu
5,218,233 A	6/1993	Takahashi	6,576,844 B1	6/2003	Kamata
5,281,158 A	1/1994	Lin	6,580,182 B2	6/2003	Janning
5,342,661 A	8/1994	Wilcox, II	6,588,914 B1	7/2003	Tang
5,422,766 A	6/1995	Shu	6,595,657 B1	7/2003	Shieh
5,442,258 A	8/1995	Shibata	6,609,814 B2	8/2003	Ahroni
5,453,664 A	9/1995	Harris	6,634,766 B1	10/2003	Gordon
5,455,750 A	10/1995	Davis et al.	6,644,836 B1	11/2003	Adams
5,456,620 A	10/1995	Kaminski	6,657,398 B2	12/2003	Chang
5,481,444 A	1/1996	Schultz	D486,385 S	2/2004	Smith-Kielland et al.
5,550,720 A	8/1996	Carroll	6,752,512 B2	6/2004	Pan
5,560,975 A	10/1996	Casper	6,794,825 B1	9/2004	Kao
5,580,159 A	12/1996	Liu	6,805,463 B2	10/2004	Shieh
5,586,905 A	12/1996	Marshall et al.	6,840,655 B2	1/2005	Shen
5,652,032 A	7/1997	Kaczor et al.	6,883,951 B2	4/2005	Wu
5,702,262 A	12/1997	Brown et al.	6,908,215 B2	6/2005	Wu
5,707,136 A	1/1998	Byers	6,913,838 B2	7/2005	McCullough et al.
5,709,457 A	1/1998	Hara	6,929,383 B1	8/2005	Janning
5,720,544 A	2/1998	Shu	6,942,355 B1	9/2005	Castiglia
5,776,559 A	7/1998	Woolford	6,951,405 B2	10/2005	Yao
5,788,361 A	8/1998	Lee	6,980,076 B1	12/2005	Rolling et al.
5,791,765 A	8/1998	Lin	6,982,385 B2	1/2006	Wu
5,791,940 A	8/1998	Chen et al.	7,014,352 B2	3/2006	Wu
5,807,134 A	9/1998	Hara	7,045,965 B2	5/2006	Li et al.
5,816,849 A	10/1998	Schmidt	7,052,156 B2	5/2006	Primeau
5,816,862 A	10/1998	Tseng	7,055,980 B2	6/2006	Wu
5,820,248 A	10/1998	Ferguson	7,055,981 B2	6/2006	Yao
5,828,183 A	10/1998	Wang	7,132,139 B2	11/2006	Yang
5,829,865 A	11/1998	Ahroni	7,235,815 B2	6/2007	Wang
5,834,901 A	11/1998	Shen	7,253,556 B1	8/2007	Gibboney
5,839,819 A	11/1998	Pan	7,264,392 B2	9/2007	Massabki et al.
5,848,838 A	12/1998	Presta	7,445,824 B2	11/2008	Leung et al.
5,852,348 A	12/1998	Lin	7,547,843 B2	6/2009	Deve et al.
5,854,541 A	12/1998	Chou	7,581,870 B2	9/2009	Massabki et al.
5,855,705 A	1/1999	Gauthier	7,585,552 B2	9/2009	Meseke
5,860,731 A	1/1999	Martinez	7,695,298 B2	4/2010	Arndt et al.
5,860,830 A	1/1999	Wu	D620,836 S	8/2010	Chen
5,893,634 A	4/1999	Wang	7,772,495 B2	8/2010	Wu et al.
5,908,238 A	6/1999	Huang	7,893,627 B2	2/2011	Li
			8,007,129 B2	8/2011	Yang
			8,053,042 B1	11/2011	Loomis
			8,062,718 B2	11/2011	Schooley
			8,100,546 B2	1/2012	Lutz et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

8,298,633 B1 10/2012 Chen
 8,371,028 B2 2/2013 Goldsworthy et al.
 D678,211 S 3/2013 Chen
 8,454,186 B2 6/2013 Chen
 8,454,187 B2 6/2013 Chen
 8,469,750 B2 6/2013 Chen
 D686,523 S 7/2013 Chen
 8,568,015 B2 10/2013 Chen
 8,569,960 B2 10/2013 Chen
 D696,153 S 12/2013 Chen
 8,876,321 B2 11/2014 Chen
 2002/0097573 A1 7/2002 Shen
 2002/0118540 A1 8/2002 Ingrassia
 2002/0149936 A1 10/2002 Mueller et al.
 2003/0142494 A1 7/2003 Ahroni
 2003/0198048 A1 10/2003 Frederick
 2003/0206412 A1 11/2003 Gordon
 2004/0004435 A1 1/2004 Hsu
 2004/0012950 A1 1/2004 Pan
 2004/0090770 A1 5/2004 Primeau
 2004/0096596 A1 5/2004 Palmer, III et al.
 2004/0105270 A1 6/2004 Shieh
 2004/0182597 A1 9/2004 Smith et al.
 2005/0048226 A1 3/2005 Gary et al.
 2005/0077525 A1 4/2005 Lynch et al.
 2005/0122723 A1 6/2005 Frederick
 2005/0249892 A1 11/2005 Rocheleau
 2005/0286267 A1 12/2005 Wang
 2006/0000634 A1 1/2006 Arakawa
 2006/0106444 A1 5/2006 Michael et al.
 2007/0092664 A1 4/2007 Chun
 2007/0177402 A1 8/2007 Wu
 2007/0230174 A1 10/2007 Hicks et al.
 2007/0253191 A1 11/2007 Chin et al.
 2008/0007951 A1 1/2008 Chan
 2008/0025024 A1 1/2008 Yu
 2008/0186731 A1 8/2008 Graham
 2008/0186740 A1 8/2008 Huang et al.
 2008/0205020 A1 8/2008 Vich
 2008/0303446 A1 12/2008 Ding
 2009/0002991 A1 1/2009 Huang
 2009/0059578 A1 3/2009 Lau

2009/0260852 A1 10/2009 Schaffer
 2009/0289560 A1 11/2009 Oliva
 2009/0308637 A1 12/2009 Amils
 2010/0000065 A1 1/2010 Cheng et al.
 2010/0053991 A1 3/2010 Boggs
 2010/0072747 A1 3/2010 Krize
 2010/0195332 A1 8/2010 Wasem
 2010/0196628 A1 8/2010 Shooley
 2011/0062875 A1 3/2011 Altamura
 2011/0076425 A1 3/2011 Cheng et al.
 2011/0100677 A1 5/2011 Chen et al.
 2011/0215368 A1 9/2011 Chen
 2011/0245824 A1 10/2011 Schaffer
 2011/0286223 A1 11/2011 Chen
 2011/0303939 A1 12/2011 Chen
 2011/0305022 A1 12/2011 Chen
 2012/0009360 A1 1/2012 Fu et al.
 2013/0120971 A1 5/2013 Chen
 2013/0163250 A1 6/2013 Chen
 2013/0214691 A1 8/2013 Chen
 2014/0036483 A1 2/2014 Chen

FOREIGN PATENT DOCUMENTS

CN 2751226 Y 1/2006
 CN 201187701 Y 1/2009
 CN 103680693 A 3/2014
 CN 204026296 U 12/2014
 DE 8436328 4/1985
 DE 10235081 A1 2/2004
 GB 1150390 4/1969
 GB 1245214 9/1971
 GB 2137086 A 10/1984
 GB 2172135 A 9/1986
 GB 2396686 A 6/2004
 WO WO 91/10093 7/1991
 WO WO 96/24966 8/1996
 WO WO 96/26661 A1 9/1996

OTHER PUBLICATIONS

U.S. Appl. No. 14/485,911, filed Sep. 15, 2014, inventor Johnny Chen. State Intellectual Property Office of the People's Republic of China, "Notification Passing Examination on Formalities," Application No. 201310596921.4, Issue No. 2014092901092450, Issue Date Oct. 9, 2014 (5 pgs.).

Fig. 1
Prior Art




Fig. 2
Prior Art





Fig. 3













Fig. 6










Fig. 10

Fig. 11A




Fig. 11B




Fig. 12A




Fig. 12B




Fig. 13A




Fig. 13B




Fig. 14A




Fig. 14B




Fig. 15




Fig. 16




Fig. 17





Fig. 18







Fig. 22




Fig. 23




Fig. 24




Fig. 25




FIG. 26




FIG. 27




FIG. 28







FIG. 29








Fig. 32

Fig. 33A




Fig. 33B




Fig. 33C




Fig. 33D




Fig. 34




Fig. 35




Fig. 36




Fig. 37




Fig. 38




Fig. 39





Fig. 40
Prior Art






FIG. 42




Fig. 43





Fig. 44







Fig. 46



1

DECORATIVE LIGHTING WITH REINFORCED WIRING

CROSS-REFERENCE TO RELATED APPLICATIONS

The present application is a continuation of U.S. patent application Ser. No. 14/485,911, filed Sep. 15, 2014 which is a continuation-in-part of U.S. patent application Ser. No. 14/328,221, filed Jul. 10, 2014, which claims the benefit of U.S. Provisional Application No. 61/877,854, filed Sep. 13, 2013, all of which are incorporated herein by reference in their entireties.

FIELD OF THE INVENTION

The present invention is generally directed to decorative lighting. More specifically, the present invention is directed to decorative lighting wiring, decorative light strings, lighted trees, lighted sculptures, and lamp assemblies having reinforced wiring, as well as methods of manufacturing and using same.

BACKGROUND OF THE INVENTION

Decorative lighting, such as seasonal holiday lighting, generally includes decorative light strings, lighted trees, lighted decorative sculptures and other such lights and lighted objects. Such decorative lighting often comprises one or more strings of lights constructed of multiple wires, lamp assemblies and an electrical connector or power plug. Wires used in decorative lighting typically include an electrical conductor surrounded by an insulating material. The electrical conductor usually comprises multiple, individual strands of copper conductors. For example, a typical 50 light string of incandescent Christmas lights may be constructed using 22AWG wire that includes 16 individual copper strands twisted together and covered with an insulating polymer material, such as polyvinyl chloride (PVC).

To ensure safety, such wiring as used in decorative lighting applications may be required to meet various standards and requirements relating to both electrical and mechanical performance. For example, wires may be subject to dielectric testing, tensile-strength testing, breakage testing, cold temperature bending, flammability testing, and so on. From a mechanical perspective, some important and often-tested wire characteristics include tensile strength, breakage strength, and elongation. Not only does a decorative light string need to be able to conduct electricity safely, but it also needs to withstand physical abuse with limited risk of breakage. Breakage, including breakage of any portion of the wiring, could result in shock or electrocution to persons coming into contact with the decorative lighting or structures touching the decorative lighting, such as a tree.

One simple way to increase the mechanical integrity of wiring is to rely on relatively large gauge wiring. For example, while a 22AWG wire may be sufficient to safely conduct the expected electrical current of a light string, a 20AWG wire may actually be used to increase mechanical strength. However, while simply increasing the wire gauge may provide mechanical strength, the material cost to use oversized wire generally outweighs the resulting benefits.

Another known and commonly-used method of increasing mechanical strength of a decorative light string is to twist pairs of wires together. While this technique does not increase the mechanical strength of an individual wire, twisting two wires together, such as a first polarity wire and a second

2

polarity wire, mechanically strengthens the overall decorative light string along its length. Such a known arrangement is depicted in FIG. 1, which illustrates a typical "twisted-pair" light string. In the light string of FIG. 1, the wires L1, L2, and L3 of the light string are twisted along the length of the light string. As such, if opposing forces were applied to the light string, for example pulling power plug 1 and end connector 2 in opposite directions, the twisted pairs of wires are stronger than single wires, and the likelihood of a wire breaking is decreased.

Referring to FIG. 2, a portion of a prior art net light is depicted. The net light depicts a second known method for strengthening decorative light strings, namely, wrapping a non-conductive, reinforcing strand about each individual conductive wire or wire segment. For example, the prior art net light of FIG. 2 includes non-conductive reinforcing strands 211 and 212 wrapped or twisted about multiple individual wires 13 that connect the various lamp assemblies 12. Should a portion of the net light be subject to pulling, the reinforcing strands serve to diminish the possibility that any individual wire will break.

SUMMARY

Embodiments of the invention resolve the deficiencies of known decorative lighting wiring, decorative light strings, lighted trees, lighted decorative sculptures and other such lights and lighted objects.

In an embodiment, the invention comprises a reinforced wire for decorative lighting, the wire defining a central longitudinal wire axis and comprising: a longitudinally-extending reinforcing strand, the reinforcing strand comprising one or more fibers comprising a polymer material and defining a reinforcing-strand axis; a plurality of conductor strands wound about the reinforcing strand, each of the plurality of conductor strands defining a conductor strand axis; an outer insulating layer adjacent to, and covering, one or more of the conductor strands; wherein the reinforcing strand in cross section normal to the wire axis defines an asymmetrical shape.

In another embodiment, the invention comprises a reinforced wire for decorative lighting, the wire defining a central longitudinal wire axis and comprising: a longitudinally-extending reinforcing strand, the reinforcing strand comprising a polymer material and defining a central reinforcing-strand axis; a plurality of conductor strands wound about the reinforcing strand, each of the plurality of conductor strands defining a central conductor-strand axis; an outer insulating layer adjacent to, and covering, one or more of the conductor strands; wherein the central reinforcing-strand axis is offset from the wire axis and the plurality of conductor strands are asymmetrically wound about the reinforcing strand.

Embodiments also include various reinforced decorative lighting assemblies, including an assembly comprising: a first lamp assembly including a first lamp holder and a first lamp element, a second lamp assembly including a second lamp holder and a second lamp element, and a first reinforced decorative-lighting wire having a first end and a second end, the first reinforced decorative-lighting wire defining a central longitudinal wire axis and including: a longitudinally-extending reinforcing strand, the reinforcing strand comprising one or more fibers comprising a polymer material and defining a reinforcing-strand axis; a plurality of conductor strands helically twisted about the reinforcing strand; an outer insulating layer adjacent to, and covering, one or more of the conductor

3

strands; wherein the reinforcing strand in cross section normal to the wire axis defines an asymmetrical shape, and the first end of the first reinforced decorative-lighting wire is received by the first lamp holder and is in electrical connection with the first lamp element, and the second end of the first reinforced decorative-lighting wire is received by the second lamp holder, and is in electrical connection with the second lamp element.

Another embodiment includes a reinforced decorative lighting assembly, comprising: a first power wire having a plurality of conductor strands and having a first ampacity; a second power wire having a plurality of conductor strand; a plurality of lamp assemblies including a plurality of lamp elements, the plurality of lamp assemblies including a first lamp assembly in electrical connection with the first power wire, and a second lamp assembly in electrical connection with the second power wire; a plurality of reinforced decorative-lighting wires electrically connecting the plurality of lamp elements, each of the reinforced decorative-lighting wires having a second ampacity and including: a longitudinally-extending reinforcing strand, the reinforcing strand comprising one or more fibers comprising a polymer material and defining a reinforcing-strand axis; a plurality of conductor strands helically twisted with the reinforcing strand; an outer insulating layer adjacent to, and covering, one or more of the conductor strands; wherein the first ampacity of the first power wire is greater than the second ampacity of the reinforced decorative lighting wire.

Such embodiments may include reinforced decorative light strings, trees, sculptures, and other such assemblies.

Other embodiments include methods of manufacturing embodiments of reinforced decorative lighting wiring and assemblies, as described herein.

BRIEF DESCRIPTION OF THE FIGURES

The invention can be understood in consideration of the following detailed description of various embodiments of the invention in connection with the accompanying drawings, in which:

FIG. 1 depicts a prior art decorative light string having a twisted-pair wiring construction;

FIG. 2 depicts a prior art net light having that includes external wire-reinforcing strands;

FIG. 3 is a perspective view of a reinforced decorative wire, according to an embodiment of the claimed invention;

FIG. 4A is a cross-sectional view of the reinforced decorative wire of FIG. 3;

FIG. 4B is a cross-sectional view of the reinforced decorative wire of FIG. 3, depicting variations in conductor and strand position caused during manufacturing;

FIG. 5 is a cross-sectional view of another embodiment of a reinforced decorative wire, according to an embodiment of the claimed invention;

FIG. 6 is a cross-sectional view of another embodiment of a reinforced decorative wire, according to an embodiment of the invention;

FIG. 7 is a block diagram of a process for manufacturing reinforced decorative wire, according to an embodiment;

FIG. 8 is a front view of a plate for a stranding process step of the process of FIG. 7;

FIG. 9A is a cross-sectional view depicting eight conductor strands relative to a single, central reinforcing strand prior to final completion of an embodiment of the reinforced decorative wire of FIG. 1;

4

FIG. 9B is a cross-sectional view of an embodiment of a completed decorative wire having an asymmetrical configuration, according to the embodiment of FIG. 9A;

FIG. 10 is a perspective view of the reinforced wire of FIG. 9B;

FIG. 11A is a cross-sectional view depicting seven conductor strands relative to a single reinforcing strand prior to final completion of an embodiment of the reinforced decorative wire of FIG. 1;

FIG. 11B is a cross-sectional view of an embodiment of a completed decorative wire having an asymmetrical configuration, according to the embodiment of FIG. 11A;

FIG. 12A is a cross-sectional view depicting nine conductor strands relative to a single reinforcing strand prior to final completion of an embodiment of the reinforced decorative wire of FIG. 1;

FIG. 12B is a cross-sectional view of an embodiment of a completed decorative wire having an asymmetrical configuration, according to the embodiment of FIG. 12A;

FIG. 13A is a cross-sectional view depicting ten conductor strands relative to a single reinforcing strand prior to final completion of an embodiment of the reinforced decorative wire of FIG. 1;

FIG. 13B is a cross-sectional view of an embodiment of a completed decorative wire having an asymmetrical configuration, according to the embodiment of FIG. 13A;

FIG. 14A is a view of a reinforced, series-connected, decorative light string, according to an embodiment of the claimed invention;

FIG. 14B is a front, exploded view of a lamp assembly of the decorative light string of FIG. 14A, according to an embodiment of the claimed invention;

FIG. 15 is a front view of a reinforced wire attached to a wire terminal of the reinforced decorative light string of FIG. 14A;

FIG. 16 is an electrical schematic of the reinforced decorative light string of FIG. 14A;

FIG. 17 is a view of a reinforced, parallel-connected, decorative light string, according to an embodiment of the claimed invention;

FIG. 18 is an electrical schematic of the reinforced decorative light string of FIG. 17;

FIG. 19 is a front, perspective exploded view of a lamp assembly of the decorative light string of FIG. 17, according to an embodiment of the claimed invention;

FIG. 20 is a front, perspective exploded view of another embodiment of a lamp assembly of the decorative light string of FIG. 17;

FIG. 21 is a front view of a pair of wire-piercing terminals of a lamp assembly of the reinforced decorative light string of FIG. 17;

FIG. 22 is a view of a reinforced series-parallel connected decorative light string, according to an embodiment of the claimed invention;

FIG. 23 is an electrical schematic of the reinforced decorative light string of FIG. 22;

FIG. 24 is a view of a reinforced parallel-series connected decorative light string, according to an embodiment of the claimed invention;

FIG. 25 is an electrical schematic of the reinforced decorative light string of FIG. 24;

FIG. 26 is a schematic and wire layout of a 3-circuit reinforced decorative light string with a power end connector, according to an embodiment of the claimed invention;

FIG. 27 is a schematic and wire layout of a 3-circuit reinforced decorative light string with a power end connector, the

light string configured as an icicle light string, according to an embodiment of the claimed invention;

FIG. 28 is a schematic and wire layout of a multi-circuit, reinforced chasing decorative light string, according to an embodiment of the claimed invention;

FIG. 29 is a schematic and wire layout multi-circuit, synchronized decorative light string, according to an embodiment of the claimed invention;

FIG. 30 is a front view of an artificial tree including a reinforced light string, according to an embodiment of the claimed invention;

FIG. 31 is a front view of a reinforced-wire, lighted artificial tree including a reinforced light string and trunk wiring system, according to an embodiment of the claimed invention;

FIG. 32 is a block diagram of a trunk-wiring system of the lighted tree of FIG. 31 according to an embodiment of the claimed invention;

FIGS. 33A-33D are front views of electrical connectors in trunk portions of the lighted tree of FIG. 31;

FIG. 34 is a front view of a portion of the lighted tree of FIG. 31, depicting a light string attached to multiple trees and extending between two branches;

FIG. 35 is a front view of a mechanical and electrical trunk connection system of the tree of FIG. 31, according to an embodiment of the claimed invention;

FIG. 36 is a front view of a mechanical and electrical trunk connection system of the tree of FIG. 31, according to another embodiment of the claimed invention;

FIG. 37 is a front view of a sub-net of a reinforced-wire net light, according to an embodiment of the claimed invention;

FIG. 38 is a front view of a reinforced-wire net light, according to an embodiment of the claimed invention;

FIG. 39 is a front view of a portion of the reinforced-wire net light of FIG. 38;

FIG. 40 is a front view of a portion of a prior-art net light;

FIG. 41 is a schematic of the reinforced-wire net light according to FIG. 38;

FIG. 42 is a schematic of another embodiment of a reinforced-wire net light;

FIG. 43 is a schematic of another embodiment of a reinforced-wire net light;

FIG. 44 is a schematic of yet another embodiment of a reinforced-wire net light

FIG. 45 is a schematic of an LED-based net light with reinforced wire; and

FIG. 46 is a front view of a reinforced-wire decorative sculpture, according to an embodiment of the claimed invention.

While the invention is amenable to various modifications and alternative forms, specifics thereof have been shown by way of example in the drawings and will be described in detail. It should be understood, however, that the intention is not to limit the invention to the particular embodiments described. On the contrary, the intention is to cover all modifications, equivalents, and alternatives falling within the spirit and scope of the invention as defined by the appended claims.

DETAILED DESCRIPTION

The prior art methods of reinforcing and strengthening decorative lighting each have their own drawbacks. Oversized wire and twisted pair configurations tends to drive up material cost and make lighting heavier and bulkier, while non-conductive, reinforcing strands may be considered not only unattractive, but expensive to manufacture due to increased complexity.

Embodiments of the claimed invention overcome the shortcomings of the prior art by providing internally-reinforced, electrically-conducting wires having superior tensile strength and elongation for decorative lighting, decorative lighting wiring structures, reinforced wiring, lighted trees, nets, and other reinforced-wire decorative lighting apparatuses and methods.

Unlike known electrically-conducting wire or “cords” used in decorative lighting applications which typically consist of multiple conductor strands twisted together and surrounded by an insulating material, embodiments of the present invention generally non-conductive reinforcing strands or threads of material combined with conductor strands of material. While all materials may be considered to embody some degree of conductivity, herein, the term “conductive” will be understood to refer to materials exhibiting a relatively high degree of electrical conductivity or low electrical resistance, for example, a metal or a conductive polymer. “Non-conductive” will be understood to refer to those materials exhibiting a relatively low degree of electrical conductivity, or low electrical resistivity, including insulators, nonmetallic materials, including materials such as most polymers and plastics.

Referring to FIG. 3, an embodiment of reinforced decorative-lighting wire or cord 100 is depicted. In an embodiment, reinforced decorative-lighting wire 100 includes one or more reinforcing strands or threads 102, one or more conductor strands 104, and insulating layer or jacket 106. Conductor strands 104 may form one or more layers, such as the depicted first conductor layer 108 and second conductor layer 110. As will be described further below, reinforcing strands 102 and conductor strands 104 may be arranged in a variety of manners, and in a variety of quantities, dependent upon a number of factors, including desired wire properties, including, but not limited to, tensile strength, resistivity and conductivity.

Reinforced decorative-lighting wire 100 may comprise a variety of sizes, resistances, and ampacities, and may be described in terms of electrically-equivalent wire gauge standards, e.g., 20 AWG (American Wire Gauge), 22 AWG, 24 AWG, etc. For example, in an embodiment, wire 100 may comprise a conductive equivalent to a wire normally described as a 22 AWG wire having an equivalent cross sectional area of conductive copper of approximately 0.326 mm² and having a typical resistance of approximately 52.96 ohms/km, though the overall diameter of the complete wire may be greater than a standard 22AWG wire due to the additional reinforcing strands.

Reinforced decorative-lighting wire 100 may also be described in terms of other equivalent wire standards, such as Underwriter’s Laboratories Standard UL 62 insofar as it pertains to decorative-lighting wire, including standards directed to Type XTW or Type CXTW as typically used in decorative-lighting applications. For example, an embodiment of a reinforced decorative-lighting wire 100 may be designed to include characteristics equivalent to selected characteristics of an 18, 20 22, 25, or 25 AWG CXTW wire, particularly conductive characteristics such as DC resistance per conductor strand, and insulative characteristics.

As depicted in FIG. 3, an embodiment of reinforced decorative-lighting wire 100 comprises a single reinforcing strand 102, and multiple conductor strands 104. In an embodiment, conductor strands 104 form two layers: first conductor layer 108 and second layer 110, though it will be understood that conductors 104 may form one, two, or more than two layers. Layers 108 and 110 form a stranded conductor of reinforced wire 100. A reinforced wire 100 having the stranded conductor comprising multiple conductor strands 104 may also be

referred to as a “single” conductor reinforced wire **100** to differentiate from standard twisted pairs of wires typically used in decorative lighting. However, it will be understood that in some applications, pairs of single-conductor reinforced wires **100** may be twisted about one another to form reinforced twisted-pair wire sets.

In an embodiment, and as depicted, reinforcing strand **102** extends axially along a length of wire **100**, and along central wire Axis A, surrounded by, or adjacent to, conductor strands **104**. In an embodiment, reinforcing strand **102** is generally located radially at a center of wire **100**.

Reinforcing strand **102** may define a generally cylindrical shape defining a circular cross-sectional area, though the cross-sectional area may define other shapes, such as square, oval, rectangular, and so on. In other embodiments, and as will be described further below with respect to FIGS. 4B and 9A-13B, reinforcing strand **102** may define a generally circular cross-sectional shape prior to assembly into wire **100**, but then define a different, shape, such as an asymmetrical shape, after a manufacturing assembly process.

In an embodiment, central reinforcing strand **102** comprises one or more fibers or strands of fibrous reinforcing material. In the depicted embodiment, reinforcing strand **102** comprises a single strand or fiber of reinforcing material. In other embodiments, reinforcing strand **102** comprises multiple strands of reinforcing material that may comprise twisted strands, threads or fibers such that reinforcing strand **102** comprises a yarn of multiple strands or fibers.

In the embodiment depicted, reinforcing strand **102** comprises a single 1500 Denier fiber having an outside diameter of approximately 0.45 mm. In another embodiment, reinforcing strand **102** comprises a fiber ranging from 500 Denier to 2500 Denier. In other embodiments, reinforcing strand **102** may comprise a larger or smaller diameter and/or greater or lesser Denier fiber depending on the properties of the reinforcing material and desired reinforcing properties. In an embodiment, reinforcing strand **102** comprises a single or multi-fiber strand sized to be within the range of 1000 to 1500 Denier. Reinforced wire **100** with reinforcing strands **102** comprising such a size may provide appropriate reinforcing strength for wires **100** that most decorative lighting applications that would typically use an 18-24 AWG standard wire.

The reinforcing material of reinforcing strand **102** may comprise a generally non-conductive or nonmetallic material, such as a plastic or polymer, including a polyester or polyethylene (PE) material. In one such embodiment, reinforcing strand **102** comprises a polyethylene terephthalate (PET) material. Other reinforcing materials may include, though will not be limited to, polystyrene, polyvinyl chloride (PVC), polyamide (PA), and so on. Reinforcing strand **102** may consist entirely or substantially of a non-conductive or nonmetallic material, such as PET, though in some embodiments, reinforcing strand **102** may comprise a composite material. Such a composite material may comprise a non-conductive material, such as PET, as well as some other conductive, partially-conductive, or other non-conductive material.

In an embodiment, and as depicted, reinforcing strand **102** comprises a substantially solid structure in cross section (radially), as compared to a hollow core strand such as a pipe or other annular shape. Further, in an embodiment, reinforcing strand **102** comprises the same material continuously along its axial length. In an embodiment, reinforcing strand **102** may have a hardness that is less than a hardness of a conductor strand **104**. In an embodiment, reinforcing strand **102** has a Rockwell hardness of R117.

In an embodiment, reinforcing strand **102** comprises primarily a PET material, having a specific gravity ranging from

1380-1405 kg/m³, and a melting point of 200-250 degrees Celsius. In other embodiments, reinforcing strand **102** comprises a polymer having a specific gravity that ranges from 1000-2000 kg/m³, and a melting point of 150-300 degrees Celsius. Material in such a range may provide an appropriate balance of strength and flexibility for decorative light string applications. Further, as will be explained further below, such properties allow for deformation of reinforcing strand **102** during the manufacturing assembly process.

In an embodiment, wherein reinforcing strand **102** comprises primarily a PET material, strand **102** comprises an elongation at break of 300%, or may comprise an elongation range of 200% to 400%, and a tensile strength of 55 MPa (7,977 psi). Herein, tensile strength refers to its ordinary meaning as understood in the field of conductive wires, including tensile strength being the maximum amount of stress that wire **100** can withstand before failing or breaking, while being stretched or pulled axially along axis A (along a length of wire **100**) by opposing axial forces labeled F1 and F2 in FIG. 3.

In another embodiment wherein strand **102** comprises a PET material, an elongation property of strand **102** ranges from 200% to 400%, and a tensile strength ranges from 45 to 65 MPa. In an embodiment, the elongation of strand **102** may be less than an elongation of conductor strand **104**. In another embodiment, the elongation of a strand **102** may be approximately the same as, or greater than, a conductor strand **104**. In an embodiment, the tensile strength of a strand **102** may be less than the tensile strength of a conductor strand **104**. In another embodiment, the tensile strength may be approximately the same as, or greater than, a conductor strand **104**. In an embodiment, the elongation of a strand **102** may be less than the overall elongation of reinforced wire **100**. In another embodiment, the elongation may be approximately the same as, or greater than, reinforced wire **100**. In an embodiment, the tensile strength of a strand **102** may be less than the overall tensile strength of reinforced wire **100**. In another embodiment, the tensile strength may be approximately the same as, or greater than, reinforced wire **100**.

Conductor strands **104** may comprise any number of known conductive materials, including metals and metal alloys, such as copper, aluminum, steel, nickel, aluminum, and so on. Embodiments of alloys may include copper aluminum alloy, copper steel alloy, and so on. In an embodiment, one or more conductor strands comprise soft-annealed copper strands, which may be uncoated, or in some embodiments, coated with tin. Conductor strands **104** comprised of copper, including comprised primarily of copper, provide not only superior tensile strength, but also superior ductility properties as compared to conductor strands **104** comprising other metals, such as aluminum. A relatively higher ductility deriving from the use of copper conductor strands **104**, in combination with a polymer reinforcing strand **102**, allows deformation, particularly elongation when wire **100** is subjected to tensile stress. Such a feature provides advantages in decorative lighting. In contrast, stranded conductors commonly used in overhead power line applications typically rely on aluminum conductors having low ductility, resulting in low elongation. In such an application, sagging of the heavy power lines/conductors is a concern, and the desirable low ductility or inability to elongate, is an important consideration. On the other hand, in decorative lighting, the ability of a wire to deform or elongate (relatively high ductility, e.g., the ductility of copper) may be advantageous. For example, when subjected to a tensile stress or force, wire **100** may elongate rather than break, thereby preventing exposure of conductor strands **104**,

and preventing a potentially hazardous situation. Elongation properties of reinforced decorative lighting wire **100** are discussed further below.

Further, properties of high tensile strength, flexibility, and the ability to stretch or elongate when subjected to axial pulling may be advantageous for reinforced wire **100** when applied to a decorative lighting apparatus. Unlike cables and wires used in overhead power transmission applications, wires used in decorative lighting applications tend to be supported over much of their length. For example, decorative light strings applied to trees, such as Christmas trees, are generally affixed to the branches of the tree and are well supported, with only very short runs of wire that are unsupported. Conversely, in overhead power transmission applications, extremely long lengths of wire are unsupported between power poles. Consequently, the materials and properties of cables and wires for such power transmission applications may be significantly different than those of reinforced decorative lighting wire **100** as described herein.

In addition to ductility, tensile strength of conductor strands **104** and associated conductor layers **106** and **108**, as well as overall tensile strength of reinforced wire **100** remains a consideration. In an embodiment of reinforced wire **100** comprising soft-annealed copper conductor strands **104**, a tensile strength of each copper strand **104** will have a higher tensile strength, for example, ranging from 200-250 N/mm², as compared to aluminum alloys, for example, 100 N/mm². In an embodiment, each conductor strand **104** has a tensile strength that is less than a tensile strength of reinforcing strand **102**. In one such embodiment, conductor strands **104** comprise a copper material, and reinforcing strand **102** comprises PET.

In an embodiment, each conductor strand **104** comprises a continuous, solid-core strand, though the entire wire **100** comprises a multi-stranded wire. In other embodiments, each conductor strand **104** may comprise multiple, individual strands. In an embodiment, all strands have approximately the same average diameter.

In a stranded conductor embodiment of wire **100**, individual conductor strands comprise 27 to 36 AWG copper conductor strands. In an embodiment, conductor strands comprise 27 AWG strands. In an embodiment, conductor strands comprise copper strands having diameters measuring, on average, 0.16 mm (34 AWG, or 0.16AS). In other embodiments, copper strands comprise other diameters, including strands that have average diameters of 0.16 mm, or average diameters of approximately 0.16 mm, such as 0.16 mm \pm 10%. In another embodiment, average diameters of copper strands used in a single wire **100** range from 0.15 mm to 0.16 mm, or in another embodiment 0.25 mm \pm 10%. In decorative lighting applications, a relatively wide range or tolerance in strand diameter may be sufficient due to a common practice of operating decorative light strands at currents significantly below maximum safe ampacity limits. Conductor strands **104** may comprise copper strands complying with ASTM B 3-90 standards.

Conductor strands **104** extend axially along Axis A, and may or may not be twisted about reinforcing strand **102** or other conductor strands **104**.

Conductor strands **104** may generally be cylindrical, presenting a generally circular cross section, though in other embodiments, each strand **104** may present other cross-sectional shapes.

The number of conductor strands **104** may vary based on a combination of factors, including desired conductive properties, and mechanical design characteristics. For example, for a 22 AWG equivalent wire, which in the decorative lighting

industry may typically comprise 16 copper strands, reinforced decorative-lighting wire **100** may also comprise 16 conductor strands. In another embodiment reinforced wire **100** may be equivalent to 25AWG in its current-carrying capability (maximum of 0.73 A), and may comprise 8 conductor strands, which in an embodiment comprises (8) 0.16 mm diameter strands. In other embodiments of 25 AWG equivalent wire, reinforced wire **100** may include 8-10 conductor strands **104**; in an embodiment, each conductor strand **104** may have a diameter averaging 0.16 mm, or alternatively, 0.157-0.154 mm.

In other embodiments of wire **100**, which in an embodiment may comprise 24 AWG equivalent wire, reinforced wire **100** may include 8 conductor strands **104**; in an embodiment, each conductor strand **104** may have a diameter averaging 0.16 mm, or alternatively, 0.157-0.154 mm.

In embodiments, the above configurations of strands **104** may be combined with polymer reinforcing strands **102** sized to fall within a range of 1000 to 1500 Denier.

The number of conductor strands **104** may be greater or fewer than that of an equivalent wire having similar conductive properties, though it will be understood that particular embodiments of wire **100** are intended to match the electrical or conductive properties of equivalent standard wires described by the American Wire Gauge standard, e.g., 22 AWG wire, such that even if the number of strands is not equal to the number of strands in an equivalent standard wire, the size of each conductor strand **104** will be increased or decreased to maintain electrical equivalence. An embodiment of a reinforced decorative wire **100** having electrical properties similar or equivalent to a 22 AWG wire will be described below to further clarify and emphasize the above.

Referring also to FIG. 4, in the embodiment depicted, first conductor layer **108** is formed of multiple conductor strands **104** twisted about centrally-positioned reinforcing fiber **102**. In the depicted embodiment, first conductor layer **108** comprises five conductor strands **104**. In other embodiments, first conductor layer **108** comprises more or fewer strands. In an embodiment, the number of strands **104** in first conductor layer **108** ranges from three strands to eight strands.

Strands **104** extend axially along Axis A and in an embodiment, are twisted about reinforcing strand **102**. As depicted, strands **104** are helically twisted about reinforcing strand **102** in a counter-clockwise direction, though in other embodiments, strands **104** may be twisted or wrapped about reinforcing wire **102** in a clockwise direction.

Central axes of conductor strands **104** are depicted in FIGS. 3, 4A and 4B by arrows B1-B5 (first layer **108**) and C1-C11 (second layer **110**).

The twist or “pitch” of conductor strands **104** may be defined by a “length of lay”, or the length of conductor strand **104** required to turn a full rotation, or turn 360 degrees. As compared to standard gauge wire having equivalent electrical properties, wire **100** of the claimed invention may have lesser lengths of lay when the same number of conductor strands **104** are used. For example, in an embodiment of a 22 AWG equivalent wire, a length of lay of a conductor strand **104** of first layer **108** is approximately 18.5 mm, as compared to approximately 32 mm for an equivalent standard 22 AWG wire commonly used for decorative lighting. The additional twists per unit of length, or decreased length of lay provides axial reinforcing strength in addition to the reinforcing strength added by reinforcing strands **102**.

Furthermore, the shorter length of lay may allow further stretching and elongation of wire **100** without breakage when subjected to axial opposing forces, such as F1 and F2 as depicted in FIG. 3.

11

In an embodiment, conductor strands **104** of layer **108** each have an approximately equal length of lay, though in other embodiments, including some described further below, conductor strands **104** may have different lengths of lay.

Additionally, unlike typical wires used in decorative lighting that comprise only conductive strands, i.e., no reinforcing strand, the use of one or more reinforcing strands **102** in wire **100** may allow for some slight radial compression of strands **102** by conductor strands **104** when wire **100** is subjected to axial forces. This provides the added advantage of allowing wire **100** to elongate even further than a typical decorative lighting wire of a similar wire gauge and ampacity.

Second conductor layer **110** is formed on first conductor layer **108**, and also comprises a plurality of conductor strands **104**. In an embodiment, and as depicted, second conductor layer **110** comprises eleven conductor strands **104**. In other embodiments, second conductor layer **110** comprises more or fewer strands **104**. In an embodiment, the number of conductor strands **104** in second layer **110** ranges from four strands to 30 strands.

Strands **104** extend axially along Axis A, and are adjacent strands **104** of first layer **108**. In an embodiment, strands **104** of second layer **110** are adjacent to, and twisted about first layer **108**. As depicted, strands **104** are twisted about layer **108** and its strands **104** in a counter-clockwise direction. As such, in an embodiment, conductor strands **104** of second conductor layer **110** twists in the same direction as the direction that conductor strands **104** of second conductor layer **108** twist. In other embodiments, strands **104** may be twisted over layer **108** in a clockwise direction, and may twist in a direction opposite to a twist direction of first conductor layer **110**. Strands **104** forming conductor layer **108** generally are positioned adjacent one another.

In an embodiment, conductor strands **104** of layer **110** each have an approximately equal length of lay, though in other embodiments, including some described further below, conductor strands **104** may have different lengths of lay.

Insulating layer (or jacket) **106** wraps about second conductive layer **110**, covering and insulating conductor strands **104** and reinforcing strand **102**. Insulating layer **106** may comprise any of a variety of known insulating materials, including polymers such as PVC, PE, thermoplastics, and so on. In addition to providing insulative properties, insulating layer **106** may add mechanical strength through its other properties. In an embodiment, insulating layer **106** has a minimum elongation percentage of 150%. In an embodiment, insulating layer **106** comprises a polymer having a composition different than the polymer comprising reinforcing strand **102**.

Referring still to FIGS. **3** and **4**, in an embodiment, wire **100** comprises a reinforced 22 AWG-electrically-equivalent wire comprising a single reinforcing strand **102** extending axially along a center of wire **100**, surrounded by 16 twisted conductor strands **104**, and overlaid with an insulating jacket layer **106**. The 16 conductor strands **104** comprise first conductive layer **108**, consisting of 5 conductive strands **104**, and second conductive layer **110**, consisting of 11 conductive strands **104**. In an embodiment, reinforcing strand **102** comprises PET material in the form of a 1500 Denier strand; conductor strands **104** comprise primarily copper; and insulating layer **106** comprises PVC.

Each conductive strand **104** defines an approximately 0.16 mm diameter, circular or round wire, such that the equivalent cross-sectional area of the conductive portion of wire **100** is approximately the same as a standard 22 AWG wire, also denoted as 16/0.16AS, meaning 16 strands of 0.16 mm diameter conductor strands. In this embodiment, the resistivity

12

ranges from 54 to 57 ohms/km. In an embodiment, the resistivity is 56.8 ohms/km or less. In an embodiment, the resistivity is substantially 55 ohms/km.

The length of lay, sometimes referred to as lay of strand, of each conductor strand **104** of first layer **108**, in an embodiment is 32 mm or less. In an embodiment, the length of lay of conductor strand **104** of first layer **108** ranges from 15 mm to 25 mm. In an embodiment, the length of lay of conductor strands **104** of first layer **108** is approximately 18.5 mm. In an embodiment the length of lay of all conductor strands **104** of first layer **108** are approximately the same. In an embodiment, a lineal length of each strand per unit length is within 5% of an average lineal length (note: the lineal length of a strand will be longer than a unit length due to the helical twisting of a wire, e.g., a 1 foot length of wire **100** will include strands **104** having lineal lengths longer than 1 ft. In other embodiments, the lineal length of individual strands **104** may vary more substantially per unit length of wire **100**, particularly when lengths of lay of individual strands **104** are allowed to vary from strand to strand.

The length of lay of conductor strands **104** of second conductive layer **110** may be the same as conductor strands **104** of first conductor layer **108**, or in some embodiments, may be different. In an embodiment a length of lay of conductor strands **104** of second layer **110** is 32 mm or less. In an embodiment, the length of lay of conductor strand **104** of second layer **110** ranges from 15 mm to 25 mm. In an embodiment, the length of lay of conductor strands **104** of second layer **110** is substantially 18.5 mm. In an embodiment, lengths of lay of conductor strands **104** of both layers **108** and **110** are, on average, approximately 18.5 mm. In an embodiment, the direction of twisting is the same, as depicted in FIG. **3**.

In an embodiment, including an embodiment of 22 AWG reinforced wire **100**, insulation layer **106**, comprising primarily PVC material, has a minimum thickness of 0.69 mm. In an embodiment, insulation **106** comprises a thickness ranging from 0.69 mm to 1.0 mm. In an embodiment, an average thickness of insulating layer **106** has an average thickness of 0.76 mm or greater. In one such embodiment, insulating layer **106** has an average thickness of 0.84. In an embodiment insulating layer **106** has an insulation resistance of at least 225 M Ω /Kft.

In an embodiment, the overall diameter of wire **100** in 22 AWG ranges from 2.40 to 2.70 mm. In an embodiment, an average overall diameter is approximately 2.6 mm; in an embodiment, an average overall wire **100** diameter is 101 mil.

With respect to elongation, in an embodiment, wire **100** has an elongation of 150% or greater. In an embodiment, the elongation of wire **100** ranges from 150% to 400%. In one embodiment, wire **100** exhibits 300% elongation, significantly longer than standard, all-copper multi-stranded 22 AWG CXTW wire.

With respect to tensile strength, embodiments of wire **100** have an improved tensile strength, which in one embodiment includes a tensile strength of 1,500 PSI or greater. In an embodiment, the tensile strength ranges from 1,500 PSI to 4,000 PSI, in another embodiment, the tensile strength ranges from 2,500 to 3,500 PSI. Such a range may provide sufficient strength for various decorative lighting applications, including trees, net lights, sculptures, and so on. In some applications where wires are affixed tightly to supporting structure, such as trees of metal frames, a required tensile strength may be on the lower end of the range, while wires of light strings that are not affixed to, or are less supported, may require higher tensile strength due to possible pulling or yanking by a user.

Another method of describing and measuring “strength” of a wire, including a reinforced wire **100**, and as commonly used in decorative lighting is to measure an axially-applied pulling force required to cause the wire to begin to break, such that an outer insulation shows breakage, or an inner conductor shows breakage. In an embodiment, reinforced wire **100** may withstand axial pulling forces of various ranges depending on the particular reinforced wire **100** configuration.

In an embodiment, reinforced wire **100** may withstand a minimum axially-applied pulling force ranging from 22 lbf to 46 lbf. In one such embodiment, reinforced wire **100** comprises an ampacity equivalent to a 22AWG wire, and can withstand a minimum 22.4 lbf without breaking; in another embodiment, reinforced wire **100** comprises an ampacity equivalent to a 20AWG wire, and can withstand a minimum 30 lbf without breaking; in another embodiment, reinforced wire **100** comprises an ampacity equivalent to a 18AWG wire, and can withstand a minimum 46 lbf without breaking.

In another embodiment, reinforced wire **100** comprises 7-10 conductor strands **104** defining a range of minimum axial pulling force ranging from 22.4 lbf to 46 lbf. In one such embodiment, reinforced wire **100** comprises 8 conductor strands and has a minimum axial pulling force at breakage of 46 lbf; in one such embodiment, each conductor strand **104** may have an average diameter in the range of 0.15 mm to 0.17 mm; alternatively, each conductor strand **104** may have an average diameter of 0.154 mm to 0.157 mm. Such ranges accommodate expected current flows in various decorative lighting applications, while offering substantial overall tensile strength.

In an embodiment, wire **100** includes a 1500 Denier PET reinforcing strand **102** extending axially along Axis A, 16 copper conductor strands of 0.16 mm average diameter (5 first layer **108** strands and 11 second layer **110** strands) having a 55 Ω /km resistivity, and insulating layer **106** of PVC material. In one such embodiment, elongation is greater than 300% (in an embodiment is 306%), with a tensile strength of 2800 PSI, requiring a force of approximately 21 kg to break. Such a wire may be used as a substitute for standard 22 AWG wire, including 22 AWG CXTW wire for improved decorative-lighting applications.

Referring to FIG. 4B, the wire **100** of FIGS. 3 and 4A is depicted again, but in this case, the configuration of wire **100**, namely the relative positions of conductor strands **104** and reinforcing strand **102**, are somewhat different. In an embodiment, because of the malleable properties of reinforcing strand **102**, including the fibrous nature, pliability, and so on, during manufacturing of wire **100**, reinforcing strand **102** may be deformed somewhat, which in turn, may cause first and second layer strands **108** and **110** to move relative to one another, and relative to reinforcing strand **102**. As depicted in FIG. 4b, at a particular cross section, reinforcing strand **102** does not comprise a circular cross section, but rather, comprises another shape due to deformation. Such “deformation”, may actually be the result of radial displacement of individual strands or fibers of reinforcing strand **102** that occur when layers of conductor strands **104** are wound or twisted about generally central reinforcing strand **102**. As will be explained further below with respect to FIGS. 7-13B, such variation, may be caused by radial movement or deformation of reinforcing strand **102** and may vary axially, or along a length of wire **100**. Consequently, while FIG. 4A depicts an ideal embodiment of wire **100** in cross section, in other embodiments wire **100** may comprise the relative structure depicted in FIG. 4B, or some other similar structure. As such, embodiments of reinforced decorative wire **100** may include a central reinforcing strand that may only be substantially, or

mostly centrally located. Further, in such an embodiment, conductor strands **104** may not be evenly spaced about reinforcing strand **102**, as depicted, nor will strands **104** of layer **110** be evenly spaced about layer **108**.

As described above, embodiments of wire **100** are not limited to the 1-5-11 configuration described above (1 reinforcing strand **102**, 5 first layer conductors **105** and 11 second layer conductors **110**).

Although embodiments of reinforced wire **100** may comprise multi-layer conductor strand embodiments, such as those depicted in FIGS. 3-4B, embodiments of reinforced wire **100** may include only a single layer of conductor strands **104** and a single reinforcing strand **102**. Some such embodiments will be further described below, and may include the following embodiments: 10 conductor strands **104** with a single reinforcing strand **102**, which in an embodiment includes 0.15-0.16 mm diameter strands **104** and 1000 Denier strand **102**; 9 conductor strands **104** with a single reinforcing strand **102**, which in an embodiment includes 0.15-0.16 mm diameter strands **104** and 1000 Denier strand **102**; 8 conductor strands **104** with a single reinforcing strand **102**, which in an embodiment includes 0.15-0.16 mm diameter strands **104** and 1500 Denier strand **102**; and 7 conductor strands **104** with a single reinforcing strand **102**, which in an embodiment includes 0.15-0.16 mm diameter strands **104** and 1500 Denier strand **102**. In some such 7, 8, 9, or 10 stranded embodiments, when fewer conductor strands **104** are used, a larger diameter and stronger reinforcing strand **102** may be included to make up for the decrease in tensile strength due to fewer conductor strands **104**.

Referring to FIG. 5, another embodiment of reinforced decorative-lighting wire **100** is depicted. This alternate embodiment of wire **100** is substantially the same as the embodiment depicted in FIGS. 3 and 4, and described above, with the exception of reinforcing strands **102**. In this embodiment, rather than a single reinforcing strand **102**, wire **100** includes three reinforcing strands **102a**, **102b**, and **102c**. Reinforcing strands **102a-102c** extend axially through the center portion of wire **102**. Strands **102a-102c** may or may not be twisted about one another. Twisting multiple strands **102** may provide an additional reinforcing strength.

In an embodiment, fewer than three strands **102**, namely two strands may be used. In other embodiments, greater than three strands **102** may be used.

In an embodiment, the cross-sectional area of the three reinforcing strands **102a**, **102b**, and **102c** is equivalent to the 1500 Denier strand described above with respect to the embodiment of FIGS. 3 and 4. In other embodiments, the size of reinforcing strands **102** may be larger or smaller, depending on desired wire **100** strength, with larger size strands and/or more strands **102** being used for stronger reinforced wire **100**.

Referring to FIG. 6, another embodiment of wire **100** is depicted. In this embodiment, wire **100** still includes multiple reinforcing strands **102**, first conductor layer **108** comprising multiple conductors **104**, second conductor layer **110** comprising multiple conductors **104**, and outer insulating layer **106**. In the depicted embodiment, first conductor layer **108** includes five conductors **104** and second conductor layer **110** includes eleven conductors **104**, similar to the embodiments described above with respect to FIGS. 3-5. However, in this embodiment, wire **100** includes four reinforcing strands **102**.

As depicted, first conductor layer **108** actually includes a single, central conductor **104a** surrounded by four outer conductors **104b**, **104c**, **104d**, and **104e**. Between each outer conductor **104b**, **104c**, **104d** and **104e** is a reinforcing strand

102. Second conductor layer 110 is adjacent both the four conductors 104b-e, and the four reinforcing strands 102.

Embodiments of the invention are not intended to be limited to the specific patterns and structures depicted in FIGS. 3-6. It will be understood that the number of conductors 104, number of reinforcing strands 102, and their combinations, may vary.

Referring to FIG. 7, a simplified block diagram of an embodiment of a manufacturing assembly process 130 of the invention for manufacturing reinforced decorative lighting wire 100 is depicted. In an embodiment, metal rod 131, which may comprise a copper rod, is drawn to a smaller diameter, as will be understood by those skilled in the art, at drawing process 132. Drawing process or step 132 may include multiple stages of drawing, such as two stages of drawing, to reduce the diameter of rod 131 down to a small diameter of a conductor strand 104. At step 133, heat treating or annealing equipment may be used to treat conductor strands 104 to improve ductility of strands 104. Although a single rod 131 is depicted as fed into process 132 and 133, it will be understood that multiple rods 131 may be drawn and heated simultaneously.

In an embodiment, at step 134, a "stranding process" twists multiple conductor strands 104 about one or more reinforcing strands 102. In an embodiment, multiple spools feed multiple conductor strands 104 to perforated plate 135, and one or more spools (labeled "RS" to represent reinforcing strand 102) feeds one or more reinforcing strands 102.

Referring also to FIG. 8, in an embodiment, perforated plate 135 includes multiple apertures 136, including a central aperture 136a. Conductor strands 104 are threaded through various apertures 136, as are one or more reinforcing strands 102. In the embodiment depicted, only one reinforcing strand 102 is used, and is located centrally, such that it passes through aperture 136.

During the stranding process, in an embodiment, conductor strands 104 and reinforcing strand 102 are fed to rotating cylinder 137, which may comprise a capstan 137, which rotates, causing conductor strands 104 and strand 102 to be twisted about one another. The selection of the apertures 136 through which the conductors are threaded, at least in part, determines the nature of the resulting wound or twisted strand combination. In the embodiment depicted, eight conductor strands 104 are twisted about a central reinforcing strand 102. Conductor strands 104 pass through one or more apertures 136 in FIG. 8, while reinforcing strand 102 passes through central aperture 136a. Such an embodiment results in a predetermined pattern of a single conductor strand 104 layer about a single, central reinforcing strand 102.

As will be described further below with respect to FIGS. 9A-13B, other patterns defined by selection of apertures 136 may be used to create other embodiments of multi-stranded wire 100 having. In an embodiment, more than one reinforcing strand may be used, and more than one layer of conductor strands 102 may be used.

After passing through apertures 136 of plate 135, strands 104 and 102 couple with a rotating structure, such as capstan 137, which rotates, causing strands 104 to be twisted about strand 102.

In embodiment process 130 includes a re-heat process step 138. Re-heat process step 138 raises the temperature of conductor strands 104 and reinforcing strand 102 prior to extrusion step 139. The increased temperature aids in the extrusion process.

At process step 139, insulative layer 106 is added to the twisted assembly of strands 104 and 102 via an extrusion process. As will be understood by those skilled in the art, in an

embodiment, insulative material is fed into an extruder, heated, and drawn or pushed through a die onto the exterior of the twisted assembly of strands 104 and/or reinforcing strand 102 to form layer 106, thereby creating finished reinforced wire 100.

It will be understood that other steps or processes may be used to manufacture and assemble embodiments of reinforced wire 100. Referring to FIGS. 9A-13B, a number of embodiments of reinforced wire 100 are depicted. FIGS. 9A, 11A, 12A, and 13A depict patterns of conductor strands 104 in relation to one another and to a central reinforcing strand 102 at a pre-assembly, or initial positional relationship, prior to completion of the stranding process. Strands 104 and 102 are depicted in cross section. In each embodiment, conductor strands 104 are arranged circumferentially about reinforcing strand 102. In an embodiment, strands 104 are arranged equidistantly about strand 102, or substantially equidistantly, about reinforcing strand 102. In other embodiments, conductor strands 104 may not be circumferentially arranged equidistantly.

It will be understood that although strands 104 are depicted as having circular cross sections in this view, during actual assembly, a cross-sectional view of strands 104 after some twisting of strands 104 would cause a shape of each strand in cross section to appear somewhat non-circular, similar to the cross-sectional shapes of strands 104 depicted in FIGS. 4 and 5. For the sake of illustration and simplicity, strands 104 are depicted as having circular cross-sectional shapes.

In contrast, FIGS. 9B, 11B, 12B, and 13B depict embodiments of wire 100 in cross-section after assembly via manufacturing assembly process 130. As depicted, the final positions or final positional relationships of conductor strands 104 relative to reinforcing strand 102 are different as compared to the initial positions of conductor strands 104 relative to reinforcing strand 102.

In the embodiments of reinforced wire 100 depicted in FIGS. 9B-13B, the shape of reinforcing strand 102 as viewed in cross-section, i.e., radially, has been transformed from a generally circular shape to an asymmetrical shape due to pressure and heat applied to reinforcing strand 102 during the manufacturing process. Dots, or small solid circles in the Figures in each conductor strand 104 indicate central axes of each conductor strand 104. Further, the final, assembled positions of conducting strands 104 relative to reinforcing strand 102, and relative to one another are also changed as compared to an initial or pre-assembly position. The result is a change from a generally symmetrical configuration to an asymmetrical configuration.

Referring to FIGS. 9B and 10, an embodiment of reinforced wire 100 is depicted in further detail. As viewed in a cross-section normal to axis A of wire 100, reinforcing strand 102 defines an asymmetrical shape. An axis passing through the area centroid of reinforcing strand 102 (indicated by the point at which axis A' intersects reinforcing strand 102) is defined as a central reinforcing-strand axis A'. Due to the deformation of reinforcing strand 102 during the manufacturing process, central reinforcing-strand axis A' is offset radially from wire axis A.

The amount that axis A' is offset from axis A may vary from embodiment to embodiment, depending on a number of factors including material properties and manufacturing process settings. With respect to materials, softer, more pliable materials used for reinforcing strands 102 may result in a more conformable, malleable, or deformable reinforcing strand 102. In an embodiment, reinforcing strand 102 comprises a PET material with one or more of the properties described above. Manufacturing process settings include pressure

applied by conductor strands **104** onto reinforcing strand **102** during the stranding process, conductor strand **104** and reinforcing strand **102** material temperature during stranding, as well as pre-heat and extrusion process temperatures.

In an embodiment, the offset of axis A' to axis A may vary from 1% to 50%; in another embodiment, the offset may range from 5% to 35%.

The asymmetrical shape of reinforcing strand **102** may vary along axis A', as may the offset of axis A' from axis A.

As depicted, deformation of reinforcing strand **102** may result in conductor strands **104** being wound or twisted asymmetrically about the circumference of reinforcing strand **102**, such that some space may exist between strands **104**. In such an embodiment, portions of outer insulating layer **106** may be extruded directly onto exposed portions of reinforcing strand **102** that are not covered by a conductor strand **104**. In an embodiment, the contact between layer **106** and reinforcing strand **102** creates a strengthening bond between the materials of layer **106** and reinforcing strand **102** that may be stronger than the bond created between layer **106** and metal conductor strands **104**, thereby adding further tensile strength to reinforced wire **100**. In one such embodiment, insulating layer **106** comprises a first polymer material, and reinforcing strand **102** comprises a second, different, polymer material. In one such embodiment, reinforcing strand **102** comprises a PET material, and insulating layer **106** comprises a PVC material.

In one such embodiment, reinforced wire **100** comprises a longitudinally-extending reinforcing strand **102** comprising a first polymer material, a plurality of conductor strands **104** helically wound about reinforcing strand **102**, and outer insulating layer **106** comprising a second polymer material, the outer insulating layer adjacent to, and in contact with, one or more of conductor strands **104**. The plurality of conductor strands **104** define a gap between two conductor strands **104**, and outer insulating layer **106** is in direct contact with the portion of the reinforcing strand **102** in the gap such that the second polymer material is bonded to the first polymer material.

In one such embodiment, conductor strands **104** are asymmetrically wound about the reinforcing strand such that central longitudinal wire axes of the conductor strands **104** are not equidistantly spaced about the central longitudinal wire axis A.

In an embodiment, the gap as measured radially from a first conductor strand **104** to a second conductor strand **104** along an axis normal to the central longitudinal axis of the wire, and defines a width that is greater than 10% of a diameter of any of the plurality of conductor strands **104**, but not greater than a diameter of reinforcing strand **102**.

The asymmetrical winding of conductor strands **104** about deformable reinforcing strand **102** may result in the lineal lengths of each conductor strand **104** varying per unit length of finished wire **100**. In other words, some conductor strands **104** may be wound slightly differently about strand **102**, e.g., different lengths of lay, different helical radius, etc., such that some strands may be slightly longer than others when straightened. While such variance may affect final ampacity of wire **100**, for decorative lighting applications, such variances in ampacity may be tolerated. Further, on average, variances in lengths of strands **104** may average out such that overall ampacity is not affected, or not greatly affected.

Further, length of lay may also vary from strand **104** to strand **104** in some embodiments, such that a length of lay of all strands **104** in a reinforced wire **104** may not be equal.

Further, the deformable properties of reinforcing strand **102** may allow some portions of some or all conductor strands

104 to embed in part into reinforcing strand **102**, which results in greater contact area between some conductor strands **104** and reinforcing strand **102**, thereby increasing the structural strength, including tensile strength, of reinforcing wire **102**.

In addition to the additional structural enhancements to reinforced wire **100**, manufacturing process **130** and its resultant reinforced wire **100** having an asymmetrical configuration provides a number of manufacturing benefits, including ease of manufacturing and cost savings. Unlike wires and cables known in the art, the asymmetrical reinforcing wire configuration **100** herein does not require that all conductor strands **104** be precisely wound about reinforcing strand **102**, such that process **130** may be completed quicker and with less waste.

Referring specifically to FIGS. **9B**, **11B**, **12B**, and **13B**, in an embodiment a set of reinforced decorative lighting wire **100**, outside diameters of one or more wire **100** configurations may be substantially equal. In an embodiment, the assembled 7, 8, 9 and 10 conductor strand reinforced wire **100** embodiments all have substantially the same outside diameter. In an embodiment, such an outside diameter may be 2.2 mm+/-0.2 mm, though it will be understood that other embodiments may have other outside diameters based upon desired insulating layer **106** thickness, overall strength requirements, and so on. In other embodiments, 7 and 8 conductor embodiments may have the same outside diameter, while 9 and 10 conductor strand embodiments have substantially the same outside diameter. In an embodiment, 7, 8, and 9 conductor strand wires **100** have substantially the same outer diameter, which in an embodiment may be 2.22 mm+/-0.5 mm.

In an embodiment of a set having substantially the same outer diameters, yet different numbers of conductor strands **104** of a same or similar diameter, the overall outer diameter of the wire **100** may be controlled by manipulating the thickness/diameter of reinforcing strand **102** and/or the thickness of insulating layer **106**. In an embodiment, the outer diameter is held constant for wires **100** having different quantities of strands **104** by decreasing the diameter of reinforcing strand **102** when increasing the number of strands **104**.

For example, an 8-conductor strand wire **100** having a 1500 Denier reinforcing strand and an outer layer **106** may have the same wire diameter as a 9-conductor strand wire **100** having a 1000 Deneier reinforcing strand **102** and an outer layer **106**. The difference in diameters being attributed in whole, or in part, to the change in size of reinforcing strand **102**. In such an embodiment, an average thickness of insulating wire **106** may be substantially the same for both wires **100** having a different number of strands **104**.

One advantage of having substantially the same outside diameter on different configurations of reinforced wire **100** is that a common lamp holder **150** (see FIG. **14** below), may be used with more than one wire **100** configuration, rather than requiring a larger lamp holder be used for wires having more conductors and a smaller lamp holder be used for wires having fewer conductors.

In another set of reinforced wires **100**, a thickness of reinforced wire **100** insulating layer **106** is substantially the same independent of the number of conductor strands **104** of the wire **100**. In an embodiment, an insulating layer **106** is the same thickness for reinforced wire **100** comprising 7, 8, 9, or 10 conductor strands **104**. In one such embodiment, an average thickness of layer **106** is within a range of 0.75 to 0.81 mm; in one such embodiment, an average thickness of layer **106** is within the range of 0.79 mm+/-2 mm.

Referring generally to FIGS. 14A-33, reinforced decorative lighting wire 100 may be used to create a variety of reinforced decorative lighting structures, including reinforced light strings, reinforced net lights, lighted trees with reinforced decorative lighting, outdoor sculptures with reinforced decorative lighting, and so on.

Several embodiments of reinforced decorative light strings and structures of the present invention are depicted in FIGS. 14A-24.

Referring specifically to FIG. 14A, reinforced decorative light string 140 is depicted. In this embodiment, reinforced decorative light string 140 comprises optional power plug 142, first power-terminal wire 144 (also referred to herein as a first power wire 144), second power-terminal wire 146 (also referred to herein as a second power wire 146), multiple light-connecting wires 148a-148o, and a plurality of lamp assemblies 150a-150p. Lamp assembly 150a comprising a "first" lamp assembly, lamp assembly 150p comprising a "second" or "last" lamp assembly, and lamp assemblies 150b-150o comprising "intermediate" lamp assemblies (located "intermediate" or between lamp assemblies 150a and 150p). In an embodiment, first power-terminal wire 144, second power-terminal wire 146 and light-connecting wires 148 all comprise reinforced decorative lighting wire 100. In another embodiment, only some of wires 144, 146, and 148 comprise reinforced decorative lighting wire 100, while some of wires 144, 146, and 148 comprise traditional, non-reinforced wire having the same or similar conductive properties of reinforced lighting wire 100. In one such embodiment, first power-terminal wire (or "lead") wire 144 and second power-terminal ("return") wire 146 comprise reinforced wire 100, while light-connecting wires 148 comprise traditional, non-reinforced wire. Such a structure may be particularly suited for use on a lighted artificial tree where wires 144 and 146 connect to a tree trunk and require greater strength. In another such embodiment, wires 144, 146, and one or several wires 148 may comprise reinforced lighting wire 100. In one such embodiment for use on a lighted artificial tree, wires 148 that span or crossover from one branch to another branch may comprise reinforced wire 100, while other wires 148 adjacent a single branch, do not comprise reinforced wire 100.

Power plug 142 may comprise a traditional power plug comprising housing 156, first power terminal 158 and a second power terminal 160 for plugging into an outlet of an external power source, which may be an alternating-current (AC) power source. In an embodiment, power plug 142 may include a power transformer or power adapter that transforms the external source power to a lower voltage. For example, power plug 142 may transform a received 110 or 120 VAC power to 9 VDC (volts direct-current). In another embodiment, housing 156 and terminals 158/160 may comprise different shapes and sizes appropriate for a particular application. For example, if reinforced decorative light string 140 is used on a lighted tree (as will be described further below), a non-traditional plug and terminal arrangement may be used.

In other embodiments, reinforced decorative light string 140 may not include power plug 142. In one such embodiment, first and second power wires 144 and 146 may connect directly to a wiring harness of a lighted tree, or connect to a wiring harness or external source using individual wire connectors for each terminal or power wire 144 and 146.

In an embodiment, first power-terminal wire 144 is coupled to power plug 142 and in electrical connection with first power terminal 158. Second power-terminal wire 146 is also coupled to power plug 142, but electrically connected with second power terminal 160. For the particular electrical configuration depicted, first power-terminal wire 144 com-

prises a first electrical polarity, and second power-terminal wire 146 comprises a second, opposite, electrical polarity. In the case of DC power, a first electrical polarity may comprise a positive, while a second electrical polarity may comprise a negative polarity, or vice versa.

In the embodiment depicted, each of intermediate light-connecting wires 148, namely 148a-148o, makes an electrical connection between adjacent lamp assemblies to form a series electrical connection between lamp assemblies 150.

Although depicted as a single series circuit, in other embodiments, decorative light string 140 may comprise multiple electrical circuits, such as two or more series circuits, each series circuit in parallel with the other. In one such embodiment, and as described further below with respect to FIG. 22, first power wires 144a and 144b, and second power wires 146a and 146b will conduct current from multiple circuits, and therefore, may be configured to have a higher ampacity than individual wires 148. In one such embodiment, first power-terminal wires 144a and 144b and second power wires 146a and 146b will comprise more or larger conductor strands 104, which increase the tensile strength relative to intermediate wires 148, and as such, in an embodiment may not comprise reinforcing strands 102, thereby, may not comprise reinforcing wires 100.

Referring also to FIGS. 14B and 15, further details of the electrical connection between the wires of decorative light string 140 and lamp assemblies 148, using lamp assembly 150a as an example, are depicted.

As depicted and exemplified in the exploded view of FIG. 14B, each lamp assembly 150 includes a socket 152 and lamp element 154. As depicted, lamp assembly 150a includes socket 152a and lamp element 154. In an embodiment, lamp assembly 150 may also include an adapter or base attached to the lamp element 154.

In the depicted embodiment, lamp element 154 comprises an incandescent lamp or bulb having a filament 158 electrically connected to a first lead 160 and a second lead 162. However, in other embodiments, lamp elements 154 may comprise other types of lamp elements, including light-emitting diodes (LEDs) or LED lamps that comprise an LED chip and a pair of electrical leads in electrical connection with the LED chip.

In the embodiment depicted, reinforced decorative light string 140 comprises 16 lamp assemblies 150 (150a to 150p), however, other embodiments may include more or fewer lamp assemblies 150. In an embodiment, reinforced decorative light string 140 includes 50 lamp assemblies, intended to be connected to an AC power source, such as a 110 VAC power source, such that each lamp assembly is configured to operate at approximately 2.2 VAC.

In an embodiment, and as depicted, an end of each wire electrically connected to lamp element 154 includes a wire terminal 158. As depicted, each of wires 144 and 148a have a portion of insulation layer 106 is stripped at an end to expose conductor layer 110 and conductors 104. In an embodiment, wire terminal 158 is crimped on to the end of each wire or wire segment, such that a portion of terminal 158 is crimped onto a portion of insulation layer 106 and a portion is crimped onto, or otherwise in contact with, conductors 104, thereby forming an electrical connection between each wire terminal 158 and its respective wire 144 or 148.

Socket 152 generally comprises a generally hollow, cylindrical body having an opening at opposite ends, and comprising a polymer material. Socket 152 is configured to receive lamp element 154 at a top end 164, and when present, adapter 156. Socket 152 is also configured to receive wires 144 and 148a with their respective wire terminals 158 at bottom end

166. In an embodiment, socket 164 defines a pair of slots 168 for receiving and securing wire terminals 158 inside the cavity formed by socket 164.

Although the above description refers to wires 144 and 148a, as depicted, it will be understood that each lamp assembly 150 connects to wires 144, 146, and/or 148 in a similar manner.

Still referring to FIGS. 14A, 14B, and 15, an embodiment of the invention comprises a reinforced decorative lighting structure that includes wires 144, 146, 148, each wire having at least one crimped-on terminal 158, with each terminal 158 inserted into a lamp holder 152. In such an embodiment, the decorative lighting structure may comprise a sub-assembly of reinforced decorative light string 140 without power plug 142 and without lamp elements 154. Such a structure may be common to a variety of decorative light strings, trees with decorative lighting, net lights, sculptures or so on. Lamp elements 154 such as LEDs may be used in one embodiment, or incandescent bulbs in another embodiment. A power plug 142 may be added, and so on.

Referring to FIG. 16, an electrical schematic of reinforced decorative light string 140 is depicted. As depicted, reinforced decorative light string 140 comprises a series-connected configuration, such that each lamp element 154, including lamp elements 154a-154p, are electrically connected in series.

Comparing FIG. 14A, depicting a series-connected, reinforced decorative light string 140 of the claimed invention, to FIG. 1, depicting a prior-art decorative light string that includes standard wires twisted about one another, benefits of reinforced decorative light string 140 become apparent. As described briefly above, prior art light strings using standard, non-reinforced wire typically rely on the twisting of wires to create a stronger light string that resists breaking when subjected to axial pulling forces (see also force F1 depicted in FIG. 14A).

The use of reinforced wire 100 with its increased tensile strength alleviates the need to twist wires together, such that the “single-wire” configuration of reinforced decorative light string 140 is possible. The term “single wire” herein refers to a light string, such as reinforced decorative light string 140, that includes wires with reinforced wire 100, and only a single wire extending between, and connected to, a pair of lamp holders or sockets 152, the single wire not being twisted about another wire or a reinforcing strand. For example, and as described above, wires 148a-148o are not twisted about each other, nor are external strands twisted or wrapped about such wires.

In contrast, the “twisted pair” prior art depicted in FIG. 1 relies on twisting of wires or pairs of wires between lamp holders in order to increase overall tensile strength of the light set wiring, and to prevent wire breakage.

Although embodiments of a single-wire configuration comprise the present invention, embodiments of the present invention may also comprise a twisted-pair configuration for even further strength.

In addition to increased tensile strength and elongation, another advantage of a non-twisted-pair, or single-wire light string, such as single-wire reinforced decorative light string 140, lies in the ability of the light string to be flexibly distributed about a structure, such as an artificial tree. The decorative light string of FIG. 1 extends from one end to another in a linear fashion. In contrast, reinforced, single-wire decorative light string 140 may be flexibly adjusted to form a two-dimensional distribution, e.g., a square, circle, etc. Such flexibility allows reinforced decorative light string 140 to be attached to multiple branches and sub-branches of a tree, or

portions of a lighted sculpture, in more creative and flexible ways, and at the same time, display less wire in any particular viewed area of the tree or sculpture.

Although reinforced decorative light string 140 is depicted as a simple single-circuit, series connected light string in FIGS. 14A-16, reinforced decorative light string 140 may comprise other configurations. Such configurations include series-parallel (multiple sets of series-connected lights, the sets in parallel), parallel, or parallel-series (multiple sets of parallel connected lights, the sets connected in series) configurations, or combinations thereof. The physical wire configurations may also vary, and are not necessarily limited to single-wire configurations. A number of such embodiments are depicted and described with respect to FIGS. 17-18.

Although each light string 140 is depicted as including a power plug 142, it will be understood that embodiments of a light string 140 may not include a power plug 142. In one such embodiment, light string 140 is configured to be applied to a lighted artificial tree such that wires 144 and 146 are electrically connected to power conductors of the tree by means other than a power plug 142. In other embodiments of a light string 140, alternate types of power plugs 142 may be used, such as a locking-connector power plug 142.

Referring specifically to FIGS. 17 and 18, reinforced decorative light string 140 comprises an electrically parallel decorative light string. In the parallel embodiment depicted, decorative light string 140 comprises optional power plug 142, first power-terminal wire 144, second power-terminal wire 146, multiple light-connecting wires 148, and a plurality of lamp assemblies 170. First power-terminal wire 144, second power-terminal wire 146 and light-connecting wires 148 comprise reinforced decorative lighting wire 100. In an alternate embodiment, first power-terminal wire 144 and second power-terminal wire 146 do not comprise reinforced wire 100 due to their larger wire size and inherent strength relative to wires 148 (as similarly described above).

Although the plurality of reinforced wires 148 may be twisted for additional strength, in an embodiment, and as depicted, wires 148 may not be generally twisted about one another, though some wires 148 may cross one another, and be adjacent one another.

Lamp assemblies 170 (170a-170j) may be substantially the same as lamp assemblies 150, and connect to wires 148 and other wires in a manner substantially the same as lamp assemblies 150. In an embodiment, lamp assemblies 170 may be configured for incandescent bulbs 154, similar to lamp assemblies 150. In such a configuration, differences between lamp assemblies 150 and 170 relate to the number of wires received by each lamp assembly. As depicted, lamp assemblies 170 each receive four wires 148, with the exception of the lamp assembly 170j further from plug 142, which receives only two wires 148.

In another embodiment, lamp assemblies 170 may include lamp elements that comprise LEDs 172, rather than incandescent bulbs 154. The number of lamp assemblies 170 may vary, depending on a number of factors, including desired lamp assemblies in a single string, desired string length, tree size, and so on. In an embodiment, reinforced decorative light string 140 includes 20 to 100 lamp assemblies, though more or fewer lamp assemblies may be used.

As depicted in FIG. 18, LEDs 172 of reinforced decorative light string 140 may all be electrically connected in parallel. In one such embodiment, each LED 172 is configured to receive a low-voltage power, such as 3 VDC, though low-voltage AC power, or other voltages may also be used. Just as the lamp elements of parallel-configured reinforced decorative light string 140 are not limited to incandescent bulbs or

LEDs, so too may the power delivered to reinforced decorative light string **140** not be limited only to DC power, or to a particular voltage.

Referring to FIGS. **19-21**, lamp assemblies **170** may connect to embodiments of reinforced wire **100**, such as wires **148**, in a manner different from that as described with respect to FIGS. **14B** and **15**. In an embodiment, rather than stripping ends of wires **148** and crimping on a terminal **158**, lamp assemblies **170** may comprise wire-piercing lamp assemblies that attach to continuous wires or wire segments.

Referring specifically to FIGS. **19** and **21**, in an embodiment, lamp assembly **170** of reinforced decorative light string **140** comprises a wire-piercing lamp assembly that includes lamp holder **172**, lamp element **174**, and wire-piercing elements **176a** and **176b**. Wire-piercing elements **176a** and **176b** are in electrical connection to first and second leads of lamp element **174**. In an embodiment, lamp holder **172** includes top portion **172a** and bottom portion **172b**. Bottom portion **172b** is configured to receive and secure wires **148**. Top portion **172a** is configured to receive lamp assembly **174**, which may comprise an incandescent bulb, LED or other lamp element.

As depicted in FIG. **21**, when top portion **172b** is coupled to top portion **172a**, wire piercing elements **176a** and **176b** pierce insulating layer and make contact with conductor strands **104**, which includes making contact with one or more of layers **108** and **110**. As such, an electrical connection is made between a first lead of lamp element **174** and a wire **148**, and a second lead of lamp element **174** and a wire **148**. In such a configuration, wires **148** are continuous between lamp holders **172**, rather than comprising wire segments with ends received by lamp holders **172**.

Embodiments of wire-piercing light-assemblies are depicted and described in US 2011/0286223A1, published Nov. 24, 2011, and entitled "Wire-Piercing Light-Emitting Diode Illumination Assemblies", which is herein incorporated by reference in its entirety.

Another embodiment of a wire-piercing light assembly **170** is depicted in FIG. **20**. In this embodiment, lamp assembly **170** includes lamp element **174**, top portion **180**, insert **182**, and socket **184**. Embodiments of this wire-piercing wire-assembly and similar assemblies are depicted and described in US 2013/0163250A1, published Jun. 27, 2013, and entitled "Decorative Lamp Assembly and s Including a Lamp Assembly", which is herein incorporated by reference in its entirety. Other embodiments of wire-piercing lamp assemblies that may be used with reinforced wire **100** are depicted and described in the following publications, which are also incorporated by reference in their entireties: US 2013/0078847A1 and US 2013/0214691A1.

Referring to FIGS. **22** and **23**, another embodiment of a reinforced decorative light string **140** is depicted. In this embodiment, reinforced decorative light string **140** comprises a series-parallel-connected reinforced decorative light string.

In this embodiment, reinforced decorative light string **140** comprises optional power plug **142**, first power-terminal wires **144a** and **144b**, second power-terminal wires **146a** and **146b**, multiple light-connecting wires **148**, and a plurality of lamp assemblies **190a** to **190h**. First power wires **144** (**144a** and **144b**), second power wires **146** (**146a** and **146b**) and light-connecting wires **148** comprise reinforced decorative lighting wire **100**. In other embodiments as described below, power wires **144** and **146** do not comprise reinforced wire **100**.

Each lamp assembly **190** comprises a lamp element **154** (e.g., incandescent lamp or LED), and a lamp holder **192** or **193**. Lamp holders **192a** are configured to receive three wires,

which may be a combination of wires **144** and **148** or **146** and **148** or only wires **148**; lamp holders **193** are configured to receive two wires. As depicted, lamp assemblies **190a** (first lamp assembly), and lamp assembly **190d** comprise three-wire lamp holders **192**, while the remaining lamp holders comprise two-wire lamp holders **193**. In other embodiments, lamp assemblies **190e** and **190h** may comprise three-wire lamp holders and reinforced decorative light string **140** may include an additional first power-terminal wire and an additional second power-terminal wire connected to lamp assemblies **190e** and **190h** and to an end connector plug for connecting to another (not depicted).

In the embodiment depicted, reinforced decorative light string **140** comprises two sets of lamp elements **154**, first set **191a** and second set **191b**. Lamp elements **154** of first set **191a** are electrically connected in series; lamp elements **154** of second **191b** are electrically connected to one another; and first set **191a** is electrically connected in parallel with second set **196b**. The number of lamp elements **154** in each set may vary, and in particular, may be larger than that depicted. In an embodiment, each of first and second sets **191a** and **191b** include 50 lamp elements. In an embodiment, each lamp element is configured to receive approximately 2.2 VAC power. Further, the number of sets of lamp assemblies is not limited to two sets, and may be larger for an individual reinforced decorative light string **140** having a series parallel construction.

In an embodiment, all intermediate or shorter wires **148** may comprise reinforced wire **100**, while first and second power wires **144** and **146** do not comprise reinforced wire **100**, but rather, comprise traditional decorative lighting wire that does not include an internal reinforcing strand **102**.

In one such embodiment, each of non-reinforced first and second power wires **144** and **146** comprise more conductor strands **104** as compared to each intermediate wire **148**, or alternatively, wires **144** and **146** have a greater cross-sectional area of conductor as compared to intermediate wires **148**, which may be due to a greater current carrying requirement of power wires **144** and **146** as compared to intermediate wires **148**. This may be the case for multiple circuits of wires **148** all powered by a single set of wires **144** (**144a** and **144b**) and **146** (**146a** and **146b**). However, in an embodiment, a tensile strength or axial pulling force at breakage of wires **144** and **146** as compared to wires **148** is approximately the same. In an embodiment, approximately the same means within 10%; in another embodiment, approximately the same means within 5%; in another embodiment, approximately the same means within 1% difference between wires **144/146** and wires **148**. The advantage is that wires of the decorative lighting string **140** have substantially the same strength, regardless of whether standard wire or reinforced wire. Further, it will be understood that such configurations apply to decorative lighting strings as applied to trees, net lights, sculptures, and other decorative lighting assemblies as described herein and further below.

In an embodiment, a thickness of an insulating layer **106** of each wire **148** is approximately the same as an insulating layer of a non-reinforced wire **144** or **146**. In one such embodiment, the tensile strength of the light string **140** for wires **144/146** and wires **148** are approximately the same,

In an embodiment, an outside diameter of non-reinforced power wires **144/146** are approximately the same as intermediate wires **148**. Such an embodiment provides a more uniform, and therefore aesthetically pleasing, look to the reinforced decorative light string **140** or reinforced decorative lighting assembly.

In an embodiment, each series circuit of reinforced decorative light string **140** has an overall length that does not exceed 13 feet, while the overall length of the light string **140** does not exceed 51 feet, as required in some decorative lighting applications. In one such embodiment, reinforced decorative light string **140** is configured to conduct a maximum of 170 mA.

In an embodiment, reinforced decorative light string **140** includes reinforced wire **100** that comprises 7-10 conductor strands **104**. In an embodiment, the number of conductor strands **104** depends upon desired ampacity. In an embodiment, the reinforced wire **100** used may comprise 8 or 10 conductor strands. In one such embodiment having 8 strands, each conductor defines an average diameter that is within a range of 0.15 mm to 0.16 mm.

In an embodiment, intermediate wires **148** comprise reinforced wire configured for a first ampacity, and power wires **144** and **146** are configured for a second, higher ampacity. In one such embodiment, a sum of the cross-sectional area of conductor strands **104** of either of power wire **144** or **146** is greater than a sum of the cross-sectional area of all of conductor strands **104** of an intermediate wire **148**, wherein "cross-sectional" refers to a section normal to a wire axis.

In an embodiment, all intermediate wires **148** are limited to an average maximum of 20 inches in length.

Referring to FIGS. **24** and **25**, another embodiment of reinforced decorative light string **140** is depicted. In this embodiment, reinforced decorative light string **140** comprises a parallel-series configuration.

In this embodiment, decorative light string **140** comprises optional power plug **142**, first power-terminal wire **144**, second power-terminal wire **146**, multiple light-connecting wires **148**, and a plurality of lamp assemblies, including lamp assemblies **190a** to **190h**. First power-terminal wires **144**, second power-terminal wires **146** and light-connecting wires **148** comprise reinforced decorative lighting wire **100**.

Each lamp assembly **190** (**190a** to **190h**) comprises a lamp element **172**, such as an LED, and a lamp holder **192** or **194**. Lamp holders **192** are configured to receive three wires, which may be a combination of wires **144** and **148** or **146** and **148** or only wires **148**; lamp holders **194** are configured to receive four wires. As depicted, lamp assemblies **190a** (first lamp assembly), and lamp assembly **190d** comprise three-wire lamp holders **192**, while the remaining lamp holders comprise four-wire lamp holders **193**. In other embodiments, lamp holders **190e** and **190h** may comprise three-wire lamp holders and decorative light string **140** may include an additional first power-terminal wire and an additional second power-terminal wire connected to lamp holders **190e** and **190h** and to an end connector plug for connecting to another (not depicted).

In the embodiment depicted, reinforced decorative light string **140** comprises two sets of lamp elements **172**, first set **198a** and second set **198b**. Lamp elements **172** of first set **198a** are electrically connected in parallel; lamp elements **172** of second **198b** are electrically connected to one another in parallel; and first set **198a** is electrically connected in series with second set **198b**, to form a parallel-series light string. The number of lamp elements **172** in each set may vary. In an embodiment, the number of lamp elements **172** in each set **198** ranges from 3 to 60; in an embodiment, the number of lamp elements **172** ranges from 10 to 20 lamp elements; in an embodiment, the number of lamp elements **172** is the same in each set, but different in other embodiments. Each lamp element **172** may be configured to operate at a particular voltage or range. In an embodiment, lamp elements **172** may be configured to operate at 3V, AC or DC, though lamp elements

172 may be configured to receive any designed voltage, including generally used voltages such as 2.5V, 3V, 6V, 12V, and so on.

Further, the number of sets **198** of lamp elements **172** may be greater than the two sets **198a** and **198b** depicted. In an embodiment, the number of sets ranges from 2 sets to 50 sets; in an embodiment, the number of sets ranges from 3 sets to 10 sets.

The resultant voltage at each light set **198** at each lamp element **172** In an embodiment, each lamp element **172** is configured to receive 3V power (AC or DC); in another embodiment, each lamp element **172** is configured to receive 2.5V; in other embodiments, lamp elements **172** are configured for other voltages as needed and depending on the particular power source available and a reinforced decorative light string **140** configuration. Further, the number of sets of lamp assemblies is not limited to two sets, and may be larger for an individual reinforced decorative light string **140** having a series-parallel construction. In an embodiment, reinforced decorative light string **140** includes three sets **198**, each set **198** and each lamp element **172** configured to receive 3V.

Referring to FIG. **26**, an embodiment of a reinforced decorative light string **140** comprising three electrical circuits is depicted. Similar to light string **140** as depicted and described with respect to FIG. **22** above, light string **140** of FIG. **26** includes multiple sets of lamp assemblies **150** wired in series, each set wired in parallel (parallel-series configuration).

While FIG. **26** comprises a schematic depiction of this particular embodiment of reinforced decorative lighting string **140**, it will be understood that each line represents a wire or wire segment, e.g., **144a**, **148**, etc., such that FIG. **26** also depicts an actual wire layout (though lengths of wires are representational only).

In this embodiment, reinforced decorative light string **140** comprises power plug **142**, first power or power-terminal wires **144**, second power or power-terminal wires **146**, first series-circuit lamp assemblies **150a** interconnected by first intermediate wires **148a**, second series-circuit lamp assemblies **150b** interconnected by second intermediate wires **148b**, third series-circuit lamp assemblies **150c** interconnected by third intermediate wires **148c**, and power end connector **305**. In an embodiment, power wires **144** include power wires **144a**, **144b**, **144c**, and **144d**, while power wires **146** includes power wires **146a**, **146b**, **146c** and **146d**. Power wires **144** and **146** conduct current for the entire light string **140**, as well as power for other light strings that may be plugged into end connector **305**. Conversely, each intermediate wire **148** conducts current only for its respective single series circuit.

In an embodiment, all wires, including wires **144a-d**, **146a-d**, and **148a-c** comprise reinforced decorative lighting wire **100**.

In another embodiment, only intermediate wires **148a-c** comprise reinforced wires **100**, while power wires **144a-d** and **146a-d** comprise standard, non-reinforced wires. As discussed above with respect to FIG. **22**, for multiple circuit light strings, power wires **144** and **146** in a non-reinforced configuration will generally be configured with more conductor strands and ampacity, such that their inherent strength is similar to, approximately the same as, or greater than, the strength of individual reinforced intermediate wires **148**. In such a configuration, it may not be necessary to reinforce power wires **144** and **146** since the outcome would be to have power wires that may be unnecessarily stronger than wires **148**.

In an embodiment, intermediate wires **148** comprise reinforced wire configured for a first ampacity, and power wires

144 and 146 are configured for a second, higher ampacity. In one such embodiment, a sum of the cross-sectional area of conductor strands 104 of either of power wire 144 or 146 is greater than a sum of the cross-sectional area of all of conductor strands 104 of an intermediate wire 148, wherein

Referring to FIG. 27, in an embodiment, reinforced light string 140 may be configured in an “icicle” configuration, as will be understood by those skilled in the art. In an icicle configuration, a set of wires extends horizontally, while multiple sets of wires extend vertically away from the horizontally extending wires to form an “icicle” pattern. In one such embodiment, the total length of wire 100 used in a series circuit may be limited to 12 feet maximum.

As depicted, icicle light string 140 is substantially the same as decorative light string 140 as depicted in FIG. 26, with the exception of the various lengths of wires, and wire configurations. In an embodiment, icicle light string 140 comprises power plug 142, first power or power-terminal wires 144, second power or power-terminal wires 146, first series-circuit (circuit Ca) lamp assemblies 150a interconnected by first intermediate wires 148a, second series-circuit (circuit Cb) lamp assemblies 150b interconnected by second intermediate wires 148b, third series-circuit (circuit Cc) lamp assemblies 150c interconnected by third intermediate wires 148c, and power end connector 305. In an embodiment, power wires 144 include power wires 144a, 144b, 144c, and 144d, while power wires 146 includes power wires 146a, 146b, 146c and 146d. Power wires 144 and 146 conduct current for the entire light string 140, as well as power for other light strings that may be plugged into end connector 305. Conversely, each intermediate wire 148 conducts current only for its respective single series circuit.

In an embodiment, all wires of icicle light string 140 comprise reinforced wire 100.

In another embodiment, only intermediate wires 148a-c comprise reinforced wires 100, while power wires 144a-d and 146a-d comprise standard, non-reinforced wires for reasons described above with respect to light string 140 of FIG. 26.

Because an icicle configuration include multiple strands of downward (as would be the case when applied to a house or similar outdoor structure) hanging strands comprising multiple wires 148 and lamp assemblies 150 may be particularly prone to tangling and pulling when being applied to a structure. The use of reinforced wire 100 on an icicle light string 140 minimizes to possibility of wire damage or breakage under such conditions.

Referring to FIG. 28, an embodiment of a “chasing” reinforced decorative light string 140 is depicted. Chasing light string 140 includes power plug 140, first power wire 144 and second power wire 146, controller 147, first circuit power wires 149, 151 and 153, second circuit power wires 155, 157 and 159, and three series circuits a, b, and c. In an embodiment, first circuit power wires 149, 151 and 153 are “live”, “hot” or positive wires, while second circuit power wires 155, 157, and 159 are “neutral” or ground wires.

Each series circuit a, b, and c is controlled by controller 147, as will be understood by those skilled in the art. In an embodiment, controller 147 may comprise a processor, microcontroller, microcomputer, microprocessor, or similar such processing unit. Controller 147 may also include memory devices in electrical communication with the processor and storing software including algorithms for controlling the multiple circuits.

Series circuit a comprises series power wire 153, and a plurality of lamp assemblies 150a connected in series by a

plurality of intermediate wires 148a. Series circuit b comprises series power wire 151, and a plurality of lamp assemblies 150b connected in series by a plurality of intermediate wires 148b. Series circuit c comprises series power wire 149, and a plurality of lamp assemblies 150c connected in series by a plurality of intermediate wires 148c.

In an embodiment, wires of chasing light string 140 may be twisted along a longitudinal or horizontal axis parallel to depicted wires 149-155, such that chasing light string 140 resembles a single strand of sequential lights, the lights being a sequence comprising a light assembly 150a followed by a light assembly 150b, followed by a light assembly 150c, and so on. Various patterns of turning circuits a, b, and c on and off can create a variety of lighting effects.

Similar to embodiments described above, all wires of chasing reinforced decorative light string 140 may comprise reinforced decorative lighting wire 100. In other embodiments, only selected wires, and in particular main or power wires, may comprise reinforced wire 100.

In one such embodiment, first and second power wires 144 and 146 do not comprise reinforced wire, nor do wires 149, 151, 153, 155, 157, and 159, though all wires 148 comprise reinforced wire 100, for reasons and advantages similar to those described above with respect to FIGS. 22, 26 and 27.

Referring to FIG. 29, a synchronized, multi-circuit reinforced decorative light string 140 is depicted. Synchronized light string 140 of FIG. 29 is similar to chasing light string 140 of FIG. 28 above, in that a controller 147 provides control over multiple circuits of lamp assemblies 150.

In an embodiment, synchronized light string 140 includes power plug 142, first power wire 144, second power wire 146, main controller 147, first synchronized connector 163a, second synchronized connector 163b, connector 167, controller-connector wires 165a, 165b, and 165c, circuit power wires 149a-c, 151a-c, 155 and 157a-d, a plurality of intermediate wires 148, and a plurality of lamp assemblies 150. Connector 167 in an embodiment is configured to communicatively coupled to a synchronized connector 163a of another synchronized light string 140.

As depicted, synchronized light string 140 comprises multiple circuits of series connected lamp assemblies 150, each two series circuits connected in parallel. Series circuits a1 and a2 are wired in parallel, while series circuits b1 and b2 are wired in parallel to one another.

In an embodiment, synchronized connectors comprise 3-wire connectors, and may each may comprise a sub-controller in communication with main controller 147. As such, main controller 147 may communicate with multiple sub-controllers of multiple synchronized light strings 140 that may be connected one to another using synchronized connectors 163 and connectors 167. In an embodiment, sub-controllers control power to the series circuits of lights to create different lighting effects.

In an embodiment, all wires of synchronized, reinforced light string 140 comprise reinforced wire 100.

In other embodiments, only intermediate wires 148 comprise reinforced wire 100 for reasons similar to those described above with respect to FIGS. 22, 26, and 27, and may have a lower ampacity than those of power wires 144 or 146, or other non-intermediate wires. In one such embodiment, intermediate wires 148 comprise reinforced wire configured for a first ampacity, and power wires 144 and 146 are configured for a second, higher ampacity. In one such embodiment, a sum of the cross-sectional area of conductor strands 104 of either of a power wire 144 or 146 is greater than a sum of the cross-sectional area of all of conductor strands 104 of an

intermediate wire **148**, wherein “cross-sectional” refers to a section normal to a wire axis A.

Each of the above reinforced decorative light string **140** include reinforced wire **100** in any of the first and second power-terminal wires **144**, **146**, intermediate light-connecting wires **148**, or other wires. Each reinforced decorative light string **140** may be a single-wire as described above, wherein one or more light-connecting wires **148** is generally not twisted about another light-connecting wire **148** or reinforcing strand. In one such embodiment, a wire **148** of reinforced decorative light string **140** does not turn or twist about another wire at all, which in an embodiment means another wire does not make a full turn about another wire. In other embodiments, reinforced decorative light string **140** includes wires **148** that only make up to three full turns about another wire, such that they are partially twisted. In other embodiments, reinforced decorative light string **140** may include twisting of wires **148** in any fashion, such that the reinforced decorative light string comprises a “twisted-pair” light string.

Embodiments of reinforced decorative light strings **140** as described in the figures above may be applied to artificial trees, outdoor sculptures, and so on in order to create safer, stronger, and more attractive decorative lighting products.

In an embodiment, all wires of light string **140** comprise reinforced lighting wire **100**. In another embodiment, only wires **144** and **146** comprise reinforced lighting wire **100**, while wires **148** comprise standard, non-reinforced wires. In yet another embodiment, wires **144** and **146** comprise reinforced wires, and fewer than all of the wires **148** comprise reinforced lighting wire **100**. In one such embodiment, only one of wires **148** comprises a reinforced lighting wire **100**. In such an embodiment, the one reinforced wire **148** may be a wire configured to extend from a first branch of an artificial tree to a second branch of an artificial tree. The various light strings **140** depicted in the other figures may comprise similar such embodiments.

Referring to FIG. **30**, an embodiment of reinforced-wire artificial lighted tree **200** is depicted. Reinforced wire tree **200** may include multiple tree sections, including top section **202**, middle section **204** and bottom section **206**, as well as trunk **210**. Tree sections may be separable along trunk **210**. In other embodiments, tree **200** may not be separable, and trunk **210** may be a continuous trunk. Tree **200** may also include base **208** supporting reinforced wire tree **200**.

Reinforced-wire lighted tree **200** also includes a plurality of reinforced decorative light strings **140**, according to any of the embodiments described above, including light strings **140** in a series, parallel, series-parallel, or parallel-series, electrical configuration. In the embodiment depicted, tree **200** includes reinforced light strings **140** distributed about branches of the various tree sections **202** to **206**, with one or more power plugs **142** accessible to a user of tree **200**. In this embodiment, reinforced decorative light strings are located externally on tree sections **202** to **206**.

In an embodiment, a light string **140** is distributed over more than one branch, such that one or more wires span two branches, or extend from one branch to another branch. In such an embodiment, at least the wire spanning from one branch to another branch may comprise reinforced lighting wire **100**.

The use of reinforced decorative light strings **140** on tree **200** provides a number of advantages over the use of conventional light strings. For example, and as mentioned briefly above, the use of reinforced wire provides additional safety benefits by strengthening the wires of the light strings **140** on tree **200**, decreasing the likelihood that manipulation of the tree causes wiring to break. Further, the use of single-wire

constructed reinforced light strings **140** decreases the amount of wire generally used, as twisted pairs of wires are avoided, thereby increasing the aesthetic appearance of tree **200**.

Referring to FIG. **31**, in another embodiment, embodiments of light strings **140** as described above are applied to another lighted artificial tree **201** having a central wiring system housed at least in part inside trunk **210**.

As depicted, reinforced-wire lighted tree **201** may also include tree sections **202**, **204**, and **206**, base **208**, trunk **210**, power cord **212**, and multiple reinforced decorative light strings **140**. Unlike the embodiment of tree **200** described above, tree **201** includes a central wiring system **214** housed inside trunk **210**, as described further below with respect to FIG. **32**.

Referring to FIG. **32**, central, trunk wiring system **214** in electrical connection with multiple reinforced decorative light strings **140** is depicted. In the depicted embodiment, trunk wiring system **214** includes a pair of power wires **216** and **218** extending (in segments) from a bottom area of trunk **210** to a top area of trunk **210**. In the embodiment depicted, trunk **210** includes three trunk portions, top trunk portion **210a**, middle trunk portion **210b**, and bottom trunk portion **210c**. In an embodiment, power wires **214** and **216** extend inside trunk **210**, inside each trunk section **210a** to **210c**. As depicted, each power wire **214** comprises individual power wires **214a**, **214b**, and **214c**, housed respectively, fully or partially, in trunk portions **210a**, **210b**, and **210c**.

Trunk portion **210a** is configured to mechanically connect to trunk portion **210b**, and trunk portion **210b** is configured to mechanically connect to trunk portion **210c**, such that trunk **210** is formed. When the mechanical connections between trunk portions are made, electrical connections between portions of central wire system **214** are made. In other words, power wire portion **216a** becomes electrically connected to power wire portion **216b**, which becomes electrically connected to power wire portion **216c**. Similarly, wire portions **218a** to **218c** become electrically connected. Wiring system **214** may comprise standard, non-reinforced wires, or may include reinforced wire **100** of the claimed invention. Although not depicted, wiring system **214** may include a power converter or adapter for changing a power source voltage, for example, from 110 VAC to 9 VDC, which may be internal to, or external, to trunk **210**.

Mechanical and electrical connections may be made between tree sections **202**, **204**, and **206**, and their respective trunk portions and wiring sub-systems in a number of ways, some of which are described herein, and some of which are known and described in patent publications including: U.S. Pat. No. 8,454,186, entitled “Modular Lighted Tree with Trunk Electrical Connectors”; US20120075863, entitled “Decorative Light Strings for Artificial Lighted Tree; and US 20130163231, entitled “Modular Lighted Artificial Tree”, which are all herein incorporated by reference in their entireties.

Still referring to FIG. **32**, each reinforced decorative light string **140** is electrically connected to one of power wire pairs **216** and **218** so as to receive power from an external power source **220**. Reinforced decorative light strings **140** are depicted in a simplified manner, resembling a series connection, but it will be understood, and as described above, that tree **201** may include light strings **140** having any combination of the above-described electrical configurations.

As depicted, tree section **202** includes a single reinforced light string **140** connected to central wiring system **214** above, or at a top portion of trunk portion **210a**. In this embodiment, power wires **216a** and **218a** extend outside trunk portion **210** to connect to a light string **140**.

As depicted, and in an embodiment, tree section **204** includes two reinforced decorative light strings **140**, namely, **140b1** and **140b2**. In this embodiment, reinforced decorative light string **140b1** comprises a single-wire light string, such as a series-connected string or a series-parallel light string. Reinforced decorative light string **140b1** is electrically connected to power wires **214b** and **216b**, which represent a first electrical polarity and a second electrical polarity, at first end **224** of **140b1** and second end **226** of **140b1**, respectively. First end **224** includes first power-terminal wire **144**, which is electrically connected to power wire **214b**, while second end **226** includes second power-terminal wire **146**, which is electrically connected to power wire **216b**.

In the embodiment depicted, first terminal wire **144** enters generally hollow trunk portion **210b** at a first location **228**, which may be an aperture, then connects inside trunk portion **210b** to power wire **214b**. In another embodiment, first terminal wire **144** may terminate at an electrical connector at first location **228** (see description below regarding FIGS. **33A** to **33D**), and make electrical connection to power wire **214b** via the electrical connector.

Second terminal wire **146** enters generally hollow trunk portion **210b** at second location **230**, which may be an aperture, then connects inside trunk portion **210b** to power wire **216b**. In another embodiment, second terminal wire **146** may terminate at an electrical connector at first location **230**, and make electrical connection to power wire **216b** via the electrical connector.

In an embodiment, first location, aperture, or opening **228** will be unique from second location, aperture or opening **230**. In an embodiment, and as depicted, first location **228** is located vertically above second location **230**. In such an embodiment, and particularly for a single-wire light string **140**, lamp elements and wiring may be more easily distributed about a greater external area (more branches) of tree section **204**. In another embodiment, first location **228** is located at a same vertical level, but opposite, or even adjacent second location **230**.

In other embodiments, both power wires **144** and **146** may electrically connect to central wiring system **214** at approximately the same location. Still referring to FIG. **32**, reinforced light string **140b2** electrically connects to trunk wiring system **214** at location **232**, which may also comprise an opening or aperture in the trunk, with or without an electrical connector.

Referring also to FIGS. **33A** to **33D**, several embodiments of electrical trunk connectors **240** coupled to trunk **210** (including any of trunk portions **210a**, **210b**, or **210c**), are depicted.

Referring specifically to FIG. **33A**, in an embodiment, trunk **210** of tree **201** includes one or more electrical connectors **240a** configured to receive power plug **142** of reinforced light string **140**. In this embodiment, electrical connector **240a** comprises a pair of slotted openings **242** and **244** configured to receive a pair of electrical terminals **246** and **248**, respectively of power plug **142**. Electrical connector **240a** is in electrical connection with central wiring system **214**, and may include a pair of electrical terminals adjacent slotted openings **242** and **244** such that power wire **214** electrically connects to a first terminal of electrical connector **240a**, which electrically connects to terminal **244** of plug **142**, which electrically connects to first power-terminal wire **144** of reinforced light string **140**. Similarly, power wire **216a** electrically connects to a second terminal of electrical connector **240a**, which electrically connects to terminal **246** of plug **142**, which electrically connects to second power-terminal wire **146** of reinforced light string **140**. As such, power

source **220** provides electrical power to reinforced light string **140** via trunk wiring system **214** and electrical connector **240a**.

Referring to FIG. **33B**, and still to FIG. **32**, a different embodiment of an electrical connector **240** is depicted. Electrical connector system **240b** includes a pair of connecting wires **250** and **252** in electrical connection with power wires **216** and **218**, respectively. Electrical connector **240b** system also includes a pair of electrical connectors **254** and **256**, each electrically connected to each of connecting wires **250** and **252**, respectively. In an embodiment, electrical connectors **254** and **256** comprise a female connector adapted to receive a corresponding male electrical connector, such as an embodiment of electrical connectors **258** and **260**, respectively. Electrical connectors **258** and **260** are in electrical connection with first power-terminal wire **144** and second power-terminal wire **146**. In other embodiments, the electrical connection system may include different kinds of connector sets **254/256** and **258/260**, such as spade terminal connectors, coaxial connectors, ring terminals, and other such connector sets for connecting a pair of wires.

In an embodiment, grommet **262** may be inserted into opening **232** to secure and protect connecting wires **250** and **252**.

Referring to FIG. **33C**, in an embodiment, first power wire **144** and second power wire **146** are directly connected to power wires **216** and **218** inside trunk **210**. In such an embodiment, wires **144** and **146** may pass through opening **232**, which may include a grommet or other securing device **262**.

Referring to FIG. **33D**, another embodiment of an electrical connector **240** coupled to trunk **210** is depicted. Similar to the embodiment depicted in FIG. **33A**, electrical connector **240d** is electrically connected to trunk wiring system **214**, such that a pair of electrical contacts or terminals **266** and **268** are in electrical connection with power wires **216** and **218**. Electrical connector **240d** is coupled to the wall of trunk **210** at location/opening **232**, and is configured to receive a power plug **264** so as to provide power to reinforced light string **140**. In this embodiment, a non-traditional electrical connector system is used. Electrical connector **264** includes flat terminals **270** positioned adjacent connector body **264** that are configured to make electrical connection to terminals **266** and **268**. It will be understood that various methods and devices, such as electrical connectors, may be used to electrically connect reinforced decorative light strings **140** to trees **200** or **201**, and the claimed invention is not intended to be limited to the specific embodiments described above.

In an embodiment, reinforced-wire lighted tree **201** includes one or more reinforced decorative light strings **140** that include non-reinforced wire for first and second power wires **144** and **146**, and reinforced wire **100** for intermediate wires **148**. Further, some, and in an embodiment, a majority, of intermediate wires **148** are in contact with branches of reinforced-wire lighted tree **201**, thereby receiving some degree of support from the branches.

The increased tensile strength of reinforced decorative light strings **140** in conjunction with the various connectors described above, provides additional safety for a user of tree **200** or **201**. For example, it is not uncommon for persons removing light strings from outlets to pull on the light string wiring to disconnect the light string from the power source. If a user were to attempt to disconnect a light string **140** from its connection to trunk **210** by pulling on wires **144**, **146**, or **148**, the increased tensile strength of reinforced wire **100** would decrease that chances that the light string wiring would break, and increase the chances that the plug would become

disconnected from the electrical trunk connector, thereby further increasing the overall safety of the lighted tree.

As described in part above, in an embodiment, all wires comprising a light string **140** may include reinforced wiring. In other embodiments only some wires in a light string **140** may be reinforced. In one such embodiment, and still referring to FIGS. **32-33D**, one or both of a lead wire **144** and a return wire **146** may comprise reinforced wiring **100**. Because the lead and/or return wires that form the connection between the rest of the light string **140** and a power plug or power source tend to be handled by a user and potentially are subject to pulling forces, the use of reinforced wiring at the lead and return portion of the light string **140** advantageously strengthens the light string **140** at the point where it is most needed.

Further, it would not be uncommon for a person or user to move, pivot, or bend branches of a tree **200**, thereby pulling on attached lights strings. Consequently, in other embodiments, portions of a light string **140** that span multiple branches may comprise reinforced wiring **100**. Branches of a tree **200** may be hinged, or in some way able to pivot at connection to a trunk of the tree **200**. If a light string **140** spans multiple branches of a tree **200**, as depicted in FIGS. **30** and **31**, a pulling force may be exerted on a light string **140** on that portion of the light string **140** that extends between the branches. FIG. **34** depicts such a situation.

In FIG. **34**, a portion of tree **200** with reinforced decorative light string **140** is depicted. In the depicted portion, tree **200** includes lower branch **203L** and upper branch **203U** both pivotally connected to trunk **T** at trunk rings **R**. Each branch **203** includes multiple sub-branches **205**. Branch **203U** is depicted as being moved in a generally upward direction **B**.

Reinforced decorative light string **140** is attached to each of branches **203U** and **203L**. As depicted, intermediate light-connecting wires **148** are wrapped about branches **203U** and **203L**, including at their various sub-branches **205**, or may be attached to branches **203** or sub-branches **205** via clips **209**. As specifically depicted, light string **140** may be clipped to a branch **203** at two or more points, including at a branch point proximal trunk **T**, and a point distal trunk **T**.

When branch **203U** is pivoted in a direction indicated by arrow **B**, intermediate light-connecting wire **148F** is subjected to a pulling force **F_p**, as depicted. To prevent damage or breakage in such a situation, intermediate wire **148F** may comprise reinforced decorative wire **100**. In an embodiment, other intermediate light-connecting wires **148** may not include reinforced decorative wire **100** as they may not be subjected to force **F_p** caused by branch movement.

In an embodiment, wires **144** and/or **146**, in addition to intermediate wire **148F** may comprise reinforced wire. In yet another embodiment, multiple intermediate wires **148**, such as those adjacent to intermediate wire **148F** may be reinforced. In an embodiment, wherein light string **140** spans more than two branches **203**, light string **140** may include multiple intermediate wires **148F** that extend from branch-to-branch, such that all such intermediate wires **148F** are reinforced. Intermediate wire **148F** extends from branch **203L** to **203U**, and comprises reinforced decorative wire **100**.

Further, it will be understood that such a light string **140** having intermediate wire **148F** may also be distributed about branches that are adjacent one another, meaning at approximately the same height relative to trunk **T**. In such an embodiment, wire **148F** may still span from one branch **203** to another branch **203**, but will do so in approximately the same horizontal plane, rather than extending from a lower branch to an upper branch.

In another embodiment, such a light string **140** may extend between upper and lower branches, and between adjacent, same-height branches.

Referring to FIGS. **35** and **36** two embodiments of an internal trunk connector system **270a** and **270b** are depicted. Such internal trunk connector systems **270** may be used together with trunk wiring system **214** and reinforced decorative light strings **140** described above, in trees **201**. In some embodiments, trunk wiring system **214** may include reinforced decorative lighting wire **100** inside trunk portions of a modular lighted tree **201**.

Referring specifically to FIG. **35**, in an embodiment, trunk connector system **270** couples two tree sections together, such as tree section **204** and tree section **206** of tree **201** having an internal trunk wiring system **214**, mechanically, and electrically (see also FIG. **31**).

In an embodiment, trunk portion **210b** houses connector body **272** at first end **273** of trunk portion **210b**. Connector body **272** may be inserted into trunk portion **210b** such that it is fully inside trunk portion **210b**, or in other embodiments, portions of connector body **272** may extend out of, or be even/flush with, end **273**. A pair of electrical terminals **274** and **276**, which may have a first and second electrical polarity, are in electrical connection with power wires **216b** and **218b**, respectively. In an embodiment, power wires **216a** and **218b** may comprise reinforced wire **100**. Using reinforced wiring internal to tree **201** increases the durability of wiring system **214**, and prevents damage that might occur during manufacturing or use. In other embodiments, power wires **216a** and **218b** may comprise known, non-reinforced decorative wire. Connector body **272** receives and secures at least a portion of terminals **274** and **276**, and in an embodiment, terminals **274** and **276** extend outwardly and away from connector body **272**, forming “male” terminals. Terminals **274** and **276** may form other types of electrical contacts or terminals in addition to the pin-like terminals depicted, such as spade terminals, coaxial terminals, and so on. In an alternate embodiment, a mechanical sleeve may be used to join trunk portions.

In an embodiment, trunk portion **210c** houses connector body **278** at first end **279** of trunk portion **210c**. Connector body **278** may be inserted into trunk portion **210b** such that it is fully inside trunk portion **210b**, or in other embodiments, portions of connector body **272** may extend out of, or be even/flush with, end **273**. As depicted, connector body **278** is flush with the very end of end **279**. A pair of electrical terminals **284** and **286**, which may have a first and a second electrical polarity, are in electrical connection with power wires **216c** and **218c**, respectively. Terminals **284** and **286** may also form, or be in contact with, a pair of sockets **282** and **284** configured to receive male terminals **274** and **276**.

When trunk portion **210b** of tree section **204** is coupled to trunk portion **210c** of tree section **206**, terminals **274** and **276** are received by sockets **280** and **282**, making electrical connection with terminals **284** and **286**, such that power wires **216a** and **216b** are in electrical connection, and power wires **218a** and **218b** are in electrical connection with one another. Consequently, electrical power is available in tree section **204** at power wires **216b** and **218b**.

When trunk portion **210b** of tree section **204** is coupled to trunk portion **210c** of tree section **206**, a mechanical connection is also made. In the depicted embodiment, first end **273** of trunk portion **210b** is generally not tapered, while first end **279** of trunk portion **210c** is tapered so as to be received by end **273**. Consequently, when trunk portions **210b** and **210c** are coupled together, both an electrical and mechanical connection are made.

35

Referring specifically to FIG. 36, an alternate embodiment of a connector system 270 is depicted. Connector system 270b comprises a generally coaxially connection system. In the embodiment depicted, trunk 210b houses connector body 290 securing electrical terminal set 292. Electrical terminal set 292 forms cavity or socket 294 and includes first terminal 296 and second terminal 298.

First electrical terminal 296 is electrically connected to power wire 218b, and is located at a base of socket 294. In an embodiment, terminal 296 may form a simple flat conductive portion. In another embodiment, terminal 296 is formed of a conductive inside surface of socket 294.

Second electrical terminal 298, in an embodiment, forms a cylindrical portion having a conductive outer surface, or portion thereof.

Trunk portion 210c of tree section 206 houses connector body 300, which in turn supports electrical terminal set 302. Electrical terminal set 302 includes first electrical terminal 304 and second electrical terminal 306. In an embodiment, first terminal 304 comprises a pin terminal projecting upwardly along a central axis of trunk 210c. In an embodiment second terminal 306 comprises a cylindrical conductive portion, including a conductive inner surface or portion thereof.

Electrical terminal 304 is electrically connected to power wire 216c, and terminal 306 is electrically connected to power wire 218c.

When trunk portion 210b is coupled to trunk portion 210c, a mechanical and electrical connection is made between tree sections 204 and 206. Terminal 304 is received into socket 294 and makes electrical connection to terminal 296; terminal 306 receives terminal 298 and the two terminals make electrical connection. Consequently, power wires 216b and 216c are in electrical connection, as are power wires 218b and 218c.

In embodiments of reinforced decorative light wire trees 201, including those described above, may comprise decorative light strings 140 having intermediate wires 148 that are each 20 inches or less in length, and comprise 8 conductor strands. In one such embodiment tree 201 is configured not to conduct more than 300 mA total current. In an embodiment, wires 148 include an outer layer configured to withstand a 60 degrees C. temperature.

Embodiments of this connector system 270b are depicted and described in U.S. Pat. No. 8,454,186, entitled "Modular Lighted Tree with Trunk Electrical Connectors", which is herein incorporated by reference in its entirety.

Reinforced decorative light strings 140 and reinforced decorative lighting wire may be used to create other reinforced-wire decorative lighting products in addition to trees. Such reinforced products include net lights, outdoor sculptures, lawn stakes, and other such goods.

Referring to FIGS. 37-39 and 41-45, embodiments of reinforced-wire net light 300 is depicted. Net light 300 generally comprises a patterned array of lamp elements 154 and reinforced wires 100 forming a two-dimensional decorative lighting structure. Known net lights typically require some kind of reinforcing strands wrapped about the various wiring segments so as to provide additional strength. FIG. 40 depicts a portion of a prior-art design of a net light that includes non-conductive strands A and B wrapped about each wire segment, such as wire segment 13. While embodiments of reinforced-wire net light 300 could include non-conductive strands wrapped about conductive wire segments for even more strength, the use of reinforced wire 100 reduces or eliminates the need for such non-conductive strands wrapped about the net wires.

36

FIG. 37 depicts sub-net 300a depicting an embodiment of a wiring layout, while FIGS. 38 and 41 depict completed net light 300 comprising sub-net 300a with pattern-support cords 302. FIG. 39 depicts a portion of net light 300 illustrating an embodiment of a connection scheme for attaching and aligning pattern-support cords 302 to sub-net 300.

Referring specifically to FIG. 37, sub-net 300a includes power plug 142, first power-terminal wires 144a, b, and c, second power-terminal wires 146a, b, and c, end connector 305, and three light sets 306, 308, and 310, of lamp assemblies 150. End connector 305 is electrically connected to power plug 142 and configured to receive a power plug 142 of a second net light or other electrically powered device, thereby providing power to such a device when power plug 142 is connected to an external power source.

In the embodiment depicted, first light set 306, second light set 308, and third light set 310 each include 50 lamp assemblies 150, and a plurality of intermediate, light-connecting wires 148, as well as first and second power-terminal wires 144 and 146. As described above, each lamp assembly 150 includes a lamp element 154, which could be an incandescent light, LED, or other light source. As depicted, lamp elements 154 of each set are electrically connected in series, while each set 306, 308, and 310 are electrically connected to one another in parallel, thereby forming a series-parallel light set. It will be understood that reinforced net lights of the claimed invention are not limited to series-parallel electrical configurations, and as described above with respect to reinforced decorative light strings 140, may include other electrical configurations such as series, parallel, parallel-series, and combinations thereof. Similarly, embodiments of sub-net 300a and net light 300 are not limited to the specific quantity of lamp elements 150 and light sets 306-308 depicted.

In the embodiment depicted, lamp assemblies 150 are arranged in a matrix pattern with lamp assemblies 150 aligned horizontally in rows, and lamp assemblies aligned in columns vertically, with sub-net 300a and net light 300 forming a two-dimensional rectangular shape. As also depicted, and referring to column 312, every other lamp assembly 150 is staggered from another in a left-to-right pattern so as to create a diamond pattern as depicted (and further described) with respect to FIG. 38. In other embodiments, sub-net 300a and net light 300 is not limited to a rectangular shape, and may form a square, triangle, polygonal, or other shape. Further, sub-net 300a and net light 300 is not limited to a diamond pattern, and could define a square or other pattern.

Referring specifically to FIGS. 38, 39 and 41, an embodiment of reinforced-wire net light 300 is depicted. Reinforced-wire net light 300 includes sub-net 300a and one or more pattern-support cords 314.

Pattern-support cords 314 may comprise a cord, strand, twine, fiber, rope, wire, or other flexible, cord-like material coupled to sub-net 300a. Support cord 314 may comprise any of a variety of materials, including polymeric material, such as PVC, PE, PET, and so on. In an embodiment support cords 314 comprise the same material as reinforcing strands 104 of reinforced wire 100. In an embodiment, support cord 314 has a diameter that is approximately the same as the diameter of conducting wires 148; in an embodiment, the diameter of support cord 314 ranges from 50% to 150% of the diameter of wires 148; in an embodiment, support cords 314 have substantially the same coloring as conducting wires 148 so as to appear to be actual conducting wires, thereby enhancing the appearance of net light 300.

In an embodiment, one or more support cords 314 are strung vertically, from a top (side with plug 142) to a bottom of sub-net 300a, alternately connecting lamp assemblies 150.

Referring specifically to FIG. 39, a support cord 314 is depicted as coupled to three lamp holders 152. In an embodiment, each lamp holder 152 includes a clip portion 316 that clips support cord 314 to lamp holder 152 and lamp assembly 150. In the embodiment depicted, a support cord 314 forms a zig-zag, or back-and-forth pattern as it alternately couples to lamp holders 152 of net light 300. Support cords 314 may also connect horizontal portions of net light 300 as depicted.

The addition of support cords 314 to sub-net 300a provides the structural connections to the sub-net to form the final three-dimensional “net” shape with its diamond, square, or other pattern. Unlike known net lights that require support cords also be wrapped about wires 148 to supplement the lower tensile strength of the non-reinforced wiring, embodiments of reinforced-wire net lights 300 do not require that support cords or other external reinforcing strands be wrapped about wires 148.

FIG. 41 depicts a wire-cord schematic of reinforced net light 300, wherein dotted lines represent support cords 314, solid lines represent reinforced decorative wires, including wires 144 (which include first power wires 144a-144d), 146 (which include second power wires 146a-146d), and intermediate wires 148, and circles represent lamp assemblies 150. In the depicted embodiment, three individual, continuous strands of support cord 314 are used, 314a, 314b, and 314c. In other embodiments, more lengths of cord 314 may be used, and any of cords 314a, b, or c may comprise multiple portions. In this depiction, solid lines intersecting approximately a center of a circle indicate that the wire is electrically connected to the lamp assembly, while solid lines contacting a side of a circle indicate that the wire is not electrically connected to the lamp assembly but is adjacent to, and in embodiments, connected to the lamp assembly.

Such a layout of wires and cords provides minimal overlap of wiring and cord, thereby minimizing the amount and length of wire used, and also providing an aesthetically pleasing uniform appearance.

Further, in an embodiment of reinforced net light 300, all wires, including wires 144, 146 and 148 may comprise reinforced wire 100; in other embodiments, only some wires may comprise reinforced wire 100. In one such embodiment, only wires 144 and 146 may comprise reinforced wire 100 as these wires are more likely to be subjected to unusual pulling forces due to their connections to power plug 142 and end connector 305. In one such embodiment, one some of power wires 144 and 146 comprise reinforced wire 100, such as only wires 144a and 146a. In another embodiment, only wires 148 extending between lamp assemblies 150 may comprise reinforced wire 100, while power wires 144 and 146 do not comprise reinforced wire 100. In one such embodiment, power wires 144 and 146 do not comprise reinforced wire 100 because wires 144 and 146 may be twisted together for added strength, unlike wires 148 which generally are not twisted about one another.

In an embodiment, each of four lamp assemblies 150 define a diamond shape, as depicted. In such an embodiment, an end of cord 314, end 314a is located at one corner of net 300, extends downward along a side of net 300, then extends upwardly, connected from lamp assembly 150 to lamp assembly 150 in a zig-zag pattern. Cord 314 then extends horizontally, or laterally toward the other side of net 300, then extends downwardly in a zig-zag pattern again. The up and down zig-zag pattern is repeated laterally across net 300.

In an embodiment, the majority of lamp assemblies 150 not located at the edges of net 300 connect to two wires 148, and a cord 314.

Referring to FIG. 42, another embodiment of a net light 300 is depicted. Net light 300 of FIG. 42 is substantially the same as net light 300 of FIGS. 38 and 41, with the exception of some wiring configuration and connection configurations.

Net light 300 similarly includes three circuits, circuits a, b, and c. Each circuit a, b, and c comprises multiple light assemblies 150 (150a for circuit a, 150b for circuit b, and 150c for circuit c) wired in series, with intermediate wires 148a, b, c, respectively interconnecting the lamp assemblies. Some intermediate wires 148 extend from a top portion of net light 300 to a bottom portion (wires 148a1, 148b1, and 148c1). In an embodiment, reinforced net light 300 of FIG. 42 also includes external support cords 314, similar to the configuration of reinforced net light 300 of FIG. 41.

Net light 300 also includes first power wires 144a, 144b, 144c, and 144d, and second power wires 146a, 146b, 146c, and 146d. Reinforced net light 300 of FIG. 42 differs somewhat from reinforced net light 300 of FIG. 41 at least in the aspect of the electrical connection point of first and second power wires 144/146 and lamp assemblies 150. In the depicted embodiment of FIG. 42, first power wires 144a and 144b connect at a common lamp assembly 150a1, first power wires 144b and 144c connect at a common lamp assembly 150b1, first power wires 144c and 144d connect at a common lamp assembly 150c1. Second power wires 146a and 146b connect at a common lamp assembly 150a2, second power wires 146b and 146c connect at a common lamp assembly 150b2, second power wires 146c and 148d connect at a common lamp assembly 150c2.

In an embodiment, first power wires 144a-d and second power wires 146a-d are configured to conduct a greater electrical current than each of intermediate wires 148, similar to embodiments of light strings 140 as described above. In an embodiment, only intermediate wires 148 comprise reinforced wire 100 for reasons similar to those described above with respect to FIGS. 22, 26, and 27, and may have a lower ampacity than those of power wires 144 or 146, or other non-intermediate wires. In one such embodiment, intermediate wires 148 comprise reinforced wire configured for a first ampacity, and power wires 144 and 146 are configured for a second, higher ampacity, and do not comprise reinforced wire. In one such embodiment, a sum of the cross-sectional area of conductor strands 104 of either of a power wire 144 or 146 is greater than a sum of the cross-sectional area of all of conductor strands 104 of an intermediate wire 148, wherein “cross-sectional” refers to a section normal to a wire axis A. In one such embodiment power wires 144 and 146 in a non-reinforced configuration will generally be configured such that their inherent strength is similar to, approximately the same as, or greater than, the strength of individual reinforced intermediate wires 148. In such a configuration, it may not be necessary to reinforce power wires 144 and 146 since the outcome would be to have power wires that may be unnecessarily stronger than wires 148.

FIGS. 43-45 depict additional embodiments of net light 300.

Referring to FIG. 45, a wire-cord schematic of a net light 300 having 100 lamp assemblies 150 is depicted. In this embodiment, net light 300 defines a rectangular perimeter shape, with smaller rectangular shapes formed by sets of four lamp assemblies 150 in an interior of net light 300. Connections between wires, cords, and lamp assemblies are substantially similar to those described above.

In this embodiment, dashed lines represent cords 314, solid lines represent wires, some or all of which may comprise reinforced decorative light wire 100, and circles represent lamp assemblies 150. In this embodiment, a majority of wires

148 extend in a first direction, which for purposes of description will herein be referred to as a “lengthwise” direction along length L, while the majority of cord or portions or cord **314**, extend in a second direction, referred to as a “widthwise” direction along width W. In such an embodiment, most wire extends transverse to, or as depicted, perpendicular to, adjacent portions of cord **314**.

In the embodiment depicted, cord **314** comprises two portions, cord portion **314a** and cord portion **314b**. Arrowheads represent ends of cord portions. Each cord portion extends horizontally from lamp assembly **150** to lamp assembly **150**, across a width of net light **300**, then vertically to a next lamp assembly **150**, then back across the width W of net light **300**. In an embodiment, each or cord portions **314a** and **314b** comprise contiguous cords. In other embodiments, each cord portion **314a** or **314b** may comprise multiple sub-portions of cords.

In this embodiment, net light **300** comprises 100 lamp assemblies **150**, made up of 4 circuits, each circuit comprising 25 lamp assemblies in series with one another (the first to fourth series circuits labeled as Circuit 1 to Circuit 4). In the depicted embodiment, each of the four circuits are wired in parallel to one another. In an embodiment, and as depicted, Circuit 1 comprises 25 lamp assemblies **150**, intermediate wires **148-1a** to **148-1x** and power wires **144a** and **146a**; Circuit 2 comprises 25 lamp assemblies **150**, intermediate wires **148-2a** to **148-2x** and power wires **144b** and **146b**; Circuit 3 comprises 25 lamp assemblies **150**, intermediate wires **148-3a** to **148-3x** and power wires **144c** and **146c**; and Circuit 4 comprises 25 lamp assemblies **150**, intermediate wires **148-4a** to **148-4x** and power wires **144d** and **146d**. End connector **305** is electrically connected to power wires **144e** and **146e** to make power available to other lighted devices at an end opposite plug **142**.

FIG. **44** depicts another embodiment of a net light **300** having 100 lamp assemblies **150**. In this embodiment, net light **300** is substantially similar to the net light **300** depicted and described above with respect to FIG. **43**, except that the net light **300** of FIG. **44** comprises two circuits of 50 lamp assemblies connected in series, Circuit 1 and Circuit 2, each of the two circuits connected in parallel to one another. In the depicted embodiment, lamp assemblies comprise a variety of colors, as indicated by letter designation at the circle: R for red, G for green, B for blue, Y for yellow, and O for orange. In such an embodiment, lamp assemblies may be arranged in a color pattern as depicted. Further, although only two circuits are depicted, it will be understood that more than two circuits may be used, and further that net light **300** and its circuits may comprise any of a variety of electrical connections, including series circuits wired in parallel (depicted), parallel circuits wired in series, all parallel, or all series.

FIG. **45** depicts yet another embodiment of a net light **300**. In this embodiment, net light **300** comprises LED-based lamp assemblies **150**. LED-based lamp assemblies **150** operate on DC power supplied by power conditioning circuit **350**, which may comprise a rectifier circuit, as depicted, a transformer, or other such power conversion or conditioning circuit. As depicted, net light **300** comprises power plug **142**, incoming power wires **143a**, **143b**, **145a**, and **145b**, power-conditioning circuit **350**, first and second power wire sets **144** and **146** delivering negative and positive polarity power, respectively, to lamp assemblies **150** via intermediate wires **148**. In the depicted embodiment, net light **300** comprises four 25 lamp circuits, each circuit having lamp assemblies **150** wired in series, each circuit or group of lamp assemblies **150** wired in parallel.

In an embodiment, net light **300** may also include current-limiting resistors **400**. In one such embodiment, and as depicted, each circuit includes one or more current-limiting resistors **400** wired in series with lamps **150**.

Further, in the embodiment depicted, net light **300** may receive an incoming power, such as an AC power, that is rectified or conditioned by circuit **350**, thereby supplying DC power to lamps **150**. At the same time, the incoming power is also transmitted to an end connector plug **304**, such that both AC and DC power flow through net light **300** and are available for use.

Net light **300** also includes support cords **314**, including cords **314a** and **314b**. Similar to the embodiments described above, the amount or length of cord **314** wrapped about wires **148** is minimal. As depicted, only several perimeter wires **148** at opposite ends are adjacent, intertwined, or wrapped about cords **314**.

In an embodiment, net light **300** may also comprise restraining cord **402** that structurally couples a perimeter wire **148** conducting DC power to power wires **145a** and **145b**.

In an embodiment, any of the net light configurations described above may include reinforced wire **100** that can withstand **461bf** axially-applied pulling force before breaking; in one such embodiment, an average axially-applied pulling force before breakage averages 56 lbf+/-10%.

Referring to FIG. **46**, an embodiment of a reinforced-wire decorative-lighting sculpture **400** is depicted.

Reinforced-wire decorative lighting sculpture **400** includes one or more reinforced decorative light strings **140** coupled to frame **402**. Sculpture **400** may comprise multiple portions, such as an upper or first portion **400a** and a lower or second portion **400b**, as depicted. In an embodiment, first portion **400a** may be fully or partially separable from second portion **400b** at coupling devices **404**, which may comprise clips, hooks, hinges, or other such coupling devices, or combinations thereof.

Frame **402**, in an embodiment, comprises a generally rigid material, such as metal or plastic, or a natural material such as grapevine, configured to maintain a frame shape. Shapes include animals, such as the deer depicted, human figures or characters, icons such as stars, snowflakes, or other such shapes. Frame **402** may include multiple portions, such as first frame portion **402a** corresponding to first sculpture portion **400a** and second frame portion **402b** corresponding to second sculpture portion **400b**.

One or more reinforced decorative light strings **140**, such as those described above, may be fastened or draped onto frame **402**. When reinforced light strings **140** are fastened onto frame **402**, sculpture **400** may include a plurality of frame clips **406** coupling wires **148** of a reinforced decorative light string **140** to frame **402**.

The use of reinforced decorative light strings **140**, including reinforced wire **100**, provides benefits over known decorative-lighting sculptures, particularly those that have separable portions, such as sculpture portions **400a** and **400b**. Lighted sculptures often are separable so that the sculpture may be taken apart, or otherwise broken down into a storage position. The movement and manipulation of the frame portions may cause portions of the light strings to be pulled. Because embodiments of reinforced-wire decorative sculpture **400** include reinforced decorative light strings **140** having increased tensile strength, any unexpected strains applied to reinforced light strings **140** are less likely to cause wires **148** to break, thereby causing the set to fail and/or become a safety hazard. As described above, all wires of light string **140** may comprise reinforced decorative light wiring **100**, or only some wires may comprise reinforced wire, such as only wires

144 and 146; in other embodiments only wires 144 and 146 and selected wires 148 are reinforced. In such an embodiment, intermediate wires 148 that extend from one sculpture portion or frame portion to another sculpture portion of frame portion may be reinforced wire 100, while other wires 148 do not comprise reinforced decorative light wire 100. Such an embodiment may not be limited to reinforced wires 148 that span sculpture or frame sections, but rather, wires 148 that may be expected to be subjected to pulling forces due to their location, position, function, and so on, may comprise reinforced wire. In another embodiment, only some intermediate wires 148 comprise reinforced wire 100, such as wires 148 extending between sculpture or frame sections, while other wires 148 and wires 144 and 146 do not comprise reinforced wire 100.

Further, in an embodiment of a sculpture 400, only wires 148 extending between lamp assemblies 150 may comprise reinforced wire 100, while power wires 144 and 146 do not comprise reinforced wire 100. In one such embodiment, power wires 144 and 146, and other wires, do not comprise reinforced wire 100 because wires 144 and 146 may be twisted together for added strength, unlike wires 148 which generally are not twisted about one another.

In an embodiment, any of the net light configurations described above may include reinforced wire 100 that can withstand 30 lbf axially-applied pulling force before breaking; in one such embodiment, an average axially-applied pulling force before breakage averages 33 lbf \pm 10%.

The embodiments above are intended to be illustrative and not limiting. Additional embodiments are within the claims. In addition, although aspects of the present invention have been described with reference to particular embodiments, those skilled in the art will recognize that changes can be made in form and detail without departing from the spirit and scope of the invention, as defined by the claims.

Persons of ordinary skill in the relevant arts will recognize that the invention may comprise fewer features than illustrated in any individual embodiment described above. The embodiments described herein are not meant to be an exhaustive presentation of the ways in which the various features of the invention may be combined. Accordingly, the embodiments are not mutually exclusive combinations of features; rather, the invention may comprise a combination of different individual features selected from different individual embodiments, as understood by persons of ordinary skill in the art.

Any incorporation by reference of documents above is limited such that no subject matter is incorporated that is contrary to the explicit disclosure herein. Any incorporation by reference of documents above is further limited such that no claims included in the documents are incorporated by reference herein. Any incorporation by reference of documents above is yet further limited such that any definitions provided in the documents are not incorporated by reference herein unless expressly included herein.

For purposes of interpreting the claims for the present invention, it is expressly intended that the provisions of Section 112, sixth paragraph of 35 U.S.C. are not to be invoked unless the specific terms “means for” or “step for” are recited in a claim.

What is claimed:

1. A reinforced wire for decorative lighting, the wire defining a central longitudinal wire axis and comprising:
a longitudinally-extending reinforcing strand, the reinforcing strand comprising one or more fibers comprising a polymer material and defining a longitudinal reinforcing-strand axis;

a plurality of conductor strands wound about the reinforcing strand, each of the plurality of conductor strands defining a conductor strand axis, and each of the plurality of conductor strands in contact with the reinforcing strand;

an outer insulating layer adjacent to, and covering, one or more of the conductor strands; wherein the reinforcing strand in cross section normal to the longitudinal reinforcing-strand axis defines an asymmetrical shape.

2. The reinforced wire of claim 1, wherein the plurality of conductor strands are not evenly circumferentially spaced about the reinforcing strand.

3. The reinforced wire of claim 1, wherein at least some of the plurality of conductor strands are embedded into the reinforcing strand and conform to the asymmetrical shape of the reinforcing strand.

4. The reinforced wire of claim 1, wherein the plurality of conductor strands are wound asymmetrically about the reinforcing strand.

5. The reinforced wire of claim 1, wherein the reinforcing strand axis is a central longitudinal axis passing through a centroid of the reinforcing strand in the cross section, the reinforcing strand axis being offset from the wire axis.

6. The reinforced wire of claim 5, wherein the reinforcing strand axis is offset from the wire axis by a distance ranging from 5% to 35% of a maximum diameter of the reinforcing strand.

7. The reinforced wire of claim 1, wherein the insulating layer overlays a portion of the reinforcing strand such that the insulating layer directly contacts the portion of the reinforcing strand.

8. The reinforced wire of claim 7, wherein the insulating layer comprises a polymer material, the polymer material of the insulating material being different from the polymer of the reinforcing strand.

9. The reinforced wire of claim 8, wherein the polymer material of the reinforcing strand comprises a single-fiber 1000 to 1500 Denier polyethylene terephthalate (PET) material.

10. The reinforced wire of claim 1, wherein the plurality of conductor strands ranges from six strands to ten strands.

11. The reinforced wire of claim 10, wherein the plurality of conductor strands consists of eight strands.

12. The reinforced wire of claim 10, wherein an average diameter of each of the plurality of conductor strands ranges from 0.15 mm to 0.16 mm.

13. The reinforced wire of claim 10, wherein an average diameter of each of the plurality of conductor strands ranges from 0.20 mm to 0.30 mm.

14. The reinforced wire of claim 1, wherein the reinforcing strand exhibits tensile strength ranging from 45 to 65 MPa, and each of the plurality of conductor strands comprises a tensile strength ranging from 200-250 N/mm².

15. The reinforced wire of claim 1, wherein each of the plurality of conductor strands defines a diameter ranging from 0.15 mm to 0.16 mm.

16. A reinforced wire for decorative lighting, the wire defining a central longitudinal wire axis and comprising:

a longitudinally-extending reinforcing strand, the reinforcing strand comprising a polymer material and defining a central reinforcing-strand axis;

a plurality of conductor strands wound about the reinforcing strand, each of the plurality of conductor strands defining a central conductor-strand axis, and each of the plurality of conductor strands in contact with the reinforcing strand;

an outer insulating layer adjacent to, and covering, one or more of the conductor strands; wherein the central reinforcing-strand is arranged within the wire such that the central reinforcing-strand axis is offset from the wire axis and the plurality of conductor strands are asym- 5 metrically wound about the reinforcing strand.

17. The reinforced wire of claim **16**, wherein the plurality of conductor strands are asymmetrically wound about the reinforcing strand such that the central conductor-strand axes are not equidistant from either the wire axis or the central 10 reinforcing-strand axis.

18. The reinforced wire of claim **16**, wherein the reinforcing strand in cross section normal to the wire axis defines an asymmetrical shape.

19. The reinforced wire of claim **16**, wherein the reinforcing 15 strand comprises a polyethylene terephthalate (PET) material, the conductor strands comprise seven to ten strands of copper material, and the reinforced wire exhibits a tensile strength ranging from 2,000 to 3,500 PSI.

20. The reinforced wire of claim **16**, wherein the insulating 20 layer overlays a portion of the reinforcing strand such that the insulating layer directly contacts the portion of the reinforcing strand.

21. The reinforced wire of claim **20**, wherein the insulating 25 layer comprises a polymer material, the polymer material of the insulating material being different from the polymer of the reinforcing strand.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 9,243,788 B2
APPLICATION NO. : 14/627427
DATED : January 26, 2016
INVENTOR(S) : Chen

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

On Title Page, Column 1, item (51), under “Int. Cl.”,
delete “*F21V 23/00* (2015.01)” and
insert -- *F21V 23/00* (2006.01) --, therefor.

On Title Page, Column 1, item (51), under “Int. Cl.”,
delete “*F21W 121/04* (2006.01)
F21Y 105/00 (2006.01)”.

On Page 3, Column 2, item (56), under “OTHER PUBLICATIONS”, Line 1
delete “iventor” and insert -- inventor --, therefor.

Signed and Sealed this
Thirtieth Day of August, 2016



Michelle K. Lee
Director of the United States Patent and Trademark Office