



US009255502B1

(12) **United States Patent**  
**Glass**

(10) **Patent No.:** **US 9,255,502 B1**  
(45) **Date of Patent:** **Feb. 9, 2016**

(54) **ENGINE WITH EXHAUST SYSTEM AND EXTERNAL ACOUSTIC EMISSIONS VALVE**

(71) Applicant: **Dean W. Glass**, Carlton, OR (US)

(72) Inventor: **Dean W. Glass**, Carlton, OR (US)

(73) Assignee: **NORTHWEST ULD, INC.**, McMinnville, OR (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/461,214**

(22) Filed: **Aug. 15, 2014**

**Related U.S. Application Data**

(60) Provisional application No. 61/866,312, filed on Aug. 15, 2013.

(51) **Int. Cl.**  
**F02B 75/28** (2006.01)  
**F01N 1/18** (2006.01)

(52) **U.S. Cl.**  
CPC ..... **F01N 1/18** (2013.01)

(58) **Field of Classification Search**  
CPC ..... F02B 2075/025; F02B 2075/1808; F02B 77/13; F02B 27/04; F02M 35/10262; F02M 35/1244; F02M 35/1272; F02M 35/1294; F02M 35/16  
USPC ..... 123/51 B, 51 A, 51 BA, 51 BB, 51 BC, 123/51 BD; 60/289, 272, 324; 244/53 A  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,320,668 A	6/1943	Smith	
3,066,755 A	12/1962	Diehl	
3,692,142 A	9/1972	Stemp	
3,744,589 A	7/1973	Mellin	
3,927,731 A	12/1975	Lancaster	
4,579,195 A	4/1986	Nieri	
5,612,006 A	3/1997	Fisk	
6,684,633 B2	2/2004	Jett	
6,959,782 B2	11/2005	Brower et al.	
7,472,774 B1	1/2009	Monson et al.	
7,721,845 B2	5/2010	Gorenflo	
8,602,159 B2	12/2013	Harris et al.	
2005/0023078 A1	2/2005	Brower et al.	
2006/0156711 A1*	7/2006	Carpenter	F01N 3/22 60/289
2011/0180347 A1	7/2011	Butler	

\* cited by examiner

*Primary Examiner* — Lindsay Low


*Assistant Examiner* — Long T Tran

(74) *Attorney, Agent, or Firm* — Marsh Fischmann & Breyfogle LLP

(57) **ABSTRACT**

An engine with an acoustic emissions valve or reflector for an exhaust system is disclosed. This reflector is disposed outside of the exhaust system—the reflector is disposed in the atmosphere into which the exhaust system discharges. The reflector is moved between a reflecting position (where the reflector reflects or obstructs acoustic emissions from the exhaust system) and a non-reflecting position (where the reflector does not obstruct the bulk exhaust gas flow from the exhaust system) by rotation of the crankshaft.

**20 Claims, 15 Drawing Sheets**






Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7






Fig. 8A




Fig. 8B




Fig. 8C




Fig. 8D




Fig. 9






Figure 13




Figure 12




Figure 14




Figure 15



## ENGINE WITH EXHAUST SYSTEM AND EXTERNAL ACOUSTIC EMISSIONS VALVE

### CROSS-REFERENCE TO RELATED APPLICATIONS

This patent application is a non-provisional patent application of and claims priority to U.S. Provisional Patent Application Ser. No. 61/866,312, that is entitled "CRANKSHAFT TIMED REFLECTOR," that was filed on Aug. 15, 2013, and the entire disclosure of which is hereby incorporated by reference in its entirety herein.

### FIELD OF THE INVENTION

The present invention generally relates to the field of engines and, more particularly, to the addressing acoustic emissions generated by operation of the engine.

### BACKGROUND

Mufflers, silencers, expansion chambers, and similar acoustic mitigation devices utilize wave principles of energy dispersion, absorption, and wave interaction to modify the acoustic wave ultimately exiting these devices. There remains a need for at least some applications to further modify the acoustic signature provided by these types of devices, preferably without modifying either the associated engine or an existing muffler.

### SUMMARY

A first aspect of the invention is directed to an engine (e.g., two cycle) that includes a first cylinder, a first piston that is disposed within this first cylinder, a crankshaft that is interconnected with this first piston, an exhaust system that is fluidly connected with the first cylinder and that includes an exhaust discharge port, and a reflector. The reflector extends from and is rotated by the crankshaft, and the reflector is positioned within the atmosphere—the reflector is not internal to the exhaust system. The reflector is disposable into alignment with and completely out of alignment with the exhaust discharge port (e.g., a port that discharges from the exhaust system to atmosphere) by rotation of the crankshaft.

### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of one embodiment of an engine with an exhaust system reflector, with the exhaust system reflector being in a non-reflecting position for acoustic emissions discharged from the exhaust system.

FIG. 2 is another perspective view of the engine of FIG. 1, with the exhaust system reflector being in a reflecting position for acoustic emissions discharged from the exhaust system.

FIG. 3 is an end view of the engine of FIG. 1, with the exhaust system reflector being in the reflecting position of FIG. 2.

FIG. 4 is a top view of the engine of FIG. 1, with the exhaust system reflector being in a reflecting position for acoustic emissions discharged from the exhaust system.

FIG. 5 is another perspective view of the engine of FIG. 1, with the exhaust system reflector being in another non-reflecting position for acoustic emissions discharged from the exhaust system.

FIG. 6 is an end view of the engine of FIG. 1, with the exhaust system reflector being in the non-reflecting position of FIG. 5.

FIG. 7 is a side view of the engine of FIG. 1, illustrating the spacing between an exhaust discharge port and the exhaust system reflector.

FIG. 8A is a side view schematic of the exhaust system reflector of the engine of FIG. 1, where the reflector is aligned with and spaced from an exhaust discharge port of the exhaust system.

FIG. 8B is a side view schematic of the exhaust system reflector of the engine of FIG. 1, where the reflector is completely out of alignment with an exhaust discharge port of the exhaust system.

FIG. 8C is a side view schematic of an alternative position for the exhaust system reflector of the engine of FIG. 1, where the reflector is aligned with and abuts an exhaust discharge port of the exhaust system.

FIG. 8D is an end view schematic of the exhaust system reflector and associated counterweight from the engine of FIG. 1, with the exhaust system reflector being in a non-reflecting position for acoustic emissions discharged from the exhaust system, and illustrating the position of the counterweight in relation to the exhaust discharge port.

FIG. 9 is a schematic of one configuration of a cylinder for the engine of FIG. 1, along with a corresponding piston.

FIG. 10 is a schematic of a portion of a piston and cylinder wall.

FIG. 11 is a timing schematic for an exhaust system reflector.

FIG. 12 is a schematic of an embodiment of an exhaust system reflector for a single-cylinder engine.

FIG. 13 shows the exhaust system reflector of FIG. 12 in relation to an open end of an exhaust conduit for the exhaust system.

FIG. 14 is a schematic of an embodiment of an exhaust system reflector for a dual-cylinder engine.

FIG. 15 is a schematic that illustrates a clearance between an open end of an exhaust system conduit and an exhaust system reflector.

### DETAILED DESCRIPTION

FIGS. 1-7 present various views of one embodiment of an engine 10. The engine 10 includes a crankshaft 16, an engine case 14, a cylinder 40 (which may include one or more cooling fins 42 for moving heat generated during operation of the engine 10), a spark plug or other igniter 48, an exhaust system 60, an exhaust system reflector 80 located downstream of the exhaust system 60, and a counterweight 90. One or more engine mounts 12 may be utilized for securing the engine 10 relative to a vehicle of any appropriate type, such as an unmanned aerial vehicle. Rotation of the crankshaft 16 may rotate a propeller (in the case of an aerial vehicle), may rotate an axle and each associated wheel (in the case of a ground vehicle), or the like.

The exhaust system 60 for the engine 10 includes a muffler 62 that receives a discharge or exhaust/exhaust flow from the cylinder 40 during operation of the engine 10 and via an exhaust header 76 that fluidly interconnects the cylinder 40 and the muffler 62. The muffler 62 may be of any appropriate size, shape, configuration, and/or type. An exhaust conduit 64 (e.g., a tailpipe or stinger) extends from the muffler 62 and includes an open end or exhaust discharge port 66. As such, exhaust from the cylinder 40 flows into/through the header 76, then into/through the muffler 62, and then into/through the exhaust conduit 64 such that the exhaust exits through the open end 66 of the exhaust conduit 64.

The exhaust flowing out of the exhaust system 60 through the open end 66 of the exhaust conduit 64 may be character-

ized as including two primary components—a bulk exhaust gas flow and acoustic emissions (e.g., one or more acoustic waves). The exhaust system reflector **80** is used by the engine **10** to force at least a part of the acoustic emissions (after having exited the exhaust system **60** through the open end **66** of the exhaust conduit **64**, or at least after having reached the open end **66** of the exhaust conduit **64** (FIG. **8C**)) back into the exhaust conduit **64** (via its open end **66**) and preferably then back into the muffler **62**. This reflection and/or obstruction of at least part of the acoustic emissions should dampen the acoustic emissions (e.g., further lower the acoustic emissions from operation of the engine **10**; accommodate additional acoustic wave destructive interference) more than if the acoustic emissions make a single pass through the muffler **62** in proceeding from the cylinder **40** to the exhaust conduit **64**. In addition to the foregoing, the reflector **80** should also be sized and timed (relative to the position of the open end **66** of the exhaust conduit **64**) to reduce the potential of an unacceptable amount of the bulk exhaust gas flow being redirected or obstructed by the reflector **80**, which could generate a back pressure in the muffler **62** and the cylinder **40**, which in turn could adversely affect the operational performance of the engine **10**. Preferably no portion of the bulk exhaust gas flow is reflected or obstructed by the exhaust system reflector **80** at any time. As such, the reflector **80** may also be referred to as an acoustic emissions valve **80** that is positioned downstream of the exhaust system **60**. Such an acoustic emissions valve **80** may be moved into a position (by the crankshaft **16**) so as to reflect or obstruct acoustic emissions, but may be moved out of this position (by the crankshaft **16**) so as to not obstruct the bulk exhaust gas flow that has exited the exhaust system **60**.

The exhaust system reflector **80** may be integrated with the crankshaft **16** in any appropriate manner so that the exhaust system reflector **80** and the crankshaft **16** rotate in unison—the reflector **80** will rotate  $360^\circ$  each time that the crankshaft **16** rotates  $360^\circ$ . The reflector **80** could be separately attached to the crankshaft **16** in any appropriate manner, the reflector **80** could actually be part of the crankshaft **16**, or the like. The counterweight **90** may also be incorporated by the crankshaft **16** in any appropriate manner so that the counterweight **90** and the crankshaft **16** also rotate in unison—the counterweight **90** will rotate  $360^\circ$  each time that the crankshaft **16** rotates  $360^\circ$ . The counterweight **90** could be separately attached to the crankshaft **16** in any appropriate manner, the counterweight **90** could actually be part of the crankshaft **16**, or the like. In the illustrated embodiment, the counterweight **90** is mounted  $180^\circ$  from the reflector **80** relative to a rotational axis of the crankshaft **16** (e.g., the counterweight **90** and reflector **80** are disposed in opposing relation relative to the crankshaft **16**). The counterweight **90** functions to maintain an appropriate rotational balance for the crankshaft **16**. Other configurations where rotation of the crankshaft **16** moves the reflector **80** in the manner to be described herein may be utilized by the engine **10**.

The reflector **80** is located outside of the exhaust system **60**. The exhaust system **60** discharges to the atmosphere **78**. As such, the reflector **80** is located within the atmosphere **78**. In order to reflect at least part of the acoustic emissions back into the exhaust system **60**, but to not reflect any substantial portion of the bulk exhaust gas flow back into the exhaust system **60**, the reflector **80** is rotated into and out of alignment with the open end **66** of the exhaust conduit **64** through rotation of the crankshaft **16**. “In alignment” in relation to the relative positioning of the reflector **80** and the open end **66** of the exhaust conduit **64** means that at least part the flow out of the open end **66** of the exhaust conduit **64** impacts the reflector **80** in a manner that reflects at least part of this flow back into the

exhaust system **60** (where this flow is in the form of acoustic emissions in this instance). “Out of alignment” in relation to the relative positioning of the reflector **80** and the open end **66** of the exhaust conduit **64** means that the flow out of the open end **66** of the exhaust conduit **64** does not impact the reflector **80** in a manner that obstructs flow out of the exhaust system **60** (where this flow is in the form of the bulk exhaust gas flow in this instance). It should be appreciated that in certain instances the reflector **80** will be blocking/reflecting only a portion of the flow exiting the exhaust system **60** (e.g., as the reflector **80** is being rotated into alignment with the open end **66** of the exhaust conduit **64**, and where the flow in this instance is in the form of acoustic emissions).

FIG. **1** illustrates one rotational position of the crankshaft **16** and the reflector **80** where the reflector **80** and the open end **66** of the exhaust conduit **64** are not aligned—the reflector **80** is not positioned to reflect acoustic emissions back into the exhaust system **60** through the open end **66** of the exhaust conduit **64** (the reflector **80** should also not obstruct the bulk exhaust gas flow being discharged from the exhaust system **60** through the exhaust discharge port **66** when the reflector **80** is in the FIG. **1** position). FIGS. **2-4** each illustrate another rotational position of the crankshaft **16** and the reflector **80** where the reflector **80** and the open end **66** of the exhaust conduit **64** are aligned—the reflector **80** is now positioned to reflect acoustic emissions back into the exhaust system **60** through the open end **66** of the exhaust conduit **64** (at this point in time the bulk exhaust gas flow should not be at the reflector **80**, so the reflector **80** should not be generating a back pressure in the exhaust system **60** with the reflector **80** being in the position shown in FIGS. **2-4**). FIGS. **5-6** illustrate yet another rotational position of the crankshaft **16** and the reflector **80** where the reflector **80** and the open end **66** of the exhaust conduit **64** are once again no longer aligned—the reflector **80** is not positioned to reflect acoustic emissions back into the exhaust system **60** through the open end **66** of the exhaust conduit **64** (the reflector **80** should also not obstruct the bulk exhaust gas flow being discharged from the exhaust system **60** when the reflector **80** is in the position of FIGS. **5-6**).

FIG. **8A** is a schematic that illustrates features regarding the position/orientation of the reflector **80** relative to the exhaust system **60** such that the reflector **80** is able to reflect acoustic emissions from the exhaust system **60** back into the exhaust system **60** (or obstruct such acoustic emissions from even leaving the exhaust system **60**—discussed below in relation to FIG. **8C**). For a frame of reference, the rotational axis **18** for the crankshaft **16** is illustrated (but not the crankshaft **16** itself). Waves or acoustic emissions **72** are shown in FIG. **8A**, and advance along what may be characterized as a primary propagation vector **74** after exiting the open end **66** of the exhaust conduit **64**. In the FIG. **8A** configuration, the acoustic emissions **72** travel through the atmosphere **78** to reach the reflector **80** (again, as the reflector **80** is positioned within atmosphere **78**).

A reflecting surface **82** of the reflector **80** (in the FIG. **8A** position) may be characterized as being disposed at least substantially perpendicular to the above-noted primary propagation vector **74**. Note that this reflecting surface **82** of the reflector **80** is also oriented orthogonal relative to the rotational axis **18** of the crankshaft **16** in the illustrated embodiment. When the reflector **80** is aligned with the open end **66** of the exhaust conduit **64**, the primary propagation vector **74** intersects the reflecting surface **82** of the reflector **80**. It should also be noted that there are no mechanical obstructions of any type between the open end **66** of the exhaust conduit **64** and the reflecting surface **82** of the reflec-

tor **80**—the acoustic emissions **72** are not reflected in proceeding through the atmosphere **78** from the exhaust discharge port **66** to the reflecting surface **82** of the reflector **80**. The acoustic emissions **72** may be characterized as proceeding through free space between the exhaust discharge port **66** and the reflector **80**. Another characterization is that after exiting the exhaust system **60**, the movement of the acoustic emissions **72** to the location of the reflector **80** is not constrained to proceed along a pre-defined path. Yet another characterization is that in the space between the open end **66** of the exhaust system **60** and the reflector **80**, there are no radial boundaries to the flow of the exhaust—the exhaust does not flow through a containment structure of any type proceeding from the open end **66** of the exhaust conduit **64** to the location of the reflector **80** (when disposed in a reflecting position).

FIG. **8A** also shows that a projection **92** from the open end **66** of the exhaust conduit **64** intersects the reflecting surface **82** of the reflector **80** when the reflector **80** is at least partially aligned with the open end **66** of the exhaust conduit **64**. A perimeter of the projection **92** coincides with a perimeter of the open end **66** of the exhaust conduit **64**. This projection **92** may also be referred to as the primary exhaust output path.

FIG. **8B** illustrates the above-noted “other portion” of the exhaust from the exhaust system **60**—the bulk exhaust gas flow **70**. In this regard, the bulk exhaust gas flow **70** through the exhaust system **60** may be characterized as being collectively defined by a plurality of flow lines **68**. The bulk exhaust gas flow **70** (like the acoustic emissions **72**) may also be characterized as advancing along the above-noted primary propagation vector **74** after exiting the open end **66** of the exhaust conduit **64**. Although the reflecting surface **82** of the reflector **80** is still oriented orthogonal to this primary propagation vector **74**, the reflector **80** in the FIG. **8B** position is completely out of alignment with the open end **66** of the exhaust conduit **64**, and as such the reflector **80** does not obstruct the bulk exhaust gas flow **70** out of the exhaust system **60** (through the open end **66** of the exhaust conduit **64**). As further illustrative of this point, the above-noted projection **92** of the open end **66** of the exhaust conduit **64** does not intersect the reflecting surface **82** of the reflector **80** when the reflector **80** is completely out of alignment with the open end **66** of the exhaust conduit **64**.

Rotation of the crankshaft **16** moves the reflector **80** between a reflecting position and a non-reflecting position in relation to the acoustic emissions **72** that reach the exhaust discharge port **66** of the exhaust system **60**. Initially and in the case of the embodiment illustrated in FIGS. **1-8B**, the reflector **80** is actually spaced from the exhaust system **60**—acoustic emissions **72** from the exhaust system **60** exit the open end **66** of the exhaust conduit **64** and proceed through the atmosphere **78** before encountering the reflector **80** (when disposed in a reflecting position). The acoustic emissions **72** exiting through the exhaust discharge port **66** of the exhaust system **60** may be characterized as proceeding unimpeded until reaching the location of the reflector **80**—it may be that there are no reflections or mechanically-induced distortions of the acoustic emissions **72**, after exiting the exhaust system **60** and prior to reaching the location of the reflector **80** (which again moves between reflecting and non-reflecting positions). When the reflector **80** is in a reflecting position, these acoustic emissions **72** are reflected by the reflector **80** (e.g., back into the exhaust system **60** via the open end **66** of the exhaust conduit **64**, including back into the muffler **62**). When the reflector **80** is in a non-reflecting position, bulk exhaust gas flow **70** discharged through the exhaust discharge port **66** of the exhaust system **60** proceeds unimpeded both up to and

beyond the location of the reflector **80**. As such, the configuration and movement of the reflector **80** should not generate any significant back pressure within the exhaust system **60** and/or the cylinder **40**. Preferably the reflector **80** is never in the reflecting position when any bulk exhaust gas flow **70** reaches the reflector **80**.

FIGS. **8A** and **8B** also illustrate that the reflecting surface **82** of the reflector **80** is positioned at least substantially adjacent to or in proximity to the open end **66** of the exhaust conduit **64**. However, a small spacing **84** may in fact exist between the reflecting surface **82** of the reflector **80** and the open end **66** of the exhaust conduit **64**. The actual magnitude of the spacing **84** may be selected such that: 1) the reflector **80** will reflect at least part of the exhaust (e.g., acoustic emissions) from the exhaust system **60** back into the exhaust system **60** (via the open end **66** of the exhaust conduit **64**); and 2) the reflector **80** does not actually contact the exhaust conduit **64** as the reflector **80** is being rotated by the crankshaft **16** (e.g., accounting for thermal expansion and/or contraction during operation of the engine). In one embodiment, the spacing **84** is about 0.015 inch (measured along the maximum discharge velocity vector **72**).

FIG. **8C** illustrates a variation from that presented in FIG. **8A**. Here and when the reflector **80** is in the reflecting position, the reflector **80** may actually contact the open end **66** of the exhaust conduit **64**. As such, having the reflector **80** in the reflecting position in this case keeps acoustic emissions **72** (on their initial pass through the exhaust system **60**) from actually leaving the exhaust system **60** through the exhaust discharge port **66**.

The engine **10** again may include a counterweight **90** for rotational balancing of the crankshaft **16** (in view of the reflector **80** extending therefrom). FIG. **8D** shows the above-discussed relative positional relationship of the reflector **80** and counterweight **90**. FIG. **8D** also shows that the counterweight **90** is incorporated so that the counterweight **90** is not aligned with the output end **66** of the exhaust conduit **64** throughout the full 360° of rotation of the crankshaft **16** and the counterweight **90**. At no time is the counterweight **90** positioned to reflect any portion of the exhaust from the exhaust system **60** back into the exhaust system **60** (through the open end **66** of the exhaust conduit **64**).

The engine **10** may use one or more cylinders **40**, and furthermore may be of a two-cycle configuration (although the arrangement disclosed herein with regard to an exhaust system reflector **80** may be used/adapted for a four-cycle configuration as well). A schematic of a representative cylinder **40** for the engine **10** of FIGS. **1-7** is presented in FIG. **9**, and is of a two-cycle configuration. A piston **30** reciprocates within the cylinder **40**. In this regard, a connecting rod **20** is appropriately fixed relative to the crankshaft **16** and extends to a pivot **22**. A piston rod **24** extends from the pivot **22** to another pivot **26** associated with the piston **30**. As such, rotation of the crankshaft **16** about its rotational axis **18** will drive the piston **30** up and down in alternating fashion (in the view shown in FIG. **9**).

The cylinder **40** includes an intake port **44** and an exhaust port **46**. One or more valves may be associated with one or more of the ports **44**, **46**. An air/fuel mixture may be drawn into the engine case **14** during movement of the piston **30** from a bottom dead center position toward a top dead center position (after the piston **30** passes the intake port **44**). This movement of the piston **30** also compresses the air/fuel mixture that is contained within the combustion chamber **50** (located between the piston **30** and a closed end **52** of the cylinder **40**, and directed into the chamber **50** through the intake port **44**/engine case **14**). At some point in time during

the movement of the piston **30** toward its top dead center position, the piston **30** will isolate the exhaust port **46** from the combustion chamber **50**.

When the piston **30** reaches (or is at least near) its top dead center position, the spark plug **48** ignites the air/fuel mixture within the combustion chamber **50**, which drives the piston **30** from its top dead center position back toward its bottom dead center position. At some point in time during the movement of the piston **30** toward its bottom dead center position, the exhaust port **46** will be exposed to the combustion chamber **50** to allow a flow of exhaust out of the combustion chamber **50**, through the exhaust port **46**, and into the above-discussed exhaust system **60** (e.g., into/through the exhaust header **76**, and then into/through the muffler **62**, and then into/through the exhaust conduit **64**). Movement of the piston **30** toward its bottom dead center position will at some point in time compress the air/fuel mixture that has previously entered the engine case **14** through the intake port **44**.

Acoustic emissions **72** and bulk exhaust gas flow **70** will be discharged from the cylinder **40** on each revolution of the crankshaft **16**. During one part of the revolution of the crankshaft **16**, the reflector **80** will be in position to obstruct/reflect the acoustic emissions **72** from a given discharge from the cylinder **40** (their initial pass through the exhaust system **60**) (e.g., FIGS. 2-4). During the remainder of the revolution of the crankshaft **16**, the reflector **80** will be in position so as to not obstruct the corresponding bulk exhaust gas flow **70** from this same discharge from the cylinder **40**. It should be appreciated that when the reflector **80** is in a non-reflecting position (e.g., FIGS. 1, 5, and 6) acoustic emissions **72**, that have already been attenuated in at least some respect by the reflector **80**, may in fact proceed past the reflector **80**.

FIG. 10 presents a schematic of a section of a piston-cylinder wall including a cylinder wall **101**, an exhaust port window or exhaust port **102**, and a piston **103**. As the piston **103** moves along the cylinder wall **101**, the exhaust port **102** is repeatedly uncovered/opened and covered/closed. As a result of the compression or upstroke phase by the piston **103** and the intended combustion event in the engine cylinder, the piston **103** is forcibly pushed from the crankshaft position known as top-dead-center through the expansion or down stroke phase in response to the high pressure combustion product/exhaust gases retained in the cylinder. At a known crankshaft position in the expansion or down stroke of the piston **103**, the exhaust port **102** is uncovered or opened. The uncovering or opening of the exhaust port or exhaust valve **102** in the down stroke releases an acoustic wave into the exhaust system consisting of components such as a header and muffler. In the exhaust system, the acoustic wave may be subjected to conduits, chambers, and packing to absorb and create reflected waves with the objective of modifying the acoustic signature of the wave front exiting the muffler stinger or tail-pipe.

By reflecting the acoustic wave that initially exits the exhaust system stinger or tail-pipe back through an existing exhaust system, additional acoustic wave interactions with the existing packing and chambers, including destructive interference, serves to further modify the acoustic signature of the exhaust system.

To accomplish a timed reflector, the crankshaft angle (effectively a representation of time) corresponding to the arrival of the exhaust port pressure wave at the exit of the muffler stinger is evaluated. Crankshaft angle of the exhaust port pressure wave arrival at the muffler stinger is calculated using the exhaust system length measured from the exhaust port **102** to the exit of the stinger; velocity of the exhaust port pressure wave; and rotational speed of the engine.

Timing the reflector to be in position when the exhaust port acoustic wave exits the muffler stinger is important to achieving the desired acoustic signature. Of importance to achieving acoustic modification is the crankshaft position of the opening of the exhaust port **102** and timing the reflector to be in position at the appropriate crankshaft position. Examples of a nominal timing computation are presented in Table 1 as follows:

TABLE 1

Crankshaft Rotation And Transit of Exhaust Port Pressure Wave					
Engine Speed	crankshaft	Distance pressure wave travels per deg of	Crankshaft rotation, degrees, during transit of pressure wave from exhaust port window to exit of stinger, L		
			L = 26 in	L = 30 in	L = 34 in
revolution/ min	revolution/ sec	rotation in/deg	angle deg	angle deg	angle deg
3200	53.3	1.06	24.5	28.2	32.0
7200	120	0.47	55.1	63.5	72.0

Exhaust Port Open at 110 deg after Top Dead Center

Exhaust Port Close at 110 deg before Top Dead Center

Acoustic wave (sound wave) speed, estimate = 1700 ft/sec

A representation of the above-noted timing discussed above is shown in FIG. 11. Consider for example the desire to modify the acoustic signature of a single cylinder engine between 3200 rev/min and 7200 rev/min; exhaust system length of 30 in; the exhaust port **102** opens **202** and thereby initiates the exhaust port acoustic wave at 110 degrees from engine top-dead-center **201**; exhaust port acoustic wave speed of 1,700 ft/sec; the leading section of the reflector is centered at approximately 135 deg and identified by reference numeral **203** (which equals the sum of 110 deg crankshaft angle of the exhaust port opening and the 25 degree crankshaft angle (i.e., time for the 3200 rev/min exhaust port acoustic wave to travel through the exhaust system)) from top-dead-center **201**, and the trailing section of the reflector is centered at approximately 175 deg (reference numeral **204**, which equals the sum of 110 deg crankshaft angle exhaust port opening and the 7200 rev/min 65 degree crankshaft angle (i.e., time for the 7200 rev/min exhaust port acoustic wave to travel through the exhaust system) from top-dead-center **201** spans the estimated crankshaft angles corresponding to the initial arrival of the exhaust port acoustic wave at the stinger exit for engine speeds between 3200 rev/min and 7200 rev/min). The nominal angle swept by the reflector, theta **205**, is a relatively small portion of the engine cycle and does not include the angular position of exhaust port close **206**. For optimal effectiveness, the reflector must fully cover the stinger exit cross-sectional area. Hence, the leading and trailing sections of the reflector should completely cover the cross sectional area of the stinger exit.

In addition to timing of the reflector deployment, the nominal physical dimensions of the reflector are guided by the calculation results presented in Table 1 above as well. Returning to the previous example of a single cylinder engine, having an exhaust system length of 30 inches; desired additional acoustic signature modification between 3200 rev/min and 7200 rev/min engine speed; the nominal angular sweep **205** of the reflector is described by the difference between the crankshaft angular position when the exhaust port acoustic wave arrives at the stinger exit at the highest engine speed of interest and the crankshaft angular position when the exhaust port acoustic wave arrives at the stinger exit at the lowest

engine speed of interest. For the example under consideration, the included angle **205** of the reflector of approximately 35 degrees is a starting point of the angular dimension for sizing the timed reflector. For optimal effectiveness, the reflector should fully cover the stinger exit cross-sectional area as noted. Hence, the leading and trailing sections of the reflector should completely cover the cross-sectional area of the stinger exit and should in fact extend beyond the calculated estimate of angle **205**. As should be recognized by those of skill in the art, the sizing computations presented in Table 1 utilize certain assumptions and are intended to provide a starting point for the sizing of the reflector. It is well recognized in the art of acoustic modulating devices, including mufflers and silencers, that additional adjustments or tuning may be required to achieving the desired acoustic signature.

FIGS. **12** and **13** show a reflector **310** attached to and rotatable with a crankshaft **320**. The length dimension of the reflector **310** (how far the reflector **310** extends from the crankshaft **320**) depends on parameters including but not limited to the distance from the centerline **324** and orientation of the crankshaft **320** to the centerline **334** and diameter of the exhaust system stinger **330** at its open end **332**. The reflector **310** may be oriented such that its reflecting surface is disposed at least substantially perpendicular to the exhaust path. Again, preferably the reflector **310** is timed such that it reflects the acoustic portion of the exhaust back into the exhaust system, but does not obstruct any substantial portion of the bulk exhaust gas flow (e.g., which would generate back pressure in the exhaust system and an engine cylinder(s)). Such a back pressure will likely adversely affect performance of the engine. Although reflecting the acoustic portion of the exhaust back into the exhaust system should not significantly impact engine performance, a resonator could be included in the exhaust system (e.g., within the muffler) to further accommodate acoustic wave destructive interference. Such a reflected wave resonator could be configured so as to not function as a resonator for the acoustic waves originating at the engine exhaust port (e.g., **102**).

FIGS. **12/13** and FIG. **14** are schematics of one and two cylinder timed reflectors **310**, **410**, respectively. Shared attributes of the two exemplary reflectors **310**, **410** are timed reflector surfaces and crankshaft connection **314** and **414**. Crankshaft connection is not limited to post manufacture installation using a clamshell or similar clamping attachment configuration. Inclusion of the timed reflector **310**, **410** can also be accomplished as an inherent attribute of the crankshaft design. Inclusion of the reflector **310**, **410** directly in the crankshaft design eliminates the need for post assembly clocking/positioning of the reflector **310**, **410** with respect to top-dead-center to achieve the desired acoustic modification. Consideration must be given to crankshaft balance when including the reflector **310**, **410** either as a removable or integral device. Specifically, to maintain the balance of the rotating crankshaft **320**, **420**, the need for inclusion of a counterweight must be evaluated. The simplicity of the reflector design lends itself to ready incorporation of counterweight as needed.

FIG. **6** illustrates an additional consideration in the design of a timed reflector in accordance with the foregoing: clearance **650** between the open end **532** of the stinger **530** and the reflecting surface of the timed reflector **410**. To allow for thermal expansion of the components, it has been determined that 0.015 inches is an initial reasonable clearance value.

Those of ordinary skill in the art will recognized that physical configuration, spatial orientation, dimensions of the timed reflector is not prescribed by the description provided herein nor limited to the exemplary configurations. Additionally,

those of ordinary skill in the art will recognize that there are many choices of construction material of the timed reflector and that the reflector/valve may incorporate surface texture, treatments, perforations and the like to achieve the desired characteristics of the reflected pressure wave and hence the desired acoustic signature.

The foregoing description of the present invention has been presented for purposes of illustration and description. Furthermore, the description is not intended to limit the invention to the form disclosed herein. Consequently, variations and modifications commensurate with the above teachings, and skill and knowledge of the relevant art, are within the scope of the present invention. The embodiments described hereinabove are further intended to explain best modes known of practicing the invention and to enable others skilled in the art to utilize the invention in such, or other embodiments and with various modifications required by the particular application(s) or use(s) of the present invention. It is intended that the appended claims be construed to include alternative embodiments to the extent permitted by the prior art.

What is claimed:

**1.** An engine, comprising:

a first cylinder;

a first piston disposed within said first cylinder;

a rotatable crankshaft interconnected with said first piston;

an exhaust system fluidly connected with said first cylinder

and comprising an exhaust discharge port; and

a reflector extending from and rotated by said crankshaft,

wherein said reflector is positioned within atmosphere,

and wherein said reflector is disposable into alignment

with and completely out of alignment with said exhaust

discharge port by rotation of said crankshaft.

**2.** The engine of claim **1**, wherein said reflector obstructs acoustic emissions that progress through said exhaust system when said reflector is aligned with said exhaust discharge port.

**3.** The engine of claim **2**, wherein said reflector does not obstruct bulk exhaust gas flow out of said exhaust discharge port when said reflector is completely out of alignment with said exhaust discharge port.

**4.** The engine of claim **2**, wherein a bulk exhaust gas flow from said cylinder does not reach said reflector when said reflector is aligned with said exhaust discharge port.

**5.** The engine of claim **1**, wherein said reflector does not obstruct bulk exhaust gas flow out of said exhaust discharge port when said reflector is completely out of alignment with said exhaust discharge port.

**6.** The engine of claim **1**, wherein a projection extending from said exhaust discharge port intersects said reflector when said reflector is aligned with said exhaust discharge port, and wherein a perimeter of said projection coincides with a perimeter of said exhaust port.

**7.** The engine of claim **6**, wherein said projection does not intersect said reflector when said reflector is completely out of alignment with said exhaust discharge port.

**8.** The engine of claim **6**, wherein said acoustic emissions proceed unimpeded from said exhaust discharge port to said reflector.

**9.** The engine of claim **1**, wherein a projection extending from said exhaust discharge port does not intersect said reflector when said reflector is completely out of alignment with said exhaust discharge port, and wherein a perimeter of said projection coincides with a perimeter of said exhaust discharge port.

**10.** The engine of claim **1**, a bulk exhaust gas flow from said cylinder is discharged through said exhaust discharge port along a primary propagation vector, wherein said primary

**11**

propagation vector intersects said reflector when said reflector is aligned with said exhaust discharge port, and wherein said primary propagation vector does not intersect said reflector when said reflector is completely out of alignment with said exhaust discharge port.

**11.** The engine of claim **10**, wherein a reflecting surface of said reflector is oriented orthogonal to said primary propagation vector.

**12.** The engine of claim **1**, wherein a reflecting surface of said reflector is oriented orthogonal to a rotational axis of said crankshaft.

**13.** The engine of claim **1**, wherein said reflector is positioned adjacent to, but spaced from, said exhaust discharge port when said reflector is aligned with said exhaust discharge port.

**14.** The engine of claim **13**, wherein said reflector is spaced about 0.015 inches from said exhaust discharge port when said reflector is aligned with said exhaust discharge port.

**12**

**15.** The engine of claim **1**, wherein said reflector is disposed in abutting relation to said exhaust discharge port when said reflector is aligned with said exhaust discharge port.

**16.** The engine of claim **15**, wherein said counterweight and said reflector are disposed at the same location along a common rotational axis.

**17.** The engine of claim **16**, wherein said counterweight is at all times disposed completely out of alignment with said exhaust discharge port.

**18.** The engine of claim **1**, wherein said exhaust system comprises a muffler and an exhaust conduit extending from said muffler, wherein said exhaust discharge port is defined by an open end of said exhaust conduit.

**19.** The engine of claim **1**, further comprising:  
a counterweight extending from and rotated by said crankshaft.

**20.** The engine of claim **19**, wherein said counterweight is at all times disposed completely out of alignment with said exhaust discharge port.

\* \* \* \* \*