

US009264920B2

(12) **United States Patent**
Lin

(10) **Patent No.:** **US 9,264,920 B2**
(45) **Date of Patent:** **Feb. 16, 2016**

(54) **NETWORK MANAGING METHOD AND DEVICE FOR WIRELESS NETWORK SYSTEM**

(56) **References Cited**

(71) Applicant: **Wistron NeWeb Corporation**, Hsinchu (TW)

(72) Inventor: **Yung-Cheng Lin**, Hsinchu (TW)

(73) Assignee: **Wiston NeWeb Corporation**, Hsinchu Science Park, Hsinchu (TW)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 160 days.

(21) Appl. No.: **14/188,700**

(22) Filed: **Feb. 25, 2014**

(65) **Prior Publication Data**
US 2015/0078199 A1 Mar. 19, 2015

(30) **Foreign Application Priority Data**
Sep. 17, 2013 (TW) 102133624 A

(51) **Int. Cl.**
H04W 24/02 (2009.01)
H04W 64/00 (2009.01)
G01S 5/14 (2006.01)

(52) **U.S. Cl.**
CPC *H04W 24/02* (2013.01); *G01S 5/14* (2013.01); *H04W 64/00* (2013.01)

(58) **Field of Classification Search**
None
See application file for complete search history.

U.S. PATENT DOCUMENTS

7,764,231	B1 *	7/2010	Karr et al.	342/457
7,860,516	B2 *	12/2010	Hodges et al.	455/456.1
7,970,411	B2	6/2011	Pande	
2005/0037775	A1 *	2/2005	Moeglein et al.	455/456.1
2009/0016279	A1 *	1/2009	Beser	370/329
2010/0135178	A1	6/2010	Aggarwal	
2012/0054302	A1 *	3/2012	Priyadarshan et al.	709/217
2013/0053056	A1	2/2013	Aggarwal	
2013/0072230	A1 *	3/2013	Bansal et al.	455/456.2
2013/0170374	A1 *	7/2013	Aljadeff	370/252

FOREIGN PATENT DOCUMENTS

TW	200948127	11/2009
TW	201334600	8/2013

* cited by examiner


Primary Examiner — Hicham Foud

(74) *Attorney, Agent, or Firm* — Winston Hsu; Scott Margo

(57) **ABSTRACT**

A network managing method is utilized for a wireless network system. The wireless network includes multiple wireless access equipments and multiple user equipments. The method uses the wireless access equipments to measure a plurality of echo back time of the user equipments to obtain multiple measurement results, determines locations of the user equipments according to the measurement results and locations of the wireless access equipments, and adjusts wireless operations from the wireless access equipments to the user equipments according to the locations and priorities of the user equipments.

18 Claims, 9 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7A




FIG. 7B




FIG. 7C

1

NETWORK MANAGING METHOD AND DEVICE FOR WIRELESS NETWORK SYSTEM

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a network managing method and a network managing device for a wireless network system, and more particularly, to a network managing method and a network managing device capable of adaptively providing wireless services for user equipments in a wireless network system to provide a convenient network environment.

2. Description of the Prior Art

With advances in wireless communication technology, a portable wireless device, such as a notebook, a personal digital assistant (PDA), a tablet, a smart phone, etc., has become an essential device for people in work or in life, and a user may simultaneously carry or use multiple portable wireless devices. Under such a condition, how to manage operations of the multiple portable wireless devices in a wireless network system becomes one of the industry goals.

SUMMARY OF THE INVENTION

It is therefore an objective of the present invention to provide a network managing method and a network managing device for a wireless network system to improve disadvantages of the prior art, so as to provide a convenient network environment.

The present invention discloses a network managing method for a wireless network system, wherein the wireless network system comprises a plurality of wireless access equipments and at least one user equipment. The network managing method comprises the plurality of wireless access equipments measuring a plurality of echo back time of the at least one user equipment to obtain a plurality of measurement results; determining locations of the at least one user equipment according to the plurality of measurement results and locations of the plurality of wireless access equipments; and adjusting wireless operations from the plurality of wireless access equipments to the at least one user equipment according to the locations and priorities of the at least one user equipment.

The present invention further discloses a network managing device for a wireless network system, wherein the wireless network system comprises a plurality of wireless access equipments and at least one user equipment. The network managing device comprises a processor; and a memory for storing a program code to manage the wireless network system, wherein the program code instructs the processor to perform following steps: controlling the plurality of wireless access equipments to measure a plurality of echo back time of the at least one user equipment to obtain a plurality of measurement results; determining locations of the at least one user equipment according to the plurality of measurement results and locations of the plurality of wireless access equipments; and adjusting wireless operations from the plurality of wireless access equipments to the at least one user equipment according to the locations and priorities of the at least one user equipment.

These and other objectives of the present invention will no doubt become obvious to those of ordinary skill in the art after

2

reading the following detailed description of the preferred embodiment that is illustrated in the various figures and drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic diagram of a wireless network system according to an embodiment of the present invention.

FIG. 2 is a schematic diagram of a network managing process according to an embodiment of the present invention.

FIG. 3 is a schematic diagram of a principle of a triangulation method utilized for the network managing process in FIG. 2.

FIG. 4 to FIG. 7C are schematic diagrams of operating situations of the wireless network system in FIG. 1.

DETAILED DESCRIPTION

Please refer to FIG. 1, which is a schematic diagram of a wireless network system **10** according to an embodiment of the present invention. The wireless network system **10** includes wireless access equipments AP₁-AP_n, user equipments CLT₁-CLT_m, and a network managing device **100**. The wireless access equipments AP₁-AP_n may be access points adapted to a wireless network and are not limited hereinafter. The wireless access equipments AP₁-AP_n may perform data exchanges with the user equipments CLT₁-CLT_m by a wireless transmission method, such that the user equipments CLT₁-CLT_m may access an Intranet, Internet, etc. The network managing device **100** includes a processor **102** and a storage device **104**. The processor **102** may be a microprocessor or an application-specific integrated circuit (ASIC). The storage device **104** may be any one data storage device. For example, the storage device **104** may be a read-only memory (ROM), a random-access memory (RAM), a CD-ROMs, a magnetic tapes, a floppy disks, an optical data storage devices, etc., which is not limited hereinafter. Additionally, a program code **106** is stored in the storage device **104** to instruct the processor **102** to receive echo back time measured by the wireless access equipments AP₁-AP_n and to control wireless operations of the wireless access equipments AP₁-AP_n accordingly.

Specifically, please refer to FIG. 2, which is a schematic diagram of a network managing process **20** according to an embodiment of the present invention. In the embodiment, the network managing process **20** is performed in the network managing device **100** in FIG. 1 and the network managing process **20** may be compiled as the program code **106**, which is stored in the storage device **104** to control the processor **102** to perform the network managing process **20**. As shown in FIG. 2, the network managing process **20** includes the following steps:

Step **200**: start.

Step **202**: control the wireless access equipments AP₁-AP_n to measure a plurality of echo back time of the user equipments CLT₁-CLT_m to obtain a plurality of measurement results.

Step **204**: determine locations of the user equipments CLT₁-CLT_m according to the plurality of measurement results and locations of the wireless access equipments AP₁-AP_n.

Step **206**: adjust the wireless operations from the wireless access equipments AP₁-AP_n to the user equipments CLT₁-CLT_m according to the locations and priorities of the user equipments CLT₁-CLT_m.

Step **208**: end.

Thus, according to the network managing process 20, the network managing device 100 controls the wireless access equipments AP₁-AP_n to measure the plurality of echo back time of the user equipments CLT₁-CLT_m to accordingly determine the locations of the user equipments CLT₁-CLT_m. Then, the network managing device 100 adjusts the wireless operations from the wireless access equipments AP₁-AP_n to the user equipments CLT₁-CLT_m based on both the priorities and the locations of the user equipments CLT₁-CLT_m. Under such a situation, the wireless access equipments AP₁-AP_n may provide proper wireless services for the user equipments CLT₁-CLT_m according to the locations and the priorities of the user equipments CLT₁-CLT_m.

In detail, in step 202, the plurality of echo back time of the user equipments CLT₁-CLT_m measured by the wireless access equipments AP₁-AP_n may be periods between the wireless access equipments AP₁-AP_n outputting beacons to the user equipments CLT₁-CLT_m and the wireless access equipments AP₁-AP_n receiving response signals corresponding to the beacons from the user equipments CLT₁-CLT_m. In other words, since a required time of a signal transmission is related to a distance between a transmitter and a receiver, the network managing device 100 may determine the distances from each user equipment to corresponding neighbor wireless access equipments according to the plurality of echo back time of the user equipments CLT₁-CLT_m to obtain the locations of the user equipments CLT₁-CLT_m by utilizing a triangulation method in step 204.

The principle of the triangulation method is shown in FIG. 3. A user equipment CLT_a may receive the beacons respectively outputted from the wireless access equipments AP_{a1}, AP_{a2}, and AP_{a3}, and then the user equipment CLT_a outputs the response signals to the wireless access equipments AP_{a1}, AP_{a2}, and AP_{a3}. When the wireless access device AP_{a1} outputs the beacon to the user equipment CLT_a and receives the corresponding response signal from the user equipment CLT_a, the wireless access device AP_{a1} may obtain the echo back time of the user equipment CLT_a, which is related to the location of the user equipment CLT_a. Then, the network managing device 100 may determine that the user equipment CLT_a is roughly located on a circle with a center at the wireless access equipment AP_{a1} and with a radius R₁. Accordingly, the network managing device 100 may also determine that the user equipment CLT_a is roughly located on a circle with a center at the wireless access equipment AP_{a2} and with a radius R₂, and on a circle with a center at the wireless access equipment AP_{a3} and with a radius R₃. Thus, the network managing device 100 may determine that the user equipment CLT_a is roughly located at an intersectional point of the circles with the radiuses R₁, R₂, and R₃, and the network managing device 100 may determine the location of the user equipment CLT_a according to the locations of the wireless access equipments AP_{a1}, AP_{a2}, and AP_{a3}.

Notably, FIG. 3 is utilized for explaining the principle of the triangulation method and is not to limit the scope of the present invention. For example, the network managing device 100 is not limited to determine the location of the user equipment by utilizing three wireless access equipments, and the network managing device 100 may also determine the location of the user equipment by utilizing more than three wireless access equipments to enhance the accuracy of determination.

Next, in step 206, after the network managing device 100 determines the locations of the user equipments CLT₁-CLT_m, the network managing device 100 further adjusts the

wireless operations of the wireless access equipments AP₁-AP_n according to the priorities of the user equipments CLT₁-CLT_m, such as adjusting beam-forming methods and mesh routing methods of the wireless access equipments AP₁-AP_n.

For example, in an embodiment, as shown in FIG. 4, wireless access equipments AP_{b1}, AP_{b2}, and AP_{b3} in the wireless access equipments AP₁-AP_n provide the wireless services for user equipment groups CLT_{G1} and CLT_{G2} of the user equipments CLT₁-CLT_m, and a priority of the user equipment group CLT_{G1} is greater than a predefined degree or greater than a priority of the user equipment group CLT_{G2}. Then, according to the embodiment of the present invention, the network managing device 100 may control the wireless access equipments AP_{b1} and AP_{b2} to adjust the beam-forming methods according to the location of the user equipment group CLT_{G1}, such that the wireless signal beams of the wireless access equipments AP_{b1} and AP_{b2} may substantially point toward the user equipment group CLT_{G1} to prioritize providing the wireless services for the user equipment group CLT_{G1}. In addition, the network managing device 100 controls the wireless access equipments AP_{b3} to maintain the wireless operation with all directions to ensure normal operations of wireless communication.

In another embodiment, the network managing device 100 may further adjust the mesh routing methods of the wireless access equipments AP₁-AP_n. As shown in FIG. 5, for simplicity, only the wireless access equipments AP_{c1}-AP_{c9} in the wireless access equipments AP₁-AP_n are described in FIG. 5. The wireless access equipments AP_{c1}-AP_{c9} are connected to a router 500 of an external network, and a user equipment with higher priority is in a region Z₁. Thus, the network managing device 100 adjusts the beam-forming methods of the wireless access equipments AP_{c1} and AP_{c2} to prioritize providing the wireless services for the user equipment in the region Z₁. Additionally, for ensuring that the user equipment in the region Z₁ may preferentially perform data exchanges via the router 500, the network managing device 100 further increases the routing priority of the path from the wireless access equipment AP_{c1} to the wireless access equipment AP_{c9} (i.e. the dashed line path in FIG. 5) and the path from the wireless access equipment AP_{c2} through the wireless access equipment AP_{c3} to the wireless access equipment AP_{c9} (i.e. the dotted line path in FIG. 5). Moreover, the path from the wireless access equipment AP_{c6} to the wireless access equipment AP_{c1} and the path from the wireless access equipment AP_{c5} to the wireless access equipment AP_{c3} may be temporally forbade. Thereby, the wireless access equipment AP_{c1} and AP_{c2} may ensure to prioritize performing signal exchanges with the wireless access equipment AP_{c9}, such that the user equipment in the region Z₁ may preferentially perform the data exchanges by the router 200. On the other sides, controlling the wireless access equipment AP_{c4} to connect to the wireless access equipment AP_{c9} only through the wireless access equipment AP_{c3}, or allowing the wireless access equipment AP_{c4} to directly connect to the wireless access equipment AP_{c9} under specific applications may also facilitate the wireless access equipments AP_{c1} and AP_{c2} to prioritize providing the wireless services for the user equipment in the region Z₁.

Notably, the mesh routing adjustment in FIG. 5 is utilized for ensuring that the wireless access equipments AP_{c1} and AP_{c2} may prioritize providing the wireless services for the user equipment in the region Z₁, which is not limited herein-after. For example, in another embodiment, in addition to directly connect to the wireless access equipment AP_{c9}, the

5

wireless access equipment AP_c1 may also connect to the wireless access equipment AP_c9 through the wireless access equipment AP_c3, and the wireless access equipment AP_c3 is configured to prioritize performing the signals from the wireless access equipments AP_c1 and AP_c2. In addition, the wireless access equipment AP_c4 may also be controlled to connect to the wireless access equipment AP_c3. All of the above belong to the scope of the present invention.

Furthermore, please refer to FIG. 6, if the user equipment in the region Z1 moves toward a region Z2, according to the embodiment of the present invention, since the wireless access equipment AP_c3 is close to the region Z2, the network managing device 100 may control the wireless access equipment AP_c3 instead of the wireless access equipment AP_c2 to prioritize providing the wireless services for the user equipment in the region Z2 according to the movements of the user equipment. Additionally, the network managing device 100 may also adjust the beam-forming methods of the wireless access equipments AP_c1 and AP_c3 to adjust the wireless signal beams of the wireless access equipments AP_c1 and AP_c3 to substantially point toward the region Z2. Under such a situation, for ensuring that the user equipment in the region Z2 may preferentially perform the data exchanges by the router 200, the network managing device 100 may further increase the routing priority of the path from the wireless access equipment AP_c1 to the wireless access equipment AP_c9 (i.e. the dashed line path in FIG. 6) and the path from the wireless access equipment AP_c3 to the wireless access equipment AP_c9 (i.e. the dotted line path in FIG. 6). Additionally, the path from the wireless access equipment AP_c6 to the wireless access equipment AP_c1, the path from the wireless access equipment AP_c2 to the wireless access equipment AP_c3, and the path from the wireless access equipment AP_c5 to the wireless access equipment AP_c3 may also be temporally forbade. Thereby, the wireless access equipments AP_c1 and AP_c3 may ensure to prioritize performing signals exchanges with the wireless access equipment AP_c9, such that the user equipment in the region Z2 may preferentially perform the data exchanges by the router 200.

In the above embodiment, the network managing device 100 determines the locations or the movement situations of the user equipments CLT_1-CLT_m according to the echo back time measured by the wireless access equipments AP_1-AP_n. Then, the network managing device 100 accordingly adjusts the wireless operations of the wireless access equipments AP_1-AP_n to prioritize providing the wireless services for the user equipment with higher priority. However, in addition to adjust the wireless operations of the wireless access equipments AP_1-AP_n passively according to the movement situations, the network managing device 100 of the present invention may also actively adjust the wireless operations of the wireless access equipments AP_1-AP_n in other embodiments. That is, when the network managing device 100 detects that the user equipment, which is required to be preferentially serviced, moves from a region to another region, the network managing device 100 may previously adjust the wireless operations of the wireless access equipments AP_1-AP_n to deal with the movement situation of the user equipment. The detecting methods may be based on the movement of the user equipment (such as the moving speed or the moving direction, etc.) or based on a predefined path configuration data.

For example, as shown in FIG. 5 and FIG. 6, if the network managing device 100 determines that the user equipment in the region Z1 starts moving to the region Z2 according to the measurement results of the wireless access equipments

6

AP_1-AP_n, the network managing device 100 may previously adjust the wireless operations of the wireless access equipments AP_c1-AP_c9 to be the situation in FIG. 6. Moreover, if a path configuration data indicates that the user equipment in the region Z1 is scheduled to move to the region Z2 at a specific time, the network managing device 100 may adjust the wireless operations of the wireless access equipments AP_c1-AP_c9 to be the situations in FIG. 6 before or just at the specific time. As a result, the network managing device 100 may previously adjust the wireless operations of the wireless access equipments AP_c1-AP_c9 according to the possible movement situations of the user equipment to improve the network efficiency.

On the other hands, in the wireless network system 10, with a continuous increase of the obtained movement situations of the user equipments CLT_1-CLT_m, the network managing device 100 may accordingly determine building shields in a signal coverage of the wireless network system 10 to further adjust the wireless operations of the wireless access equipments AP_1-AP_n. For example, please refer to FIG. 7A, which is a schematic diagram of a signal coverage 70 of the wireless network system 10. In FIG. 7A, the solid lines represent the movement situations of the user equipments CLT_1-CLT_m, which are statistically analyzed by the network managing device 100 and are the normal moving situations of the user equipments CLT_1-CLT_m in the signal coverage 70. The network managing device 100 may analyze the movement types of the user equipments CLT_1-CLT_m (such as to avoid or to bypass some certain regions) according to the normal moving situations of the user equipments CLT_1-CLT_m, so as to determine building shields BR1-BR8 in the signal coverage 70, i.e. shown in FIG. 7B. When the building shields BR1-BR8 are determined, the network managing device 100 further determines moving trends of the user equipments CLT_1-CLT_m accordingly to adjust the wireless operations of the wireless access equipments AP_1-AP_n. For example, in FIG. 7C, if a user equipment CLT_d1 with higher priority move toward the building shield BR1, the network device 100 may determine that the user equipment CLT_d1 may bypass the building shield BR1, and the wireless signal beams are not required to be adjusted to point to the building shield BR1. If another user equipment CLT_d2 with higher priority is located in a region surrounded by the building shield BR2-BR5, the network device 100 may determine that the user equipment CLT_d2 may stay in the region or move to an outside of the region from the gap between the building shield BR2 and BR5, and the network device 100 may prepare for the two situations in advance. Furthermore, if a user equipment group CLT_Gd with higher priority moves to a region surrounded by the building shields BR5-BR8 at a specific time, the network managing device 100 determines that the user equipment group CLT_Gd may only move into the region surrounded by the building shields BR5-BR8 from the gap between the building shield BR5 and BR7, and the network device 100 may prepare for the movement situation in advance.

As can be seen, the embodiments of the present invention may determine the locations or the movement types of the user equipments CLT_1-CLT_m according to the echo back time measured by the wireless access equipments AP_1-AP_n to actively or passively adjust the wireless operations of the wireless access equipments AP_1-AP_n for the specific user equipments with higher priority. Notably, the above embodiments are utilized for explaining the present invention, and any alternations according to the above embodiments all belong to the scopes of the present invention. For example, the determination of the echo back time is not lim-

ited by the beacons and the corresponding response signals. Packages or signals of other types may also be utilized in the present invention for the determination of the echo back time, which are not limited hereinafter. In general, the beacons are periodically outputted from the wireless access equipments AP_1-AP_n to determine whether the wireless connections are normally working. In one embodiment, the network managing device 100 may also control the wireless access equipments AP_1-AP_n to output the specific packages for accordingly determining the echo back time and the locations of user equipments. Furthermore, the number n of the wireless access equipments AP_1-AP_n is required to be greater than or equal to 3 to correctly perform the triangulation method, and the network device 100 may previously obtain the locations of the wireless access equipments AP_1-AP_n. In addition to adjusting the beam-forming methods and the mesh routing methods of the wireless access equipments AP_1-AP_n, the network device 100 may also prioritize providing the wireless services for the specific user equipments by adjusting the operating powers of the wireless access equipments AP_1-AP_n or by other methods, etc.

On the other hands, the determining or configuring methods of the priority are also not limited to specific rules. For example, in one embodiment, a priority configuration table may be previously stored in the storage device 104 of the network managing device 100 to record the media access control (MAC) addresses and the priorities of the specific user equipments. When any user equipment moves into the signal coverage of the wireless network system 10 to establish the connections with the specific wireless access equipments, the network managing device 100 may determine the priority of the user equipment according to the priority configuration table. Moreover, in another embodiment, the priorities may also be related to the locations of the regions; that is, the network managing device 100 may control the wireless access equipments AP_1-AP_n to prioritize providing the wireless services for the user equipment located in the specific region. All of the above belong to the scope of the present invention.

The prior art may not adaptively provide the wireless services for the user equipments with different priorities. In comparison, the present invention may actively or passively provide the proper wireless services according to the locations, the priorities, or the movement types, etc. to provide a convenient network environment.

Those skilled in the art will readily observe that numerous modifications and alterations of the device and method may be made while retaining the teachings of the invention. Accordingly, the above disclosure should be construed as limited only by the metes and bounds of the appended claims.

What is claimed is:

1. A network managing method for a wireless network system, wherein the wireless network system comprises a plurality of wireless access equipments and a plurality of user equipments, the network managing method comprising:

measuring, by the plurality of wireless access equipments, a plurality of echo back time of the plurality of user equipments to obtain a plurality of measurement results; determining locations of the plurality of user equipments according to the plurality of measurement results and locations of the plurality of wireless access equipments; and

adjusting wireless operations from the plurality of wireless access equipments to the plurality of user equipments according to the locations and priorities of the plurality of user equipments.

2. The network managing method of claim 1, wherein a number of the plurality of wireless access equipments is greater than or equal to 3.

3. The network managing method of claim 1, wherein the plurality of echo back time are periods between the plurality of wireless access equipments outputting a plurality of beacons to the plurality of user equipments and the plurality of wireless access equipments receiving a plurality of response signals corresponding to the plurality of beacons from the plurality of user equipments.

4. The network managing method of claim 1, wherein adjusting the wireless operations from the plurality of wireless access equipments to the plurality of user equipments comprises adjusting beam forming methods and mesh routing methods of the plurality of wireless access equipments for the plurality of user equipments.

5. The network managing method of claim 1, wherein the step of adjusting the wireless operations from the plurality of wireless access equipments to the plurality of user equipments according to the locations and the priorities of the plurality of user equipments comprises:

controlling the plurality of wireless access equipments to prioritize providing wireless services for a user equipment of the plurality of user equipments when a priority of the user equipment is greater than a predefined degree.

6. The network managing method of claim 1, further comprising:

determining movement situations of the plurality of user equipments according to the plurality of measurement results; and

adjusting the wireless operations from the plurality of wireless access equipments to the plurality of user equipments according to the movement situations and the priorities of the plurality of user equipments.

7. The network managing method of claim 6, wherein the step of adjusting the wireless operations from the plurality of wireless access equipments to the plurality of user equipments according to the movement situations and the priorities of the plurality of user equipments comprises:

controlling the plurality of wireless access equipments to prioritize providing wireless services for a user equipment of the plurality of user equipments when a priority of the user equipment is greater than a predefined degree and the user equipment moves toward a region.

8. The network managing method of claim 1, further comprising:

receiving a path configuration data; and

adjusting the plurality of wireless access equipments to prioritize providing wireless services for a region within a period when the path configuration data indicates that the plurality of user equipments moves to the region within the period.

9. The network managing method of claim 1, further comprising:

determining normal moving situations of the plurality of user Equipments in a signal coverage of the wireless network system according to the plurality of measurement results;

determining at least one building shield in the signal coverage according to the normal moving situations of the plurality of user equipments in the signal coverage of the wireless network system; and

determining moving trends of the plurality of user equipments according to the at least one building shield and the locations of the plurality of user equipments to adjust

9

the wireless operations from the plurality of wireless access equipments to the plurality of user equipments.

10. A network managing device for a wireless network system, wherein the wireless network system comprises a plurality of wireless access equipments and a plurality of user equipments, the network managing device comprising:

a processor; and

a memory for storing a program code to manage the wireless network system,

wherein the program code instructs the processor to perform following steps:

controlling the plurality of wireless access equipments to measure a plurality of echo back time of the plurality of user equipments to obtain a plurality of measurement results;

determining locations of the plurality of user equipments according to the plurality of measurement results and locations of the plurality of wireless access equipments; and

adjusting wireless operations from the plurality of wireless access equipments to the plurality of user equipments according to the locations and priorities of the plurality of user equipments.

11. The network managing device of claim **10**, wherein a number of the plurality of wireless access equipments is greater than or equal to 3.

12. The network managing device of claim **10**, wherein the plurality of echo back time are periods between the plurality of wireless access equipments outputting a plurality of beacons to the plurality of user equipments and the plurality of wireless access equipments receiving a plurality of response signals corresponding to the plurality of beacons from the plurality of user equipments.

13. The network managing device of claim **10**, wherein adjusting the wireless operations from the plurality of wireless access equipments to the plurality of user equipments comprises adjusting beam forming methods and mesh routing methods of the plurality of wireless access equipments for the plurality of user equipments.

14. The network managing device of claim **10**, wherein the step of adjusting the wireless operations from the plurality of wireless access equipments to the plurality of user equipments according to the locations and the priorities of the plurality of user equipments comprises:

controlling the plurality of wireless access equipments to prioritize providing wireless services for a user equipment of the plurality of user equipments when a priority of the user equipment is greater than a predefined degree.

10

15. The network managing device of claim **10**, wherein the program code indicates to the processor to further perform following step:

determining movement situations of the plurality of user equipments according to the plurality of measurement results; and

adjusting the wireless operations from the plurality of wireless access equipments to the plurality of user equipments according to the movement situations and the priorities of the plurality of user equipments.

16. The network managing device of claim **15**, wherein the step of adjusting the wireless operations from the plurality of wireless access equipments to the plurality of user equipments according to the movement situations and the priorities of the plurality of user equipments comprises:

controlling the plurality of wireless access equipments to prioritize providing wireless services for a user equipment of the plurality of user equipments when a priority of the user equipment is greater than a predefined degree and the user equipment moves toward a region.

17. The network managing device of claim **10**, wherein the program code indicates to the processor to further perform following step:

receiving a path configuration data; and

adjusting the plurality of wireless access equipments to prioritize providing wireless services for a region within a period when the path configuration data indicates that the plurality of user equipments moves to the region within the period.

18. The network managing device of claim **10**, wherein the program code indicates to the processor to further perform following step:

determining normal moving situations of the plurality of user equipments in a signal coverage of the wireless network system according to the plurality of measurement results;

determining at least one building shield in the signal coverage according to the normal moving situations of the plurality of user equipments in the signal coverage of the wireless network system; and

determining moving trends of the plurality of user equipments according to the at least one building shield and the locations of the plurality of user equipments to adjust the wireless operations from the plurality of wireless access equipments to the plurality of user equipments.

* * * * *