



US009270516B2

(12) **United States Patent**
Kemmerer, Jr. et al.

(10) **Patent No.:** **US 9,270,516 B2**
(45) **Date of Patent:** **Feb. 23, 2016**

(54) **PEER-TO-PEER INTERCONNECTION BETWEEN SERVICE PROVIDERS**

2008/0162637 A1* 7/2008 Adamczyk et al. 709/204
2010/0091707 A1* 4/2010 Janneteau et al. 370/328
2014/0269537 A1* 9/2014 Kemmerer et al. 370/329

(71) Applicant: **GENBAND US LLC**, Frisco, TX (US)

FOREIGN PATENT DOCUMENTS

(72) Inventors: **Frederick C. Kemmerer, Jr.**, Hollis, NH (US); **Carroll L. Gray-Preston**, Morrisville, NC (US); **Jeremy Fuller**, Linlithgow (GB)

WO 99/17506 A2 4/1999

OTHER PUBLICATIONS

(73) Assignee: **GENBAND US LLC**, Frisco, TX (US)

European Patent Office, "Extended European search report," issued in EP Application No. 14159606.4, Mailed Date: Jun. 6, 2014, 5 Pages.

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 183 days.

* cited by examiner

(21) Appl. No.: **13/838,769**

Primary Examiner — Kenny Lin

(22) Filed: **Mar. 15, 2013**

(74) Attorney, Agent, or Firm — Fogarty, L.L.C.

(65) **Prior Publication Data**

US 2015/0236888 A1 Aug. 20, 2015

(51) **Int. Cl.**
G06F 15/16 (2006.01)
H04L 29/06 (2006.01)

(52) **U.S. Cl.**
CPC **H04L 29/06326** (2013.01)

(58) **Field of Classification Search**
None
See application file for complete search history.

(56) **References Cited**


U.S. PATENT DOCUMENTS

7,313,631 B1* 12/2007 Sesmun et al. 709/245
2003/0007482 A1* 1/2003 Khello et al. 370/352

(57) **ABSTRACT**

Embodiments of methods and systems for peer-to-peer interconnection between service providers are presented. In one embodiment, a method includes receiving, at a session controller, a request for access to a target communication device, the target communication device being communicatively coupled to a foreign service provider network. The method may also include referencing a list of available routes for peer-to-peer communication with the target communication device on the foreign service provider network from a database of available routes. Additionally, the method may include identifying, in a peer-to-peer interconnect controller, a path for communication with the target communication device in response to the list of available routes. In one embodiment, the method also includes establishing a peer-to-peer communication session from a peering point to the target communication device over the path.

21 Claims, 6 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4





FIG. 5



1

PEER-TO-PEER INTERCONNECTION BETWEEN SERVICE PROVIDERS

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is related to U.S. patent application Ser. No. 13/841,185, entitled “Determining Peer-to-Peer Communication Paths between Service Providers,” filed on Mar. 15, 2013, and Ser. No. 13/840,072, entitled “Direct Routing of Communication Sessions for Mobile IP Communication End Points,” filed on Mar. 15, 2013, each of which are incorporated herein by reference in their entirety.

TECHNICAL FIELD

This disclosure relates generally to telecommunications, and more specifically, to methods and systems for peer-to-peer interconnection between service providers.

BACKGROUND

The following discussion sets forth the inventors’ own knowledge of certain technologies and/or problems associated therewith. Accordingly, this discussion is not an admission of prior art, and it is not an admission of the knowledge available to a person of ordinary skill in the art.

The telecommunications market includes many different service providers, each typically offering compatible communications services. Compatibility is often required so that customers of one service provider can communicate with friends, family, or other end users who may be customers of another service provider. Although service providers typically offer services that are compatible with other service provider networks, there has not conventionally been a direct connect option between users of diverse service provider networks.

One prior solution for handling interfaces between different service provider networks is conventionally handled by a third party intermediary. The third party intermediary would typically establish an interconnect agreement with many different service providers, and then provide connection services between users of the different service provider networks.

In certain situations, a communication will hop between multiple third parties or across multiple carriers in order to find an agreed path between communication endpoints. In some situations, it is possible to employ direct interconnect between carriers, but it typically requires interconnect agreements to be in place and systems to be configured in advance. In legacy systems, a call may be routed through several carriers before connecting between the end users. Each connection may include connection and/or termination fees. These prior systems become very complex and expensive.

SUMMARY

Embodiments of methods and systems for peer-to-peer interconnection between service providers are presented. In one embodiment, a method includes receiving, at a session controller, a request for access to a target communication device, the target communication device being communicatively coupled to a foreign service provider network. The method may also include referencing a list of available routes for peer-to-peer communication with the target communication device on the foreign service provider network from a database of available routes. Additionally, the method may

2

include identifying, in a peer-to-peer interconnect controller, a path for communication with the target communication device in response to the list of available routes. In one embodiment, the method also includes establishing a peer-to-peer communication session from a peering point to the target communication device over the path.

BRIEF DESCRIPTION OF THE DRAWINGS

Reference will now be made to the accompanying drawings, wherein:

FIG. 1 is a block diagram illustrating one embodiment of a system for peer-to-peer interconnection between service providers.

FIG. 2 is a block diagram illustrating another embodiment of a system for peer-to-peer interconnection between service providers.

FIG. 3 is a block diagram illustrating another embodiment of a system for peer-to-peer interconnection between service providers.

FIG. 4 is a flowchart of a method for peer-to-peer interconnection between service providers.

FIG. 5 is a system state diagram illustrating one embodiment of a method for peer-to-peer interconnection between service providers.

FIG. 6 is a block diagram of a computer system configured to implement various systems and methods described herein according to some embodiments.

DETAILED DESCRIPTION

Embodiments disclosed herein are directed generally to methods and systems for peer-to-peer interconnection between service providers.

The term “telecommunications,” as used herein, is intended to encompass voice communications or telephony, as well as other forms of communications (e.g., video communications, videoconferencing, instant messaging or IM, Short Messaging Service or SMS, emails, etc.) that may take place electronically, for example, over wireless networks, circuit-switched networks, packet-switched networks, or any combination thereof.

FIG. 1 is a block diagram illustrating one embodiment of a system for peer-to-peer interconnection between service providers. In one embodiment, the system 100 includes a first service provider network 102 and a second service provider network 104. Examples of service providers include, but are not limited to, AT&T®, Verizon®, Vodafone™, etc. In one embodiment, the provider networks 102 may be the networks may be packet-switched, circuit-switched, wireless, or any combination thereof. In general embodiments, a first communication device 106 on the first service provider network 102 may be configured to communicate with a second communication device 108 on a second service provider network 104 over a peer-to-peer communication interconnection path 110 between the first service provider network 102 and the second service provider network 104. In one embodiment, first communication device 106 and second communication device 108 are user communication devices (e.g., telephones, mobile phones, laptops, tablet computers, etc.) for a user who is a subscriber of the first service provider network 102 and second service provider network 104 respectively. As used herein, the term “foreign service provider” means a different service provider network than one that a user subscribes to (e.g., second service provider network 104 as to first communication device 106 in FIGS. 1-2).

3

Beneficially, such an embodiment may enable the first communication device **106** to initiate, negotiate, and carry out communications with the second communication device **108** without requiring a central route lookup function or an administrator. More specifically, certain embodiments may eliminate use of centralized or third-party interconnection sources, and the associated expenses of routing and relating number lookup information. Thus, use of such centralized or third-party interconnection sources by the service providers **102,104** is not required for enabling communication between devices **106,108**. Further benefits may include elimination of class **4** interconnection elements in existing network infrastructures.

FIG. **2** is a block diagram illustrating another embodiment of a system **200** for peer-to-peer interconnection between service providers. As in FIG. **1**, system **200** may also include a first service provider network **102** and a second service provider network **104**, each providing user connectivity to a first communication device **106** and second communication device **108** respectively. In addition, the system **200** may include a peer-to-peer interconnect control **202a-b**, and a session controller **204a-b**.

Peer-to-peer interconnect control **202** may be configured to access and query active subscribers database **206** and available routes database **208**. In one embodiment, each of the first service provider network **102** and the second service provider network **104** each maintain an active subscribers database **206a,b** and an available routes database **208a,b** respectively for storing connectivity information for the local network. For example, an identifier associated with first communication device **106** may be stored in active subscribers database **206a**, which is maintained by first service provider network **102**. Similarly, available routes database **208a** may store a listing of available connection routes for accessing first communication device **106**. Likewise, the active subscribers database **206b** and available routes database **208b** maintained by second service provider network **104** may include information for connecting to second communication device **108**.

Peer-to-Peer interconnect control **202a** may handle coordination of peer-to-peer communication routing for all devices on first service provider network **102**. In one embodiment, peer-to-peer interconnect control **202a** may be a communication interface to second service provider network **104** and other service provider networks. Session controller **204a** may be in communication with peer-to-peer control **202a**, and may serve as an internal interface to first communication device **106**. Peering point **210a** may handle device-to-device communication between the first communication device **106** and the second communication device **108** once the peer-to-peer link has been negotiated and routed by peer-to-peer interconnect control **202a**.

Thus, in a simplified view, the peer-to-peer interconnect control **202a** negotiates and routes peer-to-peer communication links between service provider networks, session controller **204a** handles intra-network interfaces between devices, and peering point **210a** handles content communication between service provider networks once the link has been established by peer-to-peer interconnect control **202a**. One of ordinary skill in the art will recognize that each of the corresponding devices in the second service provider network have a similar and corresponding function.

FIG. **3** is a block diagram illustrating another embodiment of a system **300** for peer-to-peer interconnection between service providers **102-104**. The embodiment of FIG. **3** illustrates additional components which may facilitate peer-to-peer interconnection between service provider networks. In addition to the components described in FIGS. **1-2**, the

4

embodiment of FIG. **3** includes a Distributed Inter-Carrier Secure DNS System (DICSDS) **302**, a DNS root node **304**, and an E.164 Number (ENUM) database **306**. In addition, each service provider network may include a DNS database **308a,b** respectively.

In one embodiment, DICSDS **302** may be a common DNS system among service providers and E.164 providers. In one embodiment, DNS name resolution data may be controlled by the owning service provider via their local segment of the DICSDS **302**. In one embodiment, DICSDS **302** may facilitate address lookup for interface nodes within service provider networks. For example, peer-to-peer interconnect control **202a** on the first service provider network **102** may query DICSDS **302** to determine an address for P2P interconnect control **202b** on the second service provider network **104** in order to initiate P2P route negotiations.

ENUM database **306** may contain a commonly accessible list of ENUM identifiers, which DICSDS **302** may access in response to a query from a P2P interconnect control **202**. ENUM database **306** enables E.164 number to Service Provider mapping via DNS. DNS root node **304** enables the first service provider **102** and the second service provider **104** to create a common DNS system, such that both service providers have access to common address data.

FIG. **4** is a flowchart of a method **400** for peer-to-peer interconnection between service providers **102, 104**. In one embodiment, the method **400** starts when the session controller **204a** receives a request for access to a target communication device, the target communication device being communicatively coupled to a foreign service provider network as shown at block **402**. For example, the session controller **204a** may receive a request from the first communication device **106** to access the second communication device on the second service provider network.

In one embodiment, the peer-to-peer interconnect controller **202a** may reference a list of available routes for peer-to-peer communication with the target communication device on the foreign service provider network as shown in block **404**. For example, session controller **204a** may forward the request to P2P interconnect control **202a**, which contacts P2P interconnect control **202b** on the second service provider network and request access to available route information for accessing second communication device **108**.

Additionally P2P interconnect control **202a** may identify a path for communication with the target communication device in response to the list of available routes as shown at block **406**. For example, P2P interconnect control **202b** may forward available communication routes to P2P interconnect control **202a**. The available communication routes may include one or more communication paths to second communication device **108**, which are stored in available routes database **208b** on the second service provider network **104**.

In one embodiment, peering point **210a** may establish a peer-to-peer communication session with the target communication device over the path as shown in block **408**. For example, once a communication path to second communication device **108** is identified and a P2P link is negotiated, peering point **210a** may interface peering point **210b** on the second service provider network **104** and communicate content between the first communication device **106** and the second communication device **108**.

FIG. **5** is a system state diagram illustrating one embodiment of a method **500** for peer-to-peer interconnection between service providers. In one embodiment the method **500** starts when first communication device **106** initiates, at state **502**, a session to second communication device **108**. In the depicted embodiment, first communication device **106** is

5

a subscriber on first service provider network **102** and second communication device is a subscriber on second service provider network **104**. More specifically, first communication device **106** may send a request to session controller **204a** as shown by state **502**.

At state **504**, P2P interconnect control **202a** may perform an ENUM query to look up the identity of the second service provider **104**. Additionally, as shown at state **506**, the P2P interconnect control **202a** may query the DNS route server to obtain the Name Server address where the address of P2P interconnect control **202b** for second service provider network **104** can be obtained and obtain the node address for P2P interconnect control **202b**.

At state **508**, P2P interconnect control **202a** of the first service provider network **102** may contact P2P interconnect control **202b** of the second service provider network **104** to confirm that P2P interconnect services are supported by second service provider network **104**. Additionally, P2P interconnect control **202a** may obtain any redirect information due to roaming through query of Active Subscriber Database and provide the route record of the closest peering point to the subscriber. If, in one embodiment, it is determined that the service provider of the called party does not support certain embodiments, then the system may fall-back to traditional routing.

At state **510**, P2P interconnect control **202b** to may query available routes database **208b** to identify available routes to second communication device **108** and return the available routes to P2P interconnect control **202a** on the first service provider network **102**. At state **512**, P2P interconnect control **202a** may use the available route information to select a route to peering point **210b**, which may render a Session Detail Record (SDR) for accounting use at the end of the session. At state **514**, session controller **204a** may establish signaling between peering point **210a** and remote peering point **210b** using the selected route. At state **516**, a media path may be established between peering point **210a** and peering point **210b**, which enables the first communication device **106** to communicate content with second communication device **108**.

As noted above, embodiments of peer-to-peer interconnection between service providers may be implemented or executed, at least in part, by one or more computer systems. One such system is illustrated in FIG. **6**. In various embodiments, system **600** may be a server, a workstation, a desktop computer, a laptop, a tablet computer, a mobile device, a smart phone, or the like. In some cases, system **600** may be used to implement communication devices **101** and/or **102**, and application server(s) **105** shown in FIG. **1**. As illustrated, computer system **600** includes one or more processor(s) **610A-N** coupled to a system memory **620** via an input/output (I/O) interface **630**. Computer system **600** further includes a network interface **640** coupled to I/O interface **630**, and one or more input/output devices **650** (e.g., a Bluetooth® adaptor, a Wifi adaptor, or the like), keyboard **670**, and display(s) **680**.

In various embodiments, computer system **600** may be a single-processor system including one processor **610A** (e.g., processor **201** shown in FIG. **2**), or a multi-processor system including two or more processors **610A-N** (e.g., two, four, eight, or another suitable number). Processor(s) **610A-N** may include any processor capable of executing program instructions. For example, in various embodiments, processor(s) **610A-N** may be general-purpose or embedded processors implementing any of a variety of instruction set architectures (ISAs), such as the x86, PowerPC®, ARM®, SPARC®, or MIPS® ISAs, or any other suitable ISA. In multi-processor systems, each of processor(s) **610A-N** may commonly, but

6

not necessarily, implement the same ISA. Also, in some embodiments, at least one processor **610A** may be a graphics processing unit (GPU) or other dedicated graphics-rendering device.

System memory **620** may be configured to store program instructions (e.g., algorithms for querying databases, accessing foreign service provider networks, etc.) and/or data accessible by processor(s) **610A-N**. In various embodiments, system memory **620** may be implemented using any suitable memory technology, such as static random access memory (SRAM), synchronous dynamic RAM (SDRAM), nonvolatile/Flash-type memory, or any other type of memory. As illustrated, program instructions and data implementing certain operations such as, for example, those described in connection with FIGS. **4-8**, may be stored within system memory **620** as program instructions **625** and data storage **635**, respectively. Additionally or alternatively, methods described herein may be implemented as a software program that is stored within system memory **620** and is executable by processor(s) **610A-N**. In other embodiments, program instructions and/or data may be received, sent or stored upon different types of computer-accessible media or on similar media separate from system memory **620** or computer system **600**. Generally speaking, a computer-accessible medium may include any tangible or non-transitory storage media or memory media such as electronic, magnetic, or optical media—e.g., disk or CD/DVD-ROM coupled to computer system **600** via I/O interface **630**. The terms “tangible” and “non-transitory,” as used herein, are intended to describe a computer-readable storage medium (or “memory”) excluding propagating electromagnetic signals, but are not intended to otherwise limit the type of physical computer-readable storage device that is encompassed by the phrase computer-readable medium or memory. For instance, the terms “non-transitory computer-readable medium” or “tangible memory” are intended to encompass types of storage devices that do not necessarily store information permanently, including for example, random access memory (RAM). Program instructions and data stored on a tangible computer-accessible storage medium in non-transitory form may further be transmitted by transmission media or signals such as electrical, electromagnetic, or digital signals, which may be conveyed via a communication medium such as a network and/or a wireless link.

In an embodiment, I/O interface **630** may be configured to coordinate I/O traffic between processor(s) **610A-N**, system memory **620**, and any peripheral devices in the device, including network interface **640** or other peripheral interfaces, such as input/output devices **650**. In some embodiments, I/O interface **630** may perform any necessary protocol, timing or other data transformations to convert data signals from one component (e.g., system memory **620**) into a format suitable for use by another component (e.g., processor(s) **610A-N**). In some embodiments, I/O interface **630** may include support for devices attached through various types of peripheral buses, such as a variant of the Peripheral Component Interconnect (PCI) bus standard or the Universal Serial Bus (USB) standard, for example. In some embodiments, the function of I/O interface **630** may be split into two or more separate components, such as a north bridge and a south bridge, for example. In addition, in some embodiments some or all of the functionality of I/O interface **630**, such as an interface to system memory **620**, may be incorporated directly into processor(s) **610A-N**.

Network interface **640** may be configured to allow data to be exchanged between computer system **600** and other devices attached to a network (e.g., telecommunications net-

work 104 of FIG. 1), such as other computer systems, or between nodes of computer system 600. In various embodiments, network interface 640 may support communication via wired or wireless general data networks, such as any suitable type of Ethernet network, for example; via telecommunications/telephony networks such as analog voice networks or digital fiber communications networks; via storage area networks such as Fibre-Channel SANs, or via any other suitable type of network and/or protocol.

Input/output devices 650 may, in some embodiments, include one or more display terminals, keyboards, keypads, touchpads, scanning devices, RFID readers, NFC readers, voice or optical recognition devices, or any other devices suitable for entering or retrieving data by one or more computer system 600. Multiple input/output devices 650 may be present in computer system 600 or may be distributed on various nodes of computer system 600. In some embodiments, similar input/output devices may be separate from computer system 600 and may interact with one or more nodes of computer system 600 through a wired or wireless connection, such as over network interface 640.

As shown in FIG. 6, memory 620 may include program instructions 625, configured to implement certain embodiments described herein, and data storage 635, comprising various data may be accessible by program instructions 625. In an embodiment, program instructions 625 may include software elements of embodiments illustrated in the above figures. For example, program instructions 625 may be implemented in various embodiments using any desired programming language, scripting language, or combination of programming languages and/or scripting languages (e.g., C, C++, C#, Java™, JavaScript™, Perl, etc.). Data storage 635 may include data that may be used in these embodiments (e.g., recorded communications, profiles for different modes of operations, etc.). In other embodiments, other or different software elements and data may be included.

A person of ordinary skill in the art will appreciate that computer system 600 is merely illustrative and is not intended to limit the scope of the disclosure described herein. In particular, the computer system and devices may include any combination of hardware or software that can perform the indicated operations. In addition, the operations performed by the illustrated components may, in some embodiments, be performed by fewer components or distributed across additional components. Similarly, in other embodiments, the operations of some of the illustrated components may not be provided and/or other additional operations may be available. Accordingly, systems and methods described herein may be implemented or executed with other computer system or processor-based configurations.

Although certain embodiments are described herein with reference to specific examples, numerous modifications and changes may be made in light of the foregoing description. Accordingly, the specification and figures are to be regarded in an illustrative rather than a restrictive sense, and all such modifications are intended to be included within their scope. Any benefits, advantages, or solutions to problems that are described herein with regard to specific embodiments are not to be construed as a critical, required, or essential feature or element of any or all the claims. Furthermore, it should be understood that the various operations described herein may be implemented in software, hardware, or a combination thereof. The order in which each operation of a given technique is performed may be changed, and the elements of the systems illustrated herein may be added, reordered, combined, omitted, modified, etc. It is intended that the embodiments described herein embrace all such modifications and

changes and, accordingly, the above description should be regarded in an illustrative rather than a restrictive sense.

Unless stated otherwise, terms such as “first” and “second” are used to arbitrarily distinguish between the elements such terms describe. Thus, these terms are not necessarily intended to indicate temporal or other prioritization of such elements. The term “coupled” is defined as “connected” and/or “in communication with,” although not necessarily directly, and not necessarily mechanically. The terms “a” and “an” are defined as one or more unless stated otherwise. The terms “comprise” (and any form of comprise, such as “comprises” and “comprising”), “have” (and any form of have, such as “has” and “having”), “include” (and any form of include, such as “includes” and “including”) and “contain” (and any form of contain, such as “contains” and “containing”) are open-ended linking verbs. As a result, a system, device, or apparatus that “comprises,” “has,” “includes” or “contains” one or more elements possesses those one or more elements but is not limited to possessing only those one or more elements. Similarly, a method or process that “comprises,” “has,” “includes” or “contains” one or more operations possesses those one or more operations but is not limited to possessing only those one or more operations.

The invention claimed is:

1. A method, comprising:

receiving, at a session controller in a home service provider network, a request for access to a target communication device, the target communication device being communicatively coupled to a foreign service provider network; referencing a list of available routes for peer-to-peer communication with the target communication device on the foreign service provider network from a database of available routes maintained by the foreign service provider network;

identifying, in a peer-to-peer interconnect controller node in the home service provider network and/or the foreign service provider network, the peer-to-peer interconnect controller node separate from the requesting device, a path for communication with the target communication device in response to the list of available routes; and establishing a peer-to-peer communication session from a peering point in the home service provider network associated with, and separate from, the requesting device, directly to a peering point in the foreign service provider network associated with, and separate from, the target communication device, over the path.

2. The method of claim 1, wherein referencing the list of available routes does not include a central route lookup function.

3. The method of claim 1, wherein the list of available routes is stored, at least in part, in a database of available routes maintained on the home service provider network.

4. The method of claim 1, further comprising performing an E.164 Number query to identify the foreign service provider network.

5. The method of claim 1, further comprising querying a Domain Name System (DNS) server to identify a network address for the peer-to-peer interconnect control node associated with the foreign service provider network.

6. The method of claim 1, wherein referencing a list of available routes for peer-to-peer communication with the target communication device and/or identifying a path for communication with the target communication device further comprises querying the peer-to-peer interconnect control node associated with the foreign service provider network to identify routing information for reaching the target communication device.

7. The method of claim 6, wherein the routing information comprises a list of available routes stored in a database of available routes maintained on the foreign service provider network.

8. The method of claim 6, further comprising rendering a Session Detail Record (SDR) for route use in response to the routing information for reaching the target communication device.

9. The method of claim 1, wherein establishing a peer-to-peer communication session further comprises establishing a signaling session directly between the peering point on the foreign service provider network and the peering point on a home service provider network.

10. The method of claim 1, wherein establishing a peer-to-peer communication session further comprises establishing a direct media path between the peering point on the foreign service provider network and the peering point on a home service provider network.

11. A system, comprising:

a session controller node configured to receive a request for access to a target communication device, the target communication device being communicatively coupled to a foreign service provider network;

a peer-to-peer interconnect controller node coupled to the session controller node and separate from a requesting device, the peer-to-peer interconnect controller node configured to:

reference a list of available routes for peer-to-peer communication with the target communication device on the foreign service provider network maintained by the foreign service provider network; and

identify a path for communication with the target communication device in response to the list of available routes; and

a peering point separate from the requesting device and coupled to the session controller and configured to establish a direct peer-to-peer communication session with a peering point in the foreign service provider network associated with, and separate from, the target communication device, over the path.

12. The system of claim 11, wherein referencing the list of available routes does not include a central route lookup function.

13. The system of claim 11, further comprising an available routes database on a home service provider network, the available routes database configured to store at least a part of the list of available routes.

14. The system of claim 11, further comprising an E.164 Number database configured to store information for identifying the foreign service provider network.

15. The system of claim 11, further comprising a Domain Name System (DNS) server configured to identify a network address for a peer-to-peer interconnect control node associated with the foreign service provider network.

16. The system of claim 11, further comprising a peer-to-peer interconnect control node associated with the foreign service provider network configured to identify routing information for reaching the target communication device.

17. The system of claim 16, further comprising a database of available routes maintained on the foreign service provider network configured to store the routing information comprising a list of the available routes.

18. The system of claim 16, wherein the peer-to-peer interconnect control associated with the foreign service provider network is configured to render a Session Detail Record (SDR) for accounting use in response to the information for reaching the target communication device.

19. The system of claim 11, wherein establishing a peer-to-peer communication session further comprises establishing a signaling session directly between the peering point on the foreign service provider network and the peering point coupled to the session controller.

20. The system of claim 11, wherein establishing a peer-to-peer communication session further comprises establishing a direct media path between the peering point coupled to the session controller and the peering point in the foreign service provider network.

21. A tangible computer-readable storage medium having program instructions stored thereon that, upon execution by a computer system, causes the computer system to:

receive a request from a requesting communication device separate from the computer system for access to a target communication device, the target communication device being communicatively coupled to a foreign service provider network;

reference a list of available routes for peer-to-peer communication with the target communication device on the foreign service provider network;

identify a path for communication with the target communication device in response to the list of available routes; and

establish a peer-to-peer communication session directly between a peering point associated with and separate from the requesting device in a home service provider network and a peering point in the foreign service provider network associated with and separate from the target communication device, over the path.

* * * * *