

US009270577B2

(12) **United States Patent**  
**Wassermann**

(10) **Patent No.:** **US 9,270,577 B2**  
(45) **Date of Patent:** **Feb. 23, 2016**

(54) **SELECTION OF ONE OF FIRST AND SECOND LINKS BETWEEN FIRST AND SECOND NETWORK DEVICES**

(75) Inventor: **Gary Michael Wassermann**, Roseville, CA (US)

(73) Assignee: **HEWLETT PACKARD ENTERPRISE DEVELOPMENT LP**, Houston, TX (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 339 days.

(21) Appl. No.: **13/563,156**

(22) Filed: **Jul. 31, 2012**

(65) **Prior Publication Data**

US 2014/0040659 A1 Feb. 6, 2014

(51) **Int. Cl.**

**H04L 12/707** (2013.01)  
**G06F 11/20** (2006.01)  
**H04L 12/24** (2006.01)  
**H04L 12/703** (2013.01)  
**H04L 12/851** (2013.01)  
**H04L 12/26** (2006.01)

(52) **U.S. Cl.**

CPC ..... **H04L 45/22** (2013.01); **G06F 11/2005** (2013.01); **G06F 11/2007** (2013.01); **G06F 11/2012** (2013.01); **H04L 41/0663** (2013.01); **H04L 45/28** (2013.01); **H04L 41/0893** (2013.01); **H04L 43/0811** (2013.01); **H04L 43/10** (2013.01); **H04L 47/24** (2013.01)

(58) **Field of Classification Search**

USPC ..... 709/240, 250, 223; 370/217, 392, 216, 370/222, 256

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

6,732,186 B1 \* 5/2004 Hebert ..... H04L 41/0681 709/226

7,603,481 B2 10/2009 Carter

7,630,295 B2	12/2009	Hughes et al.	
7,640,364 B2	12/2009	Craft et al.	
2004/0085894 A1 *	5/2004	Wang .....	H04L 41/0663 370/216
2005/0232183 A1 *	10/2005	Sartori .....	H04B 7/15542 370/319
2006/0002292 A1 *	1/2006	Chang et al. ....	370/225
2006/0013125 A1 *	1/2006	Vasseur .....	H04L 45/02 370/217
2006/0250965 A1 *	11/2006	Irwin .....	370/238
2008/0198766 A1 *	8/2008	Ogawa .....	370/254
2009/0185492 A1 *	7/2009	Senarath .....	H04B 7/155 370/238
2010/0220736 A1 *	9/2010	Mohapatra .....	H04L 45/04 370/401
2010/0260042 A1 *	10/2010	Kwon .....	H04L 45/00 370/227
2010/0265957 A1 *	10/2010	Foxworthy .....	H04B 7/18584 370/401
2010/0325257 A1	12/2010	Goel et al.	
2011/0019539 A1 *	1/2011	Suzuki .....	H04L 49/552 370/225
2011/0047291 A1 *	2/2011	Ishii .....	H04L 45/00 709/238
2012/0093156 A1	4/2012	Budhani et al.	
2012/0124414 A1 *	5/2012	Dallas .....	G06F 11/2005 714/6.2

**OTHER PUBLICATIONS**

Branch Repeater VPX Best Practice and Deployment Guide, (Research Paper).

\* cited by examiner

*Primary Examiner* — Andrew Lai

*Assistant Examiner* — Jamaal Henson

(74) *Attorney, Agent, or Firm* — Hewlett Packard Enterprise Patent Department

(57) **ABSTRACT**

Embodiments herein relate to selection of one of first and second links between first and second network devices. The first link is to transmit the traffic between the first and second network devices directly and the second link is to transmit the traffic between the first and second network devices through a network appliance.

**20 Claims, 4 Drawing Sheets**




FIG. 1




FIG. 2




FIG. 3





FIG. 4





## 1

**SELECTION OF ONE OF FIRST AND  
SECOND LINKS BETWEEN FIRST AND  
SECOND NETWORK DEVICES**

BACKGROUND

Networks, such as local area networks (LAN) or wireless LANs (WLAN), may employ a network appliance between two network devices that direct traffic. The network devices may be switches or routers while the network appliance may provide a useful service, such as network acceleration or intrusion protection.

BRIEF DESCRIPTION OF THE DRAWINGS

The following detailed description references the drawings, wherein:

FIG. 1 is an example block diagram of a first network device to direct traffic to a second network device via one of first and second links;

FIG. 2 is another example block diagram of a first network device to direct traffic to a second network device via one of first and second links;

FIG. 3 is an example block diagram of a computing device including instructions for selection of one of first and second links between first and second network devices; and

FIG. 4 is an example flowchart of a method for selection of one of first and second links between first and second network devices.

DETAILED DESCRIPTION

Specific details are given in the following description to provide a thorough understanding of embodiments. However, it will be understood by one of ordinary skill in the art that embodiments may be practiced without these specific details. For example, systems may be shown in block diagrams in order not to obscure embodiments in unnecessary detail. In other instances, well-known processes, structures and techniques may be shown without unnecessary detail in order to avoid obscuring embodiments.

Networks, such as local area networks (LAN) or wireless LANs (WLAN), may employ a network appliance between two network devices that direct traffic, such as routers or switches. The network appliance may provide a useful service, such as network acceleration or a firewall. However, the network appliance may also introduce a new point of failure. Should the network appliance fail, the two network devices may have to find a new path, thus altering the MAC tables of the network devices as well as changing the overall network topology.

Moreover, attempting to create a specialized network appliance that allows traffic to pass through it even if the specialized network appliance fails, may require expensive hardware and software integration, present timing issues and/or may create compatibility issues. For instance, the specialized network appliance may require a watchdog timer to periodically determine if software of the specialized network appliance is responsive along with hardware to bridge two network interface cards (NIC) of the specialized network appliance if the software fails. Also, using the specialized network appliance may create a need to modify other existing network appliances and/or the network devices of the network.

Moreover, the specialized network appliance still may not overcome a hardware failure, such as a failure of at least one of the NICs or a failure of a physical link connecting to the

## 2

specialized network appliance itself. Also, the specialized network appliance may lack an auto-recover feature, such as an ability to undo bridging the NICs.

In addition, the network appliance may create an unnecessary bottleneck between the two network devices by having all the traffic pass through the network appliance when only some of the traffic, such as TCP traffic, may be relevant to the network appliance. For instance, the network appliance may not be able to handle the bandwidth that would otherwise flow unfettered through the two network devices, thus reducing throughput. Other solutions, such as adding separate specialized hardware, like a load balancer, may present similar problems to that of the specialized network appliance.

Embodiments herein relate to selection of one of first and second links between first and second network devices. For example, the first network device may include the first link, the second link and a traffic module. The first link is to the second network device and the second link is to a network appliance. The first and second network devices switch and/or direct traffic. The network appliance is to connect to the second network device and to modify or filter at least some of the traffic passing between the first and second network devices via the second link. The traffic module is to select one of the first and second links to transmit the traffic from the first network device to the second network device at a given time. The network layer topology is not changed if one of the first and second links fails.

Thus, embodiments may offer an additional link between the two network devices that bypasses the network appliance. As a result, throughput may be increased and a load on the network appliance may be decreased, without adding special-purpose hardware to the network appliance or introducing a new point of failure. Moreover, there may even be a lighter load on the two network devices because if one of the links fails, the first and second network devices may switch-over to the other link without changing the layer 3 or network topology of the network. For example, the two network devices would not need to flush MAC tables or process MAC moves and MAC learns, if one of the links fails.

Referring now to the drawings, FIG. 1 is an example block diagram of a first network device **100** to direct traffic to a second network device **120** via one of first and second links. The first and second network devices **100** and **120** may be any type of device that connects network segments or network devices. For example, the first and second network devices **100** and **120** may be switches, hubs, routers, bridges, gateways, and the like. Further, the first and network devices **100** and **120** may switch and/or direct traffic.

The embodiment of FIG. 1 illustrates the first network device **100**, a network appliance **110**, and the second network device **120**. The first network device **100** includes a traffic module **102**. The traffic module **102** and the network appliance **110** may include, for example, a hardware device including electronic circuitry for implementing the functionality described below, such as control logic and/or memory. In addition or as an alternative, the traffic module **102** and the network appliance **110** may be implemented as a series of instructions encoded on a machine-readable storage medium and executable by a processor. Further, the traffic module **102** and the network appliance **110** may include mechanical, electrical and/or logical signals and a protocol for sequencing the signals.

The first network device **100** includes a first link to the second network device and a second link to the network appliance **110**. The network appliance **110** is to connect to the second network device **120**, and to modify at least some of the traffic passing between the first and second network devices



**100** and **120** via the second link. The first and second links may represent any type of channel for connecting one location to another for the purpose of transmitting and receiving information, such as copper wires, optical fibers, and wireless communication channels.

The traffic module **102** is to select one of the first and second links to transmit the traffic from the first network device **100** to the second network device **120** at a given time. Thus, the traffic module **102** may include a mechanism, such as a switch or multiplexer, to select between the two links. The traffic module **102** will be explained in greater detail below with respect to FIG. 2. Further, a network layer topology is not changed if one of the first and second links fails.

The network layer topology may refer to how data flows within a network, regardless of its physical design. For example, the network layer topology may refer to an arrangement of links between nodes at the network layer or layer 3 in a seven-layer OSI model of computer networking. The network layer may be responsible for packet forwarding including routing through intermediate routers, whereas a data link layer in the seven-layer OSI model may be responsible for media access control, flow control and error checking. The network layer may provide functional and procedural means of transferring variable length data sequences from a source to a destination host via one or more networks while maintaining the quality of service functions. In this instance, the traffic will still flow between the first and second network devices **100** and **120**, even if one of the first and second links fails.

The network appliance **110** may be, for example, a network accelerator and/or a firewall device. The network accelerator, such as a local area network (LAN) or wireless LAN (WLAN) accelerator, may provide lower latency and higher throughput. For example, the network accelerator may enforce quality of service rules, compress data, compress IP headers, accelerate TCP, accelerate CIFS (Common Internet File System), mitigate lost packets with forward error correction, cache repeated data patterns at the byte level, and the like. The firewall device may keep a network secure. For example, the firewall device may control the incoming and outgoing network traffic by analyzing the data packets and determining whether the data packets should be allowed through or not, based on a predetermined rule set. The second network device **120** may be at least somewhat similar to the first network device **100**.

FIG. 2 is another example block diagram of a first network device **200** to direct traffic to a second network device **220** via one of a first and second link. The first and second network devices **200** and **220** may be any type of device that connects network segments or network devices. For example, the first and second network devices **200** and **220** may be switches, hubs, routers, bridges, gateways, and the like. Further, the first and second network devices **200** and **220** may switch and/or direct traffic.

The embodiment of FIG. 2 illustrates the first network device **200**, a network appliance **210**, and the second network device **220**. The first network device **200**, the network appliance **210**, and the second network device **220** of FIG. 2 may at least respectively include the functionality and/or hardware of the first network device **100**, the network appliance **110**, and the second network device **120** of FIG. 1.

The first network device **200** is shown to include a traffic module **202**, a MAC table **204**, a trunk-balance table **206** and a forwarding policy module **208**. The traffic module **202** of FIG. 2 may at least respectively include the functionality and/or hardware of the traffic module **102** of FIG. 1. The MAC table **204**, the trunk-balance table **206** and the forward-

ing policy module **208** may include, for example, a hardware device including electronic circuitry for implementing the functionality described below, such as control logic and/or memory. In addition or as an alternative, the MAC table **204**, the trunk-balance table **206** and the forwarding policy module **208** may be implemented as a series of instructions encoded on a machine-readable storage medium and executable by a processor and/or data stored on the machine-readable storage medium.

The second network device **220** is shown to include a traffic module **222**, a MAC table **224**, a trunk-balance table **226** and a forwarding policy module **228**. The traffic module **222**, the MAC table **224**, the trunk-balance table **226** and the forwarding policy module **228** of the second network device **220** may at least respectively include the functionality and/or hardware of the traffic module **202**, the MAC table **204**, the trunk-balance table **206** and the forwarding policy module **208** of the first network device **200**.

Referring to the first network device **200**, in one embodiment, the traffic module **202** is to direct all the traffic to the second link but to redirect all the traffic from the second link to the first network link if the second link fails. Thus, the traffic module **202** may direct all the traffic to the second network device **220** through the network appliance **210**, unless the second link fails, such as if the network appliance **210** malfunctions. In this case, the previously unused, first link may be selected by the traffic module **202** to transmit the traffic to the second network device **220**, while the second link now remains unused.

However, should the second link recover, such as if the network appliance **210** is fixed or replaced, the traffic module **202** may redirect all the traffic from the first link back to the second link. In order to determine whether a link is healthy or has failed, the first network switch **200** may use a keep-alive mechanism, such as Bidirectional Forwarding Detection (BFD).

Further, in order to direct or redirect traffic to one the links, the first network switch **200** may reprogram the trunk-balance table **206**. The trunk-balance table **206** may be a table used to select which of a trunk's or link aggregation's links a packet will egress on. For example, if the first network device **200** includes a plurality of physical ports **230**, such as 48 physical ports, several of them, including the ports used for the first link and the second link, may be aggregated into a trunk, which is a single logical port. The trunk-balance table may then demultiplex network traffic to the trunk's members. Thus, reprogramming the trunk-balance table **206** may include redirecting traffic from one physical port **230** to another within a logical port. The first network device **200** aggregates, at the data link layer, the traffic to be output to the second network device **220** along one of the first and second links.

In another embodiment, instead of transmitting all the traffic through one of the links, such as through the network appliance **210** via the second link, the traffic module **202** may determine which of the traffic to output to which of the first and second links based on a network forwarding policy, which may be stored at the forwarding policy module **208**. The network forwarding policy may be based on numerous types of parameters. In one instance, the network forwarding policy is based on a type of the traffic. The traffic module **202** may output a first type of the traffic to one of the first and second links and to output a second type of the traffic to a remainder of the first and second links. The traffic module **202** may analyze a header of a packet to determine the type of the traffic.



For example, if the first type is Transmission Control Protocol (TCP) related data and the second type is non-TCP related data, the traffic module **202** may output the TCP related data to the second link and the non-TCP related data to the first link. This is because the network appliance **210** may be only be configured to analyze TCP related data. As a result, latency may be decreased, throughput may be increased, and a load on the network appliance **210** may be decreased.

In another instance, an active set of links that includes the first and second links may be maintained. Each of the links of the active set may be associated with a cost. The network forwarding policy may be based on the cost of the links of the active set. The traffic module **202** is to select one of the links from the active set of links to transmit the traffic from the first network device **200** to the second network device **220**. For example, if the cost of the first link is 10 and a cost of the second link is 5, the traffic module **202** may select the lower cost link, such as the second link, to transmit the traffic from the first network device **200** to the second network device **220**. If at least two links have a same cost, the traffic module **202** may select more than link, such as the at least two links having the same cost, to transmit the traffic from the first network device **200** to the second network device **220**. Moreover, if one the links fails, the traffic module **202** may remove the failed link from the active set of links. Thus, the traffic module **202** would then not be able to select the failed link.

The media access control (MAC) table **204** may be a table that lists which MAC address is connected to which logical port of the first network device **200**. The MAC address may be an identification number used in other machines, such as a serial number of a network card, switch and router, etc. Thus, the first network device **200** may reference its MAC table **204** and forward a packet or frame only to the logical port to which the destination is connected. The first network device **200** may receive information from previous transmissions with other network elements, such as the second network device **220**, to build up its MAC table **204**. Each of the network devices **200** and **220** may include separate MAC tables **204** and **224**.

As noted above, the first network device **200** aggregates its physical ports **230** used for the first and second links into one logical port at the data link layer. If a link carrying traffic fails, the first network device **200** may switch over to the other link without a change in the layer 3 or network topology of the network, because the path between first and second network devices remains intact. Thus, the MAC table **204** of the first network device **200** may retained even if the selected link fails and the traffic is redirected to the other of the first and second links. Also, an extra MAC learn and a MAC move are not processed by a processor (not shown) of the first network device **200** if the selected link fails and the traffic is redirected to the other of the first and second links.

As previously mentioned, the second network device **220** may be similar to the first network device **200**. Thus, the traffic module **222** of the second network device **220** may also select one of the first and second links to transmit traffic from the second network device **220** to the first network device **200** at a given time. Further, the traffic module **222** of the second network device **220** may determine which of the traffic to output to which of the first and second links based on a network forwarding policy stored at the forwarding policy module **228**.

For example, the first and second network devices **200** and **220** may both select one the first and second links to transmit traffic, if the network appliance **210** is a network accelerator, as bi-directional traffic may need to be processed. However, only one of the first and second network devices **200** and **220**

may need to select one the first and second links to transmit traffic, if the network appliance is a firewall, because only unidirectional traffic, such as incoming or outgoing traffic, may need to be examined. While FIG. 2 shows only two links, embodiments may include more than two links between two network devices, and thus more than two members of the logical ports that are connected to an other network device.

FIG. 3 is an example block diagram of a computing device **300** including instructions for selection of one of first and second links between first and second network devices. In the embodiment of FIG. 3, the computing device **300** includes a processor **310** and a machine-readable storage medium **320**. The machine-readable storage medium **320** further includes instructions **322**, **324** and **326** for selection of one of the first and second links between the first and second network devices. The computing device **300** may be, for example, a router, a switch, a gateway, a bridge or any other type of user device capable of executing the instructions **322**, **324** and **326**. In certain examples, the computing device **300** may be included or be connected to additional components such as a storage drive, a server, a network appliance, etc.

The processor **310** may be, at least one central processing unit (CPU), at least one semiconductor-based microprocessor, at least one graphics processing unit (GPU), other hardware devices suitable for retrieval and execution of instructions stored in the machine-readable storage medium **320**, or combinations thereof. The processor **310** may fetch, decode, and execute instructions **322**, **324** and **326** to implement for selection of one of the first and second links between the first and second network devices. As an alternative or in addition to retrieving and executing instructions, the processor **310** may include at least one integrated circuit (IC), other control logic, other electronic circuits, or combinations thereof that include a number of electronic components for performing the functionality of instructions **322**, **324** and **326**.

The machine-readable storage medium **320** may be any electronic, magnetic, optical, or other physical storage device that contains or stores executable instructions. Thus, the machine-readable storage medium **320** may be, for example, Random Access Memory (RAM), an Electrically Erasable Programmable Read-Only Memory (EEPROM), a storage drive, a Compact Disc Read Only Memory (CD-ROM), and the like. As such, the machine-readable storage medium **320** can be non-transitory. As described in detail below, machine-readable storage medium **320** may be encoded with a series of executable instructions for selection of one of the first and second links between the first and second network devices.

Moreover, the instructions **322**, **324** and **326** when executed by a processor (e.g., via one processing element or multiple processing elements of the processor) can cause the processor to perform processes, such as, the process of FIG. 4. For example, the select instructions **322** may be executed by the processor **310** to select one of the first and second links to output traffic from the first network device (not shown) to the second network device (not shown). The first link is to transmit the traffic between the first and second network devices directly. The second link is to transmit the traffic between the first and second network device through a network appliance (not shown).

The monitor instructions **324** may be executed by the processor **310** to monitor the selected link for link failure. The switch instructions **326** may be executed by the processor **310** to switch selection from the selected link to an other of the first and second links without changing a network topology of the computing device **300**, such as a network switch, if the selected links fails.



7

FIG. 4 is an example flowchart of a method 400 for selection of one of first and second links between first and second network devices. Although execution of the method 400 is described below with reference to the first network device 200, other suitable components for execution of the method 400 can be utilized, such as the first network device 100 and/or the second network device 220. Additionally, the components for executing the method 400 may be spread among multiple devices. The method 400 may be implemented in the form of executable instructions stored on a machine-readable storage medium, such as storage medium 320, and/or in the form of electronic circuitry.

At block 410, first network device 200 aggregates traffic from a plurality of physical ports 230 of the first network device 200 to be output to a second network device 220, into a single logical port. Next, at block 420, the first network device 200 selects one of a plurality of links from the first network device to the second network device, to output the traffic from the single logical port. The first link of the plurality of links is to form a direct connection between the first and second network devices 200 and 220. A second link of the plurality of links is to connect a network appliance 210 between the first and second network devices 200 and 220. Then, at block 430, the first network device 200 redirects traffic from the selected link to an other link of the plurality of links without remapping a MAC table 204 of the first network device 200, if the selected links fails.

According to the foregoing, embodiments may provide a method and/or device for selection of one of first and second links between first and second network devices. By offering an additional link between the two network devices that bypasses the network appliance, throughput may be increased and load on the network appliance and network devices may be decreased, without adding special-purpose hardware to the network appliance or introducing a new point of failure. Moreover, if one of the links fails, the first and second network devices may switch-over to the other link without changing the layer 3 or network topology of the network.

I claim:

1. A first network device, comprising:
  - a first link to a second network device, the first and second network devices to at least one of switch and direct traffic;
  - a second link to the second network device, wherein the second link includes a network appliance between the first network device and the second network device, the network appliance to connect to the second network device and to at least one of modify and filter at least some of the traffic passing between the first and second network devices via the second link; and
  - a traffic module to select one of the first and second links to transmit the traffic from the first network device to the second network device at a given time, wherein a network layer topology is not changed if one of the first and second links fails, and wherein the network appliance is at least one of a network accelerator and a firewall device.
2. The first network device of claim 1, wherein the traffic module is to direct all the traffic to the second link and to redirect all the traffic from the second link to the first network link if the second link fails.
3. The first network device of claim 2, wherein,
  - the traffic module is to redirect all the traffic from the first link back to the second link if the second link recovers,

8

the first network switch includes a keep-alive mechanism to determine if at least one of the first and second links has failed, and

the first network switch is to reprogram a trunk-balance table to redirect traffic from one of the first and second links to another of the first and second links.

4. The first network device of claim 1, wherein the traffic module is to determine which of the traffic to output to which of the first and second links based on a network forwarding policy.

5. The first network device of claim 4, wherein, the network forwarding policy is based on a type of the traffic,

the traffic module is to output a first type of the traffic to one of the first and second links, and

the traffic module is to output a second type of the traffic to a remainder of the first and second links.

6. The first network device of claim 5, wherein the traffic module is to analyze a header of a packet to determine the type of the traffic.

7. The first network device of claim 6, wherein the first type is Transmission Control Protocol (TCP) related data and the second type is non-TCP related data.

8. The first network device of claim 4, further comprising: an active set of links including the first and second links, each of the links of the active set associated with a cost, wherein

the network forwarding policy is based on the cost of the links of the active set,

the traffic module is to select one of the links from the active set of links to transmit the traffic from the first network device to the second network device, and

the traffic module is to remove a failed link from the active set of links.

9. The first network device of claim 4, wherein, the second network device includes a traffic module to select one of the first and second links to transmit traffic from the second network device to the first network device at a given time, and

the traffic module of the second network device is to determine which of the traffic to output to which of the first and second links based on a network forwarding policy.

10. The first network device of claim 1, wherein, the first network device includes a plurality of ports to output the traffic to the second network device, and the first network device is to aggregate at the data link layer the traffic to be output to the second network device along one of the first and second links.

11. The first network device of claim 1, wherein, the first and second network devices are switches, and the media access control (MAC) table of the first network device is retained if the selected link fails and the traffic is redirected to the other of the first and second links.

12. The first network device of claim 11, wherein an extra MAC learn and a MAC move are not processed by a processor of the first network device if the selected link fails and the traffic is redirected to the other of the first and second links.

13. The first network device of claim 1, wherein, the first and second network devices are at least one of a router and a switch,

the first and second network devices are to select one the first and second links to transmit traffic, if the network appliance is a network accelerator, and

one of the first and second network devices are to select one the first and second links to transmit traffic, if the network appliance is a firewall.



14. A method, comprising:  
 aggregating, at a first network device, traffic from a plurality of physical ports to be output to a second network device, into a single logical port;  
 selecting, at the first network device, one of a plurality of links from the first network device to the second network device to output the traffic from the single logical port, a first link of the plurality of links to form a direct connection between the first and second network devices and a second link of the plurality of links to form a second connection between the first and second network devices, wherein the second link includes a network appliance between the first and second network devices; and  
 redirecting, at the first network device, traffic from the selected link to an other link of the plurality of links without remapping a media access control (MAC) table of the first network device, if the selected links fails, wherein the network appliance is at least one of a network accelerator and a firewall device.

15. The method of claim 14, wherein:  
 the first network device and the second network devices are switches, and  
 a media access control (MAC) table of the first network device is retained if the selected link fails and the traffic is redirected to the other of the first and second links.

16. The method of claim 14, wherein:  
 the first and second network devices are at least one of a router and a switch,  
 the first and second network devices are to select one the first and second links to transmit traffic, if the network appliance is a network accelerator, and  
 one of the first and second network devices are to select one the first and second links to transmit traffic, if the network appliance is a firewall.

17. A non-transitory computer-readable storage medium storing instructions that, if executed by a processor of a network switch, cause the processor to:

select one of first and second links to output traffic from a first network device to a second network device, the first link to transmit the traffic between the first and second network devices directly and the second link to transmit the traffic between the first and second network devices, wherein the second link includes a network appliance between the first network device and the second network device;  
 monitor the selected link for link failure; and  
 switch selection from the selected link to an other of the first and second links without changing a network topology of the network switch, if the selected links fails, wherein the network appliance is at least one of a network accelerator and a firewall device.

18. The non-transitory computer-readable storage medium of claim 17, wherein:  
 the first network device and the second network devices are switches, and  
 a media access control (MAC) table of the first network device is retained if the selected link fails and the traffic is redirected to the other of the first and second links.

19. The non-transitory computer-readable storage medium of claim 18, wherein an extra MAC learn and a MAC move are not processed by a processor of the first network device if the selected link fails and the traffic is redirected to the other of the first and second links.

20. The non-transitory computer-readable storage medium of claim 17, wherein:  
 the first and second network devices are at least one of a router and a switch,  
 the first and second network devices are to select one the first and second links to transmit traffic, if the network appliance is a network accelerator, and  
 one of the first and second network devices are to select one the first and second links to transmit traffic, if the network appliance is a firewall.

\* \* \* \* \*