



US009270705B1

(12) **United States Patent**
Chen et al.

(10) **Patent No.:** **US 9,270,705 B1**
(45) **Date of Patent:** ***Feb. 23, 2016**

(54) **APPLYING SECURITY POLICY TO AN APPLICATION SESSION**

H04L 63/0407; H04L 51/04; H04M 1/72547;
G06F 21/00

See application file for complete search history.

(71) Applicant: **A10 Networks, Inc.**, San Jose, CA (US)

(56) **References Cited**

(72) Inventors: **Lee Chen**, Saratoga, CA (US); **Dennis Oshiba**, Fremont, CA (US); **John Chiong**, San Jose, CA (US)

U.S. PATENT DOCUMENTS

5,774,660 A 6/1998 Brendel et al.
5,935,207 A 8/1999 Logue et al.

(73) Assignee: **A10 Networks, Inc.**, San Jose, CA (US)

(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 2 days.

FOREIGN PATENT DOCUMENTS

This patent is subject to a terminal disclaimer.

CN 1372662 A 10/2002
CN 1449618 10/2003

(Continued)

(21) Appl. No.: **14/323,884**

Cardellini et al., "Dynamic Load Balancing on Web-server Systems", IEEE Internet Computing, vol. 3, No. 3, pp. 28-39, May-Jun. 1999.

(22) Filed: **Jul. 3, 2014**

(Continued)

Related U.S. Application Data

Primary Examiner — Carl Colin

Assistant Examiner — Gary Lavelle

(63) Continuation of application No. 14/061,720, filed on Oct. 23, 2013, now Pat. No. 8,813,180, which is a continuation of application No. 13/650,179, filed on Oct. 12, 2012, now Pat. No. 8,595,791, which is a

(74) *Attorney, Agent, or Firm* — Carr & Ferrell LLP

(Continued)

(51) **Int. Cl.**
H04L 29/06 (2006.01)
G06F 21/00 (2013.01)

(57) **ABSTRACT**

Applying a security policy to an application session, includes: recognizing the application session between a network and an application via a security gateway; determining by the security gateway a user identity of the application session using information about the application session; obtaining by the security gateway the security policy comprising network parameters mapped to the user identity; and applying the security policy to the application session by the security gateway. The user identity may be a network user identity or an application user identity recognized from packets of the application session. The security policy may comprise a network traffic policy mapped and/or a document access policy mapped to the user identity, where the network traffic policy is applied to the application session. The security gateway may further generate a security report concerning the application of the security policy to the application session.


(Continued)

(52) **U.S. Cl.**
CPC **H04L 63/20** (2013.01); **G06F 21/00** (2013.01); **H04L 51/04** (2013.01); **H04L 63/02** (2013.01);

(Continued)

(58) **Field of Classification Search**
CPC ... H04L 63/20; H04L 63/0227; H04L 67/306; H04L 67/10; H04L 63/02; H04L 65/1026;

27 Claims, 11 Drawing Sheets



Related U.S. Application Data

continuation of application No. 12/788,339, filed on May 27, 2010, now Pat. No. 8,312,507, which is a continuation-in-part of application No. 12/771,491, filed on Apr. 30, 2010, now Pat. No. 7,979,585, which is a continuation of application No. 11/582,613, filed on Oct. 17, 2006, now Pat. No. 7,716,378.

(51) **Int. Cl.**

H04L 29/08 (2006.01)
H04L 12/58 (2006.01)

(52) **U.S. Cl.**

CPC *H04L 63/0227* (2013.01); *H04L 63/0407* (2013.01); *H04L 65/1026* (2013.01); *H04L 67/10* (2013.01); *H04L 67/306* (2013.01); *H04L 67/42* (2013.01)

(56)

References Cited

U.S. PATENT DOCUMENTS

5,958,053 A	9/1999	Denker	7,970,934 B1 *	6/2011	Patel	H04L 41/147 709/244
6,003,069 A	12/1999	Cavill	7,990,847 B1	8/2011	Leroy et al.	
6,047,268 A	4/2000	Bartoli et al.	7,991,859 B1	8/2011	Miller et al.	
6,219,706 B1	4/2001	Fan et al.	8,090,866 B1	1/2012	Bashyam et al.	
6,321,338 B1	11/2001	Porras et al.	8,122,116 B2	2/2012	Matsunaga et al.	
6,374,300 B2	4/2002	Masters	8,185,651 B2	5/2012	Moran et al.	
6,587,866 B1	7/2003	Modi et al.	8,191,106 B2 *	5/2012	Choyi	H04L 63/20 713/150
6,748,414 B1	6/2004	Bournas	8,224,971 B1	7/2012	Miller et al.	
6,772,334 B1	8/2004	Glawitsch	8,296,434 B1	10/2012	Miller et al.	
6,779,033 B1	8/2004	Watson et al.	8,312,507 B2	11/2012	Chen et al.	
7,010,605 B1	3/2006	Dharmarajan	8,379,515 B1	2/2013	Mukerji	
7,058,718 B2	6/2006	Fontes et al.	8,554,929 B1	10/2013	Szeto et al.	
7,069,438 B2	6/2006	Balabine et al.	8,560,693 B1	10/2013	Wang et al.	
7,076,555 B1	7/2006	Orman et al.	8,584,199 B1	11/2013	Chen et al.	
7,143,087 B2	11/2006	Fairweather	8,595,791 B1	11/2013	Chen et al.	
7,181,524 B1	2/2007	Lele	RE44,701 E	1/2014	Chen et al.	
7,228,359 B1	6/2007	Monteiro	8,681,610 B1	3/2014	Mukerji	
7,234,161 B1	6/2007	Maufer et al.	8,782,221 B2	7/2014	Han	
7,236,457 B2	6/2007	Joe	8,813,180 B1	8/2014	Chen et al.	
7,254,133 B2	8/2007	Govindarajan et al.	8,826,372 B1	9/2014	Chen et al.	
7,269,850 B2	9/2007	Govindarajan et al.	8,885,463 B1	11/2014	Medved et al.	
7,277,963 B2	10/2007	Dolson et al.	8,897,154 B2	11/2014	Jalan et al.	
7,301,899 B2	11/2007	Goldstone	8,965,957 B2	2/2015	Barros	
7,308,499 B2	12/2007	Chavez	8,977,749 B1	3/2015	Han	
7,310,686 B2	12/2007	Uysal	8,990,262 B2	3/2015	Chen et al.	
7,328,267 B1	2/2008	Bashyam et al.	9,094,364 B2	7/2015	Jalan et al.	
7,334,232 B2	2/2008	Jacobs et al.	9,106,561 B2	8/2015	Jalan et al.	
7,337,241 B2	2/2008	Boucher et al.	2001/0049741 A1	12/2001	Skene et al.	
7,343,399 B2	3/2008	Hayball et al.	2002/0032777 A1	3/2002	Kawata et al.	
7,349,970 B2	3/2008	Clement et al.	2002/0078164 A1	6/2002	Reinschmidt	
7,370,353 B2	5/2008	Yang	2002/0091844 A1	7/2002	Craft et al.	
7,391,725 B2	6/2008	Huitema et al.	2002/0103916 A1	8/2002	Chen et al.	
7,398,317 B2	7/2008	Chen et al.	2002/0133491 A1	9/2002	Sim et al.	
7,423,977 B1	9/2008	Joshi	2002/0138618 A1	9/2002	Szabo	
7,430,755 B1	9/2008	Hughes et al.	2002/0143991 A1	10/2002	Chow et al.	
7,467,202 B2	12/2008	Savchuk	2002/0178259 A1	11/2002	Doyle et al.	
7,472,190 B2	12/2008	Robinson	2002/0194335 A1	12/2002	Maynard	
7,506,360 B1	3/2009	Wilkinson et al.	2002/0194350 A1	12/2002	Lu et al.	
7,512,980 B2	3/2009	Copeland et al.	2003/0009591 A1	1/2003	Hayball et al.	
7,533,409 B2	5/2009	Keane et al.	2003/0014544 A1	1/2003	Petty	
7,552,323 B2	6/2009	Shay	2003/0023711 A1	1/2003	Parmar et al.	
7,584,262 B1	9/2009	Wang et al.	2003/0023873 A1	1/2003	Ben-Itzhak	
7,590,736 B2	9/2009	Hydrie et al.	2003/0035409 A1	2/2003	Wang et al.	
7,613,193 B2	11/2009	Swami et al.	2003/0035420 A1	2/2003	Niu	
7,613,822 B2	11/2009	Joy et al.	2003/0131245 A1	7/2003	Linderman	
7,673,072 B2	3/2010	Boucher et al.	2003/0135625 A1	7/2003	Fontes et al.	
7,675,854 B2	3/2010	Chen et al.	2003/0195962 A1	10/2003	Kikuchi et al.	
7,707,295 B1	4/2010	Szeto et al.	2004/0062246 A1	4/2004	Boucher et al.	
7,711,790 B1	5/2010	Barrett et al.	2004/0073703 A1	4/2004	Boucher et al.	
7,747,748 B2	6/2010	Allen	2004/0078419 A1	4/2004	Ferrari et al.	
7,792,113 B1	9/2010	Foschiano et al.	2004/0078480 A1	4/2004	Boucher et al.	
7,826,487 B1	11/2010	Mukerji et al.	2004/0111516 A1	6/2004	Cain	
7,881,215 B1	2/2011	Daigle et al.	2004/0187032 A1	9/2004	Gels et al.	
			2004/0199616 A1	10/2004	Karhu	
			2004/0199646 A1	10/2004	Susai et al.	
			2004/0202182 A1	10/2004	Lund et al.	
			2004/0210663 A1	10/2004	Phillips et al.	
			2004/0213158 A1	10/2004	Collett et al.	
			2005/0009520 A1 *	1/2005	Herrero	H04L 29/12188 455/435.1
			2005/0021848 A1	1/2005	Jorgenson	
			2005/0027862 A1	2/2005	Nguyen et al.	
			2005/0036501 A1	2/2005	Chung et al.	
			2005/0036511 A1	2/2005	Baratakke et al.	
			2005/0044270 A1	2/2005	Grove et al.	
			2005/0074013 A1	4/2005	Hershey et al.	
			2005/0080890 A1	4/2005	Yang et al.	
			2005/0102400 A1	5/2005	Nakahara et al.	
			2005/0125276 A1 *	6/2005	Rusu	G06Q 30/02 705/304
			2005/0163073 A1	7/2005	Heller et al.	
			2005/0198335 A1	9/2005	Brown et al.	
			2005/0240989 A1	10/2005	Kim et al.	
			2005/0249225 A1	11/2005	Singhal	
			2006/0023721 A1	2/2006	Miyake et al.	
			2006/0036610 A1	2/2006	Wang	
			2006/0036733 A1	2/2006	Fujimoto et al.	

(56)

References Cited

U.S. PATENT DOCUMENTS

2006/0069774 A1 3/2006 Chen et al.
 2006/0069804 A1 3/2006 Miyake et al.
 2006/0077926 A1* 4/2006 Rune H04L 45/34
 370/328
 2006/0092950 A1 5/2006 Arregoces et al.
 2006/0098645 A1 5/2006 Walkin
 2006/0168319 A1 7/2006 Trossen
 2006/0187901 A1 8/2006 Cortes et al.
 2006/0190997 A1 8/2006 Mahajani et al.
 2006/0251057 A1 11/2006 Kwon et al.
 2006/0277303 A1 12/2006 Hegde et al.
 2006/0280121 A1 12/2006 Matoba
 2007/0019543 A1 1/2007 Wei et al.
 2007/0118881 A1 5/2007 Mitchell et al.
 2007/0156919 A1 7/2007 Potti et al.
 2007/0185998 A1 8/2007 Touitou et al.
 2007/0195792 A1 8/2007 Chen et al.
 2007/0230337 A1 10/2007 Igarashi et al.
 2007/0245090 A1 10/2007 King et al.
 2007/0259673 A1* 11/2007 Willars H04W 52/0225
 455/453
 2007/0283429 A1 12/2007 Chen et al.
 2007/0286077 A1 12/2007 Wu
 2007/0288247 A1 12/2007 Mackay
 2007/0294209 A1* 12/2007 Strub H04L 67/22
 2008/0031263 A1 2/2008 Ervin et al.
 2008/0101396 A1 5/2008 Miyata
 2008/0109452 A1 5/2008 Patterson
 2008/0109870 A1* 5/2008 Sherlock H04L 63/1425
 726/1
 2008/0134332 A1 6/2008 Keohane et al.
 2008/0228781 A1 9/2008 Chen et al.
 2008/0250099 A1 10/2008 Shen et al.
 2008/0291911 A1 11/2008 Lee et al.
 2009/0049198 A1 2/2009 Blinn et al.
 2009/0070470 A1 3/2009 Bauman et al.
 2009/0077651 A1 3/2009 Poeluev
 2009/0092124 A1 4/2009 Singhal et al.
 2009/0106830 A1 4/2009 Maher
 2009/0138606 A1 5/2009 Moran et al.
 2009/0138945 A1 5/2009 Savchuk
 2009/0141634 A1 6/2009 Rothstein et al.
 2009/0164614 A1 6/2009 Christian et al.
 2009/0172093 A1 7/2009 Matsubara
 2009/0213858 A1 8/2009 Dolganow et al.
 2009/0222583 A1 9/2009 Josefsberg et al.
 2009/0228547 A1 9/2009 Miyaoka et al.
 2010/0008229 A1 1/2010 Bi et al.
 2010/0036952 A1 2/2010 Hazlewood et al.
 2010/0054139 A1 3/2010 Chun et al.
 2010/0061319 A1 3/2010 Aso et al.
 2010/0064008 A1 3/2010 Yan et al.
 2010/0083076 A1 4/2010 Ushiyama
 2010/0094985 A1 4/2010 Abu-Samaha et al.
 2010/0106833 A1 4/2010 Banerjee et al.
 2010/0106854 A1 4/2010 Kim et al.
 2010/0162378 A1 6/2010 Jayawardena et al.
 2010/0210265 A1 8/2010 Borzsei et al.
 2010/0217793 A1 8/2010 Preiss
 2010/0223630 A1 9/2010 Degenkolb et al.
 2010/0228819 A1 9/2010 Wei
 2010/0235507 A1 9/2010 Szeto et al.
 2010/0235522 A1 9/2010 Chen et al.
 2010/0235880 A1 9/2010 Chen et al.
 2010/0265824 A1 10/2010 Chao et al.
 2010/0268814 A1 10/2010 Cross et al.
 2010/0293296 A1 11/2010 Hsu et al.
 2010/0312740 A1 12/2010 Clemm et al.
 2010/0318631 A1 12/2010 Shukla
 2010/0322252 A1 12/2010 Suganthi et al.
 2010/0330971 A1 12/2010 Selitser et al.
 2010/0333101 A1 12/2010 Pope et al.
 2011/0007652 A1 1/2011 Bai
 2011/0023071 A1 1/2011 Li et al.
 2011/0029599 A1 2/2011 Pulleyn et al.

2011/0032941 A1 2/2011 Quach et al.
 2011/0040826 A1 2/2011 Chadzelek et al.
 2011/0047294 A1 2/2011 Singh et al.
 2011/0060831 A1 3/2011 Ishii et al.
 2011/0093522 A1 4/2011 Chen et al.
 2011/0110294 A1 5/2011 Valluri et al.
 2011/0145324 A1 6/2011 Reinart et al.
 2011/0153834 A1 6/2011 Bharrat
 2011/0185073 A1 7/2011 Jagadeeswaran et al.
 2011/0191773 A1 8/2011 Pavel et al.
 2011/0196971 A1 8/2011 Reguraman et al.
 2011/0276695 A1 11/2011 Maldaner
 2011/0276982 A1 11/2011 Nakayama et al.
 2011/0289496 A1 11/2011 Steer
 2011/0302256 A1 12/2011 Suresheandra et al.
 2011/0307541 A1 12/2011 Walsh et al.
 2012/0023231 A1 1/2012 Ueno
 2012/0030341 A1 2/2012 Jensen et al.
 2012/0066371 A1 3/2012 Patel et al.
 2012/0084419 A1 4/2012 Kannan et al.
 2012/0084460 A1 4/2012 McGinnity et al.
 2012/0144014 A1 6/2012 Natham et al.
 2012/0144015 A1 6/2012 Jalan et al.
 2012/0170548 A1 7/2012 Rajagopalan et al.
 2012/0173759 A1 7/2012 Agarwal et al.
 2012/0191839 A1 7/2012 Maynard
 2012/0240185 A1 9/2012 Kapoor et al.
 2012/0290727 A1 11/2012 Tivig
 2012/0297046 A1 11/2012 Raja et al.
 2013/0046876 A1 2/2013 Narayana et al.
 2013/0074177 A1 3/2013 Varadhan et al.
 2013/0083725 A1 4/2013 Mallya et al.
 2013/0100958 A1 4/2013 Jalan et al.
 2013/0136139 A1 5/2013 Zheng et al.
 2013/0166762 A1 6/2013 Jalan et al.
 2013/0173795 A1 7/2013 McPherson
 2013/0176854 A1 7/2013 Chisu et al.
 2013/0191486 A1 7/2013 Someya et al.
 2013/0198385 A1 8/2013 Han et al.
 2014/0012972 A1 1/2014 Han
 2014/0089500 A1 3/2014 Sankar et al.
 2014/0164617 A1 6/2014 Jalan et al.
 2014/0169168 A1 6/2014 Jalan et al.
 2014/0207845 A1 7/2014 Han et al.
 2014/0258536 A1 9/2014 Chiong
 2014/0269728 A1 9/2014 Jalan et al.
 2014/0330982 A1 11/2014 Jalan et al.
 2014/0359052 A1 12/2014 Joachimpillai et al.
 2015/0039671 A1 2/2015 Jalan et al.
 2015/0156223 A1 6/2015 Xu et al.

FOREIGN PATENT DOCUMENTS

CN 1529460 9/2004
 CN 1575582 2/2005
 CN 1725702 1/2006
 CN 101004740 A 7/2007
 CN 101094225 12/2007
 CN 101189598 5/2008
 CN 101247349 A 8/2008
 CN 101261644 A 9/2008
 CN 102546590 7/2012
 CN 102571742 7/2012
 CN 102577252 7/2012
 CN 102918801 2/2013
 CN 103533018 A 1/2014
 CN 103944954 7/2014
 CN 104040990 9/2014
 CN 104067569 9/2014
 CN 104106241 10/2014
 CN 104137491 11/2014
 CN 104796396 A 7/2015
 EP 1209876 5/2002
 EP 1770915 4/2007
 EP 1885096 2/2008
 EP 2577910 4/2013
 EP 2622795 8/2013
 EP 2647174 10/2013
 EP 2760170 7/2014

(56)

References Cited

FOREIGN PATENT DOCUMENTS

EP	2772026	9/2014
EP	2901308 A2	8/2015
HK	1182560	11/2013
HK	1183569 A	12/2013
HK	1183996 A	1/2014
HK	1189438	6/2014
HK	1198565 A1	5/2015
HK	1198848 A1	6/2015
HK	1199153 A1	6/2015
HK	1199779 A1	7/2015
JP	0997233	4/1997
JP	11338836	10/1999
JP	2000276432 A	10/2000
JP	200151859	2/2001
JP	2006332825 A	12/2006
JP	200840718	2/2008
JP	2013528330	5/2011
JP	2014143686	8/2014
JP	2015507380 A	3/2015
KR	10-0830413	5/2008
WO	01/13228	2/2001
WO	0114990	3/2001
WO	WO0145349	6/2001
WO	03103237	12/2003
WO	WO2004084085 A1	9/2004
WO	2008053954	5/2008
WO	2011049770	4/2011
WO	2011149796	12/2011
WO	2012050747	4/2012
WO	2012075237	6/2012
WO	2013070391	5/2013
WO	2013081952	6/2013

WO	2013096019	6/2013
WO	2013112492	8/2013
WO	2014052099	4/2014
WO	2014088741	6/2014
WO	2014093829	6/2014
WO	WO2014138483	9/2014
WO	WO2014144837	9/2014
WO	WO2014179753	11/2014

OTHER PUBLICATIONS

Hunt et al. NetDispatcher: A TCP Connection Router, IBM Research Report RC 20853 May 19, 1997.

Spatscheck et al., "Optimizing TCP Forwarder Performance", IEEE/ACM Transactions on Networking, vol. 8, No. 2, Apr. 2000.

Kjaer et al. "Resource allocation and disturbance rejection in web servers using SLAs and virtualized servers", IEEE Transactions on Network and Service Management, IEEE, US, vol. 6, No. 4, Dec. 1, 2009.

Sharifian et al. "An approximation-based load-balancing algorithm with admission control for cluster web servers with dynamic workloads", The Journal of Supercomputing, Kluwer Academic Publishers, BO, vol. 53, No. 3, Jul. 3, 2009.

Noguchi, "Realizing the Highest Level "Layer 7" Switch" = Totally Managing Network Resources, Applications, and Users =, Computer & Network LAN, Jan. 1, 2000, vol. 18, No. 1, p. 109-112.

Takahashi, "The Fundamentals of the Windows Network: Understanding the Mystery of the Windows Network from the Basics", Network Magazine, Jul. 1, 2006, vol. 11, No. 7, p. 32-35.

Ohnuma, "AppSwitch: 7th Layer Switch Provided with Full Setup and Report Tools", Interop Magazine, Jun. 1, 2000, vol. 10, No. 6, p. 148-150.

* cited by examiner




FIG. 1a




FIG. 1b




FIG. 1c




FIG. 2




FIG. 3




FIG. 4a




FIG. 4b




FIG. 5




FIG. 6




FIG. 7

Network Traffic Policy 451

Network based Application Session Access Control

Session Connection Rate Control

Traffic Shaping Control

Bandwidth Rate Capacity

Quality of Service or DSCP Marking Control

Packet Forwarding Control

Link Interface Preference

Server Load Balancing Preference

Application Session Modification Control

FIG. 8

APPLYING SECURITY POLICY TO AN APPLICATION SESSION

CROSS-REFERENCE TO RELATED APPLICATIONS

The present application is a continuation and claims the priority benefit of U.S. patent application Ser. No. 14/061,720, filed on Oct. 23, 2013, issued on Aug. 19, 2014, as U.S. Pat. No. 8,813,180; which in turn is a continuation of U.S. patent application Ser. No. 13/650,179, filed on Oct. 12, 2012, issued on Nov. 26, 2013, as U.S. Pat. No. 8,595,791; which in turn is a continuation of U.S. patent application Ser. No. 12/788,339, filed on May 27, 2010, issued on Nov. 13, 2012 as U.S. Pat. No. 8,312,507; which in turn is a continuation-in-part of U.S. patent application Ser. No. 12/771,491, filed on Apr. 30, 2010, issued on Jul. 12, 2011, as U.S. Pat. No. 7,979,585; which in turn is a continuation of U.S. patent application Ser. No. 11/582,613, filed on Oct. 17, 2006, issued on May 11, 2010, as U.S. Pat. No. 7,716,378. The disclosures of each of the above referenced applications are hereby incorporated by reference.

BACKGROUND OF THE INVENTION

1. Field

This invention relates generally to data networking, and more specifically, to a system and method to apply a network traffic policy based on a user identity during an application session.

2. Related Art

The secure data network of a company is a critical component for day-to-day functioning of company business activities. Company employees access the secure data network for communication within the company and with the outside world. Company information, oftentimes proprietary or confidential, is exchanged during the communication.

Typically, an employee gains access to the company's secure data network by means of a network logon procedure using a private user identity, such as a user name "Robert P. Williamson" or an employee number "NG01-60410". Subsequent information exchange using the company's office applications, such as email, file transfer or document control is traceable based on the private user identity through network event logs.

Since the late 1990's, we have been witnessing the phenomenal rising popularity of public communication applications and services, such as email and Instant Messaging offered by Yahoo™, America Online™ (AOL), or Google™, conferencing and collaboration services offered by WebEx™ or Centra™, or peer-to-peer services for a variety of file sharing. Generally, a public communication service allows a user to exchange information through messaging, text chat or document exchange using a public user identity, such as "butterdragon", "fingemail1984", or "peterrabbit".

However, in a company setting, when an employee connects to a public communication service with a public user identity over the company's secure data network, the information exchange is not easily traceable if at all since the public user identity is not tied to the private user identity.

In one example, a company's information technology (IT) department notices that an employee Victor has been using the company's email system to send out proprietary documents, violating the company's security policy. After issuing a warning to Victor, the IT department finds no further violations. Unfortunately, they are not aware of the fact that Victor

has continued this activity using Yahoo™ email with a public user identity "PiratesOfCaribbean@Yahoo.com".

In another example, two weeks before a major trade show, a company implements a security measure to monitor communication activities of employees of director level and above to ensure confidentiality of competitive information. This security measure, covering company email, phone conversation and voice messaging, nevertheless proves to be a failure as sensitive information leaks out to a business reporter anyway prior to the trade show. The source of the leak may never be confirmed, but the business reporter privately discloses that he gets the information from an anonymous employee of the company using AOL Instant Messaging™ with screen name "opensecret2006".

The above discussion illustrates the need for a security solution to associate a user identity to a public application.

BRIEF SUMMARY OF THE INVENTION

Method for applying a security policy to an application session, includes: recognizing the application session between a network and an application via a security gateway; determining by the security gateway a user identity of the application session using information about the application session; obtaining by the security gateway the security policy comprising network parameters mapped to the user identity; and applying the security policy to the application session by the security gateway. The user identity may be a network user identity or an application user identity recognized from packets of the application session. The security policy may comprise a network traffic policy mapped and/or a document access policy mapped to the user identity, where the network traffic policy is applied to the application session. The security gateway may further generate a security report concerning the application of the security policy to the application session.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1a illustrates a secure network.
 FIG. 1b illustrates an access session and an application session.
 FIG. 1c illustrates an access session record and an application session record.
 FIG. 2 illustrates a process to generate an application session record.
 FIG. 3 illustrates a process to recognize an application session.
 FIG. 4a illustrates a process to determine a public user identity of application session.
 FIG. 4b illustrates a data packet in an AIM log-on packet.
 FIG. 5 illustrates a process to determine a private user identity.
 FIG. 6 illustrates an embodiment of a security gateway obtaining a security policy by querying a corporate directory.
 FIG. 7 illustrates a security policy including a security control.
 FIG. 8 illustrates a plurality of embodiments of network traffic policy.

DETAILED DESCRIPTION OF THE INVENTION

FIG. 1a illustrates a secure network. A secure network 160 includes a host 130. User 120 uses host 130 to access a public application 180 hosted in application server 190. Application server 190 is outside of secure network 160. The network traffic between host 130 and appli-

cation server **190** passes through security gateway **150**. The security gateway **150** is operationally coupled to a processor **171** and a computer readable medium **172**. The computer readable medium **172** stores computer readable program code for implementing the various embodiments of the present invention as described herein.

Host **130** is a computing device with network access capabilities. The host **130** is operationally coupled to a processor **173** and a computer readable medium **174**. The computer readable medium **174** stores computer readable program code for implementing the various embodiments of the present invention as described herein. In some embodiments, host **130** is a workstation, a desktop personal computer or a laptop personal computer. In some embodiments, host **130** is a Personal Data Assistant (PDA), a smartphone, or a cellular phone.

In some embodiments, secure network **160** is an Internet Protocol (IP) network. In some embodiments, secure network **160** is a corporate data network or a regional corporate data network. In some embodiments, secure network **160** is an Internet service provider network. In some embodiments, secure network **160** is a residential data network. In some embodiments, secure network **160** includes a wired network such as Ethernet. In some embodiments, secure network **160** includes a wireless network such as a WiFi network.

Public application **180** provides a service that allows user **120** to communicate with other users in a real-time fashion. In some embodiments, the service includes text chat. In some embodiments, the service includes a voice call or a video call. In some embodiments, the service includes a network game. In some embodiments, the service includes exchanging a document, such as sending or receiving a text document, a PowerPoint™ presentation, an Excel™ spreadsheet, an image file, a music file or a video clip. In some embodiments, the service includes a collaborative document processing such as creating a document, a business plan, an agreement, wherein user **120** collaborates with other users in a real time fashion. In some embodiments, the service includes a collaborative information exchange such as a conference call. In some embodiments, the service is a social networking service. In some embodiments, the service includes real-time collaboration and non real-time collaboration.

In one example, public application **180** provides America Online Instant Messenger™ service. In one example, public application **180** provides Yahoo Instant Messenger™ voice service. In some embodiments, public application **180** provides a file sharing service such as Kazaa™ file sharing service. In some embodiments, public application **180** provides a network game service such as Microsoft™ Network Game service. In some embodiments, public application **180** provides an on-line collaborative document processing such as Google Docs™, and Salesforce.com™. In some embodiments, public application **180** provides an on-line information exchange and communications such as WebEx™. In some embodiments, public application **180** provides live information streaming such as live video streaming, live audio streaming, and instantaneous picture uploading.

Security gateway **150** is situated at the edge of secure network **160**. Security gateway **150** connects secure network **160** to public application **180**. Security gateway **150** receives network traffic from secure network **160** and transmits the network traffic to application server **190**. Likewise, security gateway **150** receives network traffic from application server **190** and transmits the network traffic to secure network **160**.

In some embodiments, security gateway **150** includes the function of a corporate Wide Area Network (WAN) gateway. In some embodiments, security gateway **150** includes the

function of a residential broadband gateway. In some embodiments, security gateway **150** includes the function of a WAN gateway for an Internet service provider.

FIG. **1b** illustrates an access session and an application session.

User **120** uses host **130** to access secure network **160** during an access session **162**.

Host **130** has a host identity **134**. Host **130** uses host identity **134** to connect to secure network **160**. In some embodiments, host identity **134** includes an IP address. In some embodiments, host identity **134** includes a Media Access Control (MAC) address.

Within secure network **160**, user **120** has a private user identity **124**. In some embodiments, private user identity **124** is an employee number or an employee name. In some embodiments, private user identity **124** is an Internet service subscription identity. In some embodiments, access session **162** is established after a successful network user log-in procedure, such as an employee network log-in, for secure network **160** using private user identity **124**. Private user identity **124** is associated with host identity **134**. In some embodiments, host **130** is a guest computing device. Private user identity **124** is associated with an Ethernet switch port where host **130** connects. In this embodiment, private user identity **124** is a port number, an Ethernet interface identity, or an Ethernet VLAN identity.

User **120** uses host **130** to access public application **180** in an application session **182**. User **120** uses a public user identity **127** during application session **182**. In some embodiments, public application **180** prompts user **120** to log-in before establishing application session **182**. During the application user log-in procedure, user **120** provides to public application **180** public user identity **127**. In another embodiment, public application **180** selects a public user identity **127** for user **120** for application session **182**. In some embodiments, public user identity **127** is set up through a user registration process or a service subscription process. Network traffic in application session **182** passes through security gateway **150**.

FIG. **1c** illustrates an access session record and an application session record.

Access session record **164** records information about access session **162**. The information includes private user identity **124**, host identity **134** and access session time **166**. In some embodiments, access session time **166** is the starting time when access session **162** is established. In some embodiments, access session time **166** includes the starting time and the ending time when user **120** finishes access session **162**. In some embodiments, access session time **166** is a time stamp for a time during access session **162**.

Application session record **184** records information about application session **182**. The information includes private user identity **124**, public user identity **127**, and application session time **186**. In some embodiments, the information further includes host identity **134**. In some embodiments, application session time **186** includes the starting time when application session **182** is established. In some embodiments, application session time **186** includes a time stamp during application session **182**. In some embodiments, application session time **186** includes a time stamp when security gateway **150** recognizes application session **182**.

FIG. **2** illustrates a process to generate an application session record.

The process of generating application session record **184** includes multiple steps.

In step **201**, security gateway **150** recognizes an application session.

5

In step 202, security gateway 150 determines a public user identity of the application session.

In step 203, security gateway 150 determines a private user identity using information about the application session.

FIGS. 3-5 illustrates steps 201-203 respectively.

FIG. 3 illustrates a process to recognize an application session.

Security gateway 150 inspects network traffic between host 130 and application server 190 to recognize application session 182 for public application 180.

In some embodiments, security gateway 150 inspects data packet 339 between host 130 and application server 190 for the recognition of application session 182.

Security gateway 150 includes an application identifier 355 for public application 180. Application identifier 355 includes information for recognizing application session 182. In some embodiments, application identifier 355 includes a transport layer information, such as Transmission Control Protocol (TCP) or User Datagram Protocol (UDP); and at least one transport port number, such as a TCP port number or a UDP port number. In some embodiments, application identifier 355 includes application layer information, such as one or more data filters wherein a data filter specifies a value and a position of the value in a data packet. In one example, a data filter is [byte 0 with value "0x52"]. In one example, a data filter is [byte 4-7 with ASCII value of "ADEH"].

Security gateway 150 matches data packet 339 against application identifier 355.

In some embodiments, application identifier 355 includes transport protocol type of TCP and a destination TCP port number of 5190, the TCP port number used by AIM protocol. In this embodiment, data packet 339 is a TCP packet from host 130 to application server 190. Security gateway 150 matches data packet 339 against application identifier 355 and determines that public application 180 provides AIM service.

Security gateway 150 creates application session record 184. Security gateway 150 extracted the source IP address from the IP header of data packet 339, and stores the source IP address as host identity 134. In some embodiments, data packet 339 includes link layer information, such as a source MAC address; security gateway 150 extracts and stores the source MAC address as host identity 134.

In some embodiments, security gateway 150 connects to a clock 359. Clock 359 indicates the current time of day. Security gateway 150 stores the time of day indicated by clock 359 in application session time 186.

FIG. 4a illustrates a process to determine a public user identity of application session 182.

The method for determining public user identity 127 is typically specific to public application 180. In some embodiments, data packet 339 is an application packet. For example, public application 180 provides AIM service; data packet 339 is an AIM packet.

An AIM packet includes multiple fields, for example

Command start field is a 1-byte data field starting at byte offset 0 having a fixed hexadecimal value "0x02";

Channel ID field is a 1-byte data field starting at byte offset 1;

Sequence number field is a 2-byte integer starting at byte offset 2;

Data field length field is a 2-byte data field starting at byte offset 4;

Family field is a 2-byte data field starting at byte offset 6; and

Subtype field is a 2-byte data field starting at byte offset 8.

6

An AIM log-on packet is a AIM packet with family field having a fixed hexadecimal value of "0x00 0x17" and subtype field having a fixed hexadecimal value of "0x00 0x06".

AIM log-on packet further includes buddy name length field, a 1-byte integer starting at byte offset 19, and a variable length buddy name field starting at byte offset 20. Buddy name length field indicates the length in bytes of buddy name field.

Security gateway 150 matches data packet 339 to determine if data packet 339 is an AIM log-on packet. In some embodiments, data packet 339 is an AIM log-on packet 400 illustrated in FIG. 4b. Security gateway 150 extracts buddy name length field 405. Security gateway 150 further extracts buddy name field 407. In this embodiment, buddy name length field 405 is integer "13" and buddy name field 407 is "JohnSmith1984". Security gateway 150 stores "JohnSmith1984" as public user identity 127 in application session record 184.

In some embodiments, data packet 339 is not an AIM log-on packet. Security gateway 150 inspects another data packet from host 130.

FIG. 5 illustrates a process to determine a private user identity.

Secure network 160 includes an identity server 570. The identity server 570 is operationally coupled to a processor 581 and a computer readable medium 582. The computer readable medium 582 stores computer readable program code for implementing the various embodiments of the present invention as described herein. Identity server 570 includes access session record 164 of access session 162 during which user 120 accesses application session 182.

Security gateway 150 queries identity server 570. Security gateway 150 sends host identity 134 and application session time 186 to identity server 570.

Identity server 570 receives host identity 134 and application session time 186. Identity server 570 matches host identity 134 and application session time 186 against access session record 164. Identity server 570 determines that host identity 134 matches host identity of access session record 164. Identity server 570 further determines that application session time 186 matches access session time 166 of access session record 164 as application session time 186 is between the starting time and the ending time of access session record 164. Identity server 570 sends private user identity 124 of access session record 164 to security gateway 150 as a response to the query.

Security gateway 150 receives private user identity 124 from identity server 570, and stores private user identity 124 in application session record 184.

In some embodiments, security gateway 150 stores public user identity 127 in application session record 184 after recognizing a log-on approval indication for the public user identity 127 from public application 180.

In some embodiments, security gateway 150 queries identity server 570 immediately after determining public user identity 127. In some embodiments, security gateway 150 queries identity server 570 after application session 182 ends.

In some embodiments, security gateway 150 queries identity server 570 by sending a plurality of host identities in a bulk request; and receives a plurality of private user identities in a bulk response.

In some embodiments, application session record 184 includes additional user information associated with private user identity 124, such as cubicle or office number, cubicle or office location, telephone number, email address, mail-drop location, department name/identity, or manager name.

In some embodiments, security gateway 150 obtains the additional user information from identity server 570. In some embodiments, security gateway 150 obtains the additional user information by querying a different server, such as a corporate directory server, by using the private user identity 124 received from identity server 570.

In some embodiments, public application 180 provides file transfer service using File Transfer Protocol (FTP) protocol or a proprietary protocol. In some embodiments, public application 180 provides email service using Simple Mail Transfer Protocol (SMTP), Internet Message Access Protocol (IMAP) or Post Office Protocol version 3 (POP3) protocol.

By using the application session record, the private user identity 124 and the public user identity 127 for an application session 182 may be determined. In some embodiments as illustrated by FIG. 6, upon determining the public user identity and the private user identity, security gateway 150 obtains security policy 402 for the application session 182 by querying corporate directory 470. In an embodiment, corporate directory 470 comprises security policy 402. In some embodiments, corporate directory 470 is a server computer comprising a storage 601 that includes security policy 402. In some embodiments, corporate directory 470 is a database comprising security policy 402. In another embodiment, corporate directory 470 is a software module with program code stored on a computer readable medium (not shown) running in a computer. In some embodiments, corporate directory 470 resides in identity server 570. In some embodiments, corporate directory 470 uses directory technologies such as Microsoft Active Directory™, lightweight directory access protocol (LDAP) directory services, web services, directory services using Java™ technologies. In some embodiments, corporate directory 470 includes a policy server hosting security policy 402 and other policies.

Security gateway 150 queries corporate directory 470 for a security policy, where the query includes user identity 424. User identity 424 may include private user identity 124 or public user identity 127. Corporate directory 470 matches user identity 424 against security policy 402 and determines security policy 402 is applicable to user identity 424. In some embodiments security policy 402 maps network parameters to a user identity and there is a match between user identity 424 and the user identity in the security policy 402. In some embodiments, security policy 402 maps network parameters to a group identity (not shown) and user identity 424 is a member of the group identity. In response to finding the match between the user identity 424 and the user identity in the security policy 402, corporate directory 470 sends security policy 402 to security gateway 150.

In some embodiments, security gateway 150 generates security report 475 based on application session record 184 and security policy 402. In some embodiments, security gateway 150 generates security report 475 based on a pre-determined user identity or a list of pre-determined user identities. For example, the security report may be generated based on an input of user identity or identities. In some embodiments, security gateway 150 generates security report 475 based on a pre-defined schedule or when requested by an operator.

In some embodiments, security policy 402 includes a security control function as illustrated in FIG. 7. Security gateway 150 applies the security policy 402 received from corporate directory 470 in response to the query to application session 182. Security policy 402 typically are configured by a company to protect against improper access to the company confidential documents and to protect against improper usage of the company secure network 160 vital for the company operation. In some embodiments, in response to receiving the secu-

rity policy 402, the security gateway 150 confirms that the received security policy 402 contains a user identity that matches the user identity 424 sent in the query. In response to the confirmation, the security gateway 150 applies the security policy 402 to the application session 182. In FIG. 7, security policy 402 includes network traffic policy 451 or document access policy 453.

FIG. 8 illustrates a plurality of embodiments of network traffic policy 451. In some embodiments, network traffic policy 451 specifies network based application session access control indicating if user identity 424 is denied or allowed to continue application session 182. If denied, security gateway 150 may stop forwarding data packets 439 of application session 182. In some embodiments, network traffic policy 451 specifies bandwidth rate capacity such as 1 Mbps, 100 MB per day, or 5 GB per month. In an embodiment, bandwidth rate capacity is measured in packets such as 100 packets per second, 10 thousand packets per day or 4 million packets per month. In some embodiments, network traffic policy 451 specifies a quality of service (QOS) mapped to user identity 424 for application session 182. For example, network traffic policy 451 indicates a change of Differentiated Services Code Point (DSCP) marking in the data packets 439 of application session 182. In some embodiments, network traffic policy 451 specifies a queuing delay, a queuing priority, a packet forwarding path, a link interface preference, a server load balancing preference, a packet routing policy, or other control to handle data packets 439 of application session 182.

In some embodiments, network traffic policy 451 includes a traffic shaping control. In one example, traffic shaping control specifies a TCP profile such as a change of window segment size, or a TCP window adjustment.

In some embodiments, network traffic policy 451 indicates session connection rate control based on user identity 424 specifying a rate or capacity such as 10 session connections per second, 35 concurrent sessions, 100 sessions during lunch hour, 500 sessions a day, 24 voice sessions a day, or 75 file transfer sessions an hour. In some embodiments, network traffic policy 451 may specify, when exceeding the rate or capacity, if application session 182 is denied or data packets 439 of application session 182 are dropped.

In some embodiments, network traffic policy 451 includes application session modification control mapped to user identity 424, specifying how data packets 439 of application session 182 are modified for the user with the user identity 424. In one example, application session modification control specifies security gateway 150 should perform network address translation (NAT) to application session 182 for user identity 424. In one example, security gateway 150 should perform port address translation (PAT) to application session 182 using a pre-determined port number for user identity 424. In another example, security gateway 150 should perform content substitution if application session 182 is a HTTP session and if a Universal Resource Locator (URL) in data packets 439 of application session 182 matches a pre-determined URL for user identity 424. In an example, security gateway 150 should perform filename substitution if application session 182 is a file transfer session and if a filename matching a pre-determined filename is found in data packets 439 of application session 182 for user identity 424. In another example, security gateway 150 should insert a cookie for user identity 424 if application session 182 is an HTTP session, with optionally data packets 439 matching a pre-determined POST or GET request of a URL.

Returning to FIG. 7, in some embodiments, document access policy 453 specifies if access to document 447 is

allowed or denied. In some embodiments, document **447** includes a file, a business agreement, a contract, a spreadsheet, a presentation, a drawing, a textual document, a manual, a program, a piece of software program, a design, a product specification, a datasheet, a video file, an audio file, an email, a voice mail, a fax, a photocopy of a document, or any business document. In some embodiments, document **447** includes an URL leading to digital information such as database query result, a web page, a video, or a piece of music. In some embodiments, document **447** includes real time transfer or streaming of information such as video streaming, audio streaming, a web cast, a podcast, a video show, a teleconference session, or a phone call. In some embodiments, document access policy **453** includes document identity **443** and document user identity **444**. Document identity **443** identifies document **447**. Document user identity **444** identifies the user whose access to the document **447** is affected by the document access policy **453**. In an embodiment, security gateway **150** compares user identity **424** with document user identity **444**. In response to determining that the user identity **424** matches the document user identity **444**, in some embodiments, security gateway **150** allows document **447** with document identity **443** to be accessed by user identity **424**. In another embodiment, security gateway **150** denies access to document **447** with document identity **443**. In denying access, the security gateway **150** may disconnect application session **182** or discard data packets **439**. In some embodiments, security gateway **150** confirms that data packets **439** include document identity **443**. In response to confirming that data packets **439** include document identity **443**, security gateway **150** applies document access policy **453**.

In some embodiments security policy **402** includes time **457** where security policy **402** is applicable within time **457**. In some embodiments, time **457** indicates a beginning time such as 8 am, 4 pm, midnight. In an embodiment, time **457** indicates a time range such as 8 am to 10 am, 7 pm to 5 am, morning hours, lunch, rush hour, prime time. Security gateway **150** compares clock **359** with time **457** and determines if security policy **402** is applicable.

In some embodiments, security gateway **150** generates security message **472** when security gateway **150** determines if security policy **402** is applicable to application session **182** for user identity **424**. In some embodiments, security gateway generates security message **472** when security gateway **150** applies security policy **402** to application session **182**. In some embodiments, security report **475** includes security message **472**. In one example, security message **472** includes security policy **402** and user identity **424**. In one example, security message **472** includes the actions security gateway **150** applies to application session **182** using security policy **402**.

The invention can take the form of an entirely hardware embodiment, an entirely software embodiment or an embodiment containing both hardware and software elements. In a preferred embodiment, the invention is implemented in software, which includes but is not limited to firmware, resident software, microcode, etc.

Furthermore, the invention can take the form of a computer program product accessible from a computer-usable or computer-readable medium providing program code for use by or in connection with a computer or any instruction execution system. For the purposes of this description, a computer-usable or computer readable medium can be any apparatus that can contain, store, communicate, propagate, or transport the program for use by or in connection with the instruction execution system, apparatus, or device.

The medium can be an electronic, magnetic, optical, electromagnetic, infrared, or semiconductor system (or apparatus or device) or a propagation medium. Examples of a computer-readable medium include a semiconductor or solid state memory, magnetic tape, a removable computer diskette, a random access memory (RAM), a read-only memory (ROM), a rigid magnetic disk and an optical disk. Current examples of optical disks include compact disk—read only memory (CD-ROM), compact disk—read/write (CD-R/W) and DVD.

A data processing system suitable for storing and/or executing program code will include at least one processor coupled directly or indirectly to memory elements through a system bus. The memory elements can include local memory employed during actual execution of the program code, bulk storage, and cache memories which provide temporary storage of at least some program code in order to reduce the number of times code must be retrieved from bulk storage during execution.

Input/output or I/O devices (including but not limited to keyboards, displays, point devices, etc.) can be coupled to the system either directly or through intervening I/O controllers.

Network adapters may also be coupled to the system to enable the data processing system to become coupled to other data processing systems or remote printers or storage devices through intervening private or public networks. Modems, cable modem and Ethernet cards are just a few of the currently available types of network adapters.

Foregoing described embodiments of the invention are provided as illustrations and descriptions. They are not intended to limit the invention to precise form described. In particular, it is contemplated that functional implementation of invention described herein may be implemented equivalently in hardware, software, firmware, and/or other available functional components or building blocks, and that networks may be wired, wireless, or a combination of wired and wireless. Other variations and embodiments are possible in light of above teachings, and it is thus intended that the scope of invention not be limited by this Detailed Description, but rather by the Claims following.

What is claimed is:

1. A method for applying a security policy to an application session, comprising:
 - recognizing the application session between a network and an application via a security gateway;
 - retrieving, by the security gateway, an application session record for the application session, the application session record comprising a first user identity used for accessing the application through a first host, a first host identity for the first host, and an application session time;
 - recognizing, by the security gateway, an access session between a second host and the network;
 - retrieving, by the security gateway, an access session record for the access session, the access session record comprising a second user identity used for accessing the network through the second host, a second host identity for the second host, and an access session time;
 - querying, by the security gateway, an identity server by sending the first host identity and the application session time in the application session record, the identity server comprising the access session record for the access session between the second host and the network;
 - comparing, by the identity server, the first host identity in the application session record with the second host identity in the access session record, and comparing the access session time with the application session time;

11

returning, by the identity server, the second user identity in the access session record if the first host identity in the application session record matches the second host identity in the access session record, and if the access session time matches the application session time; 5

storing, at the identity server, the second user identity as a network user identity used for accessing the network in the application session record;

determining, by the security gateway, at least one security policy applicable to the application session based on a group identity; and 10

applying the at least one security policy to the application session by the security gateway if the network user identity is a member of the group identity.

2. The method of claim 1, wherein the determining, by the security gateway, at least one security policy applicable to the application session further comprises determining that the at least one security policy is applicable for the time period. 15

3. The method of claim 1, wherein the at least one security policy comprises a network traffic policy.

4. The method of claim 3, wherein the network traffic policy comprises a bandwidth rate capacity for the network.

5. The method of claim 3, wherein the network traffic policy comprises a quality of service mapped to the network user identity for the application session.

6. The method of claim 3, wherein the network traffic policy comprises one or more of: a queuing delay, a queuing priority, a packet forwarding path, a link interface preference, a server load balancing preference, and a packet routing policy. 25

7. The method of claim 3, wherein the network traffic policy comprises a traffic shaping control.

8. The method of claim 7, wherein the traffic shaping control comprises a TCP profile.

9. The method of claim 3, wherein the network traffic policy comprises an application session modification control based on the network user identity. 35

10. A computer program product for applying a security policy to an application session, the computer program product comprising:

a non-transitory computer readable storage medium having computer readable program code embodied thereon, the computer readable program code configured to:

recognize the application session between a network and an application via a security gateway; 45

retrieve, by the security gateway, an application session record for the application session, the application session record comprising a first user identity used for accessing the application through a first host, a first host identity for the first host, and an application session time; 50

recognize, by the security gateway, an access session between a second host and the network;

retrieve, by the security gateway, an access session record for the access session, the access session record comprising a second user identity used for accessing the network through the second host, a second host identity for the second host, and an access session time; 55

query, by the security gateway, an identity server, by sending the first host identity and the application session time in the application session record, the identity server comprising the access session record for the access session between the second host and the network; 60

compare, by the identity server, the first host identity in the application session record with the second host

12

identity in the access session record, and compare the access session time with the application session time; return, by the identity server, the second user identity in the access session record if the first host identity in the application session record matches the second host identity in the access session record, and if the access session time matches the application session time; 5

store, at the identity server, the second user identity as a network user identity used for accessing the network in the application session record;

determine, by the security gateway, at least one security policy applicable to the application session based on a group identity; and

apply the at least one security policy to the application session by the security gateway, if the network user identity is a member of the group identity.

11. The computer program product of claim 10, wherein the computer readable program code configured to determine, by the security gateway, at least one security policy applicable to the application session is further configured to determine that the at least one security policy is applicable for the time period. 20

12. The computer program product of claim 10, wherein the at least one security policy comprises a network traffic policy.

13. The computer program product of claim 12, wherein the network traffic policy comprises a bandwidth rate capacity for the network.

14. The computer program product of claim 12, wherein the network traffic policy comprises a quality of service mapped to the network user identity for the application session. 25

15. The computer program product of claim 12, wherein the network traffic policy comprises one or more of: a queuing delay, a queuing priority, a packet forwarding path, a link interface preference, a server load balancing preference, and a packet routing policy.

16. The computer program product of claim 12, wherein the network traffic policy comprises a traffic shaping control.

17. The computer program product of claim 16, wherein the traffic shaping control comprises a TCP profile.

18. The computer program product of claim 12, wherein the network traffic policy comprises an application session modification control based on the network user identity.

19. A system, comprising:

a corporate directory comprising at least one security policy; and

a security gateway, wherein the security gateway:

recognizes an application session between a network and an application;

retrieves an application session record for the application session, the application session record comprising a first user identity used for accessing the application through a first host, a first host identity for the first host, and an application session time;

recognizes an access session between a second host and the network;

retrieves an access session record for the access session, the access session record comprising a second user identity used for accessing the network through the second host, a second host identity for the second host, and an access session time;

queries an identity server by sending the first host identity and the application session time in the application session record, the identity server comprising the

13

access session record for the access session between the second host and the network, wherein the identity server:

compares the first host identity in the application session record with the second host identity in the access session record, and compares the access session time with the application session time;

returns the second user identity in the access session record if the first host identity in the application session record matches the second host identity in the access session record, and if the access session time matches the application session time; and

stores the second user identity as a network user identity used for accessing the network in the application session record;

determines at least one security policy applicable to the application session based on a group identity; and

applies the at least one security policy to the application session if the network user identity is a member of the group identity.

20. The system of claim **19**, wherein the determines at least one security policy applicable to the application session fur-

14

ther comprises determines that the at least one security policy is applicable for the time period.

21. The system of claim **19**, wherein the at least one security policy comprises a network traffic policy.

22. The system of claim **21**, wherein the network traffic policy comprises a bandwidth rate capacity for the network.

23. The system of claim **21**, wherein the network traffic policy comprises a quality of service mapped to the network user identity for the application session.

24. The system of claim **21**, wherein the network traffic policy comprises one or more of: a queuing delay, a queuing priority, a packet forwarding path, a link interface preference, a server load balancing preference, and a packet routing policy.

25. The system of claim **21**, wherein the network traffic policy comprises a traffic shaping control.

26. The system of claim **25**, wherein the traffic shaping control comprises a TCP profile.

27. The system of claim **21**, wherein the network traffic policy comprises an application session modification control based on the network user identity.

* * * * *