

(12) **United States Patent**
Lee et al.

(10) **Patent No.:** **US 9,270,800 B2**
(45) **Date of Patent:** **Feb. 23, 2016**

(54) **SYSTEMS AND METHODS FOR PROVIDING ALTERNATE LINE SELECTION INFORMATION ON A MOBILE DEVICE**

(75) Inventors: **John Jong-Suk Lee**, Thornhill (CA); **Leon Vymenets**, Thornhill (CA); **Kevin Oerton**, Waterloo (CA); **Sherryl Lee Lorraine Scott**, Toronto (CA)

(73) Assignee: **BLACKBERRY LIMITED**, Waterloo, Ontario (CA)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 639 days.

(21) Appl. No.: **12/041,683**

(22) Filed: **Mar. 4, 2008**

(65) **Prior Publication Data**
US 2009/0227242 A1 Sep. 10, 2009

(51) **Int. Cl.**
H04B 1/38 (2015.01)
H04M 1/57 (2006.01)
H04M 1/2745 (2006.01)

(52) **U.S. Cl.**
CPC **H04M 1/57** (2013.01); **H04M 1/27455** (2013.01); **H04M 2250/66** (2013.01)

(58) **Field of Classification Search**
USPC 455/575.1, 566
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,367,558 A 11/1994 Gillig et al.
5,448,622 A 9/1995 Huttunen
5,526,403 A 6/1996 Tam
5,815,566 A 9/1998 Ramot et al.
5,940,488 A * 8/1999 DeGrazia et al. 379/93.23

5,984,178 A 11/1999 Gill et al.
6,016,336 A 1/2000 Hanson
6,154,660 A 11/2000 Singh
6,256,516 B1 7/2001 Wagner et al.
6,279,826 B1 8/2001 Gill et al.
6,285,364 B1 9/2001 Giordano et al.
6,289,025 B1 9/2001 Pang et al.
6,311,055 B1 10/2001 Boltz
6,366,302 B1 4/2002 Crosby et al.
6,515,997 B1 2/2003 Feltner et al.
6,574,470 B1 6/2003 Chow et al.

(Continued)

FOREIGN PATENT DOCUMENTS

CA 2624042 9/2008
CA 2624043 9/2008

(Continued)

OTHER PUBLICATIONS

TalkPlus "Multiple Numbers on a Mobile Phone Gives Business a New Edge" Retrieved from Internet: http://lunchat.typepad.com/my_weblog/2007/01/talkplus.html.


(Continued)

Primary Examiner — Charles Appiah
Assistant Examiner — Randy Peaches
(74) *Attorney, Agent, or Firm* — Perry + Currier, Inc.

(57) **ABSTRACT**

A system and method for providing a user interface that allows users to change the active line on which an outgoing call may be placed. In example embodiments, upon detecting call screen interaction a line selection menu is displayed. The line selection menu contains a plurality of line identifiers, each line identifier uniquely identifying a corresponding one of the multiple communication lines accessible at the mobile device. A system and method is also presented for providing a call log for identifying call activity associated with a plurality of communication lines.

20 Claims, 10 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

D479,531	S	9/2003	Yanagida	
6,757,372	B1	6/2004	Dunlap et al.	
6,768,975	B1	7/2004	Gill et al.	
6,865,625	B2	3/2005	Davani et al.	
6,998,976	B2	2/2006	Kawai et al.	
7,020,273	B2	3/2006	Kraft et al.	
7,036,048	B1	4/2006	Gill et al.	
7,046,994	B1	5/2006	Padawer et al.	
7,092,495	B2	8/2006	Kraft et al.	
7,123,901	B2	10/2006	Brown	
7,231,208	B2	6/2007	Robertson et al.	
7,231,229	B1	6/2007	Hawkins et al.	
7,336,260	B2	2/2008	Martin et al.	
7,561,682	B2	7/2009	Doherty et al.	
7,715,535	B2	5/2010	Vander Veen et al.	
7,860,489	B2	12/2010	Kuhl et al.	
8,478,345	B2 *	7/2013	Marui et al.	455/566
2002/0042288	A1	4/2002	Nakayama	
2002/0127999	A1	9/2002	Brown	
2002/0183091	A1	12/2002	Heo	
2003/0083050	A1	5/2003	Kraft et al.	
2003/0190025	A1	10/2003	Okamura et al.	
2004/0137967	A1	7/2004	Bodley	
2004/0215845	A1	10/2004	Davani et al.	
2005/0009571	A1	1/2005	Chiam et al.	
2005/0170854	A1	8/2005	Benco et al.	
2006/0084450	A1 *	4/2006	Dam Nielsen et al.	455/466
2006/0205432	A1	9/2006	Hawkins et al.	
2006/0234693	A1	10/2006	Isidore et al.	
2007/0047695	A1	3/2007	Tal et al.	
2007/0081641	A1	4/2007	Veen et al.	
2007/0123194	A1	5/2007	Karaoguz et al.	
2007/0129103	A1	6/2007	Al-Shaikh	
2007/0191060	A1	8/2007	Baek	
2007/0217132	A1	9/2007	Collins	
2007/0253380	A1	11/2007	Jollota et al.	
2008/0100693	A1	5/2008	Jobs et al.	
2008/0242277	A1	10/2008	Chen et al.	
2008/0242356	A1	10/2008	Marui et al.	
2010/0159901	A1	6/2010	Vandeer Veen et al.	
2010/0167710	A1 *	7/2010	Alhainen	455/416
2010/0297988	A1	11/2010	Kuhl et al.	

FOREIGN PATENT DOCUMENTS

CN	1819683	A	8/2006
CN	101277326		10/2008
EP	1289234		3/2003
EP	1628460		2/2006
EP	1758360	A2	2/2007
EP	1761096		3/2007
EP	1768360		3/2007
EP	1768360	A1 *	3/2007
EP	1976240	B1	10/2008
EP	1976241	A1	10/2008
EP	1976244		10/2008
EP	1976241		1/2011
WO	9417639		8/1994
WO	9417639	A1	8/1994
WO	9735413		9/1997
WO	9821871		5/1998
WO	9821871	A1	5/1998
WO	2006067541		6/2006

OTHER PUBLICATIONS

TalkPlus “BlackBerry Overview” Retrieved from Internet: <http://www.talkplus.com/blackberry/overview>.
 TalkPlus “With the TalkPlus Nokia Symbian application, you can:” Retrieved from Internet: <http://www.talkplus.com/nokia/overview>.
 TalkPlus “With the TalkPlus Windows Mobile Application, you can:” Retrieved from Internet: <http://www.talkplus.com/windowsmobile/overview>.

TalkPlus “With the TalkPlus Palm Application, you can:” Retrieved from Internet: <http://www.talkplus.com/palm/overview.html>.
 TalkPlus “Stay Connected . . . Stay in Control Simplify your life with TalkPlus on your phone” Retrieved from Internet: <http://www.talkplus.com/>.
 TalkPlus “TalkPlus BlackBerry Application Quick Start Guide” Retrieved from Internet: <http://www.talkplus.com/blackberry/quickstart.html>.
 TalkPlus “FAQ’s” Retrieved from Internet: <http://www.talkplus.com/blackberry/faq.html>.
 Wikipedia “Alternate line service” Retrieved from Internet: http://en.wikipedia.org/wiki/Alternate_line_service.
 Sprint Nextel “FAQs: Second Line Service” Retrieved from Internet: http://www.nextel.com/en/support/faq/alternate_line_serv.shtml.
 Palm.com “Alternate Line Service (ALS, or line 2)” Retrieved from Internet: [http://www.pals.com/us/support/guides/Treo650GSMTutorial/Alternate_line_Service_\(ALS,_or_Line_2\).htm](http://www.pals.com/us/support/guides/Treo650GSMTutorial/Alternate_line_Service_(ALS,_or_Line_2).htm).
 U.S. Appl. No. 11/691,172 “System and Method for Providing a User Interface That Facilitates User Selection of a Communication Line for an Outgoing Call on a Mobile Device”, filed Mar. 26, 2007.
 European Search and Examination Report. Application 08152234.4. Dated: Jun. 2, 2008.
 European Examination Report, (App. No. 08152234.4), dated Jun. 28, 2010.
 European Examination Report, (App. No. 09177240.0), dated Aug. 19, 2010.
 European Examination Report (Application No. 08152234.4) dated Nov. 4, 2008.
 Final Office Action. Co-pending U.S. Appl. No. 12/852,551. Dated: May 19, 2011.
 Office Action. Co-pending U.S. Appl. No. 11/691,172. Dated: Feb. 3, 2011.
 Chinese Office Action (and English Translation thereof). Related Chinese Patent Application No. 200910134634.5. Dated: May 25, 2011.
 Office Action. Co-pending U.S. Appl. No. 12/852,551. Dated: Dec. 29, 2010.
 Response, Co-pending U.S. Appl. No. 12/852,551. Dated: Mar. 29, 2011.
 Terminal Disclaimer & Extension of Time. Co-pending U.S. Appl. No. 12/852,551. Dated: Mar. 30, 2011.
 Chinese Office Action (and English Translation thereof). Related Chinese Patent Application No. 200910134635.X. Dated: Jun. 27, 2011.
 Office Action. Co-pending U.S. Appl. No. 11/691,187, Dated: Feb. 2, 2011.
 Response. Co-pending U.S. Appl. No. 11/691,187. Dated: May 2, 2011.
 Chinese First Office Action. Application No. 200810086781.5. Dated: Jul. 14, 2010.
 Notice of Allowance. co-pending U.S. Appl. No. 11/691,051. Dated: Oct. 12, 2010.
 Co-pending U.S. Appl. No. 12/852,551, “System and Method for Providing a User Interface for Managing Calls Received at a Mobile Device”, filed Aug. 9, 2010.
 Co-pending U.S. Appl. No. 12/718,070, “Method and Apparatus for Line Selection in a Communication Device”, filed Mar. 5, 2010.
 “Nextel Alternate Line Service FAQs” prior to Feb. 9, 2005.
 Final Office Action. Co-pending U.S. Appl. No. 11/691,187. Dated: Apr. 12, 2010.
 Amendment. Co-pending U.S. Appl. No. 11/691,187. Dated: Jun. 14, 2010.
 Request for continued Examination (RCE). Co-pending U.S. Appl. No. 11/691,187. Dated: Jun. 14, 2010.
 Notice of Allowance. Co-pending U.S. Appl. No. 11/691,051. Dated: Apr. 21, 2010.
 European Communication Under Rule 71(3) EPC. Application No. 07104939. Dated: Jun. 15, 2010.
 Co-pending U.S. Appl. No. 11/691,187, “System and Method for Providing Calling Feature Icons in a User Interface that Facilitates User Selection of a Communication Line for an Outgoing Call on a Mobile Device”, Filed Mar. 26, 2007.

(56)

References Cited

OTHER PUBLICATIONS

Amendment. Co-pending U.S. Appl. No. 11/691,187. Dated: Feb. 3, 2010.

United States Office Action. Co-pending U.S. Appl. No. 11/691,187. Dated: Nov. 6, 2009.

Co-pending U.S. Appl. No. 11/691,051, "System and Method for Providing a User Interface for Managing Calls Received at a Mobile Device", Filed Mar. 26, 2007.

Amendment. Co-pending U.S. Appl. No. 11/691,051. Dated: Jan. 21, 2010.

United States Office Action. Co-pending U.S. Appl. No. 11/691,051. Dated: Oct. 26, 2009.

Co-pending U.S. Appl. No. 11/235,509, "Method and Apparatus for Line Selection in a Communication Device", Filed Sep. 27, 2005.

Response to Rule 312 Communication. Co-pending U.S. Appl. No. 11/235,509. Dated: Dec. 30, 2009.

Amendment After Allowance. Co-pending U.S. Appl. No. 11/235,509. Dated: Dec. 21, 2009.

Notice of Allowance and Fee(s) Due. Co-pending U.S. Appl. No. 11/235,509. Dated: Dec. 7, 2009.

Amendment. co-pending U.S. Appl. No. 11/235,509. Dated: Sep. 1, 2009.

United States Office Action. Co-pending U.S. Appl. No. 11/235,509. Dated: Jun. 1, 2009.

European Search and Examination Report. Application No. 07104939 Dated: Sep. 7, 2007.

European Search and Examination Report. Related EP Application No. 08164378.5. Dated: Nov. 5, 2008.

European Search and Examination Report. Related EP Application No. 08164378.5. Dated: Aug. 6, 2010.

Notice of Allowance and Fee(s) Due. Co-pending U.S. Appl. No. 11/691,172. Dated: Jul. 28, 2011.

European Communication under Rule 71(3) EPC. Received on related European Application No. 08164378.5 dated Dec. 6, 2011.

Chinese Office Action, Chinese Patent Application No. 200910134634.5, dated Apr. 17, 2012. (English Translation Provided).

Office Action. Canadian Application No. 2,657,496, dated Jun. 6, 2012.

Office Action. Canadian Application No. 2,656,983, dated Jun. 6, 2012.

Chinese Office Action, Chinese Patent Application No. 2012062700680890, dated Jul. 2, 2012. (English Translation Provided).

European Examination Report. European Patent Application No. 10190059.5, dated Jul. 5, 2012.

3rd Chinese Office Action issued on Chinese Patent Application No. 200910134635.X, dated Nov. 22, 2012 (English Translation Provided).

Chinese "Rejection Decision", Chinese Patent Application No. 200910134634.5, dated Dec. 4, 2012 (English Translation Provided).

Document relating to European Application No. 08152234.4, dated Aug. 28, 2013 (Response to Rule 71(3) Communication).

Document relating to Canadian Application No. 2,656,983, dated Jul. 26, 2013 (2nd Office Action).

Document relating to Canadian Application No. 2,657,496, dated Aug. 5, 2013 (Notice of Allowance).

Document relating to European Application No. 08152234.4, dated Aug. 6, 2013 (Communication under Rule 71(3) EPC—Intent to Grant).

Document relating to U.S. Appl. No. 11/691,172, dated Nov. 9, 2009 (Office Action).

Document relating to U.S. Appl. No. 11/691,172, dated Feb. 9, 2010 (Office Action Response).

Document relating to U.S. Appl. No. 11/691,172, dated Apr. 15, 2010 (Office Action).

Document relating to U.S. Appl. No. 11/691,172, dated Jun. 14, 2010 (Office Action Response and RCE).

Document relating to U.S. Appl. No. 11/691,172, dated Feb. 3, 2011 (Office Action).

Document relating to U.S. Appl. No. 11/691,172, dated May 2, 2011 (Office Action Response).

Document relating to U.S. Appl. No. 11/691,172, dated Jul. 28, 2011 (Notice of Allowance).

Document relating to U.S. Appl. No. 11/691,172, dated Aug. 11, 2011 (RCE & IDS).

Document relating to U.S. Appl. No. 11/691,172, dated Sep. 21, 2011 (Notice of Allowance).

Document relating to U.S. Appl. No. 11/691,172, dated Nov. 3, 2011 (RCE & IDS).

Document relating to U.S. Appl. No. 11/691,172, dated Mar. 15, 2013 (Notice of Allowance).

Document relating to U.S. Appl. No. 11/691,172, dated Jun. 12, 2013 (Issue Notification).

Sony Ericsson Mobile Communications AB, "P900 User Guide" 2003, XP002479719.

Rejection Decision. Received on related Chinese Patent Application No. 200910134635.X. Dated: Mar. 29, 2013. (English Translation Provided).

Document relating to European Application No. 10190059.5, dated Nov. 15, 2013 (Second Examination Report).

Document relating to European Application No. 08152234.4, dated Sep. 19, 2013 (Supplemental Intent to Grant "Communication under Rule 71(3) EPC").

Document relating to Chinese Patent Application No. 200910134634.5 Dated: Nov. 27, 2014 (Reexamination Notification—Original and English Translation).

Document relating to Chinese Patent Application No. 200910134635.X. Dated: Nov. 28, 2014 (Reexamination Office Action—Original and English Translation).

Document relating to Canadian Application No. 2,656,983 dated Aug. 27, 2014 (Notice of Allowance).

Corresponding Indian Patent Application No. 421/DEL/2009 dated May 22, 2015.

Document relating to European Application No. 10190059.5, dated Jun. 3, 2014 (Communication under Rule 71(3) EPC—Intent to Grant).

Document relating to European Application No. 10190059.5, dated Feb. 27, 2014 (Response).

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6A




FIG. 6B




FIG. 6C




FIG. 6D




FIG. 7




FIG. 8A




FIG. 8B




FIG. 8C




FIG. 8D

1**SYSTEMS AND METHODS FOR PROVIDING
ALTERNATE LINE SELECTION
INFORMATION ON A MOBILE DEVICE**

TECHNICAL FIELD

Embodiments described herein relate generally to mobile device applications, and more specifically to phone-equipped mobile devices that allow outgoing calls to be made by a user on a communication line selected from a plurality of communication lines.

BACKGROUND

Many modern mobile devices are multi-functional. They may be configured to allow users to engage in both electronic mail (“e-mail”) communications and telephone communications, for example. Additionally, it is common for a user to utilize the mobile device for different purposes. For example, a user may operate a single mobile device to engage in communications relating to both business and personal uses.

Phone-equipped mobile devices may be adapted to accommodate an Alternate Line Service (ALS) or similar multi-line service. With respect to these mobile devices, two or more phone numbers may be associated with a mobile device, with each phone number being associated with a different communication line. A user may wish to place an outgoing call on a specific communication line so that when the call is received by a receiving party, the phone number associated with that communication line will be identified on the receiving party’s phone where “call display” (or “Caller ID”) functionality has been enabled on that phone. Use of multiple communication lines may also be useful for line-specific tracking purposes (e.g. to facilitate separate billing for calls relating to business and personal uses).

Typically, in mobile device applications, only one communication line is deemed to be “active” at any given time (although in some instances it is possible to have a call on multiple lines at once, as will be understood). Outgoing calls are placed on the active line until an alternate communication line is selected. Outgoing calls are generally initiated by a user from a call screen provided by an application (e.g. a phone application) residing and executing on the mobile device. A user may forget or not be aware that ALS functionality is available on the mobile device. Further, a user may wish to keep track of calling activity by corresponding communication line.

BRIEF DESCRIPTION OF THE DRAWINGS

For a better understanding of example embodiments described herein, and to show more clearly how they may be carried into effect, reference will now be made, by way of example, to the accompanying drawings in which:

FIG. 1 is a block diagram of a mobile device in one example implementation;

FIG. 2 is a block diagram of a communication subsystem component of the mobile device of FIG. 1;

FIG. 3 is a block diagram of a node of a wireless network;

FIG. 4 is a block diagram illustrating further aspects of the example mobile device of FIG. 1;

FIG. 5 is a flowchart illustrating steps of a method of providing a user interface that facilitates user selection of a communication line in accordance with at least one embodiment;

2

FIGS. 6A to 6D are examples of screenshots of a user interface provided to a user in accordance with an example implementation of one embodiment;

FIG. 7 is a flow chart illustrating steps of a method of displaying a call log on a mobile device in accordance with at least one embodiment; and

FIGS. 8A to 8D are examples of screenshots of a user interface provided to a user in accordance with an example implementation of another embodiment.

DETAILED DESCRIPTION

Embodiments described herein are generally directed to a system and method for providing ALS information to mobile device users and a user interface therefor.

In a broad aspect, there is provided a method of providing on a mobile device a dynamic user interface for identifying a plurality of communication lines on which outgoing calls may be made, the method comprising: displaying a call screen on a display of the mobile device; scanning for call screen interaction; and upon detecting call screen interaction, displaying on the display a line selection menu containing a plurality of line identifiers, each line identifier uniquely identifying a corresponding one of the communication lines.

These and other aspects and features of various embodiments will be described in greater detail below.

Some embodiments described herein make use of a mobile station. A mobile station is a two-way communication device with advanced data communication capabilities having the capability to communicate with other computer systems, and is also referred to herein generally as a mobile device. A mobile device may also include the capability for voice communications. Depending on the functionality provided by a mobile device, it may be referred to as a data messaging device, a two-way pager, a cellular telephone with data messaging capabilities, a wireless Internet appliance, or a data communication device (with or without telephony capabilities). A mobile device communicates with other devices through a network of transceiver stations.

To aid the reader in understanding the structure of a mobile device and how it communicates with other devices, reference is made to FIGS. 1 through 3.

Referring first to FIG. 1, a block diagram of a mobile device in one example implementation is shown generally as **100**. Mobile device **100** comprises a number of components, the controlling component being microprocessor **102**. Microprocessor **102** controls the overall operation of mobile device **100**. Communication functions, including data and voice communications, are performed through communication subsystem **104**. Communication subsystem **104** receives messages from and sends messages to a wireless network **200**. In this example implementation of mobile device **100**, communication subsystem **104** is configured in accordance with the Global System for Mobile Communication (GSM) and General Packet Radio Services (GPRS) standards. The GSM/GPRS wireless network is used worldwide and it is expected that these standards will be superseded eventually by Enhanced Data GSM Environment (EDGE) and Universal Mobile Telecommunications Service (UMTS). New standards are still being defined, but it is believed that they will have similarities to the network behaviour described herein, and it will also be understood by persons skilled in the art that the invention is intended to use any other suitable standards that are developed in the future. The wireless link connecting communication subsystem **104** with network **200** represents one or more different Radio Frequency (RF) channels, operating according to defined protocols specified for GSM/

GPRS communications. With newer network protocols, these channels are capable of supporting both circuit switched voice communications and packet switched data communications.

Although the wireless network associated with mobile device **100** is a GSM/GPRS wireless network in one example implementation of mobile device **100**, other wireless networks may also be associated with mobile device **100** in variant implementations. Alternatively, the network and device **100** might employ WiFi/WiMax radios utilizing SIP (session initialization protocols) and VoIP (voice over internet protocols). Different types of wireless networks that may be employed include, for example, data-centric wireless networks, voice-centric wireless networks, and dual-mode networks that can support both voice and data communications over the same physical base stations. Combined dual-mode networks include, but are not limited to, Code Division Multiple Access (CDMA) or CDMA2000 networks, GSM/GPRS networks (as mentioned above), and future third-generation (3G) networks like EDGE and UMTS. Some older examples of data-centric networks include the Mobitex™ Radio Network and the DataTAC™ Radio Network. Examples of older voice-centric data networks include Personal Communication Systems (PCS) networks like GSM and Time Division Multiple Access (TDMA) systems.

Microprocessor **102** also interacts with additional subsystems such as a Random Access Memory (RAM) **106**, flash memory **108**, display **110**, auxiliary input/output (I/O) subsystem **112**, serial port **114**, keyboard **116**, speaker **118**, microphone **120**, short-range communications **122** and other devices **124**.

Some of the subsystems of mobile device **100** perform communication-related functions, whereas other subsystems may provide “resident” or on-device functions. By way of example, display **110** and keyboard **116** may be used for both communication-related functions, such as entering a text message for transmission over network **200**, and device-resident functions such as a calculator or task list. Operating system software used by microprocessor **102** is typically stored in a persistent store such as flash memory **108**, which may alternatively be a read-only memory (ROM) or similar storage element (not shown). Those skilled in the art will appreciate that the operating system, specific device applications, or parts thereof, may be temporarily loaded into a volatile store such as RAM **106**.

Mobile device **100** may send and receive communication signals over network **200** after required network registration or activation procedures have been completed. Network access is associated with a subscriber or user of a mobile device **100**. To identify a subscriber, mobile device **100** requires a Subscriber Identity Module or “SIM” card **126** to be inserted in a SIM interface **128** in order to communicate with a network. SIM **126** is one type of a conventional “smart card” used to identify a subscriber of mobile device **100** and to personalize the mobile device **100**, among other things. Without SIM **126**, mobile device **100** is not fully operational for communication with network **200**. By inserting SIM **126** into SIM interface **128**, a subscriber can access all subscribed services. Services could include: web browsing and messaging such as e-mail, voice mail, Short Message Service (SMS), and Multimedia Messaging Services (MMS). More advanced services may include: point of sale, field service and sales force automation. SIM **126** includes a processor and memory for storing information. Once SIM **126** is inserted in SIM interface **128**, it is coupled to microprocessor **102**. In order to identify the subscriber, SIM **126** contains some user parameters such as an International Mobile Subscriber Identity

(IMSI). An advantage of using SIM **126** is that a subscriber is not necessarily bound by any single physical mobile device. SIM **126** may store additional subscriber information for a mobile device as well, including datebook (or calendar) information and recent call information.

Mobile device **100** is a battery-powered device and includes a battery interface **132** for receiving one or more rechargeable batteries **130**. Battery interface **132** is coupled to a regulator (not shown), which assists battery **130** in providing power V+ to mobile device **100**. Although current technology makes use of a battery, future technologies such as micro fuel cells may provide the power to mobile device **100**.

Microprocessor **102**, in addition to its operating system functions, enables execution of software applications on mobile device **100**. A set of applications that control basic device operations, including data and voice communication applications, will normally be installed on mobile device **100** during its manufacture. Another application that may be loaded onto mobile device **100** would be a personal information manager (PIM). A PIM has functionality to organize and manage data items of interest to a subscriber, such as, but not limited to, e-mail, calendar events, voice mails, appointments, and task items. A PIM application has the ability to send and receive data items via wireless network **200**. PIM data items may be seamlessly integrated, synchronized, and updated via wireless network **200** with the mobile device subscriber’s corresponding data items stored and/or associated with a host computer system. This functionality creates a mirrored host computer on mobile device **100** with respect to such items. This can be particularly advantageous where the host computer system is the mobile device subscriber’s office computer system.

Additional applications may also be loaded onto mobile device **100** through network **200**, auxiliary I/O subsystem **112**, serial port **114**, short-range communications subsystem **122**, or any other suitable subsystem **124**. This flexibility in application installation increases the functionality of mobile device **100** and may provide enhanced on-device functions, communication-related functions, or both. For example, secure communication applications may enable electronic commerce functions and other such financial transactions to be performed using mobile device **100**.

Serial port **114** enables a subscriber to set preferences through an external device or software application and extends the capabilities of mobile device **100** by providing for information or software downloads to mobile device **100** other than through a wireless communication network. The alternate download path may, for example, be used to load an encryption key onto mobile device **100** through a direct and thus reliable and trusted connection to provide secure device communication.

Short-range communications subsystem **122** provides for communication between mobile device **100** and different systems or devices, without the use of network **200**. For example, subsystem **122** may include an infrared device and associated circuits and components for short-range communication. Examples of short range communication would include standards developed by the Infrared Data Association (IrDA), Bluetooth, and the 802.11 family of standards developed by IEEE.

In use, a received signal such as a text message, an e-mail message, or web page download will be processed by communication subsystem **104** and input to microprocessor **102**. Microprocessor **102** will then process the received signal for output to display **110** or alternatively to auxiliary I/O subsystem **112**. A subscriber may also compose data items, such as e-mail messages, for example, using keyboard **116** in con-

junction with display 110 and possibly auxiliary I/O subsystem 112. Auxiliary subsystem 112 may include devices such as: a touch screen, mouse, track ball, infrared fingerprint detector, or a roller wheel with dynamic button pressing capability. Keyboard 116 is an alphanumeric keyboard and/or telephone-type keypad. A composed item may be transmitted over network 200 through communication subsystem 104.

For voice communications, the overall operation of mobile device 100 is substantially similar, except that the received signals would be output to speaker 118, and signals for transmission would be generated by microphone 120. Alternative voice or audio I/O subsystems, such as a voice message recording subsystem, may also be implemented on mobile device 100. Although voice or audio signal output is accomplished primarily through speaker 118, display 110 may also be used to provide additional information such as the identity of a calling party, duration of a voice call, or other voice call related information.

Referring now to FIG. 2, a block diagram of the communication subsystem component 104 of FIG. 1 is shown. Communication subsystem 104 comprises a receiver 150, a transmitter 152, one or more embedded or internal antenna elements 154, 156, Local Oscillators (LOs) 158, and a processing module such as a Digital Signal Processor (DSP) 160.

The particular design of communication subsystem 104 is dependent upon the network 200 in which mobile device 100 is intended to operate, thus it should be understood that the design illustrated in FIG. 2 serves only as one example. Signals received by antenna 154 through network 200 are input to receiver 150, which may perform such common receiver functions as signal amplification, frequency down conversion, filtering, channel selection, and analog-to-digital (A/D) conversion. A/D conversion of a received signal allows more complex communication functions such as demodulation and decoding to be performed in DSP 160. In a similar manner, signals to be transmitted are processed, including modulation and encoding, by DSP 160. These DSP-processed signals are input to transmitter 152 for digital-to-analog (D/A) conversion, frequency up conversion, filtering, amplification and transmission over network 200 via antenna 156. DSP 160 not only processes communication signals, but also provides for receiver and transmitter control. For example, the gains applied to communication signals in receiver 150 and transmitter 152 may be adaptively controlled through automatic gain control algorithms implemented in DSP 160.

The wireless link between mobile device 100 and a network 200 may contain one or more different channels, typically different RF channels, and associated protocols used between mobile device 100 and network 200. A RF channel is a limited resource that must be conserved, typically due to limits in overall bandwidth and limited battery power of mobile device 100.

When mobile device 100 is fully operational, transmitter 152 is typically keyed or turned on only when it is sending to network 200 and is otherwise turned off to conserve resources. Similarly, receiver 150 is periodically turned off to conserve power until it is needed to receive signals or information (if at all) during designated time periods.

Referring now to FIG. 3, a block diagram of a node of a wireless network is shown as 202. In practice, network 200 comprises one or more nodes 202. Mobile device 100 communicates with a node 202 within wireless network 200. In the example implementation of FIG. 3, node 202 is configured in accordance with General Packet Radio Service (GPRS) and Global Systems for Mobile (GSM) technologies. Node 202 includes a base station controller (BSC) 204 with an associated tower station 206, a Packet Control Unit (PCU)

208 added for GPRS support in GSM, a Mobile Switching Center (MSC) 210, a Home Location Register (HLR) 212, a Visitor Location Registry (VLR) 214, a Serving GPRS Support Node (SGSN) 216, a Gateway GPRS Support Node (GGSN) 218, and a Dynamic Host Configuration Protocol (DHCP) 220. This list of components is not meant to be an exhaustive list of the components of every node 202 within a GSM/GPRS network, but rather a list of components that are commonly used in communications through network 200.

In a GSM network, MSC 210 is coupled to BSC 204 and to a landline network, such as a Public Switched Telephone Network (PSTN) 222 to satisfy circuit switched requirements. The connection through PCU 208, SGSN 216 and GGSN 218 to the public or private network (Internet) 224 (also referred to herein generally as a shared network infrastructure) represents the data path for GPRS capable mobile devices. In a GSM network extended with GPRS capabilities, BSC 204 also contains a Packet Control Unit (PCU) 208 that connects to SGSN 216 to control segmentation, radio channel allocation and to satisfy packet switched requirements. To track mobile device location and availability for both circuit switched and packet switched management, HLR 212 is shared between MSC 210 and SGSN 216. Access to VLR 214 is controlled by MSC 210.

Station 206 is a fixed transceiver station. Station 206 and BSC 204 together form the fixed transceiver equipment. The fixed transceiver equipment provides wireless network coverage for a particular coverage area commonly referred to as a "cell". The fixed transceiver equipment transmits communication signals to and receives communication signals from mobile devices within its cell via station 206. The fixed transceiver equipment normally performs such functions as modulation and possibly encoding and/or encryption of signals to be transmitted to the mobile device in accordance with particular, usually predetermined, communication protocols and parameters, under control of its controller. The fixed transceiver equipment similarly demodulates and possibly decodes and decrypts, if necessary, any communication signals received from mobile device 100 within its cell. Communication protocols and parameters may vary between different nodes. For example, one node may employ a different modulation scheme and operate at different frequencies than other nodes.

For all mobile devices 100 registered with a specific network, permanent configuration data such as a user profile is stored in HLR 212. HLR 212 also contains location information for each registered mobile device and can be queried to determine the current location of a mobile device. MSC 210 is responsible for a group of location areas and stores the data of the mobile devices currently in its area of responsibility in VLR 214. Further VLR 214 also contains information on mobile devices that are visiting other networks. The information in VLR 214 includes part of the permanent mobile device data transmitted from HLR 212 to VLR 214 for faster access. By moving additional information from a remote HLR 212 node to VLR 214, the amount of traffic between these nodes can be reduced so that voice and data services can be provided with faster response times and at the same time requiring less use of computing resources.

SGSN 216 and GGSN 218 are elements added for GPRS support; namely packet switched data support, within GSM. SGSN 216 and MSC 210 have similar responsibilities within wireless network 200 by keeping track of the location of each mobile device 100. SGSN 216 also performs security functions and access control for data traffic on network 200. GGSN 218 provides internetworking connections with external packet switched networks and connects to one or more

SGSNs **216** via an Internet Protocol (IP) backbone network operated within the network **200**. During normal operations, a given mobile device **100** must perform a “GPRS Attach” to acquire an IP address and to access data services. This requirement is not present in circuit switched voice channels as Integrated Services Digital Network (ISDN) addresses are used for routing incoming and outgoing calls. Currently, all GPRS capable networks use private, dynamically assigned IP addresses, thus requiring a DHCP server **220** connected to the GGSN **218**. There are many mechanisms for dynamic IP assignment, including using a combination of a Remote Authentication Dial-In User Service (RADIUS) server and DHCP server. Once the GPRS Attach is complete, a logical connection is established from a mobile device **100**, through PCU **208**, and SGSN **216** to an Access Point Node (APN) within GGSN **218**. The APN represents a logical end of an IP tunnel that can either access direct Internet compatible services or private network connections. The APN also represents a security mechanism for network **200**, insofar as each mobile device **100** must be assigned to one or more APNs and mobile devices **100** cannot exchange data without first performing a GPRS Attach to an APN that it has been authorized to use. The APN may be considered to be similar to an Internet domain name such as “myconnection.wireless.com”.

Once the GPRS Attach is complete, a tunnel is created and all traffic is exchanged within standard IP packets using any protocol that can be supported in IP packets. This includes tunneling methods such as IP over IP as in the case with some IP Security (Ipsec) connections used with Virtual Private Networks (VPN). These tunnels are also referred to as Packet Data Protocol (PDP) Contexts and there are a limited number of these available in the network **200**. To maximize use of the PDP Contexts, network **200** will run an idle timer for each PDP Context to determine if there is a lack of activity. When a mobile device **100** is not using its PDP Context, the PDP Context can be de-allocated and the IP address returned to the IP address pool managed by DHCP server **220**.

Referring now to FIG. 4, a block diagram illustrating further aspects of mobile device **100** of FIG. 1 is shown generally as **300**. As noted earlier with reference to FIG. 1, microprocessor **102**, in addition to its operating system functions, enables execution of software applications on mobile device **100**. A set of applications that control basic device operations, including data and voice communication applications, will normally be installed on mobile device **100** during its manufacture. Operating system software and other software applications are typically stored in a persistent store (e.g. flash memory **108**) or other store, on mobile device **100** or on a device coupled thereto. It will be understood that the operating system, software applications or parts thereof, may be temporarily loaded in a volatile store such as RAM **106**. Other instructions and/or data received by the mobile device **100** and subject to processing may also be temporarily stored in RAM **106**.

Software applications that are loaded or stored on mobile device **100** may be implemented as functional components or modules **310**. Modules **310** interact with various components of mobile device **100**. For instance, as shown by way of example in FIG. 4, modules **310** may interact with communication subsystem **104**, RAM **106**, flash memory **108**, display **110**, auxiliary I/O device(s) **112**, and keyboard **116**. Modules **310** may comprise, for example, an address book module **312**, a messaging module **314** (e.g. for e-mail and/or SMS or MMS messaging), phone application module **316**, and a call log module **317**.

Address book module **312** is generally configured to allow contact information (e.g. individual contact and company

names, telephone numbers, messaging addresses, and other information) to be stored and managed. Messaging module **314** facilitates the sending and receiving of electronic messages over a wireless network **200** and/or other network.

Phone application module **316** is generally configured to facilitate voice communication between the user and other parties, including the placement of outgoing calls by the user and the reception of incoming calls on the mobile device **100**. Call log module **317** is generally configured to store and manage calling activity data (for example, time and date of incoming or outgoing calls, and third party phone numbers involved in such calls).

Calls may be placed and received on a communication line specifically configured for voice communications. In certain embodiments, calls may alternatively or additionally be placed and received on other types of communication lines, including a communication line generally configured for data communications, or a communication line configured for both voice and data communications, for example. For example, mobile device **100** may be configured to provide Voice over IP (VoIP), Enterprise Voice, and/or video phone functionality.

Embodiments described herein are generally applicable to mobile devices that provide access to multiple (i.e. two or more) communication lines on which outgoing calls may be placed, as initiated by a mobile device user. Typically, these mobile devices will also be configured to allow incoming calls to be received by the user over the same communication lines.

In example embodiments, each of the multiple communication lines has a different telephone number associated therewith. For example, a user may have a business phone number and a different personal phone number. When a user places an outgoing call on a specific communication line, the phone number associated with that communication line may be identified on a receiving party’s phone that is equipped with “call display” functionality.

Referring again to FIG. 4, a line selection module (e.g. alternate line service (ALS) module) **318** is provided to facilitate selection of the communication line to be used by phone application module **316** for placing an outgoing call, for example. The line selection module **318** is configured to select a communication line to be used by phone application module **316**, based upon line selection data stored on mobile device **100** (e.g. configuration settings that define a default communication line), and/or based upon input received by the user. It will be understood that the functionality of line selection module **318** may be provided or otherwise integrated with phone application module **316** or with a different module on mobile device **100**.

The currently selected communication line on which an outgoing call may be placed at any given time is also referred to herein as the “active” line. Outgoing calls will be placed on the active line by phone application module **316** until an alternate communication line is selected.

When a user wishes to initiate an outgoing call, the user will typically be required to access a call screen provided by an application (e.g. phone application module **316**) on mobile device **100**. Data identifying the active line will be displayed to the user in a first display field (e.g. “My Number” field, or phone status field) of the call screen, allowing the user to quickly identify the communication line on which an outgoing call will be placed should the user choose to initiate such call. This display field may also be referred to as an active line data display field. The data identifying the active line typically comprises a telephone number, but may alternatively or

additionally comprise some other communication line identifier(s), such as a line descriptor, alias and/or other identifier, for example.

Should the user wish to initiate an outgoing call to be placed on an alternate communication line, the user may need to change the current active line using a different application or in a separate screen, and then return to the call screen to place the call on the alternate communication line after the change is made.

Embodiments described herein are generally directed to systems and methods for providing on a mobile device a dynamic user interface for identifying a plurality of communication lines on which outgoing calls may be made.

In some embodiments, a mobile device is provided which is configured to provide a dynamic user interface for identifying a plurality of communication lines on which outgoing calls may be made. The mobile device may comprise a processor, a display, and at least one input device, and the processor may be configured to execute an application programmed to perform the steps of the method.

A call screen may be displayed on a display of the mobile device. The call screen may be provided with a first display field (e.g. "My Number" field or phone status field) in which a first line identifier identifying a first of the plurality of communication lines may be displayed. For example, for a communication line on which the user may place an outgoing call, the telephone number correlated to the corresponding communication line may be displayed as the corresponding line identifier. As a further example, one or more line descriptors, aliases and/or other identifiers may be displayed, in addition to or instead of the telephone number, as a line identifier. The device may scan or wait for interaction with the call screen. Upon detection of call screen interaction, the device may display on the display a line selection menu containing a plurality of line identifiers, each line identifier uniquely identifying a corresponding one of the communication lines.

The call screen interaction may comprise the movement of a selection element (e.g. a highlight bar, pointer, cursor, or other means to identify and select menu or list items) displayed on the call screen. The movement of the selection element into a first display field or into an outgoing call input field may be required for the line selection menu to be displayed. Alternatively, the call screen interaction may comprise input corresponding to the initiation of an outgoing call (e.g. the inputting of a telephone number). The input may also be provided by the user by depressing a navigation tool such as a mouse button, track ball, thumb wheel, touchpad, or a pre-programmed key, for example.

In some embodiments, a computer-readable medium is provided comprising instructions executable on a processor of the mobile device for implementing the method.

In another embodiment, a mobile device is provided which is configured to provide a dynamic user interface for identifying a plurality of communication lines on which outgoing calls may be made. The mobile device provides access to a plurality of communication lines on which outgoing calls may be made by a user, the mobile device comprising a processor, a display, and at least one input device, wherein the processor is configured to execute an application programmed to perform the steps of the method.

In yet another embodiment, a method of providing on a mobile device a call log for identifying call activity associated with a plurality of communication lines, is provided. The method comprises: displaying a call screen on a display of the mobile device and displaying call log data within a call log field on the display. The call log data includes at least one call

entry and each call entry includes: call data corresponding to a third party telephone number, and a line indicia. Further, each line indicia uniquely corresponds to one of the communication lines.

The call entry may comprise a call activity indicia, wherein each call activity indicia uniquely corresponds to a calling activity. The calling activity may include placing an outgoing call or receiving an incoming call.

In some aspects, the method may include selecting one from a plurality of call log categories, wherein each call log category corresponds to at least one communication line, and filtering the call entries for call entries corresponding to the selected call log category. One of the plurality of call log categories may correspond to all of the communication lines, collectively. At least one call entry corresponding to the selected call log category may be displayed.

In some aspects, the method may also include: grouping the call log entries by line indicia, and displaying the grouped call log entries. Furthermore, the groups of call log entries may be ranked. For certain embodiments, a communication line is selected and the group of call log entries having the line indicia corresponding to the selected communication line is displayed first.

A computer-readable medium may be provided which comprises instructions executable on a processor of the mobile device for implementing the method. Similarly, embodiments may be directed to a system for providing a user interface that facilitates user selection of a communication line for an outgoing call on a mobile device, the mobile device providing access to a plurality of communication lines on which outgoing calls may be made by a user, the mobile device comprising a processor, a display, and at least one input device, wherein the system is configured to execute an application programmed to perform the steps of the method.

In alternate embodiments, a mobile device has a call log for identifying call activity associated with a plurality of communication lines on the mobile device. The mobile device comprises a processor, a display, and at least one input device, wherein the mobile device is configured to access a plurality of communication lines, and wherein the processor is configured to execute an application programmed to perform the steps of: displaying a call screen on a display of the mobile device and displaying call log data within a call log field on the display. The call log data comprises at least one call entry and each call entry includes: call data corresponding to a third party telephone number, and a line indicia. In turn, each line indicia uniquely corresponds to one of the communication lines.

Referring now to FIG. 5, a flowchart illustrating steps of a method of providing on a mobile device a dynamic user interface for identifying a plurality of communication lines on which outgoing calls may be made, in accordance with at least one embodiment, is shown generally as 500. Additional details of some of the features described below in respect of the steps of method 500 may be described elsewhere in the present specification. Referring now also to FIGS. 6A to 6D, illustrated therein are screenshots of a user interface provided to a user in one example implementation of an embodiment of the method of FIG. 5 are shown.

In one embodiment, the steps of method 500 are performed at the mobile device by an application (e.g. phone application module 316 of FIG. 4) that typically executes and resides on the CPU of the mobile device (e.g. mobile device 100 of FIG. 1). The application need not be a stand-alone application, and the functionality described herein may be implemented in one or more applications executing and residing on the mobile device 100.

11

At Block 510 (shown in FIG. 5), a call screen (such as screen 600 illustrated in FIG. 6A) is displayed to the user on a display (e.g. display 110 of FIG. 1) of the mobile device 100. A user may access the call screen when the user wishes to initiate an outgoing call. This may require first activating a phone application or other application on the mobile device 100, by selecting a corresponding item or icon from a menu or home screen, for example (not shown). As noted previously, the mobile device 100 provides access to multiple communication lines on which outgoing calls may be placed.

In FIG. 6A, screenshot 600 illustrates a user interface displayed in a display 110 of a mobile device 100 (shown in FIG. 1), namely a call screen from which the user can place outgoing calls. Call screen 600 is displayed to the user, awaiting user input (e.g. a number to be dialed). A number entry field 602 is provided, and cursor 604 is settled within number entry field 602, indicating that the user may provide a call number (e.g. using a keyboard or keypad). General indicators may be displayed on call screen 600, including for example, time 606, date 608, network indicator 610, signal strength 612, battery strength 614, alarm indicator 618, service provider indicator 620, ringer indicator 622, and/or Bluetooth™ indicator 624.

A first line identifier 640 identifying a first of the multiple communication lines accessible at the mobile device 100 is displayed in a first display field 642 (“active line display field”) of the call screen 600. The first display field 642 may be referred to as a “My Number” field or a “phone status” field, and data 640 displayed therein identifies the active line, allowing the user to quickly identify the line on which an outgoing call will be placed should the user choose to initiate such a call.

The data 640 identifying the active line typically comprises a telephone number associated with the active line, but may alternatively or additionally comprise some other communication line identifier(s), such as, for example, one or more aliases, identifiers and/or other descriptors (e.g. “Mobile Line”, “Work Line”, “Alternate Line”), which may be user-defined. A line indicia or icon 644 uniquely corresponding to the active communication line may also be displayed in the first display field 642 of the call screen 600.

At Block 512 (shown in FIG. 5), the mobile device 100 scans or waits for call screen interaction by the user. As will be understood, such scanning or writing may be active or passive.

Subsequently, an input or other call screen interaction by the user may be detected. For example, such call screen interaction may involve the movement of a selection element (e.g. a highlight bar, pointer, cursor 604, or other means to identify and select menu or list items). The selection element may be re-positioned at the direction of the user, using an input device such as a thumb wheel, track ball, keyboard, mouse, touchpad or other input device. For example, the user may use a track ball on the mobile device 100, where provided, to manipulate a highlight bar shown in the call screen 600.

Alternatively, call screen interaction may be detected when a selection element (e.g. a highlight bar, pointer, cursor 604, or other means to identify and select menu or list items) displayed on the call screen 600 has been moved into the first display field 642. For example, by rotating the track ball, a highlight bar may be re-positioned to highlight the data 640 displayed in the first display field 642 (e.g. the telephone number associated with the active line) of the call screen 600. Alternatively, the detected call screen interaction may involve movement of a selection element into the outgoing call input or number entry field 602. Yet other call screen interaction

12

which may be detected may involve the inputting of a telephone number in the number entry field 602 by the user in order to initiate an outgoing call.

At Block 514 (shown in FIG. 5), upon detection of call screen interaction, as illustrated in FIG. 6C, a line selection menu 650 is displayed on the display. The line selection menu 650 comprises a plurality of line identifiers 640, each uniquely identifying a corresponding one of the communication lines on which the user may place or make an outgoing call (or receive an incoming call). Line identifiers 640 identifying at least a subset of the multiple communication lines accessible at the mobile device 100 are displayed on the line selection menu 650. In the example illustrated in FIG. 6C, the line selection menu 650 identifies all the communication lines available on the example embodiment of the mobile device 100.

In the example embodiment illustrated in FIG. 6C, the line identifier 640 corresponding to the currently active line appears first in the line selection menu 650.

It may be the case that the mobile device 100 provides access to multiple communication lines, but not all are activated for use, or the use of certain lines has been restricted in some manner (e.g. as configured by a security policy), or certain lines are otherwise unavailable, for example. In such embodiments, the line selection menu 650 may display only the line identifiers 640 corresponding to those communication lines that have been activated and on which the user is permitted to place an outgoing call.

In some embodiments, as an alternative to immediately displaying the line selection menu 650 upon detection of call screen interaction, at Block 513 (shown in FIG. 5), the call screen 600 might first prompt for a line changed instruction, e.g. by displaying a “Change Line” indicia 660 in the first display field 642 (as illustrated in FIG. 6B). In order for the line selection menu 650 to be displayed at Block 514 (shown in FIG. 5), the user may then input a “change line” command. For example, the user may depress the track wheel or track ball while the “Change Line” indicia 660 is displayed, to enter the “change line command” and cause the line selection menu 650 to be displayed.

At Block 516 (shown in FIG. 5), the user may select an alternate communication line. A selection element (e.g. a highlight bar, pointer, cursor, or other means to identify and select menu or list items) may be displayed within the line selection menu 650 and may be re-positioned at the direction of the user, using an input device such as a thumb wheel, track ball, keyboard, mouse, touch pad, touch screen or other input device. For example, the user may use a track ball on mobile device 100, where provided, to manipulate a highlight bar shown in the display 110. In particular, by rotating the track ball in this example, the highlight bar may be re-positioned to highlight the line identifier 640 associated with a particular communication line (e.g. the telephone number associated with one of the subset of the multiple communication lines) displayed in the line selection menu 650. Once the user highlights a desired communication line, by manipulating the track ball so that the highlight bar settles on the corresponding line identifier 640, the user may then take further action. For example, the user may depress the track ball to select the desired communication line.

At Block 518 (shown in FIG. 5), upon selection of a different communication line, the first display field 642 is updated with data 640 identifying the user-selected communication line. Accordingly, the user-selected communication line is identified to the user as the current active line. In the example illustrated in FIG. 6D, the “Alternate Line” has been

selected in Block **516** (shown in FIG. **5**), which has become the currently active line on which outgoing calls will be placed.

Referring now to FIG. **7**, a flowchart illustrating steps of a method of providing on a mobile device a call log for identifying call activity associated with a plurality of communication lines, in accordance with at least one embodiment, is shown generally as **700**. Additional details of some of the features described below in respect of the steps of method **700** may be described elsewhere in the present specification. Referring now also to FIGS. **8A** to **8D**, illustrated therein are screenshots of a user interface provided to a user in one example implementation of an embodiment of the method of FIG. **7** are shown.

In one embodiment, the steps of method **700** are performed at the mobile device by an application (e.g. call log module **317** of FIG. **4**) that typically executes and resides on the CPU of the mobile device (e.g. mobile device **100** of FIG. **1**). The application need not be a stand-alone application, and the functionality described herein may be implemented in one or more applications executing and residing on the mobile device.

At Block **710** (shown in FIG. **7**), a call screen (such as screen **800** illustrated in FIG. **8A**) is displayed to the user on a display (e.g. display **110** of FIG. **1**) of the mobile device **100**.

The call screen **800** provides a call log field **810** in which call log data **812** stored in memory (e.g. flash memory **108**) and associated with previously placed outgoing calls and received calls (e.g. including answered and missed calls) is displayed (at Block **712** shown in FIG. **7**). For each such call **814**, call data corresponding to: the associated date **816** of the call, a call activity indicia or icon **818** uniquely corresponding to the calling activity or nature of the call (e.g. placing an outgoing call, answering an incoming call, or missing an incoming call), and call information **820** (e.g. third telephone number and/or corresponding contact name to or from which the call has been made) is displayed. Each call entry **814** is also provided with a line indicia or icon **822** (similar to the line indicia **644**), each of which uniquely corresponds to one of the communication lines.

In some embodiments, at Block **714** (shown in FIG. **7**), the call log entries **814** are grouped according to line indicia **822** prior to being displayed in groups at Block **712**, as illustrated in FIG. **8A**. Further, in some embodiments, at Block **716** (shown in FIG. **7**) the grouped call log entries **814** may be ranked, prior to display at Block **712** (shown in FIG. **7**).

In some embodiments, at Block **718** (shown in FIG. **7**), a communication line may be selected (for example, as in accordance with method **500**, discussed above). Upon selection of a communication line, at Block **720** (shown in FIG. **7**), the group of call log entries **814** having a line indicia **822** corresponding to the selected communication line, is displayed first.

As can be seen in the example screen shot **800** of FIG. **8D**, the “Alternate Line” has been selected (for example, as per Block **516** of method **500** shown in FIG. **5**). As a result, in Block **720** (shown in FIG. **7**), the call log entries **814** having a line indicia **822** corresponding to the “Alternate Line” are displayed in a group, first before the other groups of call log entries **814**.

Furthermore, in some embodiments, as illustrated in FIG. **8A**, call log category selection buttons **830** are displayed in the call screen **800**. One call log category selection button **830** is provided for each call log category, and in turn, each call log category corresponds to at least one communication line. Thus in the illustrated example of FIG. **8A**, a call log category selection button **830** is provided for the “Work”, “Mobile”

and “Alternate” lines. In addition, one of the call log category selection buttons **830** corresponds to a call log category corresponding to “All” of the communication lines. In other embodiments, different call log categories may be established.

By “clicking” or otherwise selecting a call log category selection button **830**, at Block **722** (shown in FIG. **7**), a user may select a corresponding call log category. Once a call log category has been selected, in Block **724** (shown in FIG. **7**), the call log entries are filtered for those corresponding to the selected call log category, prior to display in Block **712** (shown in FIG. **7**). For example, if a “Mobile” call log category is selected, the call log entries would be filtered for those corresponding to the “Mobile” communication line, and only the “Mobile” call log entries would be displayed. In the example data of FIG. **8A**, the “All” call log category has been selected, and as a result, call log entries **814** corresponding to all of the communication lines are displayed.

It will be understood by persons skilled in the art that the features of the user interfaces illustrated with reference to the example screenshots described herein are provided by way of example only. It will be understood by persons skilled in the art that variations are possible in variant implementations and embodiments.

The steps of a method of providing a user interface that facilitates user selection of a communication line for an outgoing call on a mobile device in accordance with any of the embodiments described herein may be provided as executable software instructions stored on computer-readable media, which may include transmission-type media.

The invention has been described with regard to a number of embodiments. However, it will be understood by persons skilled in the art that other variants and modifications may be made without departing from the scope of the invention as defined in the claims appended hereto.

The invention claimed is:

1. A method of providing on a mobile device a call log for identifying call activity, the method comprising:
 - at the mobile device comprising a display, a communication subsystem, and a processor configured for voice communication on a plurality of communication lines via the communication subsystem, each of the plurality of communication lines associated with a unique telephone number,
 - displaying a call screen on the display;
 - displaying call log data within a call log field in the call screen;
 - wherein the call log data comprises a plurality of call log entries; and
 - wherein each call log entry comprises:
 - call data corresponding to a third party telephone number; and
 - a line icon that uniquely identifies one of the plurality of communication lines, wherein the one of the plurality of communication lines is the communication line on which voice communication to the third party telephone number was provided.
 2. The method of claim 1, wherein each call log entry comprises a call activity icon that uniquely identifies a calling activity.
 3. The method of claim 2, wherein the calling activity is selected from the group consisting of:
 - placing an outgoing call,
 - answering an incoming call, and
 - missing an incoming call.

15

4. The method of claim 1, further comprising:
 detecting selection of one of a plurality of call log categories, wherein each call log category corresponds to one of the plurality of communication lines; and
 in response to detecting the selection of one of the plurality of call log categories, filtering the plurality of call log entries to identify the call entries corresponding to the call log category that is selected.
5. The method of claim 4, further comprising displaying, within the call log field in the call screen, each call log entry corresponding to the call log category that is selected.
6. The method of claim 4, further comprising:
 detecting selection of a further call log category, wherein the further call log category corresponds to all of the communication lines;
 in response to detecting the selection of the further call log category:
 filtering the plurality of call log entries to identify the call entries corresponding to the further call log category; and,
 displaying, within the call log field in the call screen, all the call log entries.
7. The method of claim 1, further comprising:
 grouping the call log entries by line icon and,
 displaying, within the call log field in the call screen, the grouped call log entries.
8. The method of claim 7, further comprising:
 displaying, in the call screen, a plurality of buttons, each button associated with one of the plurality of communication lines; and
 in response to detecting selection of a respective one of the plurality of buttons, displaying, within the call log field in the call screen, the group of call log entries having the line icon corresponding to the selected communication line first.
9. The method as claimed in claim 1, wherein each of the plurality of communication lines is suitable for placing an outgoing telephone call.
10. A non-transitory computer-readable storage medium comprising instructions executable on a processor of the mobile device for implementing the method of claim 1.
11. A system for providing a call log for identifying call activity associated with a plurality of communication lines on a mobile device, the mobile device providing access to a plurality of communication lines suitable for making outgoing calls by a user, the mobile device comprising a processor, a display, and at least one input device, wherein the system is configured to execute an application programmed to perform the method as claimed in claim 1.
12. A mobile device comprising a processor, a display, and at least one input device, wherein the mobile device is configured to access a plurality of communication lines, and wherein the processor is configured to execute an application programmed to:
 displaying a call screen on the display of the mobile device;
 displaying call log data within a call log field in the call screen;
 wherein the call log data comprises a plurality of call log entries;

16

- wherein each call log entry comprises:
 call data corresponding to a third party telephone number and
 a line icon that uniquely identifies one of the plurality of communication lines, wherein the one of the plurality of communication lines is the communication line on which voice communication to the third party telephone number was provided.
13. The device of claim 12, wherein each of the plurality of communication lines is suitable for making outgoing telephone calls.
14. The device of claim 12, wherein each call log entry comprises a call activity icon that uniquely identifies a calling activity.
15. The device of claim 14, wherein the calling activity is selected from the group consisting of:
 placing an outgoing call,
 answering an incoming call, and
 missing an incoming call.
16. The device of claim 12, wherein the processor is further configured to:
 receive an input indicative of selection one of a plurality of call log categories, wherein each call log category corresponds to one of the plurality of communication lines; and
 in response to receipt of the input, filtering the plurality of call log entries to identify the call entries corresponding to the call log category that is selected.
17. The device of claim 16, wherein the processor is further configured to display, within the call log field in the call screen, each call log entry corresponding to the call log category that is selected.
18. The device of claim 16, wherein the processor is further configured to:
 receive a further input indicative of selection a further call log category, wherein the further call log category corresponds to all of the communication lines;
 in response to receipt of the further input:
 filter the plurality of call log entries to identify the call entries corresponding to the further call log category; and,
 display, within the call log field in the call screen, all the call log entries.
19. The device of claim 12, wherein the processor is further configured to:
 group the call log entries by line icon; and,
 display, within the call log field in the call screen, the grouped call log entries.
20. The device of claim 19, wherein the processor is further configured to:
 display, in the call screen, a plurality of buttons, each button associated with one of the plurality of communication lines; and
 in response to an input indicative of selection of a respective one of the plurality of buttons, displaying, within the call log field in the call screen, the group of call log entries having the line icon corresponding to the selected communication line first.

* * * * *