



US009271132B2

(12) **United States Patent**
Zhang et al.

(10) **Patent No.:** **US 9,271,132 B2**
(45) **Date of Patent:** **Feb. 23, 2016**

(54) **SERVICE PROCESSING METHOD, A
BASEBAND PROCESSOR CHIP AND A
TERMINAL**

(75) Inventors: **Zhi Zhang**, Shanghai (CN); **Jiwu Liu**,
Shanghai (CN); **Xianliang Chen**,
Shanghai (CN); **Xichun Gao**, Shanghai
(CN); **Yuan Xu**, Shanghai (CN); **Wenbo
Lu**, Shanghai (CN); **Ma Zhang**,
Shanghai (CN); **Yingping Hu**, Shanghai
(CN)

(73) Assignee: **Spreadtrum Communications
(Shanghai) Co., LTD**, Shanghai (CN)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 162 days.

(21) Appl. No.: **13/989,030**

(22) PCT Filed: **Aug. 12, 2011**

(86) PCT No.: **PCT/CN2011/078339**

§ 371 (c)(1),
(2), (4) Date: **Aug. 14, 2013**

(87) PCT Pub. No.: **WO2013/023341**

PCT Pub. Date: **Feb. 21, 2013**

(65) **Prior Publication Data**

US 2013/0315151 A1 Nov. 28, 2013

(51) **Int. Cl.**
H04W 4/00 (2009.01)
H04W 4/16 (2009.01)

(Continued)

(52) **U.S. Cl.**
CPC **H04W 4/16** (2013.01); **H04W 36/0022**
(2013.01); **H04W 8/183** (2013.01); **H04W 60/04**
(2013.01); **H04W 68/12** (2013.01)

(58) **Field of Classification Search**
CPC H04W 68/02; H04W 88/06; H04W 92/02;
H04W 92/10; H04W 28/22; H04W 24/00;
H04W 8/183; H04W 4/16
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,567,420 B1 * 5/2003 Tiedemann, Jr. H04W 28/22
370/230
7,085,228 B2 * 8/2006 Zaki H04L 1/0002
370/229

(Continued)

FOREIGN PATENT DOCUMENTS

CN 101500212 A 8/2009
CN 101690358 A 3/2010

(Continued)

OTHER PUBLICATIONS

Foreign Communication From a Related Counterpart Application,
PCT Application No. PCT/CN2011/078339, International Search
Report dated May 17, 2012.


(Continued)

Primary Examiner — Brian O'Connor

(57) **ABSTRACT**

A service processing method, a baseband processor chip and
a terminal are disclosed in embodiments of this invention,
wherein the service processing method comprises: in
response to a need for processing a CS domain service by a
terminal, identifying whether PS domain data that is being
received/transmitted in a PS domain service currently pro-
cessed by the terminal is critical data for maintaining the QoS
level of the PS domain service; in response to that the PS
domain data being received/transmitted is not critical data,
suspending the processing of the PS domain service and
processing the CS domain service. The embodiment of this
invention enables a terminal of Class B to process a CS
domain service during the process of receiving/transmitting
PS domain data.

31 Claims, 6 Drawing Sheets



(51) **Int. Cl.**
H04W 36/00 (2009.01)
H04W 8/18 (2009.01)
H04W 68/12 (2009.01)
H04W 60/04 (2009.01)

2011/0122809 A1 5/2011 Yun et al.
 2011/0122862 A1 5/2011 Yun et al.
 2012/0184242 A1* 7/2012 Li et al. 455/406
 2012/0218889 A1* 8/2012 Wafsa et al. 370/230
 2012/0327790 A1* 12/2012 Lee et al. 370/252

FOREIGN PATENT DOCUMENTS

(56) **References Cited**
 U.S. PATENT DOCUMENTS

GB 2419258 A 4/2006
 WO 2006137762 A1 12/2006
 WO 2010122029 A1 10/2010
 WO 2010128200 A1 11/2010

7,359,373 B2* 4/2008 Kuusinen et al. 370/352
 7,903,642 B2* 3/2011 Voutilainen et al. 370/354
 8,089,956 B2* 1/2012 Gu et al. 370/354
 8,243,725 B2* 8/2012 Aghili et al. 370/354
 8,271,025 B2* 9/2012 Brisebois et al. 455/552.1
 8,274,938 B2* 9/2012 Chang H04W 8/183
 370/329
 8,792,417 B2* 7/2014 Yeoum et al. 370/328
 2010/0317374 A1* 12/2010 Alpert et al. 455/458

OTHER PUBLICATIONS

Foreign Communication From a Related Counterpart Application,
 PCT Application No. PCT/CN2011/078339, Written Opinion dated
 May 17, 2012.

* cited by examiner




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6

1

**SERVICE PROCESSING METHOD, A
BASEBAND PROCESSOR CHIP AND A
TERMINAL**

CROSS-REFERENCE TO RELATED
APPLICATION

This application is the National Stage of, and therefore claims the benefit of, International Application No. PCT/CN2011/078339 filed on Aug. 12, 2011, entitled "A SERVICE PROCESSING METHOD, A BASEBAND PROCESSOR CHIP AND A TERMINAL," which was published in Chinese under International Publication Number WO 2013/023341 A1 on Feb. 21, 2013. The above application is commonly assigned with this National Stage application and is incorporated herein by reference in its entirety.

TECHNICAL FIELD

Embodiments of the present disclosure relate to communication techniques, and more particularly, to a service processing method, a baseband processor chip and a terminal.

BACKGROUND

In the 3rd Generation Partnership Project (3GPP) TS 22.060 specification, according to the types of services offered, General Packet Radio Service (GPRS) terminals are divided into Class A, Class B, and Class C, to distinguish their capabilities of handover between a GPRS data service and a Global System for Mobile Communication (GSM) voice service.

Wherein, a terminal of Class A can be attached to a GPRS network and a GSM network simultaneously, and supports the concurrent operation of a packet switched (PS) domain service and a GSM voice service. It is possible to browse a network and receive/send an email while a voice call is proceeding, that is, voice calling and data transmission can be performed simultaneously.

A terminal of class B can be attached to a GPRS network and a GSM network simultaneously, but it does not support the concurrent operation of a PS domain service and a GSM voice service, and can only operate one service at a certain time. Handover between a PS domain service and a GSM voice service can be realized through signaling. For example, PS domain data transmission is temporarily suspended when a call request is initiated by a terminal user, and is resumed after the completion of the call. However, in existing networks, a terminal of Class B is unable to receive a GSM service message, such as a voice call or a SMS message while receiving a PS domain data transmission.

A terminal of Class C only supports PS domain services but not GSM voice services. A terminal of Class C is primarily applied in a GPRS modem, and is not used for PS domain service requests.

The operation of a terminal of Class A needs a large amount of Central Processing Unit (CPU) bandwidth, which results in high cost and expensive price. Accordingly, terminals of Class A are uncommon on the current market. Terminals of Class C are not suitable for PS domain service requests, and thus most of the GPRS terminals available on the current market are terminals of Class B.

During the realization of this invention, the inventors have found that existing terminals of Class B have at least the following problems:

Because a terminal of Class B does not support the concurrent processing of a PS domain service and a Circuit

2

Switched (CS) domain service, when the terminal of Class B is engaged in a continuous reception/transmission of PS domain data during the process of a PS domain service, it is unable to process a CS domain service.

For example, when a terminal of Class B is continuously receiving PS domain data, if a calling user makes a call to a called user, the call request can not be admitted to the called terminal, and the called terminal does not present any prompt except to the called user while the calling terminal will receive a prompt that "the number you dialed is engaged", which may impacts the success admission rate of a GMS voice service consequently. In practice applications, even if the called user has turned on a missed call reminder service, because SMS and the voice service both belong to CS domain services, during the continuous reception of PS domain data by the called terminal, the missed call reminder platform is unable to send a SMS message notifying an incoming call to the called terminal, and until the called terminal has stopped receiving the PS domain data, the missed call reminder platform can send to the called terminal the SMS message, notifying the called user of the calling number, the calling time and other information of that call the SMS message. If the missed call reminder service is not turned on, the called user cannot be informed about the missed call at all, leading to serious impacts on user experience about the service.

SUMMARY

The technical problem to be addressed in embodiments of this invention is to provide a service processing method, a baseband processor chip and a terminal, enabling a terminal of Class B to process a CS domain service during the reception/transmission of PS domain data.

In order to address the above technique problems, a service processing method is provided, comprising:

- in response to that a terminal needs to process a CS domain service, identifying whether PS domain data that is being received/transmitted in a PS domain service currently processed on the terminal is critical data for maintaining the QoS level of the PS domain service;
- in response to that the PS domain data received/transmitted is not critical data, suspending the PS domain service and processing the CS domain service.

A baseband processor chip is provided in an embodiment of this invention, comprising:

- a first service processing unit for processing a CS domain service;
- a second service processing unit for processing a PS domain service;
- a monitor unit for monitoring whether the first service processing unit needs to process a CS domain service;
- an identification unit for, according to a monitor result of the monitor unit, in response to that the first service processing unit needs to process a CS domain service, identifying whether PS domain data that is being received/transmitted in a PS domain service currently processed by the second service processing unit is critical data for maintaining the QoS level of the PS domain service;
- a scheduling unit for, according to an identification result of the identification unit, in response to that the PS domain data received/transmitted is not critical data, instructing the second service processing unit to suspend the processing of the PS domain service and instructing a first service processing unit to process the CS domain service.

A mobile terminal is provided in an embodiment of this invention, comprising a RF chip and a baseband processor chip for, in response to a need for processing a CS domain service, identifying whether PS domain data that is being received/transmitted in a currently processed PS domain service is critical data for maintaining the QoS level of the PS domain service; and in response to that the PS domain data received/transmitted is not critical data, suspending the processing of the PS domain service and processing the CS domain service.

Based on the service processing method, the baseband processor chip and the terminal provided in the above embodiments of this invention, when a terminal requires to process a CS domain service, whether PS domain data being received/transmitted in a currently processed PS domain service is critical data for maintaining the QoS Level of the PS domain service is identified, if the PS domain data being received/transmitted is not critical data, the processing of the PS domain service is suspended and the CS domain service is processed. The problem of unable to process a CS domain service during the processing of a PS domain service on a terminal of Class B in the prior art can be solved. As compared to the prior art, the terminal of Class B is enabled to process a CS domain service during its reception/transmission of PS domain data, so that user experiment about the CS domain service and the QoS level of the CS domain service can be improved; in addition, because the PS domain data being received/transmitted is not critical data, suspending the processing of the current PS domain service will not cause the degradation in QoS level of the PS domain service, such as, a break of the PS domain service or a significant decrease in data transmission speed of PS domain data.

The technical solution of this invention will be further described below with reference to accompanying drawings and embodiments.

BRIEF DESCRIPTION

For a more explicit description of the technical solutions of embodiments of this invention or in the prior art, a brief introduction of accompanying drawings to be used in the description of these embodiments or the prior art will be given below. Obviously, accompanying drawings described below are merely some embodiments of this invention, for those skilled in the art, other accompanying drawings can be derived from these ones without any creative efforts.

FIG. 1 is a flowchart of a service processing method according to an embodiment of this invention;

FIG. 2 is a flowchart of a service processing method according to another embodiment of this invention;

FIG. 3 is a flowchart of a service processing method according to still another embodiment of this invention;

FIG. 4 is a flowchart of a service processing method according to still another embodiment of this invention;

FIG. 5 is a schematic structure diagram of a baseband processor chip according to an embodiment of this invention;

FIG. 6 is a schematic structure diagram of a terminal according to an embodiment of this invention.

DETAILED DESCRIPTION

A clear and complete description of technical solutions of embodiments of this invention will be given with reference to the accompanying drawings of the embodiments of this invention. Obviously, embodiments described herein are merely some embodiments of this invention, but not all of them. Based on those embodiments of this invention, other

embodiments can occur to those skilled in the art without any creative efforts, all of which fall within the scope of this invention.

FIG. 1 is a flowchart of a service processing method according to an embodiment of this invention. As shown in FIG. 1, the service processing method of this embodiment comprises the following steps:

101. In response to that a terminal needs to process a CS domain service, identifying whether PS domain data that is being received/transmitted in a PS domain service currently processed by the terminal is critical data for maintaining a QoS level of the PS domain service.

In various embodiments of this invention, the CS domain service may be any CS domain service in various existing communication networks, for example, a CS domain service in a GSM network, including but not limited to, a calling service, such as a voice calling and video calling service, a short message service, and a multimedia service, etc.

The PS domain service herein may be a download or upload service on a mobile communication network, including the reception/transmission of PS domain data, such as instant messaging, webpage browse, multimedia message sending and download, etc. The critical data is used to maintain the QoS level of the PS domain service, for example data for continuing the PS domain service or keeping the PS domain data transmission rate thereof, wherein the PS domain service can not be continued or the data transmission rate may have a significant decrease if the critical data is lost. In a particular application, the critical data may be data specified in a communication protocol, or user-specified data, for example uplink polling data transmitted by a GSM terminal, particular signaling involved in a PS domain service specified in a communication protocol or by a user.

In response to that the PS domain data being received/transmitted is not critical data, suspend the processing of the PS domain service and processing the CS domain service.

In the service processing method provided in the above embodiment, when a terminal requires to process a CS domain service, whether PS domain data that is being received/transmitted in a PS domain service currently processed is critical data for maintaining the QoS level of the PS domain service is identified, if the PS domain data that is being received/transmitted is not critical data, the processing of the PS domain service is suspended and the CS domain service is processed, thereby enabling a terminal of Class B to process the CS domain service during the reception/transmission of the PS domain data, so that service quality and user experiment about the CS domain service can be improved; in addition, because the PS domain data that is being received/transmitted is not critical data, suspending the processing of the current PS domain service will not cause the degradation in QoS level of the PS domain service, such as, a break of the PS domain service or a significant decrease in data transmission speed thereof, so that the service quality of the PS domain service can be effectively guaranteed.

Furthermore, as another particular embodiment of this invention, with the embodiment shown in FIG. 1, after the processing of the CS domain service, the processing of the PS domain service can be resumed to avoid a break in the data service or data loss, and thus to achieve the continuousness of the PS domain service.

Further, as another particular embodiment of this invention, the reception/transmission of critical data is prior to the processing of the CS domain service. Then, in the embodiment of the invention shown in FIG. 1, if the PS domain data that is being received/transmitted is critical data, the processing of the PS domain service is continued to receive/transmit

5

the PS domain data, and no CS domain service is processed during the reception/transmission of critical data.

The CS domain service in this embodiment of the invention includes, but not limited to, a CS domain paging message, a broadcast message, a location area update, etc. Correspondingly, the need for processing the CS domain service by the terminal may particularly comprise: a need for receiving a CS domain service message by the terminal, such as a CS domain paging message, a broadcast message, or a need for processing a specific CS domain service, for example, a service such as location area updating. Processing the CS domain service may correspondingly comprise: receiving and processing a CS domain paging message, receiving and processing a broadcast message, performing location area update for a user card of the terminal and etc. According to a particular embodiment of this invention, the criteria of requiring a CS domain paging message to be received may comprise: reaching a paging message receiving time specified by a paging period, or a paging indicator indicates the requirement of receiving a paging message. According to this embodiment, the terminal is believed to receive and process a CS domain paging message when it is the time to receive a paging message as specified by a paging period, or when it is required to receive a paging message as indicated by a paging indicator.

For example, in GSM, a terminal requires to receive a paging message on a paging indicator channel (PICH) at a time for paging message reception specified by a paging period, when the terminal in the embodiment of this invention is a GSM terminal, a CS domain paging message is required to be received and processed when it is the time to receive a paging message as specified by a paging period.

FIG. 2 is a flowchart of a service processing method according to another embodiment of this invention. In this embodiment, a description will be given, in which the CS domain service is a CS domain paging message as an example. As shown in FIG. 2, the service processing method of this embodiment comprises the following steps:

In response to that a terminal needs to receive and process a CS domain paging message, identify whether PS domain data that is being received/transmitted in a PS domain service currently processed by the terminal is critical data for maintaining a QoS level of the PS domain service. If the PS domain data that is being received/transmitted is not critical data, step 202 is executed; otherwise, if the PS domain data that is being received/transmitted is critical data, the processing of the PS domain service is continued.

Suspend the PS domain service and receive the CS domain paging message.

According to information within the CS domain paging message, identify whether a broadcast message is required to be received, or a CS domain communication service is required to be processed. If a broadcast message is required to be received, step 204 is executed. If a CS domain communication service is required to be processed, step 205 is executed. Otherwise, if it is not required to receive a broadcast message or to process a CS domain communication service, step 206 is executed.

Receive and process the broadcast message. Step 206 is executed after the receiving and processing of the broadcast message is completed.

Particularly, as still another particular embodiment of this invention, the operation of step 204 may comprise: receiving a broadcast message, and identifying whether the location area the terminal is located in has changed according to information within the broadcast message; if the location area the terminal is located in has changed, performing location area

6

update for a user card of the terminal. Step 206 is executed after the location area update is completed.

During the processing of the PS domain service, the processing of the PS domain service can be suspended, and a CS domain paging message or a broadcast message can be received, based on which a location area update can be performed for a user card of the terminal, to keep synchronization between the user card and the mobile communication network, so that dropped network connection can be prevented for the user card, and the success rate of a subsequent communication service can be effectively guaranteed.

Process the CS domain communication service, for example, a call request service, a short message service, a multimedia message service. Step 206 is executed after the CS domain communication service is completed.

During the processing of the PS domain service, a CS domain paging message can be received and a CS domain communication service can be processed, to support the processing of the CS domain service during the processing of the PS domain service. On the premise that the QoS level of the PS domain service can be effectively guaranteed, the normal processing of the CS domain service can be guaranteed also, so that the QoS and the success rate of the CS domain service can be improved.

Resume the processing of the PS domain service.

The processing of the PS domain service can be resumed after the processing of the CS domain paging message is completed to avoid a break in the PS domain service or PS domain data loss, and achieve the continuousness of the PS domain service.

FIG. 3 is a flowchart of a service processing method according to still another embodiment of this invention. In this embodiment, a description will be given, in which the CS domain service is a broadcast message as an example. As shown in FIG. 3, the service processing method of this embodiment comprises the following steps:

In response to a current time for receiving a broadcast message according to a time interval specified in a communication protocol, identify whether PS domain data that is being received/transmitted in a PS domain service currently processed by the terminal is critical data for maintaining the QoS level of the PS domain service. If the PS domain data that is being received/transmitted is not critical data, step 302 is executed; otherwise, if the PS domain data that is being received/transmitted is critical data, the processing of the PS domain service is continued.

Suspend the processing of the PS domain service, and receiving a broadcast message.

According to information within the broadcast message, identify whether the location area the terminal is located in has changed, if the location area the terminal is located in has changed, step 304 is executed; otherwise, if the location area the terminal is located in has not changed, step 305 is executed.

Perform location area update for a user card of the terminal. After the location area update is completed for the user card of the terminal, step 305 is executed.

During the processing of the PS domain service, a broadcast message can be received, and location area update can be performed for the user card of the terminal accordingly, to keep synchronization between the user card and the mobile communication network, so that dropped network connection can be prevented for the user card, and the success rate of a

subsequent communication service can be effectively guaranteed.

Resume the PS domain service.

The processing of the PS domain service can be resumed after the broadcast message is received and processed to avoid a break in the PS domain service or PS domain data loss, and achieve the continuousness of the PS domain service.

FIG. 4 is a flowchart of a service processing method according to still another embodiment of this invention. In this embodiment, a description will be given, in which the CS domain service is location area update as an example. As shown in FIG. 4, the service processing method of this embodiment comprises the following steps.

In response to a current time for performing location area update according to a time interval specified by a communication protocol, identify whether PS domain data that is being received/transmitted in a PS domain service currently processed by the terminal is critical data for maintaining the QoS level of the PS domain service. If the PS domain data that is being received/transmitted is not critical data, step 402 is executed; otherwise, if the PS domain data that is being received/transmitted is critical data, the processing of the PS domain service is continued.

Suspend the PS domain service, and perform location area update for a user card of the terminal, after which step 403 is executed.

During the processing of the PS domain service, location area update can be performed for the user card of the terminal, to keep synchronization between the user card and the mobile communication network, so that dropped network connection can be prevented for the user card, and the success rate of a subsequent communication service can be effectively guaranteed.

Resume the PS domain service.

The processing of the PS domain service can be resumed after the location area update is completed for the user card of the terminal, to avoid a break in the PS domain service or PS domain data loss, and achieve the continuousness of the PS domain service.

FIG. 5 is a schematic structure diagram of a baseband processor chip according to an embodiment of this invention. The baseband processor chip of this embodiment can be used to realize the corresponding flow of a service processing method according to the various embodiments above of this invention. As shown in FIG. 5, it comprises a first service processing unit 501, a second service processing unit 502, a monitor unit 503, an identification unit 504, and a scheduling unit 505.

Wherein, the first service processing unit 501 is used to process a CS domain service.

The second service processing unit 502 is used to process a PS domain service.

The monitor unit 503 is used to monitor whether a CS domain service is required to be processed by the first service processing unit 501, for example, a CS domain paging message, a broadcast message, a location area update, etc.

The identification unit 504 is used to according to the monitor result of the monitor unit 503, in response to that the first service processing unit 501 needs to process a CS domain service, identify whether PS domain data being received/transmitted in the PS domain service that is currently processed by the second service processing unit 502 is critical data for maintaining the QoS level of the PS domain service.

According to a specific embodiment of this invention, the PS domain service may be a download or upload service on a mobile communication network, including a process of

receiving/transmitting PS domain data, such as instant messaging, webpage browsing, multimedia message transmission and download, etc.

Wherein, critical data is used to maintain the QoS level of the PS domain service, for example data for continuing the PS domain service or keeping the PS domain data transmission rate thereof, wherein the PS domain service cannot be continued or the data transmission rate may have a significant decrease if the critical data is lost. In a particular application, the critical data may be data specified in a communication protocol, or user-specified data.

The scheduling unit 505 is used to, according to the result of the identification unit 504, in response to that the PS domain data being received/transmitted by the second service processing unit 502 is not critical data, instruct the second service processing unit 502 to suspend the processing of the PS domain service, and instruct the first service processing unit 501 to process the CS domain service.

When a CS domain service is required to be processed, the baseband processor chip of the above embodiment of the invention may identify whether PS domain data that is being received/transmitted in a currently processed PS domain service is critical data for maintaining the QoS level of the PS domain service, if the PS domain data that is being received/transmitted is not critical data, the processing of the PS domain service is suspended and the CS domain service is processed, to enable a terminal of Class B to process the CS domain service during the reception/transmission of the PS domain data, so that service quality and user experiment about the CS domain service can be improved; in addition, because the PS domain data that is being received/transmitted is not critical data, suspending the processing of the current PS domain service can not cause the degradation in quality of the PS domain service, such as, the break in the PS domain service or a significant decrease in data transmission speed thereof, so that the service quality of the PS domain service can be effectively guaranteed.

Corresponding to the above embodiment of a service processing method of this invention, according to another particular embodiment of this invention, the scheduling unit 505 is further used to, after the CS domain service has been processed by the first service processing unit 501, instruct the second service processing unit 502 to resume the processing of the PS domain service to avoid a break in the PS domain service or PS domain data loss, and thus to achieve the continuousness of the PS domain service.

Further, according to still another particular embodiment of this invention, receiving/transmitting critical data by the second service processing unit 502 is prior to processing the CS domain service by the first service processing unit 501, that is, the first service processing unit 501 does not process a CS domain service during the process of receiving/transmitting critical data by the second service processing unit 502.

In the baseband processor chip in the above embodiment of this invention, the CS domain service comprises, but not limited to, a CS domain paging message, a broadcast message, location area update etc. Correspondingly, a need for processing a CS domain service by the first service processing unit 501 may particularly comprise: a need for receiving a CS domain service message by the first service processing unit 501, such as, a CS domain paging message, a broadcast message, or a need for processing a specific CS domain service, for example, location area update and other services. Processing a CS domain service by the first service processing unit 501 may correspondingly comprise: by the first service processing unit 501, receiving and processing a CS domain paging message, receiving and processing a broad-

cast message, performing location area update for a user card of the terminal and the like. When the CS domain service required to be processed is a CS domain paging message, it is believed that the first service processing unit **501** is required to receive and process a CS domain paging message when it is the time to receive a paging message as specified by a paging period, or when a paging indicator indicates that it is required to receive a paging message.

Correspondingly, when the first service processing unit **501** receives and processes a CS domain paging message, it can particularly identify, according to information within the CS domain paging message, whether it is required to receive a broadcast message or to process a CS domain communication service; in response to a need for receiving a broadcast message, the broadcast message is received and processed; in response to a need for processing a CS domain communication service, for example, a call request service, a short message service, a multimedia message service, the CS domain communication service is processed.

Optionally, receiving and processing a broadcast message by the first service processing unit **501** may particularly comprise: receiving a broadcast message, and identifying whether the location area the terminal is located in has changed according to information within the broadcast message; in response to a change of the location area the terminal is located in, performing location area update for a user card of the terminal.

During the processing of the PS domain service by the second service processing unit **502**, the first service processing unit **501** may receive a CS domain paging message or a broadcast message, and perform location area update for the user card of the terminal accordingly, to keep synchronization between the user card and the mobile communication network, so that dropped network connection can be prevented for the user card, and the success rate of a subsequent communication service can be effectively guaranteed.

Further, in the baseband processor chip according to the above embodiment of this invention, a need for processing a CS domain service by the first service processing unit **501** may further comprise a time that is coming for receiving a broadcast message or performing location area update according to a time interval specified in a communication protocol. Correspondingly, processing a CS domain service by the first service processing unit **501** comprises: receiving and processing the broadcast message, or performing location area update for the user card of the terminal.

FIG. 6 is a schematic structure diagram of a terminal according to an embodiment of this invention. The terminal provided in this embodiment may be a terminal of Class B, which employs a single RF single baseband scheme to achieve the flows of the service processing methods according to the various above embodiments of this invention. As shown in FIG. 6, it comprises a RF chip **1** and a baseband processor chip **2**.

Wherein, the RF chip **1** is used to realize the reception and transmission of data or a message between the baseband processor chip **2** and a communication network, for example, to forward PS domain data between a General Packet Radio Service (GPRS) network and the second service processing unit **502** of the baseband processor chip **2**, to forward a CS domain service message, CS domain service data etc between a GSM network and the first service processing unit **501** of the baseband processor chip **2**.

The baseband processor chip **2** is used to in response to a need for processing a CS domain service, identify PS domain data that is being received/transmitted in a currently processed PS domain service is critical data for maintaining the

QoS level of the PS domain service, and in response to the PS domain data being received/transmitted is not critical data, suspend the processing of the PS domain service and process the CS domain service.

Wherein, the baseband processor chip **2** may particularly comprise the baseband processor chip provided in any embodiment shown in FIG. 5, and is realized with the structure of the embodiment shown in FIG. 5 of this invention.

With the terminal provided in the above embodiment of this invention, when a CS domain service is required to be processed, the baseband processor chip **2** can identify whether PS domain data that is being received/transmitted in a currently processed PS domain service is critical data, if the PS domain data that is being received/transmitted is not critical data, the processing of the PS domain service is suspended and the CS domain service is processed. As a terminal of Class B, it is enabled to process the CS domain service during the reception/transmission of the PS domain data, so that service quality and user experiment about the CS domain service can be improved; in addition, because the PS domain data that is being received/transmitted is not critical data, suspending the processing of the current PS domain service will not cause the degradation in QoS level of the PS domain service, such as, a break in the PS domain service or a significant decrease in data transmission speed thereof, so that the service quality of the PS domain service can be effectively guaranteed.

Those skilled in the art may understand that embodiments of this invention may not be necessarily implemented by or limited to the component units of the baseband processor chip and the terminal in various above embodiments of this invention, for example, the terminal may be further provided with user card slots, a display, a keyboard, an antenna or other peripheral devices according to actual requirements. In addition, the component units of the baseband processor chip may be further distributed into other component units of the terminal according to actual requirements. Among the component units of the baseband processor chip, several component units can be combined into a single unit, or a component unit can be divided into several subunits. In addition, the connection relationships between various component units of the baseband processor chip, and the connection relationships between the component units of the baseband processor chip and other component units of the terminal merely represent exemplary information flow directions, but not physical connection relationships, and are not necessarily required or limitations for the implementation of the embodiments.

Various embodiments of this invention have been described in a progressive manner, wherein each embodiment has been emphasized in view of differences from other embodiments. A mutual reference can be made to various embodiments for the same or similar portions thereof. With respect to the baseband processor chip and the terminal embodiments, due to the correspondence to the method embodiments thereof, only a simple description is given, refer to those method embodiments for related portions.

Those skilled in the art may appreciate: some or all steps of the above method embodiments can be realized by program instructions related hardware, the program aforementioned can be stored in a computer readable storage medium, the program, when executed, may execute steps of the above method embodiments; the storage medium aforementioned includes ROM, RAM, magnetic disc or optical disc and other mediums capable of storing program code.

The embodiments of this invention enable a terminal of Class B to process a CS domain service during the process of receiving/transmitting PS domain data, so that service quality

11

and user experiment of the CS domain service can be improved; in addition, because the PS domain data that is being received/transmitted is not critical data, suspending the processing of the current PS domain service will not cause the degradation in QoS level of the PS domain service, such as, the break of the PS domain service or a significant decrease in data transmission speed thereof, so that the service quality of the PS domain service can be effectively guaranteed.

The descriptions of the present invention have been presented for purposes of description and illustration, but are not intended to be exhaustive or limited to the embodiments disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art. The embodiment was chosen and described in order to best explain the principles of the invention and the practical application, and to enable those of ordinary skill in the art to understand the invention for various embodiments with various modifications as are suited to the particular use contemplated.

What is claimed is:

1. A service processing method, characterized by comprising:

in response to a need for processing a Circuit Switched (CS) domain service by a terminal, identifying whether Packet Switched (PS) domain data that is received/transmitted in a PS domain service being currently processed by the terminal is critical data for maintaining the QoS level of the PS domain service, wherein the critical data is data for keeping the PS domain service continuous and/or keeping the PS domain data transmission rate from a significant decrease;

in response to that the PS domain data being received/transmitted is not critical data suspending the processing of the PS domain service and processing the CS domain service.

2. The method according to claim **1**, characterized in that the processing of the PS domain service is resumed after the processing of the CS domain service.

3. The method according to claim **1**, characterized in that the reception/transmission of the critical data is prior to the processing of the CS domain service.

4. The method according to claim **1**, characterized in that the critical data is data specified by a communication protocol or user specified data.

5. The method according to claim **1**, characterized in that processing the CS domain service comprises:

receiving and processing a CS domain paging message; a need for processing a CS domain service comprises a time for receiving a paging message as specified by a paging period arriving, or a paging indicator indicating it is required to receive a paging message.

6. The method according to claim **1**, characterized in that, a need for processing a CS domain service comprises: a time for receiving a broadcast message or a time for performing location area update according to a time interval specified in a communication protocol arriving; processing the CS domain service correspondingly comprises: receiving and processing the broadcast message, or performing location area update for the user card of the terminal.

7. The method according to claim **2**, characterized in that processing the CS domain service comprises:

receiving and processing a CS domain paging message; a need for processing a CS domain service comprises a time for receiving a paging message as specified by a paging period arriving, or a paging indicator indicating it is required to receive a paging message.

12

8. The method according to claim **2**, characterized in that, a need for processing a CS domain service comprises:

a time for receiving a broadcast message or a time for performing location area update according to a time interval specified in a communication protocol arriving; processing the CS domain service correspondingly comprises: receiving and processing the broadcast message, or performing location area update for the user card of the terminal.

9. The method according to claim **3**, characterized in that processing the CS domain service comprises:

receiving and processing a CS domain paging message; a need for processing a CS domain service comprises a time for receiving a paging message as specified by a paging period arriving, or a paging indicator indicating it is required to receive a paging message.

10. The method according to claim **3**, characterized in that, a need for processing a CS domain service comprises:

a time for receiving a broadcast message or a time for performing location area update according to a time interval specified in a communication protocol arriving; processing the CS domain service correspondingly comprises: receiving and processing the broadcast message, or performing location area update for the user card of the terminal.

11. The method according to claim **4**, characterized in that processing the CS domain service comprises:

receiving and processing a CS domain paging message; a need for processing a CS domain service comprises a time for receiving a paging message as specified by a paging period arriving, or a paging indicator indicating it is required to receive a paging message.

12. The method according to claim **4**, characterized in that, a need for processing a CS domain service comprises:

a time for receiving a broadcast message or a time for performing location area update according to a time interval specified in a communication protocol arriving; processing the CS domain service correspondingly comprises: receiving and processing the broadcast message, or performing location area update for the user card of the terminal.

13. The method according to claim **5**, characterized in that receiving and processing the CS domain paging message comprises:

receiving the CS domain paging message; according to information within the CS domain paging message, identifying whether it is required to receive a broadcast message or process a CS domain communication service;

in response to that it is required to receive a broadcast message, receiving and processing the broadcast message;

in response to that it is required to process a CS domain communication service, processing the CS domain communication service.

14. The method according to claim **13**, characterized in that receiving and processing the broadcast message comprises:

receiving the broadcast message, and identifying whether the location area the terminal is located in has changed according to information within the broadcast message; in response to the location area the terminal is located in has changed, performing location area update for a user card of the terminal.

15. The method according to claim **6**, characterized in that receiving and processing the broadcast message comprises:

13

receiving the broadcast message, and identifying whether the location area the terminal is located in has changed according to information within the broadcast message; in response to that the location area the terminal is located in has changed, performing location area update for the user card of the terminal.

16. A baseband processor chip, characterized by comprising:

a first service processing unit, for processing a CS domain service;

a second service processing unit, for processing a PS domain service;

a monitor unit, for monitoring whether the first service processing unit needs to process a CS domain service;

an identification unit, for according to the monitor result of the monitor unit, in response to a need for processing a CS domain service by the first service processing unit, identifying whether PS domain data being received/transmitted in the PS domain service that is currently processed by the second service processing unit is critical data for maintaining a QoS level of the PS domain service, wherein the critical data is data for keeping the PS domain service continuous and/or keeping the PS domain data transmission rate from a significant decrease;

a scheduling unit, for according to the identification result of the identification unit, in response to the PS domain data that is being received/transmitted is not critical data, instructing the second service processing unit to suspend the processing of the PS domain service, and instructing the first service processing unit to process the CS domain service.

17. The baseband processor chip according to claim 16, characterized in that the scheduling unit is further used to after the CS domain service has been processed by the first service processing unit, instruct the second service processing unit to resume the processing of the PS domain service.

18. The baseband processor chip according to claim 16, characterized in that the receiving/transmitting of critical data by the second service processing unit is prior to the processing of the CS domain service performed by the first service processing unit.

19. The baseband processor chip according to claim 16, characterized in that the critical data is data specified by a communication protocol or user specified data.

20. The baseband processor chip according to claim 16, characterized in that a need for processing a CS domain service comprises a time for receiving a paging message as specified by a paging period arriving, or a paging indicator indicating it is required to receive a paging message.

21. The baseband processor chip according to claim 16, characterized in that a need for processing a CS domain service comprises:

a time for receiving a broadcast message or a time for performing location area update according to a time interval specified in a communication protocol arriving; wherein processing the CS domain service by the first service processing unit correspondingly comprises: receiving and processing the broadcast message, or performing location area update for the user card of the terminal.

22. The baseband processor chip according claim 17, characterized in that a need for processing a CS domain service comprises a time for receiving a paging message as specified by a paging period arriving, or a paging indicator indicating it is required to receive a paging message.

14

23. The baseband processor chip according to claim 17, characterized in that a need for processing a CS domain service comprises:

a time for receiving a broadcast message or a time for performing location area update according to a time interval specified in a communication protocol arriving; wherein processing the CS domain service by the first service processing unit correspondingly comprises: receiving and processing the broadcast message, or performing location area update for the user card of the terminal.

24. The baseband processor chip according to claim 18, characterized in that a need for processing a CS domain service comprises a time for receiving a paging message as specified by a paging period arriving, or a paging indicator indicating it is required to receive a paging message.

25. The baseband processor chip according to claim 18, characterized in that a need for processing a CS domain service comprises:

a time for receiving a broadcast message or a time for performing location area update according to a time interval specified in a communication protocol arriving; wherein processing the CS domain service by the first service processing unit correspondingly comprises: receiving and processing the broadcast message, or performing location area update for the user card of the terminal.

26. The baseband processor chip according to claim 19, characterized in that a need for processing a CS domain service comprises a time for receiving a paging message as specified by a paging period arriving, or a paging indicator indicating it is required to receive a paging message.

27. The baseband processor chip according to claim 19, characterized in that a need for processing a CS domain service comprises:

a time for receiving a broadcast message or a time for performing location area update according to a time interval specified in a communication protocol arriving; wherein processing the CS domain service by the first service processing unit correspondingly comprises: receiving and processing the broadcast message, or performing location area update for the user card of the terminal.

28. The baseband processor chip according to claim 20, characterized in that when receiving and processing the CS domain paging message, the first service processing unit is particularly used to receiving the CS domain paging message; according to information within the CS domain paging message, identify whether it is required to receive a broadcast message or process a CS domain communication service; in response to that it is required to receive a broadcast message, receive and process the broadcast message; in response to that it is required to process a CS domain communication service, process the CS domain communication service.

29. The baseband processor chip according to claim 28, characterized in that when receiving and processing the broadcast message, the first service processing unit is particularly used to receive the broadcast message, and identify whether the location area the terminal is located in has changed according to information within the broadcast message; in response to that the location area the terminal is located in has changed, perform location area update for a user card of the terminal.

30. A terminal, comprising a RE chip and a baseband processor chip, characterized in that the baseband processor chip is used to, in response to a need for processing a CS domain service, identify whether PS domain data being

15

received/transmitted in the PS domain service that is currently processed is critical data for maintaining the QoS level of the PS domain service, wherein the critical data is data for keeping the PS domain service continuous and/or keeping the PS domain data transmission rate from a significant decrease; 5
and in response to that the PS domain data being received/transmitted is not critical data, suspend the PS domain service and process the CS domain service.

31. The terminal according to claim **30**, characterized in that the baseband processor chip comprises the baseband 10
processor chip according to any one of claim **16** to claim **21**.

* * * * *

16