



US009274455B2

(12) **United States Patent**  
**Miura et al.**

(10) **Patent No.:** **US 9,274,455 B2**  
(45) **Date of Patent:** **Mar. 1, 2016**

(54) **IMAGE FORMING APPARATUS SUPPLYING TONER FROM CONTAINER TO ACCUMULATING UNIT BASED ON TOWER DENSITY DEVELOPER IN THE ACCUMULATING UNIT, AND METHOD OF CONTROLLING IMAGE FORMING APPARATUS**

(58) **Field of Classification Search**  
CPC ..... G03G 15/556; G03G 15/0889; G03G 15/0877; G03G 15/0879  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

(71) Applicant: **CANON KABUSHIKI KAISHA**,  
Tokyo (JP)

7,603,065 B2 \* 10/2009 Yamaguchi et al. .... 399/258  
2011/0020017 A1 \* 1/2011 Takahashi ..... 399/30  
2013/0202319 A1 \* 8/2013 Komatsu et al. .... 399/27

(72) Inventors: **Shusuke Miura**, Toride (JP); **Jiro Shirakata**, Chigasaki (JP); **Takayuki Iikura**, Kashiwa (JP)

FOREIGN PATENT DOCUMENTS

(73) Assignee: **CANON KABUSHIKI KAISHA**,  
Tokyo (JP)

JP 2013-160969 A 8/2013

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

\* cited by examiner

*Primary Examiner* — Rodney Bonnette

(21) Appl. No.: **14/565,101**

(22) Filed: **Dec. 9, 2014**

(74) *Attorney, Agent, or Firm* — Canon USA, Inc. IP Division

(65) **Prior Publication Data**

US 2015/0168904 A1 Jun. 18, 2015

(57) **ABSTRACT**

(30) **Foreign Application Priority Data**

Dec. 17, 2013 (JP) ..... 2013-260381

An image forming apparatus including a replaceable container having toner stored therein includes: an image forming unit including an accumulating unit for accumulating developer containing toner and configured to form an image by using the developer in the accumulating unit; a measurement unit configured to measure a toner density in the accumulating unit; a portion to which the container is attached; a supplementing unit configured to supplement the toner from the attached container to the accumulating unit; and a controller configured to control the supplementing unit based on first information corresponding to a difference between the toner density and a target toner density and second information corresponding to an accumulated value obtained by accumulating differences, wherein the second information does not change in a period from replacement of the container by another container until a predetermined number of times of supplement is performed.

(51) **Int. Cl.**  
**G03G 15/08** (2006.01)

**18 Claims, 6 Drawing Sheets**

(52) **U.S. Cl.**  
CPC ..... **G03G 15/0879** (2013.01); **G03G 15/0849** (2013.01); **G03G 2215/0132** (2013.01)




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5





FIG. 6



## 1

**IMAGE FORMING APPARATUS SUPPLYING  
TONER FROM CONTAINER TO  
ACCUMULATING UNIT BASED ON TOWER  
DENSITY DEVELOPER IN THE  
ACCUMULATING UNIT, AND METHOD OF  
CONTROLLING IMAGE FORMING  
APPARATUS**

## BACKGROUND OF THE INVENTION

## 1. Field of the Invention

The present invention relates to a supplement control for supplementing toner from a container to an accumulating unit.

## 2. Description of the Related Art

An image forming apparatus of an electrophotographic system forms a toner image based on an image data input to the image forming apparatus by consuming the toner stored in an accumulating unit. A configuration of the image forming apparatus in which the toner stored in the accumulating unit is consumed by forming toner images, and hence the toner is supplemented as needed to the accumulating unit from a container configured to be detachably attachable with respect to the image forming apparatus is known.

In the image forming apparatus, the fact that a concentration of a toner image developed by the accumulating unit is changed in accordance with an amount of toner accumulated in the accumulating unit is known. Accordingly, the image forming apparatus is required to supplement the toner from the container to the accumulating unit so that the amount of toner stored in the accumulating unit reaches a target amount.

In the image forming apparatus of the related art, a configuration in which a toner supplement amount is determined based on a difference between an amount of toner to be consumed from the accumulating unit by forming the toner image (amount of consumption) and a difference between the amount of toner and the target amount to be accumulated in the accumulating unit is known. For example, an image forming apparatus described in Japanese Patent Laid-Open No. 2013-160969 determines the toner supplement amount based on the amount of consumption estimated based on the image data, the difference between the amount of toner and the target amount to be accumulated in the accumulating unit, and an accumulated total value of the differences.

Here, the amount of consumption of toner is a theoretical amount based on calculation, and hence there is a slight difference between the actual amount of consumption of the toner consumed actually from the accumulating unit and the estimated amount of consumption described above. Accordingly, even though toner of an amount corresponding to the estimated amount of consumption described above is supplemented to the accumulating unit, the amount of toner in the accumulating unit may not become the target amount. Therefore, the image forming apparatus described in Japanese Patent Laid-Open No. 2013-160969 is configured to determine the toner supplement amount based on not only the estimated amount of consumption described above, but also the difference between the amount of toner and the target amount to be accumulated in the accumulating unit.

However, in the image forming apparatus described in Japanese Patent Laid-Open No. 2013-160969, there is a probability that the toner is excessively supplemented from the container to the accumulating unit or the amount of toner in the accumulating unit is remarkably reduced from the target value in the case where the container is replaced. This is because the toner supplement amount of the container after replacement is determined based on the accumulated total

## 2

value suitable for the toner supplement amount of the container which has been mounted on the image forming apparatus before the replacement even though the container has replaced.

## SUMMARY OF THE INVENTION

There is provided an apparatus including a replaceable container having toner stored therein, including: an image forming unit including an accumulating unit for accumulating developer containing toner and configured to form an image by using the toner in the accumulating unit based on an image data; a measurement unit configured to measure a toner density of the developer in the accumulating unit; a portion to which the container is attached; a detection unit configured to detect whether or not the container is replaced; a supplementing unit configured to supplement the toner from the container which is attached to the portion to the accumulating unit; a first determination unit configured to determine first information corresponding to a difference between the toner density and a target toner density of the developer in the accumulating unit; a second determination unit configured to determine second information corresponding to an accumulated value obtained by accumulating differences; and a controller configured to control the supplementing unit based on the first information and the second information, wherein the second information changes in a period from detection that the container is replaced by another container by the detection unit until the supplementing unit performs a predetermined times of supplement from another container to the accumulating unit.

There is also provided a method of controlling an image forming apparatus including: an image forming unit including an accumulating unit for accumulating developer containing toner and configured to form an image by using the toner in the accumulating unit; a measurement unit configured to measure a toner density of the developer in the accumulating unit; a portion for mounting a container having toner to be supplemented to the accumulating unit stored therein; and a supplementing unit configured to supplement the toner from the container to the accumulating unit, the method, including: determining first information corresponding to a difference between the toner density and a target toner density of the developer in the accumulating unit; determining second information corresponding to an accumulated value obtained by accumulating the differences; and controlling the supplementing unit based on the first information and the second information, wherein the second information does not change in a period from replacement of the container by another container until the supplementing unit performs a predetermined times of supplement from another container to the accumulating unit.

Further features of the present invention will become apparent from the following description of exemplary embodiments with reference to the attached drawings.

## BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic configuration drawing of an image forming apparatus.

FIG. 2 is a schematic configuration drawing of a principal portion of the image forming apparatus.

FIG. 3 is a block diagram illustrating an electric configuration of the image forming apparatus relating to toner supplement.

FIG. 4 is a flowchart of toner supplement control.



FIG. 5 is a graph showing transitions of a number of times of supplement and an amount of toner discharge by toner bottles.

FIG. 6 is a graph showing a transition of an amount of toner stored in a developing unit.

## DESCRIPTION OF THE EMBODIMENTS

### First Embodiment

FIG. 1 is a schematic cross-sectional view of an image forming apparatus 200. The image forming apparatus 200 includes four image forming portions Pa, Pb, Pc and Pd configured to form toner images of having respective color components and arranged in a line in a direction of conveyance of an intermediate transfer belt 7. The image forming portion Pa forms a yellow toner image, the image forming portion Pb forms a magenta toner image, the image forming portion Pc forms a cyan toner image, and the image forming portion Pd forms a black toner image.

Toner bottles Ta, Tb, Tc, and Td which are demountably mountable on the image forming apparatus 200 are mounted on the image forming apparatus 200. The toner bottle Ta includes yellow toner stored therein, the toner bottle Tb includes magenta toner stored therein, the toner bottle Tc includes cyan toner stored therein, and the toner bottle Td includes black toner stored therein. The toner bottles Ta, Tb, Tc, and Td correspond to a container for storing supplemental toner.

The image forming portions Pa, Pb, Pc and Pd have the same configuration, and hence the image forming portion Pa, Pb, Pc and Pd are referred to collectively as an image forming portion P in the following description. The toner bottles Ta, Tb, Tc, and Td have the same configuration, and hence the toner bottles Ta, Tb, Tc, and Td are referred to collectively as a toner bottle T.

The image forming portion P includes a photosensitive drum 1 provided with a photosensitive layer functioning as a photo sensitive member on a surface of a column-shaped metallic roller, a charger 2 configured to charge the photosensitive drum 1, and a developing unit 100 including toner stored therein. The developing unit 100 is an accumulating unit in which developer including toner is accumulated.

When the image forming action is started, the photosensitive drum 1 is driven to rotate in a direction indicated by an arrow A. After the charger 2 has charged the photosensitive drum 1 uniformly, a laser exposing device 3 exposes the photosensitive drum 1 based on image data. Accordingly, an electrostatic latent image is formed on the photosensitive drum 1. Then, the developing unit 100 develops the electrostatic latent image on the photosensitive drum 1 by using toner, and a toner image is formed on the photosensitive drum 1.

In this embodiment, two-component developer is accumulated in the developing unit 100, and supplemental toner is stored in the toner bottle T. The supplemental toner is supplemented from the toner bottle T to the developing unit 100 so that the amount of toner in the developing unit 100 becomes a target amount. The two-component developer is a developer composed of carrier and toner having magnetism.

As illustrated in FIG. 2, an inductance sensor 112 configured to detect the amount of toner accumulated in the developing unit 100 is arranged in the developing unit 100. The inductance sensor 112 outputs a signal indicating magnetic permeability of the developer stored in the developing unit 100 to a controller 500 described later (FIG. 3). An output

signal of the inductance sensor 112 is a signal that varies in accordance with the amount of toner stored in the developing unit 100.

Here, the output signal from the inductance sensor 112 will be described. When the ratio of the toner in the developer (hereinafter, referred to a “developing unit toner concentration”) is increased, the ratio of the carrier in the developer is decreased, so that an output value of the inductance sensor 112 is reduced. In contrast, when the developing unit toner concentration is reduced, the ratio of the carrier in the developer increases, and hence the output value of the inductance sensor 112 is increased. The controller 500 (FIG. 3) detects the amount of toner stored in the developing unit 100 based on the output signal of the inductance sensor 112. In other words, the output signal of the inductance sensor 112 is a signal that indicates the amount of toner stored in the developing unit 100.

FIG. 2 is a schematic configuration drawing of a principal portion of the image forming apparatus 200. The image forming apparatus 200 includes an attaching portion 20 having the toner bottle T mounted thereon, and a supply motor 120 (FIG. 3) configured to engage the toner bottle T mounted on the attaching portion 20 and drive to the toner bottle T to rotate. The toner bottle T is provided with a helical guide groove configured to convey toner to the inner peripheral surface thereof. The supply motor 120 rotates the toner bottle T, whereby the toner in the toner bottle T is supplemented from the toner bottle T to the developing unit 100. The toner discharged from a discharge port of the toner bottle T supplemented is supplied to the developing unit 100 via a conveying path 21.

Returning back to FIG. 1, an explanation of the image forming apparatus 200 will be described. The intermediate transfer belt 7 is wound around a secondary-transfer counter roller 8, a driven roller 17, tension rollers 18 and 19. The intermediate transfer belt 7 rotates in a direction indicated by an arrow B by a rotational drive of the secondary-transfer counter roller 8.

The image forming portion P is provided with a primary transfer roller 4 configured to transfer the toner image on the photosensitive drum 1 to the intermediate transfer belt 7. While the toner image formed on the photosensitive drum 1 is passing through a primary transfer nip portion T1 formed by the photosensitive drum 1 and the intermediate transfer belt 7 compressed against the primary transfer roller 4, a primary transfer voltage is applied to the primary transfer roller 4. Accordingly, the toner image on the photosensitive drum 1 is transferred to the intermediate transfer belt 7. The toner images formed on the respective photosensitive drums 1a, 1b, 1c and 1d are transferred to the intermediate transfer belt 7 in a superimposed manner, whereby the intermediate transfer belt 7 bears a full color toner image. A drum cleaner 6 removes the toner remaining on the photosensitive drum 1 which is not transferred from the photosensitive drum 1 to the intermediate transfer belt 7 at the primary transfer nip portion T1.

On a side opposite to the intermediate transfer belt 7 with respect to the secondary-transfer counter roller 8, a secondary transfer roller 9 is disposed. When the secondary transfer roller 9 presses against the secondary-transfer counter roller 8 and the intermediate transfer belt 7, a secondary transfer nip portion T2 is formed between the intermediate transfer belt 7 and the secondary transfer roller 9. By the intermediate transfer belt 7 conveyed in the direction indicated by an arrow B, the toner image on the intermediate transfer belt 7 is conveyed to the secondary transfer nip portion T2.

## 5

A conveying roller pair **61** and a registration roller pair **62** conveys a recording member **S** stored in a cassette portion **60** so that timing when the toner image reaches the secondary transfer nip portion **T2** and timing when the recording member **S** reaches the secondary transfer nip portion **T2** are matched. With an application of a secondary transfer voltage on the secondary-transfer counter roller **8** while the toner image on the intermediate transfer belt **7** and the recording member **S** pass through the secondary transfer nip portion **T2**, the toner image on the intermediate transfer belt **7** is transferred to the recording member **S**. A bolt cleaner **11** removes toner remaining on the intermediate transfer belt **7** which is not transferred to the recording member **S** at the secondary transfer nip portion **T2**.

After the toner image has transferred to the recording member **S** by the secondary transfer roller **9**, the recording member **S** is conveyed to the fixing unit **13**. The fixing unit **13** is provided with a fixing roller having a heater and a pressing roller, and fixes the toner image on the recording member **S** to the recording member **S** by heat of the heater and pressures of the fixing roller and the pressing roller. The recording member **S** having the toner image fixed thereto by the fixing unit **13** is discharged from the image forming apparatus **200** by a sheet-output-roller pair **64**.

Subsequently, a toner supplement control process for supplementing toner from the toner bottle **T** to the developing unit **100** based on an amount of consumption of toner consumed from the developing unit **100** by the image forming unit **P** when forming a toner image based on the image data and a result of detection of the inductance sensor **112** will be described.

FIG. **3** is a block diagram illustrating an electric configuration of the image forming apparatus **200** relating to toner supplement. In order to facilitate description of an interior of the controller **500**, respective functions to be executed by the controller **500** in the toner supplement control process are illustrated by blocks.

A RAM **502** is a system work memory to be used for the toner supplement control process. A ROM **503** includes a control program for controlling the toner supplement control process stored therein. An I/F **504** is an interface that can be connected to a scanner or an external PC, and receives information such as image data. The inductance sensor **112** is described in conjunction with FIG. **2**, and hence description will be omitted here.

The photo interrupter **111** is an optical sensor configured to output an ON signal in the case where the toner bottle **T** is mounted on the mounting portion **20** (FIG. **2**), and output an OFF signal when mounting of the toner bottle **T** to the mounting portion **20** (FIG. **2**) is released. The controller **500** detects the fact that a non-mounted state in which the toner bottle **T** is not mounted on the mounting portion **20** is changed to a mounted state in which the toner bottle **T** is mounted to the mounting portion **20** in accordance with a change of the output signal from the photo interrupter **111** from the OFF signal to the ON signal. In other words, the controller **500** determines whether or not the toner bottle **T** is replaced based on the output signal from the photo interrupter **111**. Since a configuration of the photo interrupter **111** is a known configuration, detailed description will be omitted.

The counter **1100** counts a summation of concentrations of the respective pixels included in an image for one page (hereinafter, referred to as a video count value) based on the image data input to the controller **500** by the I/F **504**. The video count value counted by the counter **1100** corresponds to the amount of consumption of the toner consumed from the developing unit **100** consumed by the image forming unit **P**

## 6

forming the toner image of one page of the recording member. Since a method of acquiring the video count value is a known technology, description will be omitted.

In the embodiment, the controller **500** determines the amount of toner in the developing unit **100** detected based on the output signal from the inductance sensor **112** and the amount (required amount) of toner to be supplemented to the developing unit **100** based on the video count value acquired by the counter **1100**. The controller **500** drives the supply motor **120** when the accumulated total value of the required amount exceeds a threshold value to supplement the toner from the toner bottle **T** to the developing unit **100**.

A toner supplement control in the embodiment will be described with reference to FIG. **4**. FIG. **4** is a flowchart of an operation of the controller **500**.

The controller **500** starts the toner supplement control by transfer of image data based on an original document generated by a scanner, not illustrated, by reading out the original document, or image data output from a PC, not illustrated, to the controller **500** by the I/F **504**. In the case where the image forming portion **P** forms a plurality of images based on the image data transferred from the I/F **504**, the controller **500** executes the toner supplement amount control process every time when an image on one page of the recording member is formed.

The controller **500** computes the amount of toner consumption based on the image data (**S100**). In Step **S100**, the counter **1100** counts a video count value  $V_n$  based on the image data. A consumed amount computing section **1101** refers a conversion table indicating a correspondence between the video count value and the amount of toner consumption, and determines an amount of toner consumption **C** based on the video count value  $V_n$  counted by the counter **1100**. The conversion table is memorized in advance in the ROM **503**. In the embodiment, the consumed amount computing section **1101** outputs the amount of consumption **C** of the toner consumed from the developing unit **100** by the toner image formed on the image forming portion **P** before the image forming portion **P** forms the toner image of one page of the recording member.

Before the image forming portion **P** forms a toner image the amount of consumption **C** of which is computed by the consumed amount computing section **1101**, the controller **500** detects the amount of toner stored in the developing unit **100** based on the output signal from the inductance sensor **112** (**S101**). Subsequently, a difference computing section **1200** determines the amount of toner in the developing unit **100** based on the output value **D** from the inductor sensor **112** and computes a difference  $\Delta D$  between the determined amount of toner and a target value output by a target value determining section **1201** (**S102**). The target value of the toner stored in the developing unit **100** is a value by predetermined an experiment, and is stored in advance in the ROM **503**. In Step **S102**, the target value determining section **1201** determines the target amount of the toner in the developing unit **100** based on a temperature and a humidity of a periphery of the image forming apparatus **200** detected by an environmental sensor, which is not illustrated, provided on the image forming apparatus **200**.

The difference computing section **1200** may be configured to compute a difference between the output value (toner density **D**) from the inductor sensor **112** and an output target value (target toner density  $D_{ref}$ ) from the inductor sensor **112**. In this case, the target value determining section **1201** determines the output target value of the inductance sensor **112** based on the temperature of the humidity in the periphery of

the image forming apparatus **200** detected by an environment sensor, which is not illustrated, provided in the image forming apparatus **200**.

The difference computing section **1200** determines a value  $\Delta D$  corresponding to the difference between the toner density  $D$  in the developing unit **100** and the target toner density  $D_{ref}$ .

In a case where the amount of toner is smaller than the target value, the difference  $\Delta D$  is larger than 0, and in a case where the amount of toner is larger than the target value, the difference  $\Delta D$  is smaller than 0.

After the amount of consumption is computed by the consumed amount computing section **1101**, and the difference is computed by the difference computing section **1200**, a required amount computing section **1300** computes a required amount  $X$  of toner to be supplemented from the toner bottle **T** to the developing unit **100** based on the amount of consumption  $C$ , the difference  $\Delta D$ , and an accumulated total value  $\Sigma \Delta D$  described later (**S103**). In the embodiment, the required amount  $X$  is, for example, a control parameter to be computed by using the expression (1).

$$X = (\alpha \times C) + (\beta \times \Delta D) + (\gamma \times \Sigma \Delta D) \quad (1)$$

where, constants  $\alpha$ ,  $\beta$ , and  $\gamma$  are values of gain determined in advance based on experiment. In the embodiment, for example, the constants  $\beta$  and  $\gamma$  are positive values smaller than 1.

After the required amount  $X$  has determined in Step **S103**, the required amount computing section **1300** computes a required accumulated total value  $\Sigma X$  (**S104**), and the controller **500** determines whether or not the accumulated total value  $\Sigma X$  is larger than the threshold value (**S105**). In Step **S105**, if the accumulated total value  $\Sigma X$  is larger than the threshold value, the controller **500** rotates the toner bottle **T** by one turn by the supply motor **120**, and supplements the toner from the toner bottle **T** to the developing unit **100** (**S106**).

In the embodiment, the supply motor **120** drives the toner bottle **T** to rotate, whereby the toner in the toner bottle **T** is supplied to the developing unit **100** by a substantially constant amount. Therefore, the controller **500** is capable of determining the amount of rotation of the toner bottle **T** based on the accumulated total value  $\Sigma X$  of the amount of toner to be supplemented from the toner bottle **T** to the developing unit **100**. In other word, if the accumulated total value  $\Sigma X$  is twice the threshold value or more and smaller than three times, the toner bottle **T** rotates by two turns, and if the accumulated total value  $\Sigma X$  is three times the threshold value or more and smaller than four times, the toner bottle **T** rotates by three turns. In the embodiment, the supply motor **120** drives the toner bottle **T** to rotate in accordance with the amount of rotation determined by the controller **500** while the image forming portion **P** forms the toner image.

In the embodiment, the minimum amount of rotation of the toner bottle **T** is assumed to be one turn (360 degrees). Therefore, the toner bottle **T** does not rotate if the accumulated total value  $\Sigma X$  of the amount of toner to be supplemented from the toner bottle **T** to the developing unit **100** does not exceed the threshold value.

In the embodiment, the threshold value described above is determined to be a value smaller than the estimated amount of toner to be supplemented from the toner bottle **T** to the developing unit **100** in the case where the toner bottle **T** is rotated by one turn (the minimum amount of rotation). The reason is that the difference between the toner concentration and the target value in the developing unit **100** in the case where the toner is not supplemented from the toner bottle **T** to the developing unit **100** is restrained from becoming larger than the difference between the toner concentration and the target

value in the developing unit **100** in the case where the toner is supplemented from the toner bottle **T** to the toner concentration. The estimated amount of toner to be supplemented from the toner bottle **T** to the developing unit **100** in the case where the supplementing operation for one dose is executed, that is, in the case where the toner bottle **T** is rotated by one turn is determined in advance based on experiment.

In the embodiment, the threshold value is determined to be 80% of the amount of toner to be supplemented from the toner bottle **T** to the developing unit **100** when the toner bottle **T** is rotated by one turn, for example. The value of this threshold value is memorized in the ROM **503** in advance.

However, depending on the posture and a storage environment of the toner bottle **T** when the toner bottle **T** is stored, the amount of toner supplemented actually from the toner bottle **T** to the developing unit **100** may lose touch from the amount of toner estimated in advance.

FIG. **5** is a graph showing changes of the amounts of toner discharged from toner bottles **A**, **B**, **C**, and **D** when the supply motor **120** rotates the toner bottles **A**, **B**, **C**, and **D** having different storage conditions are rotated respectively. A vertical axis represents the amount of discharge of the toner discharged from the toner bottle **T** to the developing unit **100** when the toner bottle **T** is rotated by one turn, and a lateral axis represents the number of times of rotation of the toner bottle **T**.

The toner bottles **A**, **B**, and **C** are assumed to be stored in a posture in which an end of a discharge port of the toner bottle is oriented downward in the direction of gravitational force, and the toner bottom **D** is assumed to be stored in a posture in which an end of a discharge port of the toner bottle is oriented upward in the direction of gravitational force. In addition, the toner bottles **A**, **B**, and **C** are assumed to be stored in storage places different in temperature and humidity from each other.

As illustrated in FIG. **5**, when the toner bottles **A**, **B** and **C** is rotated by one turn, the amount of toner (amount of discharge) discharged respectively from the toner bottles **A**, **B** and **C** is larger than the target value (250 mg). In addition, the amounts of discharge of the respective toner bottles **A**, **B** and **C** are gradually decreased as the numbers of times of rotation increases in the case of the toner bottles **A**, **B** and **C**, and when the toner bottles **A**, **B** and **C** rotate more than 10 times, the amounts of discharge are stabilized in the vicinity of the target amounts (250 mg).

As illustrated in FIG. **5**, when the toner bottle **D** is rotated by one turn, the amount of toner discharged from the toner bottle **D** is smaller than the target value (250 mg). In addition, in the case of the toner bottle **D**, the amount of discharge of the toner bottle **D** is gradually decreased as the numbers of times of rotation increases, and when the toner bottle **D** rotates more than 10 times, the amount of discharge is stabilized in the vicinity of the target amount (250 mg).

The reason why the amount of discharge of the toner discharged from the toner bottle **T** is not stabilized is that the toner in the toner bottle **T** is agglutinated while the toner bottle **T** is stored. When the toner in the toner bottle **T** is agglutinated in the periphery of the discharge port, the amount of discharge of the toner exceeds the target value immediately after the rotation of the toner bottle **T**. When the toner in the toner bottle **T** is agglutinated on a side opposite to the discharge port, the amount of discharge of the toner becomes smaller than the target value immediately after the rotation of the toner bottle **T**.

In the case where the toner is supplemented from the toner bottle **T** to the developing unit **100** based on the result of computation of the above-described expression (1) in a state in which the amount of toner supplied from the toner bottle **T**

to the developing unit **100** is not stable, the toner concentration in the developing unit **100** does not converge to the target value quickly. Furthermore, in the case described above, the amount of change in the toner concentration in the developing unit **100** may be increased. Accordingly, this embodiment employs a configuration in which the accumulated total value  $\Sigma\Delta D$  of the difference is not cumulated after the toner bottle T has been mounted on the mounting portion **20** until the toner bottle T rotates by 10 turns without being demounted from the mounting portion **20**.

Returning back to FIG. 4, description of the toner supplement control process of this embodiment will be continued. The controller **500** calculates the number of times of rotation of the toner bottle T after the toner bottle T has replaced. In Step **S106**, when the supply motor **120** rotates the toner bottle T by one turn, the controller **500** increment the value of a number of times of supplement N which indicates the number of times of rotation of the toner bottle T after the toner bottle T has replaced by one (**S107**). The controller **500** sets the value of the number of times of supplement N to 0 (reset) in accordance with a change of the output signal from the photo interrupter **111** from ON signal to OFF signal, and increments the value of the number of times of supplement N every time when the toner bottle T rotates by one turn.

Subsequently, the controller **500** subtracts the threshold value from the accumulated total value  $\Sigma X$  of the required amount of toner to be supplemented from the toner bottle T to the developing unit **100** (**S108**), and then the procedure goes to Step **S105**. In the process from Step **S105** to Step **S108**, the controller **500** drives the toner bottle T to rotate by the supply motor **120** until the accumulated total value  $\Sigma X$  of the required amount of toner to be supplemented from the toner bottle T to the developing unit **100** does not exceed the threshold value.

In Step **S105**, if the accumulated total value  $\Sigma X$  of the required amount of toner is not larger than the threshold value, the controller **500** determines whether or not the toner bottle T is rotated 10 times or more after the toner bottle T has been mounted (**S109**). This is because the amount of toner to be supplemented from the toner bottle T to the developing unit **100** is stabilized when the toner bottle T in the embodiment is rotated by 10 turns after the toner bottle T has been mounted.

If the toner to be supplemented from the toner bottle T to the developing unit **100** is not stabilized, the value of the accumulated total value  $\Sigma\Delta D$  of differences also varies. If the accumulated total value  $\Sigma\Delta D$  of differences is updated although the toner to be supplemented from the toner bottle T to the developing unit **100** is not stabilized, the amount of toner in the developing unit **100** may vary significantly with respect to the target value. The embodiment employs a configuration in which if the toner bottle T is not rotated by 10 turns or more after the toner bottle T has been mounted, the difference  $\Delta D$  computed in Step **S102** is not cumulated on the accumulated total value  $\Sigma\Delta D$  of differences to the current accumulated total value of differences  $\Sigma\Delta D$ .

In Step **S109**, if the value of the number of times of supplement N is smaller than 10, the controller **500** does not add the difference  $\Delta D$  computed by the differential computing section **1200** in Step **S102** to the current accumulated total value  $\Sigma\Delta D$  of differences, and terminates the toner supplement control process. In other words, an accumulated total value computing section **1202** holds the accumulated total value  $\Sigma\Delta D$  of differences computed in the toner supplement control process of the previous time. Accordingly, the required amount computing section **1300** computes the amount X of the toner to be supplemented from the toner bottle T to the

developing unit **100** based on the accumulated total value  $\Sigma\Delta D$  of differences which is not cumulated with the difference  $\Delta D$  of the previous time.

In contrast, if the value of the number of times of supplement N is 10 or more in Step **S109**, the accumulated total value computing section **1202** adds the difference  $\Delta D$  of this time to the accumulated total value  $\Sigma\Delta D$  of differences (**S110**). In the accumulating process in Step **S110**, the accumulated total value  $\Sigma\Delta D$  of differences corresponds to the accumulated total value  $\Sigma\Delta D$  of differences at the time of execution of Step **S110**. In addition, in the accumulating process in Step **S110**, the difference  $\Delta D$  of this time corresponds to the difference  $\Delta D$  computed by the differential computing section **1200** in Step **S102**.

An accumulating number of times of rotation of the toner bottle T required until the amount of toner supplied from the toner bottle T to the developing unit **100** is stabilized is different depending on the configuration of the toner bottle T. Therefore, the accumulating number of times of rotation of the toner bottle T required until the amount of toner to be supplemented from the toner bottle T to the developing unit **100** is stabilized may be determined by experiment as needed.

After the accumulated total value computing section **1202** has cumulated the difference  $\Delta D$  on the current accumulated total value  $\Sigma\Delta D$  of differences in Step **S110**, the controller **500** terminates the toner supplement amount control process. Accordingly, when the toner supplement control process for the next time is executed, the accumulated total value  $\Sigma\Delta D$  of differences updated in Step **S110** is used for determining the required amount X of toner to be supplemented.

The embodiment employs a configuration in which the accumulated total value  $\Sigma\Delta D$  of differences is not added in a period after the toner bottle T has been mounted on the mounting portion **20** until the toner bottle T is rotated by the estimated number of times of rotation which stabilizes the amount of discharge of the toner bottle T at the target amount. Therefore, according to the embodiment, significant variation of the amount of toner in the developing unit **100** with respect to the target amount after the toner bottle T has been replaced until the amount of discharge of the toner from the toner bottle T is stabilized may be restrained.

#### Comparison of Effects

A result of comparison of the toner concentration in the developing unit **100** in the case where the toner supplement control process of the embodiment and the toner supplement control process of a comparative example are executed will be described with reference to FIG. 6.

In FIG. 6, the toner concentration in the developing unit **100** in the case where the accumulated total value  $\Sigma\Delta D$  of differences is not added after the toner bottle T is replaced until the toner bottle T has been rotated by 10 turns or more is indicated by a solid line (the embodiment). Also, the toner concentration in the developing unit **100** in the case where the accumulated total value  $\Sigma\Delta D$  of differences is added although the toner bottle T has been replaced is indicated by a broken line (comparative example).

FIG. 6 is a drawing illustrating transitions of the toner concentrations in the developing unit **100** in the case where the images having the same video count value were formed continuously after the toner bottle T has been replaced. The target value of the toner concentration in the developing unit **100** was assumed to be 10%. In FIG. 6, the toner concentration when the toner bottle T was replaced was the target value (10%), and the amount of discharge of the toner of the toner bottle T before the replacement was smaller than the target amount (250 mg). In addition, the amount of discharge of the

## 11

toner of the toner bottle T after the replacement was assumed to be larger than the target amount.

In the comparative example (broken line), the toner was supplemented from the toner bottle T to the developing unit **100** after the elapse of 30 seconds from the replacement of the toner bottle T. Accordingly, the toner concentration in the developing unit **100** was increased. However, since the amount of discharge of the toner from the toner bottle T after the replacement was larger than the target amount, the toner concentration in the developing unit **100** was increased continuously, and exceeds 1.4 points higher than the target value when 40 seconds has elapsed.

This was because a response of the inductance sensor **112** was slow, and hence the accumulated total value  $\Sigma\Delta D$  make timing of supplement of toner from the toner bottle T to the developing unit **100** earlier although the amount of discharge of toner of the toner bottle T after the replacement is larger than the target amount.

Consequently, after the elapse of 60 seconds after the toner bottle T has been replaced, the toner concentration in the developing unit **100** started to lose touch with the target value toward the minus side. Then, when 75 seconds have been elapsed after the toner bottle T has been replaced, the toner concentration in the developing unit **100** was lower than the target value by 0.8 points.

This was because the accumulated total value  $\Sigma\Delta D$  of differences was changed to a value which delayed timing of supplement of toner. Accordingly, the toner was not supplemented from the toner bottle T to the developing unit **100** although the toner concentration in the developing unit **100** was lower than the target value.

Then, the toner concentration in the developing unit **100** repeated increase and decrease with respect to the target value, and was stabilized at the target value when approximately 120 seconds have elapsed after the toner bottle T has been replaced.

In contrast, in the embodiment (solid line), toner was supplemented from the toner bottle T to the developing unit **100** after the elapse of 60 seconds from the replacement of the toner bottle T. Accordingly, the toner concentration in the developing unit **100** was increased. When 80 seconds had been elapsed after the toner bottle T has been replaced, the toner concentration in the developing unit **100** was higher than the target value by 0.5 points. In addition, when approximately 100 seconds had elapsed after the toner bottle T has been replaced, the toner concentration in the developing unit **100** was stabilized at the target value.

This was because the accumulated total value  $\Sigma\Delta D$  of differences before the replacement does not make timing of supplement of toner from the toner bottle T to the developing unit **100** earlier although the amount of discharge of toner of the toner bottle T after the replacement was larger than the target amount.

According to the embodiment, since the accumulated total value  $\Sigma\Delta D$  of differences is not cumulated in a period after the toner bottle T has been replaced until the accumulated number of times of rotations of the toner bottle T becomes 10 times, the amount of variation of the toner concentration in the developing unit **100** may be restrained. In addition, according to the embodiment, since the accumulated total value  $\Sigma\Delta D$  of differences is not cumulated in the period after the toner bottle T has been replaced until the accumulating number of times of rotation of the toner bottle T reaches 10 times, the period after the toner bottle T has been replaced until the toner concentration in the developing unit **100** is stabilized at the target value may be reduced. In other words, according to the toner supplement control of the embodiment,

## 12

even when the toner bottle T has replaced, the amount of toner to be supplemented to the developing unit may be controlled with high degree of accuracy.

The embodiment employs a configuration in which the difference  $\Delta D$  is not added to the accumulated total value  $\Sigma\Delta D$  of differences in the period after the toner bottle T has been replaced until the accumulating number of times of rotation of the toner bottle T reaches 10 times. However, a configuration in which the accumulated total value computing section **1202** sets the value of the difference  $\Delta D$  to 0 and adds the difference  $\Delta D$  to the accumulated total value  $\Sigma\Delta D$  of differences in the period described above is also applicable.

The embodiment employs a configuration in which the result of computation of the accumulated total value  $\Sigma\Delta D$  of differences is memorized in the RAM **502**, and the accumulated total value  $\Sigma\Delta D$  of differences memorized in the RAM **502** is read out when computing the required amount X in the case where the toner bottle T has been rotated by 10 turns or more after the toner bottle T has been replaced. However, a configuration in which the result of computation of the accumulated total value  $\Sigma\Delta D$  of differences is not memorized in the RAM **502** in the period after the toner bottle T has been replaced until the accumulating number of times of rotation of the toner bottle T reaches 10 times is also applicable.

The embodiment employs a configuration in which the controller **500** executes the toner supplement control process every time when the image forming portion P forms an image in one page of the recording member. However, the timing of execution of the toner supplement control process by the controller **500** is not limited thereto. For example, a configuration in which the toner supplement control process in FIG. **4** is executed by the controller **500** at a predetermined time interval while a stirring screw configured to stir the toner accumulated in the developing unit **100** rotates. In this configuration, the toner may be supplemented from the toner bottle T to the developing unit **100** even at the timing when the image forming portion P does not form the toner image.

The embodiment employs a configuration in which the amount of toner to be supplied from the toner bottle T to the developing unit **100** is controlled by controlling the amount of rotation of the toner bottle T. However, a configuration in which the amount of supply is controlled in accordance with a speed of rotation of the toner bottle T is also applicable. In this configuration, the controller **500** may determine the speed of rotation of the toner bottle T based on the required amount X of toner to be supplemented from the toner bottle T to the developing unit **100** to control the supply motor **120** so that the speed of rotation of the toner bottle T achieves the determined speed of rotation.

According to the invention, even though the container is replaced, the difference between the amount of toner and the target amount of toner in the accumulating unit may be controlled.

While the present invention has been described with reference to exemplary embodiments, it is to be understood that the invention is not limited to the disclosed exemplary embodiments. The scope of the following claims is to be accorded the broadest interpretation so as to encompass all such modifications and equivalent structures and functions.

This application claims the benefit of Japanese Patent Application No. 2013-260381, filed Dec. 17, 2013 which is hereby incorporated by reference herein in its entirety.

What is claimed is:

1. An image forming apparatus comprising: an image forming unit including an accumulating unit for accumulating developer containing toner and config-

## 13

ured to form an image by using the toner in the accumu-  
 lating unit based on an image data;  
 a first sensor configured to measure a toner density of the  
 developer in the accumulating unit;  
 a portion to which a container is mountable, the container  
 5 containing toner;  
 a second sensor configured to detect absence or presence of  
 the container at the portion;  
 a driving unit configured to rotate the container mounted on  
 the portion to supply the toner from the rotating con- 10  
 tainer to the accumulating unit;  
 a difference computing section configured to determine  
 first information corresponding to a difference between  
 the toner density and a target toner density of the devel-  
 oper in the accumulating unit;  
 15 an accumulated value computing section configured to  
 accumulate the difference determined by the difference  
 computing section and determine second information  
 corresponding to an accumulated value of difference;  
 20 and  
 a controller configured to control the driving unit based on  
 the first information and the second information, and  
 determine whether the container is exchanged with  
 another container based on a detection result by the  
 25 second sensor,  
 wherein the second information does not change in a  
 period from a timing that the controller determines that  
 the container is exchanged with the other container until  
 the controller performs a predetermined times of supple-  
 30 ment from the other container to the accumulating unit.  
**2.** The image forming apparatus according to claim 1  
 wherein  
 the accumulated value computing section is configured to  
 add the difference as 0 to the accumulated value deter- 35  
 mined before the controller determines that the con-  
 tainer is exchanged with the other container in the  
 period.  
**3.** The image forming apparatus according to claim 1  
 wherein  
 the driving unit performs a supplementing action by rotat- 40  
 ing the container by a predetermined amount of rotation,  
 and  
 the period is a period after the other container is mounted  
 on the portion until the accumulated number of times of  
 45 rotation of the container reaches a predetermined num-  
 ber of times of rotation.  
**4.** The image forming apparatus according to claim 1  
 further comprising a consumed amount computing section  
 configured to determine third information correspond- 50  
 ing to an amount of toner consumed from the accumu-  
 lating unit by the image forming unit forming the toner  
 image based on the image data, wherein  
 the controller controls the driving unit based on the first  
 information, the second information, and the third infor-  
 55 mation.  
**5.** The image forming apparatus according to claim 4,  
 wherein  
 the controller is configured to determine a control value for  
 controlling the driving unit based on the first informa- 60  
 tion, the second information, and the third information,  
 the controller does not rotate the container unless a value  
 obtained by accumulating the control values exceeds a  
 threshold value.  
**6.** The image forming apparatus according to claim 5  
 wherein  
 the controller determines an amount of rotation of the  
 container based on the control value, and

## 14

the driving unit rotates the container based on the deter-  
 mined amount of rotation.  
**7.** The image forming apparatus according to claim 5,  
 wherein the controller determines the control value every  
 time when the image forming unit forms an image for one  
 page of a recording member.  
**8.** The image forming apparatus according to claim 5,  
 wherein  
 the accumulating unit includes a stifling screw configured  
 to stir the developer stored in the accumulating unit, and  
 the controller determines the control value in a predeter-  
 mined time interval while the stifling screw stirs the  
 developer.  
**9.** The image forming apparatus according to claim 4,  
 15 wherein  
 the consumed amount computing section determines a  
 video value based on the image data, and refers a con-  
 version table indicating the video value and the amount  
 of toner consumed from the accumulating unit to deter-  
 mine the third information.  
**10.** A method of controlling an image forming apparatus  
 including:  
 an image forming unit including an accumulating unit for  
 accumulating developer containing toner and configu-  
 25 red to form an image by using the toner in the accumu-  
 lating unit;  
 a first sensor configured to measure a toner density of the  
 developer in the accumulating unit;  
 a portion to which a container is mountable, the container  
 containing toner;  
 a second sensor configured to detect absence or presence of  
 the container at the portion; and  
 a driving unit configured to rotate the container mounted on  
 the portion to supply the toner from the rotating con-  
 30 tainer to the accumulating unit, the method comprising:  
 determining first information corresponding to a difference  
 between the toner density and a target toner density of  
 the developer in the accumulating unit;  
 accumulating the difference;  
 determining second information corresponding to an accu-  
 40 mulated value of difference;  
 controlling the driving unit based on the first information  
 and the second information; and  
 determining whether the container is exchanged with  
 another container based on a detection result by the  
 45 second sensor,  
 wherein the second information does not change in a  
 period from of the determining that the container is  
 exchanged with the other container until the driving unit  
 performs a predetermined times of supplement from the  
 other container to the accumulating unit.  
**11.** The method according to claim 10, further comprising  
 adding the difference as 0 to the accumulated value deter-  
 50 mined before the determining that the container is exch-  
 aged  
 with the other container in the period.  
**12.** The method according to claim 10, wherein  
 the driving unit performs a supplementing action of one  
 dose of toner by rotating the container attached on the  
 portion by a predetermined amount of rotation, and  
 the period is a period after the other container is mounted  
 on the portion until the accumulated number of times of  
 rotation of the other container reaches a predetermined  
 number of times of rotation.  
**13.** The method according to claim 12, wherein  
 65 the controlling determines a control value for controlling  
 the supplementing based on the first information and the  
 second information, and

the container attached on the portion is not rotated until a value obtained by accumulating the control values exceeds a threshold value.

**14.** The method according to claim **13**, wherein an amount of rotation of the container is determined based on the control value. 5

**15.** The method according to claim **10**, further comprising determining third information corresponding to an amount of toner consumed from the accumulating unit by the image forming unit forming the toner image based on the image data, wherein the controlling the driving unit is controlled based on the first information, the second information, and the third information. 10

**16.** The method according to claim **15**, wherein a control value for controlling the driving unit is determined based on the first information, the second information, and the third information, and the controlling the driving unit does not rotate the container until the value obtained by accumulating the control values exceeds a threshold value. 15 20

**17.** The method according to claim **16**, wherein the controlling is determined every time when the image forming unit forms an image for one page of a recording member. 25

**18.** The method according to claim **16**, wherein the accumulating unit includes a stifling screw configured to stir the developer in the accumulating unit, and the control value is determined in a predetermined time interval while the stifling screw stirs the developer in the accumulating unit. 30

\* \* \* \* \*