

(12) **United States Patent**
Young et al.

(10) **Patent No.:** **US 9,294,454 B2**
(45) **Date of Patent:** **Mar. 22, 2016**

(54) **ACTIVELY FEDERATED MOBILE AUTHENTICATION**

(71) Applicant: **Microsoft Corporation**, Redmond, WA (US)

(72) Inventors: **Kyle Stapley Young**, Duvall, WA (US); **Robert Aron Drollinger**, Redmond, WA (US); **Robert O'Brien**, Kirkland, WA (US); **David J. Runde**, Bellevue, WA (US); **Jagruti Dushyant Pandya**, Bellevue, WA (US); **Georges El Khoury**, Seattle, WA (US)

(73) Assignee: **MICROSOFT TECHNOLOGY LICENSING, LLC**, Redmond, WA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **13/893,029**

(22) Filed: **May 13, 2013**

(65) **Prior Publication Data**
US 2014/0282989 A1 Sep. 18, 2014

Related U.S. Application Data

(60) Provisional application No. 61/786,375, filed on Mar. 15, 2013.

(51) **Int. Cl.**
H04L 29/06 (2006.01)
H04L 29/08 (2006.01)

(52) **U.S. Cl.**
CPC **H04L 63/08** (2013.01); **H04L 63/0815** (2013.01); **H04L 63/0884** (2013.01); **H04L 67/02** (2013.01); **H04L 67/28** (2013.01); **H04L 2463/082** (2013.01)

(58) **Field of Classification Search**
CPC . H04L 63/08; H04L 63/0884; H04L 63/0815; H04L 67/28; H04L 67/02; H04L 2463/082
USPC 726/9
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

8,275,985 B1 * 9/2012 Narayanan et al. 713/160
8,316,443 B2 11/2012 Rits et al.

(Continued)

OTHER PUBLICATIONS

Oracle, "Introducing Communication Services," (Retrieved from http://docs.oracle.com/cd/E14148_02/wlcp/ocsg41_otn/archoverview/tpoverview.html on Mar. 14, 2013), 2008, (6 pages).

(Continued)

Primary Examiner — Joseph P Hirl


Assistant Examiner — J. Brant Murphy

(74) *Attorney, Agent, or Firm* — Thomas Marquis; Kate Drakos; Micky Minhas

(57) **ABSTRACT**

To make a trusted web service call, a client application sends a series of messages to obtain tokens that allow service requests to pass through a service relay. The user obtains a first security token by providing the user's credentials. A second token is obtained from a trust broker that validates the first token. Both tokens are then sent with a service request to a service relay. The service relay validates the second token and then passes the first token and the service request to a connector service. The connector service validates the first token and passes the service request to a target back end service. The connector service acts as the user when communicating with the back end service. Service responses are routed back to the user through the connector service and the service relay.

17 Claims, 6 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

8,321,909	B2	11/2012	Fot et al.	
2003/0112931	A1 *	6/2003	Brown et al.	379/93.23
2005/0273502	A1 *	12/2005	Patrick et al.	709/217
2008/0134295	A1 *	6/2008	Bailey et al.	G06F 21/41 726/4
2009/0254978	A1	10/2009	Rouskov et al.	
2010/0106965	A1 *	4/2010	Ross et al.	H04L 9/3213 713/156
2010/0299366	A1 *	11/2010	Stienhans et al.	707/803
2011/0010542	A1 *	1/2011	Choi et al.	H04L 9/3213 713/168
2011/0154435	A1 *	6/2011	Fot et al.	726/1
2011/0208366	A1 *	8/2011	Taft	700/295
2011/0307947	A1 *	12/2011	Kariv et al.	726/9
2011/0307948	A1 *	12/2011	Ranjan et al.	726/9
2011/0320366	A1 *	12/2011	Lalji et al.	705/301
2012/0182573	A1 *	7/2012	Mok	358/1.15
2012/0216268	A1 *	8/2012	Kassaei et al.	726/9
2012/0259748	A1	10/2012	Young et al.	
2014/0090037	A1 *	3/2014	Singh	H04L 63/0815 726/7

OTHER PUBLICATIONS

Centrify Corporation, "DirectControl's Integrated Support for Microsoft ADFS," (Retrieved from: <http://www.centrify.com/directcontrol/adfs.asp> on Mar. 15, 2013), 2004-2013, (2 pages).

Salvatori, Paolo, "Managing and Testing Topics, Queues and Relay Services with the Service Bus Explorer Tool," (Retrieved from <http://msdn.microsoft.com/en-us/library/windowsazure/hh532261.aspx> on May 13, 2013), Apr. 18, 2013, (99 pages).

Wrenn, George, "Secure SSO for Web Services," Information Security, Jan. 2004, (2 pages).

Microsoft Corporation, "Dynamics AX," (Retrieved from: <http://www.windowsphone.com/en-us/store/app/dynamics-ax/122b713d-a446-428a-b450-be041ec90340> on Mar. 14, 2013), Mar. 21, 2012, (2 pages).

Microsoft Corporation, "Dynamics AX," (Retrieved from: <http://www.windowsphone.com/en-us/store/app/dynamics-ax/cad689f0-7277-4739-a2a8-cfc882cee824> on Mar. 14, 2013), Feb. 26, 2013, (2 pages).

"International Search Report & Written Opinion for PCT Patent Application No. PCT/US2014/026926", Mailed Date: Jun. 18, 2014, Filed Date: Mar. 14, 2014, 12 Pages.

Baier, et al., "A Guide to Claims-Based Identity and Access Control, Authentication and Authorization for Services and the Web", Patterns and Practices for Microsoft Corporation Publication, Dec. 31, 2011, 400 Pages.

European Patent Office, "International Preliminary Report on Patentability Issued in PCT Application No. PCT/US2014/026926", Mailed Date: Jun. 24, 2015, 11 Pages.

Microsoft Corporation, "[MS-SPBEPO]: SharePoint Back-End Protocols Overview", Published on: Jul. 16, 2012, Available at: [download.microsoft.com/download/.../SharePoint/\[MS-SPBEPO2\].pdf](http://download.microsoft.com/download/.../SharePoint/[MS-SPBEPO2].pdf), 79 pages.

PCT, "Written Opinion of the International Preliminary Examining Authority," issued in PCT Application No. PCT/US2014/026926, Mailed Date: Feb. 23, 2015, 10 Pages.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7

1

ACTIVELY FEDERATED MOBILE AUTHENTICATION

CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims the benefit of the filing date of U.S. Provisional Patent Application No. 61/786,375 which is titled "Actively Federated Mobile Authentication" and was filed on Mar. 15, 2013, the disclosure of which is hereby incorporated by reference herein in its entirety.

BACKGROUND

Many businesses provide back office services, such as enterprise resource planning (ERP) and customer relationship management (CRM) applications, for employees. These applications typically use and store confidential and proprietary company information, such as financial data, contact information, and personnel files. Businesses limit access to these applications and the associated information to authorized users only.

When users are on-site, a business can authenticate users who access back office services via an enterprise network. However, when users are off-premises, it becomes more difficult to authenticate users and to provide services in a secure manner. To maintain security, users who need to access back office services via a mobile client, such as a smartphone or tablet, must be authenticated as authorized before being allowed to perform actions exposed by the services.

For example, many companies use expense reporting systems to reimburse employees for expenses which they incur for business purposes and time reporting systems to capture employee hours. One of the challenges for employees is tracking the various expenses incurred for business purposes and hours worked on company business, particularly when expenses are incurred when the employee is away from his or her computer. In prior systems, employees needed to use some other process, such as saving paper receipts and logging hours worked, to keep track of expenses and time. Those expenses were then added to an expense report, and the time entries filed on a time card.

SUMMARY

This Summary is provided to introduce a selection of concepts in a simplified form that are further described below in the Detailed Description. This Summary is not intended to identify key features or essential features of the claimed subject matter, nor is it intended to be used to limit the scope of the claimed subject matter.

To make a trusted web service call, a client application sends a series of messages to obtain security tokens that allow service requests to pass through a service relay. The user obtains a first token by providing the user's credentials. A second token is obtained from a trust broker that validates the first token. Both tokens are then sent with a service request to a service relay. The service relay validates the second token and then passes the first token and the service request to a connector service. The connector service validates the first token and passes the service request to a target back end service. The connector service acts as the user when communicating with the back end service. Service responses are routed back to the user through the connector service and the service relay.

For example, in one embodiment, the present invention helps solve the problem of capturing expenses that are

2

incurred and time worked when employees are traveling or otherwise away from their computer. A mobile phone application captures key expense information and associated receipts for expense reporting purposes. Employee time entries may also be captured. The expense (e.g., receipts) and time information are sent to a company's expense and time reporting systems through a mobile phone data connection. This helps the employee to easily capture the information while traveling or otherwise out of the office without needing to keep track of paper receipts, amounts paid in cash, or hours worked away from the office.

DRAWINGS

To further clarify the above and other advantages and features of embodiments of the present invention, a more particular description of embodiments of the present invention will be rendered by reference to the appended drawings. It is appreciated that these drawings depict only typical embodiments of the invention and are therefore not to be considered limiting of its scope. The invention will be described and explained with additional specificity and detail through the use of the accompanying drawings in which:

FIG. 1 illustrates components of a system that provides the ability for a mobile device to send and receive data to and from a back office service.

FIG. 2 illustrates the flow of messages in the system to allow mobile device to communicate with back office service in one embodiment.

FIG. 3 illustrates an example system in which a token from an online authorization service may be used to validate a service request.

FIG. 4 illustrates an alternative message flow that does not require the mobile device to directly contact the identity provider.

FIG. 5 is a flowchart illustrating a method or process for obtaining credentials by a mobile device to make web service calls access an enterprise service via a service relay.

FIG. 6 is a flowchart illustrating a method for processing service requests at a connector service in an enterprise network.

FIG. 7 illustrates an example of a computing and networking environment on which embodiments of the invention may be implemented.

DETAILED DESCRIPTION

Embodiments of the invention allow a user's identity information that is coupled with a web service call to flow from a service client, such as a client software application, on a mobile device to a back office system over a service relay.

FIG. 1 illustrates components of a system that provides the ability for a mobile device **101**, such as a smartphone or tablet, to send and receive data to and from a back office service **102**, such as an ERP or CRM system. Back office service **102** may be part of an enterprise network **103** that is protected by a firewall **104**. Instead of communicating with back office service **102** directly, mobile device **101** sends service requests through a globally available service relay **105**. Using the service relay **105** avoids the need to provide a public endpoint on enterprise network **103** or back end service **102**. Service relay **105** can communicate across firewall **104** and filters out unauthorized traffic that does not have the required security token.

An identity provider and security token service **106** is used to federate authentication and to provide credentials to authenticate the mobile device **101**. Identity provider **106** and

back office service **102** have a trust relationship **111**. The trust relationship allows two entities to cryptographically verify that a particular message originated from either entity. The trust relationship uses symmetric or asymmetric keys to confirm to the receiving entity that the contents of the received message have not been tampered with. Identity provider **106** can provide a token to mobile device **101** with a claim that is used to authenticate service requests sent by mobile device **101** through a service relay **105**. However, service relay **105** itself has no relationship with and does not know mobile device **101** or identity provider **106**, so service relay **105** will not simply pass service requests and tokens from mobile device **101** without further authentication.

Service relay **105** has a trust relationship **112** with online authorization service **107**. Service relay **105** and online authorization service **107** may be components of a cloud services environment **110**, for example. Online authorization service **107** is adapted to issue tokens to authenticate mobile device **101** to service relay **105**. If online authorization service **107** also has a trust relationship **113** with identity provider **106**, then the token from identity provider **106** will authenticate mobile device **101** to both back office service **102** and online authentication service **107**.

A service listening on service relay **105** receives a request **108a** from mobile device **101** and verifies mobile device **101**'s identity using the token from online authorization service **107**. To provide an additional layer of protection and flexibility for back office service **102**, service relay **105** does not communicate with back office service **102** directly. Instead, the authenticated service request **108b** is sent to a connector service **109** in enterprise network **103**. Connector service **109** then forwards the request **108c** to back office service **102**.

Mobile device **101** may run a client application that is adapted as appropriate for the operating system and/or browser used by the device. In the examples illustrated herein, actions taken by mobile device **101** are performed by or under the control of the client application. The client application is configured to communicate with the identity provider **106** and online authorization service **107** to obtain the appropriate tokens from the security token services. The client application also communicates with the service relay **105** to exchange service requests/responses and the tokens. Mobile device **101** may be any mobile device, such as a smartphone or tablet running a Microsoft Windows®, iOS, or Android operating system. The client application does not have to be on a mobile device. In other embodiments, the client application may be a Microsoft .NET software application, a service, a website, or any fixed or mobile point inside or outside the enterprise network **103** that can make a service request to back office service **102**.

FIG. 2 illustrates the flow of messages in the system to allow mobile device **101** to communicate with back office service **102** in one embodiment. Mobile device **101** first sends request for security token (RST) message **201** to identity provider **106**. The request **201** includes the user's credentials, such as a user name and password. Mobile device **101** and identity provider **106** may use a web service security protocol such as WS-Trust. The user's credentials, which are included in message **201**, are used by identity provider **106** to authenticate the user with back office service **102**. Identity provider **106** replies in message **202** with Token A, which may be a security assertion markup language (SAML) token, for example.

Token A will authenticate the mobile device **101** to back office service **102**; however, mobile device **101** must also be authenticated to service relay **105**. Mobile device **101** sends

the SAML Token A in request **203** to online authorization service **107**, which operates as a trust broker. Because online authorization service **107** and identity provider **106** have a trust relationship **113**, online authorization service **107** can verify, validate, and accept Token A and return a new Token B in reply **204**. Token B may be a simple web token (SWT), for example.

Mobile device **101** then sends a service request **205** and tokens A and B to service relay **105**. The service request may be any operation supported by back office service **102**. Token B provides service relay **105** with permission to allow the relay to occur. Service relay **105** then sends the service request **206** and Token A to connector service **109**, which validates and approves the user with Token A. Connector service **109** then sends the service request **207** to back office service **102** for processing. Connector service may act as a translation service that validates the service request, identifies the user, and then acts as the user (i.e., impersonates the user) vis-à-vis the back end service **102**. In this way, back end service **102** does not have to be concerned with authentication and does not need to know the client or the actual origin or source of a service request, and can process requests from a variety of different client platforms or implementations. As a corollary, the client does not need to know the back end service **102** or the actual destination of a service request. In this way, back office service **102** may actually be several different and possibly unrelated enterprise systems in other embodiments.

Back office service **102** sends a service response **208** to connector service **109**, which forwards the response **209** to service relay **105**. Mobile device **101** then receives the service response **210** from the service relay.

The client application on mobile device **101** is adapted to generate service requests appropriate to the back office service **102**. It will be understood that the back office service **102** may include any enterprise resource planning, customer relationship management, or other enterprise or back end service, including, for example, but not limited to, time capture, expense capture, project management, resource management, or approvals application, or other back-end system that exposes web services, which may be either SOAP or RESTful services, for example. In another embodiment, back office service **102** may be a collection of different systems having any such services. A group of systems may cooperatively provide a selected service to users through connector service **109**. Alternatively, a plurality of systems may provide different services to users through connector service **109**.

For example, cloud service environment **110** may be a Microsoft Windows Azure™ service wherein a Windows Azure™ Service Bus acts as service relay **105**, and a Windows Azure™ Access Control Service acts as online authorization service **107**. In other embodiments, cloud service environment **110** may be, for example, Amazon Web Services or any other distributed computing service having a service relay and any security token service that is compatible with the service relay and establishing trust with an identity provider. Although the online authorization service **107** is described as issuing a SWT token over the WRAP protocol, it will be understood that the online authorization service could issue any security token using any security protocol.

In an example embodiment, the identity provider **106** may be Microsoft's Active Directory with Active Directory Federation Services or any other identity provider and security token service. Although the identity provider **106** is described above as issuing a SAML token over the WS-Security &

5

WS-Trust protocol, it will be understood that the identity provider could issue any security token over any security protocol.

The service relay **105** hosts a middle tier service endpoint, which may be any relay service capable of hosting a web service endpoint and handling the token from the identity provider. In one embodiment, the web services utilize the HTTP protocol over SSL, although it will be understood that the service messages can use any transport protocol and associated transport-level security, such as Net.TCP.

In a SOAP-based service, the security tokens may be placed in the SOAP header or the HTTP header. In a REST-based service, a security token for authorizing with the service relay may be placed in the HTTP header as required and understood by service relay **105**, and the other token may be placed in the message body or the HTTP header.

Although connector service **109** is illustrated as using Token A to validate the service request from mobile device **101**, it will be understood that any token, including Token B from the online authorization service **107**, may be used to validate the service request. Accordingly, in another embodiment (illustrated in FIG. 3), if connector service **109** had a trust relationship **300** to online authorization service **107**, then Token B alone (i.e., without Token A) could be passed in message **206** along with the service request. In this scenario, connector service **109** would use the claim in Token B to validate the service request.

FIG. 3 illustrates an example system in which a token from an online authorization service **107**, such as a Windows Azure™ Access Control Service, may be used to validate a service request. Trust relationship **300** is established between connector service **109** and online authorization service **107**. When mobile device **101** needs to communicate with back office service **102**, it sends request for security token message **301** to identity provider **106**, which may include, for example, a user name and password or other credentials for mobile device **101**. Identity provider **106** replies in message **302** with Token A, such as a SAML token.

Mobile device **101** then sends the SAML Token A to online authorization service **107** in request **303**. Because online authorization service **107** and identity provider **106** have a trust relationship, online authorization service **107** can verify, validate, and accept Token A and return a new Token B in reply **304**, which may be a SWT token, for example. Token A is no longer needed because Token B can now be used to authenticate the mobile device **101** to back office service **102**. Additionally, Token B can be used to authenticate the mobile device **101** to service relay **105**.

Mobile device **101** sends a service request and Token B to service relay **105** in message **305**. The service request may be any operation supported by back office service **102**. Token B provides service relay **105** with permission to allow the relay to occur. Service relay **105** then sends the service request and Token B to connector service **109** in message **306**. Connector service **109** validates and approves the user with Token B. Connector service **109** then sends the service request **307** to back office service **102** for processing.

Back office service **102** sends a service response **308** to connector service **109**, which forwards the response **309** to service relay **105**. Mobile device **101** then receives the service response **310** from the service relay.

In one embodiment, the invention combines existing technologies into an authentication solution using an active federation pattern. In other embodiments, passive federation may be used. FIG. 4 illustrates an alternative message flow that does not require the mobile device to directly contact the identity provider **106**. Instead, the first message **401** request-

6

ing a security token goes from mobile device **101** to online authorization service **107**. In response, online authorization service **107** sends in message **402** a list of identity providers (IdP) for which service **107** has a trust relationship. Mobile device **101** selects one or more of the identity providers **403** that it recognizes and that will accept mobile device **101**'s credentials, such as identity provider **106**. The identity provider may be any WS-Trust, OpenID, or other identity provider, for example. Mobile device **101** instructs online authentication service **107** regarding which identity provider (e.g., security token service **106**) to use in message **403**. Mobile device **101** may provide user credentials in message **401** or message **403** or in another message.

In other embodiments, online authorization service **107** may send a redirect message to mobile client **101** to a web page hosted on identity provider **106** so that the client can securely enter their credentials without mobile client **101** or online authorization service **107** seeing the credentials.

Online authorization service **107** sends the user credentials to identity provider **106** in message **404** and requests a SAML or other token for validation with back office service **102**. Identity provider **106** validates the user credentials and then sends SAML Token A in message **405**. The online authentication server **107** validates token A and then generates a SWT Token B that is sent to the mobile device **101** in message **406** along with Token A. In other embodiments, only Token B is sent in message **406** and used for further authentication.

Mobile device **101** then sends a service request and tokens A and B in message **407** to service relay **105**. The service request may be any operation supported by back office service **102**. Token B provides service relay **105** with permission to allow the relay to occur. Service relay **105** then sends the service request and Token A in message **408** to connector service **109**, which validates the user with Token A. Connector service **109** then sends the service request in message **409** to back office service **102** for processing. Back office service **102** sends a service response **410** to connector service **109**, which forwards the response **411** to service relay **105**. Mobile device **101** then receives the service response **412** from the service relay.

FIG. 5 is a flowchart illustrating a method or process for a mobile device to obtain identity tokens in order to make trusted web service calls to access an enterprise service or back office service via a service relay. In step **501**, the mobile device provides user credentials to an identity provider to obtain a first token. The identity provider has an established trust relationship with the enterprise service. The token provides authentication for service requests received at the enterprise service. In step **502**, the mobile device receives the first token from the identity provider. The first token contains information (i.e., claims) about the user's identity (e.g., his or her username) to uniquely identify the user. In step **503**, the mobile device **101** provides the first token to a trust broker. The trust broker has an established trust relationship with a service relay and the identity provider.

In step **504**, the mobile device receives a second token from the trust broker in exchange for the first token. The second token provides authentication for the service relay. In step **505**, the mobile device sends a service request to the service relay with the first token and the second token.

The enterprise service may be a back office service that processes the service requests or a connector service that validates the service requests and passes the service requests to the back office service. The first token contains a representation of the user's identity in a claim (e.g., the username or other unique identifier) that allow the connector service to make web service calls to the back office service as if the

connector service was the user. The first token may be a SAML token, and the second token may be a SWT token.

FIG. 6 is a flowchart illustrating a method for processing service requests at a connector service in an enterprise network. In step 601, the connector service receives a service request and a token from a service relay. The service request is directed to a back office service in the enterprise network. The token comprises user credentials corresponding to a user who sent the service request. In step 602, the connector service validates the token and extracts claims representing the user's identity.

In step 603, the connector service uses the claims to communicate with the back office service in the user's place. In step 604, the connector service sends the service request to the back office service. In step 605, the connector service receives a response to the service request. The connector service sends the response to the service relay in step 606.

It will be understood that steps 501-504 of the process illustrated in FIG. 5 and steps 601-606 of the process illustrated in FIG. 6 may be executed simultaneously and/or sequentially. It will be further understood that each step may be performed in any order and may be performed once or repetitiously.

FIG. 7 illustrates an example of a suitable computing and networking environment 700 on which the examples of FIGS. 1-6 may be implemented. The computing system environment 700 is only one example of a suitable computing environment for mobile device 101 or for a server or computer that can run services 102, 105, 106, 107 or 109. FIG. 7 is not intended to suggest any limitation as to the scope of use or functionality of the invention. The invention is operational with numerous other general purpose or special purpose computing system environments or configurations. Examples of well-known computing systems, environments, and/or configurations that may be suitable for use with the invention include, but are not limited to: personal computers, server computers, hand-held or laptop devices, tablet devices, multiprocessor systems, microprocessor-based systems, set top boxes, programmable consumer electronics, network PCs, minicomputers, mainframe computers, distributed computing environments that include any of the above systems or devices, and the like.

The invention may be described in the general context of computer-executable instructions, such as program modules, being executed by a computer. Generally, program modules include routines, programs, objects, components, data structures, and so forth, which perform particular tasks or implement particular abstract data types. The invention may also be practiced in distributed computing environments where tasks are performed by remote processing devices that are linked through a communications network. In a distributed computing environment, program modules may be located in local and/or remote computer storage media including memory storage devices.

With reference to FIG. 7, an exemplary system for implementing various aspects of the invention may include a general purpose computing device in the form of a computer 700. Components may include, but are not limited to, various hardware components, such as processing unit 701, data storage 702, such as a system memory, and system bus 703 that couples various system components including the data storage 702 to the processing unit 701. The system bus 703 may be any of several types of bus structures including a memory bus or memory controller, a peripheral bus, and a local bus using any of a variety of bus architectures. By way of example, and not limitation, such architectures include Industry Standard Architecture (ISA) bus, Micro Channel Archi-

itecture (MCA) bus, Enhanced ISA (EISA) bus, Video Electronics Standards Association (VESA) local bus, and Peripheral Component Interconnect (PCI) bus also known as Mezzanine bus.

The computer 700 typically includes a variety of computer-readable media 704. Computer-readable media 704 may be any available media that can be accessed by the computer 700 and includes both volatile and nonvolatile media, and removable and non-removable media, but excludes propagated signals. By way of example, and not limitation, computer-readable media 704 may comprise computer storage media and communication media. Computer storage media includes volatile and nonvolatile, removable and non-removable media implemented in any method or technology for storage of information such as computer-readable instructions, data structures, program modules or other data. Computer storage media includes, but is not limited to, RAM, ROM, EEPROM, flash memory or other memory technology, CD-ROM, digital versatile disks (DVD) or other optical disk storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, or any other medium which can be used to store the desired information and which can be accessed by the computer 700. Communication media typically embodies computer-readable instructions, data structures, program modules or other data in a modulated data signal such as a carrier wave or other transport mechanism and includes any information delivery media. The term "modulated data signal" means a signal that has one or more of its characteristics set or changed in such a manner as to encode information in the signal. By way of example, and not limitation, communication media includes wired media such as a wired network or direct-wired connection, and wireless media such as acoustic, RF, infrared and other wireless media. Combinations of any of the above may also be included within the scope of computer-readable media. Computer-readable media may be embodied as a computer program product, such as software stored on computer storage media.

The data storage or system memory 702 includes computer storage media in the form of volatile and/or nonvolatile memory such as read only memory (ROM) and random access memory (RAM). A basic input/output system (BIOS), containing the basic routines that help to transfer information between elements within computer 700, such as during start-up, is typically stored in ROM. RAM typically contains data and/or program modules that are immediately accessible to and/or presently being operated on by processing unit 701. By way of example, and not limitation, data storage 702 holds an operating system, application programs, and other program modules and program data.

Data storage 702 may also include other removable/non-removable, volatile/nonvolatile computer storage media. By way of example only, data storage 702 may be a hard disk drive that reads from or writes to non-removable, nonvolatile magnetic media, a magnetic disk drive that reads from or writes to a removable, nonvolatile magnetic disk, or an optical disk drive that reads from or writes to a removable, nonvolatile optical disk such as a CD ROM or other optical media. Other removable/non-removable, volatile/nonvolatile computer storage media that can be used in the exemplary operating environment include, but are not limited to, magnetic tape cassettes, flash memory cards, digital versatile disks, digital video tape, solid state RAM, solid state ROM, and the like. The drives and their associated computer storage media, described above and illustrated in FIG. 7, provide storage of computer-readable instructions, data structures, program modules and other data for the computer 700.

A user may enter commands and information through a user interface **705** or other input devices such as a tablet, electronic digitizer, a microphone, keyboard, and/or pointing device, commonly referred to as mouse, trackball or touch pad. Other input devices may include a joystick, game pad, 5 satellite dish, scanner, or the like. Additionally, voice inputs, gesture inputs using hands or fingers, or other natural user interface (NUI) may also be used with the appropriate input devices, such as a microphone, camera, tablet, touch pad, glove, or other sensor. These and other input devices are often 10 connected to the processing unit **701** through a user input interface **705** that is coupled to the system bus **703**, but may be connected by other interface and bus structures, such as a parallel port, game port or a universal serial bus (USB). A monitor **706** or other type of display device is also connected 15 to the system bus **703** via an interface, such as a video interface. The monitor **706** may also be integrated with a touch-screen panel or the like. Note that the monitor and/or touch screen panel can be physically coupled to a housing in which the computing device **700** is incorporated, such as in a tablet-type personal computer. In addition, computers such as the computing device **700** may also include other peripheral output devices such as speakers and printer, which may be connected through an output peripheral interface or the like.

The computer **700** may operate in a networked or cloud-computing environment using logical connections **707** to one or more remote devices, such as a remote computer. The remote computer may be a personal computer, a server, a router, a network PC, a peer device or other common network node, and typically includes many or all of the elements described above relative to the computer **700**. The logical connections depicted in FIG. 7 include one or more local area networks (LAN) and one or more wide area networks (WAN), but may also include other networks. Such networking environments are commonplace in offices, enterprise-wide computer networks, intranets and the Internet. 25

When used in a networked or cloud-computing environment, the computer **700** may be connected to a public or private network through a network interface or adapter **707**. In some embodiments, a modem or other means for establishing communications over the network. The modem, which may be internal or external, may be connected to the system bus **703** via the network interface **707** or other appropriate mechanism. A wireless networking component such as comprising an interface and antenna may be coupled through a suitable device such as an access point or peer computer to a network. In a networked environment, program modules depicted relative to the computer **700**, or portions thereof, may be stored in the remote memory storage device. It may be appreciated that the network connections shown are exemplary and other means of establishing a communications link between the computers may be used. 40 45 50

Although the subject matter has been described in language specific to structural features and/or methodological acts, it is to be understood that the subject matter defined in the appended claims is not necessarily limited to the specific features or acts described above. Rather, the specific features and acts described above are disclosed as example forms of implementing the claims. 55

What is claimed is:

1. A method for making web service calls to a service on an enterprise network from a mobile device, comprising:
 providing user credentials to an identity provider to obtain a first security token, the identity provider having an established trust relationship with a trust broker and with an enterprise service, and the first security token config-

ured to provide authentication for service requests received at the enterprise service;
 providing a copy of the first security token to the trust broker, the trust broker having an established trust relationship with the service relay;
 receiving a second security token from the trust broker in response to providing the copy of the first security token, the second security token configured to provide authentication to the service relay using an additional form of authentication that is different than the first security token;
 sending a service request to the service relay, the service request comprising both the first security token and the second security token, wherein the second security token provides authentication to the service relay and provides permission for the service relay to forward the service request and the first security token to the enterprise service; and
 receiving a service response from the service relay in response to the enterprise service authenticating the mobile device using the first security token.
2. The method of claim **1**, wherein the enterprise network comprises a connector service exposing a web service endpoint for a back office service.
3. The method of claim **1**, wherein the enterprise network comprises a group of different systems cooperatively providing a single service.
4. The method of claim **1**, wherein the enterprise network comprises a group of different systems providing a plurality of different services.
5. The method of claim **1**, wherein the enterprise service is an enterprise resource planning application, and wherein the service request corresponds to a financial transaction initiated by the mobile device.
6. The method of claim **1**, wherein the enterprise service is an enterprise resource planning application, and wherein the service request corresponds to a time entry logged by the mobile device.
7. A mobile device for making web service calls to an enterprise service via a service relay, comprising:
 one or more processors;
 a memory coupled to the one or more processors, the memory storing one or more instructions executable by the one or more processors to cause the mobile device to:
 provide user credentials to an identity provider to obtain a first security token, the identity provider having an established trust relationship with a trust broker and with an enterprise service, and the first security token configured to provide authentication for service requests received at the enterprise service;
 provide a copy of the first security token to the trust broker, the trust broker having an established trust relationship with the service relay;
 receive a second security token from the trust broker in response to providing the copy of the first security token, the second security token configured to provide authentication to the service relay using an additional form of authentication that is different than the first security token;
 send a service request to the service relay, the service request comprising both the first security token and the second security token, wherein the second security token provides authentication to the service relay and provides permission for the service relay to forward the service request and the first security token to the enterprise service; and

11

receive a service response from the service relay in response to the enterprise service authenticating the mobile device using the first security token.

8. The mobile device of claim 7, wherein the enterprise service is a back office service that processes the service requests. 5

9. The mobile device of claim 7, wherein the enterprise service includes a connector service that validates service requests and passes the service requests to a back office service. 10

10. The mobile device of claim 9, wherein the first security token comprises user identification information that allows the connector service to make web service calls to the back office service as if the connector service was the user.

11. The mobile device of claim 7, wherein the enterprise service is a group of different systems providing a single service. 15

12. The mobile device of claim 7, wherein the enterprise service is a group of different systems providing a plurality of different services. 20

13. A memory device having program instructions stored thereon that, upon execution by a mobile device, cause the mobile device to:

provide user credentials to an identity provider to obtain a first security token, the identity provider having an established trust relationship with a trust broker and with an enterprise service, and the first security token configured to provide authentication for service requests received at the enterprise service; 25

provide the first security token to the trust broker, the trust broker having an established trust relationship with the service relay; 30

12

receive a second security token from the trust broker in response to providing the copy of the first security token, the second security token configured to provide authentication to the service relay using an additional form of authentication that is different than the first security token;

send a service request to the service relay, the service request comprising both the first security token and the second security token, wherein the second security token provides authentication to the service relay and provides permission for the service relay to forward the service request and the first security token to the enterprise service; and

receive a service response from the service relay in response to the enterprise service authenticating the mobile device using the first security token.

14. The memory device of claim 13, wherein the enterprise network comprises a group of different systems cooperatively providing a single service. 20

15. The memory device of claim 13, wherein the enterprise network comprises a group of different systems providing a plurality of different services.

16. The memory device of claim 13, wherein the enterprise network comprises an enterprise resource planning application, and wherein the service request corresponds to a financial transaction initiated by the user on the mobile device.

17. The memory device of claim 13, wherein enterprise network comprises an enterprise resource planning application, and wherein the service request corresponds to a time entry logged by the user on the mobile device.

* * * * *