

US009297342B2

(12) **United States Patent**
McAlister

(10) **Patent No.:** **US 9,297,342 B2**
(45) **Date of Patent:** **Mar. 29, 2016**

(54) **METHOD AND SYSTEM OF THERMOCHEMICAL REGENERATION TO PROVIDE OXYGENATED FUEL, FOR EXAMPLE, WITH FUEL-COOLED FUEL INJECTORS**

C01B 3/32 (2013.01); *C01B 3/34* (2013.01);
F02M 21/0206 (2013.01); *F02M 21/0227*
(2013.01); *F02M 21/0254* (2013.01); *F02M*
21/0266 (2013.01); *F02M 21/0287* (2013.01);
F02M 27/02 (2013.01); *F02M 51/066*
(2013.01);

(71) Applicant: **McAlister Technologies, LLC**, Phoenix, AZ (US)

(Continued)

(72) Inventor: **Roy Edward McAlister**, Phoenix, AZ (US)

(58) **Field of Classification Search**

CPC *F02M 51/0625*; *F02M 51/066*; *F02M*
51/0685
USPC 123/297, 541, 499, 498, 490;
239/132.5, 132, 132.1, 132.3, 102.2,
239/585.1

(73) Assignee: **McAlister Technologies, LLC**, Phoenix, AZ (US)

See application file for complete search history.

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,391,680 A * 7/1968 Benson 123/297
4,116,389 A * 9/1978 Furtah et al. 239/132.5

(Continued)

Primary Examiner — Mahmoud Gimie

(21) Appl. No.: **14/043,644**

(22) Filed: **Oct. 1, 2013**

(74) *Attorney, Agent, or Firm* — Perkins Coie LLP

(65) **Prior Publication Data**

US 2014/0245990 A1 Sep. 4, 2014

(57) **ABSTRACT**

The present disclosure is directed to integrated injector/igniters providing efficient injection, ignition, and complete combustion of various types of fuels. One example of such an injector/igniter can include a body having a base portion opposite a nozzle portion. The base portion receives the fuel into the body and the nozzle portion can be positioned adjacent to the combustion chamber. The injector further includes a valve carried by the nozzle portion that is movable between a closed position and an open position to inject the fuel into the combustion chamber. An actuator is coupled the valve and extends longitudinally through the body towards the base portion, and a driver is carried by the body and is movable between a first position and a second position. Thermochemical regeneration of waste heat produced by combustion and associated combustion events is captured and invested in endothermic reactions to improve efficiency of the combustion event. Hydrogen characterized fuel may be used as a heat sink.

Related U.S. Application Data

(60) Continuation of application No. 12/804,509, filed on Jul. 21, 2010, now Pat. No. 8,561,598, which is a continuation-in-part of application No. 12/581,825, filed on Oct. 19, 2009, now Pat. No. 8,297,254, which

(Continued)

(51) **Int. Cl.**


F02M 51/06 (2006.01)
F02M 27/02 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC *F02M 51/06* (2013.01); *B01J 4/002*
(2013.01); *B01J 12/007* (2013.01); *B01J*
19/127 (2013.01); *B01J 19/2475* (2013.01);
C01B 3/047 (2013.01); *C01B 3/24* (2013.01);

20 Claims, 6 Drawing Sheets



Related U.S. Application Data

is a division of application No. 12/006,774, filed on Jan. 7, 2008, now Pat. No. 7,628,137, said application No. 12/804,509 is a continuation-in-part of application No. 12/653,085, filed on Dec. 7, 2009, now Pat. No. 8,635,985, which is a continuation-in-part of application No. 12/006,774, filed on Jan. 7, 2008, now Pat. No. 7,628,137, said application No. 12/804,509 is a continuation-in-part of application No. PCT/US2009/067044, filed on Dec. 7, 2009.

- (60) Provisional application No. 61/237,425, filed on Aug. 27, 2009, provisional application No. 61/237,479, filed on Aug. 27, 2009, provisional application No. 61/237,466, filed on Aug. 27, 2009, provisional application No. 61/312,100, filed on Mar. 9, 2010, provisional application No. 61/304,403, filed on Feb. 13, 2010.

(51) **Int. Cl.**

<i>F02M 57/06</i>	(2006.01)
<i>F02M 21/02</i>	(2006.01)
<i>B01J 12/00</i>	(2006.01)
<i>B01J 19/24</i>	(2006.01)
<i>B01J 4/00</i>	(2006.01)
<i>C01B 3/32</i>	(2006.01)
<i>C01B 3/34</i>	(2006.01)
<i>C01B 3/04</i>	(2006.01)
<i>C01B 3/24</i>	(2006.01)
<i>B01J 19/12</i>	(2006.01)
<i>F02B 75/12</i>	(2006.01)

(52) **U.S. Cl.**

CPC *F02M 51/0625* (2013.01); *F02M 51/0671* (2013.01); *F02M 57/06* (2013.01); *B01J 2219/00087* (2013.01); *B01J 2219/00135* (2013.01); *B01J 2219/00157* (2013.01); *B01J 2219/00159* (2013.01); *C01B 2203/0211* (2013.01); *C01B 2203/0216* (2013.01); *C01B 2203/0266* (2013.01); *C01B 2203/061* (2013.01); *C01B 2203/085* (2013.01); *C01B 2203/0811* (2013.01); *C01B 2203/12* (2013.01); *C01B 2203/1211* (2013.01); *C01B 2203/1241* (2013.01); *F02B 2075/125* (2013.01); *Y02E 60/364* (2013.01); *Y02P 20/129* (2015.11); *Y02P 20/133* (2015.11); *Y02P 20/134* (2015.11); *Y02T 10/123* (2013.01); *Y02T 10/16* (2013.01); *Y02T 10/32* (2013.01)

(56)

References Cited

U.S. PATENT DOCUMENTS

4,700,891	A *	10/1987	Hans et al.	239/132.5
4,810,985	A *	3/1989	Mesenich	335/261
5,069,189	A *	12/1991	Saito	123/533
5,343,699	A *	9/1994	McAlister	60/273
5,983,855	A *	11/1999	Benedikt et al.	123/297
6,000,628	A *	12/1999	Lorraine	239/87
6,318,306	B1 *	11/2001	Komatsu	123/3
6,619,269	B1 *	9/2003	Stier et al.	123/490
7,886,993	B2 *	2/2011	Bachmaier et al.	239/102.2
2003/0042325	A1 *	3/2003	D'Arrigo	239/102.2
2005/0017096	A1 *	1/2005	Bachmaier et al.	239/584

* cited by examiner




Fig. 1A




Fig. 1B




Fig. 2





Fig. 3B




Fig. 3C




Fig. 4




Fig. 6

1

**METHOD AND SYSTEM OF
THERMOCHEMICAL REGENERATION TO
PROVIDE OXYGENATED FUEL, FOR
EXAMPLE, WITH FUEL-COOLED FUEL
INJECTORS**

CROSS-REFERENCE TO RELATED
APPLICATION(S)

The present application is a continuation of U.S. patent application Ser. No. 12/804,509, filed Jul. 21, 2010 titled METHOD AND SYSTEM OF THERMOCHEMICAL REGENERATION TO PROVIDE OXYGENATED FUEL, FOR EXAMPLE, WITH FUEL-COOLED FUEL INJECTORS, which claims priority to and the benefit of U.S. Provisional Application No. 61/237,425, filed Aug. 27, 2009 and titled OXYGENATED FUEL PRODUCTION; U.S. Provisional Application No. 61/237,466, filed Aug. 27, 2009 and titled MULTIFUEL MULTIBURST; U.S. Provisional Application No. 61/237,479, filed Aug. 27, 2009 and titled FULL SPECTRUM ENERGY; U.S. Provisional Application No. 61/304,403, filed Feb. 13, 2010 and titled FULL SPECTRUM ENERGY AND RESOURCE INDEPENDENCE; and U.S. Provisional Application No. 61/312,100, filed Mar. 9, 2010 and titled SYSTEM AND METHOD FOR PROVIDING HIGH VOLTAGE RF SHIELDING, FOR EXAMPLE, FOR USE WITH A FUEL INJECTOR. U.S. patent application Ser. No. 12/804,509 is a continuation-in-part of PCT Application No. PCT/US09/67044, filed Dec. 7, 2009 and titled INTEGRATED FUEL INJECTORS AND IGNITERS AND ASSOCIATED METHODS OF USE AND MANUFACTURE which claims priority to and the benefit of U.S. Provisional Application No. 61/237,466, filed Aug. 28, 2009 and titled MULTIFUEL MULTIBURST. U.S. patent application Ser. No. 12/804,509 is a continuation-in-part of U.S. patent application Ser. No. 12/653,085, filed Dec. 7, 2009 and titled INTEGRATED FUEL INJECTORS AND IGNITERS AND ASSOCIATED METHODS OF USE AND MANUFACTURE; which is a continuation-in-part of U.S. patent application Ser. No. 12/006,774 (now U.S. Pat. No. 7,628,137), filed Jan. 7, 2008 and titled MULTIFUEL STORAGE, METERING, AND IGNITION SYSTEM; and which claims priority to and the benefit of U.S. Provisional Application No. 61/237,466, filed Aug. 27, 2009 and titled MULTIFUEL MULTIBURST. U.S. patent application Ser. No. 12/804,509 is a continuation-in-part of U.S. patent application Ser. No. 12/581,825, filed Oct. 19, 2009 and titled MULTIFUEL STORAGE, METERING, AND IGNITION SYSTEM; which is a divisional of U.S. patent application Ser. No. 12/006,774 (now U.S. Pat. No. 7,628,137), filed Jan. 7, 2008 and titled MULTIFUEL STORAGE, METERING, AND IGNITION SYSTEM. Each of these applications is incorporated herein by reference in its entirety.

TECHNICAL FIELD

The following disclosure relates generally to integrated fuel injectors and igniters and associated components for directly injecting and igniting various fuels in a combustion chamber using thermochemical regeneration and more specifically, using fuel to cool the injector assembly during operation.

BACKGROUND

Fuel injection systems are typically used to inject a fuel spray into an inlet manifold or a combustion chamber of an

2

engine. Fuel injection systems have become the primary fuel delivery system used in automotive engines, having almost completely replaced carburetors since the late 1980s. Fuel injectors used in these fuel injection systems are generally capable of two basic functions. First, they deliver a metered amount of fuel for each inlet stroke of the engine so that a suitable air-fuel ratio can be maintained for the fuel combustion. Second they disperse the fuel to improve the efficiency of the combustion process. Conventional fuel injection systems are typically connected to a pressurized fuel supply, and the fuel can be metered into the combustion chamber by varying the time for which the injectors are open. The fuel can also be dispersed into the combustion chamber by forcing the fuel through a small orifice in the injectors.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1A is a schematic cross-sectional side view of an injector configured in accordance with an embodiment of the disclosure.

FIG. 1B is a cross-sectional side view of an injector configured in accordance with another embodiment of the disclosure.

FIG. 2 is a cross-sectional side partial view of an injector configured in accordance with another embodiment of the disclosure.

FIG. 3A is an isometric view of a component of the injector of FIGS. 1B and 2.

FIG. 3B is a cross-sectional side view taken substantially along the lines 3B-3B of FIG. 3A, and FIG. 3C is cross-sectional side view taken substantially along the lines 3C-3C of FIG. 3A.

FIG. 4 is a cross-sectional view of an illustrative embodiment in accordance with the disclosure.

FIG. 5 is a schematic cross-sectional view of a system in accordance with the disclosure.

FIG. 6 is a schematic view of an alternative system in accordance with the disclosure.

DETAILED DESCRIPTION

The present application incorporates by reference in their entirety the subject matter of each of the following U.S. Patent Applications, filed concurrently herewith on Jul. 21, 2010: U.S. patent application Ser. No. 12/841,170, now U.S. Pat. No. 8,555,860, and titled INTEGRATED FUEL INJECTORS AND IGNITERS AND ASSOCIATED METHODS OF USE AND MANUFACTURE; U.S. patent application Ser. No. 12/804,510, now U.S. Pat. No. 8,074,625, and titled FUEL INJECTOR ACTUATOR ASSEMBLIES AND ASSOCIATED METHODS OF USE AND MANUFACTURE; U.S. patent application Ser. No. 12/841,146, now U.S. Pat. No. 8,413,634, and titled INTEGRATED FUEL INJECTORS AND IGNITERS WITH CONDUCTIVE CABLE ASSEMBLIES; U.S. patent application Ser. No. 12/841,149, now U.S. Pat. No. 8,365,700, and titled SHAPING A FUEL CHARGE IN A COMBUSTION CHAMBER WITH MULTIPLE DRIVERS AND/OR IONIZATION CONTROL; U.S. patent application Ser. No. 12/841,135, now U.S. Pat. No. 8,192,852, and titled CERAMIC INSULATOR AND METHODS OF USE AND MANUFACTURE THEREOF; and U.S. patent application Ser. No. 12/804,508, now U.S. Pat. No. 8,387,599, and titled METHODS AND SYSTEMS FOR REDUCING THE FORMATION OF OXIDES OF NITROGEN DURING COMBUSTION IN ENGINES.

Overview

FIG. 1A is a schematic cross-sectional side view of an integrated injector/igniter **110a** (“injector **110a**”) configured in accordance with an embodiment of the disclosure. The injector **110a** illustrated in FIG. 1A is configured to inject different fuels into a combustion chamber **104a** and to be controlled to adaptively adjust the pattern and/or frequency of the fuel injections or bursts based on combustion properties and conditions in the combustion chamber **104a**. As explained in detail below, the injector **110a** and other injectors described herein can optimize the injected fuel for rapid ignition and complete combustion. In addition to injecting the fuel, the injector **110a** includes one or more integrated ignition features that are configured to ignite the injected fuel. As such, the injector **110a** can be utilized to convert conventional internal combustion engines to be able to operate on multiple different fuels. Although several of the features of the illustrated injector **110a** are shown schematically for purposes of illustration, several of these schematically illustrated features are described in detail below with reference to various features of embodiments of the disclosure. Accordingly, the relative location, position, size, orientation, etc. of the schematically illustrated components of the injector in FIG. 1A are not intended to limit the present disclosure.

In the illustrated embodiment, the injector **110a** includes a casing or body **112a** having a middle portion **116a** extending between a base portion **114a** and a nozzle portion **118a**. The nozzle portion **118a** extends at least partially through a port in an engine head **107a** to position an end portion **119a** of the nozzle portion **118a** at the interface with the combustion chamber **104a**. The injector **110a** further includes a fuel passage or channel **123a** extending through the body **112a** from the base portion **114a** to the nozzle portion **118a**. The channel **123a** is configured to allow fuel to flow through the body **112a**. The channel **123a** is also configured to allow other components, such as an actuator **122a**, to pass through the body **112a**, as well as instrumentation components and/or energy source components of the injector **110a**. In certain embodiments, the actuator **122a** can be a cable or rod that has a first end portion that is operatively coupled to a flow control device or valve **120a** carried by the end portion **119a** of the nozzle portion **118a**. The actuator **122a** can be integral with the valve **120a** or a separate component that is attached to the valve **120a**. As such, the flow valve **120a** is positioned proximate to the interface with the combustion chamber **104a**. Although not shown in FIG. 1A, in certain embodiments the injector **110a** can include more than one flow valve, as well as one or more check valves positioned proximate to the combustion chamber **104a**, as well as at other locations on the body **112a**.

According to another feature of the illustrated embodiment, the actuator **122a** also includes a second end portion operatively coupled to a plunger or driver **124a**. The second end portion can further be coupled to a controller or processor **126a**. The controller or processor **126a** can be positioned on the injector **110a** or remotely from the injector **110a**. As explained in detail below with reference to various embodiments of the disclosure, the controller **126a** and/or the driver **124a** are configured to rapidly and precisely actuate the actuator **122a** to inject fuel into the combustion chamber **104a** via the flow valve **120a**. For example, in certain embodiments, the flow valve **120a** can move outwardly (e.g., toward the combustion chamber **104a**) and in other embodiments the flow valve **120a** can move inwardly (e.g., away from the combustion chamber **104a**) to meter and control injection of the fuel. Moreover, in certain embodiments, the driver **124a** can tension the actuator **122a** to retain the flow valve **120a** in

a closed or seated position, and the driver **124a** can relax or relieve the tension in the actuator **122a** to allow the flow valve **120a** to inject fuel, and vice versa. The driver **124a** can be responsive to the controller **126a** as well as other force-inducing components (e.g., acoustic, electromagnetic and/or piezoelectric components) to achieve the desired frequency and pattern of the injected fuel bursts.

In certain embodiments, the actuator **122a** can include one or more integrated sensing and/or transmitting components to detect combustion chamber properties and conditions. For example, the actuator **122a** can be formed from fiber optic cables, insulated transducers integrated within a rod or cable, or can include other sensors to detect and communicate combustion chamber data. Although not shown in FIG. 1A, in other embodiments, and as described in detail below, the injector **110a** can include other sensors or monitoring instrumentation located at various positions on the injector **110a**. For example, the body **112a** can include optical fibers integrated into the material of the body **112a**, or the material of the body **112a** itself can be used to communicate combustion data to one or more controllers. In addition, the flow valve **120a** can be configured to sense or carry sensors in order to transmit combustion data to one or more controllers associated with the injector **110a**. This data can be transmitted via wireless, wired, optical or other transmission mediums to the controller **126a** or other components. Such feedback enables extremely rapid and adaptive adjustments for optimization of fuel injection factors and characteristics including, for example, fuel delivery pressure, fuel injection initiation timing, fuel injection durations for production of multiple layered or stratified charges, the timing of one, multiple or continuous plasma ignitions or capacitive discharges, etc.

Such feedback and adaptive adjustment by the controller **126a**, driver **124a**, and/or actuator **122a** also allows optimization of outcomes such as power production, fuel economy, and minimization or elimination of pollutive emissions including oxides of nitrogen. U.S. Patent Application Publication No. 2006/0238068, which is incorporated herein by reference in its entirety, describes suitable drivers for actuating ultrasonic transducers in the injector **110a** and other injectors described herein.

The injector **110a** can also optionally include an ignition and flow adjusting device or cover **121a** (shown in broken lines in FIG. 1A) carried by the end portion **119a** adjacent to the engine head **107a**. The cover **121a** at least partially encloses or surrounds the flow valve **120a**. The cover **121a** may also be configured to protect certain components of the injector **110a**, such as sensors or other monitoring components. The cover **121a** can also act as a catalyst, catalyst carrier and/or first electrode for ignition of the injected fuels. Moreover, the cover **121a** can be configured to affect the shape, pattern, and/or phase of the injected fuel. The flow valve **120a** can also be configured to affect these properties of the injected fuel. For example, in certain embodiments the cover **121a** and/or the flow valve **120a** can be configured to create sudden gasification of the fuel flowing past these components. More specifically, the cover **121a** and/or the flow valve **120a** can include surfaces having sharp edges, catalysts, or other features that produce gas or vapor from the rapidly entering liquid fuel or mixture of liquid and solid fuel. The acceleration and/or frequency of the flow valve **120a** actuation can also suddenly gasify the injected fuel. In operation, this sudden gasification causes the vapor or gas emitted from the nozzle portion **118a** to more rapidly and completely combust. Moreover, this sudden gasification may be used in various combinations with super heating liquid fuels and plasma or acoustical impetus of projected fuel bursts. In still

5

further embodiments, the frequency of the flow valve **120a** actuation can induce plasma projection to beneficially affect the shape and/or pattern of the injected fuel. U.S. Pat. No. 4,122,816, which is incorporated herein by reference in its entirety, describes suitable drivers for actuating plasma projection by injector **110a** and other injectors described herein.

According to another aspect of the illustrated embodiment, and as described in detail below, at least a portion of the body **112a** is made from one or more dielectric materials **117a** suitable to enable the high energy ignition to combust different fuels, including unrefined fuels or low energy density fuels. These dielectric materials **117a** can provide sufficient electrical insulation of the high voltage for the production, isolation, and/or delivery of spark or plasma for ignition. In certain embodiments, the body **112a** can be made from a single dielectric material **117a**. In other embodiments, however, the body **112a** can include two or more dielectric materials. For example, at least a segment of the middle portion **116a** can be made from a first dielectric material having a first dielectric strength, and at least a segment of the nozzle portion **118a** can be made from a dielectric material having a second dielectric strength that is greater than the first dielectric strength. With a relatively strong second dielectric strength, the second dielectric can protect the injector **110a** from thermal and mechanical shock, fouling, voltage tracking, etc. Examples of suitable dielectric materials, as well as the locations of these materials on the body **112a**, are described in detail below.

In addition to the dielectric materials, the injector **110a** can also be coupled to a power or high voltage source to generate the ignition event to combust the injected fuels. The first electrode can be coupled to the power source (e.g., a voltage generation source such as a capacitance discharge, induction, or piezoelectric system) via one or more conductors extending through the injector **110a**. Regions of the nozzle portion **118a**, the flow valve **120a**, and/or the cover **121a** can operate as a first electrode to generate an ignition event (e.g., spark, plasma, compression ignition operations, high energy capacitance discharge, extended induction sourced spark, and/or direct current or high frequency plasma, in conjunction with the application of ultrasound to quickly induce, impel, and complete combustion) with a corresponding second electrode of the engine head **107a**. As explained in detail below, the first electrode can be configured for durability and long service life. In still further embodiments of the disclosure, the injector **110a** can be configured to provide energy conversion from combustion chamber sources and/or to recover waste heat or energy via thermochemical regeneration to drive one or more components of the injector **110** from the energy sourced by the combustion events.

The features of the injector **110a** described above with reference to FIG. 1A can be included in any of the embodiments described below with reference to FIGS. 1B-9.

Additional Embodiments of Integrated Fuel Injectors and Igniters and Associated Components

FIG. 1B is a cross-sectional side view of an injector **100** configured in accordance with an embodiment of the disclosure that includes combined fuel injection and ignition features. As described in detail below, the illustrated embodiment of the injector **100** includes an electromagnetic actuator assembly and corresponding valve assembly that provide a rugged and versatile yet inexpensive assembly for precisely metering fuel to achieve the desired fuel flow characteristics. In the illustrated embodiment, the injector **100** includes several features that are generally similar in structure and function to the corresponding features of the injector **110a** described above with reference to FIG. 1A. For example, the

6

injector **100** includes a nozzle portion **102** opposite a base portion **104**. The nozzle portion **102** is configured to at least partially extend through a port in an engine head to position the end of the nozzle portion **102** at an interface with a combustion chamber. As described in detail below, the base portion **104** is configured to receive one or more fuels from a fuel source (e.g., a pressurized fuel source), and the nozzle portion **102** is configured to deliver and/or precisely meter the fuel into the combustion chamber through a fuel exit passage **103**.

In the illustrated embodiment, the injector **100** includes a force generator **106** that actuates a plunger or driver **108** to in turn move a valve assembly **110**. The force generator **106** is positioned within a bobbin or housing **109**, such as a conductive metallic casing. Suitable materials for the force generator bobbin or housing **109** include, for example, beryllia and various graphite, silver, and/or aluminum filled polymers that are designed to enhance heat transfer. The force generator **108** and/or the housing **109** can also be coupled to voltage source or other suitable energy source **111**, as well as a controller. In certain embodiments, the force generator **106** can be solenoid winding that is an electromagnetic force generator, a piezoelectric force generator, or other suitable type of force generator for moving the driver **108**.

In accordance with aspects of this disclosure, the solenoid winding may be incorporated in a circuit to serve as an electromagnet for operation of armature and valve actuation and additionally as a transformer such as a pulse transformer, transformer with multiple windings, or autotransformer for generating spark or plasma discharges at the interface to the combustion chamber. In other instances it is desired to provide a solenoid winding comprising multiple insulated conductors for the purpose of increasing the number of turns and current magnitude for greater magnetic circuit strength when energized and to thus develop increased magnetic force and decrease the pull-in time for rapid operation of an actuator. Various materials such as polyimide, polyetherimide, parylene, various modified chemical vapor deposited poly (p-xylene) films, glass ceramics, including micro and nano particles including the dielectric systems disclosed in copending US patent application Entitled "Integrated Fuel Injectors and Igniters and Associated Methods of Use and Manufacture," U.S. patent application Ser. No. 12/653,085 (the '085 application), are used to insulate the conductor windings and enable voltage transformation whereby the multiple windings are energized for very rapid pull in, and at least one winding portion is then switched to serve as the secondary of a transformer circuit to provide the turns ratio and induction desired for the spark or plasma developed at the combustion chamber interface for ignition.

The valve assembly **110** includes an actuator **112** (e.g., a cable, stiffened cable, rod, valve extension, etc.) having a flow valve **114** at the nozzle portion **102**, and an actuator stop **116** at the base portion **104** opposite the nozzle portion **102**. In certain embodiments, the flow valve **114** can be integrally formed with the actuator **112**. In other embodiments, however, the flow valve **114** can be separate from and attached to the actuator **112**. Moreover, in certain embodiments the stop **116** can be a wire, such as a constrictive spring wire, that is attached to the second end portion of the actuator **112**. For example, the stop **116** can be at least partially embedded in an annular groove in the actuator **112**, the annular groove having a depth of at least approximately 50% of the diameter of the motion stop **116**. In other embodiments, however, the stop **116** and other actuator stops disclosed herein can be any other type of protrusion on the actuator **112** that is attached to or integrally formed with the actuator **112**. The stop **116** is

positioned on the actuator **112** to contact a contact surface **113** of the driver **108** when the force generator **106** actuates the driver **108** to move the actuator **112** and consequently open the flow valve **114**.

In the closed position the flow valve **114** rests against a valve seat **122** in the nozzle portion **102**. In certain embodiments, the surface of the flow valve **114** that contacts the valve seat **122** can be a generally spherical or conical surface that is fine finished or polished for sealing against the valve seat **122**. The nozzle portion **102** can also include a biasing or attractive element **124**, such as a magnet, permanent magnet, etc., that attracts the driver **108** towards the nozzle portion **102** to at least partially retain the valve **114** in the closed position against the valve seat **122**. For example, the attractive element **124** can be coupled to a controller or computer and selectively attract the driver **108** towards the nozzle portion **102**. In other embodiments, actuation of the driver **108** can overcome the attractive force of the attractive element **124**. As described in detail below, the valve **114** can also be retained in the closed position with other biasing components and/or fuel pressure within the injectors **100**.

The driver **108** is positioned in a driver cavity **118** in the injector **100** to allow the driver **108** to move longitudinally through the injector **100** in response to excitation from the force generator **106**. Moreover, the actuator **112** is positioned in an actuator cavity or opening **120** extending longitudinally through the driver **108**. The actuator opening **120** thereby allows the driver **108** to move longitudinally in the injector **100** with reference to the actuator **112** until the driver **108** contacts the actuator stop **116**. In the illustrated embodiment, the driver **108** also includes a fuel cavity **126** extending longitudinally therethrough and spaced radially apart from the actuator opening **120**. The fuel cavity **126** is fluidly coupled to a fuel passageway or channel **128** in the base portion **104**. The fuel channel **128** is also coupled to a fuel conduit **136**, which is in turn coupled to a fuel source, such as a pressurized fuel source. In certain embodiments, the fuel conduit **136** can include a fuel filter **142** configured to filter or otherwise condition the fuel prior to entering the body of the injector **100**.

In the illustrated embodiment, the base portion **102** also includes a biasing member **130** (e.g., a spring such as a coiled compression spring) positioned in the fuel channel **128**. The biasing member **130** contacts a first biasing surface **132** of the driver **108**, as well as a second biasing surface **134** of the fuel channel **128**. In this manner, the biasing member **130** urges the driver **108** towards the nozzle portion **102** to retain the actuator **112** and corresponding flow valve **114** in the closed position.

The force generator housing **109** is coupled to a first end cap **137** at the base portion **104**, and a second end cap **138** at the nozzle portion **102**. The housing **109** can be attached (e.g., hermetically sealed via soldering, brazing, welding, structurally adhesive sealing, etc.) to each of the first and second end caps **137**, **138** to prevent fuel from escaping from the injector **100**. Seals **140**, such as o-rings, can also be used to maintain a fluid tight connection between the housing **109** and the first and second end caps **137**, **138**.

According to another aspect of the illustrated embodiment, an end portion **144** of the driver **108** in the base portion **104** has a generally conical or frustoconical shape. More specifically, the end portion **144** of the driver **108** has an outer end surface **146** that has a generally conical or frustoconical shape. The outer end surface **146** of the driver **108** is spaced apart from a corresponding contact surface **148** of the first end cap **137** having a matching contour or shape. When the flow valve **114** is in the closed position against the valve seat **122**

and the driver **108** is in a relaxed or non-actuated state, the outer end surface **146** is spaced apart from the contact surface **148** of the end cap **137** by a first distance D_1 . In addition, at this position the contact surface **113** of the driver **108** is spaced apart from the stop **116** on the actuator **112** by a second distance D_2 . The second distance D_2 accordingly allows the driver **108** to gain momentum before striking the stop **116** of the actuator **112**. For example, the first distance D_1 is the total distance that the driver **108** travels to move the flow valve **114** via the actuator **112** to open the flow valve **114**. More specifically, first distance D_1 is at least approximately equal to the second distance D_2 plus the distance that the flow valve **114** moves to be sufficiently spaced apart from the valve seat **122** to inject the fuel into the combustion chamber. In one embodiment, the second distance D_2 can be between approximately 10% to 40% of the first distance D_1 . In other embodiments, however, the second distance D_2 can be less than 10% or greater than 40% of first distance D_1 . In still other embodiments, the second distance D_2 can be eliminated from the injector **100** such that the driver **108** contacts the actuator stop **116** when the valve is in the closed position.

In operation, the fuel conduit **136** introduces fuel through the fuel filter **142** into the base portion **104** of the injector **100**. As the fuel flows through the injector **100**, a controller can precisely power the force generator **106** to actuate the driver **108**, which in turn moves the actuator **112** to lift the flow valve **114** off of the valve seat **122** (i.e., to move the flow valve **114** inwardly). The actuated driver **108** can accordingly overcome the biasing force of the biasing member **130** and/or the attractive element **124** to move away from the nozzle portion **102**. Moreover, the illustrated embodiment allows for operation of the flow valve **114** at relatively high pressure differentials by allowing the driver **108** to gain considerable momentum and associated kinetic energy while moving the second distance D_2 prior to impacting the actuator stop **116** to move the valve **114**. As such, the driver **108** can overcome a considerable pressure gradient to move the flow valve **114**. In embodiments where the second distance D_2 is eliminated, the driver **108** can directly or instantly move the actuator **112** in response to current flow in the force generator **106**.

Interruption of the current in the force generator **106** in response to the controller allows fuel flow and the resulting pressure, the biasing member **130**, and/or the attractive element **124** to urge or force the driver **108** to the normally closed position, which in turn allows the flow valve **114** to return to the normally closed position. For example, a distal end portion of the driver **108** can contact or otherwise move the flow valve **114** to the closed position on the valve seat **122**. Subsequent application of current to the force generator **106** can move the driver **108** to contact the actuator **112** and again move or lift the valve **114** off the valve seat **122** to inject fuel into the combustion chamber.

In addition to filtering particles and debris from the fuel, the filter **142** at the base portion **104** can also function as a catalytic processor for preventing any monatomic or ionic hydrogen from further passage into the injector **100**, including into the fuel channel **128**, which houses the biasing member **130**. This purpose is supported by the finding that steel alloys do not become embrittled by diatomic hydrogen (H_2) even though exposure to monatomic hydrogen and ionic hydrogen, as may be encountered during welding operations, in acidic environments, and during metal plating operations, causes degradation and embrittlement of such alloys. Accordingly, the filter **142** can prevent the adverse degradation of the biasing member **130** by hydrogen embrittlement. Equations

F1 and F2 below summarize the elimination of the hydrogen ions and atomic hydrogen by the catalytic action of the filter **142**.



In the process of Equation F1, electrons are supplied by grounding the injector **100** to an electron source via the metallic fuel conduit **136**. Electrons may also be supplied for accomplishing the process of Equation F1 by grounding one end of force generator **106** to the conductive housing **109**. Nucleation of diatomic hydrogen from monatomic hydrogen can be assured by various agents and compounds, including for example, oxides such as zinc oxide, tin oxide, chromia, alumina, and silica that may be incorporated in the filter **142** as fibers and/or particles including surfaces of substrates such as aluminum and/or aluminum-silicon alloys. Such fibers, particles, and/or other suitable forms made of metals and/or alloys such as aluminum, magnesium, or zinc can also serve as catalysts in the filter **142**. Similarly chemical vapor deposition and/or sputtered deposits of these metals on various substrates, followed by partial oxidation, can be positioned in the filter **142** to provide catalytic processing as summarized by Equations F1 and F2. Fuels that provide oxidizing potential, such as "oxygenated" fuels that contain water vapor, enable self-healing of such metal oxides. In embodiments where high strength alloy materials, such as music wire, spring steel, precipitation-hardened (PH) steel, or a chrome-silicon steel alloy, are selected for the biasing member **130**, additional protection may also be provided by plating the biasing member **130** with protective metals such as aluminum. For example, the biasing member **130** can be plated with any suitable plating methods including, for example, hot dip, electrolytic, chemical vapor, and/or sputtering processes.

The injector **100** of the illustrated embodiment is also capable of dispensing very high pressure fuels, including hydrogen-characterized fuels that are produced as mixtures of methane from anaerobic digestion, thermal dissociation, or natural gas sources, as well as hydrogen produced by electrolysis, pyrolysis, or reformation of selected hydrocarbons. Such pressurized fuels, such as 10,000 psi hydrogen, methane, ammonia, or other hydrogen characterized mixtures can be supplied to the injector **100** and precisely metered by the injector **100** to achieve desired fuel bursts.

According to another feature of the illustrated embodiment, the driver **108** is proportioned as a relatively long component in the injector **100**. More specifically, the longitudinal length of the driver **108** and the corresponding longitudinal length of the force generator **106** may be several times larger than the diameter of driver **108**. This can allow or otherwise facilitate cooling of these components by fuel that is flowing through the injector **100**. More specifically, the fuel flowing through the injector **100** can cool the driver **108** and/or force generator **106**. For example, as fuel flows along a fuel channel or passage **113** extending longitudinally along the injector **100**, as well as through the driver **108** in the fuel bore or cavity **126**, and/or around the driver **108** in a second fuel bore or passageway **150** in the driver cavity **118** generally surrounding the driver **108**, the fuel can absorb heat from the driver **108**. This is advantageous in many applications in modern overhead valve engines that virtually eliminate the opportunity to reject heat to the exterior surroundings of the injector because the temperature of the environment around and/or under the engine's valve cover generally approaches the operating limit of polymer compounds that insulate the magnet wire in the force generator **106**.

FIG. **2** is a cross-sectional side partial view of an injector **200** configured in accordance with another embodiment of the disclosure. The injector **200** includes several features that are generally similar in structure and function to the corresponding features of the injector **100** illustrated in FIG. **1B** and other injectors disclosed herein. For example, the injector **200** illustrated in FIG. **2** includes the fuel conduit **136**, the force generator **106**, the driver **108**, and the corresponding actuator **112** and associated flow valve **114**. The illustrated injector **200** also includes a biasing or attractive element **212** (e.g., a ring magnet or a permanent ring magnet) to attract or force the driver **108** to the normally closed position. The valve **114** can also include a seal **218**, such as a ring-like elastomeric seal or o-ring, for applications in which bubble free sealing is desired at the valve **114** and when utilizing fuels that may precipitate or otherwise source solid particles.

In the illustrated embodiment, the injector **200** further includes several additional fuel flow paths or channels that direct the fuel through various components of the injector **200** to allow the fuel to contact surfaces of these components and cool or otherwise transfer heat from these components to the fuel. More specifically, for cooling the force generator **106** (which may include multiple solenoid windings) in the illustrated embodiment, the injector **200** includes a first fuel cooling passage **202** coupled between the fuel conduit **136** and an inlet distributor **204** (e.g., an annular or ring-like distributor) at the force generator **106**. The inlet distributor **204** disperses the fuel into the housing **109** around the force generator **106** through multiple inlet vents **206**. The injector **200** also includes multiple outlet vents **208** to allow the fuel to exit the force generator **106** and collect at an outlet distributor or collector **210** (e.g., an annular or ring-like distributor). A second fuel cooling passage **212** extends from the outlet distributor **210** to fuel channel **214**. As the valve **114** opens, the fuel can exit the injector **200** by passing from the fuel channel **214** to the fuel exit passage **103**.

According to another feature of the illustrated embodiment, the injector **200** also includes additional fuel passages **216** extending radially outwardly to allow the fuel to pass between the force generator **106** and the driver **108**. For example, these fuel passages **216** fluidly couple the fuel bore **150** in the driver cavity **118** with the housing **109** encompassing the force generator **106**. As such, during operation the fuel can also pass radially outwardly and/or radially inwardly to transfer heat from the components of the injector **200**, such as the force generator **106** and the driver **108**, for example.

In certain embodiments, such as four stroke engine applications, the period during which fuel injection occurs typically ranges from about 30° to 120° of every other crank rotation of a complete cycle (e.g., 720°). Longitudinal fuel cavities **126** and **113** (FIG. **1**) can accordingly provide for rapid cooling of the driver **108**, particularly during the period ranging from approximately 30° to 120° of the crank rotation. As such, the driver **108** can serve as an internal heat sink to receive heat rejected from solenoid coil or force generator **106**. Additional heat can also be rejected from the force generator **106** to fuel circulating through the various fuel distributors and passageways **204**, **206**, **208**, and **216**. Accordingly, during the 690° to 720° period of crank rotation when driver **108** and valve **114** are in the normally closed position, the force generator **106** can be provided with superior heat rejection capabilities to assure efficient rapid action and long life.

Such heat transfer from the components of the injectors **100**, **200** can be beneficially added to the fuel that is delivered to the combustion chamber instead of being lost to the environment. Similarly, energy harvesting by thermoelectric,

photovoltaic, vibrational and pressure piezoelectric generators is facilitated by such heat transfer to fuel passing through these injector embodiments with such heat sinking capabilities. Such heat transfer is also beneficial for long life, minimization of friction, and rapid operation to adequately cool the force generator **106** and driver **108**. Transferring heat to the fuel that flows through the force generator **106** components and related features allows low cost modular component assemblies including the force generator **106** to be incorporated within thermally insulating glass or polymers.


FIG. **3A** is an isometric view of the driver **108**, FIG. **3B** is a cross-sectional side view taken substantially along the lines **3B-3B** of FIG. **3A**, and FIG. **3C** is cross-sectional side view taken substantially along the lines **3C-3C** of FIG. **3A** illustrating several of the features of the driver **108**. Referring to FIGS. **3A-3C** together, the driver **108** includes a body **301** with the actuator opening **120** extending centrally and longitudinally therethrough. The actuator opening **120** is configured to movably receive the actuator **112** of FIG. **1B**. The body **301** also includes the initial fuel channel **128** that is fluidly coupled to one or more fuel cavities **126** (e.g., first-sixth fuel cavities **126a-126f** illustrated in FIG. **3C**) spaced radially apart from the actuator opening **120**. The fuel cavities **126** extend longitudinally through the driver **108** to allow fuel to flow therethrough while contacting the body **301**. Although the driver **108** includes six fuel cavities **126** that are symmetrically spaced apart in the illustrated embodiment, in other embodiments the driver can have more or less fuel cavities **126** that are positioned in symmetrical or nonsymmetrical distribution patterns. An exterior surface of the body **301** also includes multiple ridges **304** (FIG. **4C**) to allow the fuel to flow around the driver **108** within the driver cavity **118** (FIG. **1B**).

According to yet another feature of the illustrated embodiment, the body **301** of the driver **108** includes a slot or slit **302** extending radially outwardly from one of the fuel cavities **128**. In certain embodiments, the slit **302** can be a generally straight slit or slot that extends radially outwardly from the actuator opening **120**. In other embodiments, however, the slit **302** can have a generally curved or spiral shape. The slit **302** is configured to be a material discontinuity in at least a portion of the body **301** of the driver **108** to prevent eddy currents from forming in the driver **108** during operation. Such eddy currents can also be prevented by forming the driver **108** from a ferromagnetic alloy with a high electrical resistance. Thermochemical Regeneration to Provide Oxygenated Fuel to Combustion Chamber

FIG. **4** illustrates a system for utilizing heat normally discarded from sources such as a heat engine to drive endothermic reactions that provide oxygenated fuel species. In addition to providing numerous significant advantages of an oxygenated fuel species, thermochemical regeneration provides 15% to 30% more fuel value along with hydrogen-characterized fuel combustion characteristics upon combustion compared to the original fuel that is selected for the processes disclosed in the following embodiments.

Hydrogen characterized combustion is seven to ten times faster than hydrocarbons such as methane and therefore enables much more torque to be developed per calorie or BTU of heat released than slower burning fuels that require much earlier ignition and thus cause heat loss and counter-torque losses during the compression period of engine operation.

Equation 501 summarizes the general process for hydrocarbons such as diesel fuel, gasoline, natural gas, propane, ethane, etc:




Equation 502 summarizes the production of oxygenated carbon fuel as shown whereby methane is reacted with steam to produce carbon monoxide and hydrogen. In operation, heat that is normally rejected through a radiator is added to fuel in a counter current heat exchanger and additional heat is added by counter current heat exchange from the exhaust gases. Steam is transported from the products of combustion through capillaries **408** and presented at the surface of capillary body **408** for reaction such as shown in Equations 501 or 502. Concurrently filed and co-pending applications are incorporated by reference above; these applications disclose various arrangements for such counter current heat exchanges.

Additional heat may be added at startup and in various conditions such as regenerative braking of a vehicle or elevator by application of electric current to heat resistor **412** which may be placed between a first tube **404** and a steam transport capillary **408** as shown. According to aspects of the disclosure, a second tube **402** may serve as a containment shield for air or refractory insulation in the space between the first tube **404** and the second tube **402**.

Fuel such as methane that has been preheated by engine coolant is routed through the space between the second tube **404** and the steam transport capillary **408** as shown to react with steam and provide oxygenated fuel such as carbon monoxide along with hydrogen in a stream **416** as shown. Hot exhaust gases, including but not limited to steam, are delivered as a mixture through inlet **418**; as the steam is depleted the cooled exhaust gases exit through outlet **420**.

Suitable materials for the steam transport capillary **408** include graphene and other forms of carbon and boron nitride (disclosed in copending patent applications incorporated herein), and various refractory materials including but not limited to substrates that serve as pressure and temperature swing media for steam removal from mixtures with nitrogen, carbon dioxide, and oxygen.

In addition to production of oxygenated fuel species from hydrocarbons, another embodiment produces oxygenated fuel species from low cost fuels such as mixtures of alcohol, water and a carbon donor. Equation 503 summarizes the process for an alcohol such as butanol and a carbon donor, for example, a colloidal or otherwise suspended carbon, from a waste source.



In this embodiment the water required for the process may be a combination of steam transported by the steam transport capillary **408** and water provided by the mixture of an alcohol, water and a suspended carbon donor. In this illustration, which is generally typical for various alcohols such as methanol, ethanol, butanol, or isopropanol, the carbon donor is depicted as "C" and the sum of steam that is transported by the steam transport capillary **408** and the water in solution is depicted as "nH₂O" or "4H₂O" for the illustrative process with butanol.



If dry or 100% butanol is used as a feedstock for thermochemical production of oxygenated carbon and hydrogen as shown in Equation 503, only about 4/9 or 45% of the water produced by combustion of the products of Equation 503 are required to be delivered by the process depicted in FIG. **500**.

As shown in FIG. **5**, a thermochemical regeneration system **530** is utilized with heat engine **532**. The heat engine **532** provides heat from an engine coolant circuit that includes priority delivery of heat by a controller **555** through a "hot" connection or inlet **548**. A cooler return **550** delivers coolant

for subsequent heat rejection by a suitable system such as an air cooled radiator (not shown). This serves the purpose of preheating fuel delivered from a sufficiently pressurized tank source **538** or through pump **540** into line **542** and through valve **544** to heat exchanger **546** as shown. According to further aspects of the disclosure, preheated fuel may then be routed to another countercurrent heat exchanger **504** for heating such fuel by heat transfer from exhaust gases **534**. According to one embodiment, the exhaust gases **534** may be routed through tubing **562** to reaction zone **506** for the carbon oxygenation process to produce fully oxygenated carbon monoxide along with hydrogen as summarized by Equation 501. Alternative configurations, as one skilled in the art would understand, are within the scope of the disclosure.

Hot steam from the exhaust stream passes across membrane **508** for supplying or supplementing other sources of water utilized in Equation 501. According to further aspects of the disclosure, regenerative energy as may be provided by energy harvesting operations such as regenerative braking or harvesting of combustion chamber energy sources including vibration, radiation, and pressure may be delivered to the tubular heat exchanger **504** by a suitable inductive or resistance heater **552** by connections **575**, **577** as shown.

Considerable thermal banking or retention of such heat in surplus of the amount consumed by the endothermic process of Equations 501, 502 or 503 may be provided by material selections such as graphite or boron nitride. Alternatively or additionally, a change of phase heat exchanger and storage capability may be provided by substances such as salt compositions that change phase at a desired temperature such as at or above the temperature required for processes such as shown in Equations 501, 502 and 503. Such thermal banking materials and/or phase change storage may be provided in the zone between tubes **501** and **504** as shown. Fuels such as those shown in Equations 500, 502, and 503 are thus heated to adequate temperature for the reactions indicated and delivered to reaction zone **508** and **506** by insulated tubing **562** as shown.

The stream of hot fuel constituents such as hydrogen and carbon monoxide produced by reactions shown in Equations 501, 502 and 503, is cooled by counter current heat exchange with fuel from the tank **538**. An optimization controller **555** controls fuel delivery through control valves **544** and **554**. Accordingly, in operation, the fuel from tank **538** is heated to approximately the temperature of the products from the reactor **506**, while the stream of hydrogen and carbon monoxide is cooled to nearly the temperature of fuel from tank **538**.

This thermochemical regeneration system provides hydrogen-characterized fuel with superior heat removal capabilities for circulation within desired spaces and places for cooling one or more fuel injection valves **566**, which in turn control direct fuel injection into the combustion chambers of the engine **532**. A resistance or inductive heater **570** with connections **568**, **572** may be utilized to further apply heat which has been generated from energy harvesting operations to increase the temperature of fuel delivered by insulated tubing **560** to reaction zone **506**.

Illustratively, application of heat generated from energy harvesting operations as described above may provide or enhance plasma generation for use in facilitating the combustion event. Plasma generation in an oxidant such as air before each fuel injection creates thrust of ionized oxidant into the remaining oxidant within the combustion chamber. The inventory of ionized oxidant greatly accelerates ignition and completion of combustion of fuel that subsequently enters the combustion chamber. The pattern of ionized oxidant projecting into the combustion chamber helps impart the flow of

remaining oxidant into fuel that follows the path of ionized air. Plasma generation within fuel entering the combustion chamber may be increased to provide sufficient electrical energy to accelerate the fuel for the purpose of overtaking the flow of ionized oxidant. In other modes plasma may be generated in fuel that is subsequently injected to produce additional groups of vectors that penetrate the oxidant within the combustion chamber. An example of such plasma thrusting of directed rays or vectors of plasma projected fuel are shown in concurrently filed applications incorporated by reference above. Plasma thrusting provides optimal utilization of the oxidant in the combustion chamber in instances that an asymmetric location is provided for fuel injector.

Modes of operating the system that intentionally bring a liquid phase fuel into the combustion chamber, or that convert the fuel into a gaseous phase on-demand, or that provide a desired fluid-gas mixture of fuel, utilize thermochemical regeneration to control the heat input (e.g. increase or decrease) to the fuel prior to injecting the fuel into the combustion chamber. For example, plasma induced fuel preparation and thrust generation is used to develop desired shapes and surface-to-volume characterizations of stratified fuel deliveries and enable efficient utilization of harvested energy. An illustrative embodiment provides for regenerative braking of a vehicle, elevator or similar event to produce electrical energy and/or conversion of combustion chamber sourced radiation, pressure, thermal or vibration energy whereby such harvested electricity is utilized to produce the desired plasma. Examples of plasma shaping and characterization of fuel injection and oxidation events include: plasma ionization of oxidant prior to the arrival of fuel; plasma ionization of oxidant prior to the arrival of fuel followed by continued ionization of injected fuel; plasma ionization of fuel that is injected into oxidant within the combustion chamber; plasma ionization of at least a layer of oxidant adjacent to a layer of fuel; plasma ionization of a layer of oxidant adjacent to a layer of fuel adjacent to a layer of oxidant; plasma ionization of a mixture of fuel and oxidant; plasma ionization of oxidant after any of the above described events; plasma production of ion currents that are electromagnetically thrust into the combustion chamber; and plasma production of ion currents that are electromagnetically thrust and magnetically accelerated to desired vectors within the combustion chamber.

Plasma thrusting of oxidant, mixtures of oxidant and fuel, or fuel ions is provided by the electromagnetic forces that are generated by high current discharges. The general approach of such plasma generation is disclosed in exemplary references such as U.S. Pat. Nos. 4,122,816; 4,774,914 and 5,076,223, herein incorporated in their entirety by reference, and may utilize various high voltage generation systems including the type disclosed in U.S. Pat. No. 4,677,960, herein incorporated in its entirety by reference. Shaping of the plasma that may be generated in oxidant, fuel, and/or mixtures of oxidant and fuel may be accomplished by an electromagnetic lens such as utilized to selectively aim streams of electrons in a cathode ray tube or as disclosed in U.S. Pat. No. 4,760,820, herein incorporated in its entirety by reference, regarding streams of ions. Generally it is undesirable to incur the engine efficiency penalty and loss of selectivity of the type of ion generation desired and adaptive ion distribution shaping capabilities that the present invention achieves by reliance upon a high-pressure fuel delivery system (such as a high-pressure fuel delivery system disclosed in U.S. Pat. No. 5,377,633, herein incorporated in its entirety by reference).

In operation, plasma generation in an oxidant, such as excess air, before each fuel injection event, selectively creates a thrust of ionized oxidant into the remaining oxidant within

the combustion chamber. The inventory of ionized oxidant greatly accelerates ignition and completion of combustion of fuel that subsequently enters the combustion chamber.

The pattern of ionized oxidant projecting into the combustion chamber is controlled by the voltage and current applied to the plasma that is formed and helps impart the flow of remaining oxidant into fuel that follows the path of ionized air. Plasma generation within fuel entering the combustion chamber may be increased to provide sufficient electrical energy to electromagnetically accelerate the fuel for the purpose of overtaking the flow of ionized oxidant.

In other modes of operation plasma generation may be modulated by control of the voltage and amperage delivered in injected fuel to provide greater velocity and penetration of fuel-rich layers or bursts into an oxidant within the combustion chamber.

As further shown in FIG. 6, one system 670 for delivering fuel from inlet 672 to the interface of a combustion chamber includes a voltage delivery source or first electrode 474 (shown the near electrically grounded location 486). Voltage sufficient to ionize fuel, fuel-oxidant mixtures or oxidant is delivered from the voltage delivery source or electrode 474 to second electrode 474' by a conductor contained within a suitable dielectric insulator. In accordance with aspects of the disclosure, fuel is delivered to a heat exchanger 476 (e.g. from a force generator, such as a solenoid winding) to remove heat from one or more valves 478, 480 such as a solenoid valve. At times of fuel injection, one or more channels or conduits including a coaxial delivery circuit 482 and 484 deliver fuel to the interface of a combustion chamber for ignition by plasma produced by electrodes 474, 474'.

Another embodiment of the disclosure provides for interchangeable utilization of fuel selections including mixtures of fuels such as diesel fuel; melted paraffin; gasoline; casing head or "drip" gasoline; methane; ethane; propane; butane; fuel alcohols; wet fuels such as 160-proof mixtures of water and one or more alcohols such as methanol, ethanol, butanol, or isopropanol; producer gas; and hydrogen. This is enabled by adaptive adjustment to provide sufficient plasma in each fuel injection delivery to suddenly produce fuel alterations including fuel evaporation/vaporization and chemical cracking to subdivide large molecules into smaller components including ionized species. Thus a wide variety of fuel selections, particularly very low cost fuels, are acceptable including fuels with contaminants such as water and cetane ratings that are far outside of acceptable "diesel fuel" specifications. Furthermore, the plasma may be generated by electrode nozzles that produce sufficient plasma thrust of such ionized fuel species to penetrate desired distances into oxidant within the combustion chamber to allow relatively low fuel delivery pressures compared to typical diesel fuel pressurization requirements for achieving similar oxidant utilization. This overcomes the disadvantages and limitations of cetane-characterized fuel selection, "diesel delay," knock and relatively uncontrolled peak combustion temperatures that characterize conventional compression-ignition systems.

Such plasma induced fuel preparation and thrust generation to develop desired shapes and surface-to-volume characterizations of stratified fuel deliveries enables efficient utilization of harvested energy. An illustrative embodiment provides for regenerative braking of a vehicle, elevator or similar event to produce electrical energy and/or conversion of combustion chamber sourced radiation, pressure, thermal or vibration energy whereby such harvested electricity is utilized to produce the desired plasma. This overcomes the substantial loss of engine efficiency due to the pressure-volume work required to compress an oxidant sufficiently to heat

it 370° C. (700° F.) or more including losses of such work-generated heat through the intentionally cooled walls of the combustion chamber along with the substantial work required to pump and pressurize diesel fuel to high pressures such as 1360 bar (20,000 PSI).

It will be apparent that various changes and modifications can be made without departing from the scope of the disclosure. Unless the context clearly requires otherwise, throughout the description and the claims, the words "comprise," "comprising," and the like are to be construed in an inclusive sense as opposed to an exclusive or exhaustive sense; that is to say, in a sense of "including, but not limited to." Words using the singular or plural number also include the plural or singular number, respectively. When the claims use the word "or" in reference to a list of two or more items, that word covers all of the following interpretations of the word: any of the items in the list, all of the items in the list, and any combination of the items in the list.

Features of the various embodiments described above can be combined to provide further embodiments. All of the U.S. patents, U.S. patent application publications, U.S. patent applications, foreign patents, foreign patent applications and non-patent publications referred to in this specification and/or listed in the Application Data Sheet are incorporated herein by reference, in their entirety. Aspects of the disclosure can be modified, if necessary, to employ fuel injectors and ignition devices with various configurations, and concepts of the various patents, applications, and publications to provide yet further embodiments of the disclosure.

These and other changes can be made to the disclosure in light of the above-detailed description. In general, in the following claims, the terms used should not be construed to limit the disclosure to the specific embodiments disclosed in the specification and the claims, but should be construed to include all systems and methods that operate in accordance with the claims. Accordingly, the invention is not limited by the disclosure, but instead its scope is to be determined broadly by the following claims.

I claim:

1. A fuel-cooled fuel injector configured to inject fuel into a combustion chamber, the fuel injector comprising:
 - a body having a base portion opposite a nozzle portion, wherein the base portion is configured to receive the fuel into the body and the nozzle portion is configured to be positioned adjacent to the combustion chamber;
 - a valve carried by the nozzle portion, wherein the valve is movable between a closed position and an open position to inject the fuel into the combustion chamber;
 - an actuator coupled the valve and extending longitudinally through the body towards the base portion;
 - a driver carried by the body and movable between a first position and a second position, wherein in the first position the driver is spaced apart from the actuator and in the second position the driver moves the actuator to move the valve to the open position;
 - a force generator comprising a solenoid winding and configured to move the driver, wherein at least a portion of the solenoid winding is in direct contact with a conductive housing surrounding the force generator to ground the force generator to the housing; and
 - a plurality of passageways extending longitudinally through the driver configured to allow fuel to flow there-through.
2. The fuel injector of claim 1 wherein the passageways are helical.

17

3. The fuel injector of claim 1 wherein driver includes a cavity extending longitudinally therethrough, and wherein the actuator is movably positioned in the cavity.

4. The fuel injector of claim 3 wherein the fuel flows through the cavity in the driver as the fuel flows from the base to the nozzle of the injector.

5. The fuel injector of claim 1, further comprising a biasing member carried by the base portion of the body, wherein the biasing member urges the driver towards the first position.

6. The fuel injector of claim 1 wherein when the driver is in the first position the driver contacts and at least partially retains the valve in the closed position.

7. The fuel injector of claim 1, further comprising a force generator operably coupled to a controller, wherein the force generator induces the movement of the driver between the first and second positions to achieve desired fuel distribution via the valve.

8. The fuel injector of claim 1 wherein the driver at least partially gains momentum prior to contacting the actuator to move the valve to the open position.

9. The fuel injector of claim 1 wherein the actuator extends through the body coaxially within the driver.

10. The fuel injector of claim 1 wherein the actuator includes one or more monitoring fibers extending there-through and operably coupled to the valve, wherein the one or more monitoring fibers are configured to detect one or more combustion chamber properties and transmit the one or more combustion chamber properties to a controller.

11. The fuel injector of claim 1 wherein the driver includes curvilinear passageways configured to allow fuel to flow therethrough.

12. The fuel injector of claim 3 wherein the body includes a plurality of ridges configured to allow fuel to flow around the driver within the driver cavity.

13. The fuel injector of claim 1 wherein the driver includes a plurality of cavities configured to allow fuel to flow there-through.

14. The fuel injector of claim 1 wherein the driver is a solenoid winding configured to allow fuel to flow over the solenoid winding.

15. A method for providing oxygenated fuel to a combustion chamber of a fuel injector comprising:

capturing waste heat from a source derived from a heat engine to drive endothermic reactions; and transporting steam from a combustion event occurring in a combustion chamber of a fuel injector through capillaries in a body of the fuel injector;

18

reacting methane with steam to produce carbon monoxide and hydrogen; and

grounding a force generator comprising a solenoid winding and configured to move a valve by positioning the solenoid winding in direct contact with a conductive housing surrounding the force generator.

16. The method of claim 15 wherein the capillary includes graphene, carbon, boron nitride and/or a refractory material.

17. A fuel injector configured to inject fuel into a combustion chamber, the fuel injector comprising:

a body having a base portion opposite a nozzle portion, wherein the base portion is configured to receive the fuel into the body and the nozzle portion is configured to be positioned adjacent to the combustion chamber;

a valve at the nozzle portion, wherein the valve is movable between a closed position and an open position;

an actuator having a first end coupled to the valve and a second end portion opposite the first end portion, wherein the second end portion has a stop;

a driver positioned in the body and movable between first and second positions, wherein in the first position the driver is spaced apart from the stop and in the second position the driver contacts the stop to move the actuator axially away from the nozzle portion to move the valve to the open position;

a force generator comprising a solenoid winding and configured to move the driver, wherein at least a portion of the solenoid winding is in direct contact with a conductive housing surrounding the force generator to ground the force generator to the housing; and

a countercurrent heat exchanger configured to exchange heat from exhaust gases to fuel in the body.

18. The fuel injector of claim 17, further comprising a pressurized storage tank and wherein the countercurrent heat exchanger is configured to preheat fuel from the pressurized storage tank.

19. The fuel injector of claim 17 wherein the driver includes an actuator opening extending longitudinally through a central portion of the driver, wherein the actuator extends through the actuator opening, wherein the driver is independently movable from the actuator, and wherein the driver and the actuator are fluidically connected.

20. The fuel injector of claim 19 wherein the driver further includes a fuel passageway spaced radially apart from the actuator opening and extending longitudinally through the driver, wherein the fuel passageway is configured to allow fuel to flow through the driver.

* * * * *