

US009298543B2

(12) **United States Patent**  
**Wang et al.**

(10) **Patent No.:** **US 9,298,543 B2**  
(45) **Date of Patent:** **Mar. 29, 2016**

(54) **ELECTRICALLY ERASABLE PROGRAMMABLE MEMORY DEVICE THAT GENERATES ERROR-DETECTION INFORMATION**

*H03M 13/09* (2013.01); *H03M 13/29* (2013.01); *H03M 13/2906* (2013.01); *H03M 13/611* (2013.01);

(Continued)

(71) Applicant: **Rambus Inc.**, Sunnyvale, CA (US)

(58) **Field of Classification Search**

CPC . *G06F 11/1008*; *G06F 11/10*; *G06F 11/1044*; *H03M 13/09*; *H03M 13/29*; *H03M 13/611*; *H03M 13/2906*

See application file for complete search history.

(72) Inventors: **Yuanlong Wang**, San Jose, CA (US); **Frederick A. Ware**, Los Altos Hills, CA (US)

(73) Assignee: **Rambus Inc.**, Sunnyvale, CA (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,585,378 A 6/1971 Bouricius et al.  
3,893,072 A 7/1975 D'Antonio et al.

(Continued)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/806,011**

OTHER PUBLICATIONS

Answers.com, "ECC Memory," <http://www.answers.com/topic/ecc-memory>, obtained Jun. 20, 2006. 2 pages.

(22) Filed: **Jul. 22, 2015**

(Continued)

(65) **Prior Publication Data**

US 2015/0324250 A1 Nov. 12, 2015

**Related U.S. Application Data**

(60) Continuation of application No. 14/175,955, filed on Feb. 7, 2014, now Pat. No. 9,092,352, which is a continuation of application No. 13/752,324, filed on Jan. 28, 2013, now Pat. No. 8,656,254, which is a

(Continued)

(51) **Int. Cl.**

*H03M 13/00* (2006.01)  
*G06F 11/10* (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC ..... *G06F 11/1008* (2013.01); *G06F 3/064* (2013.01); *G06F 3/0619* (2013.01); *G06F 3/0679* (2013.01); *G06F 11/073* (2013.01); *G06F 11/076* (2013.01); *G06F 11/10* (2013.01); *G06F 11/1004* (2013.01); *G06F 11/1402* (2013.01); *G06F 13/4286* (2013.01);


*Primary Examiner* — Shelly A Chase

(74) *Attorney, Agent, or Firm* — The Neudeck Law Firm, LLC

(57) **ABSTRACT**

A controller includes a link interface that is to couple to a first link to communicate bi-directional data and a second link to transmit unidirectional error-detection information. An encoder is to dynamically add first error-detection information to at least a portion of write data. A transmitter, coupled to the link interface, is to transmit the write data. A delay element is coupled to an output from the encoder. A receiver, coupled to the link interface, is to receive second error-detection information corresponding to at least the portion of the write data. Error-detection logic is coupled to an output from the delay element and an output from the receiver. The error-detection logic is to determine errors in at least the portion of the write data by comparing the first error-detection information and the second error-detection information, and, if an error is detected, is to assert an error condition.

**20 Claims, 14 Drawing Sheets**



**Related U.S. Application Data**

continuation of application No. 13/398,768, filed on Feb. 16, 2012, now Pat. No. 8,365,042, which is a continuation of application No. 13/013,779, filed on Jan. 25, 2011, now Pat. No. 8,132,077, which is a continuation of application No. 12/479,684, filed on Jun. 5, 2009, now Pat. No. 7,882,423, which is a division of application No. 11/330,524, filed on Jan. 11, 2006, now Pat. No. 7,562,285.

(51) **Int. Cl.**

*H03M 13/09* (2006.01)  
*H03M 13/29* (2006.01)  
*G06F 3/06* (2006.01)  
*G06F 13/42* (2006.01)  
*H04L 1/08* (2006.01)  
*H04L 1/18* (2006.01)  
*G06F 11/14* (2006.01)  
*G06F 11/07* (2006.01)  
*H04L 1/00* (2006.01)

(52) **U.S. Cl.**

CPC ..... *H04L 1/0061* (2013.01); *H04L 1/08* (2013.01); *H04L 1/1867* (2013.01); *G06F 11/1044* (2013.01); *H04L 1/0003* (2013.01); *H04L 1/0008* (2013.01); *H04L 2001/0093* (2013.01)

(56)

**References Cited**

U.S. PATENT DOCUMENTS

4,054,911 A 10/1977 Fletcher et al.  
 4,354,225 A 10/1982 Frieder et al.  
 4,359,771 A 11/1982 Johnson et al.  
 4,363,125 A 12/1982 Brewer et al.  
 4,369,510 A 1/1983 Johnson et al.  
 4,394,763 A 7/1983 Nagano et al.  
 4,456,993 A 6/1984 Taniguchi et al.  
 4,468,731 A 8/1984 Johnson et al.  
 4,527,237 A 7/1985 Frieder et al.  
 4,535,455 A 8/1985 Peterson  
 4,543,628 A 9/1985 Pomfret  
 4,584,685 A 4/1986 Gajjar  
 4,596,014 A 6/1986 Holeman  
 4,597,084 A 6/1986 Dynneson et al.  
 4,604,750 A 8/1986 Manton et al.  
 4,792,923 A 12/1988 Nakase et al.  
 4,888,773 A 12/1989 Arlington  
 4,899,342 A 2/1990 Potter et al.  
 4,914,657 A 4/1990 Walter et al.  
 4,920,539 A 4/1990 Albonesi  
 4,924,456 A 5/1990 Maxwell et al.  
 4,970,714 A 11/1990 Chen et al.  
 5,048,022 A 9/1991 Bissett et al.  
 5,065,312 A 11/1991 Bruckert et al.  
 5,070,474 A 12/1991 Tuma et al.  
 5,173,905 A 12/1992 Parkinson et al.  
 5,193,181 A 3/1993 Barlow et al.  
 5,218,691 A 6/1993 Tuma et al.  
 5,313,627 A 5/1994 Amini et al.  
 5,341,251 A 8/1994 Fincher et al.  
 5,347,643 A 9/1994 Kondo et al.  
 5,369,651 A 11/1994 Marisetty  
 5,392,302 A 2/1995 Kemp et al.  
 5,404,361 A 4/1995 Casorso et al.  
 5,450,609 A 9/1995 Schultz et al.  
 5,459,742 A 10/1995 Cassidy et al.  
 5,488,691 A 1/1996 Fuoco et al.  
 5,490,153 A 2/1996 Gregg et al.  
 5,490,155 A 2/1996 Abdoo et al.  
 5,502,733 A 3/1996 Kishi et al.  
 5,550,988 A 8/1996 Sarangdhar et al.  
 5,553,231 A 9/1996 Papenberg et al.

5,559,956 A 9/1996 Sukegawa  
 5,588,112 A 12/1996 Dearth et al.  
 5,687,183 A 11/1997 Chesley  
 5,729,550 A 3/1998 Nakajima et al.  
 5,751,932 A 5/1998 Horst et al.  
 5,751,955 A 5/1998 Sonnier et al.  
 5,778,419 A 7/1998 Hansen et al.  
 5,784,390 A 7/1998 Masiewicz et al.  
 5,838,899 A 11/1998 Leavitt et al.  
 5,841,795 A 11/1998 Olarig et al.  
 5,987,628 A 11/1999 Von Bokern et al.  
 6,003,151 A 12/1999 Chuang  
 6,009,542 A 12/1999 Koller et al.  
 6,012,136 A 1/2000 Brown  
 6,029,264 A 2/2000 Kobayashi et al.  
 6,035,037 A 3/2000 Chaney  
 6,038,679 A 3/2000 Hanson  
 6,048,090 A 4/2000 Zook  
 6,065,146 A 5/2000 Bosshart  
 6,094,732 A 7/2000 Takano  
 6,115,763 A 9/2000 Douskey  
 6,125,470 A 9/2000 Hee et al.  
 6,151,689 A 11/2000 Garcia et al.  
 6,169,710 B1 1/2001 Arai  
 6,189,123 B1 2/2001 Anders et al.  
 6,208,663 B1 3/2001 Schramm et al.  
 6,212,660 B1 4/2001 Joeressen et al.  
 6,243,845 B1 6/2001 Tsukamizu et al.  
 6,249,894 B1 6/2001 Lin et al.  
 6,308,294 B1 10/2001 Ghosh et al.  
 6,314,541 B1 11/2001 Seytter et al.  
 6,367,048 B1 4/2002 McAuliffe et al.  
 6,373,842 B1 4/2002 Coverdale et al.  
 6,393,504 B1 5/2002 Leung et al.  
 6,397,365 B1 5/2002 Brewer et al.  
 6,438,723 B1 8/2002 Kalliojarvi  
 6,507,928 B1 1/2003 Richardson  
 6,529,561 B2 3/2003 Sipola  
 6,545,994 B2 4/2003 Nelson et al.  
 6,553,003 B1 4/2003 Chang  
 6,560,725 B1 5/2003 Longwell et al.  
 6,606,589 B1 8/2003 Tuma et al.  
 6,625,749 B1 9/2003 Quach  
 6,646,911 B2 11/2003 Hidaka  
 6,697,986 B2 2/2004 Kim et al.  
 6,700,867 B2 3/2004 Classon et al.  
 6,704,898 B1 3/2004 Furuskar et al.  
 6,715,116 B2 3/2004 Lester et al.  
 6,725,414 B2 4/2004 Seyyedy  
 6,735,726 B2 5/2004 Muranaka et al.  
 6,742,159 B2 5/2004 Sakurai  
 6,745,364 B2 6/2004 Bhatt et al.  
 6,754,856 B2 6/2004 Cofler et al.  
 6,760,814 B2 7/2004 Corrigan  
 6,765,740 B2 7/2004 Tsuchiya  
 6,779,148 B2 8/2004 Tanaka  
 6,779,150 B1 8/2004 Walton et al.  
 6,792,501 B2 9/2004 Chen et al.  
 6,823,424 B2 11/2004 Larson et al.  
 6,832,340 B2 12/2004 Larson et al.  
 6,845,472 B2 1/2005 Walker et al.  
 6,851,081 B2 2/2005 Yamamoto  
 6,880,103 B2 4/2005 Kim et al.  
 6,883,130 B2 4/2005 Wilhelmsson et al.  
 6,892,159 B2 5/2005 Weiss et al.  
 6,909,758 B2 6/2005 Ramesh et al.  
 6,912,682 B1 6/2005 Aoki  
 6,931,582 B2 8/2005 Tamura et al.  
 6,941,493 B2 9/2005 Phelps  
 6,977,888 B1 12/2005 Frenger et al.  
 6,990,604 B2 1/2006 Binger  
 7,027,539 B2 4/2006 Yang et al.  
 7,047,473 B2 5/2006 Hwang et al.  
 7,072,307 B2 7/2006 Tong et al.  
 7,168,023 B2 1/2007 Morgan et al.  
 7,200,770 B2 4/2007 Hartwell et al.  
 7,231,580 B2 6/2007 Shiota et al.  
 7,249,289 B2 7/2007 Muranaka et al.  
 7,257,762 B2 8/2007 Holm et al.

(56)

## References Cited

## OTHER PUBLICATIONS

## U.S. PATENT DOCUMENTS

|              |     |         |                    |                       |
|--------------|-----|---------|--------------------|-----------------------|
| 7,310,757    | B2  | 12/2007 | Ngo et al.         |                       |
| 7,339,759    | B2  | 3/2008  | Hashimoto          |                       |
| 7,340,641    | B1  | 3/2008  | Binger             |                       |
| 7,355,803    | B2  | 4/2008  | Yang               |                       |
| 7,418,436    | B2  | 8/2008  | Maeda et al.       |                       |
| 7,421,547    | B2  | 9/2008  | Matsui et al.      |                       |
| 7,519,894    | B2  | 4/2009  | Wei et al.         |                       |
| 7,523,381    | B2  | 4/2009  | Eggleston et al.   |                       |
| 7,529,965    | B2  | 5/2009  | Ikeuchi et al.     |                       |
| 7,548,495    | B2  | 6/2009  | Kobayashi          |                       |
| 7,562,285    | B2  | 7/2009  | Wang et al.        |                       |
| 7,570,447    | B2  | 8/2009  | Koga et al.        |                       |
| 7,624,298    | B2  | 11/2009 | Kasahara et al.    |                       |
| 7,636,262    | B2  | 12/2009 | Kim et al.         |                       |
| 7,657,783    | B2  | 2/2010  | Levitan            |                       |
| 7,831,882    | B2  | 11/2010 | Tsern et al.       |                       |
| 7,831,888    | B2  | 11/2010 | Wang et al.        |                       |
| 7,836,386    | B2  | 11/2010 | Schumacher et al.  |                       |
| 7,882,423    | B2  | 2/2011  | Wang et al.        |                       |
| 7,949,931    | B2  | 5/2011  | Lastras-Montano    |                       |
| 7,996,731    | B2  | 8/2011  | Macri et al.       |                       |
| 8,042,023    | B2  | 10/2011 | Balb               |                       |
| 8,132,077    | B2  | 3/2012  | Wang et al.        |                       |
| 8,352,805    | B2  | 1/2013  | Shaeffer et al.    |                       |
| 8,555,116    | B1  | 10/2013 | Shaeffer et al.    |                       |
| 8,892,963    | B2* | 11/2014 | Macri              | G06F 11/08<br>711/133 |
| 2001/0056567 | A1  | 12/2001 | Sakurai            |                       |
| 2002/0053042 | A1  | 5/2002  | Brown              |                       |
| 2002/0144210 | A1  | 10/2002 | Borkenhagen et al. |                       |
| 2003/0066010 | A1  | 4/2003  | Acton              |                       |
| 2003/0088805 | A1  | 5/2003  | Majni et al.       |                       |
| 2003/0115417 | A1  | 6/2003  | Corrigan           |                       |
| 2003/0177434 | A1  | 9/2003  | Su et al.          |                       |
| 2004/0073649 | A1  | 4/2004  | Inami et al.       |                       |
| 2004/0088497 | A1  | 5/2004  | Deans et al.       |                       |
| 2004/0139310 | A1  | 7/2004  | Maeda et al.       |                       |
| 2004/0205433 | A1  | 10/2004 | Gower et al.       |                       |
| 2004/0209420 | A1  | 10/2004 | Ljungcrantz et al. |                       |
| 2004/0237001 | A1  | 11/2004 | Schulz et al.      |                       |
| 2004/0264030 | A1  | 12/2004 | Yang               |                       |
| 2005/0055522 | A1  | 3/2005  | Yagi               |                       |
| 2005/0073899 | A1  | 4/2005  | Gallivan et al.    |                       |
| 2005/0262241 | A1  | 11/2005 | Gubbi et al.       |                       |
| 2006/0075291 | A1  | 4/2006  | Takahashi          |                       |
| 2006/0077750 | A1  | 4/2006  | Pescatore          |                       |
| 2006/0098320 | A1  | 5/2006  | Koga et al.        |                       |
| 2006/0123483 | A1  | 6/2006  | Cohen              |                       |
| 2006/0126460 | A1  | 6/2006  | Kobayashi          |                       |
| 2006/0277434 | A1  | 12/2006 | Tsern et al.       |                       |
| 2007/0002482 | A1  | 1/2007  | Daikokuya et al.   |                       |
| 2007/0011562 | A1  | 1/2007  | Alexander et al.   |                       |
| 2007/0016698 | A1  | 1/2007  | Vogt               |                       |
| 2007/0043917 | A1  | 2/2007  | Matsui et al.      |                       |
| 2007/0104327 | A1  | 5/2007  | Macri et al.       |                       |
| 2007/0150872 | A1  | 6/2007  | Vohra              |                       |
| 2007/0162825 | A1  | 7/2007  | Wang et al.        |                       |
| 2007/0226597 | A1  | 9/2007  | Taito et al.       |                       |
| 2008/0046802 | A1  | 2/2008  | Honda              |                       |
| 2008/0163007 | A1  | 7/2008  | Shaeffer et al.    |                       |
| 2008/0195922 | A1  | 8/2008  | Lee                |                       |
| 2009/0006863 | A1  | 1/2009  | Mizuno             |                       |
| 2009/0204871 | A1  | 8/2009  | Eggleston et al.   |                       |
| 2010/0217915 | A1  | 8/2010  | O'Connor et al.    |                       |
| 2011/0246857 | A1  | 10/2011 | Bae et al.         |                       |
| 2012/0179866 | A1  | 7/2012  | Davis et al.       |                       |

Cardarilli et al., "Design of a Fault Tolerant Solid State Mass Memory," IEEE Transactions of Reliability, vol. 52, No. 4, Dec. 2003, pp. 476-491. 16 pages.

Dell Computer Corporation et al., "Serial ATA II: Electrical Specification," Rev. 1, May 26, 2004. 187 pages.

Digital Equipment Corporation, "ESE50 SDI Solid State Disk Service Guide," Jun. 1993. 132 pages.

Digital Equipment Corporation, "ESE50 SDI Solid State Disk: User Guide," Jun. 1993. 33 pages.

Digital Equipment Corporation, "Hardware Documentation—Machines DEC—VAX Hardware Reference," printed from <http://www.netbsd.org/documentation/hardware/Machines/DEC/vax> on May 13, 2005. 91 pages.

Digital Equipment Corporation, "Software Product Description, Product Name: HSC High Performance Software," Ver. 8.6, Jun. 1996. 6 pages.

Digital Equipment Corporation, "Software Product Description, Product Name: HSC Software," Ver. 6.5, Jun. 1992. 4 pages.

Geisler, J., "Error Detection & Correction," Taylor University, Computer and System Sciences Department, Sep. 16, 2005. 21 pages.

Grosspietsch et al., "A Memory Interface Chip Designed for Fault Tolerance," VLSI System Design, Jun. 1987, pp. 112-118. 5 pages.

Grosspietsch et al., "The VLSI Implementation of a Fault-Tolerant Memory Interface—a Status Report," VLSI '85, 1986, pp. 155-164. 10 pages.

Haas et al., "Advances in Server Memory Technology," presented at Spring 2005 Intel Developers Forum, San Francisco, CA, Mar. 1, 2005. 31 pages.

Hanna, P., "Error Detection and Correction," Lecture 9, Queen's University—Belfast, Jan. 3, 2005. 12 pages.

Hodgart et al., "A (16,8) Error Correcting Code (T=2) for Critical Memory Applications," DASIA2000, Montreal, Canada, May 22-26, 2000. 4 pages.

Kilbuck et al., "Fully Buffered DIMM—Unleashing Server Capacity," Micron Technology, Inc., Apr. 8, 2005. 199 pages.

May et al., "HiPER: A Compact Narrow Channel Router with Hop-by-Hop Error Correction," IEEE Transactions on Parallel and Distributed Systems, vol. 13, No. 5, May 2002, pp. 485-498. 14 pages.

MMCA Technical Committee, "The MultiMediaCard," System Specification, Version 3.31, May 2003. 150 pages.

PCT International Preliminary Report on Patentability dated Aug. 12, 2008 in International Application No. PCT/US2007/011733. 22 pages.

PCT International Search Report and Written Opinion dated Jan. 11, 2008 in International Application No. PCT/US2007/011733. 13 pages.

PCT International Search Report and Written Opinion dated Mar. 6, 2007 in International Application No. PCT/US2006/020698. 16 pages.

Pearson Education, "Error Detection and Correction," Logic and Computer Design Fundamentals, 3rd Edition, 2004, pp. 1-5. 5 pages.

SanDisk Corporation, "Flash ChipSet Product Manual," Revision 5, Oct. 1998. 135 pages.

SanDisk Corporation, "SanDisk SD Card: Product Manual," Version 2.2, Document No. 80-13-00169, Nov. 2004. 123 pages.

Siewiorek, Dan, "20 Fault Tolerance & Memory Hierarchy," Lecture Handout, Carnegie Mellon University, Nov. 23, 1998. 18 pages.

Wicker, Stephen B., "Error Control Systems for Digital Communications and Storage" Prentice-Hall, 1995, pp. 392-423. 17 pages.

Wikipedia, "Forward Error Correction," [http://en.wikipedia.org/wiki/forward\\_error\\_correction](http://en.wikipedia.org/wiki/forward_error_correction), printed Jun. 20, 2006. 3 pages.

\* cited by examiner




Figure 1




Figure 2A




Figure 2B




Figure 3




Figure 4A






Figure 4B




Figure 5




Figure 6




Figure 7A




Figure 7B




Figure 8




Figure 9

1100




Figure 10






Figure 11

**1****ELECTRICALLY ERASABLE  
PROGRAMMABLE MEMORY DEVICE THAT  
GENERATES ERROR-DETECTION  
INFORMATION**

## RELATED APPLICATIONS

This application is a continuation of U.S. application Ser. No. 14/175,955, filed Feb. 7, 2014, which is a continuation of U.S. application Ser. No. 13/752,324, filed Jan. 28, 2013, now U.S. Pat. No. 8,656,254, which is continuation of U.S. application Ser. No. 13/398,768, filed Feb. 16, 2012, now U.S. Pat. No. 8,365,042, which is a continuation of U.S. patent application Ser. No. 13/013,779, filed Jan. 25, 2011, now U.S. Pat. No. 8,132,077, which is continuation of U.S. patent application Ser. No. 12/479,684, filed Jun. 5, 2009, now U.S. Pat. No. 7,882,423, which is a divisional of U.S. patent application Ser. No. 11/330,524, filed Jan. 11, 2006, now U.S. Pat. No. 7,562,285, entitled "Unidirectional Error Code Transfer for a Bidirectional Data Link," which are incorporated herein by reference in their entireties.

This application is also related to U.S. patent application Ser. No. 12/479,688, filed Jun. 5, 2009, entitled "Unidirectional Error Code Transfer Method for Bidirectional Data Link," now U.S. Pat. No. 7,831,888, which is incorporated herein by reference in its entirety.

## FIELD

The subject matter disclosed herein relates generally to integrated circuits, methods and systems having error detection, error correction and/or retry modes of operation using a bidirectional data link.

## BACKGROUND

Low bit-error-rate (BER) communication of data over a communications channel is often considered an important requirement in many systems. In the case of memory devices and systems, fulfilling this requirement is increasingly difficult due to signaling and circuit limitations. In future memory devices and systems, scaling of interface circuitry to accommodate higher data rates may be restricted by transistor sensitivity and threshold limits. In addition, even though interconnect lengths and a loss tangent may be constant, the higher data rates may increase noise due to an increased bandwidth. Given constraints on interface overhead and latency, developing faster interfaces with a low BER may become more challenging and expensive. This poses a problem, since conventional interfaces in memory devices and systems typically have an extremely low BER. For example, the BER in the interface in a dynamic random access memory (DRAM) is typically less than a soft error rate in the DRAM core, i.e., less than  $10^{-30}$ . If the BER in the interface increases in future high-speed designs, ensuring reliability with different processes, systems and environments for conventional memory devices and systems may be difficult.

## BRIEF DESCRIPTION OF THE DRAWINGS

For a better understanding, reference should be made to the following detailed description taken in conjunction with the accompanying drawings, in which:

FIG. 1 is a block diagram illustrating an embodiment of a system.

FIG. 2A is a block diagram illustrating an embodiment of a controller.

**2**

FIG. 2B is a block diagram illustrating an embodiment of a device.

FIG. 3 is a diagram illustrating a data stream and an error code stream in an embodiment of a system.

FIG. 4A is a block diagram illustrating an embodiment of a controller.

FIG. 4B is a block diagram illustrating an embodiment of a device.

FIG. 5 is a diagram illustrating a data stream and a command stream in an embodiment of a system.

FIG. 6 is a block diagram illustrating an embodiment of generating error code bits.

FIG. 7A is a block diagram illustrating an embodiment of a controller.

FIG. 7B is a block diagram illustrating an embodiment of a device.

FIG. 8 is a flow diagram illustrating a method of operation of an embodiment of a system.

FIG. 9 is a flow diagram illustrating a method of operation of an embodiment of a system.

FIG. 10 is a flow diagram illustrating a method of operation of an embodiment of a system.

FIG. 11 is a block diagram illustrating an embodiment of a system.

Like reference numerals refer to corresponding parts throughout the drawings.

## DETAILED DESCRIPTION OF EMBODIMENTS

A controller is described. In some embodiments, the controller may be a memory controller. The controller includes a first link interface that is to couple to a first link to communicate bi-directional data and a second link to transmit unidirectional error-detection information. A first encoder is to dynamically add first error-detection information to at least a portion of write data. A first transmitter, coupled to the first link interface, is to transmit the write data. A first delay element is coupled to an output from the first encoder. A first receiver, coupled to the first link interface, is to receive read data. A second encoder, coupled to an output from the first receiver, is to dynamically add second error-detection information to at least a portion of the read data. A second receiver, coupled to the first link interface, is to receive third error-detection information corresponding to at least the portion of the read data and fourth error-detection information corresponding to at least the portion of the write data. First error-detection logic is coupled to an output from the first delay element, an output from the second encoder and an output from the second receiver. The first error-detection logic is to determine errors in at least the portion of the write data by comparing the first error-detection information and the fourth error-detection information, and is to determine errors in at least the portion of the read data by comparing the second error-detection information and the third error-detection information. If an error is detected, the first error-detection logic is to assert an error condition.

The controller may include retry logic and/or instructions to perform a retry remedial action if the error condition is asserted. The retry remedial action may include re-transmitting the write data using the first transmitter and the first link interface. The retry remedial action may include re-receiving the read data using the first receiver and the first link interface after the read data is re-transmitted by a device.

The controller may include a third encoder to dynamically add fifth error-detection information to at least a portion of write mask information, and a second transmitter coupled to an output from the third encoder and to the first link interface.

The first link interface is to couple to a third link to transmit unidirectional command information including the fifth error-detection information, and the first link interface is to couple to the first link to communicate the write mask information.

In another embodiment, a device is described. In some embodiments, the device may be a memory device, including a memory core that utilizes solid-state memory, semiconductor memory, organic memory and/or another memory material. The device includes a second link interface that is to couple to the first link to communicate bi-directional data and the second link to transmit unidirectional error-detection information. A fourth encoder is to dynamically add the third error-detection information to at least the portion of the read data. A second transmitter, coupled to the second link interface, is to transmit the read data. A third receiver, coupled to the second link interface, is to receive the write data. A fifth encoder, coupled to an output from the third receiver, is to dynamically add the fourth error-detection information to at least the portion of the write data. A third transmitter is coupled to the second link interface, and is selectively coupled to one of an output from the fourth encoder and an output from the fifth encoder.

The read data may be re-transmitted using the second transmitter and the second link interface if the device receives remedial action instructions from the controller. The write data may be re-received using the third receiver and the second link interface if the device receives remedial action instructions from the controller.

The device may include a sixth encoder, coupled to an output from the third receiver, to dynamically add sixth error-detection information to at least the portion of the write mask information. The second link interface is to couple to the third link to receive the unidirectional command information. A fourth receiver, coupled to the second link interface, is to receive the fifth error-detection information. Second error-detection logic, coupled to an output from the fourth receiver and an output from the sixth encoder, is to determine errors in at least the portion of the write mask information by comparing the fifth error-detection information and the sixth error-detection information. If an error is detected, the second error-detection logic is to disable a write operation to the memory core.

In another embodiment, a system is described. In some embodiments, the system may be a memory system. The system includes the controller and at least the device. The first link interface in the controller is coupled to the first link and the second link. The second link interface in the device is coupled to the first link and the second link. In some embodiments, the first link interface in the controller and the second link interface in the device may each be coupled to the third link.

In another embodiment, a process for operating a controller is described. The first error-detection information is dynamically added to at least the portion of the write data. The write data is transmitted. The fourth error-detection information corresponding to at least the portion of the write data is received. The fourth error-detection information is compared to a delayed version of the first error-detection information to determine errors in at least the portion of the write data. If an error is detected, an error condition is asserted.

In another embodiment, a process for operating a controller is described. The read data is received. The second error-detection information is dynamically added to at least the portion of the read data. The third error-detection information corresponding to at least the portion of the read data is received. The second error-detection information is com-

pared to the third error-detection information to determine errors in at least the portion of the read data. If an error is detected, an error condition is asserted.

In another embodiment, a process for operating a device is described. The write mask information is received. The sixth error-detection information is dynamically added to at least the portion of the write mask information. The fifth error-detection information corresponding to at least the portion of the write mask information is received. The fifth error-detection information and the sixth error-detection information are compared to determine errors in at least the portion of the write mask information. If an error is detected, a write operation to the memory core is disabled.

In some embodiments, dynamically adding error-detection information may include generating and/or incorporating pre-existing error-detection code information and/or error correction code information (such as a Bose-Chaudhuri-Hochquenghem code) into at least a portion of the transmit data (such as in one or more write data packets and/or one or more read data packets) and/or at least a portion of the write mask information. In some embodiments, the generated error-detection code information is only used locally, i.e., it is not transmitted with the write data and/or the write mask information. In some embodiments, the dynamic adding of respective error-detection code information may include generating and/or incorporating pre-existing error-detection code information or error correction code information into at least a portion of command information, such as commands or address information. In some embodiments, the error-detection code information (such as one or more parity bits or parity codes) and/or error correction code information may be generated in real time in accordance with at least a portion of the transmit data, the write mask information and/or the command information. Such dynamically generated error-detection code information and/or error correction code information may then be used locally and/or incorporated into the transmit data, the write mask information and/or the command information.

In some embodiments, the controller and/or the device may include instructions for and/or may perform one or more additional actions during a respective retry remedial action. The one or more additional actions may be mediated by retry information transmitted from the controller to the device and/or from the device to the controller. The instructions for and/or the performance of the one or more additional actions may include re-transmitting write data, read data, command information and/or write mask information with at least a portion of the re-transmitted write data, read data, command information and/or write mask information having error protection provided by an error correction code that is dynamically generated. The instructions for and/or the performance of the one or more additional actions may include re-transmitting write data, read data, command information and/or write mask information with improved bit error rate (BER). For example, re-transmission may use a circuit having a power greater than that used in a previous transmission for improved transmit characteristics; re-transmission may clock the respective data or information with one symbol per clock cycle (as opposed to transmitting on both rising and falling clock edges or transmitting multiple symbols per clock cycle); re-transmission may use a data or information rate that is less than that used in the previous transmission by adjusting, for example, a clock generator; re-transmission may use a data or information stream having blanks inserted before and/or after the respective data or information in order to have an intersymbol interference that is less than that in the previous transmission; re-transmission may use a different modu-

lation code than that used in the previous transmission by adjusting, for example, a modulator; re-transmission may use a voltage swing that is greater than that used in the previous transmission by adjusting, for example, a voltage generator; re-transmission may use a number of pins that are coupled to one or more of the links (such as the first link, the second link and/or the third link) that is less than the number of pins coupled to one or more of the links in the previous transmission; re-transmission may occur after a predetermined idle time (such as 1, 2 or several clock cycles, or 1, 2 or 3 symbol periods, where a symbol period is an amount of time associated with communication of a symbol of write data or read data); and/or re-transmission may use another transmitter and/or receiver in the controller and/or in the device.

While some embodiments include separate first and second links (i.e., side band communication) to communicate the bi-directional data and the unidirectional error-detection information between the controller and the device, in other embodiments the bi-directional data and the unidirectional error-detection information may be communicated using a common link (i.e., in-band signaling). Such in-band signaling may utilize a technique including time division multiplexing, frequency division multiplexing and/or spread-spectrum signaling.

In some embodiments, the first link, the second link and/or the third link may include one or more pins, one or more lines or wires, one or more pairs of wires, one or more reference or back planes, one or more interconnects, one or more interfaces and/or one or more communications channels. The links may be used for inter-chip communication, such as between one or more semiconductor chips or dies, or for communication within a semiconductor chip, also known as intra-chip communication, such as between modules in an integrated circuit.

In some embodiments, the controller and/or the device may include control logic. The control logic may delay subsequent write operations to the device until the retry remedial action is completed, may delay command operations to a location in the device corresponding to the write or read data until the retry remedial action is completed, or may reorder receive data after the retry remedial action is completed in order to restore the read data received from the device during remedial action to a position corresponding to an original sequence of command operations.

The controller may also include a buffer. The buffer may be used to avoid data hazards. The write data to be transmitted to the device may be temporarily stored in the buffer and, if a read to a location in the device corresponding to the write data occurs during the retry remedial action, the write data may be obtained from the buffer.

By incorporating the error detection, error correction and/or retry modes of operation in the controller, the device or systems including at least one controller and at least one device, the embodiments allow occasional interconnect- or communications-channel-induced bit errors and thereby may allow a reduction in the BER requirements of the interconnect. Such an additional degree of freedom may enable interconnects having increased bandwidth at lower cost and with less complexity.

Reference will now be made in detail to embodiments, examples of which are illustrated in the accompanying drawings. In the following detailed description, numerous specific details are set forth in order to provide a thorough understanding of the subject matter presented herein. However, it will be apparent to one of ordinary skill in the art that the subject matter may be practiced without these specific details. In other instances, well-known methods, procedures, compo-

ments, and circuits have not been described in detail so as not to unnecessarily obscure aspects of the embodiments.

Attention is now directed towards embodiments that address the difficulties associated with the existing memory systems described above. These embodiments may be utilized in one or more controllers, one or more devices and/or one or more systems. In some embodiments, the one or more controllers may be memory controllers, the one or more devices may be memory devices and/or the one or more systems may be memory systems.

FIG. 1 is a block diagram illustrating an embodiment of a system 200. The system 200 includes at least one controller 210 and one or more devices 218. While FIG. 1 illustrates the system 200 having one controller 210 and three devices 218, other embodiments may have additional controllers and fewer or more devices 218. The controller 210 has control logic 212 and each device 218 has control logic 220. In other embodiments, some of the devices 218 may not have the control logic 220. In embodiments where the devices 218 are memory devices, two or more of the devices, such as devices 218-1 and 218-2, may be configured as a memory bank 216.

The controller 210 and the devices 218 are connected by one or more links 214. While the system 200 illustrates three links 214, other embodiments may have fewer or more links 214. The links 214 may be used for bi-directional and/or uni-directional communications between the controller 210 and one or more of the devices 218. Bi-directional communication may be simultaneous. In some embodiments, one or more of the links 214 and the corresponding transmitters, such as transmitters 312 (FIG. 2A), and/or receivers, such as receivers 322 (FIG. 2A), may be dynamically configured, for example, by control logic 212, for bi-directional and/or uni-directional communication.

Data may be communicated on one or more of the links 214 using one or more sub-channels, such as a baseband sub-channel corresponding to a first frequency band and/or a passband sub-channel corresponding to a second frequency band. In some embodiments, such as those where at least one of the links 214 is ac-coupled, the baseband sub-channel may not contain DC (i.e., does not include 0 Hz). In some embodiments, the first frequency band and the second frequency band may be orthogonal. In other embodiments there may be substantial overlap of one or more neighboring pairs of frequency bands. A respective sub-channel may also correspond to a group of frequency bands.

The control logic 212 in the system 200 may be configured to dynamically allocate and/or adjust one or more frequency bands, such as the first frequency band and/or the second frequency band, based on a predetermined data rate, for example, multiple gigabits per second (“Gbits/s” or “Gbps”), between the controller 210 and at least one of the devices 218 and/or the predetermined data rate between at least one of the devices 218 and the controller 210. The control logic 212 may dynamically allocate and/or adjust one or more frequency bands in at least one link 214 by adjusting at least one corresponding transmitter, such as one of the transmitters 312 (FIG. 2A), and at least one corresponding receiver, such as one of the receivers 322 (FIG. 2B). In this example, adjustments to at least one of the transmitters 312 (FIG. 2A) and/or at least one of the receivers 322 (FIG. 2B) may be communicated from the controller 210 to at least one of the devices 218 using at least one of the links 214.

While the embodiment 200 couples the controller 210 to multiple devices 218, in other embodiments two or more controllers may be coupled to one another. The coupled controllers may utilize the unidirectional transfer of error code information described below.

The challenges associated with the existing systems may be at least partially addressed by encoding error detection codes or information on both sides of a link, for example, in a controller and in one or more devices. Two versions of the error-detection information, one generated in the controller and another generated in one or more devices, may be compared in the controller. If errors are detected, an error condition may be asserted and corresponding remedial action, such as re-transmitted write and/or read data, may be taken. The error-detection information may be communicated between the device and the controller using in-band signaling or side-band communication. As described further below with reference to FIG. 4, this approach may reduce an overall latency.

FIG. 2A is a block diagram illustrating an embodiment 300 of a controller 308 incorporating unidirectional error code information transfer. Write data 112 may be synchronized using a flip-flop 310-1 (which is gated by a clock signal that is not shown) and transmitted using transmitter 312-1 on bi-directional data link 326. The write data 112 may also be encoded using encoder 314-1 to generate first write-data error-detection information. An embodiment of an encoder, such as the encoder 314-1 is described further below with reference to FIG. 6. The first write-data error-detection information may be delayed by delay element 316-1 and coupled to error-detection logic 318-1. The delay element 316-1 may compensate for a round-trip delay discussed further below.

Referring to FIG. 2B, which illustrates an embodiment 350 of a device 352, the write data 112 may be received by a receiver 322-3 and synchronized using a flip-flop 310-5 (which is gated by a clock signal that is not shown). The received write data 112 may be coupled to an encoder 314-3 to generate second write-data error-detection information. The second write-data error-detection information may be synchronized using a flip-flop 310-6 and selectively coupled to subsequent components using multiplexer 354. An output from the multiplexer 354 may be synchronized using a flip-flop 310-7 and transmitted on unidirectional error code link 324 using transmitter 312-2.

Referring back to FIG. 2A, the second write-data error-detection information may be received by the controller 308 using receiver 322-1. The second write-data error-detection information may be synchronized using a flip-flop 310-2 and coupled to the error-detection logic 318-1. The error-detection logic 318-1 may compare the first write-data error-detection information and the second write-data error-detection information to determine if the write data 112 was received by the device 352 without error. For example, the error detection logic 318-1 may detect an error using a multi-bit XOR operation in conjunction with one or more parity bits associated with the write data 112. If an error is detected, the error-detection logic 318-1 may assert an error condition 320-1. Retry logic 328 may perform remedial action if the error condition 320-1 is asserted. The remedial action may include re-transmitting the write data 112 to the device 352.

Referring back to FIG. 2B, a similar procedure may be utilized for read data 122. The read data 122 may be synchronized using a flip-flop 310-9 and transmitted using transmitter 312-3 on the bi-directional data link 326. The read data 122 may also be encoded using encoder 314-4 to generate first read-data error-detection information. The first read-data error-detection information may be synchronized using a flip-flop 310-8 and selectively coupled to subsequent components using the multiplexer 354. An output from the multiplexer 354 may be synchronized using the flip-flop 310-7 and transmitted on the unidirectional error code link 324 using the transmitter 312-2.

Referring to FIG. 2A, the read data 122 may be received by a receiver 322-2 and synchronized using the flip-flop 310-3. The received read data 122 may be coupled to an encoder 314-2 to generate second read-data error-detection information. The second read-data error-detection information may be synchronized by a flip-flop 310-4 and coupled to error-detection logic 318-2. The controller 308 may also receive the first read-data error-detection information using the receiver 322-1. The first read-data error-detection information may be synchronized using the flip-flop 310-2 and coupled to the error-detection logic 318-2. The error-detection logic 318-2 may compare the first read-data error-detection information and the second read-data error-detection information to determine if the read data 122 was received by the controller 308 without error. If an error is detected, the error-detection logic 318-2 may assert an error condition 320-2. The retry logic 328 may perform remedial action if the error condition 320-2 is asserted. The remedial action may include transmitting retry information to the device 352 (using a command link that is not shown) such that the read data 122 may be re-transmitted to the controller 308.

In some embodiments, at least one of the transmitters 312 may perform parallel-to-serial conversion. In some embodiments, at least one of the receivers 322 may perform serial-to-parallel conversion. While the retry logic 328 is incorporated in the controller 308 in the embodiment 300, in other embodiments the retry logic 328 may be a separate component. The retry logic 328 may include hardware, such as logic gates to detect and/or interpret the respective error condition, and/or software, including instructions corresponding to the retry remedial action. Providing retry logic that can initiate retry remedial actions enables a system to use transmit and receive data rates greater than a first threshold while maintaining an error rate lower than a second threshold. In some embodiments the first threshold may be on the order of approximately 1 Gbps, 2 Gbps, 5 Gbps or 10 Gbps. In an exemplary embodiment, the second threshold is  $10^{-20}$  with error condition detection and retry. If error detection and retry are not used, the second threshold may be  $10^{-10}$ .

In an exemplary embodiment, the flip-flops 310 have a one clock cycle delay. The delay element 316-1 has a delay of five clock cycles. A bandwidth used in the error code link 324 may be much less than a bandwidth used in the data link 326.

While not shown, the controller 308 may include one or more modulators, one or more de-modulators, one or more voltage generators and at least one clock generator. The one or more voltage generators may generate one or more voltage signals that set signal levels of one or more of the transmitters 312 and/or the receivers 322. The clock generator may generate one or more clock signals that control timing of transmitting and receiving of data by one or more of the transmitters 312 and/or the receivers 322 using one or more of the flip-flops 310. The one or more modulators and/or the one or more de-modulators may implement bit-to-symbol coding and symbol-to-bit coding, respectively. Suitable symbol coding may include two or more level pulse amplitude modulation (PAM), such as two-level pulse amplitude modulation (2PAM), four-level pulse amplitude modulation (4PAM), eight-level pulse amplitude modulation (8PAM), sixteen-level pulse amplitude modulation (16PAM) or a higher level pulse amplitude modulation. In embodiments with one or more passband sub-channels, multi-level PAM is also referred to as multi-level on-off keying (OOK), such as two-level on-off keying (2OOK), four-level on-off keying (4OOK), eight-level on-off keying (8OOK) or a higher level on-off keying. Suitable coding in one or more passband sub-

channels may also include two or more level quadrature amplitude modulation (QAM).

The controller **308** (FIG. 2A) and the device **352** (FIG. 2B) may have fewer or more components. Functions of two or more components (as described above) may be implemented in a single component. Alternatively, functions of some components may be implemented in additional instances of the components. While the embodiments **300** (FIG. 2A) and **350** (FIG. 2B) illustrate one transmitter **312** and two receivers **322**, and two transmitters **312** and one receiver **322**, respectively, there may be fewer or more of these components. While the data link **326** has been illustrated as bi-directional, as noted previously this may include simultaneous bi-directional communication, reconfiguration for unidirectional communication, as well as dynamic configuration of the data link **326**.

FIG. 3 is a diagram illustrating a data stream on the data link **326** and an error code stream on the error code link **324** in an embodiment of a system **400** corresponding to the embodiments **300** (FIG. 2A) and **350** (FIG. 2B). The system **400** illustrates a read-write (RW) bubble **412** and a write-read (WR) bubble **418**. While the system **400** illustrates single rate clocking, in other embodiments dual data rate clocking (i.e., clocking on rising and falling edges of clock **410**) or other data rates with multiple symbols per clock cycle may be used. While there is a larger write data to error code delay **414** in the approach utilized in embodiments **300** (FIG. 2A) and **350** (FIG. 2B), the overall latency is reduced. By delaying the read error code information relative to the read data, as illustrated by read data to error code delay **416**, a single encode delay may be utilized, thereby allowing read data to be returned more quickly.

As mentioned previously, while embodiments **300** (FIG. 2A) and **350** (FIG. 2B) illustrate an approach using sideband communication, via the error code link **324**, in other embodiments in-band signaling may be utilized. This is illustrated in FIGS. 4A and 4B.

FIG. 4A is a block diagram illustrating an embodiment **500** of a controller **510** incorporating unidirectional error code information transfer. The write data **112** may be synchronized using a flip-flop **512-1** (which is gated by a clock signal that is not shown) and transmitted using transmitter **514-1** on bi-directional data and unidirectional error-code link **528**. The write data **112** may also be encoded using encoder **516-1** and flip-flop **512-2** to generate first write-read error-detection information. The feedback loop may allow encoding of a group of write data **112** symbols or data packets. The first write-read error-detection information may be delayed by delay element **518-1** (to compensate for a delay in receiving a burst of read data **122** discussed further below) and coupled to a multiplexer **520-1**. The multiplexer may selectively couple the first write-read error-detection information or a feedback loop to an encoder **516-2** (the feedback loop may allow encoding of a group of write data **112** symbols or data packets along with a group of read data **122** symbols or data packets). The encoder **516-2** may also have read data **122** as an input. The encoder **516-2** may generate second write-read error-detection information. An output from the encoder **516-2** may be synchronized using flip-flop **512-3** and may be coupled to error-detection logic **522**.

Referring to FIG. 4B, which illustrates an embodiment **550** of a device **552**, the write data **112** may be received by a receiver **526-2** and synchronized using a flip-flop **512-6** (which is gated by a clock signal that is not shown). The received write data **112** may be encoded using encoder **516-3** and flip-flop **512-7** to generate third write-read error-detection information. The feedback loop may allow encoding of a

group of received write data **112** symbols or data packets. The third write-read error-detection information may be delayed by delay element **518-2** (to compensate for a delay in receiving a burst of read data **122**) and coupled to a multiplexer **520-2**. The multiplexer may selectively couple the third write-read error-detection information or a feedback loop to an encoder **516-4** (the feedback loop may allow encoding of a group of received write data **112** symbols or data packets along with a group of read data **122** symbols or data packets). The encoder **516-4** may also have read data **122** as an input. The encoder **516-4** may generate fourth write-read error-detection information. An output from the encoder **516-4** may be synchronized using flip-flop **512-8** and coupled to multiplexer **520-3**. The multiplexer **520-3** may selectively couple the fourth write-read error-detection information or the read data **122** to a flip-flop **512-9** (for synchronization) and to a transmitter **514-2**. The transmitter **514-2** may transmit the read data **122** and/or the fourth write-read error-detection information on the data and error-code link **528**.

Referring back to FIG. 4A, the read data **122** and/or the fourth write-read error-detection information may be received by the controller **510** using receiver **526-1**. The fourth write-read error-detection information and/or the read data **122** may be synchronized using a flip-flop **512-5**. As mentioned previously, the read data **122** may be coupled to the encoder **516-2**. The fourth write-read error-detection information may be coupled to the error-detection logic **522**. The error-detection logic **522** may compare the second write-read error-detection information and the fourth write-read error-detection information to determine if the write data **112** was received by the device **552** without error and if the read data **122** was received by the controller **510** without error. For example, the error detection logic **522** may detect an error using a multi-bit XOR operation in conjunction with one or more parity bits associated with the write data **112** and the read data **122**. If an error is detected, the error-detection logic **522** may assert an error condition **524**. Retry logic **530** may perform remedial action if the error condition **524** is asserted. The remedial action may include re-transmitting the write data **112** to the device **552** and re-transmitting the read data to the controller **510**. The remedial action may include transmitting retry information to the device **552** (using a command link that is not shown) such that the read data **122** may be re-transmitted to the controller **510**.

In some embodiments, at least one of the transmitters **514** may perform parallel-to-serial conversion. In some embodiments, at least one of the receivers **526** may perform serial-to-parallel conversion. While the retry logic **530** is incorporated in the controller **510** in the embodiment **500**, in other embodiments the retry logic **530** may be a separate component. The retry logic **530** may include hardware, such as logic gates to detect and/or interpret the respective error condition, and/or software, including instructions corresponding to the retry remedial action. The retry remedial action may enable transmit and receive data rates greater than the first threshold with an error rate lower than the second threshold. In some embodiments the first threshold may be on the order of approximately 1 Gbps, 2 Gbps, 5 Gbps or 10 Gbps. In an exemplary embodiment, the second threshold is  $10^{-20}$  with error condition detection and retry. If error detection and retry are not used, the second threshold may be  $10^{-10}$ .

In an exemplary embodiment, the flip-flops **512** have a one clock cycle delay. The delay elements **518** may delay the most recent encoded write data **112** until the next burst of read data **122** is received. If a read burst is not received within a predetermined time interval, the controller **510** may instruct the device **552** to provide the fourth write-read error detection

## 11

information directly without waiting for the read burst using a command transmitted on the command link (not shown). Time division multiplexing may be utilized on the data and error-code link **528** to interleave the write data **112**, the read data **122** and the fourth write-read error-detection information. The encoders **516** may generate error-detection information for four data packets of write data **112** and four data packets of read data **122** which are coded as a group. Each data packet may include thirty-two bits of data. The data and error-code link **528** may include sixteen parallel signal lines. The encoders **516** may, at least in part, implement a vertical/horizontal parity code in conjunction with a cyclic redundancy code (CRC). In other embodiments, the encoders **516** may implement a CRC code, a parity code, a Hamming code, a Reed-Solomon code, and/or another error checking and correction code.

While not shown, the controller **510** may include one or more modulators, one or more de-modulators, one or more voltage generators and at least one clock generator. The one or more voltage generators may generate one or more voltage signals that set signal levels of one or more of the transmitters **514** and/or the receivers **526**. The clock generator may generate one or more clock signals that control timing of transmitting and receiving of data by one or more of the transmitters **514** and/or the receivers **526** using one or more of the flip-flops **512**. The one or more modulators and/or the one or more de-modulators may implement bit-to-symbol coding and symbol-to-bit coding, respectively. Suitable symbol coding may include two or more level pulse amplitude modulation (PAM), such as two-level pulse amplitude modulation (2PAM), four-level pulse amplitude modulation (4PAM), eight-level pulse amplitude modulation (8PAM), sixteen-level pulse amplitude modulation (16PAM) or a higher level pulse amplitude modulation. In embodiments with one or more passband sub-channels, multi-level PAM is also referred to as multi-level on-off keying (OOK), such as two-level on-off keying (2OOK), four-level on-off keying (4OOK), eight-level on-off keying (8OOK) or a higher level on-off keying. Suitable coding in one or more passband sub-channels may also include two or more level quadrature amplitude modulation (QAM).

The controller **510** and the device **552** (FIG. 4B) may have fewer or more components. Functions of two or more components (as described above) may be implemented in a single component. Alternatively, functions of some components may be implemented in additional instances of the components. While the embodiments **500** and **550** (FIG. 4B) illustrate one transmitter **514** and one receiver **526** there may be fewer or more of these components. While the data and error-code link **528** has been illustrated as bi-directional for data and unidirectional for error-code information, as noted previously this may include simultaneous bi-directional communication, reconfiguration for unidirectional communication, as well as dynamic configuration of the data and error-code link **528**.

FIG. 5 is a diagram illustrating a data stream **612** and a command stream **610** in an embodiment of a system **600** corresponding to the embodiments **500** (FIG. 4A) and **550** (FIG. 4B). While the system **600** illustrates single rate clocking, in other embodiments dual data rate clocking (i.e., clocking on rising and falling edges of the clock **410**) or other data rates with multiple symbols per clock cycle may be used. In the system **600**, read and write data are separated by read-write (RW) bubble **412** and write-read bubble (WR) **614**. In the encoders **516**,  $N_W$  cycles **616** of write data **112** and  $N_R$  cycles **618** of read data **122** are concatenated and encoded. The resulting write-read error-detection information (SD) is

## 12

transmitted during cycle **620**. Cycle **620** may coincide with a synchronization command (S) sent by the controller **510** (FIG. 4A) at the end of a read command sequence. As described previously, in an exemplary embodiment, the  $N_W$  cycles **616** and the  $N_R$  cycles **618** may number four.

FIG. 6 is a block diagram illustrating an embodiment **700** of generating error code bits, such as the write or read error-detection information in embodiments **300** (FIG. 2A) and **350** (FIG. 2B). Sixteen bit slices **708**, each containing sixteen bits, are bit-wise summed to generate horizontal parity **710** and vertical parity **712**, respectively. The input data may include two-hundred fifty-six bits of write data **112** or two-hundred fifty-six bits of read data **122**. The input bits in embodiment **700** are intended as an illustration. Other embodiments may use a different number of bits and/or a different number of bit slices.

The horizontal parity is encoded using a CRC coder **714-1** and the vertical parity is encoded using a CRC coder **714-2**. In an exemplary embodiment, each of the CRC coders **714** may implement six-bit encoding using six XOR gates each having sixteen inputs. The CRC coders **714** may output write or read error-detection information or error check (ECHK) bits **716**, which are also referred to as check codes. In an exemplary embodiment, each CRC coder **714** may output six bits for a given set of input data, such as horizontal or vertical input bits. An additional four blank bits may also be included. Note that in general a CRC encoder with a k-bit check code can cover up to  $2^{k-1}-k-1$  input data bits. The check code (k bits) and the data bits (up to  $2^{k-1}-k-1$  bits) together are called a code word. Any one-bit, two-bit or three-bit errors and any burst errors with length at most k in a code word can be detected by the CRC code. The CRC coder **714** may use the polynomial

$$X^6+X^5+X^3+X^2+X+1$$

as a generation polynomial. The horizontal and vertical parity bits may be multiplied with a generation matrix corresponding to the generation polynomial to generate the check codes.

A further approach addresses the issue of write masking when a bidirectional data link, such as the data link **326** (FIG. 2A), couples a memory controller and a memory device. Write mask information permits individual bytes of write data **112** to be written or not-written into a respective column address location. Such write mask information may be transferred between a controller, such as the controller **308** (FIG. 2A), and a device, such as the device **352** (FIG. 2B), using sideband communication or in-band signaling. In embodiments with a sideband link, there may be 1/8 fewer signal lines than in the data link. In in-band signaling, the write mask information may be communicated on the data link. A write key technique may be used or bandwidth in the data link may be allocated explicitly for the write mask information. In these embodiments, the data rate of the write mask information may be the same as that used for the write data.

Whether write mask information is communicated using sideband communication or in-band signaling, it may be susceptible to errors during communication on a link. The remedial action and retry instructions described previously may not, however, adequately address errors in the write mask information. This is because an error in the write mask information may result in erroneous overwriting of a byte location that is not supposed to be overwritten. In the case of an error in the received write data **112**, the bad data in the device, such as the device **352** (FIG. 2B), is only a copy. The original write data **112** is in the controller, such as the controller **308** (FIG. 2A), and may be re-transmitted. In the case of some errors in the write mask information, however, the only copy of data at

a byte location that is not to be written resides at that byte location in the device. There is no copy in the controller. As a consequence, an error in the write mask information could destroy the only copy of the data at that byte location.

FIGS. 7A and 7B illustrate embodiments of a solution to this challenge. FIG. 7A is a block diagram illustrating an embodiment **800** of a controller **810**. The controller **810** may be a memory controller. A data stream containing write data **812** and write mask information is coupled to an encoder **314-5**. The encoder receives the write mask information and generates first write-mask error-detection information. The first write-mask error-detection information is synchronized using a flip-flop **310-10** and is coupled to a transmitter **312-4**. Address and command information **814** is synchronized using a flip-flop **310-12** and is also coupled to the transmitter **312-4**. The transmitter **312-4** transmits the address and command information **814** and the first write-mask error-detection information on a request link **818**. The request link **818** may operate at a lower data rate than the data link **326**. Such as lower data rate may reduce a probability of an error during the communication of the first write-mask error-detection information. The write mask information **816** may also be synchronized using flip-flop **310-1** and coupled to the transmitter **312-1**. The transmitter transmits the write data **812** and the write mask information **816** on the data link **326**.

FIG. 7B illustrates an embodiment **850** of a device **852**, which may be a memory device. The write mask information **816** may be received by receiver **322-3**. The write mask information **816** may be synchronized using a flip flop **310-5**. The write mask information **816** may be encoded using encoder **314-6** to generate second write-mask error-detection information. The second write-mask error-detection information may be coupled to error detection logic **318-3**.

The first write-mask error-detection information may be received via the request link **818** using receiver **322-4**. The first write-mask error-detection information may be synchronized using flip-flop **310-11** and coupled to the error-detection logic **318-3**. The error-detection logic **318-3** may compare the first write-mask error-detection information and the second write-mask error-detection information to determine if the write mask information **816** has been received without an error. If no error has occurred, the write operation is allowed to proceed. If an error has occurred, the error-detection logic **318-3** may output signals that disables a write operation **856** to a memory core, thereby prevent an accidental erasure of the data at the corresponding column address location. The device **852** may transmit retry instructions to the controller **810** (FIG. 7A), for example, using a retry link (not shown). The retry instructions may request that the write mask information **816** and/or the corresponding write data **812** be re-transmitted. The retry instructions may be processed by retry logic **820** (FIG. 7A).

The approach described in embodiments **800** (FIG. 7A) and **850** may be utilized if there is sufficient space and/or bandwidth on the request link **818**. This is often the case since a row address in the address and command information **814** is typically larger in size than a corresponding column address. If there are multiple devices **852**, such as multiple DRAM chips, however, there may not be sufficient communications capacity on the request link **818**. In such a circumstance, a separate link may be included for the write-mask error-detection information. Alternatively, different error-detection codes may be utilized for different groups of one or more devices **852** coupled to a common request link **818**.

Attention is now directed towards processes for operating controllers, devices and/or systems. FIG. 8 is a flow diagram illustrating a method of operation of an embodiment **900** of a

system. First write-data error-detection information is dynamically added to at least a portion of write data (**910**). Dynamically adding error-detection information may include generating (for example, in real time) and appending error-detection information. The write data is transmitted (**912**). Second write-data error-detection information corresponding to at least the portion of the write data is received (**914**). The second write-data error-detection information and a delayed version of the first write-data error-detection information are compared to determine errors in at least the portion of the write data (**916**). An error condition is asserted if an error is detected (**918**). In some embodiments, there may be fewer or additional operations, an order of the operations may be rearranged and/or two or more operations may be combined.

FIG. 9 is a flow diagram illustrating a method of operation of an embodiment **1000** of a system. Read data is received (**1010**). First read-data error-detection information is dynamically added to at least a portion of the read data (**1012**). Second read-data error-detection information corresponding to at least the portion of the read data is received (**1014**). The first read-data error-detection information and the second read-data error-detection information are compared to determine errors in at least the portion of the read data (**1016**). An error condition is asserted if an error is detected (**1018**). In some embodiments, there may be fewer or additional operations, an order of the operations may be rearranged and/or two or more operations may be combined.

FIG. 10 is a flow diagram illustrating a method of operation of an embodiment **1100** of a system. Write mask information is received (**1110**). First write-mask error-detection information is dynamically added to at least a portion of the write mask information (**1112**). Second write-mask error-detection information corresponding to at least the portion of the write mask information is received (**1114**). The first write-mask error-detection information and the second write-mask error-detection information are compared to determine errors in at least the portion of the write mask information (**1116**). A write operation to a memory core is disabled if an error is detected (**1118**). In some embodiments, there may be fewer or additional operations, an order of the operations may be rearranged and/or two or more operations may be combined.

The unidirectional transfer of error-detection information and related methods of operation are well-suited for use in improving communication in systems and devices. They are also well-suited for use in improving communication between a memory controller chip and a DRAM chip. The DRAM chip may be either on the same printed circuit board as the controller or embedded in a memory module. The apparatus and methods described herein may also be applied to other memory technologies, such as static random access memory (SRAM) and electrically erasable programmable read-only memory (EEPROM).

Devices and circuits described herein can be implemented using computer aided design tools available in the art, and embodied by computer readable files containing software descriptions of such circuits, at behavioral, register transfer, logic component, transistor and layout geometry level descriptions stored on storage media or communicated by carrier waves. Data formats in which such descriptions can be implemented include, but are not limited to, formats supporting behavioral languages like C, formats supporting register transfer level RTL languages like Verilog and VHDL, and formats supporting geometry description languages like GDSII, GDSIII, GDSIV, CIF, MEBES and other suitable formats and languages. Data transfers of such files on machine readable media including carrier waves can be done electronically over the diverse media on the Internet or



through email, for example. Physical files can be implemented on machine readable media such as 4 mm magnetic tape, 8 mm magnetic tape, 3½ inch floppy media, CDs, DVDs and so on.

FIG. 11 is a block diagram an embodiment of a system 1200 for storing computer readable files containing software descriptions of the circuits. The system 1200 may include at least one data processor or central processing unit (CPU) 1210, a memory 1214 and one or more signal lines 1212 for coupling these components to one another. The one or more signal lines 1212 may constitute one or more communications busses.

The memory 1214 may include high-speed random access memory and/or non-volatile memory, such as one or more magnetic disk storage devices. The memory 1214 may store a circuit compiler 1216 and circuit descriptions 1218. The circuit descriptions 1218 may include circuit descriptions for transmit and receive circuits 1220, one or more synchronization circuits 1222 (such as flip-flops), one or more multiplexers 1224, one or more encoders 1226, one or more delay circuits 1228, one or more error-detection logic circuits 1230, one or more memory cores 1232, one or more controller circuits 1234 and/or one or more retry logic circuits 1236.

Attention is now directed towards additional embodiments of unidirectional error-code transfer. In some embodiments, a controller includes a link interface, a first encoder, a first transmitter, a first delay element coupled to an output from the first encoder, a first receiver coupled to the link interface, a second encoder coupled to an output from the first receiver, a second receiver coupled to the link interface, and error-detection logic coupled to an output from the first delay element, an output from the second encoder and an output from the second receiver. The link interface is to couple to a first link to communicate bi-directional data and a second link to transmit unidirectional error-detection information. The first encoder is to dynamically add first error-detection information to at least a portion of write data. The first transmitter is to transmit the write data. The first receiver is to receive read data. The second encoder is to dynamically add second error-detection information to at least a portion of the read data. The second receiver is to receive third error-detection information corresponding to at least the portion of the read data and fourth error-detection information corresponding to at least the portion of the write data. The error-detection logic is to determine errors in at least the portion of the write data by comparing the first error-detection information and the fourth error-detection information, and is to determine errors in at least the portion of the read data by comparing the second error-detection information and the third error-detection information, and, if an error is detected, is to assert an error condition.

The controller may include retry logic to perform a retry remedial action if the error condition is asserted. In some embodiments, the retry remedial action includes re-transmitting the write data using the first transmitter and the link interface. In some embodiments, the retry remedial action includes re-receiving the read data using the first receiver and the link interface after the read data is re-transmitted by a device.

The controller may include a third encoder to dynamically add fifth error-detection information to at least a portion of write mask information and a second transmitter coupled to an output from the third encoder and to the link interface. The link interface may couple to a third link to transmit unidirectional command information including the fifth error-detection information. The link interface may couple to the first link to communicate the write mask information.

In another embodiment, a device includes a link interface, a first encoder, a first transmitter is coupled to the link interface, a first receiver coupled to the link interface, a second encoder coupled to an output from the first receiver, and a second transmitter coupled to the link interface, and selectively coupled to one of an output from the first encoder and an output from the second encoder. The link interface is to couple to a first link to communicate bi-directional data and a second link to receive unidirectional error-detection information. The first encoder is to dynamically add first error-detection information to at least a portion of read data. A first transmitter is to transmit the read data. The first receiver is to receive write data. The second encoder is to dynamically add second error-detection information to at least a portion of the write data.

The read data may be re-transmitted using the first transmitter and the link interface if the device receives remedial action instructions from a controller.

The write data may be re-received using the first receiver and the link interface if the device receives remedial action instructions from a controller.

The device may include a third encoder coupled to an output from the first receiver, a second receiver coupled to the link interface, and error-detection logic coupled to an output from the second receiver and an output from the third encoder. The third encoder is to dynamically add third error-detection information to at least a portion of write mask information. The link interface is to couple to a third link to receive unidirectional command information including fourth error-detection information. The error-detection logic is to determine errors in at least the portion of the write mask information by comparing the third error-detection information and the fifth error-detection information, and, if an error is detected, is to disable a write operation to a memory core.

In other embodiments, a system includes a first link to communicate bi-directional data, a second link to communicate unidirectional error-detection information, a controller, and a device. The controller includes a first link interface coupled to the first link and the second link, a first encoder to dynamically add first error-detection information to at least a portion of write data, a first transmitter coupled to the first link interface, a first delay element coupled to an output from the first encoder, a first receiver coupled to the first link interface, a second encoder coupled to an output from the first receiver, a second receiver coupled to the first link interface, and first error-detection logic coupled to an output from the first delay element, an output from the second encoder and an output from the second receiver. The first transmitter is to transmit the write data. The first receiver is to receive read data. The second encoder is to dynamically add second error-detection information to at least a portion of the read data. The second receiver is to receive third error-detection information corresponding to at least the portion of the read data and fourth error-detection information corresponding to at least the portion of the write data. The first error-detection logic is to determine errors in at least the portion of the write data by comparing the first error-detection information and the fourth error-detection information, and is to determine errors in at least the portion of the read data by comparing the second error-detection information and the third error-detection information, and, if an error is detected, is to assert an error condition. The device includes a second link interface coupled to the first link and the second link, a third encoder to dynamically add the third error-detection information to at least a portion of the read data, a second transmitter coupled to the second link interface, a third receiver coupled to the second link interface, a fourth encoder coupled to an output

from the third receiver, and a third transmitter coupled to the second link interface, and selectively coupled to one of an output from the third encoder and an output from the fourth encoder. The second transmitter is to transmit the read data. The third receiver is to receive the write data. The fourth encoder is to dynamically add the fourth error-detection information to at least a portion of the write data.

A retry remedial action may be performed if the error condition is asserted. In some embodiments, the retry remedial action includes instructions for re-transmitting the write data using the first transmitter and the link interface in the controller. In some embodiments, the retry remedial action includes instructions re-receiving the read data using the first receiver and the link interface in the controller after the read data is re-transmitted using the second transmitter and the second link interface in the device.

The system may include a third link to communicate unidirectional command information. The controller may include a fifth encoder to dynamically add fifth error-detection information to at least a portion of write mask information and a fourth transmitter coupled to an output from the third encoder and to the link interface. The first link interface is coupled to a third link to transmit unidirectional seventh error-detection information. The first link interface is coupled to the first link to communicate the write mask information. The device may include a sixth encoder coupled to an output from the third receiver, a fourth receiver coupled to the second link interface, and a second error-detection logic coupled to an output from the fourth receiver and an output from the fourth encoder. The sixth encoder is to dynamically add sixth error-detection information to at least a portion of the write mask information. The second link interface is coupled to the third link and the fourth receiver is to receive the fifth error-detection information. The second error-detection logic is to determine errors in at least the portion of the write mask information by comparing the fifth error-detection information and the sixth error-detection information, and, if an error is detected, is to disable a write operation to a memory core.

In another embodiment, a controller includes a link interface, an encoder to dynamically add first error-detection information to at least a portion of write data, a transmitter coupled to the link interface, a delay element coupled to an output from the encoder, a receiver coupled to the link interface, and error-detection logic coupled to an output from the delay element and an output from the receiver. The link interface is to couple to a first link to communicate bi-directional data and a second link to transmit unidirectional error-detection information. The transmitter is to transmit the write data. The receiver is to receive second error-detection information corresponding to at least the portion of the write data. The error-detection logic is to determine errors in at least the portion of the write data by comparing the first error-detection information and the second error-detection information, and, if an error is detected, is to assert an error condition.

In another embodiment, a controller includes a link interface, a first receiver coupled to the link interface, an encoder coupled to an output from the first receiver, a second receiver coupled to the link interface, and error-detection logic coupled to an output from the encoder and an output from the second receiver. The link interface is to couple to a first link to communicate bi-directional data and a second link to transmit unidirectional error-detection information. The first receiver is to receive read data. The encoder is to dynamically add first error-detection information to at least a portion of the read data. The second receiver is to receive second error-detection information corresponding to at least the portion of the read data. The error-detection logic is to determine errors in at least

the portion of the read data by comparing the first error-detection information and the second error-detection information, and, if an error is detected, is to assert an error condition.

In another embodiment, a system includes a link to communicate bi-directional data and unidirectional error-detection information, a controller, and a device. The controller includes a first link interface, a first encoder to dynamically add first error-detection information to at least a portion of write data, a first transmitter coupled to the first link interface, a first delay element coupled to an output from the first encoder, a first receiver coupled to the link interface, a second encoder coupled to an output from the first receiver and selectively coupled to an output from the first delay element, and error-detection logic coupled to an output from the second encoder and an output from the first receiver. The first link interface is to couple to the link. The first transmitter is to transmit the write data. The first receiver is to receive read data and second error-detection information corresponding to at least a portion of the read data and at least the portion of the write data. The second encoder is to dynamically add third error-detection information to at least the portion of the read data and at least the portion of the write data. The error-detection logic is to determine errors in at least the portion of the write data and at least the portion of the read data by comparing the second error-detection information and the third error-detection information, and, if an error is detected, is to assert an error condition. The device includes a second link interface, a second receiver coupled to the second link interface, a third encoder to dynamically add fourth error-detection information to at least a portion of write data, a second delay element coupled to an output from the third encoder, a fourth encoder coupled to read data and selectively coupled to an output from the second delay element, and a second transmitter coupled to the second link interface, selectively coupled to the read data and selectively coupled to an output from the fourth encoder. The second link interface is to couple to the link. The receiver is to receive write data. The fourth encoder is to dynamically add the second error-detection information to at least the portion of the write data and at least a portion of the read data. The second transmitter is to transmit the read data and the second error-detection information.

In another embodiment, a device includes a link interface, a receiver coupled to the link interface, a first encoder to dynamically add first error-detection information to at least a portion of write data, a delay element coupled to an output from the first encoder, a second encoder coupled to read data and selectively coupled to an output from the delay element, and a first transmitter coupled to the link interface, selectively coupled to the read data and selectively coupled to an output from the second encoder. The link interface is to couple to a link to communicate bi-directional data and unidirectional error-detection information. The receiver is to receive write data. The second encoder is to dynamically add second error-detection information to at least the portion of the write data and at least a portion of the read data. The first transmitter is to transmit the read data and the second error-detection information.

In another embodiment, a controller includes a link interface, a first encoder to dynamically add first error-detection information to at least a portion of write data, a transmitter coupled to the link interface, a delay element coupled to an output from the first encoder, a receiver coupled to the link interface, a second encoder coupled to an output from the receiver and selectively coupled to an output from the delay element, and error-detection logic coupled to an output from

19

the second encoder and an output from the receiver. The link interface is to couple to a link to communicate bi-directional data and unidirectional error-detection information. The transmitter is to transmit the write data. The first receiver is to receive read data and second error-detection information corresponding to at least a portion of the read data and at least the portion of the write data. The second encoder is to dynamically add third error-detection information to at least the portion of the read data and at least the portion of the write data. The error-detection logic is to determine errors in at least the portion of the write data and at least the portion of the read data by comparing the second error-detection information and the third error-detection information, and, if an error is detected, is to assert an error condition.

In another embodiment, a device includes a link interface, a first receiver coupled to the link interface, an encoder to dynamically add first error-detection information to at least a portion of the write mask information, a second receiver coupled to the link interface, and error-detection logic coupled to an output from the second receiver and an output from the encoder. The link interface is to couple to a first link to communicate write mask information and a second link to receive unidirectional error-detection information. The first receiver is to receive the write mask information. The second receiver is to receive second error-detection information. The error-detection logic is to determine errors in at least the portion of the write mask information by comparing the first error-detection information and the second error-detection information received by the second receiver, and, if an error is detected, is to disable a write operation to a memory core.

The foregoing descriptions of specific embodiments of the present invention are presented for purposes of illustration and description. They are not intended to be exhaustive or to limit the invention to the precise forms disclosed. Rather, it should be appreciated that many modifications and variations are possible in view of the above teachings. The embodiments were chosen and described in order to best explain the principles of the invention and its practical applications, to thereby enable others skilled in the art to best utilize the invention and various embodiments with various modifications as are suited to the particular use contemplated.

What is claimed is:

1. A solid state memory device comprising:
  - an input to receive a clock signal;
  - a memory core;
  - a link interface to receive write data bits in parallel, on rising and falling edges of the clock signal, and first error-detection information from a controller, the first error-detection information encoded by the controller in connection with the write data bits;
  - a circuit, coupled to the link interface, to generate second error-detection information corresponding to the received write data bits;
  - circuitry to determine an error event based on the first error-detection information and the second error-detection information and signal an error condition if the error event is detected; and
  - a buffer circuit to hold the write data bits in the event that the logic circuitry signals the error condition, wherein a write operation of the write data bits to the memory core is disabled if the error event is detected.
2. The memory device of claim 1, wherein the first error-detection information received from the controller is to include a first cyclic redundancy check (CRC) code, and the second error-detection information is to include a second CRC code.

20

3. The memory device of claim 1, wherein the memory device signals the error condition to the controller for the controller to perform a remedial action, wherein the remedial action is to include re-receiving the write data bits along with command information corresponding to the write data bits from the controller.

4. The memory device of claim 3, wherein the re-received command information is to have error protection provided by an error correction code.

5. The memory device of claim 1 wherein the link interface comprises a first receiver to receive the write data bits via a data link, and a second receiver to receive the first error-detection information via an error code link.

6. The memory device of claim 1, wherein the second receiver receives the first error detection information after a delay time expires relative to when the first receiver receives the write data bits.

7. The memory device of claim 1, wherein the solid state memory device is implemented on a chip.

8. The memory device of claim 7, further comprising:
 

- first flip-flop circuitry coupled to the first receiver, to synchronize reception of the write data bits to the clock signal; and
- second flip-flop circuitry coupled to the second receiver, to synchronize reception of the first error-detection information to the clock signal.

9. The memory device of claim 1 wherein circuitry to determine the error event detects the error based on a comparison between the first error-detection information and the second error-detection information.

10. A method of operation in a solid state memory device, the method comprising:

- receiving a write data bits in parallel, on rising and falling edges of a clock signal, and first error-detection information from a controller, the first error-detection information encoded by the controller using the write data bits;
- generating second error-detection information corresponding to the received write data bits;
- comparing the first error-detection information with the second error-detection information;
- signaling an error condition to the controller if comparing the first error-detection information with the second error-detection information signals an error condition; and
- performing a remedial action in the event of the error condition, the remedial action including disabling a write operation of the write data bits in the event of the error condition.

11. The method of claim 10, wherein the remedial action comprises re-receiving the write data bits.

12. The method of claim 10, wherein the first error-detection information received from the controller is to include a first cyclic redundancy check (CRC) code, and the second error-detection information is to include a second CRC code.

13. The method of claim 10, wherein the remedial action is to include re-receiving command information corresponding to the write data bits.

14. The method of claim 13, wherein the re-receiving the command information includes receiving an error correction code to protect the command information.

15. The method of claim 10 wherein receiving the write data bits and first error-detection information comprises:
 

- receiving the write data bits via a data link; and
- receiving the first error-detection information via an error code link.

**21**

**16.** The method of claim **15**, wherein receiving the write data bits and receiving the first error-detection information further comprises receiving the first error-detection information after a latency period transpires relative to receiving the write data bits.

**17.** The method of claim **10** further comprising performing a serial-to-parallel conversion on the write data bits and first error-detection information.

**18.** The method of claim **17** further comprising:  
synchronizing reception of the write data bits; and  
synchronizing reception of the first error-detection information.

**19.** The method of claim **18** wherein:  
synchronizing reception of the write data bits comprises  
synchronizing reception of the write data bits to the  
clock signal; and  
synchronizing reception of the first error-detection information comprises synchronizing reception of the first error-detection information to the clock signal.

**22**

**20.** A solid state memory device comprising:  
means for receiving a write data bits in parallel, on rising and falling edges of the a clock signal, and first error-detection information from a controller, the first error-detection information encoded by the controller in connection with the write data bits;  
means for generating second error-detection information corresponding to the received write data bits; and  
means for comparing the first error-detection information with the second error-detection information and signal an error condition based on the first error-detection information and the second error-detection information, the memory device to perform a remedial action in the event of the error condition, the remedial action including re-receiving the write data bits, and disabling a write operation of the write data bits in the event of the error condition.

\* \* \* \* \*