

US009305364B2

(12) **United States Patent**  
**Chen et al.**

(10) **Patent No.:** **US 9,305,364 B2**  
(45) **Date of Patent:** **Apr. 5, 2016**

(54) **MOTION ESTIMATION SYSTEMS AND METHODS**

(71) Applicant: **Caterpillar Inc.**, Peoria, IL (US)

(72) Inventors: **Qi Chen**, Dunlap, IL (US); **Paul Russell Friend**, Morton, IL (US)

(73) Assignee: **Caterpillar Inc.**, Peoria, IL (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 93 days.

(21) Appl. No.: **13/770,476**

(22) Filed: **Feb. 19, 2013**

(65) **Prior Publication Data**

US 2014/0233790 A1 Aug. 21, 2014

(51) **Int. Cl.**

**G06T 7/20** (2006.01)

**G01B 11/00** (2006.01)

**G01S 17/02** (2006.01)

**G01S 17/42** (2006.01)

**G01S 17/89** (2006.01)

**G01S 7/48** (2006.01)

**G01S 15/89** (2006.01)

(52) **U.S. Cl.**

CPC ..... **G06T 7/204** (2013.01); **G01S 7/4808** (2013.01); **G01S 17/023** (2013.01); **G01S 17/42** (2013.01); **G01S 17/89** (2013.01); **G01S 15/89** (2013.01); **G06T 2207/10016** (2013.01); **G06T 2207/10028** (2013.01)

(58) **Field of Classification Search**

CPC ..... G06T 2207/10016; G06T 7/2033; G06T 7/20; G06K 9/3241; G06K 9/00771

USPC ..... 382/103, 154, 106, 206; 345/154, 582; 356/5.01, 601; 340/154

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,771,840 B1 \* 8/2004 Ioannou et al. .... 382/285  
7,336,805 B2 2/2008 Gehring et al.

(Continued)

FOREIGN PATENT DOCUMENTS

GB 201116959 D0 \* 11/2011 ..... 356/4.01  
WO WO2011/146523 11/2011

OTHER PUBLICATIONS

Motion Segmentation and Scene Classification from 3D LIDAR Data; Dominik Steinhäuser, . . . ; 2008 IEEE Intelligent Vehicles Symposium; Eindhoven University of Technology; Eindhoven, The Netherlands, Jun. 4-6, 2008 Technische University Munchen, Munich, Germany.\*

(Continued)

*Primary Examiner* — Stephen R Koziol


*Assistant Examiner* — Pinalben Patel

(74) *Attorney, Agent, or Firm* — Finnegan, Henderson, Farabow, Garrett & Dunner, LLP

(57) **ABSTRACT**

A motion estimation system is disclosed. The motion estimation system may include one or more memories storing instructions, and one or more processors configured to execute the instructions to receive, from a scanning device, scan data representing at least one object obtained by a scan over at least one of the plurality of sub-scanning regions, and generate, from the scan data, a sub-pointcloud for one of the sub-scanning regions. The sub-pointcloud includes a plurality of surface points of the at least one object in the sub-scanning region. The one or more processors may be further configured to execute the instructions to estimate the motion of the machine relative to the at least one object by comparing the sub-pointcloud with a reference sub-pointcloud.

**18 Claims, 4 Drawing Sheets**



(56)

References Cited

U.S. PATENT DOCUMENTS

7,643,966 B2 \* 1/2010 Adachi et al. .... 703/1  
7,728,833 B2 6/2010 Verma et al.  
8,208,689 B2 6/2012 Savolainen et al.  
8,340,400 B2 \* 12/2012 Lukas et al. .... 382/154  
8,473,144 B1 \* 6/2013 Dolgov et al. .... 701/28  
8,805,015 B2 \* 8/2014 Chang et al. .... 382/103  
2003/0067461 A1 \* 4/2003 Fletcher et al. .... 345/420  
2009/0232355 A1 \* 9/2009 Minear et al. .... 382/103  
2009/0262974 A1 10/2009 Lithopoulos  
2010/0074473 A1 \* 3/2010 Kotaba .... 382/106  
2010/0121577 A1 \* 5/2010 Zhang et al. .... 701/301  
2010/0302247 A1 \* 12/2010 Perez et al. .... 345/440


2011/0200248 A1 \* 8/2011 Matabosch I Gerones  
et al. .... 382/154  
2011/0205338 A1 \* 8/2011 Choi et al. .... 348/46  
2011/0274343 A1 \* 11/2011 Krishnaswamy et al. .... 382/154  
2012/0121132 A1 \* 5/2012 Asahara et al. .... 382/103  
2013/0156262 A1 \* 6/2013 Taguchi et al. .... 382/103  
2013/0179119 A1 \* 7/2013 Coddington et al. .... 702/159  
2014/0016821 A1 \* 1/2014 Arth et al. .... 382/103  
2014/0233010 A1 \* 8/2014 Baldwin et al. .... 356/4.01

OTHER PUBLICATIONS


Ernesto Homar, Registration of 3-D Points Clouds For Urban Robot  
Mappings, IRI, 2008.\*

\* cited by examiner


100




**FIG. 1**




**FIG. 2**




**FIG. 3**

**FIG. 4**





**FIG. 5**



**FIG. 6**

## 1

MOTION ESTIMATION SYSTEMS AND  
METHODS

## TECHNICAL FIELD

The present disclosure relates generally to systems and methods for motion estimation, more specifically, to systems and methods for motion estimation by using pointclouds.

## BACKGROUND

Autonomously controlled and/or semi-autonomously controlled machines are capable of operating with little or no human input by relying on information received from various machine systems. For example, a machine guidance system may detect a location and movement of the machine based on inputs received about the machine's environment and may then control future movements of the machine based on the detected location and movement. In order to effectively guide the machine, however, it may be desirable to ensure that the location and movement of the machine are being detected and updated with a frequency high enough to ensure proper machine operation.

U.S. Pat. No. 7,336,805 to Gehring et al. that was issued on Feb. 26, 2008 ("the '805 patent") discloses an exemplary guidance system for a motor vehicle. Specifically, the system acquires image data of a surrounding field of the motor vehicle by using an imaging sensor. The system then extracts positional parameters of at least one potential destination relative to the motor vehicle from the acquired image data. Based on the extracted positional parameters, the system calculates an optimized travel path, so as to assist a subsequent vehicle guidance for the at least one potential destination.

Although the system of the '805 patent may be useful in guiding a motor vehicle along an optimized travel path, the system of the '805 patent calculates the travel path based on the image data of the entire surrounding field of the motor vehicle. Due to the large size of the image data, the calculation may unnecessarily consume large amounts of computing resources. As a result, the system of the '805 patent may not provide and update the optimized travel path with a high enough frequency.

The motion estimation system of the present disclosure is directed toward solving the problem set forth above and/or other problems of the prior art.

## SUMMARY

In one aspect, the present disclosure is directed to a motion estimation system. The motion estimation system may include one or more memories storing instructions, and one or more processors configured to execute the instructions to receive, from a scanning device, scan data representing at least one object obtained by a scan over at least one of the plurality of sub-scanning regions, and generate, from the scan data, a sub-pointcloud for one of the sub-scanning regions. The sub-pointcloud includes a plurality of surface points of the at least one object in the sub-scanning region. The one or more processors may be further configured to execute the instructions to estimate the motion of the machine relative to the at least one object by comparing the sub-pointcloud with a reference sub-pointcloud.

In another aspect, the present disclosure is directed to a computer-implemented method of estimating a motion of a machine. The method may include dividing a full scanning region into a plurality of sub-scanning regions. The method

## 2

may also include receiving, from a scanning device, scan data representing at least one object obtained by a scan over at least one of the plurality of sub-scanning regions. The method may further include generating, by a processor, a sub-pointcloud from the scan data for one of the sub-scanning regions. The sub-pointcloud may include a plurality of surface points of the at least one object in the sub-scanning region. The method may still further include estimating, by the processor, the motion of the machine relative to the at least one object by comparing the sub-pointcloud with a reference sub-pointcloud.

In still another aspect, the present disclosure is directed to a system for motion estimation. The system may include a scanning device capable of being mounted on a machine and configured to scan at least one object over a sub-scanning region among a plurality of sub-scanning regions of a full scanning region and generate a sub-pointcloud of the sub-scanning region. The sub-pointcloud may include a plurality of surface points of the at least one object in the sub-scanning region. The system may also include a controller configured to estimate a motion of the machine relative to the at least one object by comparing the sub-pointcloud with a corresponding reference sub-pointcloud.

## BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic illustration of a work site and an exemplary machine consistent with certain disclosed embodiments.

FIG. 2 is a schematic illustration of a scanning mechanism that may be included in the machine of FIG. 1.

FIG. 3 is a schematic illustration of a method of motion estimation that may be performed by the machine of FIG. 1.

FIG. 4 is a flowchart depicting an exemplary method of motion estimation that may be performed by the machine of FIG. 1.

FIG. 5 is a schematic illustration of a method of motion estimation that may be performed by the machine of FIG. 1.

FIG. 6 is a schematic illustration of a method of motion estimation that may be performed by the machine of FIG. 1.

## DETAILED DESCRIPTION

FIG. 1 illustrates an environment **100** and an exemplary machine **110** performing a task at environment **100**. Environment **100** may be a worksite such as, for example, a mine site, a landfill, a quarry, a construction site, or any other type of environment. Environment **100** may also be an exploration site in a location that might be difficult for a human operator to be present, such as another planet. Environment **100** may include one or more moving or stationary objects **120** located a particular distance from machine **110**. For example, objects **120** may include landmarks, geological markers, trees, buildings, drills, pipelines, etc.

Machine **110** may embody a machine configured to perform some type of operation associated with an industry such as mining, construction, farming, transportation, power generation, or any other industry known in the art. For example, machine **110** may be an earth moving machine such as a haul truck, a dozer, a loader, a backhoe, an excavator, a motor grader, a wheel tractor scraper or any other earth moving machine. Alternatively, machine **110** may be a planetary exploration robot. Machine **110** may travel along a certain travel direction in environment **100**. Machine **110** may also rotate or circle around a certain axis.

Machine **110** may include a motion estimation system **130** for estimating an ego motion of machine **110**. "Ego motion",



as used herein, refers to the three-dimensional (3D) motion of machine **110** relative to objects **120** within environment **100**. The ego motion may have six parameters, three for translation velocities in x, y, z coordinates, and three for rotation angles (yaw, pitch, and roll), although any other coordinate system with different parameters may be used.

Motion estimation system **130** may include a scanning device **140** and a controller **150** connected to each other by a bus **160**. While a bus architecture is shown in FIG. **1**, any suitable architecture may be used, including any combination of wired and/or wireless networks. Additionally, such networks may be integrated into any local area network, wide area network, and/or the Internet.

Scanning device **140** may be mounted on a surface of machine **110** to sense objects **120** within a particular region that is scanned by scanning device **140**. Scanning device **140** may be, for example, a LIDAR (light detection and ranging) device, a RADAR (radio detection and ranging) device, a SONAR (sound navigation and ranging) device, optical device such as a camera, or another device known in the art. In one example, scanning device **140** may include an emitter that emits a detection beam, and an associated receiver that receives any reflection of that detection beam. Based on characteristics of the received beam, scanning device **140** may generate scan data representing objects **120** within the particular region that is scanned by scanning device **140**.

Motion estimation system **130** may also include other sensors such as, for example, accelerometers, gyroscopes, global positioning system (GPS) devices, radar devices, etc. These sensors may be used to measure, e.g., location, horizontal, vertical, and forward velocities and accelerations, inclination angle (e.g., pitch), inclination angular rate, heading, yaw rate, roll angle, roll rate, etc.

Controller **150** may receive scan data transmitted by scanning device **140**, and determine an ego motion of machine **110** based on the scan data. Based on the determined ego motion, controller **150** may control movement of machine **110**. Controller **150** may also control the scanning movement of scanning device **140**.

Controller **150** may include processor **152**, storage **154**, and memory **156**, included together in a single device and/or provided separately. Processor **152** may include one or more known processing devices, such as a microprocessor from the PENTIUM™ or XEON™ family manufactured by INTEL™, the TURION™ family manufactured by AMD™, or any other type of processor. Memory **156** may include one or more storage devices configured to store information used by controller **150** to perform certain functions related to disclosed embodiments. Storage **154** may include a volatile or non-volatile, magnetic, semiconductor, tape, optical, removable, nonremovable, or other type of storage device or computer-readable medium. Storage **154** may store programs and/or other information, such as information related to processing data received from scanning device **140**, as discussed in greater detail below.

FIG. **2** schematically illustrates a scanning mechanism of scanning device **140**. In one embodiment, scanning device **140** may be configured to rotate about an axis **O** in 360 degrees to scan a full scanning region **200**, which is shown as a circle having a center at scanning device **140**. As it scans full scanning region **200**, scanning device **140** may generate scan data representing objects **120** within the 360 degrees of full scanning region **200**, and transmit the scan data to controller **150**. Based on the scan data, controller **150** may generate a first pointcloud. A “pointcloud”, as used herein, is a 3D pointcloud that includes a plurality of data points. Each data point within the first pointcloud may correspond to a 3D coordi-

nate, such as (x, y, z), of one of a plurality of surface points of objects **120** within full scanning region **200** relative to scanning device **140**. Thus, the first pointcloud may be a representation of the environment around machine **110** within full scanning region **200**. In some embodiments, scanning device **140** may generate the pointcloud by itself, and output the generated pointcloud to controller **150**.

While the embodiment of FIG. **2** describes scanning device **140** as being rotatable about axis **O**, in other embodiments, scanning device **140** may be configured to scan full scanning region **200** without rotating. For example, when scanning device **140** includes a LIDAR device, one or more optical devices internal to or external to scanning device **140** may cause a laser beam to cover full scanning region **200** without the need for scanning device **140** itself to rotate about axis **O**. In another example, scanning device **140** may sweep back and forth to scan full scanning region **200**. Moreover, while FIG. **2** illustrates that full scanning region **200** includes 360 degrees, the present disclosure is not so limited, and full scanning region **200** may be any portion of the 360 degrees, such as 180 degrees, 90 degrees, etc., based on the application of machine **110**.

Because scanning device **140** is mounted to machine **110**, it moves as machine **110** moves. As it moves, scanning device **140** may continuously generate scan data from full scanning region **200**. However, because it is moving, the scan data from a subsequent scan of full scanning region **200** may differ from that of a previous scan on full scanning region **200**. Thus, for example, if controller **150** generates a the second pointcloud representing a subsequent scan, it may differ from the first pointcloud. Controller **150** may compare the second pointcloud with the first pointcloud to estimate the ego motion of scanning device **140**, and thereby estimate the ego motion of machine **110** on which scanning device **140** is mounted.

In some embodiments, controller **150** may derive a transformation matrix **M** for transforming the second pointcloud, which may be represented by matrix **B**, into a transformed pointcloud **M×B** such that a difference between the transformed pointcloud **M×B** and the first pointcloud does not exceed a threshold. For example, transformation matrix **M** may be derived to minimize an average difference between each one of the (x, y, z) coordinates of each data point in the transformed pointcloud **M×B** and its nearest point in the first pointcloud. To validate the transformation matrix **M**, the threshold may be implemented so that the minimized average difference is smaller than a threshold value such as, for example, 1 mm, or any other value determined, for example, based on the application of machine **110** and characteristics of objects **120** within environment **100**. Transformation matrix **M** may be used to estimate the ego motion of machine **110**. For example, transformation matrix **M** may include one or more values representing an estimated change in position of machine **110** in one or more directions, such as along the x-, y-, or z-axes and/or an estimated change in the orientation of machine **110**, such as a change in yaw, pitch, or roll angles. If the minimized average difference is still higher than the threshold, then a valid transformation matrix **M** could not be found between the first pointcloud and the second pointcloud. In such case, controller **150** could not estimate the ego motion of machine **110**.

In certain embodiments, the first and second pointclouds generated by controller **150** may include tens of thousands or even millions of data points. The large number of data points may make it computationally expensive to calculate the ego motion of machine **110** using the entire set of data points. In addition, due to various mechanical constraints, a full scan of 360 degrees by scanning device **140** may take approximately



## 5

0.1 second. Thus, if controller **150** waits for the full scan to be completed before estimating the ego motion of machine **110**, controller **150** may be limited to doing so at a frequency of approximately 10 Hz. In certain embodiments, such a frequency may not be high enough for properly controlling the movement of machine **110**.

FIG. **3** schematically illustrates an exemplary method of motion estimation that may be performed by motion estimation system **130** to increase the frequency with which the ego motion of machine **110** may be determined and to reduce the computational requirements associated with doing so. In this embodiment, full scanning region **300** may be divided into N sub-scanning regions, wherein N is any integer greater than 1. In the exemplary embodiment as shown in FIG. **3**, full scanning region **300** is divided into ten sub-scanning regions **300a-300j**. Each one of sub-scanning regions **300a-300j** is shown as a sector of full scanning region **300**. Based on scan data received from scanning device **140** for each one of sub-scanning regions **300a-300j**, controller **150** may generate a sub-pointcloud for each one of the ten sub-scanning regions **300a-300j**. Controller **150** may compare each sub-pointcloud with a reference sub-pointcloud, and estimate the ego motion based on the comparison. A reference sub-pointcloud may be, for example, a sub-pointcloud determined based on a previous scan of scanning device **140** over a sub-region of full scanning region **300**.

In this way, controller **150** does not have to wait for the full scan of 360 degrees to be completed in order to estimate the ego motion. Rather, controller **150** may estimate the ego motion after a scan over a sub-scanning region is completed, thus increasing the frequency at which controller **150** outputs an ego motion estimation by a factor of N, the number of sub-scanning regions contained within full scanning region **300**. In addition, the number of data points in one sub-pointcloud is N times less than the number of data points in the full pointcloud. Therefore, the computational complexity for estimating the ego motion is also lowered, enabling faster calculations of the ego motion estimation.

Although FIG. **3** shows that full scanning region **300** is divided into N sub-scanning regions in the x-y plane defined by the rotational movement of scanning device **140**, the present disclosure is not so limited. When scanning device **140** is a LiDAR device, it may project more than one, for example, 64, laser beams, and thus it may cover a three-dimensional full scanning region. In this case, the three-dimensional full scanning region may be divided into N sub-scanning regions vertically, e.g., in a z-direction that is perpendicular to the x-y plane. Alternatively, the full scanning region may first be divided into N sub-scanning regions in the x-y plane, and then each sub-scanning region may be further divided into M sub-scanning regions vertically. Therefore, the number of data points in each sub-pointcloud may be further reduced.

The reference sub-pointcloud may be selected among a plurality of reference sub-pointclouds. In some embodiments, the plurality of reference sub-pointclouds may be stored in storage **154**. For example, scanning device **140** may scan over full scanning region **300** including sub-scanning regions **300a-300j**, and controller **150** may generate and store sub-pointclouds for respective sub-scanning regions **300a-300j** in storage **154** as the plurality of reference sub-pointclouds. The reference sub-pointclouds may be updated every time when a scan over the same sub-scanning region is performed.

The operation of motion estimation system **130** will now be described in connection with the flowchart of FIG. **4**. First, controller **150** may divide a full scanning region into a plu-

## 6

ality of sub-scanning regions (step **410**). For example, controller **150** may determine how to divide full scanning region **300** and the number N of the sub-scanning regions based on a user input, the size and characteristics of environment **100** (e.g., surface roughness, density of objects **120** within environment **100**, etc.), the capabilities of processor **152**, a speed of scanning device **140**, a speed of machine **110**, or any combination of the above.

Then, scanning device **140** may perform may scan a first sub-scanning region, e.g., sub-scanning region **300a** (step **412**). Scanning device **140** may transmit scan data obtained by the scan over sub-scanning region **300a** to controller **150**. Based on the scan data, controller **150** may generate a sub-pointcloud for sub-scanning region **300a** (step **414**). Alternatively, scanning device **140** may generate the sub-pointcloud by itself, and transmit the generated sub-pointcloud to controller **150**. Then, controller **150** may determine whether a reference sub-pointcloud for the same sub-scanning region, i.e., sub-scanning region **300a**, exists in storage **154** (step **416**).

When scanning device **140** has previously scanned sub-scanning region **300a**, a reference sub-pointcloud has been previously generated for scanned sub-scanning region **300a** and stored in storage **154**. In such case, controller **150** may determine that a reference sub-pointcloud for the same sub-scanning region exists in storage **154** (step **416**, Yes), and then controller **150** may estimate an ego motion of machine **110** by comparing the sub-pointcloud with one of a plurality of reference sub-pointclouds stored in storage **154** (step **418**). Controller **150** may output a signal representing the estimated ego motion (step **420**). Controller **150** may also store the sub-pointcloud in storage **154** as a new reference sub-pointcloud for sub-scanning region **300a** (step **422**).

When scanning device **140** has not previously scanned sub-scanning region **300a**, controller **150** may determine that a reference sub-pointcloud for sub-scanning region **300a** does not exist in storage **154** (step **416**, No). Then, the process may move directly to step **422** where the sub-pointcloud is stored as a new referenced sub-pointcloud for sub-scanning region **300a**.

Afterwards, controller **150** may determine whether to continue the motion estimation (step **424**). For example, controller **150** may check to see if a stop signal is received from an upper level controller, or from a user. When controller **150** determines that it should continue the motion estimation (step **424**, Yes), controller **150** may instruct scanning device **140** to scan a subsequent sub-scanning region, i.e., sub-scanning region **300b** (step **426**). Then, the process may return to step **414** where a sub-pointcloud is generated based on the scan data obtained by the scan over sub-scanning region **300b**. When controller **150** determines that it should not continue the motion estimation (step **424**, No), the motion estimation process will end.

Controller **150** may select the reference sub-pointcloud among the plurality of reference sub-pointclouds stored in storage **154** based on a previously estimated motion of machine **110**, the number of the sub-scanning regions, and/or a rotation speed of scanning device **140**. For example, controller **150** may first determine linear velocities along the x-, y-, or z-axes, and angular velocities (yaw rate, roll rate, and pitch rate) of machine **110** based on a previously estimated motion of machine **110**. Based on the linear velocities and the angular velocities of machine **110**, and the rotation speed of scanning device **140**, controller **150** may estimate the amount of displacement between a plurality of current sub-scanning regions covered by a current scan and a plurality of previous sub-scanning regions covered by a previous scan. Then, con-



troller **150** may select a previous sub-scanning region that substantially overlaps with a current sub-scanning region, and select the reference sub-pointcloud corresponding to that previous sub-scanning region for estimating motion. “Sub-  
substantially overlap”, as used herein, refers to a situation in  
which the previous sub-scanning region has more than half of  
its area in common with the current sub-scanning region.

For example, machine **110** may be moving in a linear direction indicated by an arrow **510** in FIG. **5**. A first scan by scanning device **140** may cover full scanning region **500** which may be divided into N sub-scanning regions starting with a sub-scanning region **500a**. A second and subsequent scan by scanning device **140** may cover full scanning region **500'** which may be divided into N sub-scanning regions starting with a sub-scanning region **500a'**. Because the linear velocity of machine **110** is small, sub-scanning regions **500a** and **500a'** overlap with each other, and cover substantially the same object. Therefore, controller **150** may use a sub-pointcloud corresponding to sub-scanning region **500a** as a reference sub-pointcloud, and compare a sub-pointcloud corresponding to sub-scanning region **500a'** with the reference sub-pointcloud, to estimate the ego motion of machine **110**.

In some embodiments, when the number N of sub-scanning regions exceeds a threshold value, and the velocity of machine **110** is large relative to the revolution rate of scanning device **140**, the reference sub-pointcloud may be generated based on scan data obtained by a previous scan over a different sub-scanning region. For example, machine **110** may be rotating in a direction indicated by an arrow **610** in FIG. **6**. A first scan by scanning device **140** may cover full scanning region **600** which may be divided into N sub-scanning regions starting with a sub-scanning region **600a**. A second and subsequent scan by scanning device **140** may cover full scanning region **600'** which may be divided into N sub-scanning regions starting with a sub-scanning region **600a'**. Because the angular velocity of machine **110** is large, sub-scanning region **600a'** does not overlap with sub-scanning region **600a**. Rather, sub-scanning region **600a'** substantially overlap with sub-scanning region **600c**. Therefore, controller **150** use a sub-pointcloud corresponding to sub-scanning region **600c** as a reference sub-pointcloud, and compare a sub-pointcloud corresponding to sub-scanning region **600a'** with the reference sub-pointcloud to estimate the ego motion of machine **110**.

In some embodiments, controller **150** may analyze the reference sub-pointclouds stored in storage **154** and the previously estimated ego motion, and instruct scanning device **140** to scan only a subset of the sub-scanning regions. For example, as shown in FIG. **5**, at time t1, controller **150** may receive scan data from a scan over full scanning region **500** and may generate sub-pointclouds for each of the sub-scanning regions as the reference sub-pointclouds. By analyzing the reference sub-pointclouds, controller **150** may determine that object **120** is only present in sub-scanning region **500a**. Additionally, by referring to the previously estimated ego motion, controller **150** may determine that machine **110** is moving in the linear direction indicated by arrow A. Therefore, controller **150** may instruct scanning device **140** to scan, at time t2, only sub-scanning region **500a'**, rather than the entire full scanning region **500**.

In another example, as shown in FIG. **6**, at time t1, controller **150** may determine that object **120** is only present in sub-scanning region **600a**. Controller **150** may also estimate that, based on the estimated ego motion of machine **110**, sub-scanning region **600i'** would correspond to sub-scanning region **600a**. Then, controller **150** may instruct scanning device **140** to scan only sub-scanning region **600i'** at time t2.

In this way, computation resource and power required for motion estimation may be further reduced.

#### INDUSTRIAL APPLICABILITY

The disclosed motion estimation system **130** may be applicable to any machine where motion estimation is desired. According to the above embodiments, the disclosed motion estimation system **130** estimates the ego motion of machine **110** after scanning device **140** completes a scan over a sub-scanning region. Therefore, the disclosed motion estimation system **130** allows for a faster output rate of the ego motion.

In addition, the disclosed motion estimation system **130** estimates the ego motion of machine **110** based on data points contained in sub-pointclouds, the number of which is N times less than the number of data points in the full pointcloud. Therefore, the disclosed motion estimation system **130** allows for a lower computational requirement.

It will be apparent to those skilled in the art that various modifications and variations can be made to the disclosed motion estimation system. Other embodiments will be apparent to those skilled in the art from consideration of the specification and practice of the disclosed motion estimation system. It is intended that the specification and examples be considered as exemplary only, with a true scope being indicated by the following claims and their equivalents.

What is claimed is:

**1.** A system for estimating a motion of a machine, the system comprising:

one or more memories storing instructions; and

one or more processors configured to execute the instructions to:

divide a full scanning region into a plurality of sub-scanning regions;

receive, from a scanning device, first scan data representing at least one object obtained by a first scan over the full scanning region;

generate, from the first scan data, a plurality of first sub-pointclouds for the plurality of sub-scanning regions included in the full scanning region;

store the plurality of first sub-pointclouds as a plurality of reference sub-pointclouds in a storage device;

receive, from the scanning device, second scan data representing the at least one object obtained by a second scan over less than the full scanning region and including at least one of the plurality of sub-scanning regions;

generate, from the second scan data, a second sub-pointcloud, the second sub-pointcloud including a plurality of surface points of the at least one object in the sub-scanning region;

select a reference sub-pointcloud among the plurality of reference sub-pointclouds obtained by the first scan;

estimate the motion of the machine relative to the at least one object by comparing the second sub-pointcloud with the selected reference sub-pointcloud; and

update at least one of the reference sub-pointclouds with the second sub-pointcloud.

**2.** The system of claim **1**, wherein the one or more processors are further configured to derive a transformation matrix for transforming the sub-pointcloud into a transformed pointcloud such that a difference between the transformed pointcloud and the reference sub-pointcloud does not exceed a threshold, and estimate the motion of the machine based on the transformation matrix.

**3.** The system of claim **1**, wherein the reference sub-pointcloud is selected such that the reference sub-pointcloud cor-



9

responds to a previous sub-scanning region covered by a previous scan and the previous sub-scanning region substantially overlaps with said one of the sub-scanning regions.

4. The system of claim 1, wherein the full scanning region is a circle having a center at the scanning device, and each sub-scanning region is a sector of the full scanning region.

5. The system of claim 1, wherein the one or more processors are further configured to: generate a sub-pointcloud for each the plurality of sub-scanning regions, and estimate the motion of the machine by comparing the sub-pointcloud for each sub-scanning region to a corresponding reference sub-pointcloud.

6. The system of claim 1, wherein the one or more processors are further configured: receive, from the scanning device, initial scan data obtained by an initial scan over the plurality of sub-scanning regions; generate, from the initial scan data, reference sub-pointclouds for the respective sub-scanning regions; store the reference sub-pointclouds in a storage device; and update at least one of the reference sub-pointclouds when scan data is received for the corresponding sub-scanning region.

7. The system of claim 6, wherein the one or more processors are further configured to analyze the reference sub-pointclouds and a previously estimated ego motion, and instruct the scanning device to scan a subset of the sub-scanning regions based on a result of the analysis.

8. The system of claim 1, wherein the sub-pointcloud includes three-dimensional coordinates information of at least a subset of points of the at least one object.

9. A computer-implemented method of estimating a motion of a machine, comprising:

dividing a full scanning region into a plurality of sub-scanning regions;

receiving, from a scanning device, first scan data representing at least one object obtained by a first scan over the full scanning region;

generating, from the first scan data, a plurality of sub-pointclouds for the plurality of sub-scanning regions included in the full scanning region;

storing the plurality of sub-pointclouds as a plurality of reference sub-pointclouds in a storage device;

receiving, from the scanning device, second scan data representing the at least one object obtained by a second scan over less than the full scanning region and including at least one of the plurality of sub-scanning regions;

generating, by a processor, a second sub-pointcloud from the second scan data, the second sub-pointcloud including a plurality of surface points of the at least one object in the sub-scanning region;

selecting, by the processor, a reference sub-pointcloud among the plurality of reference sub-pointclouds obtained by the first scan;

estimating, by the processor, the motion of the machine relative to the at least one object by comparing the second sub-pointcloud with the selected reference sub-pointcloud; and

updating at least one of the reference sub-pointclouds with the second sub-pointcloud.

10. The method of claim 9, further including: deriving a transformation matrix for transforming the sub-pointcloud into a transformed pointcloud such that a

10

difference between the transformed pointcloud and the reference sub-pointcloud does not exceed a threshold; and

estimating the motion of the machine based on the transformation matrix.

11. The method of claim 9, wherein the reference sub-pointcloud is selected such that the reference sub-pointcloud corresponds to a previous sub-scanning region covered by a previous scan and the previous sub-scanning region substantially overlaps with said one of the sub-scanning regions.

12. The method of claim 9, further including: generating a sub-pointcloud for each one of the plurality of sub-scanning regions; and estimating the motion of the machine relative to the at least one object based on the sub-pointcloud for each sub-scanning region.

13. The method of claim 9, further including: receiving, from the scanning device, initial scan data obtained by an initial scan over the plurality of sub-scanning regions; generating, from the initial scan data, reference sub-pointclouds for the respective sub-scanning regions; storing the reference sub-pointclouds in a storage device; and

updating at least one of the reference sub-pointclouds when scan data is received for the corresponding sub-scanning region.

14. The method of claim 13, further including: analyzing the reference sub-pointclouds and a previously estimated ego motion; and instructing the scanning device to scan a subset of the sub-scanning regions based on the analysis result.

15. The method of claim 9, wherein the sub-pointcloud includes three-dimensional coordinates information of at least a subset of points of the at least one object.

16. A system, comprising:

a scanning device capable of being mounted on a machine and configured to:

scan at least one object over a full scanning region;

generate a plurality of first sub-pointclouds for a plurality of sub-scanning regions of the full scanning region;

scan the at least one object over a sub-scanning region less than the full scanning region and among the plurality of sub-scanning regions; and

generate a second sub-pointcloud of the sub-scanning region, the second sub-pointcloud including a plurality of surface points of the at least one object in the sub-scanning region; and

a controller configured to:

store the plurality first sub-pointclouds as a plurality of reference sub-pointclouds in a storage device;

select a reference sub-pointcloud among the plurality of reference sub-pointclouds;

estimate a motion of the machine relative to the at least one object by comparing the second sub-pointcloud with the selected reference sub-pointcloud; and

update at least one of the reference sub-pointclouds with the second sub-pointcloud.

17. The system of claim 16, wherein the scanning device is a light detection and ranging (LIDAR) unit that includes:

a light projecting unit configured to project a light beam to the at least one object and scan the light beam over the sub-scanning region; and

a photo sensing unit configured to sense a feedback light beam from the at least one object to generate the sub-pointcloud.

18. The system of claim 16, wherein:  
the scanning device is further configured to scan the at least  
one object by rotating about an axis in 360 degrees,  
the full scanning region is a circle having a center at the  
scanning device, and  
each sub-scanning region is a sector of the full scanning  
region.

5

\* \* \* \* \*