



US009314108B2

(12) **United States Patent**
DeFranks et al.

(10) **Patent No.:** **US 9,314,108 B2**
(45) **Date of Patent:** **Apr. 19, 2016**

(54) **PLUNGER MATRIX MATTRESS ASSEMBLIES**

(71) Applicant: **DREAMWELL, LTD.**, Las Vegas, NV (US)

(72) Inventors: **Michael S. DeFranks**, Atlanta, GA (US); **Rahul Kirtikar**, Atlanta, GA (US); **J. Evan Spirk**, Gates Mills, OH (US); **Gary R. Stephan**, Seven Hills, OH (US); **Craig Saunders**, Rocky River, OH (US)

(73) Assignee: **DREAMWELL, LTD.**, Las Vegas, NV (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 254 days.

(21) Appl. No.: **14/084,859**

(22) Filed: **Nov. 20, 2013**

(65) **Prior Publication Data**

US 2014/0137333 A1 May 22, 2014

Related U.S. Application Data

(60) Provisional application No. 61/728,565, filed on Nov. 20, 2012, provisional application No. 61/825,748, filed on May 21, 2013, provisional application No. 61/879,437, filed on Sep. 18, 2013.

(51) **Int. Cl.**
A47C 27/04 (2006.01)
A47C 27/06 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC *A47C 27/04* (2013.01); *A47C 23/002* (2013.01); *A47C 23/125* (2013.01); *A47C 27/00* (2013.01); *A47C 27/06* (2013.01); *A47C 27/14* (2013.01); *F16F 3/00* (2013.01)

(58) **Field of Classification Search**
CPC *A47C 27/04*
USPC 5/716–719, 722, 933; 267/142, 267/220–221

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

52,585 A 2/1866 McClanatham
66,849 A 7/1867 Johnson

(Continued)

FOREIGN PATENT DOCUMENTS

AT 383260 B 6/1987
BE 415647 A 6/1936

(Continued)

OTHER PUBLICATIONS

Notification Concerning Transmittal of International Preliminary Report on Patentability (Chapter I of the Patent Cooperation Treaty), issued in International Application No. PCT/US2013/070907, dated Jun. 4, 2015; 9 pages.

(Continued)


Primary Examiner — Fredrick Conley

(74) *Attorney, Agent, or Firm* — Cantor Colburn LLP

(57) **ABSTRACT**

A plunger matrix mattress includes a number of independently movable foam padded plungers that form an array of independently movable points of support. This type of mattress significantly improves body contouring over conventional coil spring mattress designs. The plunger matrix mattress also allows substantial airflow through the mattress improving over conventional foam mattress designs. Different plungers may have different spring and dampening characteristics to allow different plungers and plunger zones of the mattress to exhibit different firmness levels. Individual plungers may be removed and replaced independently, for example to replace the plunger with another plunger with a different spring characteristic, and make other types of adjustments and repairs. A variety of optional design features and configurations provide for a wide range of alternative configurations with differing levels of sophistication and functionality to produce a range of models designed to meet differing customer preferences and price points.

20 Claims, 24 Drawing Sheets



* cited by examiner




FIG. 1




FIG. 2




FIG. 3A

34




FIG. 3B




FIG. 4




FIG. 5




FIG. 6









FIG. 7






FIG. 9A




FIG. 9B




FIG. 9C




FIG. 9D




FIG. 9E




FIG. 9F




FIG. 9G




FIG. 9H




FIG. 10




FIG. 11A




FIG. 11B




FIG. 11C




FIG. 12




FIG. 13A




FIG. 13C




FIG. 13B




FIG. 13D




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21A




FIG. 21B




FIG. 21C








FIG. 22






FIG. 24A




FIG. 24B




FIG. 24C

1

**PLUNGER MATRIX MATTRESS
ASSEMBLIES****CROSS REFERENCE TO RELATED
APPLICATION**

This application claims priority to U.S. Provisional Patent Application Ser. No. 61/728,565 entitled "Mattress Assemblies" filed Nov. 20, 2012; and U.S. Provisional Patent Application Ser. No. 61/825,748 entitled "Mattress Assemblies" filed May 21, 2013, and U.S. Provisional Patent Application Ser. No. 61/879,437 entitled "Support Systems Including Wave Springs" filed Sep. 18, 2013; which are incorporated by reference.

BACKGROUND

The present disclosure generally relates to mattress assemblies and, more particularly, to mattress assemblies including a matrix of independently movable foam padded plungers.

Standard mattress designs have evolved very little in the past fifty years. A standard mattress generally includes a set of metal coil springs mounted either on a base under a pad, or sandwiched between a pair of pads. The metal springs and pad or pads are then covered with a batting material. The entire structure is then sewn into a cloth cover and the edges are wrapped and sewn. Thus, once the mattress is fabricated, the components are not replaceable. Due to the size and inherent firmness of the metal springs, spring-based mattresses exhibit a limited ability to conform to a person's body contour, which is improved only with great difficulty. While the independent coil springs are designed to compress under a person's body weight to match the surface of the mattress to the contour of the person's body to some extent, many users still experience pressure points in certain body locations, particularly when not lying flat on their backs, leading to unnatural body positions and restless sleep.

The limitations of metal spring mattresses combined with improved quality and durability of foam products has led to the relatively recent development of the foam core mattress as a viable alternative to the coil spring mattress. A foam core mattress can provide significant improvements in body contour, elimination of pressure points, and improved comfort and support compared to conventional spring-based mattresses. A basic foam mattress typically includes one or more layers of foam having desirable properties assembled into a fabric cover which often appears identical to a standard metal spring mattress. A foam mattress may include a center core of relatively high resilience foam sandwiched between two layers of lower resilience foam encased in a fabric shell. This construction allows for a reversible mattress.

While foam mattresses overcome some of the disadvantages of coil spring mattresses, they exhibit other disadvantages including excessive firmness, difficulty adjusting the firmness, and a lack of air flow through the foam core trapping body heat within the mattress. There is, therefore, a continuing need for improved mattress designs overcoming the disadvantages of coil spring and foam mattresses.

SUMMARY

Embodiments of the present invention meet the needs described above in a plunger matrix mattress that includes a number of independently movable foam padded plungers that form an array of independently movable points of support. The plunger matrix mattress significantly improves body contouring over conventional coil spring mattress designs.

2

The plunger matrix mattress also allows substantial airflow through the mattress improving over conventional foam mattress designs. Different plungers may have different spring and dampening characteristics to allow different plungers and plunger zones of the mattress to exhibit different firmness levels. In certain embodiments, individual plungers may be removed and replaced independently, for example to replace the plunger with another plunger with a different spring or dampening element, and make other types of adjustments and repairs. A variety of optional design features and configurations provide for a wide range of alternative configurations with differing levels of sophistication and functionality that can be deployed in a variety of combinations to produce a range of models designed to meet differing customer preferences and price points.

In a particular embodiment, the mattress assembly includes a frame and a plunger matrix supported by the frame including a number of plungers suspended by a plunger support platform in which each plunger provides an independent point of support. A top pad is located above the plunger matrix and a cover is placed over the plunger matrix and the top pad. The plunger matrix defines a support profile for a person lying on the mattress assembly, which may be divided into a number of zones having different firmness, dampening, vertical deflection or other characteristics. For example, zones exhibiting different characteristics may be provided for head, shoulder, back, bottom, and leg sections of the mattress.

Each plunger typically includes a pin guide removably captured within an aperture through the plunger support platform. The pin may include a flange positioned above the plunger support platform, and a guide body extending from the flange through the aperture. A pin slidably received within the pin guide includes a flange located above the flange of the pin guide and a shaft extending from the flange through the guide body. The flange of the pin carries a deformable head. A tension spring has a first end fixed to the guide body and a second end located below the guide body that receives a bottom end of the pin shaft. The spring is configured to resiliently stretch with downward motion of the pin with respect to the pin guide. A dampening device captured around the shaft of the pin between the flange of the pin and the flange of the pin guide resiliently deforms with downward motion of the pin with respect to the pin guide. Certain embodiments include a clip allowing the plunger to be removed from the plunger support platform after manufacture of the plunger mattress assembly.

The disclosure may be understood more readily by reference to the following detailed description of the various features of the disclosure and the drawings included therein.

**BRIEF DESCRIPTION OF THE SEVERAL
VIEWS OF THE DRAWINGS**

The Figures provide various embodiments and components of a plunger matrix mattress providing a large number of independent suspension points.

FIG. 1 is a perspective view of a first illustrative embodiment of the plunger matrix mattress.

FIG. 2 is a side view of a person lying on a second illustrative embodiment of the plunger matrix mattress.

FIGS. 3A and 3B are conceptual illustrations of plunger matrix mattress illustrating different firmness zones.

FIG. 4 is an exploded view of the first illustrative embodiment of the plunger matrix mattress.

FIG. 5 is a perspective view of the second alternative embodiment of the plunger matrix mattress with foam side sections.

3

FIG. 6 is an exploded view of the second illustrative embodiment of the plunger matrix mattress

FIG. 7 is a perspective view of a third alternative embodiment of the plunger matrix mattress with a foam perimeter.

FIGS. 8A-8E are views of example patterns for an edge frame or edge cover of the plunger matrix mattress.

FIGS. 9A-9H are perspective views of alternative foam heads for the plungers of the mattress.

FIG. 10 is a perspective view of an alternative mattress embodiment including a combination of a plunger matrix and coil spring sections.

FIGS. 11A-11C are perspective views of alternative plunger designs for the plunger matrix mattress.

FIG. 12 is an exploded view of an illustrative plunger design for the plunger matrix mattress.

FIGS. 13A-13D are views showing alternative plunger pin guide designs for the plunger matrix mattress.

FIG. 14 is a sectional view of a first illustrative plunger in its fully raised position.

FIG. 15 is a sectional view of the first illustrative plunger in a fully lowered position.

FIG. 16 is a sectional view of a second illustrative plunger with a height adjustment collar in a fully raised position.

FIG. 17 is a sectional view of the second illustrative plunger with a height adjustment collar in a fully lowered position.

FIG. 18 is a sectional view of a third illustrative plunger with dual tension springs in a fully raised position.

FIG. 19 is a sectional view of the third illustrative plunger with dual tension springs in a partially lowered position.

FIG. 20 is a sectional view of the third illustrative plunger with dual tension springs in a fully lowered position.

FIGS. 21A-21C show alternative variegated plunger matrix designs utilizing plunger heads having different sizes and shapes.

FIG. 22 is a perspective diagram showing a modular plunger matrix mattress configured for convenient shipping as disassembled components.

FIGS. 23A-23D are perspective diagrams illustrating a customer assembly procedure for the modular plunger matrix mattress.

FIGS. 24A-24C are side views of a folding plunger matrix mattress configured for use with a mechanically adjustable bed frame.

DETAILED DESCRIPTION

Embodiments of the present invention may be realized in plunger matrix mattress assemblies providing an array of independently movable points of support that significantly improve body contouring and support over conventional coil spring mattress designs. Unlike conventional mattresses, the plunger matrix mattress provides users with improved support when the user is not lying flat on the mattress. While conventional mattresses give support when the user is lying on their back, the support becomes very uneven when the user is not lying flat, for example when lying on their side, on a pile of blankets or on a pillow. The plunger matrix system affords a much greater range of vertical deflection, which enables the mattress to properly align the user's body even when the user is lying on an obstruction or otherwise in an unnatural position. The plunger matrix mattress also allows substantial air-flow through the mattress improving over conventional foam core mattress designs.

Unlike conventional mattresses, the individual plungers may be configured with different springs, plunger heads, and dampening elements to provide plungers or plunger zones

4

with differing firmness characteristics. Individual plungers may also be removed and replaced independently to change the firmness characteristic of individual plungers and make other types of adjustments and repairs after the mattress has been manufactured. Different plungers with different springs, heads and dampening elements exhibiting different firmness and other characteristics may be arranged into a wide range of different support zones exhibiting different, customizable support profiles. For example, zones with different firmness may be provided for head, shoulder, back, bottom, and leg sections of the mattress. Each mattress may have a custom support profile specified by the customer. In mattress designed for two persons, independent side-by-side support profiles may be configured for each person sharing the mattress. Plunger matrix designs may be incorporated into flat mattresses as well as folding embodiments designed for mechanically adjusting bed frames.

In one embodiment, the mattress includes a matrix of independently movable foam padded plungers, a mattress pad on top of the plungers, a frame, and a rigid plunger support platform supported by the frame. The plungers are individually suspended from the plunger platform and spring loaded to provide an independent point of support. Each plunger includes a pin configured to move up and down within a pin guide that is received within a corresponding aperture through the plunger support platform. A tension spring captured on the pin guide urges the plunger upward while allowing the pin to move downward in response to weight applied to the top of the plunger. An edge frame may surround the plungers or the portions of the plungers extending above the plunger platform to provide additional support at the edges of the mattress. Foam blocks or sections of coil springs may also be included along one or more edges of the mattress to provide additional edge support.

In a particular embodiment, nested coil springs are combined on a plunger to provide a non-linear spring characteristic. As another option, different plunger may be configured with different height adjustment collars to adjust the maximum travel and spring characteristic of the plunger. A wide range of different plunger head shapes and sizes may be combined to create a variety of mattress configurations. For example, a variety of foam caps configurations may be utilized within the same mattress, such as hexagonal, dome shaped, tessellation geometries, and designs with various protrusions on the top surface to provide massage sensation and compelling aesthetic designs. The plunger may also include a dampening device, such as a foam collar around the shaft of the pin above plunger support platform to provide a non-linear load-deformation response and/or dampen the spring action of the plunger. The foam collars, which may be removed by way of a longitudinal slit through the collar or by removing the pin from the plunger, may be unitary or segmented with different foam sections exhibiting different levels of firmness. The foam collar segments may have varying materials, density, height, width and other characteristics. In a particular design, for example, the segmented collar may include sections exhibiting progressive firmness. As another alternative, the dampening device may be a coil spring, which may be located under a cover and combined with a foam component to reduce noise and improve the dampening effect.

Various embodiments of the mattress may include a cover or perimeter encasement having a webbed, foam encasement, polyurethane or polyethylene foam or other suitable construction. The mattress may be located within a zip-on or other type of cover to encapsulate and protect the internal mattress assembly. In this particular configuration, the plung-

5

ers are located within the envelope of the mattress. In other designs, the plungers may extend below the bottom surface of the mattress into the foundation below. A variety of selectable covers may be provided, such as waterproof covers, washable covers, covers with extra batting, decorative designs, and so forth.

A particular alternative has a modular design including a sectioned plunger matrix, folding edge frame, top pad and zip-on cover configured for shipping in several cartons. Another embodiment includes a segmented, folding plunger matrix configured to flex on top of a mechanically adjustable frame. A variety of foam block, coil spring, plunger design, edge frame, plunger head, mattress zone, replaceable parts, and other optional features provide for a wide range of alternative designs with differing levels of sophistication and functionality that can be deployed in a variety of combinations to produce a range of models designed to meet differing customer preferences and price points. For all embodiments described below, a range of details and optional features, such as foam layers, membranes, vents, component covers, vibration dampeners, shock absorbers and the like have been omitted to avoid cluttering the diagrams and may be included as standard or optional features.

Turning now to the figures, FIG. 1 is a perspective view of a simplified embodiment of the plunger matrix mattress 10 illustrating certain basic components of a typical mattress. The assembly includes a foam cover 12 on top of a matrix of plungers 14 surrounded by an edge frame 15. A representative plunger 16 is enumerated to aid in the description. The plunger and edge frame assembly is typically located within a cover or skirt 17 that provides a perimeter encasement to protect and may add structural integrity to the mattress. The cover typically includes vents or a breathable material to provide air flow through the mattress. While a webbed edge frame 15 is illustrated, the edge frame and perimeter encasement may be constructed of any suitable material having a range of desired configurations, such as polyurethane, polyethylene foam, structural plastic, or other suitable construction. The perimeter encasement may also employ conventional batting and fabric covering to give the plunger matrix a similar appearance to a conventional coil spring matrix.

FIG. 2 is a side view of a person lying on an alternative plunger matrix mattress 20 illustrating independent plunger movement to the contour of the person's body. The basic elements of the mattress 10 include the top foam layer 12 and the matrix of independently spring-loaded plungers 14 suspended by a plunger support platform 21, which is supported by a suitable frame component 22. In certain embodiments in which the plungers are located entirely within a self-contained mattress, the frame component 22 may be formed by a flange on the inside surface of an edge frame that surrounds plunger support platform. In other embodiments, the frame component 22 may be part of a bottom frame that allows the portions of the plungers located below the plunger support platform 21 to extend into the foundation provided by the bottom frame.

Referring to the illustrative plunger 16, the plunger is suspended by a pin guide (not shown in this figure) that is captured within an aperture through the plunger support platform 21. The plunger 16 includes an upper foam head 23 carried on a plunger pin 24 that is captured within the pin guide. The pin moves up and down in the pin guide against the spring action of a tension spring 26 captured on the pin guide below the plunger support platform 21. A foam or other type of dampening collar 25 positioned around the shaft of the plunger pin located above the plunger support platform 21 is compressed during downward motion of the pin to provide a

6

non-linear load-deformation response and/or dampen the spring action of the plunger. This particular embodiment also includes foam blocks 28a-28b alongside the plunger matrix at the head and foot of the mattress.

The representative plunger 16 moves independently against its respective tension spring 26 in response to weight exerted on the upper foam head 23 to provide the mattress with a large number of independent points of support for the person lying on the mattress. The plungers are designed to accept different springs, height adjustment collars, foam caps, and foam or coil spring collars allowing different plungers to exhibit different firmness, damping, depth of motion, and other characteristics. The full plunger matrix 14 may therefore include plungers with different springs, heads, and dampening elements to produce a configurable support profile 30. Plungers with different characteristics may be organized into a range of custom zones, which can be varied from mattress to mattress to accommodate different customer preferences.

Truly independent movement of the individual plungers through a much larger vertical range than conventional coil springs results in improved body contouring and comfort in comparison to conventional coil spring mattresses. The relatively thin top foam layer 12 and the open nature of the plunger matrix 14 allow substantial air flow through the mattress in comparison to conventional foam mattresses. Each plunger may be independently removed from the mattress after manufacture, and a different plunger configured with a different spring, dampening element, height adjustment element, or other design features may be inserted to provide an alternative plunger exhibiting different levels of firmness and other characteristics. The entire mattress is therefore configurable post-manufacturing through removal and replacement of various plungers and other components to vary the support profile 30. It should be noted that certain elements present in typical embodiments, such as an edge frame, a frame supporting the plunger support platform, a pin guide for each plunger, a cover or skirt over the mattress, and other details are not shown for ease of illustration.

To provide an example of configurable support profile feature, FIG. 3A is a conceptual view of support profile 32 for a twin mattress divided into five firmness zones. The firmness profile of the particular example mattress is a standard twin mattress (e.g., 74.5 inches×38 inches) that includes a 10 inch long zone A (head zone), a 12 inch zone B (shoulder zone), an 8 inch zone C (back zone), a 12 inch zone D (bottom zone), and a 32.5 inch zone C (back zone). FIG. 3B is a conceptual view of a two person mattress (e.g., king or queen size) with firmness profile 34 including two sets of zones A1-E1 and A2-E2 located side-by-side. Each set of zones may exhibit different, customized support profiles for two persons who share the mattress. While a wide range of zones with different sizes, shapes and firmness characteristics may be configured, the zoning examples shown in FIGS. 3A and 3B are considered to be suitable as standard configurable zones for many users. It should be noted that the support profile of any particular mattress may be changed over time by swapping out or rearranging plungers or other components to accommodate growth, weight or preference changes of the person using the mattress.

FIG. 4 is an exploded view of a bed assembly 40 incorporating the plunger matrix mattress 10 shown in FIG. 1. The components of the mattress assembly are shown generally to scale for a twin mattress. This figure shows the plunger matrix 14 including the representative plunger 16 received within a corresponding aperture 41 through a plunger support platform 21. The plunger matrix 14 is surrounded by the edge

frame **15** and the foam pad **12** sits on top of the plunger matrix **14**. The cover **17** in this example may be a skirt providing mattress with protection and a pleasing outer appearance. A bottom frame **42**, which may include additional cross bars and other conventional features, supports the mattress **10**. In the particular example shown in FIG. **4**, the bottom frame **42** includes a flange **44** that is sufficiently wide to underlie and support the edge frame **15** and an outer portion of the support platform **21**.

It should be appreciated that the plunger matrix may be realized in a range of different embodiments with the plunger support platform supported in different locations in different embodiments. In the configuration shown in FIG. **4**, for example, the plunger support platform **21** and edge frame **15** are both configured to sit on the flange **44** of the bottom frame **42**. In the alternative configuration shown in FIG. **6**, the plunger support platform **21** and edge frame **15** are both configured to sit on the frame board **66**, which sits on the flange of the bottom frame **64**. These configurations allow the plungers to extend into the foundation formed by the frames **42** and **62**. In another configuration shown in FIG. **22**, the plunger matrix may be supported by a flange **225** on the inside of the edge frame **224** with the plungers positioned to move entirely within the envelope of an integral mattress. For this embodiment, one or more top covers and zip-on envelopes may be included to add cushioning, hold the components of the mattress together and lend structural to the mattress as an integrated unit.

FIG. **5** is a perspective view of the alternative plunger matrix mattress **20** including foam blocks **28a** and **28b** located alongside the plunger matrix **14** at the head and foot sections of the mattress. FIG. **6** is an exploded view of a mattress assembly **60** including the mattress **20** and a frame assembly **62**. In this embodiment, the plunger matrix **20** is supported by the frame assembly **62**, which includes a bottom frame **64** and a frame board **66** supported by the bottom frame. The frame board **66** includes a window **68** sized to allow the plungers to extend through the frame board into the foundation provided by the bottom frame **64**. The mattress **20** includes a foam top **12**, foam blocks **28a** and **28b**, the plunger matrix **14** supported by the plunger support platform **21**, and the edge frame **15** located under a cover **17**. The edge frame **15** and the plunger support platform **21** both sit on the frame board **66**, which sits on the bottom frame **64**. In this particular embodiment, the edge frame is sized to cover only the upper portions of the plungers above the plunger support platform **21** with the bottom portions of the plungers extending into the foundation provided by the frame **62**. The cover **17** may be a skirt that allows the plungers to extend through the frame board. The foam blocks **28a-28b** produce head and foot sections with increased firmness in those portions of the mattress where the desired body contouring is low. The foam sections also provide mattress sections where a person may sit or stand without sinking excessively into the mattress.

Many other mattress configurations may be designed with various combinations of plunger matrix sections, foam core sections, and coil spring sections. To provide another example to illustrate the adaptability of the design, FIG. **7** shows a mattress **70** with four foam block edge sections **28A-28D**. This configuration provides increased firmness around the full perimeter of the mattress, which may be desirable for sitting on the edges of the mattress. Coil spring sections may also be utilized for the edge sections or other areas of the mattress. As another design option, coil spring may be utilized instead of foam collars on the plungers for the entire plunger matrix or in certain areas of the mattress. As another option, a section of coil springs may be placed on top

of a foam block, and so forth, to create different configurations to meet different price points and customer preferences.

FIGS. **8A-8E** are views of example edge patterns for the plunger matrix mattress. It should be appreciated that the edge of the mattress may be a structural frame (typically covered by a skirt or batting) or a zip-on envelope depending on the particular design. FIG. **8A** shows an edge frame **15** with two-tiered lattice pattern **80** having an upper section **82** and a lower section **84**. The upper and lower sections each include two rows of sinusoidal patterns in which the repeat pattern (sinusoidal wavelength) is shorter in the upper section than in the lower section. This design provides greater firmness in the upper section **82** than in the lower section **84** to provide a desirable support characteristic for a person sitting on the edge of the mattress. FIG. **8B** shows an alternative oval lattice pattern **86**, while FIG. **8C** shows a diamond pattern **87**. Other embodiments may have a cover on the edge and include batting or another soft material under the exterior cover. For this type of embodiment, FIG. **8D** shows a ventilation pattern **86**, while FIG. **8E** shows a cloth exterior. These examples are merely illustrative and many other types of edge patterns and external materials may be selected as a matter of design choice.

FIGS. **9A-9F** are perspective views of alternative foam heads for the plungers of the mattress to provide different shapes, contact profiles, massage textures, and desirable aesthetic configurations. FIG. **9A** shows a hexagonal head **91** with a smooth surface, FIG. **9B** shows a hexagonal head **92** with relief slots, FIG. **9C** shows a square or diamond shaped head **93**, FIG. **9D** shows a square or diamond shaped head **94** with an integral collar **95**, and FIG. **9E** shows a dome shaped head **96**. Other heads may be designed to provide a massage or other tactile sensation. For example, FIG. **9F** shows a hexagonal head **97** with protruding ridges, FIG. **9G** shows a hexagonal head **98** with protruding dimples, and FIG. **9H** a hexagonal head **99** with a combination of protruding ridges and dimples. Different mattress may include various combinations of head shapes, sizes, and surface textures to provide a wide range of potential support point configurations. The plunger heads may also be removed and replaced, as desired, after the mattress has been constructed. Again, these examples are merely illustrative and many other types of head patterns, textures, and materials may be selected as a matter of design choice.

FIG. **10** is a perspective view of an alternative mattress design **100** that includes a combination of a plunger matrix **101**, a coil spring head section **102**, and coil spring foot section **103**. To provide a specific example, this alternative may be configured as a mattress with **230** plungers in the matrix **101**, **42** coil springs in the head section **102**, and **84** coil springs in the foot section **103**. The mattress includes a sturdy frame **104** around the perimeter of structural foam or another suitable material. The coil springs of the head section **102** are supported by a first foam base block **105a**, and the coil springs in the foot section **103** are supported by a second foam base block **105b**. A platform support frame **106** supports a plunger support platform **107**, which suspends the plunger matrix **101** providing a sufficient space in the foundation formed by the support frame **196** to accommodate plunger movement. The entire structure sits on a bottom panel **108** and is typically covered by a skirt. It should be noted that certain details are omitted for ease of illustration, such as a side panel of the foam frame **106**, a side panel of the platform support frame **106**, the top foam pad, the skirt to expose the internal components, and other design details.

FIG. **11A** is a perspective view of an illustrative plunger **16**, which includes a hexagonal foam head **23**, an internal mov-

able pin **24**, an external foam collar **25** on the upper portion of the pin, and a tension spring **26**. This figure shows additional features including a pin guide **110** that includes a clip **112** represented by one arm of a two-arm clip enumerated in the figure for selectively securing the pin guide to the plunger support platform. The clips can be manually pinched to insert and remove the plunger from engagement with the plunger support platform. In an alternative embodiment that is not configured for removing and replacing the plunger after the mattress has been manufactured, the plunger may not include a clip and may be permanently installed in the mattress. This particular embodiment also includes a bushing **114** at the bottom of the tension spring **26** providing a dampening and noise reducing support surface for the bottom of the spring **26**. As an optional feature, a number of selectable height adjustment collars represented by the collars **116a-116c** may be threaded onto the spring **26** to constrain expansion of the portion of the spring captured by the height adjustment collar. The height adjustment collar prevents a portion of the spring from expanding to alter the firmness and the extension length of the spring. The height adjustment collars with different lengths **116a-116c** may therefore be installed on the spring to adjust the spring characteristic and depth of travel of the plunger. The height adjustment collar may include a stop that engages with the clip **112** on the pin guide **110** or another component when the collar has been threaded to the top of the spring to prevent the height adjustment collar from backing off the spring during use of the mattress.

FIG. **11B** is a perspective view of an illustrative plunger **16'** showing an alternative configuration for the external foam collar surrounding the upper portion of the pin. This particular collar includes three sections **117a**, **117b** and **117c** of differently configured foam blocks. The different blocks have different shapes, heights and widths. They may also exhibit different densities and be formed of different types of material. As an option, the sections may be configured to produce a progressive dampening effect or progressive firmness on the pin as the pin moves downward. For example, the segmented foam collar may exhibit a relatively soft firmness during initial movement pin corresponding to compression of primarily of the top layer **117a**, and then becomes increasingly firm as the second layer **117b** is primarily compressed, with the third layer **117c** providing significantly firmer resistance to prevent the plunger from bottoming out during normal use.

FIG. **11C** is a perspective view of an illustrative plunger **16"** in which foam collar surrounding the top portion of the pin has been replaced by a coil spring **118**. The coil spring **118** is typically located within a cover **119** to reduce noise and vibration. In various embodiments, a coil spring may be combined with one or more foam sections or layers to customize the spring rate response and dampening characteristics of the plungers. For example, a foam or other type of layer may be placed at the top and bottom ends of the coil spring to reduce spring noise and soften the feel.

FIG. **12** is an exploded view of the illustrative plunger **16** providing a more detailed view of the components. The components are shown generally to scale for a plunger having a height of 12 inches. The foam head **23** selectively attaches to a flange **120** on the pin **24**, for example through a pocket on the bottom of the foam head that receives the flange on the top of the pin. The pin moves up and down within the pin guide **110**. The foam collar **25**, which surrounds the top portion of the pin **24**, is captured between the flange **120** of the pin and a flange **122** on the top of the pin guide **110** causing the foam collar to be compressed as the pin moves downward within the pin guide. The spring **26** is fastened a spring mount **123** (in this embodiment a robust thread) on the pin guide to firmly

hold the spring to the pin guide as the spring expands in response to weight applied to the top of the plunger. A first window bearing **124** that snaps into the top of the pin guide **110** and a second window bearing **126** that snaps into the bottom of the pin guide center and stabilize the pin **24** as it moves within the pin guide. A cap **128** may snap onto the bottom of the pin to provide dampening and spread the force applied by the pin to the bottom of the spring. An additional dampening bushing **114** may be captured on an axial spur on the end of the spring **26**. The optional height adjust collar **116** may be threaded onto the spring **26** to constrain expansion of a portion of the spring.

FIGS. **13A-13D** illustrate various options for the pin guide. FIG. **13A** shows a pin guide **130** in which the window bearings have been replaced by extended bearings **131a-131b** that snap into the pin guide body to increase the support and stability provided to the pin. The shaft of the pin **24** has a "X" cross-section with four elongated fins in this embodiment, and the extended bearings **131a-131b** each include four channels that receive corresponding fins of the pin while allowing the pin to freely slide within the pin guide. FIG. **13B** shows another alternative pin guide **132** in which the extended bearings have been replaced by four integral channels formed on the internal surface of the pin guide.

FIG. **13C** illustrates a pin guide **135** configured to engage a pair of nested tension springs. To support the springs in a nested configuration, the pin guide includes two spring mounts **136** and **137** configured to support respective upper ends of the nested springs. In this embodiment, the spring mounts are robust threads around the guide body disposed in an axially tiered relation. As shown in FIG. **13D**, an outer tension spring **138** is fixed to the outer thread **136**, while an inner spring **139** is fixed to the inner thread **137**. Although the specific spring selected may vary, the outer spring mount **136** generally corresponds to the spring mount on a single-spring pin guide, and the outer spring **138** generally corresponds to the spring of the single-spring embodiment. In the dual-spring embodiment, the inner spring **139** is narrower and shorter than the outer spring with an upper end fixed to a second spring **137** that is just below and axially inset from the first spring mount **136** for the upper end of the outer spring **138**.

The sectional views of FIGS. **14-15** show the operation of the single-spring embodiment. FIG. **14** is a sectional view of the plunger **16** of the single-spring embodiment with the pin **24** in its upper position. The foam head **23** is positioned on top of the pin **24**, the pin is slidably received within the pin guide, and the pin guide **110** is captured within the aperture **41** through the plunger support platform **21**. The foam collar **25** is captured between the flange **120** on the top of the pin **24** and the flange **122** on the top of the pin guide **110** to provide a non-linear load-deformation response and/or dampen the spring action of the plunger. The spring **26** is fastened to the thread **123** on the pin guide **110**. There is a cap **128** on the bottom of the pin **22** and a flexible bushing **114** engaged with a spur on the bottom of the spring **26**. FIG. **15** is a sectional view of the plunger **16** in the fully lowered position. The pin **24** has moved downward with respect to the pin guide **110**, the foam collar **25** has been compressed to provide a non-linear load-deformation response and/or dampen the spring action, and the tension spring **26** has expanded.

The sectional views of FIGS. **16-17** show the operation of the single-spring embodiment with a height adjustment collar. FIG. **16** is a sectional view of the illustrative plunger **16** with a height adjustment collar **116** in a fully raised position. The height adjustment collar is threaded onto the spring **26** to constrain expansion of an upper portion **162** of the spring,

11

while allowing only a bottom portion **164** of the spring to expand with movement of the pin **24**. FIG. **17** is a sectional view of the plunger **16** in the fully lowered position. The upper portion **162** of the spring **26** is not expanded due to the height adjustment collar **116**, while the bottom portion **164** of the spring has expanded. The foam collar **25** has been compressed, but to a lesser extent than in FIG. **15** without the height adjustment collar. As noted previously, height adjustment collars with different lengths may be utilized to adjust the spring characteristic and pin travel length of the plunger.

The sectional views of FIGS. **18-20** show the operation of a dual-spring embodiment. FIG. **18** is a sectional view of an alternative plunger **180** with dual tension springs **138**, **139** in a fully raised position. The nested coil springs provide the plunger with a nonlinear spring characteristic by tensioning only the outer spring **138** during a first portion of the downward motion of the pin **24**, and then tensioning both springs **138**, **139** during subsequent downward motion of the pin. The plunger may be similar to the illustrative plunger **16** described previously except for the utilization of a dual-spring pin guide **135**, the nested tension springs **138** and **139** (see also FIGS. **13C-13D**) and an elongated slot **182** provided in a fin of the movable pin **24**, which typically has a shaft with an X shaped cross-section with four elongated fins. The slot **182** extends along a bottom portion of the shaft of the pin, for example about a third of the way up the shaft. The outer tension spring **138** is fixed to an outer thread **136** and the inner tension spring **139** is fixed to an inner thread **137** on the dual-spring pin guide **135**. A spur **184** on the end of the inner spring **139** is slidably captured within the slot **182**, which allows the spur to slide freely within the slot during a first portion of the downward travel of the pin. The slot **182** therefore accommodates stretching of only the outer spring **138** (without stretching the inner spring **139**) during an initial portion of the downward travel of the pin **24** until the point where the top of the slot **182** reaches the spur **184** of the inner spring as shown in FIG. **19**.

As a result, the bottom of the pin **24** stretches the outer spring **138** throughout the entire downward travel of the pin, while the spur **184** at the bottom of the inner spring **139** slides freely within the slot **182** during an initial portion of the downward motion of the pin. The outer spring **138** is therefore tensioned by the full range of travel of the pin **24**, while the inner spring **139** is only tensioned during a portion of the downward motion of the pin. That is, the inner spring **139** is not tensioned during the initial downward travel of the pin **24** while the spur **184** at the bottom of the inner spring **139** slides freely within the slot **182**. FIG. **19** shows the point at which the pin **24** has moved downward a sufficient amount to cause the spur **184** to become the engage with the top of the slot **182**, causing the inner spring to be tensioned by further downward motion of the pin. FIG. **20** shows the point at which the pin **24** has moved down to its fully lowered position with both springs **138**, **139** tensioned. As a result, only the outer spring **138** is tensioned during the first portion of downward movement of the pin **24**, while both the outer and the inner spring **138**, **139** are tensioned during a second portion of downward movement of the pin.

FIGS. **21A-21C** show alternative variegated plunger matrix designs utilizing plunger heads having different sizes and shapes. FIG. **21A** illustrates a variegated plunger matrix design **210** with square or diamond shaped plunger heads of differing sizes. FIG. **21B** illustrates a variegated plunger matrix design **212** with plunger heads that differ in both size and shape. FIG. **21C** illustrates a variegated plunger matrix design **214** with tessellate plunger heads that differ in both size and shape. Each design is typically configured with zones

12

of plungers having different springs and damping characteristic to provide a customized support profile. In these examples, the different areas having similar plunger heads may represent zones with different springs and damping characteristics and the different head shapes may be designed to aid in producing a desired support profile. It will be appreciated that these examples are merely illustrative and that that may variegated plunger matrix designs using a wide range of plunger shapes and sizes may be developed as a matter of design choice. The variegated plunger matrix sections may also be combined with coil spring and foam block sections to further vary the design options.

FIG. **22** is a perspective diagram showing a modular plunger matrix mattress **220** configured for convenient shipping as disassembled components. The plunger matrix is configured as three sections **222a**, **222b** and **222c** designed to be placed side-by-side to create a standard size mattress. Each plunger matrix section includes a respective plunger support platform **223a**, **223b** and **223c**, which may be configured with interlocking structures or fasteners to secure the sections together. The plunger matrix sections are sized to fit snugly within an edge frame **224** that includes a flange **225** to support the plunger support platforms in a central location of the edge frame. A top pad **226** is configured for placement over the top of the edge frame housing the plunger matrix sections. Foam layer **228** is designed to go over the plunger matrix, edge frame and top cover to protect and add structural stability to the self-contained mattress. A variety of selectable zip-on covers may be provided to go on top of the foam layer **228**, for example to provide a water proof cover, a washable cover, additional batting, or a desired outer appearance of the mattress. Each plunger matrix section **222a**, **222b** and **222c** may typically be shipped in a respective box, while the edge frame **224**, foam pad **226**, foam layer **228** and any additional covers ordered by the customer may typically be shipped in a separate box, to create a multi-box (in this example four boxes) modular mattress that can be conveniently shipped by postal or parcel delivery service.

FIGS. **23A-23D** are perspective diagrams illustrating a customer assembly procedure for the modular plunger matrix mattress **220**. The customer unfolds the edge frame **224** and inserts the plunger matrix **222a**, **222b** and **222c** in place with the plunger support platforms located on the flange **225** of the edge frame as shown in the series of diagrams **23A-C**. The customer then places the foam pad **226** on top of the plunger matrix and zips one or more envelopes represented by the layer **228**, typically including at least a foam layer and an outer cover, over the assembly as shown in FIG. **23D**. The foam pad **226** in this example includes a number of lattice covered ventilation windows represented by the enumerated window **230**. The outer cover is typically constructed from a sturdy, breathable, machine washable fabric. The cover may also include similar or other suitable types of ventilation structures.

Each plunger matrix section is configured for shipping within a respective box, while the edge frame is configured to be folded for shipping within a separate box. The top pad and cover are also configured to be folded or rolled and placed within the same box as the edge frame to create a multi-box shipping configuration for the modular mattress assembly.

FIGS. **24A-24C** are side views of a folding plunger matrix mattress **240** configured for use with a mechanically adjusting bed frame. FIG. **24A** is a side view of the assembled mattress, which may be configured as a modular unit similar to the mattress **220** described with reference to FIG. **22**. The basic elements of the mattress are a cover **241**, a top pad **242** and a mattress assembly including an edge frame (not shown)

13

and a plunger matrix **243**. FIG. **24B** is a side view of the plunger matrix **243**, which is configured as four sections **244a-244d** connected by flexible connectors **246a-246c**. FIG. **24C** illustrates the flexible connectors allowing the plunger matrix to flex to accommodate a mechanically adjusting bed frame. The connectors may be configured to slide onto the plunger matrix platform sections and may be secured in place by the edge frame as well as other suitable fasteners or cooperating structures.

For all of the embodiments described above, a range of specific materials may be utilized for the various components, which may generally be varied in size, shape and other characteristic within ranges of suitable parameters as matters of design choice. The following material specifications are provided for certain representative embodiments to aid in enablement and, while they are intended to be suitable for representative embodiments, the invention is not limited to these particular materials or embodiments.

Referring to FIGS. **4** and **6**, in a particular embodiment exhibiting desirable weight, cost, strength, and ease of assembly characteristics, the top pad **12** may be constructed from standard polyurethane foam (PUF), viscoelastic PUF, latex foam, PUF with gel components, PUF with a phase changing material (PCM), polyethylene foam (PEF), reticulated foam or other suitable materials. The edge frame **15** may be constructed from PUF, PEF, thermoplastic polymers or other suitable materials. The cover **17** may be constructed from fabric, such as a woven or knitted fabric including fibers made of polypropylene, polyester, Rayon®, Modal®, Tencel®, cotton, wool or other suitable materials. The foam blocks **28a** and **28b** may be constructed from standard PUF, viscoelastic PUF, latex foam, PUF with gel components, PUF with a PCM, PEF, reticulated foam or other suitable materials. The plunger support platform **21** and the support board **66** may be constructed from plastic, wood, a Sintra®-polystyrene foam-Sintra® sandwich, bio-composite or another suitable material. The bottom frames **42** and **62** may be constructed from wood, metal, plastic or another suitable material.

Referring to the combined plunger matrix and coil spring embodiment shown in FIG. **10**, the coil springs in the head and foot sections **102** and **103** may be coil springs typically utilized in mattresses. The foam frame **104** may be Acetal®, Delrin® or another suitable material. The foam base blocks **105a** and **105b** may be standard PUF, viscoelastic PUF, latex foam, PUF with gel components, PUF with a PCM, PEF, reticulated foam, combinations of these components, or other suitable materials. The platform support frame **106** may be plastic, wood, a Sintra®-polystyrene foam-Sintra® sandwich, bio-composite or another suitable material. The bottom panel **108** may be a flame retardant nonwoven material, or other suitable materials. This embodiment may include a top pad typically constructed from PUF, viscoelastic PUF, latex foam, PUF with gel components, PUF with a phase changing material (PCM), PEF, reticulated foam and/or other suitable materials and a skirt, such as a fire retardant (FR) knitted barrier or FR highloft nonwoven material, other types of woven or non-woven fabrics, or other suitable materials.

Referring to the illustrative plunger **16** shown in FIG. **12**, the foam head **23** may be a molded component constructed from PUF, PEF or other suitable materials. The pin **24** typically includes a shaft with an X cross-section with four elongated fins [approximately $\frac{1}{8}$ inch thick] and may include reinforcing flanges along the fins to add rigidity. The pin **24** may be constructed from ABS. The pin guide **110** and bearings **124**, **126** may be molded components constructed from Acetal®, Delrin® or another suitable material. The foam collar **25** may be a molded component constructed from PUF,

14

PEF or other suitable materials. The end cap **128** may be a molded component constructed from PUF, PEF or other suitable materials. The bushing **114** may be a molded component constructed from Santoprene® or other suitable materials. The height adjustment collar may also be a molded component constructed from polypropylene, high density polyethylene or other suitable materials.

A variety of collars and springs may be employed to provide different spring and dampening characteristics. To specify one example spring, which is necessarily varied within a range from the base specification to implement customized support profiles, an plunger spring may have a diameter of 1.28 inches and a wire thickness of 0.056 inches. For a dual-spring plunger, and additional inner spring may have a diameter of 1.02 inches and a wire thickness of 0.061 inches.

In a particular embodiment of the modular mattress **220** shown in FIG. **22** exhibiting desirable weight, cost, strength, and ease of assembly characteristics, the plunger support platforms **223a-223c** may be constructed from plastic, wood, a Sintra®-polystyrene foam-Sintra® sandwich, bio-composite or another suitable material. The edge frame **224** may be constructed from PUF, PEF, thermoplastic polymers or other suitable materials with side wall dimensions of 1 to 4 inches. The top pad **226** may be constructed from standard PUF, viscoelastic PUF, latex foam, PUF with gel components, PUF with a PCM, PEF, reticulated foam or other suitable materials and may include other foam, batting and ventilation elements as matters of design choice. The outer cover **228** may be constructed from fabric, such as woven or knitted fabric including fibers made of polypropylene, polyester, Rayon, Modal, Tencel, cotton, wool or other suitable materials and may include ventilation components as a matter of design choice. For the folding embodiment shown in FIGS. **24A-24C**, the edge connectors **246a-246c** may be constructed from PUF, PEF, rubber or other suitable materials.

This written description uses examples to disclose the invention, including the best mode, and also to enable any person skilled in the art to make and use the invention. The patentable scope of the invention is defined by the claims, and may include other examples that occur to those skilled in the art. Such other examples are intended to be within the scope of the claims if they have structural elements that do not differ from the literal language of the claims, or if they include equivalent structural elements with insubstantial differences from the literal languages of the claims.

What is claimed is:

1. A mattress assembly, comprising:
a frame;

a plunger matrix supported by the frame comprising a plurality of plungers suspended by a plunger support platform wherein each plunger provides an independent point of support and the plunger matrix defines a support profile for a person lying on the mattress assembly;

a top pad located above the plunger matrix;

a cover over the plunger matrix and the top pad;

wherein each plunger comprises:

a pin guide removably captured within an aperture through the plunger support platform comprising a flange positioned above the plunger support platform, a guide body extending from the flange through the aperture,

a pin slidably received within the pin guide comprising a flange located above the flange of the pin guide and a shaft extending from the flange through the guide body,

a deformable head carried by the flange of the pin;

15

- a tension spring having a first end fixed to the guide body and a second end located below the guide body positioned to receive a bottom end of the pin shaft, wherein the spring is configured to resiliently stretch with downward motion of the pin with respect to the pin guide, and
- a dampening device captured around the shaft of the pin between the flange of the pin and the flange of the pin guide, wherein the dampening device is configured to resiliently deform with downward motion of the pin with respect to the pin guide; and
- wherein the support profile comprises plungers organized into a plurality of zones in which the plungers of each zone are similarly configured while the plungers of different zones are configured differently to define a varying firmness characteristic of the support profile across the zones.
2. The mattress assembly of claim 1, wherein each plunger further comprises a clip configured to be manually operated to removably secure the plunger within an aperture through a plunger support platform.
3. The mattress assembly of claim 1, wherein:
- the frame comprises an edge frame extending around a perimeter of the plunger support platform defining a flange on an internal surface of the edge frame supporting the plunger support platform in a position allowing the plungers to move up and down within an internal space defined by the edge frame; and
- the cover encapsulates the edge frame, the plunger matrix, and the top pad into a self-contained mattress unit.
4. The mattress assembly of claim 1, wherein:
- the frame comprises a bottom frame comprising a flange positioned to support the plunger support platform while allowing bottom portions of the flange to extend under the flange of the frame into a foundation located below the flange; and
- the cover comprises a skirt with an open bottom allowing the bottom portions of the plungers to extend into the foundation.
5. The mattress assembly of claim 1, wherein the zones are defined at least in part by different spring types on plungers in different zones.
6. The mattress assembly of claim 1, wherein the zones are defined at least in part by different dampening devices on plungers in different zones.
7. The mattress assembly of claim 1, wherein the zones are defined at least in part by different height adjustment collars captured on the springs of the plungers in different zones.
8. The mattress assembly of claim 1, wherein the zones are defined at least in part by different plunger heads.
9. The mattress assembly of claim 1, wherein the plunger matrix comprises plungers with heads having different shapes.
10. The mattress assembly of claim 1, wherein the plunger matrix comprises plungers with heads having different sizes.
11. The mattress assembly of claim 1, wherein at least a portion of the plunger heads comprise protrusions imparting a massage or other tactile characteristic to the heads.
12. The mattress assembly of claim 11, wherein the protrusions comprise ridges, dimples, or a combination of ridges and dimples.
13. The mattress assembly of claim 1, wherein the dampening device of one or more plungers comprises a unitary foam collar.

16

14. The mattress assembly of claim 1, wherein the dampening device of one or more plungers comprises a segmented foam collar wherein each segment exhibits a different firmness characteristic.
15. The mattress assembly of claim 1, wherein the dampening device of one or more plungers comprises a foam collar exhibiting a progressive firmness characteristic.
16. The mattress assembly of claim 1, wherein the dampening device of one or more plungers comprises a coil spring.
17. The mattress assembly of claim 1, further comprising sections of foam blocks located adjacent to the plunger matrix in head and foot regions of the mattress, side regions of the mattress, or around a perimeter of the plunger matrix.
18. The mattress assembly of claim 1, further comprising sections of coil springs located adjacent to the plunger matrix.
19. The mattress assembly, comprising:
- a frame;
- a plunger matrix supported by the frame comprising a plurality of plungers suspended by a plunger support platform wherein each plunger provides an independent point of support and the plunger matrix defines a support profile for a person lying on the mattress assembly wherein each plunger comprises:
- a pin guide removably captured within an aperture through the plunger support platform comprising a flange positioned above the plunger support platform, a guide body extending from the flange through the aperture,
- a pin slidably received within the pin guide comprising a flange located above the flange of the pin guide and a shaft extending from the flange through the guide body, a deformable head carried by the flange of the pin; and
- a tension spring having a first end fixed to the guide body and a second end located below the guide body positioned to receive a bottom end of the pin shaft, wherein the spring is configured to resiliently stretch with downward motion of the pin with respect to the pin guide;
- sections of foam blocks located adjacent to the plunger matrix in head and foot regions of the mattress, side regions of the mattress, or around a perimeter of the plunger matrix;
- a top pad located above the plunger matrix and the foam blocks;
- a cover over the plunger matrix, the foam blocks, and the top pad;
- wherein the support profile comprises plungers organized into a plurality of zones in which the plungers of each zone are similarly configured while the plungers of different zones are configured differently to define a varying firmness characteristic of the support profile across the zones.
20. A mattress assembly, comprising:
- a frame;
- a plunger matrix supported by the frame comprising a plurality of plungers suspended by a plunger support platform wherein each plunger provides an independent point of support and the plunger matrix defines a support profile for a person lying on the mattress assembly, wherein each plunger comprises:
- a pin guide removably captured within an aperture through the plunger support platform comprising a flange positioned above the plunger support platform, a guide body extending from the flange through the aperture,

a pin slidably received within the pin guide comprising
a flange located above the flange of the pin guide and
a shaft extending from the flange through the guide
body,
a deformable head carried by the flange of the pin; and 5
a tension spring having a first end fixed to the guide body
and a second end located below the guide body posi-
tioned to receive a bottom end of the pin shaft,
wherein the spring is configured to resiliently stretch
with downward motion of the pin with respect to the 10
pin guide;
sections of coil springs located adjacent to the plunger
matrix in head and foot regions of the mattress;
a top pad located above the plunger matrix and the coil
springs; 15
wherein the support profile comprises plungers organized
into a plurality of zones in which the plungers of each
zone are similarly configured while the plungers of dif-
ferent zones are configured differently to define a vary-
ing firmness characteristic of the support profile across 20
the zones.

* * * * *