

US009317154B2

(12) **United States Patent**  
**Perlin et al.**

(10) **Patent No.:** **US 9,317,154 B2**  
(45) **Date of Patent:** **\*Apr. 19, 2016**

(54) **METHOD AND APPARATUS FOR SENSING UTILIZING TILES**

(75) Inventors: **Kenneth Perlin**, New York, NY (US); **Charles Hendee**, Brooklyn, NY (US); **Alex Grau**, Astoria, NY (US); **Gerald Seidman**, New York, NY (US)

(73) Assignees: **New York University**, New York, NY (US); **Tactonic Technologies, LLC**, New York, NY (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 841 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **13/317,131**

(22) Filed: **Oct. 11, 2011**

(65) **Prior Publication Data**

US 2012/0086659 A1 Apr. 12, 2012

**Related U.S. Application Data**

(60) Provisional application No. 61/404,897, filed on Oct. 12, 2010, provisional application No. 61/462,789, filed on Feb. 8, 2011, provisional application No. 61/572,642, filed on Jul. 19, 2011, provisional application No. 61/572,938, filed on Jul. 25, 2011.

(51) **Int. Cl.**

**G06F 3/041** (2006.01)  
**G06F 3/00** (2006.01)  
**G06F 3/044** (2006.01)  
**G06F 3/045** (2006.01)

(52) **U.S. Cl.**

CPC ..... **G06F 3/0414** (2013.01); **G06F 3/005** (2013.01); **G06F 3/044** (2013.01); **G06F 3/045** (2013.01); **G06F 2203/04103** (2013.01); **G06F 2203/04112** (2013.01); **G06F 2203/04113** (2013.01)

(58) **Field of Classification Search**

CPC ..... G06F 3/041; G06F 1/13336  
USPC ..... 345/156–184  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

5,986,221 A \* 11/1999 Stanley ..... 177/136  
2008/0147350 A1 \* 6/2008 Jean ..... 702/150  
2009/0237325 A1 \* 9/2009 Luo et al. .... 345/2.1  
2009/0251430 A1 \* 10/2009 Hung et al. .... 345/173  
2009/0256817 A1 \* 10/2009 Perlin et al. .... 345/174

\* cited by examiner


*Primary Examiner* — Carolyn R Edwards

(74) *Attorney, Agent, or Firm* — Ansel M. Schwartz

(57) **ABSTRACT**

An apparatus for sensing includes a computer. The apparatus includes one or more individual sensing tiles in communication with the computer that form a sensor surface that detects force applied to the surface and provides a signal corresponding to the force to the computer which produces from the signal a time varying continuous image of force applied to the surface, where the surface is contiguous, and detected force can be sensed in a manner that is geometrically continuous and seamless on a surface. A method for determining locations of tiles of a sensor.

**8 Claims, 64 Drawing Sheets**






FIG. 1






FIG. 2




FIG. 3






FIG. 4




FIG. 5






FIG. 6






FIG. 9A






FIG. 9B




FIG. 10




FIG. 11




FIG. 12




FIG. 13






FIG. 14






FIG. 15






FIG. 18




FIG. 19






FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27






FIG. 28




FIG. 29




FIG. 30



FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 35




FIG. 36






FIG. 37




FIG. 38




FIG. 39







FIG. 40






FIG. 43




FIG. 44






FIG. 45




FIG. 46




FIG. 47




FIG. 48




FIG. 49




FIG. 50






FIG. 51




FIG. 52




FIG. 53




FIG. 54




FIG. 55




FIG. 56




FIG. 57




FIG. 58 A




FIG. 58 B




FIG. 59






FIG. 60




FIG. 61A




FIG. 61B




FIG. 62A

FIG. 62B




FIG. 63




FIG. 64




FIG. 65




FIG. 66A




FIG. 66B




FIG. 66C






FIG. 67








FIG. 70




FIG. 71




FIG. 72




FIG. 73




FIG. 74




FIG. 75




FIG. 76




FIG. 77 A




FIG. 77 B




FIG. 77 C




FIG. 78




FIG. 79






FIG. 80




FIG. 81







FIG. 82






FIG. 86




FIG. 87




FIG. 88




FIG. 89 A




FIG. 89 B




FIG. 90 A








FIG. 90 B








FIG. 94




FIG. 95




FIG. 96A








FIG. 96B






FIG. 99




FIG. 100




FIG. 101






FIG. 102








FIG. 105




FIG. 106




FIG. 107




FIG. 108




FIG. 109




FIG. 110




FIG. 111




FIG. 112




FIG. 113






FIG. 114








FIG. 117




FIG. 118




FIG. 119




FIG. 120




FIG. 121




FIG. 122




FIG. 123




FIG. 124




FIG. 125




FIG. 126




FIG. 127




FIG. 128




FIG. 129






FIG. 130A




FIG. 130B




FIG. 130C




FIG. 130D




FIG. 131




FIG. 132




FIG. 133




FIG. 134




FIG. 135



## METHOD AND APPARATUS FOR SENSING UTILIZING TILES

### CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims priority from U.S. provisional patent application 61/404,897 filed Oct. 12, 2010; and from U.S. provisional patent application 61/462,789 filed Feb. 8, 2011; and from U.S. provisional patent application 61/572,642 filed Jul. 19, 2011; and from U.S. provisional patent application 61/572,938 filed Jul. 25, 2011, all of which are incorporated by reference herein.

### FIELD OF THE INVENTION

The present invention is related to a sensor which reconstructs a continuous position of force on a surface from interpolation based on data signals received from a grid of wires. (As used herein, references to the “present invention” or “invention” relate to exemplary embodiments and not necessarily to every embodiment encompassed by the appended claims.) More specifically, the present invention is related to a sensor which reconstructs a continuous position of force on a surface from interpolation based on data signals received from a grid of wires where the sensor includes a plurality of plates and a set of protrusions.

The present invention relates to receiving at a computer 2d and 3d output from a 2d sensor and a 3d sensor and producing with the computer a combined output that is a function of the 2d and 3d output. More specifically, the present invention relates to receiving at a computer 2d and 3d output from a 2d sensor and a 3d sensor and producing with the computer a combined output that is a function of the 2d and 3d output, where the 2d sensor senses imposed force on its surface and the 3d sensor is a camera.

### BACKGROUND OF THE INVENTION

This section is intended to introduce the reader to various aspects of the art that may be related to various aspects of the present invention. The following discussion is intended to provide information to facilitate a better understanding of the present invention. Accordingly, it should be understood that statements in the following discussion are to be read in this light, and not as admissions of prior art.

In prior art, Rosenberg et al teach how to capture a time-varying two dimensional array of pressure upon a surface in a way that properly interpolates sensed pressure at points between individual sensing elements. This is an improvement over previous methods, such as that of TekScan, which do not interpolate between sensing elements, and therefore must use a very finely spaced two dimensional sensing element array to approximate capture of the continuous pressure image.

Moreover, Gesture sensing based only on range imaging cameras can be very powerful, since it can track entire hand or foot movements, maintain consistent identity over time of each hand of each user, and in some cases provide unambiguous finger and toe identity (depending on distance of camera to surface and hand or foot position). This stands in marked contrast to purely surface-based Touch Devices, such as those based on variable resistance or capacitance, which provide little or no information about finger and hand position or toe and foot position in the space above the surface. Yet range imaging camera suffers from several deficiencies:

(1) Frame rate (30 fps for the Kinect) is too slow to properly sample the movement of a finger pressing down and releasing

a key. By way of comparison, the standard sampling rate for USB keyboards is 125 Hz (more than four times video rate). This higher sampling rate is needed for unambiguous detection and disambiguation of multiple overlapping typed key-strokes.

(2) It is impossible to determine from a range image alone how much pressure is being applied to a surface, thereby rendering range imaging cameras inadequate for subtle movement of virtual objects on a display, rapid and accurate control of 3D computer game characters, musical instrument emulation, simulated surgery, simulated painting/sculpting, gait monitoring, dance, monitoring stance for purposes of physical therapy, and other applications that benefit from a significant measure of isometric control.

It is therefore also impossible to determine from a 3D image gestures based on movements and variations in pressure on the underside of fingers or hands or feet or toes. For example, if a user shifts weight between different fingers, or between fingers and different parts of the palm, or between the foot heel, metatarsal or toes, these changes will be undetectable to a range imaging camera.

The decade of 2001-2011 has seen the gradual development of LCD displays that contain an optically sensitive element in each pixel (variously developed by Sharp, Toshiba and Matsushita). This approach enables the sensing of both touch and hovering. However, the optically sensitive pixel approach suffers from a number of deficiencies as compared to the present touch-range fusion apparatus approach: (1) The cost per unit area is intrinsically far higher than the cost per unit area of the approach here; (2) Such sensors cannot be seamlessly tiled to arbitrarily large form factors; (3) variations in the pressure of a detected touch **111** can be determined only with very low fidelity (via changes in fingertip contact shape); (4) hand shape can only be detected within a relatively small distance above the display. This makes it impossible to maintain a persistent model of hand and finger identity or to recognize many hand gestures. In addition, it is not practical to use such technologies for foot sensing, since the added cost to manufacture such sensors so that they possess sufficient physical robustness to withstand the weight of a human body would add prohibitively to their cost.

### BRIEF SUMMARY OF THE INVENTION

One key innovation of the current invention is that, unlike Rosenberg et al., this method is able to capture a time-varying two dimensional array of pressure upon a surface of arbitrarily large size. Therefore, unlike the method of Rosenberg et al., the current invention can be used for seamless time-varying pressure capture over entire extended surfaces, such as walls, floors, tables, desks or roadways.

The key innovative techniques of the current invention which enable this capability are (1) the organization of the sensing element array into physically distinct tiles, and (2) a method of interpolation between sensing elements that can operate across tile boundaries.

Also, because the current invention is based on a strategy of seamless tiling, it is able to make use of an optimization whereby the resolution of the sub-array formed by each physical tile is chosen so as to make optimal use of a microcontroller that controls the data capture from that tile. This permits a uniquely economical implementation to be effected, whereby control of a tile requires only a single commercially available microcontroller, without requiring the use of any additional transistors or other switchable electronic components.



In addition, a Touch-Range fusion apparatus and software abstraction layer are described that reliably combine the Pressure Imaging Apparatus or other Touch Device data with the data from one or more range imaging cameras in order to create a high quality representation of hand and finger action for one or more users, as well as foot and toe action of one or more users, as well as identify and track pens and other objects on or above a Touch Device. It is believed there is currently no technology available at the commodity level that provide high quality input, over a large-scale surface, of finger-identification, pressure, and hand gesture or foot gesture, with simultaneous support of identifiable multiple users. This invention will lead to products that will fill that gap.

The present invention pertains to an apparatus for sensing. The apparatus comprises a computer. The apparatus comprises two or more individual sensing tiles in communication with the computer that form a sensor surface that detects force applied to the surface and provides a signal corresponding to the force to the computer which produces from the signal a time varying continuous image of force applied to the surface, where the surface is contiguous, detected force can be sensed in a manner that is geometrically continuous and seamless on a surface.

The present invention pertains to a sensor. The sensor comprises a grid of wires that define intersections and areas of space between the wires. The sensor comprises a set of protrusions that are in contact with a plurality of intersections of the grid of wires, and a mechanical layer that is disposed atop the set of protrusions, so that force imparted to the top of that mechanical layer is transmitted through the protrusions, and thence to the protrusions. The sensor comprises a computer in communication with the grid which causes prompting signals to be sent to the grid and reconstructs a continuous position of force on the surface from interpolation based on data signals received from the grid.

The present invention pertains to a sensor. The sensor comprises a computer having N dual analog/digital I/O pins and M digital I/O pins for data, where M and N are positive integers greater than three. The sensor comprises a pressure sensing array having N rows and M columns, with the N I/O pins in communication with the N rows and up to M columns in communication with the M I/O pins without using any transistors or other switchable electronic components outside of the computer.

The present invention pertains to a method for determining locations of tiles of a sensor. The method comprises the steps of sending a query signal from a computer to at least a plurality of the tiles in communication with the computer asking each of the plurality of tiles to identify at least one adjacent tile with which the tile is in electrical communication. There is the step of receiving by the computer responses to the query from the plurality of tile. There is the step of forming with the computer from the responses a geometric map of the tiles' locations relative to each other.

The present invention pertains to a method for sensing. The method comprises the steps of detecting a force applied to a sensor surface formed of two or more individual sensing tiles from an object moving across the surface where the surface is contiguous, detected force can be sensed in a manner that is geometrically continuous and seamless on a surface. There is the step of providing a signal corresponding to the force to a computer from the tiles in communication with the computer. There is the step of producing with the computer from the signal a time varying continuous image of force applied to the surface.

The present invention pertains to a method for sensing. The method comprises the steps of imparting a force to a top of a

mechanical layer that is transmitted through to intersections defined by a grid of wires having areas of space between the wires. There is the step of causing prompting signals with a computer in communication with the grid to be sent to the grid. There is the step of reconstructing with the computer a continuous position of the force on the surface from interpolation based on data signals received from the grid.

The present invention pertains to a sensor. The sensor comprises a grid of wires that define intersections and areas of space between the wires. The sensor comprises a set of protrusions that engage with a plurality of intersections of the grid of wires, and an outer surface layer having an inner face that is in juxtaposition with the set of protrusions and an outer face, so that force imparted to the outer face of the outer surface layer is transmitted through the inner face of the outer surface layer to the protrusions and the plurality of intersections. The sensor comprises a computer in communication with the grid which causes prompting signals to be sent to the grid and reconstructs an antialiased image of force upon the outer face of the outer surface layer from interpolation based on data signals received from the grid.

The present invention pertains to a method for sensing. The method comprises the steps of imparting a force to an outer face of an outer surface layer that is transmitted through an inner face of the outer surface layer to a set of protrusions and a plurality of intersections defined by a grid of wires having areas of space between the wires. There is the step of causing prompting signals with a computer in communication with the grid to be sent to the grid. There is the step of reconstructing with the computer an antialiased image of the force on the outer face of the outer surface from interpolation based on data signals received from the grid.

The present invention pertains to a sensor. The sensor comprises a grid of wires that define intersections and areas of space between the wires. The sensor comprises a set of protrusions that are in contact with a plurality of intersections of the grid of wires, and an outer surface layer having an inner face that is disposed in contact with the grid of wires and an outer face, so that force imparted onto the outer face of the outer surface layer is transmitted through the inner face of the outer surface layer to the protrusions, and thence to the intersections of the grid wires which are thereby compressed between the outer surface layer and protrusions; and that the protrusions thereby focus the imparted force directly onto the intersections. The sensor comprises a computer in communication with the grid which causes prompting signals to be sent to the grid and reconstructs an antialiased image of force upon the outer face of outer surface layer from interpolation based on data signals received from the grid.

The present invention pertains to a sensor. The sensor comprises a grid of wires that define intersections and areas of space between the wires. The sensor comprises a set of protrusions that are in contact with a plurality of intersections of the grid of wires, and a mechanical layer having a plurality of plates that is disposed atop the grid of wires, so that force imparted to the top of the mechanical layer is transmitted through the intersections, and thence to the. The sensor comprises a computer in communication with the grid which causes prompting signals to be sent to the grid and reconstructs a continuous position of force on the surface from interpolation based on data signals received from the grid.

The present invention pertains to a sensor. The sensor comprises a grid of wires that define intersections and areas of space between the wires. The sensor comprises a set of protrusions that are in contact with a plurality of intersections of the grid of wires. The sensor comprises a plate layer having a plurality of plates that is disposed atop the grid of wires. The



5

sensor comprises a flexible touch layer disposed on the plate layer, wherein force imparted to the touch layer is transmitted through the plate layer and at least one protrusion to the intersections. The sensor comprises a computer in communication with the grid which causes prompting signals to be sent to the grid and reconstructs a continuous position of force on the surface from interpolation based on data signals received from the grid.

The present invention pertains to a sensor. The sensor comprises a grid of wires that define intersections and areas of space between the wires. The sensor comprises a set of protrusions that are in contact with a plurality of intersections of the grid of wires. The sensor comprises a plate layer having a plurality of plates that is disposed atop the grid of wires. The sensor comprises a flexible touch layer disposed on the plate layer, wherein force imparted to the touch layer is transmitted through the plate layer to the intersections layer, and thence to the protrusions. The sensor comprises a computer in communication with the grid which causes prompting signals to be sent to the grid and reconstructs a continuous position of force on the surface from interpolation based on data signals received from the grid.

The present invention pertains to a sensor. The sensor comprises a set of plates that are in contact from the bottom at their corners with a set of protrusions that are in contact from above with a plurality of intersections, each having a sensing element, of the grid of wires, and a thin top surface layer that is disposed atop the grid of plates, so that force imparted from above onto the top surface layer is transmitted to the plates and thence to the protrusions, and thence to the intersections of the grid wires which are thereby compressed between the base and protrusions; and that the protrusions above thereby focus the imparted force directly onto the sensor intersections. The sensor comprises a computer in communication with the sensor grid which causes prompting signals to be sent to the grid and reconstructs a continuous position of force on the surface from interpolation based on data signals received from the grid.

The present invention pertains to a method for sensing. The method comprises the steps of imparting force from above onto a top surface layer that is transmitted to a set of plates and thence to a set of protrusions, and thence to a plurality intersections of a grid of wires which are thereby compressed between the base and protrusions, where the set of plates are in contact from their bottom at their corners with the set of protrusions that are in contact from above with the plurality of intersections of the grid of wires disposed on the base; and that the protrusions above thereby focus the imparted force directly onto the intersections. There is the step of causing prompting signals by a computer in communication with the grid to be sent to the grid. There is the step of reconstructing with the computer a continuous position of force on the surface from interpolation based on data signals received from the grid.

The present invention pertains to a sensor. The sensor comprises a set of protrusions that are in contact from the bottom with a plurality of intersections of the grid of wires, and a set of plates that are in contact from the top with a plurality of intersections of the grid of wires, and a thin top surface layer that is disposed atop the set of plates, so that force imparted from above onto the top surface layer is transmitted to the plates, and thence to the intersections of the grid wires, and thence the protrusions, which are thereby compressed between the plates and protrusions; and that the protrusions underneath thereby focus the imparted force directly onto the sensor intersections. The sensor comprises a computer in communication with the sensor grid which causes prompting

6

signals to be sent to the grid and reconstructs a continuous position of force on the surface from interpolation based on data signals received from the grid.

The present invention pertains to an apparatus for inputting information into a computer. The apparatus comprises a 3d sensor that senses 3d information and produces a 3d output. The apparatus comprises a 2d sensor that senses 2d information and produces a 2d output. The apparatus comprises a processing unit which receives the 2d and 3d output and produces a combined output that is a function of the 2d and 3d output.

The present invention pertains to a method for inputting information into a computer. The method comprises the steps of producing a 3d output with a 3d sensor that senses 3d information. There is the step of producing a 2d output with a 2d sensor that senses 2d information. There is the step of receiving the 2d and 3d output at a processing unit. There is the step of producing a combined output with the processing unit that is a function of the 2d and 3d output.

#### BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING

In the accompanying drawings, the preferred embodiment of the invention and preferred methods of practicing the invention are illustrated in which:

FIG. 1 shows the active sensing array.

FIG. 2 shows the alignment of two Sensor Surfaces.

FIG. 3 shows schematic of Sensor Surface.

FIG. 4 shows the layers of a Sensor Surface.

FIG. 5 shows schematic of Conductor Trace Lines.

FIG. 6 shows schematic pattern of FSR placement.

FIG. 7 shows schematic of Conductor Trace Lines Test Pattern.

FIG. 8 shows schematic pattern of FSR placement Test Pattern.

FIG. 9A shows a sensor surface with Conductor and FSR Test Patterns.

FIG. 9B shows an active sensing array with Conductor and FSR Test Patterns.

FIG. 10 shows the exploded schematic makeup of a single Sensing element.

FIG. 11 shows the active area of a sensing element.

FIG. 12 shows, at a single sensing element, the layers of elements in an embodiment where the protrusions are integrated onto to the outer surface of the Active Sensing Array.

FIG. 13 shows force imparted upon touch layer in an embodiment where the protrusions are integrated onto to the outer surface of the Active Sensing Array.

FIG. 14 shows force imparted upon touch layer between two adjacent tiles in an embodiment where the protrusions are integrated onto to the outer surface of the Active Sensing Array.

FIG. 15 shows, at a single sense, the layers of elements in an embodiment where the protrusions are integrated onto the inner surface of the Semi-Rigid Touch Layer.

FIG. 16 shows a view from the body of an embodiment of the semi-rigid touch layer where the protrusions are integrated into the semi-rigid touch layer.

FIG. 17 shows layers of elements in an embodiment where the protrusions are integrated onto the inner surface of the Semi-Rigid Touch Layer at a single sensing element.

FIG. 18 shows a profile view of the redistributing of pressure between sensing elements that belong to different physical tiles and also showing the active sensing array wrapped under the tile.



FIG. 19 shows exploded view of tile and the appropriate alignment of protrusions and sensing elements for an integrated protrusion and base layer.

FIG. 20 shows layer of elements in an embodiment with an integrated protrusion and base layer.

FIG. 21 shows an embodiment where the proposed semi-rigid touch layer is unacceptably too rigid.

FIG. 22 shows an embodiment where the semi-rigid touch layer is acceptably semi-rigid.

FIG. 23 shows an embodiment where the proposed semi-rigid touch layer is unacceptably not rigid enough.

FIG. 24 shows distribution of force imparted upon a semi-rigid touch layer in an integrated protrusion and base layer embodiment.

FIG. 25 shows a region where force would be distributed to four protrusions on the same pressure tile.

FIG. 26 shows a region where force would be distributed to two protrusions on each of two adjacent pressure tiles.

FIG. 27 shows a region where force would be distributed to one protrusion on each of four adjacent pressure tiles.

FIG. 28 shows tall/narrow protrusions.

FIG. 29 shows hemispherical protrusions.

FIG. 30 shows rounded protrusions wider at the base than the height.

FIG. 31 shows rounded protrusions with base very large relative to its height.

FIG. 32 is a side view showing the active sensing array folded under the Integrated Protrusion and Base Layer embodiment.

FIG. 33 shows the side view showing the active sensing array folded under the Integrated Protrusion and Base Layer embodiment.

FIG. 34 shows the bottom view showing the active sensing array folded under the Integrated Protrusion and Base Layer, having a cavity for the PCB embodiment.

FIG. 35 shows the use of the single tile sensing apparatus.

FIG. 36 shows the use of the grid of tiles sensing apparatus.

FIG. 37 shows the schematic of a data bus of a grid of tiles using I2C.

FIG. 38 shows grid of tiles and their electronic connectors.

FIG. 39 shows a multiplicity of zones of grids of tiles.

FIG. 40 shows schematic of tiles with N/S/E/W detection lines.

FIG. 41 shows exploded inter tile alignment connectors.

FIG. 42A shows side view of alignment of inter-tile alignment connectors.

FIG. 42B shows side view of inter-tile alignment connectors in position.

FIG. 43 shows a disconnected grid of tiles.

FIG. 44 shows cables/wires to/from Microprocessor.

FIG. 45 shows adjacent tiles preserving inter-sensing element distance.

FIG. 46 shows a block diagram of the electronics for a tile functioning as both the Host communication Tile and as a Master Tile.

FIG. 47 shows a block diagram for a slave tile.

FIG. 48 shows labeled positions for use in compensation function.

FIG. 49 shows a graph of a compensation function.

FIG. 50 shows multiple tiles with common touch layer.

FIG. 51 showing applied force applied to sensing elements on different tiles in the integrated protrusion and base layer embodiment.

FIG. 52 shows an exploded view of a Tile for the Integrated Plate and Protrusion Matrix Component embodiment.

FIG. 53 shows a profile view of a Tile for the Integrated Plate and Protrusion Matrix Component embodiment.

FIG. 54 shows an exploded view of a Tile for the Distinct Plate and Protrusion Matrix Components embodiment.

FIG. 55 shows a profile view of a Tile for the Distinct Plate and Protrusion Matrix Components embodiment.

FIG. 56 shows an embodiment where the protrusions are affixed to the Active Sensing Array.

FIG. 57 shows an exploded view of embodiment where protrusions are affixed to the Active Sensing Array.

FIG. 58A shows top view of dimensions used in the prototype embodiment of the Distinct Plate Matrix and Protrusion Matrix Layers Technique.

FIG. 58B shows side view of dimensions used in the prototype embodiment of the Distinct Plate Matrix and Protrusion Matrix Layers Technique.

FIG. 59 shows Plate alignment over Active Sensing array.

FIG. 60 shows top view of Rigid Plate properly aligned and inside of corresponding sensing elements on the Active Sensing array.

FIG. 61A shows top view of Plate Matrix.

FIG. 61B shows side view of Plate Matrix.

FIG. 62A shows top view of Protrusion Matrix.

FIG. 62B shows side view of Protrusion Matrix.

FIG. 63 shows Plate Matrix aligned with an Active Sensing Array.

FIG. 64 shows the top view of a protrusion properly aligned upon the corresponding sensing element on the Active Sensing array.

FIGS. 65A-65F shows various valid and invalid configurations of protrusions.

FIGS. 66A-66C shows A Bottom, B Side, and C Top Views of the superposition of a properly aligned Plate Matrix and Protrusion Matrix.

FIG. 67 shows a cut out view of the superposition of a properly aligned Plate Matrix and Protrusion Matrix.

FIG. 68A shows a horizontal sensor, as on a table.

FIG. 68B shows a vertical sensor, as on a wall.

FIG. 69 shows an embodiment of an Integrated Plate and Protrusion Layer.

FIG. 70 shows a side view of an Integrated Plate and Protrusion Layer with slits and rectangular protrusions.

FIG. 71 shows a side view of an Integrated Plate and Protrusion Layer with slits and rectangular protrusions such that the protrusions continue through the junction to be flush with the plate.

FIG. 72 shows a side view of an Integrated Plate and Protrusion Layer with slits and trapezoidal protrusions.

FIG. 73 shows a side view of an Integrated Plate and Protrusion Layer with wider slits and rectangular protrusions.

FIG. 74 shows a top view of an Integrated Plate and Protrusion Layer with slits that, at the junctions, are not flush with the outer surface of the plates.

FIG. 75 shows a top view of an Integrated Plate and Protrusion Layer with slits and rectangular protrusions such that the protrusions continue through the junction to be flush with the plate.

FIG. 76 shows a top view of an Integrated Plate and Protrusion Layer with wider slits that, at the junctions, are not flush with the outer surface of the plates.

FIGS. 77A-77C shows examples of sets of corner protrusions constituting a protrusion over a sensing element.

FIG. 78 shows a side view of Flat Top Integrated Plate and Protrusion Layer embodiment.

FIG. 79 shows the outer face of a Flat-Top Integrated Plate and Protrusion Layer embodiment.

FIG. 80 shows the inner face of a Flat-Top Integrated Plate and Protrusion Layer embodiment.

FIG. 81 shows a Flat Top Plate Matrix Layer.



FIG. 82 shows an Integrated Protrusion and Base Support Layer.

FIG. 83 shows an acceptably rigid plate.

FIG. 84 shows an acceptably semi-rigid plate.

FIG. 85 shows an unacceptably non-rigid plate.

FIG. 86 shows a cross Section of Force Distribution at a plate.

FIG. 87 shows a schematic view of an isolated plate and its mechanically interpolated force distribution exclusively to adjacent sensing elements.

FIG. 88 shows the plate and protrusion dimensions used in the prototype embodiment of the Integrated Plate and Protrusion Layer.

FIG. 89A shows photo-resistive ink pattern for plates.

FIG. 89B shows photo-resistive ink pattern for protrusions.

FIG. 90A shows cross section view the compression plates manufacturing embodiment.

FIG. 90B shows top view the compression plates manufacturing embodiment.

FIG. 91A shows an embodiment of a plate and protrusion layer with plates having discontinuous corner protrusions and abutting corners.

FIG. 91B shows an embodiment of a single part flat top plate and protrusion layer with plates having discontinuous corner protrusions and abutting corners.

FIG. 92 shows an embodiment with the circuit board coplanar with the Active Sensing Array.

FIG. 93 shows an exploded view of an interior grid tile with bridging plates.

FIG. 94 shows a top view of an interior grid tile with bridging plates.

FIG. 95 shows a side view of an interior grid tile with bridging plates.

FIG. 96A shows the alignment of the bridging plates of adjacent tiles.

FIG. 96B shows the correct positioning of the bridging plates of adjacent tiles.

FIG. 97A shows side view of circuit board embedded in the base layer of a tile with Bridging plates.

FIG. 97B shows bottom perspective view of circuit board embedded in the base layer of a tile with Bridging plates.

FIG. 98A shows the schematic of adjacent tile alignment of tiles with bridging plates and assembly of circuitry under the support layer in position.

FIG. 98B shows the alignment of adjacent tiles with bridging plates and assembly of circuitry under the support layer.

FIG. 99 shows schematic of a grid of tiles with bridging plates being properly aligned.

FIG. 100 shows of a grid of tiles with bridging plates in position.

FIG. 101 shows of a grid of tiles with bridging plates in position with bridging tiles transparent exposing bridge plate alignment on protrusions.

FIG. 102 shows a grid of interior, north, east and northeast tiles embodiment.

FIG. 103 shows a schematic alignment of a 3x3 grid of interior, north, east and northeast tiles embodiment.

FIG. 104 shows a 3x3 grid of interior, north, east and northeast tiles embodiment in their proper positions.

FIG. 105 shows a deformable patch on a cylindrical surface.

FIG. 106 shows a deformable patch on a conic surface.

FIG. 107 shows the inside view of an assembly of a cylindrical section curved sensor.

FIG. 108 shows the outside view of an assembly of a cylindrical section curved sensor.

FIG. 109 shows a height edge view of a cylindrical section Integrated Plate and Protrusion Layer.

FIG. 110 shows an outside view of a cylindrical section Integrated Plate and Protrusion Layer.

FIG. 111 shows an inside view of a cylindrical section Integrated Plate and Protrusion Layer.

FIG. 112 shows a sensor mounted on a cylindrical surface.

FIG. 113 shows a plate matrix of hexagonal plates.

FIG. 114 shows a protrusion matrix corresponding to a hexagonal plate matrix.

FIG. 115 shows an Integrated Plate and Protrusion Layer with hexagonal plates.

FIG. 116 shows an Active Sensing Array with corresponding spacing to a hexagonal plate matrix.

FIG. 117 shows a Hexagonal Integrated Plate and Protrusion Layer positioned above the Active Sensing Array.

FIG. 118 shows a hexagonal plate with corners labeled.

FIG. 119 shows an embodiment with the protrusions affixed to the active sensing array, which is wrapped around the support layer to circuitry on the bottom of the tile.

FIG. 120 showing Connector Tails separated into banks of 16 trace lines.

FIG. 121 showing layers and applied force on the integrated protrusion and base layer embodiment.

FIG. 122 shows an embodiment with a touch device and two range imaging cameras.

FIG. 123 shows the left hand and right hand of one individual user. Beyond the individual user maximum reach, another individual user is identified.

FIG. 124 shows a range imaging camera.

FIG. 125 shows a touch imaging device.

FIG. 126 shows a pressure imaging apparatus.

FIG. 127 shows a table top embodiment.

FIG. 128 shows a floor embodiment.

FIG. 129 shows an embodiment of the Touch-Range Fusion Apparatus with a computer.

FIG. 130 shows the outline of a hand using edge detection, a skeleton matched to edge hand, and finger touches identified.

FIG. 131 shows that cubes can be placed at the four corners.

FIG. 132 shows an embodiment of the Touch-Range Fusion Apparatus.

FIG. 133 shows an embodiment with a touch device, range imaging camera, and supporting stand for the range imaging camera.

FIG. 134 shows a Touch Device 101 with a set of Contact Points Pk.

FIG. 135 is a block diagram of Data from Range Imaging Camera and Touch Device being processed by the computer and stored in computer memory.

#### DETAILED DESCRIPTION OF THE INVENTION

Referring now to the drawings wherein like reference numerals refer to similar or identical parts throughout the several views, and more specifically to FIGS. 35 and 36 thereof, there is shown an apparatus 1 for sensing. The apparatus 1 comprises a computer 3. The apparatus comprises two or more individual sensing tiles 2 in communication with the computer 3 that form a sensor surface that detects force applied to the surface and provides a signal corresponding to the force to the computer 3 which produces from the signal a time varying continuous image of force applied to the surface, where the surface is contiguous, detected force can be sensed in a manner that is geometrically continuous and seamless on a surface.



## 11

The present invention pertains to a sensor **200**, as shown in FIGS. **50-52**. The sensor **200** comprises a grid **126** of wires **23** that define intersections and areas of space between the wires **23**. The sensor comprises a set of protrusions **30** that are in contact with a plurality of intersections of the grid **126** of wires **23**, and a mechanical layer that is disposed atop the set of protrusions **30**, so that force imparted to the top of that mechanical layer is transmitted through the protrusions **30**, and thence to the. The sensor comprises a computer **3** in communication with the grid **126** which causes prompting signals to be sent to the grid **126** and reconstructs a continuous position of force on the surface from interpolation based on data signals received from the grid **126**.

The sensor **200** may include a force resistive material in proximity to a plurality of the intersections of the grid **126** of wires **23**. The force resistive material may be disposed only in proximity to a plurality of the intersections of the grid **126** of wires **23** and in spaced relationship.

The present invention pertains to a sensor. The sensor comprises a computer **3** having  $N$  dual analog/digital I/O pins and  $M$  digital I/O pins for data, where  $M$  is less than  $N$  and  $M$  and  $N$  are positive integers greater than three. The sensor comprises a pressure sensing array having  $N$  rows and  $M$  columns, with the  $N$  I/O pins in communication with the  $N$  rows and up to  $M$  columns in communication with the  $M$  I/O pins without using any transistors or other switchable electronic components outside of the computer **3**.

The present invention pertains to a method for determining locations of tiles **2** of a sensor. The method comprises the steps of sending a query signal from a computer **3** to at least a plurality of the tiles **2** in communication with the computer **3** asking each of the plurality of tiles **2** to identify at least one adjacent tile **2** that the tile **2** is in electrical communication. There is the step of receiving by the computer **3** responses to the query from the plurality of tiles **2**. There is the step of forming with the computer **3** from the responses a geometric map of the tiles' locations relative to each other.

The present invention pertains to a method for sensing. The method comprises the steps of detecting a force applied to a sensor surface formed of two or more individual sensing tiles **2** from an object moving across the surface where the surface is contiguous, detected force can be sensed in a manner that is geometrically continuous and seamless on a surface. There is the step of providing a signal corresponding to the force to a computer **3** from the tiles **2** in communication with the computer **3**. There is the step of producing with the computer **3** from the signal a time varying continuous image of force applied to the surface. There may be the step of connecting an additional tile **2** to at least one of the two tiles **2** to expand the size of the sensor surface, where the surface includes the additional tile **2** and is contiguous, detected force can be sensed in a manner that is geometrically continuous and seamless on a surface.

The present invention pertains to a method for sensing. The method comprises the steps of imparting a force to a top of a mechanical layer that is transmitted through to intersections defined by a grid **126** of wires **23** having areas of space between the wires **23**. There is the step of causing prompting signals with a computer **3** in communication with the grid **126** to be sent to the grid **126**. There is the step of reconstructing with the computer **3** a continuous position of the force on the surface from interpolation based on data signals received from the grid **126**.

The present invention pertains to a sensor **200**. The sensor comprises a grid **126** of wires **23** that define intersections and areas of space between the wires **23**. The sensor comprises a set of protrusions **30** that engage with a plurality of intersec-

## 12

tions of the grid **126** of wires **23**, and an outer surface layer having an inner face that is in juxtaposition with the set of protrusions **30** and an outer face, so that force imparted to the outer face of the outer surface layer is transmitted through the inner face of the outer surface layer to the protrusions **30** and the plurality of intersections. The sensor comprises a computer **3** in communication with the grid **126** which causes prompting signals to be sent to the grid **126** and reconstructs an antialiased image of force upon the outer face of the outer surface layer from interpolation based on data signals received from the grid **126**.

The outer surface layer may be a mechanical layer, and the set of protrusions **30** are disposed between the grid **126** of wires **23** and the mechanical layer. The grid **126** of wires **23** may be disposed between the set of protrusions **30** and the outer surface layer.

The present invention pertains to a method for sensing. The method comprises the steps of imparting a force to an outer face of an outer surface layer that is transmitted through an inner face of the outer surface layer to a set of protrusions **30** and a plurality of intersections defined by a grid **126** of wires **23** having areas of space between the wires **23**. There is the step of causing prompting signals with a computer **3** in communication with the grid **126** to be sent to the grid **126**. There is the step of reconstructing with the computer **3** an antialiased image of the force on the outer face of the outer surface from interpolation based on data signals received from the grid **126**.

The present invention pertains to a sensor **200**. The sensor comprises a grid **126** of wires **23** that define intersections and areas of space between the wires **23**. The sensor comprises a set of protrusions **30** that are in contact with a plurality of intersections of the grid **126** of wires **23**, and an outer surface layer having an inner face that is disposed in contact with the grid **126** of wires **23** and an outer face, so that force imparted onto the outer face of the outer surface layer is transmitted through the inner face of the outer surface layer to the protrusions **30**, and thence to the intersections of the grid **126** wires **23** which are thereby compressed between the outer surface layer and protrusions **30**; and that the protrusions **30** thereby focus the imparted force directly onto the intersections. The sensor comprises a computer **3** in communication with the grid **126** which causes prompting signals to be sent to the grid **126** and reconstructs an antialiased image of force upon the outer face of outer surface layer from interpolation based on data signals received from the grid **126**.

The present invention pertains to a sensor **200**. The sensor comprises a grid **126** of wires **23** that define intersections and areas of space between the wires **23**. The sensor comprises a set of protrusions **30** that are in contact with a plurality of intersections of the grid **126** of wires **23**, and a mechanical layer having a plurality of plates **35** that is disposed atop the grid **126** of wires **23**, so that force imparted to the top of the mechanical layer is transmitted through the intersections, and thence to the protrusions. The sensor comprises a computer **3** in communication with the grid **126** which causes prompting signals to be sent to the grid **126** and reconstructs a continuous position of force on the surface from interpolation based on data signals received from the grid **126**.

The mechanical layer may include a flexible touch layer disposed on the plurality of plates **35**. Each plate **35** may have corners **125** that are aligned over a corresponding protrusions **30** outer face.

The present invention pertains to a sensor **200**. The sensor comprises a grid **126** of wires **23** that define intersections and areas of space between the wires **23**. The sensor comprises a set of protrusions **30** that are in contact with a plurality of



13

intersections of the grid 126 of wires 23. The sensor comprises a plate layer having a plurality of plates 35 that is disposed atop the grid 126 of wires 23. The sensor comprises a flexible touch layer disposed on the plate layer, wherein force imparted to the touch layer is transmitted through the plate layer and at least one protrusion to the intersections. The sensor comprises a computer 3 in communication with the grid 126 which causes prompting signals to be sent to the grid 126 and reconstructs a continuous position of force on the surface from interpolation based on data signals received from the grid 126.

The present invention pertains to a sensor 200. The sensor comprises a grid 126 of wires 23 that define intersections and areas of space between the wires 23. The sensor comprises a set of protrusions 30 that are in contact with a plurality of intersections of the grid 126 of wires 23. The sensor comprises a plate layer having a plurality of plates 35 that is disposed atop the grid 126 of wires 23. The sensor comprises a flexible touch layer disposed on the plate layer, wherein force imparted to the touch layer is transmitted through the plate layer to the intersections layer, and thence to the protrusions 30. The sensor comprises a computer 3 in communication with the grid 126 which causes prompting signals to be sent to the grid 126 and reconstructs a continuous position of force on the surface from interpolation based on data signals received from the grid 126.

The present invention pertains to a sensor 200. The sensor comprises a set of plates 35 that are in contact from the bottom at their corners 125 with a set of protrusions 30 that are in contact from above with a plurality of intersections, each having a sensing element, of the grid 126 of wires 23, and a thin top surface layer 127 that is disposed atop the grid 126 of plates 35, so that force imparted from above onto the top surface layer 127 is transmitted to the plates 35 and thence to the protrusions 30, and thence to the intersections of the grid 126 wires 23 which are thereby compressed between the base 47 and protrusions 30; and that the protrusions 30 above thereby focus the imparted force directly onto the sensor intersections, as shown in FIG. 52. The sensor comprises a computer 3 in communication with the sensor grid 126 which causes prompting signals to be sent to the grid 126 and reconstructs a continuous position of force on the surface from interpolation based on data signals received from the grid 126.

Each sensing element may include FSR 24. When force is imparted to the surface layer, each protrusion may be aligned to be in contact with a corresponding sensing element 26. The sensor may include adhesive 40 disposed between the surface layer and the set of plates 35, and between the protrusions 30 and the grid 126, and between the grid 126 and the base 47.

Each plate 35 may be positioned such that its corners 125 are aligned inside of the adjacent sensing elements 26. The plates 35 may be specially aligned such that there is a gap between the plates 35, and that a center of the gap between the corners 125 of the plates 35 is aligned to correspond with a sensing element 26. Each protrusion may be a rigid bump of plastic, metal, wood or glass and focuses force onto the corresponding sensing element 26, each protrusion having a shape whose contact with the corresponding sensing element 26 lies exactly upon or inside of the corresponding sensing element 26. The protrusions 30 may continue through the gap between the plates 35 to be flush with the plates 35. The protrusions 30 may emanate from vertices of the plates 35 with the plates 35.

In regard to the surface layer in contact with the set of plates 35, and the protrusions 30 in contact with the grid 126, and the grid 126 in contact with the base 47, it is understood that in

14

contact also includes the situation when adhesive 40 is between the surface layer and the set of plates 35, and adhesive 40 is between the protrusions 30 and the grid 126, and adhesive 40 is between the grid 126 and the base 47.

The present invention pertains to a method for sensing. The method comprises the steps of imparting force from above onto a top surface layer 127 that is transmitted to a set of plates 35 and thence to a set of protrusions 30, and thence to a plurality intersections of a grid 126 of wires 23 which are thereby compressed between the base 47 and protrusions 30, where the set of plates 35 are in contact from their bottom at their corners 125 with the set of protrusions 30 that are in contact from above with the plurality of intersections of the grid 126 of wires 23 disposed on the base 47; and that the protrusions 30 above thereby focus the imparted force directly onto the intersections. There is the step of causing prompting signals by a computer 3 in communication with the grid 126 to be sent to the grid 126. There is the step of reconstructing with the computer 3 a continuous position of force on the surface from interpolation based on data signals received from the grid 126.

The present invention pertains to a sensor 200. The sensor comprises a set of protrusions 30 that are in contact from the bottom with a plurality of intersections of the grid 126 of wires 23, and a set of plates 35 that are in contact from the top with a plurality of intersections of the grid 126 of wires 23, and a thin top surface layer 127 that is disposed atop the set of plates 35, so that force imparted from above onto the top surface layer 127 is transmitted to the plates 35, and thence to the intersections of the grid 126 wires 23, and thence the protrusions 30, which are thereby compressed between the plates 35 and protrusions 30; and that the protrusions 30 underneath thereby focus the imparted force directly onto the sensor intersections. The sensor comprises a computer 3 in communication with the sensor grid 126 which causes prompting signals to be sent to the grid 126 and reconstructs a continuous position of force on the surface from interpolation based on data signals received from the grid 126.

There may be the step of imparting force to a top of a mechanical layer that is transmitted through at least one intersection of a plurality of intersections, and thence to at least one protrusion of a set of protrusions 30 in contact with at least one of the intersections, where the intersections are defined by a grid 126 of wires 23 and areas of space between the wires 23, and the mechanical layer has a plurality of plates 35 that are disposed atop the grid 126 of wires 23.

There may be the step of imparting force to a top of a mechanical layer that is transmitted through at least one protrusion of a set of protrusions 30 to at least one intersection of a plurality of intersections, where the intersections are defined by a grid 126 of wires 23 and areas of space between the wires 23, and the mechanical layer has a plurality of plates 35 that are disposed atop the grid 126 of wires 23.

The present invention pertains to an apparatus 104 for inputting information into a computer 3, as shown in FIGS. 122-129. The apparatus comprises a 3d sensor that senses 3d information and produces a 3d output. The apparatus comprises a 2d sensor that senses 2d information and produces a 2d output. The apparatus comprises a processing unit which receives the 2d and 3d output and produces a combined output that is a function of the 2d and 3d output.

Objects may be identified and tracked in 3D and 2D by the 3D and 2D sensors. Fingers, hands, feet, people, pens or other objects may be identified and tracked in 3D and 2D. The apparatus may include a memory and wherein the identity of each object is maintained over time. The identity of objects from the 3D sensor may be paired with objects from the 2D



sensor by the processing unit. The 2D sensor has a surface and the 2D sensor may sense contact on the surface. The 2D sensor may sense imposed force on the surface. The 2D sensor may include a pressure imaging sensor. The 3D sensor may include a range imaging camera. The 3D sensor may include an IR depth camera. The 3D sensor may include an RGB camera. The apparatus may include a display upon which the combined output is displayed.

The present invention pertains to a method for inputting information into a computer 3. The method comprises the steps of producing a 3d output with a 3d sensor that senses 3d information. There is the step of producing a 2d output with a 2d sensor that senses 2d information. There is the step of receiving the 2d and 3d output at a processing unit. There is the step of producing a combined output with the processing unit that is a function of the 2d and 3d output.

There may be the step of identifying and tracking objects in 3D and 2D by the 3D and 2D sensors. There may be the step of identifying and tracking fingers, hands, feet, people, pens or other objects in 3D and 2D. There may be the step of maintaining in a memory the identity of each object over time. There may be the step of pairing with the processing unit the identity of objects from the 3D sensor with objects from the 2D sensor. There may be the step of the 2D sensor senses contact on its surface. There may be the step of the 2D sensor senses imposed force on its surface. The 2D sensor may include a pressure imaging sensor. The 3D sensor includes a range imaging camera. There may be the step of displaying on a display the combined output.

The grid of conductive wires 126 is comprised of the conductive trace lines 23 on the outer and inner surface sheets 21. An intersection of the grid of wires 128 is the location where two conductive trace lines 23 meet. The intersection is also where the FSR material 24 is located. The flexible touch layer 38 constitutes a top surface layer 127 for the pressure imaging apparatus 1 in the embodiments utilizing plates 35 and protrusions 30.

The following is a description in regard to the operation of the invention.

#### A List of Hardware Components:

Active Sensing Array: The Active Sensing Array 20 as seen in FIG. 1 consists of two Sensor Surface Sheets 21 facing each other, with one rotated 90° with respect to the other, as seen in FIG. 2. Each of the two Sensor Surface Sheets 21 consists of the Non-Conductive Surface Substrate 22 with printed Conductive Trace Lines 23 with small amounts of Force Sensitive Resistive (FSR) material 24 printed over them, as seen in FIG. 3 and in an exploded view in FIG. 4, at intervals such that when the two Surface Sheets 21 are placed into mutual contact, with the inked sides facing each other, the FSR 24 material is placed in the vicinity of the intersections of the grid of Conductive Trace Line 23 as seen in FIG. 1, but is not required at other locations of the sensor surface.

#### A Description Explaining how the Tiles 2 are Connected Together:

The sensor tiles 2 are connected together by wiring and a physical linking device in an apparatus 1 containing a plurality of adjacent tiles as shown in schematic in FIG. 38.

Wiring between tiles is used for the system protocol communication and to identify local tile neighbors. The protocol wiring depends on the topology of the protocol used in the system. In one implementation, the tiles are connected together by an I<sup>2</sup>C hub. In this system, the wiring starts at the master and reaches each sensor in the grid. To detect the local neighbors of each sensor, wires 23 are passed from one sensor tile to its neighbors.

In addition to wiring, a physical connector is used to link adjacent tiles. The appearance of this connector depends on the desired use of the system. In one implementation, as seen in FIG. 41, FIG. 42A and FIG. 42B, a plastic connector 71, which has holes located at key positions, is placed between adjacent tiles 2. The holes on the connector 71 line up with tabs 72 on the base support layer 32 of each tile 2. The connector can then slide onto the two adjacent devices and provides additional support to the grid.

FIG. 41 shows an exploded view of the base layer 32 with tabs 72 and the connector 71; FIG. 42A shows proper alignment of tabs 72 into connector 71; FIG. 42B shows proper position of tabs 72 and connector 71 for two adjacent tiles.

How Each Layer in the Profile View is Made, how the Overall Profile is Made, and the Purpose of Each Layer:

#### How Each Layer is Made:

The semi-rigid touch Layer 31 and the protrusions 30 as seen in FIG. 15, can be a single mechanical component, which can be made of plastic, glass, wood, metal, or any other semi-rigid material. This component can be manufactured by a variety of standard methods, including injection molding, stamping, and cold casting.

In an alternate embodiment, as seen in FIG. 12, the protrusions 30 can be rigidly affixed to surface substrate 22 of the outer sensor surface sheet 21 at the corresponding sensing element locations. One method for doing this is by cold casting: In one method of manufacture, a mold, which can consist of silicone rubber, that contains regularly spaced holes, is placed atop the outer side of surface substrate 22, and a resin is poured into these holes. When the resin hardens, the mold is removed, and the resin forms regularly spaced bumps upon the top surface of the surface substrate 22. In this embodiment, touch layer 31 is simply a semi-rigid sheet, which can be made of plastic, glass, wood or metal, or any other semi-rigid material. One advantage of this alternate embodiment is that it ensures that the protrusions 30 remain correctly aligned with the FSR material 24 corresponding to the active area of each sensing element 27 during operation of the sensor. Such a construction constitutes an active sensing array with attached protrusions 55.

#### How the Overall Profile is Made:

The overall profile is made by assembling the component layers during the manufacturing process.

For clarity, 'Outer' or 'Outer Surface' of a component, is designated to signify the side/direction of the device from which the external force is being applied, such as a user touching the surface. 'Inner' or 'Inner Surface' is designated to be the opposite direction of Outer.

The Purpose of Each Layer from Outer to Inner, as Seen as a Sensor Cross Section in FIG. 12, where Outer to Inner in this Case is from the Top of the Page Downward:

The purpose of the semi-rigid touch layer 31 and the protrusions 30, as seen in FIGS. 12 and 13, is to redistribute continuous force 34 which is applied to the outer surface of the semi-rigid touch layer 31 so that all applied force is distributed only to the active sensing element areas 27, namely at the outer or inner surface at the junctions of conductor traces 23 in the active sensing array 20, as seen in FIG.

#### 11.

The next inner layer is the non-conductive sensor substrate 22 of the outer sensor surface sheet 21 of the active sensing array 20, which can be made of thin acetate which can, in one implementation be 5 mils in thickness, followed by the next inner layer of a the pattern of metal-infused ink conducting trace lines 23 which is printed on the inner side of the substrate 22.



The next inner layer shows FSR material **24** against FSR material **24**: The outer FSR **24** pattern that is overprinted over the conducting lines **23** of the outer sensor surface sheet **21** of the active sensing array **20**, as shown in FIGS. **3** and **4**. The inner FSR **24** is overprinted over the conducting lines **23**, the next inner layer, of the inner sensor surface sheet **21** of the active sensing array **20**. In operation, these two FSR **24** components are in contact with each other, but are not mechanically affixed to each other.

The next inner layer is the non-conductive sensor substrate **22** of the inner sensor surface sheet **21** of the active sensing array **20**, which can be made of thin acetate which can, in one implementation be 5 mils in thickness, together with the pattern of metal-infused ink conducting trace lines **23** of the previous layer, which is printed on the outer side of this substrate **22**.

The next inner layer is the support layer **32** which can be made of any solid material, such as glass, acrylic, wood or metal. In one implementation, it was made of 1/4" thick acrylic.

For clarity, the sensing element **26** comprises all the material on all of the Active Sensing Array **20** at the junction of conductor traces **23** enabling the electronically measuring force in that region, as seen in FIG. **10**. The active area of a sensing element **27** corresponds to the inner or outer area on the surface of the active sensing array **20** corresponding to that location of that sensing element, specifically where force is focused upon, as seen in FIG. **11**. As such, 'in contact with the sensing element' implies contact with the active area corresponding to that sensing element.

A detailed description of following a signal through each feature of the invention from start to finish: Specifically, how the signal is generated from an object contacting the outer surface of the touch layer and what happens to it from that point on through the conducting lines, along the network, and ultimately to the computer **3** where it is imaged, covering every specific step along the way, including how interpolation is applied to the signal as part of this detailed description following the signal.

FIG. **13** shows the imposition of force or pressure **34** applied to the semi-rigid upper plate being mechanically transmitted to nearby supporting protrusions **30**, and thence to the pressure sensing active area of the sensing elements **27** where conducting lines **23** intersect on active sensing array **20** of the tile. In this embodiment the protrusions are attached to the outer surface of the active sensing array **20**, rather than to the semi-rigid touch layer **31**.

The nearby protrusions **30** and corresponding sensing elements **26** do not need to be on the same tile, but rather can be on adjacent, mechanically separate tiles, as in FIG. **14**.

FIG. **14** shows the imposition of force or pressure **34** applied to the semi-rigid upper plate being mechanically transmitted to nearby supporting protrusions **30** on two adjacent but mechanically distinct tiles, and thence to the pressure sensing active area of the sensing elements **27** where conducting lines **23** intersect on respective active sensing arrays **20** of distinct sensor tiles. In this embodiment the protrusions **30** are attached to the outer side of the active sensing array **20**, rather than to the semi-rigid touch layer **31**.

#### Interpolation

For each sensor apparatus, force imparted on a surface is mechanically redistributed such that all the force is focused onto a grid of pressure measuring sensing elements **26** under that surface on one or a plurality of tiles **2** containing active sensing arrays **20** containing sensing elements **26**, as demonstrated the various embodiments described here within. Interpolation is achieved by this mechanical redistribution. When

contact is made upon the outer surface of the apparatus and above a sensing element **26**, the force applied to that location is registered at sensing element **26**. When the contact is moved between locations above sensing elements **26**, the force is applied to multiple sensing elements **26**. The distribution of the force of the contact at each of the sensing elements **26** is used to calculate the centroid of that contact.

In particular, consider the 2x2 array of adjoining sensing elements **26** at respective locations (i,j), (i+1,j), (i,j+1), (i+1,j+1). These intersections may be labeled, A, B, C, and D as seen in FIG. **48**, where the intersections represent the locations of sensing elements **26** on an active sensing array **20**. The forces sensed at each of these sensing elements **26** may be described by fA, fB, fC, and fD, respectively.

Because the mechanical redistribution of force described here within is approximately linearly as a function of position, the centroid position [x, y] of the touch can be well approximated by the following linear interpolation of position as a function of force at the four locations. One may first approximate the fractional east/west position of the centroid between two adjoining columns by linear interpolation followed by a compensation for any nonlinearity:

$$u'=(fB+fD)/(fA+fB+fC+fD)$$

$$u=COMP(u')$$

and the fractional north/south position between two adjoining rows by linear interpolation followed by a compensation for any nonlinearity:

$$v'=(fC+fD)/(fA+fB+fC+fD)$$

$$v=COMP(v')$$

Interpolation of touch position between rows and columns is based on relative force at the nearest row/column intersections A, B, C and D as seen in FIG. **48** and described above. From this information, the centroid position of any single touch within the sensor array can be computed.

One can make use of a compensation function, represented in the above equations by the function COMP(.). This function is a monotonic mapping from the domain 0 . . . 1 to the range 0 . . . 1. This function compensates for non-linearity in the mechanical interpolation of the sensor between successive sensor elements. For example, a pressure applied to a location that is 0.25 of the way from the left neighboring conductor line **23** for a sensing element **26** to the right neighboring conductor line **23** of a neighboring sensing element **26** will result in a proportional value of pressure, with respect to total pressure, down onto the protrusion **30** on the right which is greater than 0.0 and less than 0.5, but which is not necessarily 0.25. The use of a compensation function corrects for any disparity.

FIG. **49** shows a typical set of values for the compensation function. **91** is the fractional proportion u' from left to right of the sensed pressure, in the range from 0 to 1. **92** is the desired proportional geometric position. **93** is the function that maps **91** to **92**.

In another embodiment, even more precise compensation can be attained by defining two compensation functions: COMP\_u(u', v') and COMP\_v(u', v'). In all implementations, the compensation values can be constructed by a standard calibration procedure in which pressure is applied at known positions on the sensor, and the results stored in a table. A continuous curve, such as a piecewise linear or piecewise cubic function, is then fit between measured values from this table, to create a continuous function. In the case of COMP\_u and COMP\_v, the table is two dimensional, and the interpo-



## 19

lation between table values is effected by a continuous two dimensional function, such as piecewise bilinear or piecewise bicubic.

From the values of  $u$  and  $v$ , the coordinates of the centroid may be obtained:

$$[x,y]=[S*(i+u),S*(j+v)]$$

where  $S$  is the spacing between successive rows and columns in the sensor array. In one embodiment,  $S=3/8$ ".

## Scanning

One microcontroller is associated with each sensor tile. For each sensor tile, that tile's microcontroller scans successive row/column pairs within a sub-region. The microcontroller uses digital and analog I/O pins on the micro-controller to scan the sensor for pressure information. When connected, the sets of row and column wires **23** are either assigned to be output or input wires **23**. Output wires **23** can provide a positive voltage or be set to ground. Input wires **23** can either be set to ground or read a voltage from a wire. At the start of each frame, one output wire is set to a positive voltage, while the rest of the output wires **23** are set to ground. The input wires **23** are also set to ground, except for one wire which scans the voltage coming from the intersection of the output and input wires **23**. The firmware then scans the next input wire, while setting the others to ground. After all input wires **23** have been scanned, the next output wire is set to a positive voltage, while the first is set to ground, and the input wires **23** are scanned again. This is repeated for all the voltage wires **23**, until every intersection has been scanned.

Scanning the device gives a frame of pressure information which registers the fingers or other objects that imposed force upon the MFRL. On each sensor tile, the tile's microcontroller optionally compresses the gathered sensor image data by ignoring all data values below a chosen cut-off threshold (i.e.: this data is redefined to be identically zero). Non-zero data is formed in packets, using a compression technique such as run-length encoding.

Communication from Tiles to the Computer **3**

Data packets, each tagged with the identity of the tile from which it originated, are sent over a common data communication protocol that is shared by the microcontrollers of all of the tiles in the sensor array. One sensor tile is designated as the master tile **7**. This master tile **7** possesses a USB or similar communication connection **9** to the host computer **3**, as seen in FIG. **38**. The master tile **7** sends all of the compressed packets to the host computer **3**.

On the host computer, the packets are assembled into a single seamless image of pressure.

## Possible Applications for the Invention:

Electronic white boards.

Pressure sensitive floors. One use in this area is security, such as at an airport. In this application, the sensor array would be used in conjunction with image recognition software that can identify different individuals by the differing pressure patterns of their footsteps.

Pressure sensitive touch walls.

Pressure sensitive tables or desks.

Pressure sensitive surfaces for factories.

Pressure sensitive roadways, such as highways or bridges. Uses for this include traffic monitoring, including both speed and weight of vehicles, as well as an accurate image of number of wheels and wheel distribution, which can be used for accurate assessment and categorization of vehicle type.

Pressure sensitive seats. Uses for this include train seats, automobile seats, airplane seats and seats for assistive devices such as wheelchairs.

## 20

Pressure sensitive displays. OLED displays as part of the touch layer.

Enabling Information about the Third Invention that has to do with Matching the Number of Lines to the Computer:

A given microcontroller chip has a particular number  $N$  of dual analog/digital IO pins, while the number of purely digital IO pins **82** on the microcontroller chip  $M$ . By connecting the  $N$  dual analog/digital IO pins **81** to  $N$  rows of an active sensing array **20**, and up to  $M$  of the purely digital IO pins **82** to the  $N$  columns of the active sensing array **20**, an active sensing array **20** driven from a single microcontroller can achieve up to  $N \times M$  pressure sensing elements **26** without the requirement of supplementary electronic components. This architecture results in a simple configuration of electronic components.

One embodiment uses the PIC24HJ256GP610 microcontroller from MicroChip, which contains 84 data pins altogether, of which 32 are dual analog/digital IO pins **81**, and these can be used as analog voltage input pins, one for each row of the sensor array. Setting aside the pins that are used for external communication with other microcontrollers in the grid of tiles, at least 32 digital IO pins **82** are available as power/ground switchable pins to drive 32 columns of the sensing array. Thus, this particular microcontroller is able to drive a  $32 \times 32$  array pressure sensing tile **2**, with no other electronics required aboard the tile other than a small number of resistors and capacitors to smooth out current and avoid spikes in current.

The master tile **7** in this embodiment requires a single 3.3 volt regulator, such as the Fairchild REG1117A, to drive the 5V from the host computer's USB port to the 3.3 volts required by the microcontroller. No other electronics are required.

## Utility of the Invention

There is currently no solution for low cost pressure sensing that can be easily mass-produced and that is economically scalable to form a seamless surface of arbitrarily large surface area. There are indeed specialized technologies, such as the UnMousePad by [Rosenberg] and TekScan, Inc. devices based on sensing grids that make use of force sensitive resistance (FSR) materials **24** [Eventoff], but none of these are designed or engineered to scale up reliably to large surface area at low cost per unit sensing area.

The current invention is an inexpensive and flexible way to convert any area of floor, wall, table or any other surface into a "video camera for pressure" or pressure imaging apparatus. Once the apparatus **1** is connected via a standard method for transferring digital signals, such as a serial protocol over a USB cable, to a host computer **3**, then the time-varying pressure image of any and all touches upon the surface can be read and processed to support many different applications.

The system consists of a set of one or more modular pressure tiles **2**. These tiles **2** can be of arbitrary shape, including triangular, hexagonal or other irregular tile shape. In one embodiment, each tile **2** is a square containing  $32 \times 32$  sensing elements, so the total resolution of the sensing array will be the number of tiles times  $32 \times 32$ .

A networked tile assembly **18** is composed of a collection of tiles which communicate with each other such that the physical arrangement of tiles can be reconstructed virtually. In one embodiment the size of each tile is 12 inches  $\times$  12 inches square pressure tile **2** (though the sizes of tiles in an assembly need not necessarily be equivalent). In this embodiment, if every tile has  $32 \times 32$  sensing elements **26**, then the spacing between successive sensing elements is  $3/8$ ".

Tiles can be assembled together to create an arbitrarily large seamless pressure imaging apparatus **1**. The apparatus **1**



## 21

sends to a host computer **3** a single time-varying composite image of pressure variation across the entire surface.

Power can optionally be augmented or supplied by one or more supplementary power modules as needed.

The sensor can incorporate, on its upper surface, a mechanical force redistribution layer that distributes pressure predictably so that the sensed pressure is well distributed to the sensing elements in the tile.

Step by Step Description of User Experience:

From the user's perspective, operation is as follows and as seen in FIG. **35**.

In one time step, the user imposes a finger or other physical object **34** onto the top of the pressure sensing apparatus **1**. A continuous image of this imposed pressure is transmitted by the pressure sensing apparatus **1** to a host computer **3**.

On the host computer **3** this image of spatially varying pressure is stored in a region of computer memory. From there, computer software on the host computer **1** can be used to store the image to secondary storage such as a disk file, to display the image as a visual image on a computer display **6**, to perform analysis such as finger tracking, region finding, shape analysis or any other image analysis process which is standard in the art, or for any other purpose for which an image can be used.

On the next time step, the above process is repeated, and so on for each successive time step.

Step by Step Description of Internal Working:

Internal operation begins when fingers or other objects **34** impose downward force upon the outer surface of the semi-rigid touch layer **31**, as seen in FIG. **13**.

This force is then transmitted, and properly redistributed, from the semi-rigid touch layer **31** to the sensing elements **26** on the active sensing array **30** of each sensor tile **2**, as seen in FIG. **22**. One microcontroller **5** is associated with the tile circuit board **4** for each sensor tile **2**, as seen in FIG. **32**. Grids of tiles **2** are physically, as well as with electronic cabling **10**, connected to form a coherent sensing apparatus **1**, as seen in FIG. **36**.

Then, for each sensor tile **2**, that tile's microcontroller **5** scans the pressure values at the sensing elements at each successive row/column pairs within a sub-region as described here within to form an image of pressure.

On each sensor tile **2**, the tile's microcontroller optionally compresses the gathered sensor image data by ignoring all data values below a chosen cut-off threshold (i.e.: this data is redefined to be identically zero). Non-zero data is formed in packets, using a compression technique such as run-length encoding.

The packets, each tagged with the identity of the tile from which it originated, are sent over a common data bus that is shared by the microcontrollers of all of the tiles **2** in the sensing apparatus **1** grid, as seen in FIG. **37**. One sensor tile is designated as the host communicator tile **7**. This tile possesses a USB or similar communication connection **9** to the host computer **3**. The host connection tile **7** sends all of the compressed packets to the host computer **3**, as seen in FIG. **36**.

On the host computer **3**, the packets are assembled into a single image of pressure. The identification of each tile, stored with each packet, together with pre-stored information about the relative position of each tile, as seen in one organization of Tiles seen in FIG. **38** in the corresponding Sample Tile Topology Table (below) is used by the host computer **3** to place each sub-image in its proper location within the complete multi-tile image of pressure.

## 22

Sample Tile Topology Table, corresponding to FIG. **38**

Tile ID	Row	Column
T-0	0	0
T-1	0	1
T-2	0	2
T-3	0	3
T-4	1	0
T-5	1	1
T-6	1	2
T-7	1	3
T-8	2	0
T-9	2	1
T-10	2	2
T-11	2	3

Optionally, a protocol between the microcontrollers associated with each tile can identify neighbor information within the tile grid itself. In this option, upon initialization of the connection between the tile grid and the host computer, each microcontroller is directed to send a data packet through the shared bus which identifies all neighbors with whom it is connected, as well as the direction and Tile ID of that neighbor (north, east, west or south), as seen in FIG. **40**. In FIG. **40** and the Sample Tile Topology Table and Sample Tile Adjacency Table (below), the Tile IDs are designated T-0, T-1, etc. The host computer stores this information in a table, which is indexed by tile ID, seen in Tile Topology Table (below). Each table entry contains a list of between one and four neighbor ids for that tile in the respective North, South, East, and/or west column. As with the earlier described embodiment where the tile adjacency table is manually configured, the host computer **3** uses this connectivity information to assemble all received data packets into the coherently reconstructed measured pressure data image with sensing element data from all sensing elements on all tiles in the following manner: At each time step, starting with the location of the Host Tile, placing the pressure data for host tile in a particular block of memory corresponding the data measured from that tile's sensing elements, then placing the data for the neighbors of the host tile in their proper relative positions to the host tile, then placing data for those neighbors in their respective relative positions, and so on, in a breadth first traversal of the entire connectivity graph, until data for all tiles has been properly placed in their respective positions on a Tile Topology table. An advantage of this approach is that it allows arbitrary arrangements of tiles to be accommodated.

The above method relies upon each processor knowing the identities of its immediate neighbors. In one embodiment, processors determine these identities at initialization time as follows: (1) a neighbor-determining signal is sent from the host computer along the shared bus to each tile's microcontroller in turn. A microcontroller only acts upon the neighbor-determining signal when that signal is addressed to its own unique identity; (2) upon receiving this signal, the processor sends, in turn, an identity query to each of its immediate North, South, East and West neighbors. (3) When a processor receives such an identity query from a neighboring processor, it outputs its own identity through the shared bus to the host computer, which stores this neighbor information into a software table, such the Tile Adjacency Table below. In this way, the host computer is able to establish the identities of all immediate neighbors of all tiles.



Sample Tile Adjacency Table showing results of tile neighbor queries, corresponding to FIG. 38

Tile ID	North	South	East	West
T-0	none	T-4	T-1	none
T-1	none	T-5	T-2	T-0
T-2	none	T-6	T-3	T-1
T-3	none	T-7	none	T-2
T-4	T-0	T-8	T-5	none
T-5	T-1	T-9	T-6	T-4
T-6	T-2	T-10	T-7	T-5
T-7	T-3	T-11	none	T-6
T-8	T-4	none	T-9	none
T-9	T-5	none	T-10	T-8
T-10	T-6	none	T-11	T-9
T-11	T-7	none	none	T-10

### Tiles Seamlessly Abutting to Create a Seamless Pressure Sensing Device

The difficulty of seamlessly tiling sensor arrays can be described by analogy with LCD arrays. When a collection of LCD monitors are arrayed to create larger image, there is generally a visible gap between successive monitors. This gap is caused by the fact that there are edge connections and electronics, outside of the image area of each monitor, which takes up non-zero area. Existing FSR based pressure sensor arrays, such as the TekScan sensor array, suffer from the same problem—the non-zero area around the active sensing area which is taken up by connectors and electronic components creates a geometric gap. Because of this gap, a plurality of TekScan sensors cannot be tiled to create a seamless larger sensing surface.

A plurality of TouchCo sensors cannot be seamlessly tiled for a different reason: Because the method of the TouchCo sensor requires spatial interpolation upon a continuous area of FSR material between successive active conducting lines, the sensor cannot seamlessly interpolate in any area that is not between successive conducting lines on a single sensor array. Therefore, the sensor cannot seamlessly interpolate across different physical sensors.

Our method makes use of a mechanical interpolation layer that is able to span physically different tiles. Therefore one of the novel features of the technique here is the ability to seamlessly interpolate detected force even between physically distinct sensing array tiles.

The Mechanism for Even Force Redistribution from the Continuous Upper Touch Layer to the Discrete Sensor Layer:

A mechanical layer is imposed on top of the active sensing array 20. The purpose of this layer is to redistribute the force imposed downward onto the mechanical layer, so that all of this force is transmitted exclusively to the active areas of the surface of the active sensing array 20, Where “active area” 27 is defined as any region in which the upper and lower conductive wires 23 cross, with FSR material 24 sandwiched between them where they cross, as seen in FIGS. 10 and 11. In particular, every such intersection corresponds to a sensing element 26 for measuring pressure data.

For clarity, the sensing element 26 comprises all the material on all of the Active Sensing Array 20 at the junction of conductor traces 23 enabling the electronically measuring force in that region. The active area of a sensing element 27 corresponds to the inner or outer area on the surface of the active sensing array 20 corresponding to that location of that sensing element, specifically where force is focused upon. As such, ‘in contact with the sensing element’ implies contact with the active area corresponding to that sensing element.

In one implementation, as seen in FIG. 16, the semi-rigid touch layer 31 and protrusions 30 are constructed as a single part, implemented as a thin semi-rigid plastic sheet with small raised bumps on its underside. The protrusions 30 are spaced so that when the this part is resting over the active sensing array 20, each of these protrusions 30 sits over one of the active areas of the corresponding sensing elements 27, namely the small regions of the tile where conductive trace lines 23 cross, with FSR layers 24 sandwiched between them, as seen in FIG. 17. FIG. 16 shows a semi-rigid touch surface with protrusions 33.

This structure forms a mechanism whereby a continuous change in position of a touch on the outer side of the touch surface results in a corresponding continuous change in the relative force applied to the sensor junctions that are nearest to that touch. Those relative forces, when sent to the host computer as part of the data image, permit the host computer to reconstruct the position of the touch through simple arithmetic interpolation.

FIG. 15 and FIG. 17 show a schematic profile view of the semi-rigid touch surface with protrusions 33 sitting atop the active sensing array 20. In this implementation, the bumps 30 are rigidly affixed to the semi-rigid flat touch layer 31 as a coherent part 33. This part 33 sits atop the non conduction substrate 21 of the active sensing array 20, which consists of an upper surface 21, a lower surface 21, each of which includes a respective FSR layer 24. In this figure, the conductive trace lines 23 of the active sensing array 20 are not shown. On the inner most layer is a solid support layer 32 providing a rigid base for the apparatus to counter the surface forces. In one embodiment, the support layer 32 can be a 1/2" plate of acrylic.

In FIG. 17, it can be seen that the protrusions 30 contacts the upper surface of the sensor tile only in the active regions 27 of the active sensing array 20.

This method of redistributing pressure also works when adjacent sensor elements are on physically disjoint adjacent tiles, as shown in FIG. 18. In FIG. 18, the constituent layers of the respective tiles are the same as described above for FIGS. 15 and 17. FIG. 18 shows the semi-rigid touch and protrusions layer 33 as a continuous sheet spanning the plurality of tiles, showing the physical redistributing pressure 34 between sensor elements that belong to different physical sensor array tiles.

FIG. 18 also shows an embodiment in which the active sensing array 20 wraps around the edge of one of the tiles to connect the connector tails 25 lines of that tile to the tile’s printed circuit board 4, which are located on the underside of the support layer 32.

FIG. 18 illustrates seamless sensing across adjacent physical tiles, by using mechanical force redistribution, as in the semi-rigid touch and protrusion part 33 in this embodiment, distribute force between adjacent sensing elements on distinct tiles in a way that does not require a mechanical connection between the underlying tiles themselves. When the tile array is in operation, there is no difference in signal response between the following two cases: (a) adjacent sensing elements that are on the same physical tile, and (b) adjacent sensing elements that are on different, but adjoining, physical tiles.

During any given time step, when a force is applied at the seam between two adjoining tiles, some of the force is distributed to, as seen in the cross sectional view in FIG. 18 of one embodiment, the rightmost bump of the semi-rigid touch and protrusion layer 33 that touches the tile to the left, and the remainder of the force is distributed to the leftmost bump of 33 that touches the tile to the right.



These two respective force signals will be detected by the respective microcontrollers of the tile to the left and the tile to the right, and will be sent by each of those tiles to the host computer as part of that tile's respective force image for this time step.

The host computer will then be able to reconstruct—from the respective values along the rightmost edge of the force image from the tile on the left and along the leftmost edge of the force image from the tile on the right—the position of the force applied in the region between the two adjoining tiles, using exactly the same linear interpolation that is used to compute the position of a force applied between two conducting lines within a single tile.

The result is that from the perspective of the end user and software application developer, it makes no difference whether a touch upon the grid of sensor array tiles falls within a single tile or between two adjoining tiles of the grid.

#### Physical Implementation of the Active Sensor Array

In one embodiment, the Conductive Trace Lines **23** are printed with metal infused ink over a non-conducting substrate **22**, such as plastic, as shown in FIG. **3**. All tracings **23** can be the same line width, the routing of traces **23** continue to form a Connector Tail **25** for connection to the tile's circuit board **4**, with the tails possibly of a different/thinner line width. In one embodiment of a tile, the Connector Tail **25** to the tile's printed circuit board **4** can be folded to the underside of the tile, around the protrusion **31** and Support Layer **32**, with the circuit board **4** placed beneath the Active Sensing Array **20**, as seen in FIGS. **33** and **34**. This arrangement permits adjacent tiles to abut smoothly, with no gaps in sensing area between adjacent tiles, as seen in FIG. **18**.

One embodiment of printed electrical conductor tracing lines **23** for the surface sheet **21** of the Active Sensing Array **20** of the invention as in the schematic on FIG. **5**, all conducting lines **23** are 0.5 mm in width, and are spaced at intervals of  $\frac{3}{8}$ " , and the line width of the connector tails **25**, are 0.25 mm.

The FSR Ink **24** is printed as a grid of 1 mm squares over the Conductive lines **23** in an arrangement as shown in FIG. **6** resulting in a sensor surface sheet **21**, as seen in FIG. **3**.

Note that FSR ink **24** need only be printed in the immediate neighborhood of those parts of the sensor where conducting lines cross between top and bottom layer as seen in FIGS. **3**, **10** and **11**. This arrangement results in a very small usage of FSR per unit area.

FIG. **6** shows one embodiment the FSR layer **24** that is printed over the conducting lines **23** on the Sensor Surfaces **21** of the Active Sensing Array **20** of the invention. In this embodiment, all conducting lines **23** are 0.5 mm in width, and are spaced at intervals of  $\frac{3}{8}$ ". Therefore, each 1 mm square of printed FSR **24** is a patch that is slightly larger than 0.5 mm×0.5 mm square of the intersections of the conducting lines **23** as seen in the exploded view in FIG. **10**, so that the regions where conducting lines cross are completely covered by FSR material, as seen in FIG. **11**, with the active area of the sensing element **27** at that grid location shown as hatched.

FIG. **2** shows the exploded view of the superposition of conducting lines **23** for top and bottom Sensor Surface Sheets **21** one Active Sensing Array **20** of a tile, in their final operational positions. In one embodiment, all conducting lines are 0.5 mm in width, and are spaced at intervals of  $\frac{3}{8}$ ". FIG. **1** shows the Connector Tails **25** for connecting to the Tile Circuit Board have not yet been folded under the tile. Therefore, these Connector Tails **25** appear to stick out at a vertical and a horizontal edge.

In order to test the optimal conductor line **23** width, the technique here includes a testing procedure, a Test Active

sensing array **20** is manufactured where a Test Sensor Surface **21** is printed in which the thickness of the conducting lines **23** is varied between rows (and therefore, on the obverse side of the sensor, of columns) as in FIG. **9A**. This testing version of the active sensing array **20**, as shown in FIG. **9B**, allows for selecting the optimal choice of line width for any given application in final manufactured tiles. FIG. **9B** shows the line Conductive Trace Lines **23** (with top and bottom Sensor Surfaces **21** juxtaposed).

FIG. **8** shows the test pattern of the resistive ink **24** pattern printed on Sensor Surface Sheet **21**, for the testing embodiment of an active sensing array **20** with graduated conducting trace line widths, used to test the optimal conducting trace line **23** width, as seen in FIG. **9A**. FIG. **9B** shows a superposition of the Sensor Sheets **21**, in their final operational positions of the conducting lines **23** for the top surface **21** of the active sensing array **20** and the conducting lines **23** for the bottom surface **21** of the test active sensing array **20**, for a single tile.

How the top and the bottom ink pattern can be the same, merely rotated 90 degrees and flipped over:

In one embodiment of the present invention pattern for the Trace Lines **23**, in which the Active Sensing Array **20** area is square, the top half and bottom Sensor Sheet **21** of the Active Sensing Array **20** for the Tile **2** are exactly the same. The bottom Sensor Sheet **21** is rotated 90° and then flipped over, with respect to the Sensor Sheet **21**. When this is done, the junctions and printed FSR **24** line up with each other exactly as seen in FIG. **2**.

Electronic Components Printed and/or Assembled Directly onto the Sensor Array:

Rather than requiring a separate Printed Circuit Board (PCB), all electronics can, in one embodiment, be printed and/or assembled directly onto the active sensing array **20**, thereby greatly reducing the cost and complexity of manufacture.

#### Force Sensitive Resistors (FSR):

Force-sensing resistors consist of a semi-conductive material which changes resistance following the application of force to the surface. FSR generally consists of electrically conductive and non-conductive particles causing the material to be semi-conductive. FSR is normally supplied as a sheet or as ink which can be applied using a screen printing process. FSR is low cost and durable.

#### Firmware

For each group of tiles, there are three types of firmware: a slave and a master and host communication. The slave firmware is placed on the micro-controller for each sensor tile and is used to gather pressure information for that sensor. The master firmware is installed on at least one micro-controller and manages the communication between the group of tiles and the host communication firmware transmits the pressure data to the computer.

#### Slave Firmware

The slave firmware uses digital and analog I/O pins on the micro-controller to scan the sensor for pressure information. When connected, the sets of row and column wires are either assigned to be output or input wires. Output wires can provide a positive voltage or be set to ground. Input wires can either be set to ground or read a voltage from a wire. At the start of each frame, one output wire is set to a positive voltage, while the rest of the output wires are set to ground. The input wires are also set to ground, except for one wire which scans the voltage coming from the intersection of the output and input wires. The firmware then scans the next input wire, while setting the others to ground. After all input wires have been scanned, the next output wire is set to a positive voltage, while the first is



set to ground, and the input wires are scanned again. This is repeated for all the voltage wires, until every intersection has been scanned.

In one embodiment, 32 column wires are attached to digital I/O pins and 32 row wires are attached to additional digital I/O pins that can read different voltage levels. Using slave firmware algorithm gives a 32 by 32 array of sensing element data with 4096 levels of pressure at each intersection.

#### Master Firmware

The master firmware handles the flow of information from the individual tiles to other master tiles or to the computer. To get the pressure frame information from each tile, a communication protocol is established between the master and slave microchips. The protocol topology varies depending on the size, shape and desired behavior of the tile grouping. In the communication protocol, data can either be polled by or streamed to the master micro-controller. In a polling system, the master requests frames from individual tiles, managing the flow of data to the master tile. In a streaming system, the sensors attempt to stream its data to the master until the data has been received. The data passed to the master controller can represent the entire frame of data or can be compressed. In one case, run-length encoding reduces the size of the frame by removing repeated zeros. Another form of compression involves sending only the difference between two frames. By sending only the difference between frames, static objects on the sensor having no change in pressure signature do not require the sending of any continuous data to the master about those regions.

In one implementation, an I<sup>2</sup>C hub protocol is established between multiple tiles. Information is sent from each of the slave micro-controllers on a slave Tile 11 to a master micro-controller on Master Tile 7. In FIG. 37, a schematic for an I<sup>2</sup>C hub is shown which uses a Serial Data Line (SDA) 96, which transmits the data between the slaves and the master, and a Serial Clock (SCL) 97, which keeps time, and the power or Vdd 98.

In another implementation, the tiles can use an RS-485 communication protocol and be linked together in a daisy-chain multipoint setup. FIG. 38 shows a rectangle grid of slave tiles 11 is connected in a daisy-chained S-pattern to a terminal Master Tile 7. The Master Tile 7, acting as the Host Communicator Tile 12, connects with an external computer 3 over USB 9.

The accumulated pressure data is then passed through an addition communication protocol to the requesting device. In one implementation, a UART point-to-point communication is established between the micro-controller and the computer using a serial USB cable. Pressure data is sent from the micro-controller to software drivers located on a host computer.

In other embodiments, as seen in FIG. 39, there can be more than one master tile 7 in the grid. For larger areas and/or longer distances, groups of tiles can be reduced into zones, splitting up the data responsibilities to multiple masters 7. The data from these multiple zones can be collected through multiple communication protocols to the computer or a tree structure could be used so data is sent to a up the tree's masters until the data reaches the desired location. In other embodiments, a multi-master protocol can be used to allow slaves 11 to divide the data sent between multiple masters in the same bus, reducing the load on a single master 7 to collect the data. These masters can be but are not necessarily the Host Communicator Tile 12 that transmits data to the computer.

Stepping through the entire process from the perspective of the respective parts of one embodiment:

List of Hardware Components

Host Computer 3

USB Connector 9

Printed Circuit Board 8

Microcontroller 5

Semi-Rigid Touch Layer 31

Active Sensing Array 20

Physical Substrate Support Surface 32

Inter-Tile Communication Cable 10

Neighbor Query/Sense Wires 13

Inter-Tile Physical Link Connector 71

Apparatus Housing/Frame 14

A computer 3 is connected to a grid of tiles 7 & 11 with a USB Connector 9 to a Host Communication Tile 12 in a grid of Tiles as seen in FIG. 36.

An Inter-Tile Physical Link Connector 71 physically connects the tiles to each other, as seen in FIGS. 41, 42A, and 42B.

The Inter-Tile Physical Link connection 71 should be sized to maintain the same distance between the adjacent tile's sensing elements and the standard (in Tile) sensing element spacing.

FIG. 45 shows two adjacent tiles preserving inter-sensing element 26 distance is preserved across tiles 2.

An Inter-Tile Communication Cables 10 connects tiles, in one implementation, in a daisy chain manner as seen in FIG. 38.

FIG. 38 shows a Chain of Slave Tiles 2 to the Master 7/Host Communication Tile 12, and then via USB 9 to Computer 3.

The tiles do not need to be in any particular geometric configuration. In fact, the surface they form can be non-contiguous. FIG. 43 shows a daisy chain connection between an arrangement of non-contiguous tiles 2. The tiles 2 are connected by a daisy chain of inter tile connections 10. One of the tiles acts as master 7 and host connectivity tile 12 and has a connection 9 to the host computer 3.

A Query/Sense wire (QSW) 84-87 also is connected between adjacent tiles.

The North QSW 84 will be connected to the South QSW 85 of the tile above it (if it exists).

The South QSW 85 will be connected to the North QSW 84 of the tile below it (if it exists).

The East QSW 86 will be connected to the West QSW 87 of the tile to its left (if it exists).

The West QSW 87 will be connected to the East QSW 86 of the tile to its right (if it exists).

FIG. 40 shows a Sample Grid of Tiles with N/S/E/W neighbor query/sense connection.

In One embodiment as seen in FIG. 119, each Tile 2 consists of:

A Support Layer 32

A Printed Circuit Board (PCB) with a microprocessor 4  
The Printed Circuit board 4 may be mounted on the bottom of the Support Layer 32.

An Inter-Tile Communication Cable 10 is attached to the Printed circuit board 4 for connection to an adjacent tile 2.

Four Query/Sense Connection Wires 84-87 are attached to the Printed Circuit Board 4.

The Host Communication Tile Printed Circuit Board 95 for a Host Communication Tile 12 will also have a USB connection wire 9 for connecting with the Host Computer 3. In the case of a single tile embodiment,



## 29

that single tile's printed circuit board **4** can also provide the functionality of the Host Communication Tile.

An Active Sensing Array **20** consisting of an N×M grid of sensing elements and control wires **23**.

The active sensing array **20** is placed above the Support Layer **32**.

The active sensing array **20** is wrapped around the edge of the Support Layer **32**.

The active sensing array **20** is plugged into the tile PCB **4** using the connector Tails **25** on the Active sensing array **20**.

Protrusions **30** are affixed on the outer face of the active sensing array **20** at the corresponding sensing element **26** locations as in an active sensing array with attached protrusions **55** embodiment is shown in FIG. **119**.

A Semi-Rigid Touch Layer **31**

The Semi-Rigid Touch Layer **31** is placed on top of the active sensing array **20**.

In one embodiment, the Active Surface Array **20**, as seen in FIGS. **1-6**, for an N×M grid of sensing elements consisting of:

One layer with conductor lines **23** for N rows

One layer with conductor line **23** for M columns

Force Sensitive Resistor (FSR) material **24** at the row/column intersections

Connector Tail **25** with N and M wires corresponding to rows and columns conductor lines respectively. The connector tails are separated into banks of 16.

FIG. **119** shows Connector Tails **25** separated into banks of 16.

FIG. **46** is a block diagram of the electronics for a tile functioning as both the Host communication Tile **12** and as a Master Tile **7**. The host computer **3** is connected host communication tile **12** via a standard protocol such as USB where the data is transferred back and forth via the Rx **78** and Tx **79** line. Power can be supplied, via the USB cable, from the computer **3**, through a voltage regulator **76** as required by the microcontroller **5**. The active sensing array **20** is connected to the Printed Circuit Board **4** by plugging the connector tails **25** of the active sensor array **20** into the tail connector clip **16** on the printed circuit board **4**. The Master Tile **7** communicates with slave tiles **11** via a communication protocol such as I<sup>2</sup>C connected by inter-tile communication cables **10**. Power, or V<sub>dd</sub> **98**, is supplied to all slave devices from either the Master Tile **7** or via an external power supply **17** as needed. Adding a common ground to all active electronics, V<sub>ss</sub> **99**, completes the circuit.

FIG. **47** shows a block diagram for a slave tile **11**. The Microcontroller **5** is on the same power (V<sub>dd</sub> **98**)/ground (V<sub>ss</sub> **99**) circuit as the other tiles, including the master tile **7**. The active sensing array **20** is connected to the PCB **4** by plugging the active sensing array **20**'s connector tails **25** into the connector tail clip **16** on the printed circuit board **4**. A slave tile **11** communicates with other tiles via a communication protocol such as I<sup>2</sup>C connected by inter-tile communication cables **10**.

Tile Housing/Frame

The entire Tile **2** assembly may be housed in frame made of plastic or other materials.

The width of any housing frame perimeter must be thin enough to maintain inter-sensing element distances across tiles, as seen in FIG. **45**.

Stepping through one embodiment of capturing and transmitting Pressure Image Data across multiple tiles and to a Host Computer, to create a full time-varying multi-tile Pressure Image.

## 30

Each Tile contains (along with supporting electronics as per the description above):

A programmable microcontroller **5**

Microcode to sensor data collection and communication (described as follows)

An Active Sensing Array with N columns and M Rows **20** Inter Tile Communication wiring **10** to support a Master/Slave bus, such as I<sup>2</sup>C, as shown in FIG. **38**

The Host Communication Tile **12** (such as T-0 in FIG. **38**) contains:

A USB Connection **9** to the Host Computer **3**

Note: It is standard that commercial microprocessors provide inter circuit communication protocols such as I<sup>2</sup>C capabilities.

For example PIC24HJ256GP610 microcontroller from MicroChip provides I<sup>2</sup>C support

I<sup>2</sup>C is an industry standard Master/Slave Bus Protocol

I<sup>2</sup>C provides protocols for dynamically assigning unique IDs to slaves on the Bus

Note: It is standard that commercial microprocessors provide USB capabilities

For example, PIC24HJ256GP610 microcontroller from MicroChip provides USB support

Note: It is standard that commercial microprocessors can simultaneously support both I<sup>2</sup>C and USB communications

For example PIC24HJ256GP610 microcontroller from MicroChip has this capability

As per the above, the methodology will assume that

The Host Communication Tile **12** will contain Host Communication Tile Firmware

In the example shown in FIG. **38**, Tile T-0 is acting as the Host Communication Tile **12** and as a Master Tile **7** for the grid

All Other tiles will be considered slave tiles **11**

Slave tiles **11** will contain the slave tile Firmware

Slave tiles **11** will have obtained unique IDs as per I<sup>2</sup>C standard protocol

Firmware on the microcontroller for tiles perform several distinct tasks

1. Local Tile Sensor Grid Pressure Image Capturing

2. Getting the Data from Slaves **11** to the Master Tile **7** and/or Host Communication Tile **12**

3. Communicating Local Tile Sensor Grid Pressure Image to Host Computer **3**

4. Communicating Tile topology and/or adjacency data to the Host Computer **3** for the reconstruction of the multi-Tile Pressure Image on the Host Computer **3**

5. Initial Dynamic Discovery of neighboring tile topology adjacency data

Note this step would not be necessary if pre-assigned IDs were applied to the tiles along with manual storing of tile topology.

In a single tile apparatus embodiment, that single tile can also act as the Host Communication Tile **12**. In a single Zone apparatus embodiment, namely an apparatus containing grid of tiles with a single Master Tile **7** and as seen in FIG. **38**, that single Master Tile **7** can also act as the Host Communication Tile **12**. In a multi-zone apparatus embodiment, namely an apparatus containing grid of tiles with multiple Master Tile **7** in communication with each other and as seen in FIG. **39**, one of these master tiles **7** can also act as the Host Communication Tile **12**.

In some embodiments, the circuitry and microcode for the Master tile functionality may be on a separate printed circuit board that may or may not physically be connected to the Master Tile **7**. Similarly, in each case, in some embodiments, the circuitry and microcode for the Host Communication Tile



functionality may be on a separate printed circuit board that may or may not physically be connected to the Host Communication Tile 7.

Each connecting cable that goes between two tiles such as the Inter Tile Communication Cable 10 or the Master-master multi-zone connector cable 94 is concurrently an 'inbound cable' for one of the tiles and 'outbound cable' for the other. Relative to a specific tile though, an 'inbound cable' is one from the tile in the chain from which sensing data packets flow towards the host computer in the visa-versa for an 'inbound cable'. For example relative to FIG. 38, the cable between T-1 and T-2 is an Inbound cable for T-2 and an outbound cable for T-1.

FIG. 44 shows the cables/wires to/from a respective tile printed circuit board 4 for one embodiment of tiles such that:

All tiles have Query Sensing Wires 84-87;

All Tiles have Connector Tails 25 going into their Connector Tail Clip 16

Master Tile 7 and Non-Terminal slave tiles 11 for a zone have Outbound Inter-Tile Communication Cables 89

Slave Tiles 11 have Inbound Inter-Tile Communication Cables 88

Host Communication Tile 12 will have a USB Cable (in one embodiment)

In a multi-zone apparatus, Host Communication Tile 12 and Non-Terminal Master tiles 7 for a zone have Outbound Master-master multi-zone communication cable 74

In a multi-zone apparatus, Non Host communication Master Tiles 7 for a zone have Inbound Master-master multi-zone communication cable 73

(1) Local Tile Sensor Grid Pressure Image Capturing (Both Master and Slave)

The Image Capturing Microcode will maintain  $N \times M$  numeric Pressure Image Buffer of measured sensing element values corresponding to a Frame of pressure data for that tile. The values in this Buffer are measured in the following manner.

The (i,j) element of the Pressure Image Buffer will correspond to the pressure value for a row and column intersection.

As per method described in the text above, the (i,j) element of the Image Buffer Array may be measured by Setting all output wires to ground, except for the i-th output wire

Set the i-th output wire to Positive

Set all input wires to ground, except for the j-th input wire

The firmware will scan the j-th input wire reading it as a digital value

This value will be stored in the (i, j) element of the Pressure Image Buffer

By looping through all N and M wires a complete  $N \times M$  Pressure Image Buffer data is measured

(2) Getting the Data from Slaves Tiles 11 to the Master 7  
The Microcode on the Master Tile 7 will poll each slave tile 11 for Pressure Image Data

The reported data packet from each slave will contain the tile ID and the Pressure Image Buffer Data

For simplicity, assume the Pressure Image Buffer Data is a full copy of the Tile's Image Buffer

Alternatively it could be run length encoded

Alternatively it could provide delta (only changes from the previously reported buffer)

Either, both or other techniques can be applied to improve performance on the data transfer subsystem

The Microcode on the Slave Tiles 11 will receive a poll request and respond by sending the packet of data as per the above description, namely Tile ID+Pressure Image Buffer data

(3) Communicating Local Tile Sensor Grid Pressure Image from the Master Tile 7 to Host Computer 3, described for the embodiment where the Master Tile 7 is also acting as the Host communication Tile 12.

Expanding upon (2) above, the Master Host Communication Tile 7 will

For Each Slave Tile 11

Poll each Slave Tile 11 for Pressure Image Data over the I<sup>2</sup>C Bus

Receive the Slave Tile's 11 Pressure Image Data over the I<sup>2</sup>C Bus

Send the Slave Tile's 11 Pressure Image Data to the Host Computer 3 over USB

Send its own Pressure Image Data (if connected to a tile) to the Host Computer 3 over USB

By repeating the above step continuously, Streaming, Time-Varying Pressure Image Data for the aggregate of tiles 2 will be received by the host computer 3.

(4) Reconstruction a multi-Tile Pressure Image on the Host Computer

In one embodiment an  $A \times B$  row/column grid of Pressure Tiles 2, each containing  $N \times M$  row/column grid of sensing elements 26 in their respective Active Sensing Arrays 20, produces an effective Pressure Surface of  $(A * N)$  rows and  $(B * M)$  columns grid of addressable Pressure data of a reconstructable pressure image.

A Tile Topology Data Table on the host computer can be maintained with the position of the Tile relative to the overall Grid of Tile Topology

In one embodiment this can be manually stored on the Host Computer

In another embodiment it can be dynamically constructed from a Tile Adjacency Table

Sample Tile Topology and Tile adjacency tables corresponding to the apparatus configuration seen in FIG. 38 appear earlier in this document.

As Pressure Image Buffer Data for each tile with a provided Tile ID is received

The Tile Row r, and Tile Column c, values may be looked up in Tile Topology Table

The Tile Pressure Image Data can be mapped to the Coherent  $(N \times A) \times (M \times B)$  overall pressure Image by mapping the tile's sensing element data for (i,j) to  $(r * N + i, c * M + j)$

(5) Initial Dynamic Discovery Neighboring Tile Topology  
During an initialization phase, the relative positions of all of the tiles could be obtained by the following series of data exchanges (over the I<sup>2</sup>C Bus unless otherwise stated).

The Microcode on the Master Tile 7 performs as follows:  
For Each Slave Tile 11 and for the master tile 7

For each of North, South, East, West

Send a data packet requesting that the tile turn on the corresponding Query/Sensing wire (North 84, South 85, East 86, or West 87) for that direction for the query Tile ID

Packet Contents: Query Tile ID and the direction wire to turn on

Receive the Query/Sense response packet from the appropriate Tile

'Packet Contents: Detected', direction (North/South/East/West), Detected Tile ID, Query TileID (from detecting Tile)

Packet Contents; 'Nothing Connected', direction, Query TileID



Send the response packet to the 3 Computer over USB  
 The Microcode on the Slave designated to receive the  
 'activate wire' request to turn on the Query/Sensing Wire  
 If that tile detects that no tile is connected in the designated  
 direction (possibly due to an end resistor) 5  
 Send a 'Nothing Connected' response packet to the Master  
 Packet Contents; 'Nothing Connected', direction, Query  
 TileID  
 Otherwise, turn 'on' the designated directional Query 10  
 Sensing Wire (North **84**, South **85**, East **86**, or West **87**)  
 The Microcode on the Slave that detects the 'on' Query  
 Wire State from its corresponding Query State Wire (North  
**84**, South **85**, East **86**, or west **87**)  
 Send a 'Detected' and its Tile ID data packet to the Master 15  
 'Packet Contents: Detected', direction (North/South/East/  
 West), Detected Tile ID, Query TileID (from detecting  
 Tile)  
 Note that the detecting wire direction is the opposite direc-  
 tion as the detected tile direction, namely: detecting on 20  
 North Wire **84** indicates tile to the South; South Wire **85**  
 indicates tile to the North; East Wire **86** indicates tile to  
 the West; and West **87** Wire indicates tile to the East.  
 In the embodiment of an N×M Rectangular grid of tiles, a  
 'Tile Topology Table' can be constructed from the 'Tile Adj-  
 acency Table' as follows:  
 Create a set of M ordered column lists of tile IDs corre- 25  
 sponding to North/South Connectivity by  
 for each of the M Tile IDs that has 'none' as its northern  
 neighbor  
 Search for the Tile ID that has this for its southern  
 neighbor 30  
 Iterate until a Tile ID with 'none' as its southern  
 neighbor is obtained

Order the set of M ordered Column lists left to right as  
 follows:  
 Search the set of Column Lists' first element for the one  
 with 'none' in the WEST direction. This is the left-  
 most column (i.e. column 0)  
 Search for the Column List whose first Element is EAST  
 of the one just found  
 Iterate until at the column list who's first Element has no  
 EAST neighbor  
 One can now populate the Adjacency table by getting the  
 respective row/column numbers of the tile IDs  
 The column numbers are from the ordered column list  
 position  
 The row numbers are the position in the respective col-  
 umn list  
 A Description of the Actual Prototype that was Built  
 A description as an example of the prototype built: (a) The  
 actual materials used for each layer, (b) the dimensions, (c)  
 the size of each tile, (d) how many tiles were used, (e) the  
 product number and company which made a given compo-  
 nent.  
 Basically all details about the prototype. It can be in any  
 form, such as a table or list, whatever is easiest to provide the  
 information into the application.  
 (a) the Actual Materials Used for Each Layer  
 The individual sensing materials used for each sensing tile  
 consists of a 5 mil thick plastic substrate, printed silver elec-  
 trodes (placed at 3/8" spacing) and small rectangles of FSR  
 materials in the vicinity of the grid intersections.  
 (b) The Dimensions  
 The active sensing area of each sensing tile is 12"×12"  
 (c) The Size of Each Tile  
 Each tile is 12"×12" with 3/8" spacing between wires.  
 (d) The Product Number and Company which Made a  
 Given Component:

COMPONENT TABLE

Name	Component	Value	Manuf	Manuf Part No	Distrib	Distrib Part No	Qty
C1-C10	.1 uf capacitor	.1 uF		c0603c104k5ractu	Mouser	80-c0603c10455r	10
C11	10 uf capacitor	10 uF		C0805C106Z8VACTU	Mouser	80-C0805C106Z8V	1
CONN8	Molex 1 mm 16pin hot ziff connector	n/a	Molex	52271-1679	Mouser	538-52271-1679	1
CONN9	Molex 1 mm 16pin hot ziff connector	n/a	Molex	52271-1679	Mouser	538-52271-1679	1
CONN10	Molex 1 mm 16pin top ziff connector	n/a	Molex	52207-1685	Mouser	538-52207-1685	1
CONN11	Molex 1 mm 16pin top ziff connector	n/a	Molex	52207-1685	Mouser	538-52207-1685	1
LB	LED BLUE	n/a	Avago Technologies	HSMN-C170	Mouser	630-HSMN-C170	1
LG	LED GREEN	n/a	Avago Technologies	HSMM-C170	Mouser	630-HSMM-C170	1
LR	LED RED	n/a	Avago Technologies	HSMC-C170	Mouser	630-HSMC-C170	1
R1	R	100 Ohms		CRCW0603100RFKEA	Mouser	71-CRCW0603- 100-E3	1
R2	R	4.7K Ohms		CRCW06034K70FKEA	Mouser	71-CRCW0603- 4.7k-e3	1
RLB	R SMT 3.3K	3.3K Ohms	Vishay	CRCW06033K30JNEA	Mouser	71-CRCW0603J- 3.3K-E3	1
RLG	R SMT 3.3K	3.3K Ohms	Vishay	CRCW06033K30JNEA	Mouser	71-CRCW0603J- 3.3K-E3	1
RLR	R SMT 3.3K	3.3K Ohms	Vishay	CRCW06033K30JNEA	Mouser	71-CRCW0603J- 3.3K-E3	1
U1	PIC24HJ256GP610	n/a	Microchip	PIC24HJ256GP610- I/PF	Mouser	579- 24HJ256GP610-P/PF	1
U2	REG1117A	3.3 v	Fairchild	REG1117A-ND	DigiKey	REG1117A-ND	1
USB Transceiver	USB-RS422	n/a	FTDI, ltd.	TTL-232R-3.3V-WE	Mouser	895-TTL-232R- 5V-WE	1
Sensor	Sensing Layers	n/a	Parlex	VIP294	Parlex	VIP294	2
Total Number of parts:							27



## (e) Pressure Sensitivity

To test the pressure sensitivity of the prototype, a 5 g base that rests four points was placed with one of the points on top of a wire intersection. 5 g and 100 g weights were placed on the base to create weights from 5 g to 300 g. The intersection received a quarter of this weight, so the weight range varied from 1.25 g to 75 g at the intersection. Values were only registered by the computer for weights above 2.5 g. The values from the computer scaled linearly from 46.87 to 1320.71.

Weight at Intersection	Value on Visualizer
0 g	0
2.5 g	46.87
5 g	101.65
7.5 g	167.97
10 g	218.75
12.5 g	265.62
25 g	468.75
50 g	871.34
75 g	1320.71

## Outline

## List of all components

- Integrated Protrusion and Base Layer **42**
- Active Sensing Array **20**
- Semi-Rigid Touch Layer **33**
- USB Cable **9** and USB Transceiver **80**
- Computer **3**
- Master Tile **7**

## Operation: Outside point of view

One or more objects are placed into contact with the Pressure Sensing Apparatus **1**. The Pressure Sensing Apparatus **1** sends to the computer a two-dimensional array of pressures corresponding to the space-varying pressure of the objects upon the surface.

User touches the Pressure Sensing Apparatus **1** at multiple locations, and the device indicates both location and pressure at each location.

The Embodiment that follows is similar to the Semi-Rigid Touch Layer with Protrusions **33** and the Active Sensing Array with attached protrusions **55** embodiments described above in all aspects other than how force is transmitted to the sensing elements **26** on the Active Sensing Array **20**. In the Integrated Protrusion and Base Layer **42** assembly, this is accomplished by an assembly where the Active Sensing Array **20** sits between a Semi-Rigid Touch Layer **31** and an Integrated Protrusion and Base Layer **42** as seen in FIG. **19**. All approaches result in imposition of force **34** values being measured at each sensing element **26** on the Active Sensing Array **20**. As a result, the description of Interpolation, scanning of data from the sensing elements **26** by the Microcontroller **5**, networking slave tiles **11** and master tiles **7**, and all other techniques beyond the measuring of the sensing element **26** pressure are all achieved in a similar manner.

The Integrated Protrusion and Base Layer **42** embodiment is potentially easier and less expensive to manufacture and assemble than the Semi-Rigid Touch Layer with Protrusions **33**. In this embodiment, the Semi-Rigid Touch Layer **31** can be independent of any individual pressure tile **2** and may seamlessly span an arbitrary number of pressure tiles **2**. This makes assembly and alignment of the Pressure Sensing Apparatus **1** significantly easier. Having a seamless Semi-Rigid Touch Layer **31** along adjacent pressure tiles **2** naturally results in identical and seamless distribution of force to sens-

ing elements **26** regardless of whether the sensing elements **26** are on the same or adjacent pressure tiles **2**.

Additionally, an embodiment of the Integrated Protrusion and Base **42** Layer may include housing for the Printed Circuit Board **4** and grooves for Tile Connection Cables such as the Inter-Tile communication Connection Cables **10** and multi-zone cable **94**, thus reducing the number of parts in the Pressure Tile **2** assembly.

The Pressure Sensing Apparatus **1** can incorporate a mechanical force redistribution mechanism that properly distributes pressure so that the sensed pressure is well distributed to the sensing elements in the tile.

The Semi-Rigid Touch Layer with Protrusions **30** can be replaced by a component that is mechanically integral to the supporting base of the pressure tile **2** itself. This makes manufacture easier, is less expensive and more robust, and that makes it easier to avoid misalignment between sensing elements **26** and protrusions **30**.

In order to create a Pressure Sensing Apparatus **1** of multiple pressure tiles **2** that creates a seamless and continuous interpolating touch response, the only mechanical component that needs to be shared between the plurality of pressure tiles **2** is a featureless sheet of material, such as plastic, the position of which does not need to be precisely registered with the positions of the sensors in the grid of sensor tiles.

## Step by Step Description of Internal Working:

Internal operation begins when fingers or other objects impose downward force **34** upon the Semi-Rigid Touch Layer **31**.

This force is then transmitted, and properly redistributed, from the Semi-Rigid Touch Layer **31** through the sensing elements **26** in the Active Sensing Array **20**. The force impinging on each sensing element **26** is then imparted onto the corresponding protrusion **30** in the Integrated Protrusion and Base Layer **42**. This creates a concentration of force on the portion of the Active Sensing Array **20** where each sensing element **26** is in contact with a corresponding protrusion **30**, thereby creating a force that compresses together the two areas of FSR material **24** in mutual contact at the regions of the Active Sensing Array **20** that comprise the sensing elements **26** (where one FSR region on the outer conducting line of the Active Sensing Array **20** is in contact with a corresponding region of FSR material **24** on the Conductive Trace Lines **23** of the Active Sensing Array **20**).

The compression creates an increase of electrical conductance between those two areas of FSR material **24** in mutual contact. As the sensor's micro-controller **5** scans through the Active Sensing Array's **20** matrix of sensing elements **26**, each change in conductance is measured as a change in voltage, which the micro-controller detects via an Analog to Digital Converter (ADC) **83** that the microcontroller **5** then encodes as a digital signal. The microcontroller **5** then sends this digital signal through a USB Cable **9** to a host computer **3**.

Unlike the Semi Rigid Touch Layer with Protrusions **33** technique where the inner face of the protrusions **30** are in contact with the outer surface of the Active Sensing Array **20** as seen in FIG. **15**, this technique with the Integrated Protrusion and Base Layer **42** has the outer face of the protrusions **30** in contact with the inner surface of the Active Sensing Array **20**, as seen in FIG. **121**. This mechanical arrangement allows a concentration of force at the sensing elements **26** of the Active Sensing Array **20**, thereby enabling spatial interpolation between adjoining sensing elements **26** without the requirement of protrusions **30** above the Active Sensing Array **20**.



One microcontroller **5** can be associated with each pressure tile **2**.

#### General Purpose of Each Layer

FIG. **19** shows an exploded view of a Pressure Tile **2** with the following components: Integrated Protrusion and Base Layer **42**, 2 Active Sensing Array **20**, Semi-Rigid Touch Layer **31**. The Conductive Trace Line **23** intersections on the Active Sensing Array **20** are the locations of the FSR material **24** sensing elements **26**. When the layers are placed into contact, each intersection in the Active Sensing Array **20** is aligned with the center of a corresponding protrusion **30** in the Integrated Protrusion and Base Layer **42**.

FIG. **20** shows a Profile view of a Pressure Tile **2** with: the Semi-Rigid Touch Layer **31** which is in contact with the Active Sensing Array **20**; and the Active Sensing Array **20** which is in contact with protrusions **30** of the Integrated Protrusion and Base Layer **42**. The protrusions **30** on the Integrated Protrusion and Base layer **42** are aligned with the sensing element **26** regions on the Active Sensing Array **20**.

Active Sensing Array **20**: The Active Sensing Array **20**, shown in FIG. **1**, consists of two sensor surface sheets **21** facing each other, where one sensor surface sheet **21** is rotated 90° with respect to the other sensor surface sheet **21**, as seen in FIG. **2**. FIG. **4** shows the layers of a Sensor Surface Sheet **21** that is complete in FIG. **3**. Upon each of the two sensor surface sheets **21** is printed conductive trace lines **23**. Small amounts of force sensitive resistive (FSR) material **24** is printed at intervals such that when the two substrates are placed into mutual contact, with the FSR material **24** sides facing each other, the FSR material **24** printed on each sensor surface sheet **21** is placed in the vicinity of the intersections of the grid of conductive trace lines **23**. The grid intersection points of overlapping FSR material **24** comprise a sensing element **26** where pressure may be measured.

The Integrated Protrusion and Base Layer **42** consisting of a grid of protrusions **30** spaced such that when the Active Sensing Array **20** is affixed over this layer, one of these protrusions **30** sits directly under a sensing element **26** of the Active Sensing array **20** at the junctions of a multitude of row and column electrodes where the FSR material **24** layers are sandwiched so that pressure may be measured at each intersection point.

The Semi-Rigid Touch Layer **31** is placed in contact with one or more Active Sensing Arrays **20**, each of which is resting in contact with the protrusions **30** in its respective Integrated Protrusion and Base Layer **42**. Pressure applied to the Semi-Rigid Touch Layer **31** will focus the force to the sensing elements **26** directly above protrusions **30** on the Integrated Protrusion and Base Layer **42**. In one implementation, the Semi-Rigid Touch Layer **31** is implemented as a sheet of vinyl that can be in the range of 0.5 mm to 1.0 mm in thickness. In another implementation of a single tile configuration the Non-Conductive Surface Substrate **22** of the Active Sensing Array **20** may act as its own Semi-Rigid Touch Layer **31**. In other implementations the Semi-Rigid Touch Layer **31** may be made of glass, metal or any other material whose thickness can be chosen so that the Semi-Rigid Touch Layer's **31** rigidity falls within a useful range of rigidity.

FIGS. **21**, **22** and **23** are three cases in which the Semi-Rigid Touch Layer **31** is, respectively: FIG. **21** Too rigid; FIG. **22** Within the useful range of rigidity; FIG. **23** Insufficiently rigid. In each case, the hand shows Imposition of Force **34**, and the arrows show imparted force transmitted to the base **56** to different parts of the base **32** of the pressure tile **2**.

The Semi-Rigid Touch Layer **31** having a "useful range of rigidity" can be defined via the following constraints of maximal rigidity and minimal rigidity, respectively: The Semi-

Rigid Touch Layer **31** would be too rigid if an externally applied force within a 1 mm diameter circular region of the outer face of the Semi-Rigid Touch Layer **31**, lying within a rectangular region bounded by four nearest protrusions **30** of the Integrated Protrusion and Base Layer **42** at the rectangle's corners, were to result in pressure being applied to protrusions **30** of the Integrated Protrusion and Base Layer **42** other than those four nearest protrusions **30**, as shown in FIG. **21**. For example, a 1 cm thick plate of glass would be too rigid to serve as the Semi Rigid Touch Layer **31**. The Semi-Rigid Touch layer **31** is in the useful range of rigidity if the imposition of force **34** causes force to be imparted to those nearest protrusions **30** but not to other protrusions **30** of the Integrated Protrusion and Base Layer **42**, nor to the underlying surface of the Support Layer **32** between the protrusions **30** as shown in FIG. **22**; The Semi-Rigid Touch Layer **31** would be insufficiently rigid if the same imposition of force **34** were to cause the Semi-Rigid Touch Layer **31** to deform to sufficient extent that the Semi-Rigid Touch Layer **31** would physically come into contact with the region of the Integrated Protrusion and Base Layer **42** between those four protrusions **30**, thereby dissipating force onto inactive regions of the Active Sensing Layer **20** as shown in FIG. **23**. For example, a 0.5 mm thick sheet of rubber would be insufficiently rigid to serve as the Semi-Rigid Touch Layer **31**.

In one implementation the Semi-Rigid Touch Layer **31** consists of a 1.0 mm thick sheet of vinyl which has a Young's Modulus of elasticity of approximately 0.33 GPa's or 49000 psi would fall into the valid range of rigidity for the prototype implementation with 3/8" spacing of protrusions that are 1 mm in height. Other materials would suffice, but as the Young's Modulus increases, the thickness of the material should correspondingly decrease so as to localize the bending or elasticity of the material to a region of no more than 2x2 square sensing elements **30**.

The total size and shape of the Semi-Rigid Touch Layer **31** can be made so as to match the total size and shape of the networked grid of pressure tiles **2** in the apparatus **1**.

An Integrated Protrusion and Base Layer **42** contains a grid of upward facing protrusions **30** spaced such that when the Active Sensing Array **20** is placed on the outside face of this layer, each of these protrusions **30** is aligned with active sensing area **27** of one of the sensing elements **26** of the Active Sensing Array **20**, as seen in FIG. **20**.

A Semi Rigid Touch Layer **31** is placed in contact on the outside face of the Active Sensing Array **20**. Imposition of force **34** applied from above to this Touch Layer will be focused by the geometric arrangement of sensing elements **26** that are in contact with corresponding protrusions of the Integrated Protrusion and Base Layer **42** so that all applied pressure **34** imparted to the Semi-Rigid Touch Layer **31** becomes concentrated in the region where the sensing elements **26** of the Active Sensing Array **20** are in contact with corresponding protrusions **30** of the Integrated Protrusion and Base Layer **42**, as seen in FIG. **20**.

This configuration of components forms a mechanism whereby a continuous change in position of a touch on the outer face of the Semi-Rigid Touch Layer **31** results in a corresponding continuous change in the relative force applied to the active areas **27** of those sensing elements **26** that are nearest to that touch, as shown in FIG. **24**. Those relative forces, when sent to the host computer **3** as part of the data image, permit the host computer **3** to accurately reconstruct the centroid position of the touch through arithmetic interpolation.

FIG. **24** shows a three dimensional view of interpolation: The imposition of force **34** impinging upon the Semi-Rigid



Touch Layer 31 at a given location will be focused on the 2×2 nearest protrusions 30 of the Integrated Protrusion and Base Layer 42. Therefore in the Active Sensing Array 20 layer all of the imposition of force 34 will be concentrated on the 2×2 active sensing areas 27 of the sensing elements that are in direct mechanical contact with these four protrusions 30.

#### Functional Layers

The three components of, respectively, the Semi-Rigid Touch Layer 31, the Active Sensing Array 20, and the Integrated Protrusion and Base Layer 42, can be seen as consisting of five functional layers, for the purposes of describing the internal mechanism of operation at a single sensing element as seen in FIG. 121.

These functional layers are, respectively:

- (1) the Semi-Rigid Touch Layer 31;
- (2) the Active Sensing Array 20 consisting of: outer Non-conductive surface substrate 22, outer Conductive trace lines 23 (not shown in this FIG. 121); inner and outer FSR material 24 layers; inner Conductive trace lines 23 (not shown in this FIG. 121); and inner Non-conductive surface substrate 22; and
- (3) the Integrated Protrusion and Base Layer 42 containing protrusions 30.

The semi-rigid Touch Layer 31 redistributes the applied forced 34 such that all force 34 is distributed only to the sensing elements 26 in the Active Sensing Array 20. The focusing is accomplished at the contact points at the protrusion 30 on the Integrated Protrusion and Base Layer 42 and the active sensing area 27 corresponding to a sensing element 26 on the active sensing array 20, as seen in FIG. 20.

In one embodiment, the outer non conductive surface substrate 22 of the sensor surface 21 of the Active Sensing Array 20, which can be made of thin acetate which can, in one implementation, be 5 mils in thickness, together with the conductive trace lines 23 which are printed on the inner face of the non-conductive surface substrate 22. FSR material 24 is printed over the conducting lines of the inner face of the outer surface sheet 21 of the Active Sensing Array 20 and the conducting lines of the outer face of the inner sensor surface sheet 21 of the Active Sensing Array 20. In operation, these two FSR material 24 components are in contact with each other, but are not mechanically affixed to each other. The inner non conductive surface substrate 22 of the inner sensor surface sheet 21 of the Active Sensing Array 20, which can be made of thin acetate which can, is, in one implementation, 5 mils in thickness, together with the conductive trace lines 23 which is printed on the outer face of their non-conductive surface substrate 22.

The Integrated Protrusion and Base Layer 42 contain the protrusions 30. Its purpose as the base of the pressure tile 2 is to provide the protrusions 30 so that the force applied to the Semi-Rigid Touch Layer 31 only to the active area of the corresponding sensing element 27 on the Active Sensing Array 20.

#### Interpolation Involving a Plurality of Pressure Tiles 2

With a networked tile assembly 18 of adjacent pressure tiles 2, the Semi-Rigid Touch Layer 31 can consist of a single uninterrupted sheet of semi-rigid material (such as thin semi-rigid plastic), which covers all of the pressure tiles 2 in the grid of pressure tiles 2. This has the advantage that the mechanical interpolation process of neighboring sensing elements 30 in the Active Sensing Array 20 Layer of different adjoining pressure tiles 2 is identical with the mechanical interpolation process of neighboring sensing elements 30 within each individual pressure tile 2. The effect from the user's perspective is an interpolating touch response that is

exactly equivalent to the interpolating touch response of a single extremely large pressure tile 2.

Note that in this arrangement, there is no need for exact registration between the Semi-Rigid Touch Layer 31 and the individual pressure tiles 2, since the Semi-Rigid Touch Layer 31 itself can be a featureless and uniform sheet of material.

The nearby protrusions 30 and corresponding sensing elements 26 do not need to be on the same pressure tile 2, but rather can be on adjacent, mechanically separate, tiles, as in FIG. 122.

In one implementation, as seen in FIG. 122, the semi-rigid Touch Layer 31 spans the totality of pressure tiles 2. Pressure applied in a region between two pressure tiles 2 transmit force to the nearby supporting protrusions 30 on two adjacent but mechanically distinct pressure tiles, and thence to sensing elements 30 of the Active Sensing Arrays 20 within two distinct pressure tiles.

When pressure tiles are adjacent, such as a in a Network Tile Assembly 18, the Semi-Ridged Touch Layer 31 will span the totality of the surface, overlapping all the spaces between the underlying pressure tiles 2. As long as adjacent pressure tiles 2 are properly registered so that the distance between protrusions 30 on each pressure tile 2 is maintained across adjacent pressure tiles 2, then the interpolating force distribution across adjacent sensor tiles will be identical to that within a single pressure tile 2. In one embodiment, pressure tile 2 registration can be accomplished by having alignment brackets on each individual sensor tile as seen in FIGS. 41, 41A, 42B.

#### Three Cases of Interpolation:

1) FIG. 25 shows a region 69 where force would be distributed to four protrusions 30 on the same pressure tile 2.

2) FIG. 26 shows a region 69 where force would be distributed to two protrusions 30 on each of two adjacent pressure tiles 2. Pressure applied in a region on the edge where two pressure tiles 2 meet transmits force to the nearby supporting protrusions 30 on the two adjacent but mechanically distinct pressure tiles 2 and thence to pressure senses of the Active Sensing Arrays 20 of two pressure tiles 2. The uninterrupted Semi-Rigid Touch Layer 31 spans the two pressure tiles 2. Pressure applied along the edge of the adjacent pressure tile 2 will distribute the force to the four sensing elements 26 (two on each respective pressure tile 2) in the same manner as if those sensing elements 26 had been on the same tile. The interpolation methods can then treat the pressure values across adjacent pressure tiles 2 as if it were a coherent larger 'image'.

3) FIG. 27 shows a region where force 69 would be distributed to one protrusion 30 on each of four adjacent pressure tiles 2. Pressure applied in a region at the corner 125 where four pressure tiles 2 meet transmit force to the nearby supporting protrusions 30 on the four adjacent but mechanically distinct pressure tiles 2 and thence to pressure sensitive sensing elements 30 where conductive trace lines 23 intersect on the Active Sensing Arrays 20 of four distinct pressure tiles 2, as seen in FIG. 27. The uninterrupted Semi-Rigid Touch Layer 31 spans the four pressure tiles 2. Pressure applied at the corner 125 of these adjacent pressure tiles 2 will distribute the applied force to those four sensing elements 26 (one on each respective sensor tile) in the same manner as if the sensing elements 26 had been on the same pressure tile 2. The interpolation methods can then treat the pressure values across adjacent pressure tiles 2 as if it were a part of a single coherent larger 'image' of pressure.

The term 'image of pressure' is used here to denote a two dimensional array of pressure values. The image generated by the current invention is antialiased, as per the commonly



41

accepted definition of the term ‘antialiased’, in that pressure imparted in any area-variant pattern to the outside surface of the Semi-Rigid Touch Layer **31** is converted by the plurality of pressure tiles into a band-limited representation of the original area-variant pressure pattern that is faithful to the original pattern for all spatial frequencies lower than an upper bounding frequency that is determined by the grid resolution of each tile’s Active Sensing Array **20**.

The Integrated Protrusion and Base Layer **42** can be a single mechanical component, which can be made of plastic, glass, wood, metal, or any other semi-rigid material. This component can be manufactured by a variety of standard methods, including injection molding, stamping, and cold casting.

In an alternate embodiment, a rapid prototype for the Integrated Protrusion and Base Layer **42** may be manufactured via SLA methods. In one method of manufacture, a mold, which can consist of silicone rubber, may be made from this prototype. Resin may be poured into the mold. When the resin hardens, the mold is removed, and the resin forms a functional Integrated Protrusion and Base Layer **42**.

Advantages of protrusions **30** being underneath: Integrating the protrusions **30** with the pressure tile **2** into a single mechanical part makes it easier to register the positions of multiple pressure tiles **2**. Registering the positions across pressure tiles **2** is important in effecting an interpolation scheme that behaves the same across a plurality of pressure tiles **2** as it does within a single pressure tile **2**. By making the support layer **32** that contains the protrusions **30** an integral part of the sensor tile, registering protrusions **30** across sensor tiles is accomplished by just mechanically attaching each pressure tile **2** to its neighbors.

In one implementation, the Integrated Protrusion and Base Layer **42** would be made of injection molded plastic or cast resin from a silicone rubber mold, and would consist of a 12"×12" rectangular base with a grid of 32×32 upward facing protrusions **30** with spacing between the centers of the protrusions of  $\frac{3}{8}$ " (corresponding to the inter-sensing element spacing of Active Sensing Array **20**) and the height of the protrusions would be 2 mm.

In one implementation of the Integrated Protrusion and Base Layer **42**, as seen in FIG. **33** and FIG. **34**, the base would be molded with a cavity on its inner face, to house the pressure tile’s **2** Printed Circuit Board **4**, as shown in FIG. **33** and FIG. **34**. Channels would also be molded into the Integrated Protrusion and Base Layer **42** to support Tile Connection Cables **17**.

In another implementation, the Integrated Protrusion and Base Layer **42** face opposite the protrusions **30** may be flat. This flat side may be mounted onto a separate support layer **32** such as a  $\frac{1}{4}$ " thick sheet of acrylic with a cavity cut on inner face to house the sensor tile’s Printed Circuit Board **4**. Channels would also be cut into the Base Layer **32** to support Tile Connection Cables **10**. In this implementation, the shape of the Integrated Protrusion and Base Layer **42** part would have a flat bottom as in FIG. **32**, but laying upon a base layer **32** with the cavity in it.

If the pressure tile’s **2** Printed Circuit Board **4** is located underneath the device, then the Active Sensing Array **20** must be wrapped around the Integrated Protrusion and Base Layer **42**. When the Active Sensing Array **20** is wrapped too tightly around the Integrated Protrusion and Base Layer **42**, then unwanted force will be applied to protrusions **30**, and therefore to sensing elements **26**, near the edge of the Integrated Protrusion and Base Layer **42**. If the Active Sensing Array **20** is wrapped too loosely, then it can bow up and cause a loss of sensitivity at those sensing elements **26**. In order to prevent

42

these situations, adhesive **40** can be placed on both the protrusion **30** side and the Semi Rigid Touch Layer **31** side of the Active Sensing Array **20**.

In one implementation of the Integrated Protrusion and Base Layer **42**, which was made using standard rapid prototyping techniques, the protrusions **30** are made of ABS plastic and are each 2 mm in height and 4 mm wide at their base, with spacing between adjacent protrusion centers of  $\frac{3}{8}$ ".

The height, shape and curvature at the peak of the protrusions **30** may vary based upon the application of the pressure tile **2**. The shape of the protrusion **30** may affect the spread of force onto the active area of the sensing element **27** and durability of the apparatus.

In one implementation, as seen in FIG. **28** showing tall/narrow protrusions, each protrusion **30** may be longer than it is wide, with a rounded tip, such as a paraboloid shape with a diameter at its base of 4 mm and a height of 4 mm. This configuration focuses the force into a small area of the sensing element **26** with which the protrusion **30** is in contact, thereby giving the greatest sensitivity. Such a configuration is preferred for creating a pressure tile **2** that is sensitive to very light pressures, but is less preferred for sharp or heavy touches because high pressures may result in damage to the Active Sensing Array **20**.

In another implementation, as seen in FIG. **29**, the protrusions **30** may be hemispherical such as with a diameter at the base of 4 mm and a height of 2 mm. This shape has the benefit of providing greater mechanical strength, while also keeping the curve at the top of the protrusion **30** gradual thereby reducing the danger of mechanical damage to the Active Sensing Array **20** during very high pressure loads.

In another implementation, as seen in FIG. **30**, the protrusions **30** may have a paraboloid or sinusoidal shape that is much wider, such as a paraboloid with a diameter at its base of 4 mm and a height of 1 mm. This retains most of the advantages of a hemisphere shape while providing the benefit of being easier to fabricate using less expensive casting methods than a hemispherical protrusion since a paraboloid or similar shape does not have a vertically intersecting wall at its base.

In another implementation, as seen in FIG. **31**, the protrusions **30** may be very wide, with a paraboloid or sinusoidal shape, such as a paraboloid with a diameter at its base of 8 mm and a height of 2 mm. This configuration results in a very gradual curve at the top of the protrusion **30**, thereby minimizing the chance of damage to the sensor array when sharp or heavy pressure is applied.

#### Single Tile Assembly **48**

In one single tile assembly **48** embodiment, a single pressure tile **2** may be directly connected to a computer and does not require a master printed circuit board **19**, though a distinct or integrated Host communication Printed Circuit **38** is needed. Such an embodiment is assembled, as seen in FIG. **32** and FIG. **33**, with the flexible Active Sensing Array **20** wrapped around the edge of the tile, and plugged into the Tile Printed Circuit Board **4** which is affixed to the underside of the Integrated Protrusion and Base Layer **42**. The Semi-Rigid Touch Layer **31** sits on top of the Active Sensing Array **20**. In the single tile embodiment the Microcontroller **5** on the Tile Printed Circuit Board **4** can perform both the scanning and Host Communication, such as USB via a USB cable **9** with the computer **3**, as seen in FIG. **35**.

Networked Tile Assembly **18** of a Plurality of Pressure Tiles **2**:

In one multiple tile embodiment, slave tiles **12** may be daisy chained to a master tile **7** or master printed circuit board **19** which may have integrated or separate Host communica-



tion circuitry **95** which is connected to a computer **3**. Such an embodiment is assembled seen in FIG. **50** with series of slave tiles **12** connected to a Master Printed Circuit Board **19**, allowing for a master/slave bus protocol for getting pressure data from the series of slave tiles. The Semi-Rigid Touch Layer **31** spans the slave tiles **11**, on top of their respective individual Active Sensing Arrays **20**. The Microcontroller **5** on the Master Printed Circuit Board **19** gathers data from the slave tiles **11** and transmit that data to the Host Communication Circuitry **95** which transmit the data via a USB transceiver **30** via the USB cable **9** with the computer **3**.

#### Pressure Sensitivity

To test the pressure sensitivity of two prototypes, a 5 g base which rests on four points was placed on top of the semi-rigid touch layer **31** with each point above a sensing element **26**. 5 g weights were placed on the base to create weights from 5 g to 100 g. Each sensing element **26** received a quarter of this weight, so the mass varied from 1.25 g to 25 g at each sense.

#### Test 1:

Touch Layer-0.5 mm Vinyl

Sensor-108 kOhm resistive ink sensor.

Protrusion layer-4 mm diameter hemispheres

Weight At Intersection	Average Value on Visualizer
5 g	0
10 g	7.5
15 g	14.5
20 g	23
25 g	32

In this implementation, masses below 10 g are not registered by the pressure tile **2**. After 10 g, the average value registered by the pressure tile **2** scaled linearly with pressure.

#### Test 2:

Touch Layer-1 mm Vinyl

Sensor-108 kOhm resistive ink sensor.

Protrusion layer-2 mm diameter truncated cones

Weight At Intersection	Average Value on Visualizer
5 g	0
10 g	0
15 g	2
20 g	17.5
25 g	25

This test used a thicker semi-rigid touch layer **31**, which makes the top layer more ridged but decreases the sensitivity. As a result, values were not registered until 15 g.

In this extension on the ideas of the above embodiments encompassing an improved technique for concentrating force to the appropriate sensing elements **26** on an Active Sensing Array **20**. In this embodiment, the touch surface lies over plates **35** spanning the sensing elements **26** such that the plate corners are aligned with the protrusions **30**. This eliminates the range of rigidity requirements of the Semi-Rigid Touch Layer **31** in the above embodiment, instead utilizing a Flexible Touch Layer **38** as this touch layer lays flat on the plates **35** which in turn focus the force onto the appropriate sensing elements **26**. As a result the Flexible Touch Layer **38** can be thin and flexible for example  $\frac{1}{10}$ th the thickness and rigidity as with the prior invention (e.g. a 5 mil sheet of PET film). Such a thin/flexible touch layer on top of plates eliminates the undesired spread along the touch layer of applied force beyond the sensing elements in the immediate proximity of that applied force.

Additionally, because the Flexible Touch Layer **38** lies flat on the plates **35**, rather than on the protrusions **30**, this embodiment allows the user to interact with the device without feeling protrusions/bumps **30** through the touch layer. Also because the Touch layer lies on a plateau of plates **35**, rather than bridging protrusions **30** as in the prior invention, the Flexible Touch layer **38** can be more tightly adhered to the plates **35**, reducing compression issues that otherwise arise. This results in a lower initial detectable touch threshold, improving detection of light touches.

This technique provides a more efficient mechanism for transmitting force from the touch layer to the sensing elements than the prior invention because all dissipation of force is done on the microscopic level rather than the macroscopic level. The above embodiments required some rigidity (described as in a 'Useful Range of Rigidity') on the touch layer since the touch layer was used to spread force to the sensing elements via a macroscopic deformation of the touch layer. In this invention there is no macroscopic movement or deformation, only microscopic deformations due to: deformation of the plate; compression of the protrusions; or and/or hinging where the plates meet each other and/or the protrusions. This results in reduced loss of pressure signal due to deformation; a higher percentage of force goes to local sensing element rather than being transmitted to further neighboring sensing elements.

The step by step description of the user experience is the same as described above for this embodiment.

#### List of All Components

A list of all hardware components.

#### List of all components

A collection of sensor tiles **2**, where

A sensor tile consists of:

Flexible Touch Layer **38**

Adhesive Layer (s) **40**

Technique: Integrated Plate and Protrusion Matrix Component

Integrated Plate and Protrusion Layer **36**

Base Layer **47**

Technique: Distinct Plate and Protrusion Matrix Components

Plate Layer **53**

Integrated Protrusion and Base Layer **42**

ALL OTHER COMPONENTS ARE AS DESCRIBED ABOVE

ALL OTHER COMPONENTS ARE AS DESCRIBED ABOVE

General Purpose of Each Layer: Integrate Plate and Protrusion Layer Embodiment

FIG. **52** shows an exploded view of a Tile for the Integrated Plate and Protrusion Matrix Component embodiment: Flexible Touch Layer **38**, Integrated Plate and Protrusion Layer (IPPL) **36**, Active Sensing Array **20**, Base Layer **47**. When the layers are placed into contact, each protrusion in the IPPL **36** is aligned to be in contact with the active area of the sensing element **27** on the outside surface of the Active Sensing Array **20**. An Adhesive Layer **40** may also be used between the Flexible Touch Layer **38** and the IPPL **36** so these layers are mechanically connected. Similarly, an Adhesive Layer **40** may also be used between the IPPL **36** and the Active Sensing Array **20**. Similarly, an Adhesive Layer **40** may also be used between the Active Sensing Array **20** and the Base Layer **47**.

This Integrated Plate and Protrusion Matrix Component embodiment of the invention pertains to a pressure sensor which utilizes a different mechanism for focusing force to the sensing elements in the active Sensing Array **20** than described earlier in this document. In this embodiment as



45

seen in exploded view and FIG. 52 in side view in FIG. 53, the Flexible Touch Layer 38 which is in contact with the Integrated Plate and Protrusion Layer 36 which is in contact with the Active Sensing Array 20; which is in contact with the Base Layer 47. Each protrusion 30 in the IPPL 36 is aligned to contact the corresponding active area of a sensing element 27 on outside surface of the Active Sensing Array 20, as seen in FIG. 52 and FIG. 53.

The Distinct Plate Matrix and Protrusion Matrix Layers embodiment of this invention pertains to another technique shown in exploded view in FIG. 54 and in side view in FIG. 55 in which there is a Flexible Touch Layer 38, Plate Matrix Layer 53 Active Sensing Array 20, Integrated Protrusion and Base Layer 42. When the layers are placed into contact, each protrusion 30 in the Protrusion Layer 53 is aligned to contact the corresponding active area of a sensing element 27 on inner surface of the Active Sensing Array 20. Additionally, the corners of each plate 35 in the Plate Matrix Layer 53 are aligned with the corresponding protrusions 30 from the Protrusion Layer 53 on the outer surface of the active sensing array 20, where any protrusion may have up to four adjacent plate corners above it.

An Adhesive Layer 40 may also be used between the Flexible Touch Layer 38 and the Plate Matrix Layer 53 so these layers are mechanically connected. Similarly, an Adhesive Layer 40 may also be used between the Plate Matrix Layer 53 and the Active Sensing Array 20. Similarly, an Adhesive Layer 40 may also be used between the Active Sensing Array 20 and the Integrated Protrusion and Base Layer 42.

In an alternate embodiment, seen in FIG. 56, the protrusions are affixed to the active areas of sensing elements 27 on the outer surface of the Active Sensing Array 20. In this embodiment, the protrusions 30 and the Active Sensing Array 20 together form a single component of the device, the Active Sensing Array with attached Protrusions Layer 55. In operation, as seen in the exploded view in FIG. 57 the Flexible Touch Layer 38 rests atop the Plate Matrix Layer 53 which rests atop the Active Sensing Array with attached Protrusions Layer 55, which rests atop a base layer 47. When an external force is applied to the Flexible Touch Layer 38, that force is then imparted to the Plates Matrix Layer 53, which redistributes the force that that it becomes concentrated at the corners of the plates 35, from which it is then imparted to the Protrusions 30, thereby compressing each active sensor 26 between the affixed Protrusion 30 and the base layer 47 upon which the Active Sensing Array 20 lies atop.

Glossary of Terms and Description of Components for this Embodiment

Active Sensing Array (ASA): Described Above

Sensing element 26: is at the location between the two Surface Sheets 21 of the Active Sensing Array 20 where Conductive Trace Lines 23 cross, and at which two areas of FSR 24 are sandwiched together and that pressure may be electrically measured, as seen in FIG. 10 and FIG. 11. The sensing element 26 is the area where there is an overlap of the FSR on those two layers at a junction of intersecting Trace Lines 23 as seen in FIGS. 9 and 10.

In Contact with a Sensing element: The Active Area of a Sensing element 27 is the area on either side of the Active Sensing Array 20 corresponding to the overlap of the FSR material for that sensing element as seen in FIGS. 10 and 11. In particular, a protrusion 30 is said to be in contact with a sensing element 26 if the surface of the protrusion in contact with the Active Sensing Array 20 lies completely upon or inside of the Active Area 27 of that sensing element. A protrusion 30 is properly aligned with the sensing element 26 if it is in contact with the sensing element (as just defined).

46

Plate 35: a rectangular piece of plastic, metal, wood, glass, or other such material that has a Valid Amount of Plate Rigidity (relative to the protrusion heights, both defined below). The plate 35 is of a size and shape such that when it is positioned, the corners are aligned inside of the four adjacent sensing elements 26 on the Active Sensing Array 20. Plates 35 are arranged in a Plate Matrix 39 which may be a constituent of an Integrated Plate and Protrusion Layer (IPPL) 36 or part of a Plate Matrix Layer 53. FIG. 59 and shows a plate 35 properly aligned upon the Active Sensing Array 20. FIG. 60 shows the top view of Rigid Plate 35 properly aligned, and inside of corresponding sensing elements 26 on the Active Sensing array 20.

Plate Matrix 39: A plurality of Rigid Plates 35 spatially aligned such that there is a gap between the Rigid Plates 35 and that the center of the gap between the corners is aligned to correspond with a sensing element 26 on an Active Sensing Array 20. A Plate Matrix 39 may be a constituent of an Integrated Plate and Protrusion Layer (IPPL) 36 or of a Plate Matrix Layer 53. FIG. 61A shows the top view and FIG. 61B the side view of a Plate Matrix 39. FIG. 63 shows the proper alignment of the plate matrix 39 superimposed above the Active Sensing Array 20.

Protrusion 30: a rigid bump of plastic, metal, wood, glass, or other such material that is positioned above or below a sensing element 26 on the Active Sensing Array 20 of that sensing element and whose purpose is to focus force onto the active area 27 of that single sensing element 26. The side of the protrusion facing the Active Sensing Array 20 must be a shape whose contact with the Active Area of its corresponding sensing element would lie exactly upon or inside of the Active Area of that Sensing element 27. Protrusions are arranged in a Protrusion Matrix 43 which may be a constituent of an Integrated Plate and Protrusion Layer (IPPL) 36 or part of an Integrated Protrusion and Base Layer 42.

FIG. 64 shows the top view of a protrusion 30 properly aligned upon the corresponding sensing element 26 on the Active Sensing array 20.

FIGS. 65A-65F shows the side view of six examples of contact between protrusions 30 and active area of sensing element 27. In FIGS. 65A, 65B, 65C, and 65D, examples are shown of protrusions 30 whose contact with the active area of its corresponding sensing element 27 lies exactly upon or inside of that active area 27. In FIGS. 65E and 65F, the protrusions 30 have contact that extend beyond the active area 27 of the corresponding sensing elements 26 and thus are not appropriate protrusion configurations for this invention. In the case in FIG. 65D, the protrusion 30 above that sensing element has discontinuous aspects such that each of these aspects might be attached to different plates that meet at that sensing element 26.

Protrusion Matrix 43: A plurality of Protrusions 30 spatially aligned to correspond with the sensing elements 26 on an Active Sensing Array 20. A Protrusion Matrix 43 may be a constituent of an Integrated Plate and Protrusion Layer (IPPL) 36 or of an Integrated Protrusion and Base Layer 42. FIG. 62A shows the top view and FIG. 62B shows the side view of a Protrusion Matrix 43.

FIGS. 61A, 61B, 62A and 62B are drawn a juxtaposed as a Plate Matrix 39 and a Protrusion Matrix 43 respectively would be aligned with each other.

FIG. 66A shows the Bottom View. FIG. 66B shows the Side View, and FIG. 66C, shows the Top View Top of the superposition of a properly aligned Plate Matrix 39 and Protrusion Matrix 43.

FIG. 67 shows a Cut out view of the superposition of a properly aligned Plate Matrix 53 and Protrusion Matrix 43.



Outer and Inner Directions/Side/Face: A sensor may be placed on a table, wall, ceiling or moving object. As a result, referring to top/bottom or up/down is ambiguous. For clarity, use 'Outer' to designate the side/direction/face upon which the force is being applied and 'Inner' to designate the opposite side/direction (towards the base of the apparatus). For example in the FIG. 68A showing the device as it would be oriented on a flat surface and 68B showing the device as it would be oriented on a wall, the imposed force 34 is applied to the outer face of the Flexible Touch Layer 38. Similarly, the inner face of the protrusions in the IPPL 36 rest on the outer face of the Active Sensing Array 20 such that the inner face of the protrusions 30 are aligned with the sensing elements 26 on the Active Sensing Array 20. The inner face of the Active Sensing Array rests upon the outer face of the base layer 47. In FIGS. 68A and 68B the Outer Direction 28 and Inner Direction 29 are designated with arrows. In any cases of ambiguity, the canonical orientation is with the sensor placed on a flat surface parallel to the floor, such as on a table top with the force coming from above, as in FIG. 68A.

Integrated Plate and Protrusion Layer (IPPL) 36: A part containing both a Plate Matrix 53 and a Protrusion Matrix 43, such that the protrusions are physically connected to adjacent plates on the inner surface. The protrusions 30 extend beyond the inner surface and are spatially aligned to correspond with the sensing elements 26 on an Active Sensing Array 20. This part may be made of plastic, metal, wood, glass, or other such material that is rigid or semi-rigid. Methods for fabrication of this are described below. FIG. 69 shows an embodiment of an Integrated Plate and Protrusion Layer 36.

In various embodiments, the Integrated Plate and Protrusion Layer 36 may have some of the shapes depicted in FIGS. 70-73. In all of these embodiments, there are slits between the plates, but the shapes of the protrusions 30 vary; the width of the slit may vary as seen comparing FIG. 70 and FIG. 73; the protrusion may continue through the junction to be flush with the plate as seen comparing FIG. 70 and FIG. 71; or may be tapered/trapezoidal towards the inner face of the protrusion as seen comparing FIG. 70 and FIG. 72. FIG. 74 shows a top view corresponding to the FIG. 70 or FIG. 72 embodiment with slits. FIG. 75 shows a top view corresponding to the FIG. 71 embodiment with protrusions continuing to be flush with the plates. FIG. 76 shows a top view corresponding to FIG. 73 embodiment which has a wider slit than the embodiments shown in FIG. 70 and FIG. 74. In each of the embodiments shown in FIG. 74-76, the slit along the edges of the plates, but not at the protrusions, go completely through the material.

Corner Protrusion 54: In one embodiment, the protrusion 30 over a sensing element 26 on the Active Sensing Array 20 may contain several discontinuous aspects with each discontinuous aspect attached at the corner of one of the several plates 35 meeting at that sensing element 26 and over that sensing element 26. A Corner Protrusion 54 is defined as one of these discontinuous aspects. With Rectangular plates meeting at a sensing element, up to four Corner Protrusions 54 may impart force, acting collectively as the protrusion 30, upon that sensing element 26 as seen in FIGS. 77A-77C, 79, and 80.

FIGS. 77A-77C shows examples of one, two and three corner protrusions 54, respectively, lying above the active area 27 of a marked sensing element 26. In each of these examples, the set of corner protrusions 54 together would be considered the 'protrusion' 30 above that sensing element 26.

In another embodiment of the IPPL 36, such as the one described below using compression molding, protrusions 30 may each consist of a set of corner protrusions 54. In this embodiment, the outer surface of the IPPL would be flat,

designated as a Flat Top Integrated Plate and Protrusion Layer 41, allowing, in the case of a single tile sensor, the Flat top IPPL 41 to also function as the Flexible Touch Layer 38.

FIG. 78 shows the Side view of Flat Top IPPL 41 embodiment with plates 35 having Corner Protrusions 54 and the outer surface being flat. Protrusions 30 where corners of plates meet will consist of sets of Corner Protrusions 54 from different plates 35. In this embodiment the surface is flat with a thin amount of additional material connecting the separate plates, as seen in the in FIG. 78 and in outer view in FIG. 79 and in inner view in FIG. 80. Unlike the embodiments seen in FIGS. 70-76, the slits do not continue through between the plates, but instead form grooves from the inner face as seen in FIGS. 78-80. In such an embodiment, the thickness of such connecting material (between the outer face and the inner edge of the groove) must respect the requirements for a flexible touch layer 38. For example, for a 1 mm thick plate of ABS plastic, and 0.1 mm for the connecting material.

In embodiments of a Flat Top Integrated Plate and Protrusion Layer 41, either a shared coherent protrusion or a set of corner protrusions may be used (as shown in FIGS. 78-80, corresponding to each sensing element).

Plate Matrix Layer 53: A part containing a plurality of Rigid Plates 35 such that the plates are connected either with a thin flexible top or bottom material or with material in the grooves between the rigid plates. Unlike the IPPL 36, the protrusions 30 are not part of this component. This part may be made of plastic, metal, wood, glass, or other such material containing methods for fabrication of this are described below. FIG. 81 shows a Flat Top Plate Matrix Layer 116 embodiment of a Plate Matrix Layer 53 with thin flexible top material whose construction similar to the Flat Top IPPL 41 but without the protrusions that would be found in the Flat Top IPPL.

Integrated Protrusion and Base Layer 42: A part containing a Protrusion Matrix 43 and a supporting base 47, such that the protrusions are physically connected to base 47 on the inner surface, as seen in FIG. 82. This part may be made of plastic, metal, wood, glass, or other such material that is rigid or semi-rigid. Methods for fabrication of this are described below. In earlier embodiments described in this patent, such as the one shown and described from FIG. 19, are examples containing an Integrated Protrusion and Base Layer.

Three cases are shown in which the plate is, respectively: Sufficiently rigid shown in FIG. 83; sufficiently semi-rigid shown in FIG. 84; and insufficiently rigid allowing force to be transmitted to the base rather than the protrusions shown in FIG. 85. In each case, the externally imposed force 34 upon the plate 35 is transmitted to different locations on the base layer 47 as the depicted transmitted force 56. FIG. 83 and FIG. 84 represent "Valid Amount of Plate Rigidity relative to the Protrusion Heights", with the transmitted force 56 being focused exclusively through the protrusions 30 to the base layer 47. In FIG. 85, the plate 35 does not have a Valid Amount of Plate Rigidity relative to the Protrusion Heights because it deforms such that some force 56 is imparted on the underlying base surface in a region not through a protrusion 30. Comparing FIG. 83 and FIG. 21 shows an advantage of the embodiment involving plates 35. Unlike the embodiment shown in FIG. 21 with a Semi-Rigid touch layer 31, the plate 35 can be rigid force is not transmitted to protrusions that it is directly above.

Valid Amount of Plate Rigidity relative to the Protrusion Heights: A plate has a "Valid Amount of Plate Rigidity relative to the Protrusion heights" if an externally applied force of the outer face a plate were to result in pressure being applied exclusively to the corresponding protrusions at its corners, in



particular no force is imparted to the surface between the protrusions; The Plate 35 would not have a Valid Amount of Plate Rigidity if the same externally applied force were to cause the Plate 35 to deform to sufficient extent that the Plate 35 would physically come into contact with the region of the Base Layer between those four protrusions 30, thereby dissipating force onto inactive regions of the Active Sensing Array 20. This unacceptable case can be seen in FIG. 85 where the plate 35 deforms in the middle in an arc the full height of the protrusion 30 allowing the plate to touch the base. For example, in the case where the protrusions are spaced at 12 mm, a 0.5 mm thick rectangular piece of rubber would not have a valid amount of plate rigidity to serve a Plate. The distance of the deformation of the plate materials can be described by  $E(\text{bend})=L^3F/(4wh^3d)$ , where L is the length, w and h are the width and height, F is the applies force and d is the deflection to the load on the surface.

Flexible Touch Layer 38: This is the outer most layer that is exposed to the user for direct contact/touch. It is comprised of a thin flexible sheet of material (e.g., rubber, Teflon, or low density polyethylene.) It must be sufficiently flexible (i.e., having a Young's modulus and thickness such that the stiffness is an order of magnitude less than that of the plates—the stiffness of most materials is determined largely by the product of the materials Young's Modulus [constant to the material] and the cube of the material's thickness as in the equation below, such that force applied to the surface is primarily transmitted to the plates below the force. In one embodiment, it could be made of 0.005" polyester film.

The stiffness of a material may be computed as per:  $D=Eh^3/(12*(1-\nu^2))$ , where E=Young's Modulus; h=material thickness; D=stiffness;  $\nu$ =Poisson's Constant of the material.

The total size and shape of the Flexible Touch Layer 38 can be made so as to match the total size and shape of the networked grid of sensor tiles.

Base Layer 47: This inner most layer is a flat featureless sheet lying below the rest of the assembly. In an embodiment where the apparatus 1 will lie flat against a flat solid surface, such as a 3" thick flat glass table, the base layer does not necessarily need to provide rigid support as this will be provided by, for example, the table. In an embodiment of an apparatus 1 that would not lay flat on a surface, or on a surface that is not solid, such as a mattress, it would need to be rigid, such as a 1/4" thick acrylic sheet.

Adhesive Layer 40: An adhesive layer may be used to affix the respectively abutting functional layers. In one embodiment, the adhesive layer could be a double sided adhesive film sheet, such as Graphix Double Tack Mounting Film. In other embodiments a spray adhesive may act as the Adhesive layer used to bond these layers.

Step by Step Description of Internal Working:

FIG. 86 shows a cross section of Force Distribution: Flexible Touch Layer 38, Integrated Plate and Protrusion Layer 36, Active Sensing Array 20, Base layer 47, Externally applied touch force 34. The IPPL 36 contains Plates 35 and Protrusions 30. The Protrusions 30 are aligned with the sensing elements 26 on the Active Sensing Array 20.

Internal operation begins when fingers or other objects impose downward force 34 upon outer surface of the Flexible Touch Layer 38, as seen in FIG. 86.

This force is then transmitted through the Flexible Touch Layer 38 to the Plate 35 underneath the force 34 in the Integrated Plate and Protrusion Layer 36.

The respective downward force 34 on each plate 35 of the IPPL 36 is redistributed to the protrusions 30 in the IPPL 36 that are under the plate's 35 respective four corners. The protrusion at any corner of a Plate 35 is shared by up to three

other adjacent plates 35. In the case where force is concurrently applied to adjacent plates 35, the combined force from those adjacent plates 35 are concentrated onto respective shared protrusions 30 and measured at the sensing element 26 that this shared protrusion 30 is in contact with.

Each protrusion 30 at the four corners of a rigid plate 35 is aligned above a respective sensing element 26 on the Active Sensing array 20, concentrating the force applied to each rigid plate 35 to the active area of the sensing elements 27 at the plate's corresponding four corners.

This creates a concentration of force that is transmitted to the portion of the Active Sensing Array 20 where each protrusion 30 is in contact with a corresponding sensing element 26, thereby creating a force that compresses together the two areas of FSR material 24 in mutual contact at the regions of the Active Sensing Array 20 that comprise the sensing elements 26 (where one FSR 24 region on the outer conducting line of 23 the Active Sensing Array 20 is in contact with a corresponding region of FSR material 24 on the inner conducting line 23 of the Active Sensing Array 20 as seen in FIGS. 10 and 11).

As described earlier, this compression creates an increase of electrical conductance between those two areas of FSR material in mutual contact. As the sensor's micro-controller scans through the Active Sensing Array's array of sensing elements, each of those changes in conductance is measured as a change in voltage, which the micro-controller detects via an A/D converter that the micro-controller then encodes as a digital signal. The micro-controller then sends this digital signal through the USB to the host computer.

This configuration of components forms a mechanism for even force redistribution from the Plates to the sensing elements on the Active Sensing Array whereby a continuous change in position of a touch on the outer face of the Flexible Touch Layer results in a corresponding continuous change in the relative force applied to those sensing elements that are nearest to that touch. Those relative forces, when sent to the host computer as part of the data image, permit the host computer to accurately reconstruct the centroid position of the touch through arithmetic interpolation.

FIG. 87 shows a schematic view of interpolation: All externally applied downward force 34 impinging upon the Flexible Touch Layer 38 is transmitted to the plate 35 in the IPPL 36 abutting that force. The force 34 on that plate 35 will be focused on the 2x2 nearest protrusions 30 on the IPPL 36. Therefore in the Active Sensing Array layer 20 all of the force will be concentrated on the 2x2 corresponding active areas 27 for the where there is direct mechanical contact with these four protrusions 30 and thus mechanically distributed to the respective sensing elements 26.

The difference between this process using plates 35 and a flexible touch layer 38 and the similar process that was described without plates but with a semi-rigid touch layer 31 is that by allowing for a thinner Touch Surface 38 and distinct plates 35 under that touch surface, the local forces on the Flexible Touch Layer 38 are nearly exclusively conveyed to the plates 35 under that force and then transmitted through the corresponding protrusions 30 onto the appropriate sensing elements 26. Additionally in this Active Sensing Array 20 is affixed onto a flat surface and thus cannot deform as might occur in the method without plates.

The electronic measurement and processing of the force upon the Active Sensing Array is identical to that in the method without plates.

FIG. 52 shows an exploded view of the Layers and Assembly in the prototype single tile embodiment using an Integrated Plate and Protrusion Layer (IPPL) with Flexible Touch



## 51

Layer 38; Integrated Plate and Protrusion Layer 36; Active Sensing Array, 20; Base Layer 47. When the layers are placed into contact, each protrusion 30 in the IPPL 36 is aligned to be in contact its corresponding active sensing area 27 on the outside surface of the Active Sensing Array 20. An Adhesive Layer 40 was used between each of the above layers in this prototype embodiment.

Flexible Touch Layer 38: 5 mil Polyester Film

Integrated Plate and Protrusion Layer 36: 31-31 grid of plates with 32x32 grid of protrusions. A Custom SLA (Stereolithography) Rapid Prototyped part manufactured with Somos 11122 (Clear PC Like) created with a supplied CAD file with the IPPL 36 Geometry using standard SLA manufacturing.

FIG. 88 shows the plate and protrusion dimensions used in the prototype embodiment of the Integrated Plate and Protrusion Layer 36 in a cross section view. The plates 35 and protrusions 30 are square, so these dimensions are the same for both the width and length (not drawn to scale).

Note: In a single tile assembly there are  $(N-1) \times (M-1)$  plates for an  $N \times M$  grid of protrusions for an  $N \times M$  Active Sensing Array because there is no need for a spanning plate between abutting tiles. For example in FIG. 52, a 4x4 grid of plates are supported by a 5x5 grid of protrusions and used with an Active Sensing Array with a 5x5 grid of sensing elements.

Active Sensing Array 20: Custom printed sensor, as per description in the other earlier described embodiments, with a 32x32 grid of sensing elements spaced at  $\frac{3}{8}$ ". Each sensing element has a 4x4 mm overlapping FSR area. 100 kOhm FSR Ink was used in the ASA.

Base Layer 47: CPVC Sheet,  $\frac{1}{32}$ " Thick. Note that this embodiment was one in which it was expected that the apparatus would be placed on a solid table top for use as in the embodiment of the Base layer where the apparatus 1 will lie flat against a flat solid surface.

Adhesive Layer 40: Graphix Double Tack Mounting Film. Three adhesive layers 40 are used in this assembly.

In this prototype assembly,

a) One side of an adhesive layer 40 is affixed to the inner surface of the Flexible Touch Layer 38.

b) The opposite side of that adhesive layer 40 is affixed to the outer surface of the IPPL 36.

c) One side of a second adhesive layer 40 is affixed to the outer surface of the Active sensing array 20.

d) The opposite side of that adhesive layer 40 is affixed to the inner surface of the IPPL 36 such that the protrusions 30 on the IPPL 36 are aligned with the corresponding sensing elements 26 on the Active Sensing Array 20.

e) One side of a third adhesive layer 40 is affixed to the inner surface of the Active Sensing Array 20.

f) The opposite side of that adhesive layer 40 is affixed to the outer surface of the Base Layer 47.

Pressure Data for this IPPL Prototype Assembly

In the following tests, calibrated weights were placed above a wire intersection. A small rubber cylinder that weighed 5 g was used to concentrate the force at the intersection.

IPPL Sensor

Weight (g)	Value From Sensing element(*)
20	30
40	95
60	150
80	200

## 52

-continued

Weight (g)	Value From Sensing element(*)
100	260
120	320
140	340
160	380
180	410
200	425
250	480

(\*)In the prototype embodiment here, these are the values measured from the A/D circuitry of the PIC24 chip and based on voltages. The values are measured as 12-bit non-negative values.

Methods to Manufacture the Integrated Plate and Protrusion Layer

In one embodiment, a metal mold can be created for the IPPL using industry standard techniques for making molds for plastic parts. The IPPL parts can be manufactured via injection molding out of ABS plastic using standard injection mold and molding techniques.

Another way to manufacture a IPPL is to perform selective photo-etching on both sides of a sandwich that has been formed by affixing thin metal plates, such as 0.005" thick brass, to both sides of a plastic sheet, such as 0.003" thick Mylar or kapton, that has been coated with adhesive on both sides. One of the metal plates will form the plates layer, and the other will form the protrusions layer. In both cases, the parts of the metal plate that should not be etched away are covered with a pattern of photo-resist (such as a pattern of toner transferred from a laser printer). Equivalently, the plates can be formed from a standard photo-polymer such as DuPont Cyrel or BASF Nyloflex, which is first selectively cured by being exposed to a pattern of UV light, which in the standard process is in the range of 365 nm after which the unexposed portion is washed away.

Templates for the photo-resistive ink patterns of the two plates can be seen in the FIGS. 89A and 89B. FIG. 89A shows a photo-resistive ink pattern of the plates' side. FIG. 89B shows a photo-resistive ink pattern of the protrusions. In the embodiment where the plates are photo-polymer, the negative of these patterns is used.

Another method for creating an integrated plate and protrusion layer 36 part is to photoetch the surfaces of two thick flat metal plates, such as steel plates, so that they form negative relief patterns. A plastic that is soft when hot yet hard when cool is then placed between these two metal plates, preferably in the presence of a vacuum. The plates are heated and pressure is applied to force them together, thereby creating a relief pattern in the plastic, whereby the soft plastic is deformed away from the groove areas to fill the protrusion areas.

The photo-etching is done so as to create smooth slopes in the plate relief pattern, thereby facilitating the subsequent process of pressing the relief pattern into the plastic.

The arrangement of the two metal plates is shown in cross section in the FIG. 90A below. The top compression plate 57 which creates the grooves in the plastic that define the plate shapes. The bottom compression plate 58 which creates the protrusions in the plastic. FIG. 90B shows the resulting groove locations 59, and the resulting protrusion locations 60.

Another method of manufacture of the IPPL 36 is to create a single surface that has a relief structure of both plate shapes as well as protrusions on only one side, by splitting each protrusion to allow for continuous grooves between adjacent squares, as shown in profile view in the FIG. 91A.

Placing the relief structure which combines the rigid squares and the protrusions into a part that has a relief struc-



## 53

ture on only the bottom side confers the advantage that the top of this part will feel smooth to a user's touch. Specifically, this embodiment creates an Integrated Plate and Protrusion layer **36** that also includes a Flexible Touch Layer **38** as in the Flat Top Integrated Plate and Protrusion **41** embodiment part as seen/described in FIGS. **78-80**.

One method of manufacturing this relief structure is via compression molding of thermosetting plastic. In a variant of this process, the plastic to be compression molded is placed in contact with a thin (e.g. 0.003 inch thick) sheet of a flexible plastic such as mylar or kapton. After the compression and curing process of the connected part, the groove areas will essentially consist only of the flexible plastic **61**, with the rigid plastic being located in the plates **35** and protrusions **30**, as seen in FIG. **91B**. This will create the desired mechanical properties of rigid plates **35** and rigid protrusions **30**, with flexible hinging between adjoining plates along with an integrated Flexible Touch Layer **38**, as in a Flat Top IPPL **41**.

FIG. **54** shows an exploded view of the Layers and Assembly in the prototype single tile prototype embodiment using a distinct Plate Matrix Layer **53** and an Integrated Protrusion and Base Layer **42**.

with: Flexible Touch Layer **38**, Plate Matrix Layer **53**, Active Sensing Array **20**, Integrated Protrusion and Base **42**. The grid line intersections on the Active Sensing Array are the locations of the FSR sensing elements. When the layers are placed into contact, each protrusion **30** in the Protrusion Layer **42** is aligned to contact the corresponding active sensing area **27** on the inside surface of the Active Sensing Array **20**. Additionally, the corners of each plate in the Plate Matrix Layer are aligned to be above the outer active sensing area **27** on the outside surface of the active sensing array **20** opposite their corresponding protrusions. An Adhesive Layer was used between each of the above layers in this prototype.

Flexible Touch Layer **38**: 5 mil Polyester Film

Plate Matrix Layer **53**: 31×31 grid of plates. 1/32" Acrylic sheet, custom laser cut to the final shape using two passes. The first pass etching the grooves, but not cutting all the way through, at the corner junctions. A second pass cutting slits completely through the acrylic to resulting in the part designated in top view FIG. **58A** and cross section view FIG. **58B**. The dimensions used in the prototype are shown in FIG. **58A** and FIG. **58B** (not to scale) which has square plates, so these dimensions are the same for both the width and length.

Active Sensing Array **20**: Custom Sensor as per description in above embodiments with a 32×32 grid of sensing elements spaced at 3/8". Each sensing element has a 4×4 mm overlapping FSR area. 100 kOhm FSR Ink was used in the ASA.

Integrated Protrusion and Base Layer **42**: 32×32 grid of protrusions, 3/8" spacing, 4 mm diameter hemispherical protrusions. Custom SLA Rapid Prototyped part made with Somos 11122 (Clear PC Like).

Adhesive Layer(s) **40**: Graphix Double Tack Mounting Film. This has protective paper on either side of an adhesive plastic sheet.

In this prototype assembly,

a) One side of an adhesive layer **40** is affixed to the outer surface of the Plate Matrix Layer **53**, leaving the protective covering on the opposite side intact.

b) One side of second adhesive layer **40** is affixed to the inner surface of the Plate Matrix Layer **53**, leaving the protective covering on the opposite side intact.

c) Gently bend the Plate Matrix Layer **53** until all the connecting material in the notched grooves at each plate junctions have broken. This leaves a flexible sandwich with the Plate Matrix Layer **53** in between two adhesive layers and with each plate no longer rigidly attached to any other plate.

## 54

d) The Active Sensing Array **20** is affixed to the adhesive layer **40** (already in place) on inner side of the Plate Matrix Layer **53** using the opposite side of the adhesive layer **40** from step (b). The sensing elements **27** from the Active Sensing Array **20** need to be aligned with the plate junctions on the Plate Matrix Layer **53**.

e) One side of third adhesive layer **40** is affixed to the inner surface of the Active Sensing Array **20**.

f) The Integrated Protrusion and Base Layer **42** is affixed to the adhesive layer **40** (already in place) on inner side of the Active Sensing Array **20** using the opposite side of the adhesive layer **40** from step (e). The sensing elements **27** from the Active Sensing Array **20** need to be aligned with the protrusions **30** on the Protrusion Layer **42**.

g) The Flexible Touch Layer **38** is affixed to the adhesive layer **40** on outer side of the Plate Matrix Layer **53**, using the opposite side of the adhesive layer **40** from step (a).

Pressure Data for this Prototype Assembly

In the following tests, calibrated weights were placed above a wire intersection. A small rubber cylinder that weighed 5 g was used to concentrate the force at the intersection.

Prototype using distinct Plate Matrix Layer **53** and Integrated Protrusion and Base Layer **42**

Weight (g)	Value from Sensing element(*)
20	0
40	120
60	230
80	320
100	420
120	500
140	540
160	570
180	605
200	620
250	650

(\*)In the prototype embodiment here, these are the values measured from the A/D circuitry of the PIC24 chip and based on voltages. The values are measured as 12-bit non-negative values.

#### Methods to Manufacture the Plate Matrix Layer

One embodiment of the Plate Matrix Layer involves laser cutting as described above.

Other embodiments are analogous to the technique described for the Integrated Plate and Protrusion layer **36** described above but without steps/facets that create the protrusions.

#### Methods to Manufacture the Integrated Protrusion and Base Layer **42**

In one embodiment, a metal mold can be created for the Protrusion Layer using industry standard techniques for making molds for plastic parts. The Protrusion Layer parts can be manufactured via injection molding out of ABS plastic using standard injection mold and molding techniques.

#### Assembly of Sensor with a Thin Base Layer and Co-Planar PCB

FIG. **92** shows an embodiment of a single Stand Alone Tile: Flexible Touch Layer **38**; IPPL **36**; Base Layer **32**; Active Sensing Array **20**; Printed Circuit Board **4**.

The embodiment shown in FIG. **92** shows the Active Sensing Array **20** laying flat upon the Base Layer **32**, with its Connector Tails **25** connected to a co-planar Printed Circuit Board **4**. The base layer **47** in this corresponds to one described earlier where the apparatus **1** will lie flat against a flat solid surface. An advantage of this embodiment is that the entire sensor is thin. For example in the above embodiment, the entire sensor is under 3 mm.



#### Assembly Involving a Plurality of Tiles

In one embodiment using the Integrated Plate and Protrusion Layer (IPPL) technique, individual tile sensors that are part of grid of sensors are nearly identical to the single tiles described earlier, but may have an extra row and/or extra column of bridging plates 37. In particular, as seen in exploded view in FIG. 93, an individual tile with an  $N \times M$  Active Sensing Array 20 and corresponding  $N \times M$  matrix of protrusions 30 in the IPPL 36 may have an extra row and column of bridge plates 37 in the IPPL 36 resulting in an  $N \times M$  matrix of plates 35. This is unlike the single tile assembly described earlier where the IPPL 36 for such an  $N \times M$  Active Sensing Array 20, where there were an  $(N-1) \times (M-1)$  matrix of Plates 35. Note that there are no protrusions 30 on the additional corners of these extra bridging plates 37. The Flexible Touch Layer 38 will be a single continuous sheet spanning all tiles in the Grid of tiles.

An example embodiment of an Internal Tile used in a Plurality of tiles that is based upon an Active Sensing array 20 with a  $4 \times 4$  matrix of sensing elements 26 is seen in exploded view FIG. 93, top view FIG. 94, and side view 95. In this example, the IPPL 36 consisting of a  $4 \times 4$  matrix of Protrusions 30. There is a sub-matrix of  $3 \times 3$  plates 35 with protrusions at each corner and an additional, an additional row and column of bridging Plates 37 (providing seven additional plates) that have only some corners resting on protrusions. These bridging plates 37, as described later will span across to share protrusions 30 on neighboring tiles. As seen in FIG. 93 the layers include the Flexible Touch Layer 38, IPPL 36. Active Sensing Array 20 and Base Layer 47. The IPPL 36 is aligned such that its  $4 \times 4$  matrix of protrusions is in contact with the corresponding  $4 \times 4$  matrix of sensing elements 26 on the active sensing area. An Adhesive Layer 40 may also be used between each of the above layers. In this view, the additional row and column of bridging plates 37 is seen extending beyond the base layer 47, the IPPL 36, and the active sensing array 20 on two edges.

FIG. 96A and FIG. 96B shows the manner in which adjacent tiles 2 are aligned positioned such that the bridging plate rests on the corresponding protrusion on its adjacent tile. FIG. 96A shows two tiles being aligned. FIG. 96B shows the two tiles properly positioned.

In this embodiment, adjacent Tiles 2 are positioned such that the bridging plates 37 span the protrusions 30 of one tile 2 to the protrusions 30 of another tile 2. This results in an identical mechanical distribution of force to the appropriate sensing elements as for plates spanning protrusions within a tile.

In one implementation of the Base Layer 47, the base can be molded with a cavity on its bottom that could house the sensor tile's Printed Circuit Board 4, as shown in side view in FIG. 97A and from the bottom in FIG. 97B. Channels would also be molded into the base to support inter-tile cabling.

In FIG. 97B, this embodiment is seen with the Base Layer 47 has a cut-out region 62 on its underside into which the Printed Circuit Board 4 securely fits. The Active Sensing Array 20 wraps around two adjacent edges of the Base Layer 32 to electrically connect via the connector tails 23 on the Active Sensing Array 20 to the PCB 4. The IPPL 36 shows the bridging plate (not to scale). The Flexible Touch Layer 38 spans multiple tiles. FIG. 97A shows a side view. FIG. 97B shows a perspective view as seen from underneath.

In the embodiment with the sensor tile's 2 Printed Circuit Board 4 is located underneath the device, then the Active Sensing Array 20 must be wrapped around the Base Layer 20 as seen in FIGS. 98A and 98B.

FIGS. 98A and 98B shows the side view of Adjacent Tiles being aligned and positioned. FIG. 98A shows the tile being properly aligned. FIG. 98B shows the two tiles properly positioned. The Bridging Plate 37 spans protrusions 30 on different tiles 2. The respective Base Layers 47 extend only slightly beyond the last edge protrusion 30. This allows for a gap between the Base Layers 47 that allows the Active Sensing Array 20 to wrap around.

In this embodiment, a rectangular grid of  $N \times M$  tiles, such that the bridging plates span the protrusions of one tile to the protrusions of another tile results in an identical mechanical distribution of force to the appropriate sensing elements as with plates spanning protrusions on the same tile.

In one embodiment, an apparatus 1 with a grid of tiles 2 can be composed of identical interior tiles 63 and perimeter tiles (north tiles 64, east tiles 65, northeast corner tile 66). FIG. 94 and FIG. 95 show an Interior Tile that has bridging plates on its north and east edge. FIG. 99 shows the schematic of tiles being properly aligned. FIG. 100 shows the tiles in their proper positions with the bridging plates 37 resting upon protrusions 30 on adjacent tiles 2. FIG. 101 shows the tiles in their proper positions with the Bridge Plates 37 drawn transparently, exposing the Bridging plates 37 on the edge of a tile 2 spanning across pairs of protrusions 30 on two different tiles 2 and in the case of the corner Bridging Plate 37, spanning protrusions 30 on four different tiles 2.

#### Interpolation Along Bridge Plates Spanning Tiles

In this embodiment, Bridge Plates 37 span across pairs of protrusions 30 on different tiles or in the case of a corner Bridging Plate 37 spanning four protrusions 30 on four tiles. As there is no mechanical difference in the arrangement of a Bridge Plate 37 on protrusions across multiple tiles 2 and for a Plate 35 that spans four protrusions 30 on a single tile 2 regarding to the transmission of force to the respective sensing elements 26, the method of mechanical interpolation is identical for Bridge or non-Bridge Plates.

Note that in this arrangement, there is no need for exact registration between the Flexible Touch Layer 38 spanning the plurality of tiles and the individual sensor tiles, since the Flexible Touch Layer 38 itself can be a featureless and uniform sheet of material.

#### An Embodiment of Apparatus with an $N \times M$ Grid of Tiles with Symmetric Perimeter

In one embodiment there may be different types of tiles along the North and East and Northeast Corner of the grid of tiles as seen in FIG. 102. FIG. 103 shows the North Tiles 64 contain an eastern column of Bridge Plates 37; the East Tiles 65 contain a northern row of Bridge Plates 37; the NE Corner Tile 66 does not contain any bridge rows or Bridge Columns; the Interior tiles 63 contain both a northern bridge row and an eastern bridge column of Bridge Plates 35. In this embodiment for a Grid of  $N$  rows by  $M$  columns of tiles, there would be  $(N-1) \times (M-1)$  Interior tiles 63,  $N$  North Tiles 64,  $M$  East Tiles 65 and one NE Tile 66 as seen in FIG. 102.

FIGS. 103-104 show an example with a  $3 \times 3$  Grid of Tiles with their respective Interior 63, North 64, East 65, and NE 66 Corner Tiles in their appropriate position. FIG. 103 shows a schematic of these tiles being properly aligned with bridging plates being aligned with the corresponding protrusions on the adjacent tiles. FIG. 104 shows the tiles in their proper position.

In other embodiments, all tiles in a grid can be identical. One such embodiment would have an IPPL 36 with Corner Protrusions 54, as seen in FIGS. 77-80. In this case, the bridging plates would have corner protrusions 54 and these



corner protrusions **54** would rest upon the active sensing area **27** of the corresponding sensing element **26** of adjacent tiles **2**.

#### Interpolation Involving a Plurality of Sensor Tiles

This is the same as described above.

With a networked grid of adjacent sensor tiles **2**, the Flexible Touch Layer **38** can consist of a single uninterrupted thin sheet material (such as 5 mil polyester), which covers all of the sensor tiles **2** in the grid of sensor tiles. This has the advantage that the mechanical interpolation process of neighboring sensing elements in the Active Sensing Layer of different adjoining sensor tiles is identical with the mechanical interpolation process of neighboring sensing elements within each individual sensor tile. The effect from the user's perspective is an interpolating touch response that is exactly equivalent to the interpolating touch response of a single extremely large sensor tile, as described and seen above FIG. **104**. Similarly, the host computer **3**, once it has reconstructed the image from the Tile Topology Table, can treat the image from a grid of tiles as if it came from a single large sensor.

Note that in this arrangement, there is no need for exact registration between the Flexible Touch Layer and the individual sensor tiles, since the Flexible Touch Layer itself can be a featureless and uniform sheet of material.

#### Non Planar Sensors

In other embodiments, the sensing apparatus **1** may be made to fit upon a developable surface, namely one which can be flattened onto a plane without distortion such as a section of a cylinder as seen in FIG. **105** or cone as seen in FIG. **106**. Specifically developable surfaces have zero Gaussian curvature.

In one such embodiment, a sensor may be made in the form a section of a cylinder as seen in FIGS. **107-111**.

FIG. **107** shows an embodiment for an assembly for a 'Section of Cylinder' Curved Sensor shown from an inside view of the layers. In FIG. **108**, it is shown from an outside view. In FIG. **107** and FIG. **108** the layers are: Flexible Touch Layer **38**, Active Sensing Array **20**, IPPL **3** and Base Layer.

In this embodiment, both the Flexible Touch Layer **38** and Active Sensing Array **20** are flexible and can be manufactured similarly to the earlier embodiments. The IPPL **36** may be manufactured via an injection molding as described earlier such that the inner curvature along the plane of the inner faces of the protrusions has the same curvature as the outer surface of the Base Layer **32** which in turn would have its inner curvature matching the outer curvature of the cylinder. Corrections to this curvature may be made to account for the thickness of the Active Sensing Array **20**, but as the Active Sensing Array **20** is thin and the IPPL **36** somewhat flexible, this correction is not required. FIGS. **109-111** show respective views of the IPPL along the height of the cylinder; from the outside; and from the inside, respectively.

In this embodiment, the Base Layer **32** must be sufficiently rigid such that the force imparted on the Flexible Touch Layer is not absorbed by deformation. In one Embodiment, the Base Layer can be made of ABS plastic with the same inner curvature as the outer curvature of a solid metal cylinder. As seen in the FIG. **112**, such a tile **2** would have an inner curvature the same as that of the metal cylinder **67** that it is abutted against.

#### Non-Rectangular Plates

Sensors may be constructed with non-rectangular plates. For example, in one embodiment, a hexagonal plate matrix **39** as seen in FIG. **113** and corresponding hexagonal protrusion matrix **43** as seen in FIG. **114** may be used.

A Hexagonal IPPL **36** using the same manufacturing techniques as with the rectangular IPPL may be used to create such a part as seen in FIG. **115**.

In such an embodiment, an Active Sensing Array **20** with corresponding conductor line **23** spacing so that intersections match the protrusion **30** locations of the Hexagonal IPPL **36** may be made, as seen in FIG. **116**.

FIG. **117** shows the Hexagonal IPPL seen positioned upon the corresponding Active Sensing Array **20**.

In this embodiment, only intersections of grid wires that align with protrusions from the protrusion Matrix have sensing elements that are used in the mechanical interpolation.

In this embodiment, bi-linear interpolation may be applied to the six corners of the plate sensing element values.

Let the six sensors around any hexagonal plate be labeled, in clockwise order, A,B,C,D,E,F as in FIG. **118**.

One can measure proportional distances between opposite pairs of edges by the ratios:  $(A+B)/(A+B+D+E)$ ,  $(B+C)/(B+C+E+F)$ , and  $(C+D)/(C+D+F+A)$ , thereby defining three lines, each parallel to its associated pair of edges (one line parallel to AB and to DE, a second line parallel to BC and EF, and a third line parallel to CD and FA). These three lines intersect to form a small triangle in the interior of the hexagon. The centroid of this triangle can be taken as a useful approximation to the center of pressure applied to the plate.

#### Fusion

Gesture sensing via a real-time range imaging camera **100** has the following desirable properties: (1) ability to track gestures and (2) ability to maintain consistent identity over time of each finger of each hand or each part of each foot of each user or each part of each foot of each user. Yet range imaging cameras **100** cannot provide high quality detected touch **111** and pressure information, while typically operating at relatively low frame rates.

A pressure imaging apparatus **1** provides low cost, very high frame rate (greater than 100 frames per second), large area pressure imaging. The described touch-range fusion apparatus technology **104** can, in one embodiment, combine this pressure imaging apparatus **1** with a newly available generation of low cost real-time range imaging cameras **100** to simultaneously enable the advantages of both.

Specifically, a range imaging camera **100** tracks every detected touch **111** gesture by a user/hand/finger/foot/toe/pen/object, each having a unique persistent identifier, while using the pressure imaging apparatus **1** or other touch device **101** to determine positional centroid, pressure (in the case of pressure imaging apparatus **1**) and timing of each detected touch **111** with extremely high geometric fidelity and high temporal sampling rate.

#### Hardware

A Touch-Range Fusion Apparatus **104** can consist of a touch device **101**, such as pressure imaging apparatus **1**, and one or more range imaging cameras **100** devices. Pressure Imaging Apparatuses **1** are made of modular rectangular pressure tiles **2** that can be seamlessly adjoined to provide continuous pressure imaging across pressure tiles **2**. A Pressure Imaging Apparatus **1** can be made in a variety of sizes. Three embodiments include a small device with a 12.5"×17" form factor, a medium device with a 25"×34" form factor, and a large device with a 50"×68" form factor.

These three form factors describe the most commonly found finger and pen input non-mobile devices. The small form factor is well suited for a single user, with sufficient space to use both hands concurrently. The small form factor can be seen in such devices as the Wacom Intuous 4 Extra Large and is comparable in size to an average desktop display [8]. The medium form factor can be more easily used by multiple participants and is the size of many interactive tabletop surfaces. For example, the Microsoft Surface and Diamond Touch are approximately the same size and dimensions



as the medium form factor example [9,10]. The large form factor is primarily seen in collaborative interactions between many users at whiteboards as well as for floor sensors that can track the time-varying pressure across a surface induced by users' feet movements. SMART Electronics produces interactive whiteboards with comparable sizes [11].

One embodiment of a range imaging camera **100** contains a IR Range Camera **106** and, optionally, an RGB camera **103**. Tracking of object features is done primarily from range data. The RGB camera **103** can be used for assisting in identifying objects in the 3D space, while also providing useful visual feedback to users of the device.

FIG. **122**, FIG. **132** and FIG. **133** show three different possible placements for range imaging cameras **100** for desks/tables/walls, and FIG. **128** shows a possible placement appropriate for floors.

In one implementation, one or more range imaging cameras **100** are placed in key areas around an pressure imaging apparatus **1** to achieve the most efficient and cost-effective means of accurately identifying fingers, feet, pens and objects in 3D space. The location and number of cameras are chosen so as to limit occlusion issues, and to maximize pixel/depth resolution as needed for accurately identifying features.

Identifying Fingertips, Palms, Parts of Feet, Pens and Objects in 3D Space

Using the range imaging camera **100** data, fingertips, palms of hands, parts of feet, pens and objects are identified using image analysis process algorithms such as [1], [2], [3], [4], [5], [15], [16], [22], [23] or using any other image analysis process which is standard in the art. To begin, feature extraction is performed on the data from the range imaging cameras **100**. This can be done, possibly in conjunction with supplementary information from the RGB cameras **103**, in order to extract information about shape, including lines, edges, ridges, corners, blobs and points. 3D shape recognition provides high confidence information to the feature recognition. This information is passed to machine learning algorithms, trained on various stimuli to identify hand skeleton features, finger tips, foot shape, pens and objects. Once the object has been identified, the location in 3D space of the object features is tagged. The identity and xyz position of each feature is used to determine whether a given object or feature is in contact with or off the pad when tracking blobs on the pressure imaging apparatus **1** or other touch devices **101**.

Because the Touch-Range Fusion Apparatus **104** can have more than one range imaging camera **100**, this analysis software composites the identified features from all angles in order to give a complete list of objects within the scene to the software that will perform the fusion calculation that maps identified 3D objects to detected touches **111** upon the surface.

An added benefit to identifying finger tips, pens and objects is that palms, wrists and unwanted items can be rejected when tracking objects on the touch device **101**. If an application, for instance, requires only pen input, then all other identified objects can be rejected.

Mapping Fingertips, Feet, Pens and Objects to Tactonic Device **101** Contacts

In one case, when an object touches a Pressure Imaging Apparatus **1**, an anti-aliased image of pressure is given. This pressure image is used to find the centroid **107** of a fingertip, pen or object. Each centroid **107** can be tracked continuously across the entire Pressure Imaging Apparatus **1**. This accurate centroid **107** data is used, along with the identity of objects derived from Range Imaging Camera **100** data, described above, to give each centroid **107** an identity that can persist even when that finger or object loses contact with the surface.

Alternatively to a pressure imaging apparatus, a touch device **101** can be used that tracks the centroid **107** of each detected touch **111** upon the surface, although possibly without tracking pressure.

The identity of each centroid **107** is obtained by searching through the list of identified objects and features identified in the by the Range imaging camera **100** data, as described above. If the object/feature is located near the touch device **101** plane and above the location of the centroid **107** in the X-Y position, then the centroid's **107** identity can be obtained.

Contacts made to the touch device **101** are identified and tracked continuously as objects and hands and feet move around the device. This contact data can be used for more robust tracking of persistent identity. In particular, if the identified contact becomes obscured from the range imaging cameras **100** because of occlusion, then the contact will retain its identity as long as the object remains in contact with the touch device **101**. If initial contact is made in a region that is obscured from the range imaging camera **100**, then contact identity can be made when the object/feature reveals itself to the range imaging camera **100**.

Support for Simultaneous Multi-User Collaboration

Distinguishing between individual users **109** becomes important in larger form factors when multiple participants are using a space concurrently. Each individual user **109** is identified by looking at the entrance position of the arm, the angle of the arm, and continuous tracking of individual users **109** as their arms and hands move around the visible area. Similarly each individual user **109** is identified by continually tracking the position and orientation of each participant's body, legs and feet as they walk around upon a touch device **101** floor surface. As each foot or hand and stylus moves across the touch device **101**, its individual user **109** identification is maintained.

For example, FIG. **123** shows a Left Hand **118** and Candidate Right Hand-A **119** which is within the individual user maximum reach **108**, so the two hands may belong to the same individual user **109**. Candidate Right Hand-B **120** is beyond the individual user maximum reach **108** of Left Hand **118**, so Left Hand **118** and Candidate Right Hand-B **119** must belong to different individual users **109**.

Applications Enabled by the Invention

In addition to new unique gestures available by fusing range imaging **100** and touch device **101**, existing gestures for range imaging cameras **100** and touch device **101** are also supported. Application support software maps gestures performed on the device to actions and keystrokes on the computer. Along with the control panel, applications and plug-ins that this technology supports includes musical instrument emulation, simulated surgery, simulated painting/sculpting, athletic games and activities that depend not just upon body movement but also on shifts in weight and balance, and other applications that require a combination of isotonic and isometric control can be implemented to attain the full capability.

Uses for the Invention:

Interactive Whiteboards: According to Futuresource Consulting, Ltd. market report for this sector, 900K Interactive Whiteboards were sold in 2010, up from 750K in 2009, mostly in the Education sector. A typical Interactive Whiteboard consists of a short throw projector displaying onto a large touch device **101** (for example to 6'x4'). The current models for these large format touch device **101** utilize a set of optical cameras along the perimeter to track user detected touches **111** and gestures. While that approach can provide limited multi-touch and multi-user support, it cannot identify



the user, hand or finger of detected touches **111**. Additionally, actions may be occluded by the presence of multiple hands in the camera path. Beyond the significantly greater gesture vocabulary achievable from robust hand action tracking and the added dimension of pressure, the sensor fusion approach also addresses the educational need for robust at-board multi-student interaction and collaboration.

Personal Desktop Peripheral: A personal desktop peripheral represents a generic Computer Human Interface (CHI) technology which, like the mouse or keyboard, is application blind. While many types of applications could be created to take advantage of robust gesture vocabulary, a pregnant initial application market for this desktop peripheral would be a game controller. Computer games focus on providing vivid graphical experiences with compelling game play. Computer gamers are both comfortable and fluent with user input devices that manipulate iconic representation of their character and controls while looking at the video display (and not at the input device). The Microsoft Kinect, introduced in November 2010, sold 10M units in its first 60 days, yet it does not provide the level of controlled precision or responsiveness required for many games, such as first person shooter games. Kinect provides relatively coarse positional accuracy and low camera frame rate. For instance, the Kinect has a frame rate (30 fps) that is a quarter as responsive as keystroke input scanning (125 Hz). The touch-range fusion apparatus **104** would provide a broad canvas for game control with extremely accurate control and response for surface interaction as users touch and press upon surfaces with their hands and feet.

#### List of Components

Range Imaging Camera (RIC) **100**: produces a 2D image showing the distance to points in a scene from a specific point, which is implicitly a point in 3D. There are many types of Range Imaging Cameras **100** commercially available using well established techniques such as: Stereo triangulation, Sheet of light triangulation, Structured light, Time-of-flight, Interferometry, and Coded Aperture. In one embodiment a Microsoft Kinect peripheral can be used as the Range Imaging Camera **100**. The Kinect contains a PrimeSense Range Imaging Camera **100**. There are open source APIs available to utilize this camera in the Kinect, such as OpenCV, as well as the Microsoft Kinect API. While the Kinect also has an RGB Camera **103** which can be used in conjunction with this invention, the RGB camera **103** is not used as a required component in this invention. In the Kinect Embodiment, there is a standard USB cable **9**. FIG. **124** shows a range imaging camera **100** with an IR camera **106**, a RGB Camera **103** and a USB cable **9**.

Touch Device (TD) **101**: A touch device **101** that is able to detect and track detected touches **111** on a surface. There are many well established techniques for touch devices **101** as well as a multitude of commercial devices, such as the Apple Magic Mouse. The Magic Mouse embodiment includes a standard USB cable **9**. Similarly there are ubiquitous smart phones and tablets, such as the Apple iPhone or iPad that contain Touch Devices **101**. Embodiments of touch devices **101** include those using: Resistive, Projective Capacitive, Optical, and Frustrated Total Internal Reflection (FTIR) methods of operation.

FIG. **125** shows a Touch Device **101**, such as the Apple Magic Mouse, with a (1) Touch Device **101** and (2) USB Cable **9**.

Pressure Imaging Apparatus **1**: is a Touch Device **100** that also provides pressure data at surface contact along with positional detected touch **111** data. An embodiment of a Pressure Imaging Apparatus **1** includes a standard USB cable **9**.

Other embodiments of Touch Devices **101** that provide some degree of pressure data (although with less accuracy of pressure sensing than a pressure imaging apparatus **1**) include FTIR.

FIG. **126** shows Pressure Imaging Apparatus **1** with a USB cable **9**.

Computer **3**: A computer **3** or other device with a micro-processor with a means for receiving data from one or more touch device **101** and one or more Range Imaging Camera **100**. An embodiment of a computer **3** is a Microsoft Windows based Computer.

#### Step by Step Description of User Experience:

FIG. **127** shows a Table Top Embodiment with a Touch Device **101**, Range Imaging Camera **100** Physical Objects **102** such as User's Left **118** and Right **121** Hand.

FIG. **128** shows a Floor Embodiment with a Touch Device **101**, a Range Imaging Camera **100**, Physical Objects **102** such as Individual Users **109**.

From the user's perspective, operation is as follows:

In one time step, one or more users' hands or other physical objects **102** are within the field of view of the Range Imaging Camera **100**. A continuous image from the Range Imaging camera **100** is transmitted to the computer **3**. Concurrently any user may impose a finger, hand palm, toe, foot, knee, other body part, or other physical object onto the top of the touch device **101**. A continuous image of this imposed touch is transmitted by a touch device **101** to a host computer **3**.

On the computer **3** the Range Image of spatially varying depth is stored in a region of computer memory. From there computer software on the computer **3** can be used to store the image in secondary storage such as a disk file, to display the image as a visual image on a computer display, to perform analysis such as construction of a hand object model **105**, hand tracking, body model, body tracking, foot shape model, foot tracking, region finding, shape analysis or any other image analysis process which is standard in the art [1-5], or for any other purpose for which an image can be used.

In an embodiment with a pressure imaging apparatus **1**, on the computer **3** the image of spatially varying pressure is stored in a region of computer memory. From there computer software on the host computer can be used to store the image in secondary storage such as a disk file, to display the image as a visual image on a computer display, to perform analysis such as hand shape recognition, finger tracking, footstep shape recognition, footstep tracking, region finding, shape analysis or any other image analysis process which is standard in the art, or for any other purpose for which an image can be used.

On the next time step, the above process is repeated, and so on for each successive time step.

#### Outside Operational Point of View

FIG. **129** shows an embodiment of a Touch Device **101**, Range Imaging Camera **100**, USB Cable **9** from Touch Device **101** to a Computer **3**, a USB Cable **9** from a Range Imaging Camera **100** to Computer **3**, and Computer **3**.

One or more Touch Devices **101** and one or more Range Imaging Cameras **100** are connected to a Computer **3**.

Each Touch Device **101** has one or more of the Range Imaging Cameras **100** aimed at its surface.

Each Range Imaging Camera **100** is calibrated/registered with the Touch Device(s) **101** that it is aimed at. This is done using well established software techniques such as algorithms described in [17], [18], [19], [20], [21], or any other image analysis process which is standard in the art. A direct result of this calibration/registration in a well defined mapping of points on the 2D Touch Devices **101** to points in the 3D coordinate system of the Range Imaging Camera **100**.



## Internal Operational Point of View

Using image analysis processes on the Range Imaging Camera **100** data, such as [1], [2], [3], [4], [5], [15], [16], [22], [23] or using any other image analysis process, which is standard in the art, objects in the scene may be identified, mapped to known model types, and tracked in 3D space.

Continuous time varying 3D Articulated Models of each hand, full body, or other object with a known geometry, such as a pen, are constructed from the Range Imaging Camera **100** data using image analysis process such as [1], [2], [3], [4], [5], [15], [16], [22], [23] or using any other image analysis process which is standard in the art.

Continuous time varying detected touch **111** tracking of finger, palms, or other objects in contact with the Touch Device **101** are constructed from the surface data from the Touch Device **101** using detected touch **111** tracking process such as [7] or [22] or using any other touch tracking process which is standard in the art.

Step by Step Detailed Algorithm how to Combine the 2D and 3D Info Together

A plurality of identifiable object models; such as hand, body, pen, ball, cylinder, hammer, or any other object appropriate for an application utilizing this invention; are stored as available data of known types. This data includes any data necessary for identifying the object type as well as a geometric skeletal model including a set of Articulation Joints **112** for this object type and a set of Trackable Contact points **110** for that model. For example in a hand object model **105**, articulation joints **112** would include the wrist and individual finger joints **112** while the contact points would include the finger tips. For purposes here, the model types are identified as  $T_i$ . For example,  $T_1$  may designate the model type for hand,  $T_2$  may designate the model type for pen, etc. This object identification, mapping and tracking in 3D space can be accomplished utilizing an image analysis process such as [1], [2], [3], [4], [5], [15], [16], [22], [23] or using any other image analysis process which is standard in the art.

FIG. **130A** shows the resulting hand edge **122** of a hand detected using Range Imaging Camera **100** Data from a User's Hand **115** image and after applying standard art edge detection algorithms; FIG. **130B** shows the hand edge **122** overlaid with the resulting feature skeleton of the hand Object Model **105** derived by applying standard art algorithms; and FIG. **130C** showing the skeleton of the derived articulated hand Object Model **105** showing the Trackable Contact Points **110** in the Model, such as finger tips and Articulation Joints **112** in the Model, such as wrist, finger joints, etc.

As each object is first detected and identified as a known Model Type  $T_i$ , it will be assigned a unique element identifier,  $E_j$  which is added to a list of known Elements in the Scene. Thereupon the system will continuously time track the 3D coordinates of each joint in  $J_{jn}$  ( $n$  indicating the  $n^{th}$  Joint **112** number in  $T_i$ ), as well as the contact points **110**,  $C_{jm}$  ( $m$  indicating the  $m^{th}$  contact point **110** number in  $T_i$ ), of the element  $E_j$ . Tracking of the Joints **112** and Contact Points **110** corresponding to the element's model is maintained even when some of the joints **112** or contact points **110** become occluded (either occluded by itself as when fingers become occluded in a clenched fist, or by another objects in the scene). A contact point **110** will be considered occluded if that contact point is not visible by the Range Imaging Camera **100** at a specific moment in time.

FIG. **130D** shows an example of articulated model for a hand Element  $E_j$  with labeled joints  $J_{jn}$ , and contact points,  $C_{jm}$

Specifically the computing system will maintain a list of Elements,  $E_j$  in the scene with the following data:

Model Type,  $T_i$

At any point in time:

A set of 3D positions, one for each joint **112**  $J_{jn}$ , in Global Coordinates<sup>(\*)</sup>

A set of 3D positions, one for each contact point **110**  $C_{jm}$

A set of occlusion Boolean values, one for each contact point **110**  $C_{jm}$  indicating whether that contact point **110** is currently visible from the range imaging camera **100**

(\*)—As described in a separate section all Positions can be mapped to a global coordinate system for the scene.

Concurrently, for each touch device **101** there will be a continuous time varying set of detected touches **111** on the touch device **101** of objects in contact with the Touch Device **101** are tracked using a touch tracking process such as [7] or [22] or using any touch tracking process which is standard in the art.

As each detected touch **111** is first detected and identified it will be assigned a unique touch identifier,  $P_j$  which is added to a list of known Touches for that device. As is standard practice in the art [22], if a touch,  $P_j$ , leaves the surface and a new touch is detected within a designated time threshold and distance threshold, that touch will be given the same id,  $P_j$  as in the case of a finger tap on standard devices such as the Apple iPad. A touch that has left the surface and does not reappear on the surface within that threshold of time and distance is considered 'no longer active'.

FIG. **134** shows a Touch Device **101** with a set of Contact Points  $P_k$ .

Specifically the computer **3** will maintain a list of Touches,  $P_k$  for each device with the following data:

At any point in time:

The 2D position of the touch mapped to 3D Global Coordinates<sup>(\*)</sup>

In the case of a Pressure Imaging Apparatus **1**, the pressure value of the touch.

(\*) As described in a separate section all Detected Touch **111** Positions can be mapped to a global coordinate system for the scene.

For each contact point **110** object model type as  $T_i$  a contact radius may be specified as data. For example, the contact radius corresponding to a finger tip would be approximately  $\frac{1}{4}$ ", corresponding to the distance from the position in the model of the finger tip (inside the finger) to the surface of the object itself (corresponding to a point on the pad of the finger). This contact radius may be scaled to the side of the actual Element as appropriate for the application of the invention. For example a child's hand is much smaller than a large adult man's hand so the contact radius for the child's finger might be approximately  $\frac{1}{8}$ ". In one embodiment, a scaling factor might be computed relative to the distance of two designated adjoining joints **112**.

A Detected Touch **111**  $P_k$  is no longer active when the detected touch **111** has left the surface and has not come in contact again within time and distance thresholds described earlier (such as a tap motion). In one embodiment, the time and distance thresholds may match the associated contact point **110**. For example a foot tap have a larger time threshold than a finger tap.

Below is the algorithm for associating Detected Touches **111** with Contact points **110** and for associating Contact Points **110** with Touches:



For each time step  $t$   
 Obtain the new state of the object elements  $\{E_j\}$  in the scene at time  $t$ , derived from the Range Imaging Cameras **100** data.  
 For each new element  $E_j$  first introduced to the scene in this time step  
   For each Contact Points **110**  $C_{jm}$ , of that element  
     Set the Detected Touch **111** associated with that Contact Point **110** to 'none'  
 Obtain the new state of the Detected Touches **111**  $\{P_k\}$  at time  $t$  from the Touch System  
 For each new Detected Touch **111**  $P_k$  first introduced in this time step  
   Set the Contact Point **110** associated with that Detected Touch **111** to 'none'  
 For each Detected Touch **111**  $P_k$  that has become no longer active in this time step  
   If there is a Contact Point **110**  $C_{jm}$  associated with this Detected Touch **111**  
     Set the Detected Touch **111** associated with  $C_{jm}$  to 'none'  
   Remove this Detected Touch **111**  $P_k$  from the set of Detected Touches **111**  
 For each Detected Touch **111**  $P_k$  that does not have a contact point **110**  $C_{jm}$  associated with it  
   For each Contact Point **110**  $C_{jm}$  that does not have a detected touch **111** associated AND the Contact Point **110** is not currently occluded  
     compute the Euclidian Distance  $d$  between respective positions in Global Coordinates of the Contact Point **110**  $C_{jm}$  and the Detected Touch **111**  $P_k$   
     if  $d$  is less than the contact radius for that Contact Point **110**,  $C_{jm}$   
       Associate  $C_{jm}$  with  $P_k$   
       Associate  $P_k$  with  $C_{jm}$   
 Display the data,  $\{E_j\}$ ,  $\{C_{jm}\}$ ,  $\{J_{jm}\}$ , and  $\{P_k\}$  along with the computed associations (\*)  
 Provide this data,  $\{E_j\}$ ,  $\{C_{jm}\}$ ,  $\{J_{jm}\}$ , and  $\{P_k\}$  along with the computed associations (\*) via an API to all higher level systems for further analysis (\*\*)(\*\*)  
 On the next time step, the above process is repeated, and so on for each successive time step.

Note:

(\*) For Contact Points **110**  $C_{jm}$  that have associated Detect Touches  $P_k$ , positional information from the Detected Touch  $P_k$  will always be more accurate than the positional information from the Contact Point  $C_{jm}$  (from the Range Imaging Camera **100** data analysis). Specifically, while the position of an occluded Contact Point **110** is either inaccurate or unavailable, an accurate position for any occluded Contact Point **110**  $C_{jm}$  is available via the position of the associated detected Touch **111**  $P_k$ .

(\*\*) The data  $\{E_j\}$ ,  $\{C_{jm}\}$ ,  $\{J_{jm}\}$ , and  $\{P_k\}$  along with the computed associations may be provided to higher level systems for further analysis such as gesture synthesis or gesture analysis that would extract higher level gestures such as in [27] which in turn could be made available for use in an application FIG. **135** shows a Block Diagram showing the Range Imaging Camera **101** and Touch Device **102** connected to the Computer **3**. Using the above algorithm, the element data  $\{E_j\}$  is stored in the Computer Memory for Element Data **123** and the Detected Touch Data is stored in the Computer Memory for Detected Touch Data **124**.

Combine Multiple Range Imaging Cameras and Touch Devices

The ability to combine, over a large multiple user **109** surface, high quality semantic data about hand gesture and

hand/finger identification as well as foot gesture and foot/toe identification with numerically high quality information about the position, exact time and, in the case of a Pressure Imaging Apparatus **1** pressure of each detected touch **111** upon a surface, and to make this data available in an API, will enable new kinds of interactive human/computer interface applications that were heretofore unattainable.

The broader impact/commercial potential of this invention follows from the combination, over a large multiple user **109** surface, of high quality semantic data about hand gestures, foot gestures and object manipulation with high resolution fine detail from surface data, enabling new kinds of interactive human/computer interface applications heretofore unattainable, in scenarios where collaborators gather and/or walk around in the presence of tables and projection walls to do high quality collaborative work using natural and expressive hand, foot and object-manipulation gestures. This Touch-Range Fusion Apparatus **104** approach is superior to approaches using range imaging cameras **100** or touch device **101** alone, because it allows both isometric and isotonic gestures along with both full hand/finger segmentation and high quality touch/pressure sensing. As both range imaging cameras **100** and touch devices **101** become low priced commodities, costs become sufficiently low that this type of touch-range fusion apparatus **104** can be broadly deployed in homes, offices, schools or other places, to enable people to gather and walk around in the presence of tables and projection walls to do high quality collaborative work. This will have strong implications for education, teleconferencing, computer-supported collaborative work and educational games, as well as interactive simulation for scientific visualization, defense, security and emergency preparedness.

Separately, a novel computer human interaction technology, here called a Touch-Range Fusion Apparatus **104**, is described that enables robust gestures and high quality/precise hand/finger input as well as foot/toe input along with disambiguation of multiple individual users **109**, user hands **115**, individual fingers, individual feet and toes, pens and objects over a surface area. Data from range imaging cameras **100** is used to track movements of hands and feet and to maintain consistent hand/finger and foot/toe identity over time, and this information is combined with a surface touch device **101** to determine accurate positional surface information with a high frame rate. This results in a Touch-Range Fusion Apparatus **104** enablement along with a software abstraction that reliably combines data from one or more Range Imaging Cameras **100** with data from a Pressure Sensing Apparatus **1** or any other type of touch device **101** capable of detecting the location of one or a plurality of detected touches **111** upon a surface, to create a high quality representation of hand and finger action as well as foot and toe action for one or more users or for any other object above and upon a large area surface. This technology enables an inexpensive commercial device using only commodity range imaging cameras **100** and touch devices **101**, and where the pressure imaging apparatus **1** or other type of touch device **101** can occur at a data rate that is substantially faster than the frame rate of commodity range imaging cameras **100**, such as one hundred to two hundred frames per second, along with a software abstraction that enables robust hand and foot action/gesture and individual hand/finger/foot/toe/object identification and disambiguation.

When used in combination, range imaging cameras **100** and high-frame-rate pressure imaging touch devices **101** suffer none of the deficiencies of each technology alone. In particular, combined data from range imaging camera(s) **100** and a touch device **101** allows a software layer to determine



whether fingertips or pens are touching the surface, to continuously track identified fingertips and pens that are touching the pressure imaging apparatus **1** or touch device **101**, and to maintain the identity of touching fingertips and pens even when the target becomes obscured from the camera. In addition, collaboration between multiple simultaneous users can be supported, in the described invention allows a software layer to differentiate multiple individuals that are simultaneously using the same workspace, and to maintain owner ID on user hands **115**/styli as users' hands cross over each other or, in the presence of multiple pairs of feet, upon a floor or other surface underfoot.

Using standard art 3D Transformation Matrix techniques, a common global coordinate system can be established for multiple Range Imaging Cameras **100** and Touch Devices **101**. When one or more touch devices **101** are used, a calibration process must be completed in order to obtain the transformation matrix between the range imaging camera **100** and the surface of the touch device **101**. In one implementation, calibration cubes **113** are placed at the four corners of one touch device **101**. Using these corner coordinates, a transformation matrix is determined between the points and the range imaging camera **100**. Together, these four points create a surface plane for the touch device **101**. This process must be completed for each touch device **101** in the camera's view. If multiple range imaging cameras **100** are used, then a transformation matrix is determined for each touch device **101** and range imaging camera **100** pair, which proscribes the coordinate transformation between that touch device **101** and that range imaging camera **100**. In one implementation, this process is repeated for each touch device **101** that is being monitored. If multiple range imaging cameras **100** are associated with a touch device **101**, then a global transformation matrix can be determined between the range imaging cameras **100**, using the touch device **101** as a common reference coordinate system. Having multiple range imaging cameras **100** having overlapping views allows for the position of each subsequent range imaging camera **100** to be determined during calibration. If a global matrix is desired for a range imaging camera **100** that views no touch device **101** with another range imaging camera **100**, then that matrix must be associated with the range imaging camera **100** or the touch device **101**.

FIG. **131** shows cubes placed at the four corners of a touch device.

Gestures enabled by fusing touch devices **101** and range imaging cameras **100**.

Gestures enabled by touch devices **101** and range imaging cameras **100** rely on the identification capabilities of the range imaging cameras **100** being paired with the accuracy of the touch devices **101**.

#### Single Touch:

Any gesture made possible by the touch device **101** with a single touch can be expanded to have a specific action state based on the detected touch **111**. For instance, if fingers of the hand are being used, then each finger can have a separate action state attached. This means that if one hand is used, five separate actions can be performed, one for each finger, without needing to rely on a menu to switch between the actions. Additionally, single touch objects, such as pens can be distinguished from fingers to provide alternate interactions or to prevent accidental input.

In one implementation, input from the touch-range fused apparatus **104** can be used to emulate a mouse by mapping mouse movement to the movement of the index finger on the touch device **101**, left click to the thumb taps and right click to middle finger taps. This example illustrates the utility of the sensor fusion technique. Without the range imaging camera

**100**, finger-touch identification would be lost and without the touch imaging, accuracy and high frame rate would be lost.

#### Multi-Touch:

When the scope of interaction is expanded to multiple detected touches **111**, precision chording is possible. Using a touch device **101** without a range imaging camera **100** limits the possible action states to the number of inputs. For instance, if fingers of a single hand are used on a touch device **101**, then only five action states are available (one to five touches). When fused with a range imaging camera **100** to identify touches, chording is possible. Chording is the process of using specific detected touches **111** simultaneously to perform a gesture. For example, using the thumb and index finger simultaneously could perform a separate gesture than the thumb and middle finger simultaneously. Identifying detected touches **111** means that  $(2^n)-1$  action state combinations are possible for  $n$  number of detected touches **111**. For instance, the combination of possible action states for fingers of a single hand goes from 5 to 31 when a range imaging cameras **100** are added.

In one implementation, the right hand holds a pen that provides position input to a painting program by touching the touch device **101**. As the user draws, the left hand can use specific chording combinations to switch between 31 set actions states for the pen.

#### Palms/Hands/Feet/Objects:

Fusing a range imaging camera **100** and a touch device **101** can also be used to reject unwanted input and add action states to non-standard touch inputs like hands, feet and objects.

When using a touch device **101** by itself, unintended input can occur. For instance, a palm can be placed on a touch device **101** and can be confused for a detected touch **111**. When fused with a range imaging camera **100**, the skeleton of the hand is determined which allows the touch to be identified as a palm and the input can be rejected. The same idea can be applied to other objects that should be rejected from providing input. For instance, a coffee cup placed on the touch device **101** could be rejected.

Hands, feet and objects can also provide alternate forms of interaction that rely on what a touch device **101** would consider multiple touches. For example, touching with different parts of the palm could be mapped to different action states. Without the range imaging camera **100**, the region of the palm that was touching could not be determined.

#### Multiple Individual Users **109**:

By itself, a touch device **101** cannot distinguish individual users **109** that are touching the same device. When paired with range imaging cameras **100**, then the individual users **109** can be determined and touches can be assigned to the correct individual user **109**. This allows for simultaneous interaction from multiple individual users **109** or for collaborative interactions.

For example, the touch-range fusion apparatus **104** can disambiguate between the scenarios of a plurality of simultaneous detected touches **111** from different fingers of one hand, a plurality of simultaneous detected touches **111** from fingers belonging to different hands of the same user, a plurality of simultaneous detected touches **111** from fingers belonging to the hands of two different individual users **109**.

Similarly, the touch-range fusion apparatus **104** can be used to distinguish between the scenarios of simultaneous detected touch **111** upon a sensing floor by two feet of one user, and simultaneous detected touch **111** upon the sensing floor by the feet of two different individual users **109**.



#### Alternate Embodiments of Camera and Touch Device Configurations

In one Embodiment that would be appropriate for tabletop hand gesture tracking would consist of a Range Imaging camera **100** aimed at a narrow angle, such as a 3° onto a 12"×18" with the camera recessed 6" away from the touch device **101**.

FIG. **132** shows an Embodiment of the invention with Touch Device **101** and Range Imaging Camera **100**.

In another Embodiment the Range Imaging camera **100** can be placed on a supporting stand and aimed down at the Touch Device **101** at a modest angle, such as a 30°. This configuration could be appropriate for tabletop hand gesture tracking onto a 12"×18" touch device. It could also be appropriate for a game controller with a 5'×6' touch Pressure Imaging Apparatus **1**.

FIG. **122** shows an embodiment of the invention with Touch Device **101**, Range Imaging Camera **100**, supporting stand **114** allowing the range imaging camera **100** to face the touch device **100** at a sharper angle.

In another embodiment that would be appropriate for hand gesture tracking would consist of two Range Imaging cameras **100** can be aimed at a narrow angle, such as a 2° onto a 16×25" Touch Device **101**, as seen in FIG. **133**.

#### Utilities

The following are some utilities for the touch-range fusion apparatus **104**.

#### Electronic Whiteboard:

Our sensor fusion can be a component of an electronic whiteboard, which consists of a flat touch device **101**, one or more range imaging cameras **100**, a computer **3** and a display projector that projects the computer video images on the surface. The touch-range fusion apparatus **104** serves as the input for the electronic whiteboard. Input can come from a pen or finger, which is identified by the range imaging camera **100**, and draws a line on the electronic touch device **101**. The computer uses contact point data from the touch device **101** and maps them to pixels on the projected display image, such as the pixels where the pen's path is being traced. Individual fingers of the user can be placed onto the surface to change the color of the pen with a separate hand gesture.

#### Collaborative Surface:

A collaborative surface that uses the touch-range fusion apparatus **104** consists of a touch device **101**, one or more range imaging cameras **100**, a computer **3** and a projector. In one implementation, multiple individual users **109** gather around the touch device **101** and touch images that are displayed on the surface. Using the location, arm distances and relative arm angles, individuals can be distinguished from each other. When a user makes contact with the touch imaging surface, photos can be selected if the touch lies within the displayed photo. Dragging a finger along the surface moves the photo. The location of the user that is holding the photo, which is calculated when determine the distinctive users **109**, is used to rotate the selected image so that the image is placed right-side-up for the user.

#### Computer Peripheral:

A computer peripheral would consist of a touch-range fusion apparatus **104** and some communication protocol that passes information to and from a computer **3**. It is possible with this peripheral to emulate a mouse. Using the identification of finger tips, the thumb can be mapped to mouse movement, the index finger can be used as a left mouse click and the middle finger can be used to right click.

#### Game Controller:

A game controller that uses a touch-range fusion apparatus **104** is made up of the touch-range fusion apparatus **104** and a

communication protocol to a gaming console. Interaction can come from hands, feet, bodies, or objects. In one instance, multiple individual users **109** dance on a 6 foot by 6 foot touch device **101** as a display from the gaming console shows dance moves to complete. Each user's foot can be determined by using the range imaging camera **100** data. Correct steps are rewarded by an increase in score on the game.

#### References, all of which are Incorporated by Reference Herein

- [1] V. Savoy. Kinect Finally Fulfills Its Minority Report Destiny. Engadget. 2010.
- [2] A. Wu and M. Shah and N. Lobo. A Virtual 3D Blackboard: 3D Finger Tracking using a Single Camera, 2000, 536-543.
- [3] S. Malik, Real-time Hand Tracking and Finger Tracking for Interaction. 2003. [4] C. Jennings. Robust Finger Tracking with Multiple Camera. In Proc. of the International Workshop on Recognition, Analysis, and Tracking of Faces and Gestures in Real-Time Systems, 1999, 152-160.
- [5] <http://youtu.be/jer1Ms5dUJg> Kinect Finger Tracking Video
- [6] <http://touchco.com/> Touchco
- [7] S. Jobs. 2008. Touch screen device, method, and graphical user interface for determining commands by applying heuristics. U.S. Patent Application No. 20080122796.
- [8] <http://www.wacom.com/en/Products/Intuos.aspx> Wacom Intuos 4
- [9] <http://www.microsoft.com/surface/en/us/default.aspx> Microsoft Surface
- [10] <http://www.merl.com/projects/DiamondTouch/> Diamond Touch
- [11] <http://smartechnologies.com/> SMART Technologies
- [12] J. Y. Han. Low-cost multi-touch sensing through frustrated total internal reflection. Proceedings of the 18th Annual ACM Symposium on User Interface Software and Technology, pages 115-118, 2005.
- [13] I. Rosenberg and K. Perlin. The unmousepad: an interpolating multi-touch force-sensing input pad. In SIGGRAPH '09: ACM SIGGRAPH 2009 papers, pages 1-9, New York, N.Y., USA, 2009. ACM.
- [14] <http://www.futuresource-consulting.com/> Future Consulting
- [15] Ming-Ching Chang and Benjamin B. Kimia, Regularizing 3D Medial Axis Using Medial Scaffold Transforms, Computer Vision and Pattern Recognition, 2008. CVPR 2008. IEEE Conference.
- [16] Xia H. and Tucker P. G. (2009), Distance solutions for medial axis transform, Proceedings of 18th International Meshing Roundtable, Salt Lake City, Utah, Oct. 25-28, 2009, pp. 247-260.
- [17] <http://www.umiacs.umd.edu/~ramani/cmssc828d/lecture9.pdf>, Ramani Duraiswami, Lecture Notes on Camera Calibration, cmssc828d.
- [18] Multiple View Geometry in Computer Vision, R. Hartley and A. Zisserman, Cambridge University Press, 2000, pp. 138-183.
- [19] Three-Dimensional Computer Vision: A Geometric Approach, O. Faugeras, MIT Press, 1996, pp. 33-68.
- [20] A Versatile Camera Calibration Technique for 3D Machine Vision", R. Y. Tsai, IEEE J. Robotics & Automation, RA-3, No. 4, August 1987, pp. 323-344.
- [21] Jean-Yves Bouguet, Camera Calibration Toolbox for Matlab, [http://www.vision.caltech.edu/bouguetj/calib\\_doc](http://www.vision.caltech.edu/bouguetj/calib_doc).



- [22] Wayne Carl Westerman, John G. Elias, Maintaining activity after contact liftoff or touchdown, U.S. Pat. No. 7,782,307.
- [23] Arther R. Pope, Model-Based Object Recognition—A Survey of Recent Research, Technical Report 94-4 Jan. 4, 1994.
- [24] Farshid Arman, Model-based object recognition in dense-range images—a review, Journal ACM Computing Surveys (CSUR) Surveys Volume 25 Issue 1, March 1993.
- [25] G. Qian, J. Zhang, and A. Kidane, “People Identification Using Gait via Floor Pressure Analysis”, IEEE Sensors Journal, Vol. 10, No. 9, pp. 1447-1460, September 2010, doi: 10.1109/JSEN.2010.2045158.
- [26] Augsten, T., Kaefer, K., Meusel, R., Fetzer, C., Kanitz, D., Stoff, T., Becker, T., Holz, C. and Baudisch, P. Multi-toe: High-Precision Interaction with Back-Projected Floors Based on High-Resolution Multi-Touch Input. Proceedings of UIST 2010, New York, N.Y., Oct. 3-6, 2010, pp. 209-218.
- [27] Cullen Jennings, Robust Finger Tracking with Multiple Cameras, Proceedings of the International Workshop on Recognition, Analysis, and Tracking of Faces and Gestures in Real-Time Systems, 1999.
- [28] Jacob O. Wobbrock, Meredith Ringel Morris, Andrew D. Wilson, User-Defined Gestures for Surface Computing, Proceeding CHI '09 Proceedings of the 27th international conference on Human factors in computing systems.

Although the invention has been described in detail in the foregoing embodiments for the purpose of illustration, it is to be understood that such detail is solely for that purpose and that variations can be made therein by those skilled in the art without departing from the spirit and scope of the invention except as it may be described by the following claims.

The invention claimed is:

**1.** An apparatus for sensing comprising:

a computer and a plurality of individual sensing tiles in communication with the computer that form a sensor surface that detects force applied to the surface and provides a signal corresponding to the force to the computer which produces from the signal a time varying continuous image of force applied to the surface, where the surface is contiguous, and detected force can be sensed in a manner that is geometrically continuous and seamless on a surface, each tile having protrusions; and bridging plates which span across pairs of the protrusions on different sensing tiles, the computer causes prompting signals to be sent to the sensing tiles and reconstructs a continuous position of force on the surface from interpolation based on data signals received from the sensing tiles, each sensing tile has a microcontroller that produces data packets that have the sensing tile's identity from which the data packets are produced and which are sent over a common communication protocol shared by the microcontroller of each sensing tile to the computer, a printed circuit board having the microcontroller and a layer having an inner face below the protrusions with a cavity in which the printed circuit board is disposed.

**2.** The apparatus of claim **1** wherein the plurality of sensing tiles includes a master tile in communication with the computer and slave tiles in communication with the master tile, the master tile receives the data packets produced from the slave tiles and provide them to the computer.

**3.** The apparatus of claim **1** wherein the plurality of sensing tiles receive power from the computer.

**4.** A method for sensing comprising:

detecting a force applied to a sensor surface formed of a plurality of individual sensing tiles having protrusions from an object moving across the surface where the surface is contiguous, detected force can be sensed in a manner that is geometrically continuous and seamless on a surface with bridging plates which span across pairs of the protrusions on different sensing tiles;

including the step of producing with a microcontroller of each sensing tile data packets that have the sensing tile's identity from which the data packets are produced and which are sent over a common communication protocol shared by the microcontroller of each sensing tile to a computer, each sensing tile having a printed circuit board having the microcontroller and a layer having an inner face below the protrusions with a cavity in which the printed circuit board is disposed;

providing a signal corresponding to the force to the computer from the tiles in communication with the computer; and

producing with the computer from the signal a time varying continuous image of force applied to the surface.

**5.** The method of claim **4** including the step of connecting an additional tile to at least one of the two tiles to expand the size of the sensor surface, where the surface includes the additional tile and is contiguous, and detected force can be sensed in a manner that is geometrically continuous and seamless on a surface.

**6.** The method of claim **4** including the step of imparting force to a top of a mechanical layer that is transmitted through at least one intersection of a plurality of intersections, and thence to at least one protrusion of a set of protrusions in contact with at least one of the intersections, where the intersections are defined by a grid of wires and areas of space between the wires, and the mechanical layer has a plurality of plates that are disposed atop the grid of wires.

**7.** The method of claim **4** including the step of imparting force to a top of a mechanical layer that is transmitted through at least one protrusion of a set of protrusions to at least one intersection of a plurality of intersections, where the intersections are defined by a grid of wires and areas of space between the wires, and the mechanical layer has a plurality of plates that are disposed atop the grid of wires.

**8.** The method of claim **5** wherein the plurality of sensing tiles includes a master tile in communication with the computer and slave tiles in communication with the master tile, and there is the step of the master tile receiving the data packets produced from the slave tiles and provide them to the computer.

\* \* \* \* \*