



US009320329B2

(12) **United States Patent**
Nisguretsky

(10) **Patent No.:** **US 9,320,329 B2**
(45) **Date of Patent:** **Apr. 26, 2016**

(54) **IRREGULAR FINGER RING CONFIGURATION**

(76) Inventor: **Barry Nisguretsky**, Brooklyn, NY (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **11/623,433**

(22) Filed: **Jan. 16, 2007**

(65) **Prior Publication Data**

US 2008/0168800 A1 Jul. 17, 2008

(51) **Int. Cl.**
A44C 9/00 (2006.01)

(52) **U.S. Cl.**
CPC **A44C 9/00** (2013.01); **A44C 9/0053** (2013.01)

(58) **Field of Classification Search**
CPC A44C 9/00; A44C 9/0053; A44C 7/002; A44C 9/02
USPC 63/15, 26–32 TS, 3, 15.45, 15.5, 15.6, 63/15.65, 15.7, 5.1, 11, 15.8, 15.9, 26–28, 63/29.1, 30; D11/34, 38, 37, 23, 35, 43, D11/47, 75–76, 79; 24/3, 15, 15.45, 15.5, 24/15.6, 15.65, 15.7
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

| | | | | |
|---------------|---------|-----------------|-------|---------|
| D15,489 S * | 10/1884 | Heer | | D8/368 |
| 802,267 A | 10/1905 | Chaument | | |
| 1,115,764 A * | 11/1914 | Applas | | 63/15.6 |
| 1,146,543 A * | 7/1915 | Abel et al. | | 63/15 |
| D68,149 S * | 9/1925 | Lindeberg | | D11/38 |
| 1,668,217 A * | 5/1928 | Schrayssshuen | | 63/3 |
| 1,822,392 A * | 9/1931 | Esterman et al. | | 63/15.4 |

| | | | | |
|---------------|--------|------------------|-------|---------|
| D96,056 S * | 6/1935 | Sasger | | D11/38 |
| 2,395,745 A * | 2/1946 | King | | 285/367 |
| 3,022,648 A * | 2/1962 | Thaler | | 63/15 |
| 3,360,959 A * | 1/1968 | Schechter et al. | | 63/15.6 |
| 3,380,263 A * | 4/1968 | Astor | | 63/15.6 |
| 3,557,571 A * | 1/1971 | De Santo | | 63/15.6 |
| 3,590,598 A * | 7/1971 | Leone | | 63/15.6 |
| 3,901,045 A | 8/1975 | Ballester | | |
| 4,043,145 A | 8/1977 | Chervin | | |
| 4,215,556 A | 8/1980 | Mroz | | |
| 4,245,485 A * | 1/1981 | Bushong | | 63/15.6 |
| 4,317,264 A | 3/1982 | Bogner et al. | | |
| 4,351,166 A | 9/1982 | Belin | | |
| 4,538,430 A | 9/1985 | Parks | | |
| 5,398,525 A * | 3/1995 | Kennedy | | 63/28 |

(Continued)

FOREIGN PATENT DOCUMENTS

| | | |
|----|---------|--------|
| CH | 695205 | 1/2006 |
| GB | 2405345 | 3/2005 |


(Continued)

Primary Examiner — Abigail Morrell
(74) *Attorney, Agent, or Firm* — Andrews Kurth LLP

(57) **ABSTRACT**

A jewelry arrangement that is configured to fit on a finger. The arrangement can include a first jewelry portion and a second jewelry portion. The first jewelry portion may be attached to the inner surface of the second jewelry portion. The second jewelry portion may be positioned away from the user's skin. The first jewelry portion may contain at least one element which may contact a user's skin. In one exemplary embodiment, the elements are semi-cylindrical, rounded or arc-shaped. In an other exemplary embodiment, the elements are cylindrical. Another exemplary embodiment may contain a combination of different elements that together create a non-uniform surface. In yet another exemplary embodiment, there may be a ring crown attached to the second jewelry portion. This ring crown may also form part of the non-uniform surface created by the first jewelry portion.

32 Claims, 9 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

D431,793 S * 10/2000 Ambar D11/34
D439,190 S 3/2001 Itzkowitz
D451,045 S * 11/2001 Ambar D11/26
D451,424 S * 12/2001 Ambar D11/34
D453,486 S * 2/2002 Zillig D11/38
D460,926 S * 7/2002 Zillig D11/26
D478,170 S * 8/2003 Catlett D24/143
D489,022 S * 4/2004 Riggio D11/38
6,748,764 B1 6/2004 Roemer
D513,712 S 1/2006 Koren
D516,937 S * 3/2006 Aghjayan et al. D11/35
D522,902 S 6/2006 Kaplan
D523,370 S 6/2006 Yurman
D530,641 S 10/2006 Rota

D542,692 S * 5/2007 Sabet D11/34
D542,693 S * 5/2007 Sabet D11/34
7,350,377 B2 4/2008 Kaplan
2004/0177647 A1 * 9/2004 Dennis 63/29.1
2005/0268653 A1 * 12/2005 Kaplan 63/15.7
2006/0144083 A1 7/2006 Layton
2006/0254313 A1 11/2006 Koren
2007/0137250 A1 * 6/2007 Kohl 63/15.6

FOREIGN PATENT DOCUMENTS

JP 2004154466 6/2004
JP 2004248843 9/2004
JP 2006167041 6/2006
WO 9621374 7/1996
WO 2006116425 11/2006

* cited by examiner




FIG. 1




FIG. 2A




FIG. 2B




FIG. 2C




FIG. 2D




FIG. 3




FIG. 4




FIG. 5




FIG. 6

1

IRREGULAR FINGER RING CONFIGURATION

FIELD OF INVENTION

The present invention generally relates to jewelry arrangements, and particularly to exemplary ring arrangements.

BACKGROUND

Rings worn on user's fingers and on other portions of the user's body, such as engagement rings and wedding bands, may be made of precious or semi-precious metals, such as gold, silver or platinum, and can be fitted with a variety of precious gemstones, such as diamonds, rubies, emeralds, opals, etc. Generally, these rings have a pseudo-cylindrical or cylindrical shell or portion, the internal surface of which is shaped such that it can be easily placed/maintained on the wearer's finger. In order for the ring not to easily revolve around the finger, and thus possibly slip off the finger unintentionally, the ring can be fit in a snug manner. Another issue to be addressed is for the ring to fit snugly enough not to easily rotate on the finger, while still fitting around the knuckles of the finger. The common feature in many if not all fitted rings is to increase the pressure on the finger by slightly reducing or otherwise lessening the radial length or radius of the ring, thereby increasing the friction on the skin of the finger to have the ring maintained on the finger snugly. Prior attempts to address these issues have led to a creation of rings fitted with inserts, clasps, and other ways of adjusting the size of the ring.

While making the above-described adjustments, it is also important to maintain an aesthetically pleasing appearance of the ring. Further, although the above-described inserts, clasps, etc. may facilitate the ring fitting snugly on the user's finger, these additional elements may require additional effort by the user to actually fit the ring on a finger. In addition, the use of these additional elements may detract from the aesthetic features of the ring. It may be desirable to provide a jewelry arrangement, e.g., a ring that does not utilize additional elements or a reduction of the radial length/radius to be maintained snugly on the finger, while functioning to resolve common fitting issues.

SUMMARY OF THE INVENTION

Thus, it is one of the objects of the present invention to overcome the above-described deficiencies, and provide exemplary embodiments of a jewelry arrangement according to the present invention. According to one exemplary embodiment of the present invention, a ring arrangement can be provided which has a first jewelry portion and a second jewelry portion. The first jewelry portion preferably is attached to the inner surface of the second jewelry portion in at least one place. The first jewelry portion preferably creates a non-uniform surface that may contact a ring wearer's skin. The first jewelry portion may include at least one element which has a shape that is different from the particular skin portion. These elements may be of varying sizes and shapes. Additionally, the second jewelry portion may contain a ring crown that may be a setting for a stone. This ring crown may also form part of the non-uniform surface in the first jewelry portion.

In a different exemplary embodiment, the first jewelry portion may have a plurality of sections which extend along for the full circumference of the finger of the user. In similar exemplary embodiments, the sections may extend along for at least a quarter, an eighth or half of the circumference of the

2

finger. In a different exemplary embodiment, the first jewelry portion may have a shaped that looks like an cross, "W", "M", "U", or any other angle of such image.

In a different exemplary embodiment, the sections of the first jewelry portion may be connected by at least one end to the second jewelry portion. In some exemplary embodiments, the sections of second jewelry portion may contain more than one end which may be connected to the second jewelry portion or other sections of the first jewelry portion. The sections of the first jewelry portion may have a rounded, semi-circular, semi-cylindrical, or arc-shaped look, which may contact a portion of skin. In a different exemplary embodiment, the first and/or second jewelry portions may contain gemstones.

BRIEF DESCRIPTION OF THE DRAWINGS

The detailed description below will refer to the following illustrations, wherein like numerals refer to like elements, and wherein:

FIG. 1 is a perspective view of a first exemplary embodiment of a jewelry arrangement (e.g., ring arrangement) according to the present invention.

FIGS. 2A-2D are perspective views of certain exemplary variants of a second exemplary embodiment of a jewelry arrangement (e.g., ring arrangement) according to the present invention.

FIG. 3 is a perspective view of a third exemplary embodiment of a jewelry arrangement (e.g., ring arrangement) according to the present invention.

FIG. 4 is a perspective view of a fourth exemplary embodiment of a jewelry arrangement (e.g., ring arrangement) according to the present invention.

FIG. 5 is a perspective view of a fifth exemplary embodiment of a jewelry arrangement (e.g., ring arrangement) according to the present invention.

FIG. 6 is a perspective view of a sixth exemplary embodiment of a jewelry arrangement (e.g., ring arrangement) according to the present invention.

Throughout the figures, the same reference numerals and characters, unless otherwise stated, are used to denote like features, elements, components or portions of the illustrated embodiments. Moreover, while the subject invention will now be described in detail with reference to the figures, it is done so in connection with the illustrative embodiments. It is intended that changes and modifications can be made to the described embodiments without departing from the true scope and spirit of the subject invention as defined by the appended claims.

DETAILED DESCRIPTION OF EXEMPLARY EMBODIMENTS

FIG. 1 shows a perspective view of a first exemplary embodiment of a jewelry arrangement **100** (e.g., a ring arrangement) according to the present invention. The configuration of jewelry arrangement **100** may improve the ring's rotational stability on the finger of the user by assisting with preventing rotation around the finger. The ring arrangement **100** of FIG. 1 may include a circular or cylindrical main ring band **105**. The main ring band **105** can have an inner face **110** and an outer face **115**. The inner face **110** can have thereon one or more semi-cylindrical, rounded or arc-shaped elements **120**. These elements **120** can have ends **130** which can contact and/or are attached to the inner face **110** of the jewelry arrangement **100**. The ends **130** of each of the elements **120** can be spaced apart. Each respective element **120** having the

respective ends **130** includes a rounded portion **135** which connect the respective ends **130**.

According to one exemplary variant, a single element **120** can be provided on the inner face of **110**. In another variant, two or more of the elements **120** can be provided, spaced apart from one another, e.g., the respective ends **130** of each element **120** not contacting the respective ends **140** of any other of the elements **120** (e.g., for the entire inner face **110** or portion thereof), and none of the elements **120** overlap in a circumferential direction around jewelry arrangement **100**. In still another variant, one of the respective ends **130** of at least one of the elements is immediately adjacent to and contacts one of the respective ends **130** of another element. Indeed, as shown in the first exemplary embodiment of FIG. 1, every one of the elements **120** contacts another one of the elements **120** along the inner face **110**. It is also possible that such contacting of the elements occurs for a portion of the inner face **110** or portion thereof. The portions of the inner face **110** described above can be $\frac{1}{8}$, $\frac{1}{4}$, $\frac{3}{8}$, $\frac{1}{2}$, $\frac{3}{4}$, any other ratio.

Unlike traditional rings having a uniform inner face surface which to a large extent conforms to a shape of a finger, the exemplary embodiment of the jewelry arrangement **100** may be fitted with at least one arc-shaped, rounded or semi-cylindrical elements **120** can provide a non-uniform surface which is intended to contact the skin of the finger fitted with such jewelry arrangement **100**. By providing these exemplary inner semi-cylindrical or arc-shaped elements **120** on the inner face of **110**, the jewelry arrangement **100** may better provide a snug fit on the user's finger. This snug fit may decrease the amount of rotation of the ring arrangement once on a finger, thereby reducing the unintentional slippage of the jewelry arrangement **100** on the finger, at least partially, and limiting a readjustment of the size of arrangement **100**. Additionally, as provided in the first exemplary embodiment of the invention, shown in FIG. 1, the jewelry arrangement **100** may be adorned with precious or semi-precious gemstones **125**.

FIG. 2 shows a perspective view of a second exemplary embodiment of the jewelry arrangement **200** according to the present invention. As shown in FIG. 2, the jewelry arrangement **200** also includes the semi-cylindrical, rounded or arc-shaped elements **205**. However, these exemplary elements **205** contact adjacent elements **205**, and may not extend along the entire inner face **210** of the jewelry arrangement **200**. In addition to the elements **205**, the exemplary jewelry arrangement **200** that is intended to at least partially contact the skin may be a combination of the uniform surface **215** (e.g., provided separately from the elements **205**) which may have a rounded shape and be configured to contact the skin of the user of jewelry arrangement **200**. Uniform surface **215** can define an interior of the ring jewelry arrangement. The complete side of the second exemplary embodiment of the jewelry arrangement **200** that may be a combination of the uniform surface **205** and at least one of the elements **205**.

FIG. 3 shows a perspective of a third exemplary embodiment of the jewelry arrangement **300** of the present invention. The jewelry arrangement **300** may have cylindrical elements **305** attached to the inner surface **310** of the jewelry arrangement **300**. The additional cylindrical elements **305** may be provided instead of or in addition to other elements attached to the inner surface **310**, such as semi-cylindrical, rounded or arc-shaped elements **315**. The addition of the cylindrical elements **305** may also facilitate a non-uniform surface on the side of the jewelry arrangement **300** intended to contact the skin of the user.

As shown in FIG. 4, the exemplary embodiment of the jewelry arrangement **400** may have cylindrical elements **405** of varying sizes that may be adjacent to one another or adja-

cent to a semi-cylindrical or arc-shaped element **410** or to a uniform surface **415** which is similar to the uniform surface **215** of FIG. 2. Similar to the semi-cylindrical, rounded or arc-shaped elements **410**, the addition of the cylindrical elements **405** may reduce the amount of rotation of a fourth exemplary embodiment of the jewelry arrangement **400** once placed on the finger, thereby possibly reducing an adjustment of the radial length/radius of the jewelry arrangement **400**.

FIGS. 5 and 6 show fifth and sixth exemplary embodiments of the jewelry arrangements according to the present invention, which can include a crown. For example, FIG. 5 shows a fifth exemplary embodiment of the jewelry arrangement **500**. The exemplary jewelry arrangement **500** can include a ring crown **505** that may be supported by a main ring band **510**. Further, it is possible that the main ring band **510** may not form a completely cylinder or circle shape on its own, but may form a setting **515** for a gemstone, which may complete the cylinder or circle shape of the main ring band **510**. Similar to the embodiments shown in FIGS. 1-4, the main ring band **510** may have at least one semi-cylindrical, rounded or arc-shaped element **520** and/or at least one cylindrical element **525**.

The semi-cylindrical, rounded or arc-shaped and cylindrical elements **525** may be in a configuration to create a non-uniform surface which is intended to contact user's skin. Additionally, the semi-cylindrical, rounded or arc-shaped elements **520** and cylindrical elements **525** may be affixed to the inner surface **530** of the main ring band **510** or to other semi-cylindrical, rounded or arc-shaped elements **520** and/or the cylindrical elements **525**. In addition to the semi-cylindrical, rounded or arc-shaped and cylindrical elements, the exemplary arrangement **500** may contain a uniform surface **540** which is intended to contact the skin of the user. The complete side of the exemplary jewelry arrangement **500** intended to contact the skin of the user may be a combination of the inner surface of the main ring and at least one of the semi-cylindrical, rounded elements **520** and/or the cylindrical elements **525**.

FIG. 6 illustrates a sixth exemplary embodiment of the jewelry arrangement **600** of the present invention. The exemplary jewelry arrangement **600** of FIG. 6 can have a ring crown **605** and a setting **610** which may also form a part of the surface **615** which is intended to contact the skin of the user. The jewelry setting **610** may be attached to a main ring band **620** and to at least one of the semi-cylindrical, rounded or arch-shaped **625** and the cylindrical elements **630**, each of which can have a through-hole.

According to another exemplary embodiment of the present invention, the semi-cylindrical, rounded or arc-shaped elements can be provided on the jewelry arrangement such that the respective ends thereof are pointed toward the skin of the user, which the rounded portion between the respective ends is attached to the inner face/surface of the exemplary embodiment of the jewelry arrangement. In addition, other shapes of members attached to the inner face/surface which do not have a shape for approximately conforming to the shape of the user's finger on which the exemplary jewelry arrangement is to be placed. Such shapes include but no limited to "X", "M", "W" or others that are overlaid by an inner face/surface on a side opposite to the skin of the user, whereas exemplary variants of the second exemplary embodiment are shown in, e.g., FIGS. 2B-2D, respectively.

Although the present invention has been described with respect to particular embodiments thereof, variations are possible. The present invention may be embodied in specific forms without departing from the essential spirit or attributes thereof. For example, although the present invention is illus-

5

trated with embodiments having semi-cylindrical or arc-shaped and cylindrical elements to create non-uniform surfaces, one skilled in the art will recognize that other embodiments may use which have various geometries (such as hexagonal, oval, or tear-drops) that still create a non-uniform surface which may contact a ring wearer's skin. It is desired that the embodiments described herein be considered in all respect illustrative and not restrictive and that reference be made to the appended claims and their equivalents for determining the scope of the invention.

What is claimed is:

1. A ring jewelry arrangement, comprising: a plurality of rigid first jewelry finger ring portions; and at least one second jewelry finger ring portion positioned at a distance from a center of the ring jewelry arrangement that is further than a distance from the first jewelry finger ring portions to the center of the ring jewelry arrangement, the at least one second jewelry finger ring portion being directly and permanently connected to the first jewelry finger ring portions, wherein at least one through hole is provided between at least one of the first jewelry finger ring portions and the at least one second jewelry finger ring portion, and wherein each of the first jewelry finger ring portions has an outermost surface provided closest to the center of the ring jewelry arrangement to define an interior of the ring jewelry arrangement disposed to contact a finger received in the ring jewelry arrangement, the outermost surface curving away from the center of the ring jewelry arrangement and in a direction toward the at least one second jewelry finger ring portion, and wherein the first jewelry finger ring portions do not overlap in a circumferential direction about the at least one second jewelry finger ring portion; wherein the at least one of the first jewelry finger ring portions has a first surface that forms at least one first section of the at least one through hole and the at least one second jewelry finger ring portion has a second surface that forms at least one second section of the at least one through hole, the first surface being situated opposite to the second surface, and wherein a curvature of the first surface is different than a curvature of the second surface.
2. The arrangement of claim 1, wherein the first jewelry finger ring portions extend along for at least half of a circumference of the at least one second jewelry finger ring portion.
3. The arrangement of claim 1, wherein the first jewelry finger ring portions extend along for at least a quarter of a circumference of the at least one second jewelry finger ring portion.
4. The arrangement of claim 1, wherein the first jewelry finger ring portions extend along an entire circumference of the at least one second jewelry finger ring portion.
5. The arrangement of claim 1, wherein the at least one of the first jewelry finger ring portions has at least two ends connected to one another at outermost edges thereof by the at least one second jewelry finger ring portion, and wherein each of the ends points away and opposite from the center of the ring jewelry arrangement.
6. The arrangement of claim 5, wherein the first jewelry finger ring portions further comprise at least one cylindrical element, wherein at least one hole is provided between the at least one cylindrical element and at least one of the ends, and wherein the at least one cylindrical element has an outer substantially uniform surface.
7. The arrangement of claim 5, wherein each of the ends have outermost edges which immovably connect each of the

6

at least one first jewelry finger ring portions to the at least one second jewelry finger ring portion.

8. The arrangement of claim 5, wherein the ends are permanently and directly connected to the at least one second jewelry portion.
9. The arrangement of claim 1, where the at least one of the first jewelry finger ring portions has a shape of at least one symbol of "X", "W", "M", "U", or inverted symbols thereof.
10. The arrangement of claim 1, wherein the at least one second jewelry finger ring portion includes a plurality of second jewelry finger ring portions, each covering the respective first jewelry finger ring portion.
11. The arrangement of claim 1, wherein the at least one of the first jewelry finger ring portions comprises at least one semi-cylindrical element.
12. The arrangement of claim 1, wherein the at least one of the first jewelry finger ring portions comprises at least one arc-shaped element.
13. The arrangement of claim 1, wherein the first jewelry finger ring portions comprise at least one cylindrical element having an outer substantially uniform surface.
14. The arrangement of claim 13, wherein the at least one first jewelry finger ring portions comprise at least two cylindrical elements, and wherein the at least one hole is provided between the at least two cylindrical elements and the at least one second jewelry finger ring portion.
15. The arrangement of claim 1, wherein the at least one second jewelry finger ring portion includes at least one ring crown element which forms a part of a surface of the at least one second jewelry finger ring portion.
16. The arrangement of claim 1, wherein the at least one second jewelry finger ring portion is integral with the first jewelry finger ring portions.
17. The arrangement of claim 1, wherein the at least one through hole extends entirely through the arrangement in a direction approximately perpendicular to a plane extending from the at least one second jewelry finger ring portion towards the center.
18. The arrangement of claim 1, wherein each of the first jewelry finger ring portions includes an inner-most edge of the arrangement with respect to a location of the center of the ring jewelry arrangement.
19. The arrangement of claim 1, wherein at least two of the first jewelry finger ring portions are provided immediately adjacent to one another.
20. The arrangement of claim 19, wherein the at least one through hole extends in a direction which is approximately perpendicular to a plane extending from the at least one second jewelry finger ring portion towards the center.
21. The arrangement of claim 1, wherein ends of the outermost surfaces of at least two adjacent portions of the first jewelry finger ring portions form a "V" at a contact point thereof.
22. The arrangement of claim 1, wherein at least one end of the at least one of the first jewelry finger ring portions directly contacts another one of the first jewelry finger ring portions.
23. The ring jewelry arrangement of claim 1, wherein the at least one through hole extends generally axially with respect to the at least one second jewelry finger ring portion.
24. The ring jewelry arrangement of claim 1, further comprising at least one gemstone.
25. The ring jewelry arrangement of claim 1, wherein a curvature of the outermost surface of the at least one of the first jewelry finger ring portions is substantially the same as the curvature of the first surface of the at least one of the first jewelry finger ring portions.

7

26. A ring jewelry arrangement, comprising:
 a plurality of rigid first jewelry finger ring portions; and
 at least one second jewelry finger ring portion positioned at
 a distance from a center of the ring jewelry arrangement
 that is further than a distance from the first jewelry finger
 ring portions to the center of the ring jewelry arrange-
 ment, the at least one second jewelry finger ring portion
 being directly and permanently connected to the first
 jewelry finger ring portions, wherein at least one through
 hole is provided between at least one of the first jewelry
 finger ring portions and the at least one second jewelry
 finger ring portion, wherein the at least one of the first
 jewelry finger ring portions has a “U” shape, and
 wherein the at least one of the first jewelry finger ring
 portions has an outermost surface provided closest to the
 center of the ring jewelry arrangement, the outermost
 surface having ends which are pointed away from the
 center of the ring jewelry arrangement and in a direction
 toward the at least one second jewelry finger ring por-
 tion, and the first jewelry finger ring portions do not
 overlap in a circumferential direction about the at least
 one second jewelry finger ring portion;
 wherein the at least one of the first jewelry finger ring
 portions has a first surface that forms at least one first
 section of the at least one through hole and the at least
 one second jewelry finger ring portion has a second

8

surface that forms at least one second section of the at
 least one through hole, the first surface being situated
 opposite to the second surface, and wherein a curvature
 of the first surface is different than a curvature of the
 second surface.

27. The arrangement of claim 26, wherein at least two of
 the first jewelry finger ring portions are provided immediately
 adjacent to one another.

28. The arrangement of claim 27, wherein the at least one
 through hole extends in a direction which is approximately
 perpendicular to a plane extending from the at least one
 second jewelry finger ring portion towards the center.

29. The arrangement of claim 26, wherein the ends are
 permanently and directly connected to the at least one second
 jewelry portion.

30. The arrangement of claim 26, wherein at least one of
 the ends of one of the first jewelry finger ring portions directly
 contacts another one of the first jewelry finger ring portions.

31. The ring jewelry arrangement of claim 26, wherein a
 first curvature of the outermost surface of the at least one of
 the first jewelry finger ring portions is substantially the same
 as the curvature of the first surface of the at least one of the
 first jewelry finger ring portions.

32. The ring jewelry arrangement of claim 26, further com-
 prising at least one gemstone.

* * * * *