



US009339767B2

(12) **United States Patent**
Tanaka et al.

(10) **Patent No.:** **US 9,339,767 B2**
(45) **Date of Patent:** **May 17, 2016**

(54) **MEMBRANE CONTAINER USED IN DEHYDRATOR**

B01D 63/04; B01D 63/046; B01D 63/066;
B01D 5/0012; B01D 5/0006; B01D 5/0052;
B01D 5/0054; B01D 5/0059; B01D 5/005

(75) Inventors: **Yukio Tanaka**, Tokyo (JP); **Shinya Tachibana**, Tokyo (JP); **Hiroyuki Osora**, Tokyo (JP); **Shinji Ogino**, Tokyo (JP); **Haruaki Hirayama**, Tokyo (JP)

USPC 210/180, 184, 186, 321.72, 321.78,
210/321.79, 321.81, 321.87, 321.88, 323.2,
210/640, 644, 649, 650, 651
See application file for complete search history.

(73) Assignee: **MITSUBISHI HEAVY INDUSTRIES, LTD.**, Tokyo (JP)

(56) **References Cited**

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 383 days.

U.S. PATENT DOCUMENTS

4,038,190 A * 7/1977 Baudet et al. 210/321.81
4,261,829 A * 4/1981 Spranger 210/321.81

(Continued)

(21) Appl. No.: **13/818,250**

FOREIGN PATENT DOCUMENTS

(22) PCT Filed: **Sep. 1, 2011**

JP 5-76594 U 10/1993
JP 2001-509074 A 7/2001

(86) PCT No.: **PCT/JP2011/069877**

(Continued)

§ 371 (c)(1),
(2), (4) Date: **Apr. 4, 2013**

OTHER PUBLICATIONS

(87) PCT Pub. No.: **WO2012/035986**

Notice of Allowance dated Jul. 4, 2014, issued in Corresponding Japanese Patent Application No. 2010-209228 with English Translation (6 pages).

PCT Pub. Date: **Mar. 22, 2012**

(Continued)

(65) **Prior Publication Data**

US 2013/0186818 A1 Jul. 25, 2013

Primary Examiner — David C Mellon

Assistant Examiner — Pranav Patel

(30) **Foreign Application Priority Data**

Sep. 17, 2010 (JP) 2010-209228

(74) *Attorney, Agent, or Firm* — Westerman, Hattori, Daniels & Adrian, LLP

(51) **Int. Cl.**

B01D 63/00 (2006.01)

B01D 63/06 (2006.01)

(Continued)

(57) **ABSTRACT**

A membrane container 6 has a casing 10 including a fluid inlet 14 and a fluid outlet 16 and a membrane container body 9 including a plurality of flow paths 11 which is arranged along the flow direction of the treated fluid and in parallel to one another. Each of the plurality of flow paths 11 includes a most upstream portion 11A which is connected to the fluid inlet 14, and a most downstream portion 11C which is connected to the fluid outlet 16. Return portions 15 and 17 configured to reverse the flow direction of the treated fluid are provided between the most upstream portion 11A and the most downstream portion 11C. After passing through the fluid inlet 14, the treated fluid flows from the most upstream portion 11A down to the most downstream portion 11C via the return portions 15 and the upper return portion 17.


(52) **U.S. Cl.**

CPC **B01D 63/00** (2013.01); **B01D 61/368** (2013.01); **B01D 63/066** (2013.01); **B01D 65/00** (2013.01); **B01D 2313/08** (2013.01); **B01D 2313/086** (2013.01); **B01D 2313/20** (2013.01)

(58) **Field of Classification Search**

CPC C02F 1/44; C02F 1/448; B01D 2313/22; B01D 24/004; B01D 24/008; B01D 29/23; B01D 29/232; B01D 29/235; B01D 29/52; B01D 29/54; B01D 29/56; B01D 29/58;

4 Claims, 5 Drawing Sheets



(51) **Int. Cl.**
B01D 61/36 (2006.01)
B01D 65/00 (2006.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,732,673	A *	3/1988	Dagard et al.	210/247
5,288,308	A *	2/1994	Puri et al.	96/8
5,788,826	A	8/1998	Nyberg	
2002/0162455	A1 *	11/2002	Bikson et al.	96/8
2003/0121840	A1 *	7/2003	Pex et al.	210/185
2004/0149647	A1 *	8/2004	Hampton et al.	210/497.01
2004/0211726	A1 *	10/2004	Baig et al.	210/640
2006/0011535	A1 *	1/2006	Ikeda et al.	210/321.79
2009/0008341	A1 *	1/2009	Townson et al.	210/767
2010/0116727	A1	5/2010	Tachibana et al.	
2011/0024342	A1 *	2/2011	Fujita et al.	210/184

FOREIGN PATENT DOCUMENTS

JP	2003-103151	A		4/2003
JP	WO2009118934		*	1/2009
JP	2009-66503	A		4/2009
JP	2010-115596	A		5/2010
JP	WO2011065467		*	3/2011

OTHER PUBLICATIONS

International Search Report for PCT/JP2011/069877, mailing date of Dec. 13, 2011.

Translation of the International Preliminary Report on Patentability (PCT/IB/338) (1 page), (PCT/IB/373) (1 page) of International Application No. PCT/JP2011/069877 mailed Apr. 25, 2013 (Form PCT/ISA/237) (3 pages).

* cited by examiner

FIG.1




FIG.2




FIG.3(a)




FIG.3(b)




FIG.4




FIG.5(a)

FIG.5(b)




FIG.6





FIG.7(a)

FIG.7(b)



1

MEMBRANE CONTAINER USED IN
DEHYDRATOR

TECHNICAL FIELD

The present invention relates to a dehydrator for dehydrating a mixture (treated fluid) of water with ethanol which forms an azeotropic composition with water. More specifically, the present invention relates to a membrane container included in a dehydrator having water separation membranes.

BACKGROUND ART

In recent years, ethanol has attracted attention as a fuel source alternative to petroleum fuels. However, for adopting ethanol as a fuel, it is necessary to purify, by distillation, a crude product obtained from a biomass such as corn, and then to perform dehydration until at least 99.5 wt % is reached.

Known conventional dehydration methods include a method for separating water from the treated fluid by the pervaporation method (penetrative vaporization (PV) method) using a water separation membrane (see, for example, Patent Literature 1). In the dehydrator discussed by Patent Literature 1, a plurality of columnar water separation membranes is arranged inside a shell part in series. Each water separation membrane is provided with a plurality of flow paths, each of which having a predetermined diameter. In the water separation membrane described above, the treated fluid simultaneously flows through all the flow paths at a predetermined velocity and water is separated from the treated fluid while the treated fluid flows through the flow paths.

CITATION LIST

Patent Literature

PTL 1: Japanese Patent Application Laid-Open No. 2010-115596

PTL 2: Japanese Patent Application Laid-Open No. 2003-103151

SUMMARY OF INVENTION

Technical Problem

Incidentally, it is conventionally known that the water separation performance may greatly vary according to the velocity of flow of treated fluid in the configuration that uses the above-described water separation membranes. This phenomenon will be described in detail below.

FIG. 6 illustrates a ratio of quantity of permeated water to the quantity of permeation of a matter (containing water and ethanol) that has permeated through water separation membranes. Referring to FIG. 6, the ratio of quantity of permeated water is about 1 at the velocity of flow of approximately 0.6 m/s. The ratio of quantity of permeated water to the quantity of a matter permeated through the water separation membranes becomes lower as the flow velocity of the treated fluid becomes lower. As described above, if water separation membranes are used and if the flow velocity of the treated fluid is low, the ratio of permeated water to the matter permeated through the water separation membranes becomes low. As a result, the water separation performance may degrade.

In addition, if the flow velocity of the treated fluid is low, the problem may arise such that concentration polarization may occur in the vicinity of the water separation membranes.

2

The term "concentration polarization" refers to a phenomenon that may occur in the vicinity of water separation membranes, in which a dissolved matter (water in the example illustrated in FIG. 6) that does not permeate through water separation membranes produce a gradient of concentration in the direction perpendicular to the water separation membrane.

FIGS. 7A and 7B illustrate a case where the concentration polarization is produced and another case where the concentration polarization is not produced. More specifically, FIG. 7A illustrates a case where the flow velocity of the treated fluid is low. FIG. 7B illustrates a case where the flow velocity of the treated fluid is high. As illustrated in a chart (1) of FIG. 7A, if the flow velocity of the treated fluid is low, the concentration of water becomes lower as the distance to the water separation membrane becomes smaller while the concentration of water becomes higher as the distance to the water separation membrane in the direction perpendicular to the water separation membrane (in the direction of the cross section) becomes greater. As a result of such concentration polarization, referring to the change of the concentration of water in the direction of flow of the treated fluid illustrated in the chart (2) of FIG. 7A, the concentration of water hardly becomes low. Accordingly, it is known that the water separation performance is problematically low. On the other hand, as illustrated in the chart (1) of FIG. 7B, if the flow velocity of the treated fluid is sufficiently high, water permeates through the water separation membranes. Accordingly, no concentration polarization occurs. As a result, referring to the change of the concentration of water in the direction of flow of the treated fluid illustrated in the chart (2) of FIG. 7B, the concentration of water gradually becomes lower. Accordingly, it is known that a sufficiently high water separation performance is achieved.

For example, when a 200,000 t/year-ethanol treatment is considered, the following problems may arise for the conventional water separation membrane discussed by Patent Literature 1. In the conventional water separation membrane discussed by Patent Literature 1, the treated fluid is allowed to simultaneously flow through all the flow paths. Accordingly, the cross section of the flow path (i.e., the cross section in the direction perpendicular to the treated fluid) is large in relation to the flow rate of the treated fluid. Therefore, the flow velocity of the treated fluid cannot become high. As a result, a sufficiently high water separation performance cannot be achieved. As a matter of course, in carrying out a treatment of 200,000 t/year-ethanol or less, the water separation performance may become further lower because the flow velocity of the treated fluid further decreases. In other words, a problem such that the dehydrator cannot be scaled down due to the degraded water separation performance may arise. In addition, in order to increase the flow velocity of the treated fluid, the capacity of a pump may be increased. However, costs for the apparatus may increase in this case. Accordingly, it is necessary to take measures for increasing the velocity of flow without increasing the capacity of the pump.

The present invention is devised to solve the above-described problems. The object of the present invention is to provide a membrane container, which is used in a dehydrator and capable of increasing the velocity of flow of treated fluid and of achieving a sufficiently high water separation performance.

Solution to Problem

In order to solve the above-described problems arising in the conventional techniques, according to an aspect of the

present invention, a membrane container includes a casing which includes a fluid inlet through which treated fluid flows in, and a fluid outlet from which the treated fluid flows out, and a membrane container body including a plurality of flow paths arranged along a flow direction of the treated fluid and in parallel to one another. In the membrane container, water is separated from the treated fluid while the treated fluid passes through the plurality of flow paths, the plurality of flow paths includes a most upstream portion connected to the fluid inlet, and a most downstream portion connected to the fluid outlet, a return portion for reversing the flow direction of the treated fluid is provided between the most upstream portion and the most downstream portion, and the treated fluid, after passing through the fluid inlet, is allowed to flow from the most upstream portion down to the most downstream portion via the return portion.

In addition, according to an aspect of the present invention, an intermediate portion in which the flow direction of the treated fluid is reversed by the return portion at least once is provided between the most upstream portion and the most downstream portion of the plurality of flow paths, and the treated fluid, after passing through the fluid inlet, is allowed to flow from the most upstream portion to the most downstream portion via the intermediate portion by successively passing through the most upstream portion, the intermediate portion, and the most downstream portion in this order.

In addition, according to an aspect of the present invention, the most upstream portion is arranged around the center axis of the membrane container body, the intermediate portion is arranged in an outer periphery of the most upstream portion, and the most downstream portion is arranged in an outer periphery of the intermediate portion.

Moreover, in the aspect of the present invention, it is more useful if an aggregate cross section of the most upstream portion in a direction perpendicular to the flow direction of the treated fluid, an aggregate of the cross section of the most downstream portion, and an aggregate of the cross section of a portion of the intermediate portion of the flow path, in which the treated fluid flows in the same direction and which is located n-th (n is an integer of 1 or greater) from the most upstream portion, are set the same as one another.

Advantageous Effects of Invention

According to an aspect of the present invention, a membrane container, which is used in the dehydrator of the present invention, includes a casing which includes a fluid inlet through which treated fluid flows in, and a fluid outlet from which the treated fluid flows out, and a membrane container body including a plurality of flow paths arranged along a flow direction of the treated fluid and in parallel to one another. In the membrane container, water is separated from the treated fluid while the treated fluid passes through the plurality of flow paths, the plurality of flow paths includes a most upstream portion connected to the fluid inlet, and a most downstream portion connected to the fluid outlet, a return portion for reversing the flow direction of the treated fluid is provided between the most upstream portion and the most downstream portion, and the treated fluid, after passing through the fluid inlet, is allowed to flow from the most upstream portion down to the most downstream portion via the return portion. In the conventional technique, a sufficiently high flow velocity cannot be achieved because the treated fluid simultaneously flows through all flow paths of the membrane container body and thus the cross section of the flow path (i.e., the cross section in the direction perpendicular to the flow direction of the treated fluid) is large in relation to

the flow rate of the treated fluid. According to an aspect of the present invention, the cross section of the flow path is small in relation to the flow rate of the treated fluid because each of the plurality of flow paths is divided into a most upstream portion and a most downstream portion. Accordingly, a high flow velocity of the treated fluid that flows in the membrane container body can be achieved if a pump similar to that used in the conventional configuration is used. With the above-described configuration, no concentration polarization may occur in the membrane container body. Accordingly, a sufficiently high water separation performance can be secured. In addition, in an aspect of the present invention, because the treated fluid can flow in the membrane container body at a sufficiently high flow velocity, the dehydrator can be readily scaled down without degrading the water separation performance.

In addition, according to an aspect of the present invention, in the membrane container used in the dehydrator of the present invention, an intermediate portion in which the flow direction of the treated fluid is reversed by the return portion at least once is provided between the most upstream portion and the most downstream portion of the plurality of flow paths, and the treated fluid, after passing through the fluid inlet, is allowed to flow from the most upstream portion to the most downstream portion via the intermediate portion by successively passing through the most upstream portion, the intermediate portion, and the most downstream portion in this order. Accordingly, the cross section of the flow path is small in relation to the flow rate of the treated fluid. As a result, the flow velocity of the treated fluid that flows in the membrane container body can be further increased. Accordingly, the present invention can more efficiently prevent concentration polarization. Therefore, a sufficiently high water separation performance can be secured.

Furthermore, according to an aspect of the present invention, in the membrane container used in the dehydrator of the present invention, the most upstream portion is arranged around the center axis of the membrane container body, the intermediate portion is arranged in an outer periphery of the most upstream portion, and the most downstream portion is arranged in an outer periphery of the intermediate portion. Accordingly, the membrane container is configured so that the treated fluid is allowed to pass through components of the membrane container successively from the center toward to outside of the membrane container. As a result, the casing of the membrane container can be more simplified.

In addition, according to an aspect of the present invention, in the membrane container used in the dehydrator of the present invention, an aggregate cross section of the most upstream portion in a direction perpendicular to the flow direction of the treated fluid, an aggregate of the cross section of the most downstream portion, and an aggregate of the cross section of a portion of the intermediate portion of the flow path, in which the treated fluid flows in the same direction and which is located n-th (n is an integer of 1 or greater) from the most upstream portion, are set the same as one another. Accordingly, the flow velocity of the treated fluid that flows through each portion of the flow path can be maintained in a specific range. With the above-described configuration, a sufficiently high water separation performance can be achieved in each portion of each of the plurality of flow paths because the water separation performances of the portions of the plurality of flow paths are not different from one another.

BRIEF DESCRIPTION OF DRAWINGS

FIG. 1 is a schematic diagram illustrating the entire dehydrator according to an exemplary embodiment of the present invention.

5

FIG. 2 is a perspective view of a membrane container according to an exemplary embodiment of the present invention.

FIGS. 3A and 3B are diagrams illustrating a membrane container body of the membrane container according to an exemplary embodiment of the present invention. More specifically, FIG. 3A is a cross sectional view of the membrane container body and FIG. 3B is a longitudinal section (section along the longitudinal direction) of the membrane container body.

FIG. 4 is a cross section of FIG. 2 taken along the line A-A.

FIGS. 5A and 5B are plan views of the membrane container according to an exemplary embodiment of the present invention. More specifically, FIG. 5A is a plan view of the membrane container viewed from above and FIG. 5B is a plan view of the membrane container viewed from below.

FIG. 6 is a diagram illustrating a ratio of the quantity of permeation of water to the quantity of permeation of a matter (containing water and ethanol) that has permeated through water separation membranes.

FIG. 7A is a diagram illustrating a case in which concentration polarization has occurred because the velocity of flow of treated fluid is low.

FIG. 7B is a diagram illustrating a case in which the concentration polarization has not occurred because the flow velocity of the treated fluid is high.

DESCRIPTION OF EMBODIMENTS

Now, a dehydrator according to an exemplary embodiment of the present invention will be described below with reference to the attached drawings. FIG. 1 is a schematic diagram illustrating the entire dehydrator according to an exemplary embodiment of the present invention.

The dehydrator 1 according to the present exemplary embodiment is configured to dehydrate a crude ethanol aqueous solution used as treated fluid. The inventors assume approximately 91 wt % of the concentration of ethanol for the concentration of the crude ethanol aqueous solution. The dehydrator 1 is configured to treat and purify crude ethanol containing ethanol as an organic component to finally produce product ethanol (absolute ethanol) whose ethanol concentration is in the range of 99.5 to 99.8 wt %.

Referring to FIG. 1, the dehydrator 1 is constituted by a first tank 2, to which treated fluid (a crude ethanol aqueous solution) is supplied, a second tank 3, into which the dehydrated product ethanol flows, a plurality of water separation membrane units 4A through 4E provided between the first tank 2 and the second tank 3, and a third tank 5, into which water separated from the treated fluid flows.

As illustrated in FIG. 1, the plurality of water separation membrane units 4A through 4E is connected in series. Each of the plurality of water separation membrane units 4A through 4E is provided with a membrane container 6 (see FIG. 2), which will be described below. Each water separation membrane units 4A through 4E is configured to separate water by the pervaporation method, in which the supply side is a liquid phase and the permeation side is a gas phase. In the present exemplary embodiment, for the membrane container 6 of the water separation membrane units 4A through 4E, a flow path for the treated fluid is referred to as the "supply side", and the outside of the membrane container 6 is referred to as the "permeation side". The treated fluid flows into the water separation membrane units 4A through 4E in a state in which the permeation side of the water separation membrane units 4A through 4E is decompressed by a decompressor (not illustrated). Accordingly, the water contained in the treated fluid

6

becomes steam, and the steam is drawn out toward the permeation side. As illustrated in FIG. 1, the steam drawn out by each of the water separation membrane units 4A through 4E flows into the third tank 5.

As illustrated in FIG. 1, respective heat exchangers 7A through 7E and the water separation membrane units 4A through 4E are provided alternately to one another. It is generally known that when the pervaporation method is used, the velocity of water permeation decreases due to the temperature decrease of the treated fluid. Accordingly, the heat exchangers 7A through 7E are configured to heat the treated fluid that flows into the water separation membrane units 4A through 4E to prevent the temperature decrease of the treated fluid.

With the above-described configuration, in the dehydrator 1 according to the present exemplary embodiment, the treated fluid supplied to the first tank 2 is then fed from the pump 8 and is allowed to flow into the heat exchanger 7A, the water separation membrane unit 4A, the heat exchangers 7B, the water separation membrane unit 4B, the heat exchanger 7C, the water separation membrane unit 4C, the heat exchanger 7D, the water separation membrane unit 4D, the heat exchanger 7E, the water separation membrane unit 4E in this order. After passing through the most downstream water separation membrane unit 4E, the treated fluid flows into the second tank 3 and is then recovered as product ethanol. In addition, as illustrated in FIG. 1, the steam drawn out by each of the water separation membrane units 4A through 4E flows into the third tank 5.

FIG. 2 is a diagram which illustrates the membrane container 6 provided in each of the water separation membrane unit 4A through 4E according to the present exemplary embodiment. In the present exemplary embodiment, each of the water separation membrane units 4A through 4E (see FIG. 1) is provided with the membrane container 6. Referring to FIG. 2, the membrane container 6 has: a membrane container body 9; and a casing 10 which engages the membrane container body 9.

FIGS. 3A and 3B are diagrams which illustrate the membrane container body 9 of the membrane container 6 according to the present exemplary embodiment. More specifically, FIG. 3A is a cross sectional view of the membrane container body 9 and FIG. 3B is a longitudinal section (section along the longitudinal direction) of the membrane container body 9. The membrane container body 9 is constituted by a monolithic-type water separation membrane and has a columnar shape. Referring to FIGS. 3A and 3B, the membrane container body 9 is provided with a plurality of flow paths 11, which is formed in parallel to one another along the longitudinal direction of the membrane container body 9. The membrane container body 9 is provided in each of the water separation membrane units 4A through 4E so that the direction of flow of the treated fluid becomes parallel to the direction of extension of the flow path 11.

As illustrated in FIGS. 3A and 3B, after flowing into the water separation membrane units 4A through 4E, the treated fluid flows through the flow path 11 of the membrane container body 9 (i.e., the supply side). Then, the water contained in the treated fluid becomes steam, and the steam is drawn out by the decompression operation executed by a decompressor (not illustrated).

Note that in FIGS. 3A and 3B, the membrane container body 9 is illustrated in outlines with the dimension of each hole indicating the flow path 11 being exaggerated for easier understanding. As the material of the membrane container body 9, an inorganic porous membrane in which holes on the order of nanometers or smaller are controlled precisely can be used. The porous membrane having fine holes achieves a

molecule sieving effect of allowing small-molecule gases to pass through and exclude large-molecule gases, and exhibits a behavior of activation diffusion in which the permeation factor thereof increases with the increase in temperature. As an example of a porous membrane having fine holes, a carbon membrane, a silica membrane, and a zeolite membrane can be mentioned.

Also, the inorganic water separating membrane described in Japanese Patent No. 2808479 can also be applied. The inorganic water separating membrane described in Japanese Patent No. 2808479 is an acid-resistant composite separation membrane obtained by carrying silica gel obtained through hydrolysis of alkoxysilane containing an ethoxy group or methoxy group in the fine holes of an inorganic porous body. Note that, as a porous base member on which the inorganic water separation membrane is carried, a base member of a ceramic such as alumina, silica, zirconia, or titania is usually used, and a preferable base member is a tubular base member having a plurality of flow paths (inner tubes) which extends in the longitudinal direction and each of which have a circular cross-section. The inorganic water separation membrane is formed in a way to cover inner walls of such inner tubes.

Besides the inorganic water separation membrane, an organic membrane such as a polyvinyl alcohol membrane, a polyimide membrane or a polyamide membrane can be used as the water separation membrane.

Note that for the membrane container body **9**, a membrane container body having a diameter of 180 mm, a length in the longitudinal direction of 1,000 mm, and a columnar shape, for example, can be used. In this example, 2,000 flow paths each having a diameter of 3 mm are provided in the longitudinal direction of the membrane container body **9**. Note that the material and the size of the membrane container body **9** and the diameter, the quantity, and the like of the flow paths can be selected by a person having ordinary skill in the art according to their purpose of use.

Now, characteristics of the membrane container **6** according to the present exemplary embodiment will be described in detail below. FIG. **4** is a cross section of FIG. **2** taken along the line A-A. FIGS. **5A** and **5B** are plan views of the membrane container **6**. More specifically, FIG. **5A** is a plan view of the membrane container **6** viewed from above and FIG. **5B** is a plan view of the membrane container **6** viewed from below.

Referring to FIG. **4**, the plurality of flow paths **11** of the membrane container body **9** according to the present exemplary embodiment is constituted by a most upstream portion **11A** which is located the most upstream, an intermediate portion **11B** which is located the second most upstream, and a most downstream portion **11C** which is located the most downstream. The most upstream portion **11A** is arranged around the center axis (the radial center) of the membrane container body **9**. The intermediate portion **11B** is arranged in a radial outer periphery with respect to the most upstream portion **11A**. In addition, the most downstream portion **11C** is arranged in a radial outer periphery with respect to the intermediate portion **11B**.

As illustrated in FIGS. **3A**, **3B**, **4**, **5A**, and **5B**, the casing **10** of the membrane container **6** has: a lower shell part **12** which is arranged on a lower end **9b** of the membrane container body **9**; and an upper shell part **13** which is arranged on an upper end **9c** of the membrane container body **9**.

As illustrated in FIGS. **4**, **5A**, and **5B**, a round fluid inlet **14**, through which the treated fluid flows, is provided in the substantially radial center of the lower shell part **12**. The fluid inlet **14** of the lower shell part **12** is connected to the most upstream portion **11A** of the flow path **11**. In addition, in the periphery of the fluid inlet **14** of the lower shell part **12**, a

lower return portion **15** for connecting between the intermediate portion **11B** and the most downstream portion **11C** of the flow path **11** is provided. The lower return portion **15** is formed by forming a recess on the contact surface between the lower shell part **12** and the membrane container body **9**. The lower return portion **15** is configured to reverse the direction of flow of the treated fluid that flows through the intermediate portion **11B** to allow the treated fluid to flow into the most downstream portion **11C**.

As illustrated in FIGS. **4**, **5A**, and **5B**, the upper shell part **13** is provided with a fluid outlet **16**, which is formed along the circumferential direction of the upper end **9c** of the membrane container body **9**. The fluid outlet **16** is connected to the most downstream portion **11C** of the flow path **11**. In addition, in the substantially radial center of the upper shell part **13**, an upper return portion **17** for connecting between the most upstream portion **11A** and the intermediate portion **11B** of the flow path **11** is provided. The upper return portion **17** is formed by forming a recess on the contact surface between the upper shell part **13** and the membrane container body **9**. The upper return portion **17** is configured to reverse the direction of flow of the treated fluid that has flowed from the most upstream portion **11A** to allow the treated fluid to flow into the intermediate portion **11B**.

With the above-described configuration, in the membrane container **6** according to the present exemplary embodiment, after flowing in through the fluid inlet **14** of the lower shell part **12**, the treated fluid flows into the most upstream portion **11A** of the flow path **11**, the upper return portion **17**, the intermediate portion **11B** of the flow path **11**, the lower return portion **15**, the most downstream portion **11C** of the flow path **11**, and the fluid outlet **16** of the upper shell part **13** successively in this order. During the operation described above, water contained in the treated fluid becomes steam, and the steam is drawn out by a decompression operation carried out by the decompressor from a side surface **9a** of the membrane container body **9** to the outside of the membrane container body **9**.

Note that in the present exemplary embodiment, it is more useful if the flow velocity of the treated fluid that flows through the most upstream portion **11A**, the intermediate portion **11B**, and the most downstream portion **11C** is set within a specific range. More specifically, for example, this flow velocity can be set so that the aggregate radial cross section (the term "radial" herein refers to a direction perpendicular to the flow direction of the treated fluid) of the most upstream portion **11A**, the aggregate radial cross section of the intermediate portion **11B**, and the aggregate radial cross section of the most downstream portion **11C** become the same as one another. For example, if all the flow paths **11** have the same diameter, the same quantity of the flow paths **11** can be assigned to each of the most upstream portion **11A**, the intermediate portion **11B**, and the most downstream portion **11C**. With the above-described configuration, the most upstream portion **11A**, the intermediate portion **11B**, and the most downstream portion **11C** can have substantially the same aggregate radial cross section. Furthermore, with the above-described configuration, it is enabled to maintain the flow velocity of the treated fluid that flows through the most upstream portion **11A**, the intermediate portion **11B**, and the most downstream portion **11C** within a specific range.

According to the present exemplary embodiment, the membrane container **6** of the dehydrator **1** is provided with the fluid inlet **14** through which the treated fluid flows, the casing **10** having the fluid outlet **16** from which the treated fluid flows out, and the membrane container body **9** having the plurality of flow paths **11** provided along the flow direc-

tion of the treated fluid and in parallel to one another. The plurality of flow paths **11** is constituted by the most upstream portion **11A**, which is located at the most upstream location, the intermediate portion **11B**, which is located at the second most upstream location, and the most downstream portion **11C**, which is located at the most downstream location. The upper return portion **17** configured to reverse the flow direction of the treated fluid is provided between the most upstream portion **11A** and omitted portion **11B**, and the lower return portion **15** configured to reverse the flow direction of the treated fluid is provided between the intermediate portion **11B** and the most downstream portion **11C**. With this configuration, after flowing in through the fluid inlet **14**, the treated fluid successively passes through the most upstream portion **11A** and the intermediate portion **11B** and flows into the most downstream portion **11C**. For example, when a 200,000 t/year-ethanol treatment is considered and if the conventional water separation membrane discussed by Patent Literature 1 is used for this treatment, the treated fluid simultaneously flows through all flow paths of the membrane container body. Accordingly, the cross section of the flow path (i.e., the cross section in the direction perpendicular to the flow direction of the treated fluid) is large in relation to the flow rate of the treated fluid. As a result, a sufficiently high flow velocity cannot be achieved. On the contrary, according to the membrane container **6** of the dehydrator **1** of the present exemplary embodiment, the cross section of the flow path is small in relation to the flow rate of the treated fluid. Accordingly, a high flow velocity of the treated fluid that flows in the membrane container body **9** can be achieved if a pump similar to that used in the conventional configuration is used. As a result, no concentration polarization may occur in the membrane container body **9**. Accordingly, the present exemplary embodiment can secure a sufficiently high water separation performance.

In addition, in carrying out a treatment of 200,000 t/year-ethanol or less by using the conventional technique, a problem may arise such that the dehydrator **1** cannot be scaled down due to the degraded water separation performance. On the contrary, according to the membrane container **6** of the dehydrator **1** of the present exemplary embodiment, the treated fluid can flow in the membrane container body **9** at a sufficiently high flow velocity. Accordingly, the dehydrator **1** can be readily scaled down without degrading the water separation performance.

Note that in the present exemplary embodiment, it is useful if the flow velocity of the treated fluid that flows in the membrane container **6** is set at 0.4 m/s or higher. If the flow velocity is set at 0.4 m/s or higher, it is highly likely that concentration polarization can be prevented because the flow of the treated fluid becomes a turbulent flow. In addition, in order to further improve the water separation performance, it is more useful if the flow velocity of the treated fluid is set at 1.0 m/s.

Moreover, in the membrane container **6** of the dehydrator **1** according to the present exemplary embodiment, the most upstream portion **11A** is arranged in the periphery of the center axis (the radial center) of the membrane container body **9**, the intermediate portion **11B** is arranged in the radial outer periphery in relation to the most upstream portion **11A**, and the most downstream portion **11C** is arranged in the radial outer periphery in relation to the intermediate portion **11B**. In other words, the membrane container **6** has a configuration with which the treated fluid successively flows in the membrane container body **9** and passes through the components of the membrane container body **9** from the center toward the

outside thereof. Accordingly, the configuration of the casing **10** of the membrane container **6** can be more simplified.

In addition, according to the membrane container **6** of the dehydrator **1**, the aggregate cross sections of the portions of the plurality of flow paths **11** are set so that the aggregate radial cross section (i.e., the cross section in the direction perpendicular to the flow direction of the treated fluid) of the most upstream portion **11A**, the aggregate radial cross section of the intermediate portion **11B**, and the aggregate radial cross section of the most downstream portion **11C** become the same as one another. Accordingly, the flow velocity of the treated fluid in the portions **11A** through **11C** of the plurality of flow paths **11** becomes constant. As a result, a sufficiently high water separation performance can be achieved in each portion of each of the plurality of flow paths **11** because the water separation performances of the portions **11A** through **11C** of the plurality of flow paths **11** are not different from one another.

Exemplary embodiments of the present invention are described above. However, the present invention is not limited to the exemplary embodiments described above and can be implemented by various modifications and alterations based on the technical idea of the present invention.

In the present exemplary embodiment, the most upstream portion **11A**, the intermediate portion **11B**, and the most downstream portion **11C** are arranged so that the treated fluid flows in the membrane container **6** and successively passes through the portions from the center toward the outside. However, the configuration of the present invention is not limited to this. For example, the most upstream portion **11A**, the intermediate portion **11B**, and the most downstream portion **11C** can be arranged so that the treated fluid successively passes through the portions radially from the outside of the membrane container body **9** toward the center thereof.

In the present exemplary embodiment, the plurality of flow paths **11** is constituted by three portions, i.e., the most upstream portion **11A**, the intermediate portion **11B**, and the most downstream portion **11C**. However, the configuration of the flow path **11** is not limited to this. For example, the flow path **11** can be configured so that the flow direction of the treated fluid is reversed at least once in the membrane container body **9**. In addition, alternatively, the plurality of flow paths **11** can be constituted by two portions including the most upstream portion **11A** and the most downstream portion **11C**.

Further alternatively, the flow path **11** can be configured so that the flow direction of the treated fluid is reversed for a plurality of times in the intermediate portion **11B**. For example, the intermediate portion **11B** of the flow path **11** can be further divided into three sub portions. In this case, the intermediate portion **11B** includes: a first sub portion in which the treated fluid flows downwards after returning from the most upstream portion **11A**; a second sub portion in which the treated fluid flows upwards after returning from the first sub portion; and a third sub portion in which the treated fluid flows downwards after returning from the second sub portion. In this configuration, the first sub portion of the intermediate portion **11B** is a portion located the most upstream from the most upstream portion **11A**, the second sub portion thereof is a portion located the second most upstream from the most upstream portion **11A**, and the third sub portion thereof is a portion located the third most upstream from the most upstream portion **11A**. In the configuration described above, in order to achieve a constant flow velocity of the treated fluid in each portion of the flow path **11**, the aggregate cross sections can be set so that the aggregate radial cross section of the most upstream portion **11A**, the aggregate radial cross section

11

of the first sub portion of the intermediate portion 11B, the aggregate radial cross section of the second sub portion of the intermediate portion 11B, the aggregate radial cross section of the third sub portion of the intermediate portion 11B, and the aggregate radial cross section of the most downstream portion 11C become the same as one another.

In the present exemplary embodiment, treated fluid that contains ethanol as its organic component is used as the target of the dehydration. However, the present invention, which uses the membrane container 6 described above, is not limited to this and can be applied if the treated fluid is an organic aqueous solution. For example, the organic component contained in the organic water solution can be an organic component selected from the group consisting of alcohol such as ethanol, propanol, isopropanol, glycol; carboxylic acid such as acetic acid; ether such as dimethyl ether, diethyl ether; aldehyde, such as acetaldehyde; ketone such as acetone, methyl ethyl ketone; and ester such as ethyl acetate ester.

REFERENCE SIGNS LIST

- 1: Dehydrator
- 2: First tank
- 3: Second tank
- 4A, 4B, 4C, 4D, 4E: Water separation membrane unit
- 5: Third tank
- 6: Membrane container
- 7A, 7B, 7C, 7D, 7E: Heat exchanger
- 8: Pump
- 9: Membrane container body
- 10: Casing
- 11: Flow path
- 11A: Most upstream portion of the flow path
- 11B: Intermediate portion of the flow path
- 11C: Most downstream portion of the flow path
- 12: Lower shell part of the casing
- 13: Upper shell part of the casing
- 14: Fluid inlet
- 15: Lower return portion
- 16: Fluid outlet
- 17: Upper return portion

The invention claimed is:

1. A membrane container comprising:

a casing that comprises:

- a fluid inlet through which treated fluid flows in; and
- a fluid outlet from which the treated fluid flows out; and
- a membrane container body including a plurality of flow paths arranged along a flow direction of the treated fluid and in parallel to one another,

wherein the membrane container body has a shape of a cylinder;

wherein water is separated from the treated fluid while the treated fluid passes through the plurality of flow paths;

wherein the plurality of flow paths comprises:

- a most upstream portion connected to the fluid inlet; and
 - a most downstream portion connected to the fluid outlet,
- wherein each of the most upstream portion and the most downstream portion includes a plurality of flow paths;

12

wherein each of the flow paths constituting the most upstream portion extends in an axial direction of the cylinder, and is arranged in a spaced manner around a center axis of the cylinder;

wherein each of the flow paths constituting the most downstream portion extends in an axial direction of the cylinder, and is arranged in a spaced manner radially outward of the most upstream portion;

wherein a passage-folding portion for reversing the flow direction of the treated fluid is provided between the most upstream portion and the most downstream portion;

wherein the treated fluid, after passing through the fluid inlet, is allowed to flow to the most upstream portion constituted by the respective flow paths, to merge at the passage-folding portion, and to flow down to the most downstream portion also constituted by the respective flow paths

wherein an intermediate portion in which the flow direction of the treated fluid is reversed by the passage-folding portion at least once is provided between the most upstream portion and the most downstream portion of the plurality of flow paths, and

wherein the treated fluid, after passing through the fluid inlet, is allowed to flow from the most upstream portion to the most downstream portion via the intermediate portion by successively passing through the most upstream portion, the intermediate portion, and the most downstream portion in this order.

2. The membrane container according to claim 1, wherein the intermediate portion is arranged in an outer periphery of the most upstream portion, and wherein the most downstream portion is arranged in an outer periphery of the intermediate portion.

3. The membrane container according to claim 1, wherein an aggregate cross section of the most upstream portion in a direction perpendicular to the flow direction of the treated fluid,

an aggregate cross section of the most downstream portion as viewed in a direction perpendicular to the flow direction of the treated fluid, and

an aggregate cross section of the intermediate portion as viewed in a direction perpendicular to the flow direction of the treated fluid,

are set to be the same.

4. The membrane container according to claim 2, wherein an aggregate cross section of the most upstream portion in a direction perpendicular to the flow direction of the treated fluid,

an aggregate cross section of the most downstream portion as viewed in a direction perpendicular to the flow direction of the treated fluid, and

an aggregate cross section of the intermediate portion as viewed in a direction perpendicular to the flow direction of the treated fluid,

are set to be the same.

* * * * *