



US009353525B1

(12) **United States Patent**
Richard et al.

(10) **Patent No.:** **US 9,353,525 B1**
(45) **Date of Patent:** ***May 31, 2016**

(54) **SEMI-RIGID CONNECTIONS FOR BRACED FRAMES**

(71) Applicant: **SEISMIC STRUCTURAL DESIGN ASSOCIATES, INC.**

(72) Inventors: **Ralph M. Richard**, Tucson, AZ (US);
James E. Partridge, Pasadena, CA (US); **Clayton J. Allen**, Peoria, AZ (US);
Rudolph E. Radau, Tuscon, AZ (US)

(73) Assignee: **SEISMIC STRUCTURAL DESIGN ASSOCIATES, INC.**, Los Angeles, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 16 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **14/337,327**

(22) Filed: **Jul. 22, 2014**

Related U.S. Application Data

(62) Division of application No. 13/759,591, filed on Feb. 5, 2013, which is a division of application No. 12/342,493, filed on Dec. 23, 2008, now Pat. No. 8,365,476.

(60) Provisional application No. 61/006,188, filed on Dec. 28, 2007.

(51) **Int. Cl.**
E04C 5/06 (2006.01)
E04C 3/02 (2006.01)
E04C 3/09 (2006.01)

(Continued)

(52) **U.S. Cl.**
CPC **E04C 5/0645** (2013.01); **E04C 3/02** (2013.01); **E04C 3/09** (2013.01); **E04H 9/021** (2013.01); **E04C 2003/0404** (2013.01)

(58) **Field of Classification Search**

CPC E04H 9/028; E04B 2001/2415; E04B 2001/2418; E04B 2001/2439; E04B 2001/2448; E04B 2001/2496; E04B 2001/2463; E04B 1/2403; E04B 1/24; E04C 3/02; E04C 3/06; E04C 3/30; E04C 2003/0404

USPC 52/656.9, 167.1, 167.3, 167.4, 655.1, 52/657, 648.1, 638

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,691,712 A * 9/1972 Bowling et al. 52/393
4,409,765 A 10/1983 Pall
4,441,289 A 4/1984 Ikuo et al.

(Continued)

OTHER PUBLICATIONS

Gross, "Experimental Study of Gusseted Connections", Engineering Journal/American Institute of Steel Construction, vol. 27, No. 3, (1990), pp. 89-97.

Lopez et al., "Lessons Learned From Large-Scale Tests of Unbonded Braced Frame Subassemblages", 71st Annual Convention Proceedings, (2002), pp. 171-183.

(Continued)


Primary Examiner — Jessica Laux

(74) *Attorney, Agent, or Firm* — Barnes & Thornburg LLP

(57) **ABSTRACT**

A structural framework that includes a column, a beam, a brace beam coupled at an angle to the column and the beam, and a gusset plate to connect the brace beam with the column and the beam. The framework also includes a shear plate with horizontally slotted holes to couple to the column to the beam. The structural framework may also include double framing angles or a flex plate coupled to the gusset plate and to the beam via spacer plates to provide for a semi-rigid connection.

4 Claims, 14 Drawing Sheets



(51) **Int. Cl.**
E04H 9/02 (2006.01)
E04C 3/04 (2006.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,148,642	A *	9/1992	Plumier et al.	52/167.1
5,680,738	A	10/1997	Allen et al.	
6,022,165	A	2/2000	Lin	
6,237,303	B1	5/2001	Allen et al.	
6,516,583	B1	2/2003	Houghton	
6,591,573	B2 *	7/2003	Houghton	52/656.9
6,837,010	B2 *	1/2005	Powell et al.	52/167.3
6,993,880	B2	2/2006	Cameron et al.	
7,047,695	B2	5/2006	Allen et al.	
7,076,926	B2	7/2006	Kasai et al.	
7,178,296	B2 *	2/2007	Houghton	52/261
7,225,588	B2	6/2007	Nakamura et al.	
7,703,244	B2 *	4/2010	Suzuki et al.	52/167.3
7,784,226	B2	8/2010	Ichikawa et al.	
8,505,260	B1 *	8/2013	Chang et al.	52/704
2003/0009977	A1	1/2003	Houghton	
2009/0025308	A1 *	1/2009	Deans et al.	52/92.2

OTHER PUBLICATIONS

Lopez et al., "Structural Design and Experimental Verification Of A Buckling-Restrained Braced Frame System", Engineering Journal/fFourth Quarter, (2004), pp. 177-186.

Walters et al., "Design for Improved Performance of Buckling-Restrained Braced Frames", Convention Proceedings, (2004), pp. 507-512.

Richard, "Analysis of Large Bracing Connection Designs for Heavy Construction", American Institute of Steel Construction, (2003), pp. 31-1-31-24.

Tsai et al., "Pseudo Dynamic Tests of a Full-Scale CFT/BRB Composite Frame: Displacement Based Seismic Desing and Response Evaluations", Proceedings of the Joint NCREE/JRC Workshop on International Collaboration on Earthquake Mitigation Research, (2003).

Roeder et al., "Braced Frame Gusset Plate Connections for Seismic Design", Convention Proceedings, (2004), pp. 501-505.

Richard, "Braced-Frame Steel Structures 402" When and Why Frame Action Matters, Structural Engineer, (Apr. 2009), pp. 20, 21, 24 and 25.

* cited by examiner




FIG. 1A




FIG. 1B




FIG. 2




FIG. 3A




FIG. 3B




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16

SEMI-RIGID CONNECTIONS FOR BRACED FRAMES

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a divisional application of and claims the priority benefit of U.S. patent application Ser. No. 13/759,591, filed on Feb. 5, 2013, which is a divisional of U.S. Pat. No. 8,365,476, the entire contents of which are incorporated herein by reference, and also claims the priority benefit of U.S. Provisional Patent Application No. 61/006,188, filed on Dec. 28, 2007, which is also incorporated herein by reference.

FIELD OF THE INVENTION

Embodiments of the present invention relate broadly to a method of construction and design of members of load bearing and braced frames and their connections to enhance and provide for high resistance and ductile behavior of the frames when subjected to loading such as gravity, seismic, and wind loading. More specifically, embodiments of the present invention relate to the design and construction of structural frame members and their connections that use gusset plates to join the beams and columns to the lateral load carrying frame brace members. Embodiments of the present invention may be used, but not necessarily exclusively used, in steel frame buildings, in new construction as well as modification of existing structures.

BACKGROUND OF THE INVENTION

In the construction of modern structures such as buildings and bridges, braced frames including beams, columns, and frame braces are arranged and fastened or joined together, using known engineering principles and practices to form a skeletal load resisting framework of the structure. The arrangement of the beams, also known as girders, columns, and braces and their connections are designed to ensure the framework can support the gravity and lateral loads contemplated for the intended use of the bridge, building or other structure. Making appropriate engineering assessments of loads and how these loads are resisted represents current design methodology. These assessments are compounded in complexity when considering loads for wind and seismic events, and determining the forces, stresses, and strains. It is well known that during an earthquake, the dynamic horizontal and vertical inertia loads and stresses and strains imposed on a structure have the greatest impact on the connections of the beams, columns, and braces which constitute the seismic damage resistant frame. Under high seismic or wind loading or even from repeated exposure to milder loadings, the connections in the structure may fail, possibly resulting in the collapse of the structure and the loss of life.

The beams and columns are typically, but not limited to, conventional rolled or built up steel I-beams, also known as W sections or wide flange sections, or box sections also known as tube sections. The frame brace members may have similar shapes as the beams and columns but may also be single or double angles or channels or tubular or tee shaped members. The beams, columns and braces are usually joined using what is known in the structural engineering profession as gusset plates. The presence of these gusset plates, which may be typically either bolted or welded to the joined members, causes the structure members to be rigidly joined so that the structural frame becomes, in essence, a braced-moment frame which results in unintentional overloading of the frame

members (Richard 1986). Results of full scale tests conducted by Tsai et al. (2003), Lopez et al (2002, 2004), Gross (1990), and Roeder et al. (2004) demonstrate that stiff beam-column-brace connections attract large force and moment demands, which can lead to high moments and shears in the beams and columns. These unintentional high moments and shears in the joined members of the braced frame can result in premature fracture modes of the structural members when the frame is subjected to the design gravity, seismic, and wind loadings because these forces are not considered in the frame design. Evaluation of the full scale tests by Walters et al (2004) have shown that in conventionally designed braced frames, the moment frame action caused by the unintentional and undesirable beam and column moments and shears alone will provide a large part of the braced frame's resistance to lateral loads.

As previously stated, in conventionally braced frame designs, moment frame action caused by the gusset plates result in unintentional and undesirable moments and shears in the beams and columns. This can lead to fractures in the beam and column flanges and/or webs when the frame is subjected to lateral seismic or wind loading. Conventionally braced frame designs resist lateral load in a combination of braced frame action and moment frame action.

In the current practice of braced frame design, the beam-to-column connection at the brace gusset is normally a rigid welded and/or bolted assembly to the beam and column which creates a stiff moment resisting connection that generates moments and shears in the braced frame that are not accounted for in the braced frame design rationale. Both analytical studies and full scale tests have demonstrated the drift or displacement related joint rotation can result in the following potentially serious structural effects on the components of the braced frame: (1) a pinching or an in-plane crushing effect of the gusset plate which can lead to the buckling of the gusset plate; (2) overload of the welds and/or bolts of the gusset plate connections to the beam and column caused by the buckling of the gusset plate; (3) yielding and/or fracture of the beam and column flanges and/or webs due to high moments and shears in these components due to moment frame action that is not accounted for in conventional braced frame design rationale; and (4) unintended moment frame action that resists a large portion of the braced frame lateral loads rather than braces. This moment frame action is typically not accounted for in the design of the braced frame so that the force distribution in the braced frame is significantly different than the assumed design forces.

BRIEF DESCRIPTION OF THE DRAWINGS

The object and advantage of the embodiments of the invention will become more readily apparent to those of ordinary skill in the art after reviewing the following detailed description and accompanying documents wherein:

FIG. 1A is an example of a diagonal frame brace structural framework and FIG. 1B shows an example of a chevron frame brace structural framework according to embodiments of the invention;

FIG. 2 is a magnified view of a conventional connection amongst the beam, brace, column, and gusset plate connection according to FIG. 1A;

FIG. 3A is a beam, column, and gusset plate connection with a beam web slot and a column web slot according to embodiments of the invention;

FIG. 3B is a magnified view of a long slotted hole;

3

FIG. 4 is a modification of FIG. 3 that uses a reinforcing plate for the gusset plate to beam connection according to embodiments of the invention;

FIG. 5 is a modification of FIG. 3 that uses a reinforced concrete slab for additional connection reinforcement according to embodiments of the invention;

FIG. 6 is a beam, column, and gusset plate connection with double framing angles according to embodiments of the invention;

FIG. 7 is a beam, column, and gusset plate connection with double framing angles and spacer plates according to embodiments of the invention;

FIG. 8 is a cross-section of FIG. 7 according to embodiments of the invention;

FIG. 9 is a magnified view of the deformation of double framing angles and a gusset plate caused by a load according to embodiments of the invention;

FIG. 10 is a beam, column, and gusset plate as an all-bolted connection according to embodiments of the invention;

FIG. 11 is a cross-section of FIG. 10 according to embodiments of the invention;

FIG. 12 is a beam, column, and gusset plate connection utilizing a flex plate and spacer plate connection according to embodiments of the invention;

FIG. 13 is a cross-section of FIG. 12 according to embodiments of the invention;

FIG. 14 is a cross-section of a beam, column, and gusset plate connection with a double flex plate and spacer plate bolted connection according to embodiments of the invention;

FIG. 15 is a cross-section of a beam, column, and gusset plate connection with a double flex plate and spacer plate welded connection according to embodiments of the invention; and

FIG. 16 is a graph showing the distribution of lateral forces between the moment frame components and the frame brace in a single story braced frame as a function of the story drift or displacement according to embodiments of the invention.

DETAILED DESCRIPTION

An embodiment of the present invention provides a new and improved beam-to-column-to-brace connection, which includes a gusset plate, that reduces the bending moments and shears in the beams and columns of conventionally joined braced frames when the structural framework may be subjected to gravity and lateral loads such as those caused by wind and seismic loadings. The improved connection may extend the useful life of new braced framed structures, as well as that of braced frames in existing structures when incorporated into a retrofit modification for existing structures

The moments and shears in the beams and columns may be reduced by two ways. First, a flexure mechanism may be provided to transfer the horizontal forces in the gusset plate to the beam. Second, a shear plate may be provided to bolt the beam web to the column flange connection such that the shear plate includes horizontally slotted holes.

The flexure mechanism may include either (1) a beam web slot under the gusset plate that separates the beam flange from the beam web or (2) a flexure plate or double framing angles assembly using spacer plates that transfers the gusset plate forces to the beam flange. These flexure mechanisms essentially may eliminate the pinching frame action that leads to buckling and collapse of the gusset plate. The flexure mechanisms also may reduce the moments and shears in the column.

A shear plate with horizontally slotted holes to connect and bolt the beam web to the column may eliminate the connec-

4

tion moment caused by the horizontal bolt forces in the beam web and the horizontal force in the gusset plate to column connection.

In one embodiment according to the invention, the structural frames resist lateral loads in a truss-like action consistent with braced frame design rationale which differs from conventionally braced frame designs as explained above. Conventionally braced frame designs resist lateral load in a combination of braced frame action and moment frame action.

Embodiments of the invention may reduce the stresses and strains in the joined members caused by moment frame action when the braced frame is subjected to lateral loadings such as wind or seismic events; may reduce or eliminate the undesirable effects of the kinematic end rotation of the brace and thereby improve the performance of the brace in resisting the braced frame lateral load; and/or may limit the forces in the beams and columns of the braced frame to primarily axial forces when the braced frame is subjected to lateral loadings, such as wind or seismic events.

Additional embodiments of the invention may limit the forces in the beams and columns of the braced frame to primarily axial forces to prevent damage to these components when the braced frame is subjected to lateral loadings such as wind or seismic events; may allow for joint rotations in the braced frame which reduces the moments and shears in the members of the braced frame; may either reduce or eliminate the need for beam web stiffeners in the proximity of the gusset plate; and/or may eliminate the need for horizontal and/or vertical stiffeners on the gusset plate.

Embodiments of the invention may prevent damage to the braced frame beams and columns when the braced frame is subjected to seismic loading by keeping the beams and columns essentially elastic and allowing only the braces to be stressed to their yield loads; may reduce the residue displacements in the braced frame after the frame has been subject to seismic forces; may reduce the size of the gusset plates that are required in conventionally designed braced systems; and/or may move the working point in conventionally braced frames from the intersection of the centerlines of the beam and column to the intersection of the beam and column flange thereby reducing the size of the gusset plate.

The embodiments of the invention may reduce the rigidity of the welded and/or bolted gusset plate connection assembly. A reduction in rigidity may eliminate or significantly reduce the moments and shears in the beam, column, and brace when the braced frame is subjected to lateral drift or displacement. Such lateral drift may be due to wind or seismic loading. To this end, the embodiments of the invention may provide for a hinging or flexure mechanism in the beam or in the gusset plate to beam connection.

The effect of the hinging or flexure mechanism may create a large reduction in the beam and column moments which essentially may eliminate the moment frame action in the braced structural frame. The hinging or flexure mechanism may also reduce the moment and shears in the brace and also may allow the gusset plate to rotate with the drift of the frame and thereby may reduce the tendency for the gusset plate to buckle or collapse. Gusset plate buckling may result in the fracture of the gusset plate connection to the beam and/or column. Moreover, the hinging or flexural mechanism may reduce the possibility of unintentional large moments and shears in the columns could result in the development of plastic hinges in the columns of the braced frame.

Embodiments of the invention may also provide for the braces to absorb or dissipate substantial amounts of energy when the frame may be subjected to lateral loads such as seismic and wind loads. The braces, which may react most

5

effectively in a uniaxial state of stress, may provide for efficient use of material thereby achieving a robust structural system. Additionally, the lateral force resisting elements of the braced frame may be economically and expeditiously restored by replacing flexural elements and the braces if damaged by lateral wind or seismic loading.

Referring to FIG. 1A and FIG. 1B, there is shown examples of structural assemblies according to the embodiments of the invention. FIG. 1A depicts columns **1**, beams **2**, and diagonal frame brace members **8** to form the skeletal structural framework. FIG. 1B shows a structural framework that utilizes chevron bracing with frame brace members **8'**. Gusset plates **3** create the connection among the columns **1**, beams **2**, and diagonal frame brace members **8, 8'**. The gusset plates of FIG. 1A and FIG. 1B may be connected to the columns **1**, beams **2**, and frame brace members **8, 8'** by conventional techniques such as bolting, welding, pinning, or any combination thereof. Both the diagonal bracing of FIG. 1A and the chevron bracing of FIG. 1B may resist loads such as seismic or wind loads to maintain the structural integrity of the frame.

FIG. 2 shows an example of a conventional connection with a column **100**, beam **200**, brace member **800**, and gusset plate **300** connection according to FIG. 1A. The column **100** may include a first column flange **101**, a second column flange **102**, and a column web **104** between the first column flange **101** and the second column flange **102**. An example of a column **100** used in the structural framework may include a wide flange or I beam of 14 inches by 176 pounds per foot [W14×176 (360×262)] column. The beam **200** may include a first beam flange **201**, a second beam flange **202**, and a beam web **204** between the first beam flange **201** and the second beam flange **202**. An example of a beam **200** used in the structural framework may include a wide flange or I beam of 27 inches by 94 pounds per foot [W27×94 (690×140)] beam. A gusset plate **300** may connect the frame brace member **800** to the column **100** and the beam **200**. The gusset plate may be provided with a pin hole brace attachment detail **306** to join the frame brace member **800** to the gusset plate **300**. Other connections between the gusset plate **300** and the frame brace member **800** may be used such as a bolted detail attachment.

The gusset plate **300** may be coupled to the first column flange **101** of the column **100**. The gusset plate **300** and first column flange **101** may be coupled by a weld connection. The gusset plate **300** may be coupled to the first beam flange **201** of the beam **200** by a weld connection. Conventional stiffeners **302, 304** may be welded to the edges of the gusset plate **300** to provide extra strength to the framework. A vertical beam stiffener **207** may be welded to the beam web **204** to provide reinforcement.

The beam **200** may be joined to the column **100** via a shear plate **400**. A space **L** may be provided between the first column flange **201** and the beam web **204**. The shear plate **400** may connect to the beam web **204** and to the first column flange **101**. The shear plate **400** may be coupled to the first column flange **101** via a shop weld connection. The shear plate may also include round holes **412** to receive bolts to make the connection.

Structural analysis shows that when a structural framework such as the framework depicted in FIG. 2 is subject to certain loads, the angle between the column **100** and the beam **200** tends to close when the force due to the frame brace member **800** is in tension. The decrease in angle may cause the column **100** and beam **200** to crush and buckle the gusset plate **300**. The structural action results in undesirable and unintended moment and shear forces in the beam **200** and column **100**. Examples of such loads that may cause the angle to decrease are a lateral seismic load or a wind load.

6

FIG. 3A shows another example of a structural framework. The beam **200** may include a beam web slot **208** adjacent to the first beam flange **201**. The column **100** may include a column web slot **108** adjacent to the first column flange **101**. The slots **108, 208** and additionally long slotted holes **402** of the shear plate **400**, may reduce the moment and shear forces in the beam **200** and the column **100** when the structural frame may be subject to lateral forces. In this FIG. 3A, the second beam flange may be stabilized with a stabilization plate **206** that is attached to the beam **200** and the column **100**. The first beam flange **201** may be connected to the first column flange **101** via a complete joint penetration (CJP) weld **210**.

FIG. 3B shows a detail of an oblong long slotted hole **402** with a width **W** and a height **H**. These holes **402** may be specified by the American Institute of Steel Construction (AISC). The longitudinal direction of the long slotted hole may be twice the dimension as the width. The shear plate **400** may include a long slotted hole **402**. The long slotted hole **402** may receive a bolt so that the shear plate **400** may be bolted to the beam web **204**.

FIG. 4 shows another exemplary embodiment of the invention. An additional reinforcement plate **220** may be attached to the gusset plate **300** and the first beam flange **201** to provide additional connection strength if necessary.

FIG. 5 is a modification of the exemplary embodiment of FIG. 4. A concrete deck **230** with a reinforcement bar **232** may be provided above the stabilization plate **220** to increase the strength of the connection.

FIG. 6 shows another exemplary embodiment according to the invention. The gusset plate **300** may be attached to the first beam flange **201** via double framing angles **360**. The double framing angles may include long slotted holes **362**. The gusset plate **300** may also include the long slotted holes **362** for the attachment. The long slotted holes **362** may receive bolts. The bolts are tightened only snug tight so that when the structural frame may be subject to lateral loads, the bolts slip and reduce the moment and shear forces in the column **100** and the beam **200**.

The beam **200** may be connected to the column **100** via a shear plate **400** connection. The beam web **204** may be bolted to the shear plate **400** and the shear plate **400** may be welded to the first column flange **101**. The shear plate may have long slotted holes **402** that are able to receive bolts. The bolts may also have a snug tight fit to allow for a semi-rigid connection. The long slotted holes with the snug tight bolts allow the structural frame to have more elasticity and allow the connections to be less rigid than conventional connections. The long slotted holes **402** in the shear plate **400** restrict the bolts to resisting only vertical loads.

FIGS. 7 and 8 depict a further embodiment according to the invention. In this embodiment, the structural framework is under a compressive force **380** due to the frame brace member **800** (not depicted here). The gusset plate **300** is connected to the beam **200** via double framing angles **360** and spacer plates **366**. The double framing angles **360** may include circular holes **111** but may alternatively include long slotted holes. The framing angle **360** may include a vertical plate or leg **364** and a horizontal plate or leg **365**. The horizontal plate **365** may rest upon spacer plates **366**. The double framing angles **360** may be connected to the first beam flange **201** by bolts **112** via the spacer plates **366**.

As depicted in FIG. 8, the thickness of the spacer plates determines the height of a space between the horizontal plate **365** and the first beam flange **201**. The spacer plates **366** allow the double framing angles **360** to flex when the structural frame may be subjected to lateral loads. The spacer plates **366**

with the double framing angles **360** may reduce the moment and shear forces in the frame by providing a flexible beam to column connection.

As in FIG. 6, FIG. 7 shows that the beam web **204** may be bolted to the shear plate **400**. The long slotted holes **402** in the shear plate **400** restrict the bolts to resisting only vertical loads.

FIG. 9 shows the flexible nature of the double framing angles **360** according to embodiments of the invention. The double framing angles **360** deflect and deform in the manner shown as the dotted lines of **360'** when the structural frame may be subject to a load. The deformation **360'** may cause the bolts **112** and the gusset plate **300** to likewise deform as shown in the dotted lines of FIG. 9.

FIGS. 10 and 11 show another exemplary embodiment of the invention. FIG. 11 is a cross-section of FIG. 10 along the dotted lines of FIG. 10. In this embodiment as depicted in FIG. 11, a flex plate **501** may be provided to complete the gusset plate **300** to the beam flange **201** connection. The flex plate **501** may be welded to a vertical plate **500** via welds **600A**. The vertical plate **500** may be connected to the gusset plate **300** by a plate **400'**. The plate **400'** may have one or a plurality of holes **402'** to receive bolts to secure the gusset plate **300** to the plate **400'**. The flex plate **501** may be connected to the first beam flange **201** by spacer plates **366** and bolts **112**. The thickness of the spacer plates **366** may determine the distance the flex plate **500** is elevated from the first beam flange **201**. The beam web **204** may be connected to the first column flange **101** by a shear plate **400**.

FIGS. 12 and 13 show yet another exemplary embodiment of the invention. FIG. 13 is a cross-section of FIG. 12 at the dotted lines of FIG. 12. In this embodiment, the gusset plate **300** may be welded via a welds **600** to the flex plate **501**. Other connections may be possible to connect the gusset plate **300** to the flex plate **501**.

FIGS. 14 and 15 are further embodiments of the present invention. FIGS. 14 and 15 are modifications of FIG. 11. A double flex plate assembly may be used for the connection of the gusset plate **300** to the first beam flange **201**. The flex plate **501** is welded to the vertical plate **500** via welds **600A**. A second flex plate **502** is arranged on the first beam flange **201**. Spacer plates **367** are sandwiched between the flex plate **501** and the second flex plate **502**. FIGS. 14 and 15 differ in their ways of connecting the components of the structural framework.

FIG. 14 utilizes bolts to connect the flex plate **501** to the second flex plate **502** to the first beam flange **201**. The spacer plates **367** are bolted to both flex plates **501**, **502** by bolts **113**. The second flex plate **502** may be bolted to the first beam flange **201** by bolts **114**.

FIG. 15 utilizes bolt and weld connections. As in FIG. 14, the flex plate **501** is welded to the vertical plate **500** via welds **600A**. The flex plate **501** is bolted to the spacer plates **367** by bolts **113**. FIG. 15 differs from FIG. 14 in that the second flex plate **502** may be welded to the first beam flange **201** via welds **601**. The configurations of FIGS. 14 and 15 may use other connections practiced in the field. The double flex plates connection may provide a flexible beam to column connection so that any deformation in the beam or column may be elastic.

FIG. 16 depicts a graph of the projected distribution of the frame brace forces in a structural single story braced frame as a function of lateral displacement of the frame under loads according to the flexible connections of embodiments of the invention. An example of such structural frame is the chevron frame of FIG. 1B. Examples of the loads to be exerted on the structural frame are seismic and wind loading.

The analysis in FIG. 16 depicts the results of a structural framework tested the structural framework according to the embodiment shown in FIG. 13 which shows a flex plate design. The analysis utilized a wide flange or I beam of 21 inches by 93 pounds per foot (W21×93) and a wide flange or I column of 14 inches by 176 pounds per foot (W14×176). The area of the frame brace is 6.33 inches squared (6.33 in²). For a 2% (0.02) drift or displacement of the structural framework, the lateral displacement of the structural frame is calculated as 2.4 inches.

A total lateral force of 664677 pounds was calculated to cause the lateral displacement of 2.4 inches. The frame brace members experience a horizontal force component of 263639 pounds in tension and -285430 pounds in compression. Therefore, the total force resisted by the frame brace members is 549069 pounds (263639 lbs.+285430 lbs.=549069 lbs.). The force of 549069 bs. represents 82.6% of the total lateral force of 664677 pounds calculated for the 2% drift (549069/664677=0.826). This means that the frame brace members resist 82.6% of the lateral load. The rest of the load is exerted on the beams and the columns (664677-549069=115608 bs.). This represents that merely 17.4% of the total lateral load is resisted by the beams and the columns (115608/664677=0.174).

Typically, in braced frames of the type shown in FIGS. 1A and 1B with a rigid connection such as FIG. 2, only 50% of the lateral load is resisted by the frame brace members. The rest of the 50% of the lateral load is resisted by the beams and columns. With the embodiments of the invention, the frame brace members resist approximately 32.6% more of the lateral load than the frame brace members with conventional rigid connections.

The results of the experiment and graph show that the flex plate design is a flexible semi-rigid connection. It allows the gusset plate and the frame brace members to deform plastically while allowing the beams and the columns to elastically deform under a given load. Such result may allow the columns and beams to maintain their structural integrity and allow for easy replacement of the plastically deformed brace frame members and gusset plates.

What is claimed is:

1. A semi-rigid connection in a structural framework, comprising:

- a column having a first flange, a second flange, and a column web;
- a beam having a first flange and second flange and a beam web coupled at an angle to the column;
- a brace beam coupled diagonally to the column and the beam;
- a gusset plate having a first edge and a second edge with the first edge coupled to the first flange of the column and connects the brace beam with the column, wherein the gusset plate includes a front side and a back side;
- a shear plate having a first side and a second side and a first edge and a second edge, with the first side coupled to the beam web and the first edge coupled to the first column flange;
- a first spacer plate that has a first side and a second side;
- a second spacer plate that has a first side and a second side;
- a first framing angle that comprises a first leg and a second leg at an angle to each other, wherein the first leg is coupled to the first side of the gusset plate and the second leg is coupled to the first side of a first spacer plate and the second side of the first spacer plate is coupled to the first beam flange; and
- a second framing angle that comprises a first leg and a second leg at an angle to each other, wherein the first leg

is coupled to the second side of the gusset plate and the second leg is coupled to the first side of a second spacer plate and the second side of the second spacer plate is coupled to the first beam flange.

2. The semi-rigid connection according to claim 1, wherein the shear plate further comprises: one or a plurality of horizontally slotted holes to receive a respective bolt such that the shear plate is bolted to the beam web in a manner to resist only vertical forces between the beam web and the shear plate.

3. The semi-rigid connection according to claim 2, wherein the first spacer plate and the second spacer plate each include one or a plurality of spacer holes and the first and second framing angles comprise one or a plurality of plate holes, and wherein the first and second framing angles are coupled through the one or the plurality of plate holes and the one or the plurality spacer holes to the first beam flange.

4. The semi-rigid connection according to claim 3, wherein the first and second legs of the first and second framing angles are coupled to the first column flange.

* * * * *