



US009354402B2

(12) **United States Patent**  
**Nelson**

(10) **Patent No.:** **US 9,354,402 B2**  
(45) **Date of Patent:** **\*May 31, 2016**

(54) **FIBER OPTIC ADAPTER WITH  
INTEGRALLY MOLDED FERRULE  
ALIGNMENT STRUCTURE**

(71) Applicant: **CommScope Technologies LLC**,  
Hickory, NC (US)

(72) Inventor: **Keith Nelson**, Brooklyn Center, MN  
(US)

(73) Assignee: **CommScope Technologies LLC**,  
Hickory, NC (US)

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 0 days.

This patent is subject to a terminal dis-  
claimer.

(21) Appl. No.: **14/635,083**

(22) Filed: **Mar. 2, 2015**

(65) **Prior Publication Data**

US 2015/0241641 A1 Aug. 27, 2015

**Related U.S. Application Data**

(63) Continuation of application No. 14/499,594, filed on  
Sep. 29, 2014, now Pat. No. 8,992,095, which is a  
continuation of application No. 13/777,575, filed on  
Feb. 26, 2013, now Pat. No. 8,845,205, which is a

(Continued)

(51) **Int. Cl.**  
**G02B 6/38** (2006.01)

(52) **U.S. Cl.**  
CPC ..... **G02B 6/3869** (2013.01); **G02B 6/381**  
(2013.01); **G02B 6/3825** (2013.01);  
(Continued)

(58) **Field of Classification Search**

None

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

4,736,100 A 4/1988 Vastagh  
4,747,020 A 5/1988 Brickley et al.

(Continued)

**FOREIGN PATENT DOCUMENTS**

CN 2426610 Y 4/2001  
EP 0 597 501 A1 5/1994

(Continued)

**OTHER PUBLICATIONS**

International Search Report and Written Opinion mailed Nov. 6,  
2009.

(Continued)

*Primary Examiner* — Michelle R Connelly


(74) *Attorney, Agent, or Firm* — Merchant & Gould P.C.

(57)

**ABSTRACT**

A fiber optic adapter is disclosed. The fiber optic adapter includes a main body configured to receive a first fiber optic connector through a first end and a second fiber optic connector through a second end for mating with the first fiber optic connector. The adapter includes a ferrule alignment structure located within an axial cavity of the main body, the ferrule alignment structure including a sleeve mount and a ferrule sleeve, the sleeve mount including an axial bore and at least one latching hook extending from a center portion of the sleeve mount toward the first end of the main body and at least one latching hook extending from the center portion toward the second end of the main body, the latching hooks configured to flex for releasably latching the first and second fiber optic connectors to the fiber optic adapter. The sleeve mount and the main body of the fiber optic adapter are unitarily molded as a single piece and the ferrule sleeve is separately placed within the axial bore of the sleeve mount.

**14 Claims, 6 Drawing Sheets**



**Related U.S. Application Data**

continuation of application No. 12/548,121, filed on  
Aug. 26, 2009, now Pat. No. 8,382,382.

(60) Provisional application No. 61/092,166, filed on Aug.  
27, 2008.

(52) **U.S. Cl.**

CPC ..... **G02B 6/3831** (2013.01); **G02B 6/3833**  
(2013.01); **G02B 6/3834** (2013.01); **G02B**  
**6/3851** (2013.01); **G02B 6/3865** (2013.01);  
**G02B 6/3873** (2013.01); **G02B 6/3874**  
(2013.01)

(56) **References Cited**

## U.S. PATENT DOCUMENTS

4,792,203 A 12/1988 Nelson et al.  
4,824,196 A 4/1989 Bylander  
4,861,134 A 8/1989 Alameel et al.  
4,900,123 A 2/1990 Barlow et al.  
4,913,522 A 4/1990 Nolf et al.  
4,948,220 A 8/1990 Violo et al.  
4,995,688 A 2/1991 Anton et al.  
5,023,646 A 6/1991 Ishida et al.  
5,058,983 A 10/1991 Corke et al.  
5,067,783 A 11/1991 Lampert  
5,073,042 A 12/1991 Mulholland et al.  
5,076,688 A 12/1991 Bowen et al.  
5,142,598 A 8/1992 Tabone  
5,214,735 A 5/1993 Henneberger et al.  
5,233,674 A 8/1993 Vladic  
5,274,729 A 12/1993 King et al.  
5,274,731 A 12/1993 White  
5,317,663 A 5/1994 Beard et al.  
5,333,221 A 7/1994 Briggs et al.  
5,333,222 A 7/1994 Belenkiy et al.  
5,359,688 A 10/1994 Underwood  
5,363,465 A 11/1994 Korkowski et al.  
5,367,598 A 11/1994 Devenish, III et al.  
5,402,515 A 3/1995 Vidacovich et al.  
5,408,557 A 4/1995 Hsu  
RE34,955 E 5/1995 Anton et al.  
5,420,958 A 5/1995 Henson et al.  
5,442,726 A 8/1995 Howard et al.  
5,448,015 A 9/1995 Jamet et al.  
5,469,526 A 11/1995 Rawlings  
5,497,444 A 3/1996 Wheeler  
5,506,922 A 4/1996 Grois et al.  
5,511,144 A 4/1996 Hawkins et al.  
5,542,015 A 7/1996 Hultermans  
5,647,043 A \* 7/1997 Anderson et al. .... 385/78  
5,708,751 A 1/1998 Mattei  
5,717,810 A 2/1998 Wheeler  
5,719,977 A \* 2/1998 Lampert et al. .... 385/60  
5,734,776 A 3/1998 Puetz  
5,737,464 A 4/1998 Underwood et al.  
5,764,834 A \* 6/1998 Hultermans .... 385/60  
5,764,844 A 6/1998 Mendes  
5,774,612 A 6/1998 Belenkiy et al.  
5,778,132 A 7/1998 Csipkes et al.  
5,784,515 A 7/1998 Tamaru et al.  
5,823,646 A 10/1998 Arizpe et al.  
5,825,955 A 10/1998 Ernst et al.  
5,838,855 A 11/1998 Stephenson  
5,883,995 A 3/1999 Lu  
5,887,095 A 3/1999 Nagase et al.  
5,909,526 A 6/1999 Roth et al.  
5,923,805 A \* 7/1999 Anderson et al. .... 385/86  
5,930,425 A 7/1999 Abel et al.  
5,945,633 A 8/1999 Ott et al.  
5,956,444 A 9/1999 Duda et al.  
5,969,294 A 10/1999 Eberle et al.  
5,975,769 A 11/1999 Larson et al.  
5,987,203 A 11/1999 Abel et al.  
5,993,071 A \* 11/1999 Hultermans .... 385/70

6,027,252 A 2/2000 Erdman et al.  
6,041,155 A 3/2000 Anderson et al.  
6,044,193 A 3/2000 Szentesi et al.  
6,061,492 A 5/2000 Strause et al.  
6,069,797 A 5/2000 Widmayer et al.  
6,076,975 A 6/2000 Roth  
6,079,881 A 6/2000 Roth  
6,096,797 A 8/2000 Prantl et al.  
6,149,315 A 11/2000 Stephenson  
6,160,946 A 12/2000 Thompson et al.  
6,188,687 B1 2/2001 Mussman et al.  
6,188,825 B1 2/2001 Bandy et al.  
6,208,796 B1 3/2001 Williams Vigliaturo  
6,227,717 B1 5/2001 Ott et al.  
6,234,683 B1 5/2001 Waldron et al.  
6,236,795 B1 5/2001 Rodgers  
6,240,229 B1 5/2001 Roth  
6,247,849 B1 6/2001 Liu  
6,256,443 B1 7/2001 Uruno  
6,259,850 B1 7/2001 Crosby, Jr. et al.  
6,271,484 B1 8/2001 Tokutsu  
6,278,829 B1 8/2001 BuAbbud et al.  
RE37,489 E 1/2002 Anton et al.  
6,347,888 B1 2/2002 Puetz  
6,356,697 B1 3/2002 Braga et al.  
6,363,200 B1 3/2002 Thompson et al.  
6,367,984 B1 4/2002 Stephenson et al.  
6,385,381 B1 5/2002 Janus et al.  
6,409,392 B1 6/2002 Lampert et al.  
6,411,767 B1 6/2002 Burrous et al.  
6,418,262 B1 7/2002 Puetz et al.  
6,424,781 B1 7/2002 Puetz et al.  
6,425,694 B1 7/2002 Szilagyi et al.  
6,431,762 B1 8/2002 Taira et al.  
6,434,313 B1 8/2002 Clapp, Jr. et al.  
6,443,627 B1 9/2002 Anderson et al.  
6,452,925 B1 9/2002 Sistanizadeh et al.  
6,453,033 B1 9/2002 Little et al.  
6,464,402 B1 10/2002 Andrews et al.  
D466,087 S 11/2002 Cuny et al.  
6,480,487 B1 11/2002 Wegleitner et al.  
6,483,977 B2 11/2002 Battey et al.  
6,496,640 B1 12/2002 Harvey et al.  
6,504,988 B1 1/2003 Trebesch et al.  
6,508,593 B1 1/2003 Farnsworth et al.  
6,532,332 B2 3/2003 Solheid et al.  
6,535,682 B1 3/2003 Puetz et al.  
6,539,147 B1 3/2003 Mahony  
6,539,160 B2 3/2003 Battey et al.  
6,542,688 B1 4/2003 Battey et al.  
6,554,485 B1 4/2003 Beatty et al.  
6,556,763 B1 4/2003 Puetz et al.  
6,577,595 B1 6/2003 Counterman  
6,591,051 B2 7/2003 Solheid et al.  
6,597,670 B1 7/2003 Tweedy et al.  
6,614,980 B1 9/2003 Mahony  
6,621,975 B2 9/2003 Laporte et al.  
6,623,170 B2 9/2003 Petrillo  
6,625,375 B1 9/2003 Mahony  
6,631,237 B2 10/2003 Knudsen et al.  
RE38,311 E 11/2003 Wheeler  
6,654,536 B2 11/2003 Battey et al.  
6,661,961 B1 12/2003 Allen et al.  
6,668,127 B1 12/2003 Mahony  
6,678,457 B2 1/2004 Kim et al.  
6,712,523 B2 3/2004 Zimmel  
6,755,574 B2 6/2004 Fujiwara et al.  
6,760,530 B1 7/2004 Mandry  
6,760,531 B1 7/2004 Solheid et al.  
6,768,860 B2 7/2004 Liberty  
6,778,752 B2 8/2004 Laporte et al.  
6,788,786 B1 9/2004 Kessler et al.  
6,792,190 B2 9/2004 Xin  
6,792,191 B1 9/2004 Clapp, Jr. et al.  
6,815,612 B2 11/2004 Bloodworth et al.  
6,850,685 B2 2/2005 Tinucci et al.  
6,853,795 B2 2/2005 Dagley et al.  
6,870,734 B2 3/2005 Mertesdorf et al.  
6,901,200 B2 5/2005 Schray

(56)

## References Cited

## U.S. PATENT DOCUMENTS

6,909,833	B2	6/2005	Henschel et al.	
6,920,274	B2	7/2005	Rapp et al.	
6,925,241	B2	8/2005	Bohle et al.	
6,950,593	B2	9/2005	Hodge et al.	
6,980,725	B1	12/2005	Swiecone	
6,983,095	B2	1/2006	Reagan et al.	
7,029,322	B2	4/2006	Ernst et al.	
7,088,899	B2	8/2006	Reagan et al.	
7,103,255	B2	9/2006	Reagan et al.	
7,142,764	B2	11/2006	Allen et al.	
7,146,089	B2	12/2006	Reagan et al.	
7,171,102	B2	1/2007	Reagan et al.	
7,198,409	B2	4/2007	Smith et al.	
7,200,317	B2	4/2007	Reagan et al.	
7,218,827	B2	5/2007	Vongseng et al.	
7,233,731	B2	6/2007	Solheid et al.	
7,277,620	B2	10/2007	Vongseng et al.	
7,369,741	B2	5/2008	Reagan et al.	
7,376,323	B2	5/2008	Zimmel	
7,377,697	B2	5/2008	Kahle et al.	
7,400,813	B2	7/2008	Zimmel	
7,400,816	B2	7/2008	Reagan et al.	
7,407,330	B2	8/2008	Smith et al.	
7,416,349	B2	8/2008	Kramer	
7,457,503	B2	11/2008	Solheid et al.	
7,471,869	B2	12/2008	Reagan et al.	
7,515,805	B2	4/2009	Vongseng et al.	
7,519,259	B2	4/2009	Smith et al.	
7,583,883	B2	9/2009	Kowalczyk et al.	
8,382,382	B2 *	2/2013	Nelson	G02B 6/3825 385/55
8,845,205	B2 *	9/2014	Nelson	G02B 6/3825 385/55
8,992,095	B2 *	3/2015	Nelson	G02B 6/3825 385/55
2001/0001270	A1	5/2001	Williams Vigliaturo	
2002/0034290	A1	3/2002	Pershan	
2002/0176681	A1	11/2002	Puetz et al.	
2002/0181893	A1	12/2002	White et al.	
2003/0002812	A1	1/2003	Lampert	
2003/0007767	A1	1/2003	Douglas et al.	
2003/0095772	A1	5/2003	Solheid et al.	
2003/0113086	A1	6/2003	Jun et al.	
2003/0147597	A1	8/2003	Duran	
2003/0156797	A1	8/2003	Gherardini	
2003/0174996	A1	9/2003	Henschel et al.	
2003/0207601	A1	11/2003	Adachi	
2003/0223703	A1	12/2003	Chen et al.	
2004/0074852	A1	4/2004	Knudsen et al.	
2004/0126069	A1	7/2004	Jong et al.	
2004/0165852	A1	8/2004	Erwin et al.	
2004/0228598	A1	11/2004	Allen et al.	
2004/0264873	A1	12/2004	Smith et al.	
2005/0002633	A1	1/2005	Solheid et al.	
2005/0074211	A1	4/2005	Greub	
2005/0129379	A1	6/2005	Reagan et al.	
2005/0163448	A1	7/2005	Blackwell, Jr. et al.	
2006/0083475	A1	4/2006	Grubish et al.	
2006/0093274	A1	5/2006	Kahle et al.	
2006/0093301	A1	5/2006	Zimmel	
2006/0115220	A1	6/2006	Elkins, II et al.	
2006/0154529	A1 *	7/2006	Erdman et al.	439/654
2006/0204200	A1	9/2006	Lampert et al.	
2008/0008436	A1	1/2008	Reagan et al.	
2008/0013910	A1	1/2008	Reagan et al.	
2008/0019644	A1	1/2008	Smith et al.	
2008/0019655	A1	1/2008	Vongseng et al.	
2008/0025684	A1	1/2008	Vongseng et al.	
2008/0075411	A1	3/2008	Solheid et al.	
2008/0317425	A1	12/2008	Smith et al.	
2009/0074372	A1	3/2009	Solheid et al.	
2009/0087157	A1	4/2009	Smith et al.	
2009/0190896	A1	7/2009	Smith et al.	
2009/0196565	A1	8/2009	Vongseng et al.	
2009/0285541	A1	11/2009	Kowalczyk et al.	

2010/0054668	A1	3/2010	Nelson
2010/0111484	A1	5/2010	Allen
2013/0177279	A1	7/2013	Nelson
2015/0013889	A1	1/2015	Nelson

## FOREIGN PATENT DOCUMENTS

EP	0 731 369	A2	9/1996
EP	0 743 701	A2	11/1996
EP	0 788 002	A1	8/1997
EP	0 871 047	A1	10/1998
EP	0 967 498	A1	12/1999
EP	0 975 180	A1	1/2000
EP	1 045 267	A1	10/2000
EP	1 486 808	A2	12/2004
JP	63-229409		9/1988
JP	2000-266963		9/2000
JP	2001-33658		2/2001
JP	2001-188134		7/2001
JP	1-144266		6/2002
JP	3307618		7/2002
JP	2005-345589		12/2005
JP	3761762		3/2006
WO	WO 98/53347		11/1998
WO	WO 99/27404		6/1999
WO	WO 00/75706	A2	12/2000
WO	WO 02/21182	A1	3/2002
WO	WO 02/103429	A2	12/2002
WO	WO 03/093883	A2	11/2003
WO	WO 2004/032532	A2	4/2004

## OTHER PUBLICATIONS

“Retainer Staright [sic] Removable SC,” which shows a latch design, 2 pages (Jan. 17, 2006).

24 photos of LambdaUnite® Blank Card; “LambdaUnite® MultiService Switch (MSS)” brochure (2003); and “Lucent’s LambdaUnite® Busts Out” official release (Jan. 29, 2002).

ADC Telecommunications, Inc., brochure titled *Value-Added module System*, © 2000 (29 pages).

ADC Telecommunications, Inc., brochure titled *Value-Added module System: Optical Distribution Frame (OMX™ 600)*, © 2001 (11 pages).

ADC Telecommunications, Inc.’s 2<sup>nd</sup> Edition of Fiber Panel Products; front cover, Table of Contents, pp. 1-111, and back cover; revised Jul. 1996, Item No. 846.

ADC Telecommunications, Inc.’s Secure Fiber Entrance Terminal (SFET) Brochure; front cover, pp. 2-7, and back cover; revised May 1998, Item No. 1005.

ADC Telecommunications, Inc.’s 6th Edition of Next Generation Frame (NGF) Product Family Ordering Guide; front cover, Table of Contents, pp. 1-41, and back cover; revised Feb. 2003, Item No. 820.

ADC Telecommunications, Inc.’s Fiber Optic, Cable Assemblies and Accessories Brochure; front cover, Table of Contents, pp. 1-23, and back cover; revised Apr. 2003, Item No. 100300.

ADC Telecommunications, Inc.’s OMX™ 600, Optical Distribution Frame Brochure; front cover, Table of Contents, pp. 1-14, and back cover; revised Feb. 2001, Item No. 854.

ADC Telecommunications, Inc.’s Outside Plant, Fiber Cross-Connect Solutions Products Brochure; front cover, Table of Contents, pp. 1-48, and back cover; revised Jun. 2002, Item No. 1047.

AMP Inc. catalog entitled “Fiber Optic Products,” front and back covers and p. 59, (4 pgs.) (© 1991).

AT&T Network Systems catalog entitled “Fiber Optic Products Innovation for wide ranging applications,” front and back covers and pp. 6-1 through 6-16 (18 pages) (© 1995).

ATI Optique Catalog, ATI Optique Division of TI electronique, Version 2.6, released Mar. 27, 2002 (50 pages).

Brochure from Amphenol Corp. entitled “Amphenol® 954 Series one piece SC Connector,” 2 pgs. (1990).

*Couplers: Couplers WDMS Packaging*, Alcoa Fujikura Ltd., Telecommunications Division, © 2000 (5 pages) showing AFL splitters.

Drawings showing an ADC fiber storage trough concept including presentation entitled “Fujitsu Fiber Management Project Fiber Trough Concept”, 11 pages (Jun. 2002).

(56)

References Cited

OTHER PUBLICATIONS

Drawings showing another ADC fiber storage trough concept including presentation entitled “Fujitsu Fiber Management Project Fiber Trough Concept” by Kathy Barnes (7 pages), photos of trough disclosed in presentation by Kathy Barnes installed in a rack (3 pages) and presentation entitled “Fujitsu Fiber Management Project Fiber Trough Concept” by Dan Mertesdorf (9 pages), 19 total pages (Apr. 2002).  
FONS Corporation’s Modular Distribution Cabinets Rack Mount Enclosures, Model MDC-7, product sheet, 2 pages (2005).  
HRS catalog entitled “Optical Fibre Connectors,” front and back covers and pp. 16, 17 and 49 (5 pages) (Mar. 1991).

Iwano, S. et al., “MU-type Optical Fiber Connector System,” *NTT Review*, vol. 9, No. 2, pp. 63-71 (Mar. 1997).  
Nexans, Cross-Connect Cabinet III: Plastic Watertight Cabinet for FTTH Applications, dated 2002 (2 pages).  
Nexans, Cross-Connect Cabinet V: Metallic Watertight Cabinet for FTTH Applications, dated 2002 (2 pages).  
NRR Int’l Fiber Termination Module (FTM) & Premises Optical Distribution Cabinets (PODC) product brochure, 3 pages, undated.  
Optical fiber coupler review, Technical Report 2001, showing Sumitomo Osaka Cement Co. Ltd’s Optical Coupler (pp. 41-42).  
Sugita, E. et al., “SC-Type Single-Mode Optical Fiber Connectors,” *Journal of Lightwave Technology*, vol. 7, No. 11, pp. 1689-1696 (Nov. 1989).

\* cited by examiner

FIG. 1







FIG. 1A








FIG. 4




FIG. 5

FIG. 6





FIG. 7



1

# FIBER OPTIC ADAPTER WITH INTEGRALLY MOLDED FERRULE ALIGNMENT STRUCTURE

## CROSS REFERENCE TO RELATED APPLICATIONS

This application is a continuation of application Ser. No. 14/499,594, now U.S. Pat. No. 8,992,095, which is a continuation of application Ser. No. 13/777,575, filed Feb. 26, 2013, now U.S. Pat. No. 8,845,205, which is a continuation of application Ser. No. 12/548,121, filed Aug. 26, 2009, now U.S. Pat. No. 8,382,382, which application claims the benefit of provisional application Ser. No. 61/092,166, filed Aug. 27, 2008, which applications are incorporated herein by reference in their entirety.

## FIELD

The present disclosure relates generally to fiber optic adapters. In particular, the present disclosure relates to fiber optic adapters having bodies with integrally molded ferrule alignment features.

## BACKGROUND

Fiber optics have revolutionized communication throughout the world. Fiber optics are generally thin strings of glass designed to carry light which can be grouped together. With the increased use of fiber optics, it has become increasingly important to be able to connect and disconnect fiber optic cables from various sources. Two fiber optic cables can be optically coupled so that they are in communication with one another by using well-known connectors and adapters, thereby putting each fiber optic cable in communication with the other. The connectors are terminated to the end of each cable and then plugged into the adapters. The adapters normally include an opening at each end designed to receive the connectors. An example adapter for holding two SC-type mating connectors is described in U.S. Pat. No. 5,317,663. Improvements in the design and manufacture of fiber optic adapters are desirable.

## SUMMARY

The present disclosure relates generally to fiber optic adapters configured to receive fiber optic connectors having ferrules, wherein the ferrule alignment structures of the adapters are integrally molded as a unitary piece with the adapter body.

In one particular aspect, the present disclosure relates to a fiber optic adapter including a main body configured to receive a first fiber optic connector through a first end and a second fiber optic connector through a second end for mating with the first fiber optic connector, the adapter including a ferrule alignment structure located within an axial cavity of the main body, the ferrule alignment structure including a sleeve mount and a ferrule sleeve, the sleeve mount including an axial bore and at least one latching hook extending from a center portion of the sleeve mount toward the first end of the main body and at least one latching hook extending from the center portion toward the second end of the main body, the latching hooks configured to flex for releasably latching the first and second fiber optic connectors to the fiber optic adapter, wherein the sleeve mount and the main body of the fiber optic adapter are unitarily molded as a single piece and the ferrule sleeve is separately placed within the axial bore of

2

the sleeve mount, the ferrule sleeve configured to receive and align ferrules of the first and second fiber optic connectors.

A variety of additional inventive aspects will be set forth in the description that follows. The inventive aspects can relate to individual features and combinations of features. It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory only and are not restrictive of the broad inventive concepts upon which the embodiments disclosed herein are based.

## BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of a fiber optic adapter having features that are examples of inventive aspects in accordance with the principles of the present disclosure, the fiber optic adapter shown without the top and bottom cover panels thereof;

FIG. 1A illustrates the internal ferrule alignment features of the fiber optic adapter of FIG. 1 separately from the main body of the fiber optic adapter;

FIG. 2 illustrates the fiber optic adapter of FIG. 1 with one of the cover panels exploded from the body of the fiber optic adapter;

FIG. 3 illustrates the fiber optic adapter of FIG. 2 with the opposing cover panel exploded from the body of the fiber optic adapter;

FIG. 4 is another perspective view of the fiber optic adapter of FIG. 1, with the cover panels mounted thereon;

FIG. 5 is a cross-sectional view of the fiber optic adapter taken along line 5-5 of FIG. 1;

FIG. 6 is a cross-sectional view of the fiber optic adapter taken along line 6-6 of FIG. 1; and

FIG. 7 is a perspective view of an example fiber optic connector for use with the fiber optic adapter of FIGS. 1-6.

## DETAILED DESCRIPTION

Reference will now be made in detail to examples of inventive aspects of the present disclosure which are illustrated in the accompanying drawings. Wherever possible, the same reference numbers will be used throughout the drawings to refer to the same or like parts.

Referring to FIGS. 1-6, a fiber optic adapter 10 having features that are examples of inventive aspects in accordance with the principles of the present disclosure is shown. In the depicted embodiment, the fiber optic adapter 10 is configured to intermate SC-type connectors, one of which is shown in FIG. 7 of the present application and also shown and described in U.S. Pat. Nos. 5,317,663 and 6,712,523, the entire disclosures of which are incorporated herein by reference. However, it should be noted that the SC-type fiber optic adapter 10 described herein represents only one example embodiment of the inventive features of the disclosure and that the inventive features may be applicable to adapters configured to be used with other types of connectors (e.g., LC, LX.5, etc.). The inventive features should not be limited only to the specific embodiments described and illustrated herein.

Still referring to FIGS. 1-6, the fiber optic adapter 10 includes a main body 12 including an axial cavity 14 that is defined by a top side-wall 16, a bottom side-wall 18, a right side-wall 20, and a left side-wall 22. The axial cavity 14 of the main body 12 extends between a first opening 24 and a second opening 26. Each opening 24, 26 is sized to receive a fiber optic connector 100.

Since the embodiment of the adapter described herein is configured for use with SC-type connectors, the main body 12

3

and the axial cavity **14** are specifically sized and configured to accommodate SC-type connectors.

Referring now to FIGS. **1-3**, the main body **12** of the fiber optic adapter **10** includes a first opening **28** at the top side and a second opening **30** at the bottom side thereof. As will be discussed in further detail below, the first and second openings **28, 30** allow the fiber optic adapter main body **12** and at least a portion of the internal ferrule alignment structures **31** (see FIG. **1A**) that are located within the main body **12** to be injection-molded as a unitary piece. The first and second openings **28, 30** are covered by a pair of cover panels **32** after the fiber optic adapter **10** has been unitarily molded. The cover panels **32** may be ultrasonically welded to the main body **12** of the adapter **10**.

Preferably, the first opening **28** and the second opening **30** are of the same configuration such that the cover panels **32** used for the first opening **28** and the second opening **30** are also of the same size and shape. In this manner, the cover panels **32** for both the top and the bottom sides of the adapter **10** can be produced using the same mold/tool, reducing manufacturing costs.

Still referring to FIGS. **1-3**, located in the bottom side-wall **18** is a keyway **34** sized and shaped to receive a corresponding key **102** of an SC-type fiber optic connector **100** shown in FIG. **7** and discussed below.

Located on the exterior of the main body **12** are tabs **36, 38**. Tab **36** is located on right side-wall **20** and tab **38** is located on left side-wall **22**. The tabs **36, 38** are operative in supporting the adapter **10** on or against a planar surface such as that of a bulkhead. The main body **12** also includes a flexible cantilever arm **40** on each of the right side-wall **20** and left side-wall **22**. The flexible cantilever arms **40** define outwardly protruding tabs **42** that are configured to cooperate with the tabs **36, 38** to capture the fiber optic adapter **10** against a bulkhead. The tabs **42** of the cantilever arms **40** include ramped surfaces **44** to facilitate insertion of the fiber optic adapter **10** into an aperture defined by the bulkhead structure. The ramped surfaces **44** cause the flexible cantilever arms **40** to flex inwardly as the adapter **10** is moved passed the aperture of the bulkhead.

Although in the preferred embodiment the adapter **10** includes integrally molded flexible cantilever arms **40**, if desired, in other alternative embodiments, other types of fasteners such as a flexible clip shown and described in U.S. Pat. No. 5,317,663 may be used. Recesses may be provided on the main body **12** and the cover panels **32** to permit the use of alternative fastener means such as the flexible clip.

Also, in other embodiments of the adapter, the tabs may be longer and include fastener openings. As such, screws or similar fasteners may be used to connect the fiber optic adapter to a bulkhead structure.

The attachment structures discussed herein are non-limiting examples and other removable or non-removable fastening structures such as snap fasteners, rivets, etc. may be used to attach adapter to a bulkhead structure.

Now referring to FIGS. **5** and **6**, as discussed above, the fiber optic adapter main body **12** and at least a portion of the internal ferrule alignment features **31** of the adapter **10** are injection-molded as a unitary piece, and cover panels **32** are used to cover the first and second openings **28, 30** after the adapter **10** has been molded. In FIGS. **5** and **6**, the internal ferrule alignment components **31** of the SC-type adapter **10** are shown via cross-sectional views. Also, although the internal ferrule alignment features **31** are molded integrally with the main body **12** of the fiber optic adapter **10**, FIG. **1A** illustrates the internal ferrule alignment features of the fiber

4

optic adapter of FIG. **1** separately from the main body of the fiber optic adapter for ease of description and clarity.

The internal ferrule alignment structures **31** include a sleeve mount **50** and a ferrule sleeve **52** that is designed to be inserted within the sleeve mount **50**. As shown in FIGS. **5** and **6**, the sleeve mount **50** is molded integrally with the adapter body **12** and is configured to align the ferrules **104** of two SC-type fiber optic connectors **100** (FIG. **7**) received from opposing ends of the adapter body **12** for interconnection.

The sleeve mount **50** includes latching hooks **54**, an axial bore **56**, and flexible arms **58** defined around the axial bore **56**. Once the sleeve mount **50** is molded integrally with the main body **12** of the adapter **10**, the ferrule sleeve **52** is received within the axial bore **56** of the sleeve mount **50**. The flexible arms **58** flex out radially to receive the sleeve **52** with a snap fit arrangement. The flexible arms **58** include inwardly extending fingers **60** for capturing the sleeve **52** within the axial bore **56** once the sleeve **52** is received therein (see FIGS. **5** and **6**). The sleeve **52** can be inserted into the axial bore **56** from either end of the sleeve mount **50**. In certain embodiments, the sleeve **52** may also include a slit for allowing the sleeve **52** to compress, elastically reducing its diameter during insertion into the axial bore **56**.

It should be noted that the flexible arms **58** located at one end of the sleeve mount **50** may be positioned at an offset relationship to the flexible arms **58** located at the other end of the sleeve mount **50**. In this manner, the inwardly extending fingers **60** may be molded with molds/tools that are pulled apart from the ends of the fiber optic adapter in the longitudinal direction. During the molding process, the first and second openings **28, 30** (see FIGS. **2-3**) allow certain features of the adapter **10** to be molded with molds/tools that are pulled apart in the transverse direction while features such as the inwardly extending fingers **60** are formed with molds/tools that pulled apart in the longitudinal direction of the fiber optic adapter **10**.

Still referring to FIGS. **1A, 5** and **6**, the latching hooks **54** are configured to cooperate with the housing **106** of an SC-type connector **100** and are used for releasably latching connectors **100** to the adapter **10**, as will be described in further detail below.

Referring to FIGS. **4-6**, located on the interior of main body **12** are ridges **62**, extending longitudinally within the axial cavity **14** along the interior corners of the axial cavity **14**. The ridges **62** cooperate with the outer surface of a fiber optic connector housing **106** to receive the connector **100** within the axial cavity **14**. In certain embodiments, the ridges **62** may include ramped entry surfaces to facilitate insertion of the connector **100** within the adapter cavity **14**.

The main body **12** of the adapter **10** and the sleeve mount **50** may be constructed of a polymer by an injection molding process. It is contemplated that other materials and other molding processes may be used for the construction of the fiber optic adapter **10**.

FIG. **7** shows an SC-type fiber optic connector **100** that may be used with the fiber optic adapter **10** shown in FIG. **1-6**. Connector **100** includes an optical fiber **108** which is held therein by a ferrule **104**. The end of optical fiber is located on a contact face **110** of the ferrule **104**. Ferrule **104** is held within a housing **106** of the connector **100**. The housing **106** includes a first inner portion **112** and an axially slidable outer portion **114**. The housing **106** defines two slots **116** on opposite sides thereof and a key **102** located on a side perpendicular to the sides containing the slots **116**. As discussed previously, the key **102** is configured to engage the keyway **34** of fiber optic adapter main body **12** to properly position connector **100** through the first opening **28** of the adapter **10**. When

5

properly positioned within the axial cavity 14 of adapter 10, the ferrule 104 is received within the ferrule sleeve 52 inside the sleeve mount 50 of the adapter 10.

As is known in the art, when a first connector 100 is fully inserted into the adapter 10, the flexible latching hooks 54 of the sleeve mount 50 of the adapter engage the slots 116 in the outer portion 114 of the connector housing 106 to releasably hold connector 100 within the axial cavity 14 of adapter 10. When a second connector 100 is inserted into the opposing side of adapter 10, an optical connection is formed between the optical fiber of the first connector 100 and the optical fiber of the second connector 100 through the abutting contact faces 110 of the ferrules 114 within the ferrule sleeve 52.

When removing one of the fiber optic connectors 100, the slidable outer portion 114 of the connector housing 106 is slid axially relative to the first inner portion 112 of the connector housing 106 away from the opposing connector until the flexible latching hooks 54 of the adapter 10 are released from the slots 116 defined on the housing 106 of the connector 100, as is known in the art.

As discussed previously, the illustrated embodiment shows an SC-type fiber optic adapter 10 for receiving SC-type fiber optic connectors 100. It is anticipated that the inventive features of the present disclosure can be utilized with other types, sizes and designs of adapters and connectors.

Although in the foregoing description of the fiber optic adapter 10, terms such as “top”, “bottom”, “upper”, “lower”, “front”, “back”, “right”, and “left” were used for ease of description and illustration, no restriction is intended by such use of the terms. The fiber optic adapter 10 can be used in any orientation.

Having described the preferred aspects and embodiments of the present disclosure, modifications and equivalents of the disclosed concepts may readily occur to one skilled in the art. However, it is intended that such modifications and equivalents be included within the scope of the claims which are appended hereto.

What is claimed is:

1. A method of manufacturing a fiber optic adapter for interconnecting two fiber optic connectors in coaxial alignment, each connector including a generally cylindrical ferrule holding an end of an optical fiber, wherein the adapter includes a main body with an axial cavity defined by a top side-wall, a bottom side-wall, a right side-wall, and a left side-wall, the axial cavity extending between a first opening defined at a first end of the main body and a second opening defined at a second end of the main body, the first end configured to receive a first fiber optic connector through the first opening, and the second end configured to receive a second fiber optic connector through the second opening for mating with the first fiber optic connector, wherein the adapter also includes a ferrule alignment structure including a sleeve mount for receiving a ferrule-alignment sleeve, the sleeve mount defining a first end, a second end, and a center portion, wherein the first end of the sleeve mount is positioned toward the first end of the main body and the second end of the sleeve mount is positioned toward the second end of the main body, the sleeve mount defining an axial bore that defines a longitudinal axis extending from the first end of the sleeve mount toward the second end of the sleeve mount, the axial bore configured to receive and coaxially align the ferrules of the fiber connectors when the fiber connectors are inserted into the adapter, wherein the sleeve mount includes a first portion extending from the center portion of the sleeve mount toward the first end of the sleeve mount and a second portion extend-

6

ing from the center portion of the sleeve mount toward the second end of the sleeve mount, each of the first and second portions defining an inwardly extending finger for capturing the ferrule-alignment sleeve within the axial bore once the sleeve is received within the bore, the method comprising:

molding the main body of the fiber optic adapter and the sleeve mount as a unitary structure.

2. A method according to claim 1, further comprising using a molding tool for molding the main body and the sleeve mount of the fiber optic adapter such that parts of the molding tool are pulled apart from the first and second ends of the main body along a direction of the longitudinal axis.

3. A method according to claim 2, wherein the sleeve mount includes at least three flexible arms.

4. A method according to claim 1, further comprising inserting a ferrule-alignment sleeve into the axial bore of the sleeve mount from one of the first end and the second end of the sleeve mount.

5. A method according to claim 4, wherein the ferrule-alignment sleeve is inserted within the axial bore after the main body and the sleeve mount have been unitarily molded.

6. A method according to claim 1, further comprising molding the sleeve mount such that at least one of the first portion and the second portion of the sleeve mount defines flexible arms defined around the axial bore of the sleeve mount for receiving a ferrule-alignment sleeve, the flexible arms configured to flex out radially to receive the ferrule-alignment sleeve into the axial bore after the sleeve mount and the main body have been unitarily molded.

7. A method according to claim 1, wherein the main body and the sleeve mount are molded out of a polymer.

8. A method according to claim 1, wherein the adapter includes an outwardly protruding mounting tab on each of the right side-wall and the left side-wall.

9. A method according to claim 1, further comprising molding the sleeve mount such that the inwardly extending finger of the first portion is positioned around the axial bore at a peripherally offset relationship with respect to the inwardly extending finger of the second portion along the longitudinal axis defined by the axial bore.

10. A method according to claim 9, further comprising molding three inwardly extending fingers for each of the first portion and the second portion.

11. A method according to claim 1, wherein the manufactured fiber optic adapter is configured for interconnecting two SC type fiber connectors in coaxial alignment.

12. A method according to claim 1, further comprising molding the main body and the sleeve mount out of a polymer.

13. A method according to claim 1, further comprising molding an outwardly protruding mounting tab on each of the right side-wall and the left side-wall of the main body.

14. A method according to claim 1, wherein the sleeve mount includes two latching hooks extending from the center portion of the sleeve mount toward the first end of the main body and two latching hooks extending from the center portion of the sleeve mount toward the second end of the main body, wherein the latching hooks extending toward the first end of the main body are positioned on opposite sides of the axial bore and are configured to flex toward and away from each other to releasably latch a first connector to the adapter, and the latching hooks extending toward the second end of the main body are positioned on opposite sides of the axial bore and are configured to flex toward and away from each other to releasably latch a second connector to the adapter.